



(19) **United States**

(12) **Patent Application Publication**
Kuo

(10) **Pub. No.: US 2004/0017526 A1**

(43) **Pub. Date: Jan. 29, 2004**

(54) **LIQUID CRYSTAL DISPLAY DEVICE**

Publication Classification

(75) **Inventor: Chen Lung Kuo, Tainan County (TW)**

(51) **Int. Cl.⁷ G02F 1/1333**

(52) **U.S. Cl. 349/110**

Correspondence Address:

Finnegan, Henderson, Farabow,

Garrett & Dunner, L.L.P.

1300 I Street, N.W.

Washington, DC 20005-3315 (US)

(57) **ABSTRACT**

A liquid crystal display device mainly includes a first substrate having a light-shielding matrix formed thereon, a second substrate, and a liquid crystal layer sandwiched between the first and the second substrates. The first substrate is attached to the second substrate by a light-cured sealant. The present invention is characterized in that the light-shielding matrix has at least one transparent area located at a position facing the interface between the light-cured sealant and the liquid crystal layer thereby allowing a radiation entering the liquid crystal display device from the first substrate to reach the light-cured sealant through the at least one transparent area of the light-shielding matrix.


(73) **Assignee: CHI MEI OPTOELECTRONICS CORP.**

(21) **Appl. No.: 10/310,860**

(22) **Filed: Dec. 6, 2002**

(30) **Foreign Application Priority Data**

Jul. 26, 2002 (TW)..... 091117234






FIG. 1a (PRIOR ART)




FIG. 1b (PRIOR ART)




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

LIQUID CRYSTAL DISPLAY DEVICE

BACKGROUND OF THE INVENTION

[0001] 1. Field of the Invention

[0002] The present invention relates to a liquid crystal display (LCD) device, and more particularly to a liquid crystal display device using a light-cured sealant.

[0003] 2. Description of the Related Art

[0004] First, a conventional liquid crystal display device **100** will be described with reference to **FIGS. 1a** and **1b**. **FIG. 1a** is a perspective view of the conventional liquid crystal display device, and **FIG. 1b** is a sectional view taken along line **1b-1b** of **FIG. 1a**. Referring to **FIG. 1b**, the conventional liquid crystal display device **100** includes a first substrate **102** (i.e., a color filter substrate) and a second substrate **104** (i.e., a thin film transistor substrate) disposed to face each other with a predetermined gap therebetween. A liquid crystal layer **106** is sandwiched between the substrates **102** and **104**. The substrates **102** and **104** are affixed to each other by a sealant **107**.

[0005] Referring to **FIG. 1a**, the thin film transistor substrate **104** includes: a plurality of parallel data lines **108** and a plurality of parallel gate lines **110** which are formed on the surface of a glass substrate **112** facing the liquid crystal layer **106**; and thin film transistors (TFTs) **114** disposed at each of the intersections of the data lines **108** and the gate line **110**. Each region defined by two adjacent data lines **108** and two adjacent gate lines **110** is provided with a pixel electrode **116** connected to the drain electrode of the corresponding TFT **114**.

[0006] Referring to **FIG. 1b**, the color filter substrate **102** includes: a plurality of colored portions **118** on the surface thereof facing the liquid crystal layer **106** at positions corresponding to the pixel electrodes **116** of the thin film transistor substrate **104**; and a counter electrode **120** formed over the colored portions **118**. A light-shielding matrix (like black matrix) **122** is disposed between the adjacent colored portions **118**.

[0007] The light-shielding matrix **122** is made of a light-blocking material or a light-absorbing material for absorbing external light and improving the contrast of a displayed image. As shown in **FIG. 1b**, the light-shielding matrix **122** disposed in the periphery of the liquid crystal display device **100** covers a portion of the sealant **107** such that light can't penetrate through it to reach the portion of the sealant.

[0008] Therefore, when a UV curable sealant is used to seal the liquid crystal display device **100**, since a portion of the sealant **107** is (especially the interface between the liquid crystal layer **106** and the sealant **107**) covered by the light-shielding matrix **122**, the UV light is unable to reach the covered portion of the sealant **107** thereby resulting in incomplete curing thereof. Therefore, that uncured sealant will react with the liquid crystal layer and cause the latter to degrade in its performance as a liquid crystal material.

[0009] In the field of flat panel display, the two substrates may be affixed to each other with a thermosetting sealant. However, this method needs a relatively high curing temperature which the liquid crystal cannot tolerate, and therefore the step of curing the thermosetting sealant should be conducted prior to filling of the liquid crystal material.

[0010] However, in a newly proposed technique based on a one drop fill (abbreviated ODF) method disclosed in U.S. Pat. No. 5,263,888 to Ishihara et al., one of the substrates receives droplets of liquid crystal material prior to joining it with the other substrate. This greatly reduces the number of the manufacturing steps and increases the manufacturing efficiency. However, since the liquid crystal material is dropped prior to the step of sealing the two substrates, this method cannot use the thermal setting sealant but must use the UV curable sealant instead.

[0011] Therefore, in order to ensure that the UV curable sealant can be cured completely thereby preventing it from reacting with the liquid crystal material, the light-shielding matrix that blocks the sealant from light must be kept away from the sealant. But this means the redundant area outside the display region of liquid crystal panel will increase or the area of the display region will decrease if the area of the liquid crystal panel remains the same, either the former design or the latter design varies from the developing trend of the liquid crystal display device.

[0012] The present invention therefore seeks to provide a liquid crystal display device that overcomes or at least reduces the above-mentioned problems of the prior art.

SUMMARY OF THE INVENTION

[0013] It is an object of the invention to provide a liquid crystal display device which prevent deleterious mixing of the liquid crystal material with any potentially uncured sealants.

[0014] The liquid crystal display device according to a general aspect of the present invention mainly comprises a first substrate, a second substrate and a liquid crystal layer sandwiched between the first and the second substrates. The first substrate is attached to the second substrate by a light-cured sealant (e.g. a UV cured sealant). The first substrate has a light-shielding matrix (e.g. a black matrix). The present invention is characterized in that the light-shielding matrix has at least one transparent area located at a position facing the interface between the light-cured sealant and the liquid crystal layer thereby allowing a radiation that enters the liquid crystal display device from the first substrate to reach the light-cured sealant through the at least one transparent area of the light-shielding matrix. Since the sealant located around the interface is cured completely, even there is any other uncured sealant within the sealant, such uncured sealant will be kept from reacting with the liquid crystal material thereby assuring the performance of the liquid crystal material.

[0015] According to one embodiment of the present invention, the transparent area of the light-shielding matrix comprises a slit extending along the interface between the light-cured sealant and the liquid crystal layer.

[0016] According to another embodiment of the present invention, the transparent area of the light-shielding matrix has a saw-toothed outline

[0017] According to a further embodiment of the present invention, the light-shielding matrix has a plurality of transparent areas arranged in a plurality of parallel columns wherein at least one column of the transparent areas is formed along the interface between the light-cured sealant

and the liquid crystal layer. Preferably, the transparent areas in adjacent columns are arranged in a staggered configuration.

[0018] However, when the liquid crystal display device is in use, the light generated from the backlight will pass through the transparent area(s) of the light-shielding matrix thereby deteriorating the performance (for example, lower the contrast ratio) of the light-shielding matrix. Therefore, the present invention provides two solutions: 1) using a normally black mode liquid crystal display device comprising a pair of polarizers attached on the first and the second substrates respectively in a manner that the polarizers cover areas on the first and the second substrates facing the transparent area of the light-shielding matrix; and 2) forming an opaque pattern on the second substrate at a position corresponding to the transparent area of the light-shielding matrix.

[0019] The aforementioned opaque pattern preferably comprises an anti-reflection surface layer facing the first substrate in order to prevent the light scattered by the light-shielding matrix from being reflected from the opaque pattern to pass through the transparent area of the shielding matrix. The anti-reflection surface layer may be an oxidized metal film or may be formed of a refractory metal (e.g., Cr, Ta, Mo or Ti).

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] Other objects, advantages, and novel features of the invention will become more apparent from the following detailed description when taken in conjunction with the accompanying drawings.

[0021] FIG. 1a is a perspective view of a conventional liquid crystal display device;

[0022] FIG. 1b is a sectional view taken along line 1b-1b of FIG. 1a;

[0023] FIG. 2 is a sectional view of a portion of a liquid crystal display device according to a general aspect of the present invention;

[0024] FIG. 3 is a top plan view of a portion of a liquid crystal display device according to a first embodiment of the present invention;

[0025] FIG. 4 is a top view of a portion of a liquid crystal display device according to a second embodiment of the present invention;

[0026] FIG. 5 is a top view of a portion of a liquid crystal display device according to a third embodiment of the present invention;

[0027] FIG. 6 is a sectional view of a portion of a liquid crystal display device according to a fourth embodiment of the present invention; and

[0028] FIG. 7 is a sectional view of a portion of a liquid crystal display device according to a fifth embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0029] FIG. 2 shows a liquid crystal display device according to a general aspect of the present invention mainly

comprising a substrate 202, a substrate 204, a liquid crystal layer 206 sandwiched between the substrates 202 and 204, and a light-cured sealant 208 (e.g. a UV cured sealant) for attaching the substrate 202 to the substrate 204 and sealing the liquid crystal layer 206 therebetween. The substrate 202 has a light-shielding matrix 210 (e.g., a black matrix). The overlapping area between the light-shielding matrix 210 and the light-cured sealant 208 is designated by reference numeral 212. It is understood that the substrate 202 may be so-called color filter substrate, and the substrate 204 may be so-called thin-film transistor substrate.

[0030] The present invention is characterized in that the light-shielding matrix 210 has a transparent area 214 of the light-shielding matrix 210 formed at a position facing the interface 216 thereby allowing the sealant located around the interface 216 between the light-cured sealant 208 and the liquid crystal layer 206 to be cured completely. Since the sealant located around the interface 216 is cured completely, even there is any other uncured sealant within the sealant 208, such uncured sealant will be kept from reacting with the liquid crystal material thereby assuring the performance of the liquid crystal material.

[0031] FIG. 3 shows a top plan view of the peripheral portion of a liquid crystal display device according to a first embodiment of the present invention. In this embodiment, the light-shielding matrix 210 has a slit 302 extending along the interface 216 between the sealant 208 and the liquid crystal layer 206 thereby allowing a radiation to enter the liquid crystal display device through the slit 302 and reach the sealant 208 located around the interface 216 such that the sealant 208 located around the interface 216 can be cured completely.

[0032] FIG. 4 shows a top view of the peripheral portion of a liquid crystal display device according to a second embodiment of the present invention. The light-shielding matrix 210 has a plurality of transparent areas 402 formed along the interface 216 wherein each of the transparent areas 402 has a saw-toothed outline.

[0033] FIG. 5 shows a top view of the peripheral portion of a liquid crystal display device according to a third embodiment of the present invention. The light-shielding matrix 210 has a plurality of holes 502 arranged in a plurality of parallel columns wherein the holes arranged in the column designated with "a" extends along the interface 216. The holes in adjacent columns (i.e., a and b) are arranged in a staggered configuration. It should be noted that the liquid crystal display device is typically provided with a backlight generating light when the liquid crystal display device is in use. The light will pass through the substrate 204 and the liquid crystal layer 206, and then project from the substrate 202. The main purpose of the light-shielding matrix 210 is to reduce light leakage so as to improve the contrast of a displayed image. In order to prevent the light generated by the backlight from leaking out of the liquid crystal display device through the transparent area 214, the liquid crystal display device (see FIG. 6) according to a fourth embodiment of the present invention is a normally black mode liquid crystal display device comprising a pair of polarizers 602, 604 attached on the substrates 202, 204 respectively in a manner that the polarizers 602 and 604 cover areas on the substrates 202, 204 facing the transparent area 214 of the light-shielding matrix 210 thereby prevent-

ing the light passing through the transparent area **214** from leaking out of the liquid crystal display device. In the embodiment, when the liquid crystal layer **206** comprises a vertically aligned liquid crystal having a negative dielectric constant anisotropy, the polarization axes of the pair of polarizers **602**, **604** are perpendicular to each other. In addition, when the liquid crystal layer **206** comprises a horizontally 90 degree twisted nematic liquid crystal having a positive dielectric constant anisotropy, the polarization axes of the pair of polarizers **602**, **604** are parallel to each other.

[0034] Furthermore, FIG. 7 shows a liquid crystal display device according to a fifth embodiment of the present invention. The liquid crystal display device is characterized in that the substrate **204** has an opaque pattern **702** formed at a position facing the transparent area **214** of the light-shielding matrix **210** such that the light generated by the backlight cannot directly pass through transparent area and go out of the liquid crystal display device. The opaque pattern **702** may be formed from the electrically conductive layer (e.g. M1 or M2) on the substrate **204**. The opaque pattern **702** preferably comprises an anti-reflection surface layer **704** facing the substrate **202** in order to prevent the light (as shown by the arrow in FIG. 7) scattered by the light-shielding **210** from being reflected by the opaque pattern **702** to pass through the transparent area **214**. The anti-reflection surface layer **704** may be an oxidized metal film or may be formed of a refractory metal (e.g., Cr, Ta, Mo or Ti). Alternatively, the anti-reflection surface layer **704** may be formed from an artificial black body. The so-called artificial black body is a porous hollow container which is made of refractory metal. When light is transmitted to the surface of the artificial black body, the light will enter the pores and multi-reflection will occur in the chamber such that a part of the energy of the light is absorbed in each reflection until the energy is absorbed completely.

[0035] Although the invention has been explained in relation to its preferred embodiment, it is to be understood that many other possible modifications and variations can be made without departing from the spirit and scope of the invention as hereinafter claimed.

What is claimed is:

1. A liquid crystal display device, comprising:

a first substrate;

a second substrate;

a liquid crystal layer sandwiched between the first and the second substrates;

a light-cured sealant for attaching the first substrate to the second substrate;

a light-shielding matrix formed on the first substrate;

the light-shielding matrix having at least one transparent area located at a position facing the interface between the light-cured sealant and the liquid crystal layer thereby allowing a radiation entering the liquid crystal display device from the first substrate to reach the light-cured sealant through the transparent area of the light-shielding matrix.

2. The liquid crystal display device as claimed in claim 1, wherein the second substrate further comprising an opaque pattern formed at a position facing the at least one void of the light-shielding matrix.

3. The liquid crystal display device as claimed in claim 2, wherein the opaque pattern comprises an anti-reflection surface layer facing the first substrate.

4. The liquid crystal display device as claimed in claim 3, wherein the anti-reflection surface layer is made of refractory metal.

5. The liquid crystal display device as claimed in claim 4, wherein the refractory metal comprises a metal selected from the group consisting of Cr, Ta, Mo, and Ti.

6. The liquid crystal display device as claimed in claim 3, wherein the anti-reflection surface layer is an oxidized metal film.

7. The liquid crystal display device as claimed in claim 1, wherein the light-shielding matrix comprises a plurality of transparent areas facing the at least one void of the light-shielding matrix.

8. The liquid crystal display device as claimed in claim 1, wherein the transparent area of the light-shielding matrix has a saw-toothed outline.

9. The liquid crystal display device as claimed in claim 1, wherein the transparent area of the light-shielding matrix comprises a slit extending along the interface between the liquid crystal layer and the light-cured sealant.

10. The liquid crystal display device as claimed in claim 1, wherein the light-cured sealant is a UV cured sealant.

11. The liquid crystal display device as claimed in claim 1, wherein the light-shielding matrix is a black matrix.

12. The liquid crystal display device as claimed in claim 1, wherein the liquid crystal display device is a normally black mode liquid crystal display device comprising a pair of polarizers attached on the first and the second substrates respectively in a manner that the polarizers on the first and the second substrates cover areas on the first and the second substrates facing the transparent area of the light-shielding matrix.

13. The liquid crystal display device as claimed in claim 13, wherein the liquid crystal layer comprises a vertically aligned liquid crystal having a negative dielectric constant anisotropy, and the polarization axes of the pair of polarizers are perpendicular to each other.

14. The liquid crystal display device as claimed in claim 13, wherein the liquid crystal layer comprises a horizontally 90 degree twisted nematic liquid crystal having a positive dielectric constant anisotropy, and the polarization axes of the pair of polarizers are parallel to each other.

15. A color filter substrate for use in forming a liquid crystal display with a counter substrate, comprising:

a substrate; and

a light-shielding matrix formed on the substrate,

wherein the light-shielding matrix has at least one transparent area therein.

16. The liquid crystal display device as claimed in claim 15, wherein the color filter substrate is attached to the counter substrate by a light-cured sealant and a liquid crystal layer is sandwiched between the color filter substrate and the counter substrate, wherein:

the at least one transparent area of the light-shielding matrix is located at a position facing the interface

between the light-cured sealant and the liquid crystal layer thereby allowing a radiation entering the liquid crystal display device from the color filter substrate to reach the light-cured sealant disposed between the color filter substrate and the counter substrate through the transparent area of the light-shielding matrix.

17. The liquid crystal display device as claimed in claim 15, wherein the transparent area of the light-shielding matrix

comprises a slit extending along the interface between the liquid crystal layer and the light-cured sealant.

18. The liquid crystal display device as claimed in claim 15, wherein the light-cured sealant is a UV cured sealant.

19. The liquid crystal display device as claimed in claim 15, wherein the light-shielding matrix is a black matrix.

* * * * *

专利名称(译)	液晶显示装置		
公开(公告)号	US20040017526A1	公开(公告)日	2004-01-29
申请号	US10/310860	申请日	2002-12-06
[标]申请(专利权)人(译)	群创光电股份有限公司		
申请(专利权)人(译)	奇美电子股份有限公司.		
当前申请(专利权)人(译)	群创光电		
[标]发明人	KUO CHEN LUNG		
发明人	KUO, CHEN LUNG		
IPC分类号	G02F1/1339 G02F1/1335 G02F1/1362 G02F1/1333		
CPC分类号	G02F1/136209		
优先权	091117234 2002-07-26 TW		
其他公开文献	US7019800		
外部链接	Espacenet USPTO		

摘要(译)

液晶显示装置主要包括其上形成有遮光基质的第一基板，第二基板和夹在第一和第二基板之间的液晶层。第一基板通过光固化密封剂附着到第二基板。本发明的特征在于，遮光基质具有至少一个透明区域，该透明区域位于面对光固化密封剂和液晶层之间的界面的位置，从而允许从第一基板进入液晶显示装置的辐射通过遮光基质的至少一个透明区域到达光固化的密封剂。

