



US 20070258031A1

(19) **United States**(12) **Patent Application Publication**
CHOI et al.(10) **Pub. No.: US 2007/0258031 A1**(43) **Pub. Date: Nov. 8, 2007**(54) **LIQUID CRYSTAL DISPLAY****Publication Classification**(76) **Inventors:** Nak-Cho CHOI, Seoul (KR); Ji-Won Sohn, Seoul (KR); Mee-Hye Jung, Suwon-si (KR); Ho-Yun Byun, Hwaseong-si (KR); Seon-Ah Cho, Busan-si (KR)(51) **Int. Cl.**
G02F 1/1337 (2006.01)
(52) **U.S. Cl.** **349/129**(57) **ABSTRACT**

Correspondence Address:
Frank Chau, Esq.
F. CHAU & ASSOCIATES, LLC
130 Woodbury Road
Woodbury, NY 11797 (US)

A liquid crystal display includes a plurality of pixel electrodes that are formed in a matrix shape and each of which includes at least two parallelogram electrode pieces each having a pair of lengthwise edges and a pair of oblique edges adjacent the lengthwise edges, and a common electrode that faces the pixel electrodes and that has tilt direction determining members. Transverse center lines of the pixel electrodes that are adjacent each other in a row direction alternate, and the tilt direction determining members that correspond to the pixel electrodes that are adjacent to each other in the row direction are connected to each other in the row direction.

(21) **Appl. No.: 11/567,006**(22) **Filed: Dec. 5, 2006**(30) **Foreign Application Priority Data**

Dec. 7, 2005 (KR) 10-2005-0118535




FIG. 1




FIG.2




FIG. 4




FIG. 5




FIG.6A




FIG.6B




FIG.7A




FIG.7B




FIG.8




FIG.9





FIG.10



LIQUID CRYSTAL DISPLAY

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims priority to and the benefit of Korean Patent Application No. 10-2005-0118535 filed in the Korean Intellectual Property Office on Dec. 7, 2005, the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0002] (a) Technical Field

[0003] The present disclosure relates to a liquid crystal display.

[0004] (b) Discussion of the Related Art

[0005] Liquid crystal displays (LCDs) are now widely used as flat panel displays in various kinds of electronic devices. A liquid display typically has two display panels on which field generating electrodes such as pixel electrodes and a common electrode are formed, and a liquid crystal (LC) layer that is interposed between the panels. The LCD generates an electric field in the LC layer by applying voltages to the electrodes, and obtains desired images by controlling the strength of the electric field for determining orientations of LC molecules and polarization of light incident on the LC layer to vary the transmittance of light incident on the LC layer.

[0006] The liquid crystal display further includes switching elements that are respectively connected to the pixel electrodes, and a plurality of signal lines such as gate lines, data lines, or the like, that control the switching elements to allow a voltage to be applied to the pixel electrodes.

[0007] Among these liquid crystal displays, a liquid crystal display of a vertically aligned (VA) mode has been spotlighted because it has a large contrast ratio and a wide reference viewing angle, in which long axes of the liquid crystal molecules are perpendicular to the upper and lower display panels in a state in which an electric field is not applied. In this case, the reference viewing angle refers to a viewing angle at which a contrast ratio is 1:10 or to a luminance inversion limit angle between grays.

[0008] As methods of achieving a wide viewing angle in a liquid crystal display of a vertically aligned mode, there are a method of forming a cutout in a field generating electrode, and a method of forming a protrusion above or below the field generating electrode. Since the cutouts and the protrusions determine a tilt direction of the liquid crystal molecules, the tilt direction of the liquid crystal molecules is decentralized by appropriately disposing the cutouts and the protrusions, thereby widening the reference viewing angle.

[0009] The cutouts or the protrusions decrease the aperture ratio, however. In order to increase the aperture ratio, a structure having an ultra-high aperture ratio has been suggested for increasing a size of the pixel electrode to its maximum value. In this case, however, since the distance between the pixel electrodes is short, a strong lateral field is generated between the pixel electrodes. Alignment of the liquid crystal molecules is the scattered due to this lateral field and, as a result, texture or light leakage occurs.

[0010] Furthermore, liquid crystal displays of a VA mode have poor lateral visibility as compared to a front visibility. For example, in a liquid crystal display of a patterned vertically aligned (PVA) mode, which is provided with the cutouts, images gradually become brighter in a lateral direction. In the worst case, a luminance difference between high grays does not exist and, thus, pictures may be viewed in a state in which they are broken up.

[0011] Therefore, exemplary embodiments of the present invention have been made in an effort to provide an electrode arrangement having advantages of reducing loss caused by texture and thus improving an aperture ratio and transmittance.

SUMMARY OF THE INVENTION

[0012] An exemplary embodiment of the present invention provides a liquid crystal display that includes a plurality of pixel electrodes that are formed in a matrix shape, in which each pixel electrode includes at least two parallelogram electrode pieces each having a pair of lengthwise edges and a pair of oblique edges adjacent to the lengthwise edges, and a common electrode that faces the pixel electrodes and has tilt direction determining members. Transverse center lines of the pixel electrodes, which are adjacent to each other in a row direction, alternate, and the tilt direction determining members that correspond to the pixel electrodes that are adjacent to each other in the row direction are connected to each other in the row direction.

[0013] The tilt direction determining members may include cutouts having oblique lines that are parallel to the oblique edges of the electrode pieces and connection portions extending from the oblique lines, while the connection portions and the oblique lines meet at a predetermined angle.

[0014] The connection portions may overlap boundary lines of the pixel electrodes that are adjacent to each other in the row direction.

[0015] The pixel electrodes may be formed of the two parallelogram electrode pieces that are adjacent to each other in the row direction, and the two parallelogram electrode pieces may be partially connected to each other.

[0016] The two parallelogram electrode pieces may be reversely symmetrical on the basis of a lengthwise center line of each of the pixel electrodes.

[0017] The liquid crystal display may further include a plurality of thin film transistors connected to a plurality of pixel electrodes, a plurality of gate lines connected to the plurality of thin film transistors, and a plurality of data lines that are connected to the plurality of thin film transistors and intersect the gate lines.

[0018] At least one of the data lines may extend and pass through a boundary line of the parallelogram electrode pieces.

[0019] At least one of the data lines may extend and pass through a boundary line of the pixel electrodes that are adjacent to each other in the row direction.

[0020] The gate lines may include first portions that do not overlap the pixel electrodes and second portions that do overlap the pixel electrodes.

[0021] The first portions may extend and pass through boundary lines of the pixel electrodes that are adjacent to each other in a column direction.

[0022] The gate lines may not overlap the pixel electrodes.

[0023] The liquid crystal display may further include an organic film formed between the data lines and the pixel electrodes.

[0024] The liquid crystal display may further include a plurality of color filters facing the plurality of pixel electrodes. The plurality of color filters face the plurality of pixel electrodes located on the same column, and they may have two different colors that are alternately disposed.

[0025] The liquid crystal display may further include a plurality of color filters facing the plurality of pixel electrodes, wherein the plurality of color filters that face the plurality of pixel electrodes located on the same column may have three different colors that are alternately disposed.

[0026] The plurality of color filters that face the pixel electrodes that are adjacent to each other in the row direction may have different colors.

[0027] The liquid crystal display may further include a gate driver connected to the gate lines, a data driver connected to the data lines, and a signal controller controlling the gate driver and the data driver. The signal controller rearranges image signals obtained by treating input image signals to apply output image signals to the data driver.

BRIEF DESCRIPTION OF THE DRAWINGS

[0028] Exemplary embodiments of the present invention will be understood in more detail from the following descriptions taken in conjunction with attached drawings, in which:

[0029] FIG. 1 is a block diagram of a liquid crystal display according to an exemplary embodiment of the present invention.

[0030] FIG. 2 is an equivalent circuit view of a pixel of the liquid crystal display according to an exemplary embodiment of the present invention.

[0031] FIG. 3 is a layout view of the liquid crystal display according to an exemplary embodiment of the present invention.

[0032] FIGS. 4 and 5 are cross-sectional views of the liquid crystal display shown in FIG. 3 taken along the lines IV-IV and V-V, respectively.

[0033] FIG. 6A is a layout view showing a pixel electrode and a common electrode of the liquid crystal display according to an exemplary embodiment of the present invention.

[0034] FIG. 6B is a cross-sectional view taken along the line VIb-VIb in the liquid crystal display shown in FIG. 6A.

[0035] FIGS. 7A and 7B are plan views illustrating electrode pieces as basic units of the pixel electrode in the liquid crystal display according to an exemplary embodiment of the present invention.

[0036] FIG. 8 illustrates an arrangement of the pixel electrode, the common electrode, and a signal line of the liquid crystal display according to an exemplary embodiment of the present invention.

[0037] FIG. 9 illustrates an arrangement of a pixel electrode, a common electrode, and a signal line of a liquid crystal display according to an exemplary embodiment of the present invention.

[0038] FIG. 10 illustrates an arrangement of a pixel electrode, a common electrode, and a signal line of a liquid crystal display according to an exemplary embodiment of the present invention.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

[0039] The present invention will be described more fully hereinafter with reference to the accompanying drawings, in which exemplary embodiments of the invention are shown. As those skilled in the art would realize, the described exemplary embodiments may be modified in various different ways, all without departing from the spirit or scope of the present invention.

[0040] First, a liquid crystal display according to an exemplary embodiment of the present invention will be described in detail referring to FIGS. 1 and 2.

[0041] FIG. 1 is a block diagram of the liquid crystal display according to an exemplary embodiment of the present invention, and FIG. 2 is an equivalent circuit view of a pixel of the liquid crystal display according to an exemplary embodiment of the present invention.

[0042] As shown in FIG. 1, the liquid crystal display includes a liquid crystal panel assembly 300, a gate driver 400 and a data driver 500 connected to the liquid crystal panel assembly 300, a gray voltage generator 800 connected to the data driver 500, and a signal controller 600 for controlling the elements of the liquid crystal display.

[0043] The liquid crystal panel assembly 300 also includes a plurality of signal lines G_1 to G_n and D_1 to D_m and a plurality of pixels PX that are connected to the signal lines and arranged in a matrix shape. Meanwhile, in the equivalent circuit of a pixel shown in FIG. 2, the liquid crystal panel assembly 300 includes a lower panel 100 and an upper panel 200 that face each other, and a liquid crystal layer 3 interposed therebetween.

[0044] The signal lines G_1 to G_n and D_1 to D_m have a plurality of gate lines G_1 to G_n for transmitting gate signals (also referred to as "scanning signals"), and a plurality of data lines D_1 to D_m for transmitting data signals. The gate lines G_1 to G_n extend in a row direction so as to be substantially parallel to each other, and the data lines D_1 to D_m extend in a column direction so as to be substantially parallel to each other.

[0045] Each of the pixels PX, for example the pixel PX that is connected to the i -th (where $i=1, 2, \dots, n$) gate line G_i and the j -th (where $j=1, 2, \dots, m$) data line D_j , includes a switching element Q connected to the signal lines G_i and D_j , a liquid crystal capacitor Clc connected to the switching element, and a storage capacitor Cst. The storage capacitor Cst may be removed if deemed necessary.

[0046] Each switching element Q corresponds to a three-terminal element, such as a thin-film transistor, provided in the lower panel 100, and has a control terminal connected to the gate line G_i , an input terminal connected to the data line

D_j , and an output terminal connected to the liquid crystal capacitor C_{lc} and the storage capacitor C_{st} .

[0047] The liquid crystal capacitor C_{lc} uses a pixel electrode **191** of the lower panel **100** and the common electrode **270** of the upper panel **200** as its two terminals, and the liquid crystal layer **3** between the two electrodes **191** and **270** functions as the dielectric of the capacitor C_{lc} . The pixel electrode **191** is connected to the switching element Q , and the common electrode **270** is formed on an entire surface of the upper panel **200** and is applied with common voltage V_{com} . Unlike the structure shown in FIG. 2, the common electrode **270** may be alternatively formed on the lower panel **100**. In this case, at least one of the two electrodes **191** and **270** may be formed in the shape of a wire or rod.

[0048] The storage capacitor C_{st} that supplements the liquid crystal capacitor C_{lc} is formed by overlapping a separate signal line (not shown) and the pixel electrode **191**, which are provided on the lower panel **100**, with an insulator interposed therebetween. A predetermined voltage such as the common voltage V_{com} is applied to the separate signal line (not shown). The storage capacitor C_{st} , however, may be formed by overlapping the pixel electrode **191** and a previous gate line with an insulator interposed therebetween.

[0049] Each of the pixels PX specifically displays one of the primary colors (spatial division) or each of the pixels PX alternately displays the primary colors depending on a change of time (temporal division) to display a color, so that a desired color is displayed by spatial or temporal composition of the primary colors. Three primary colors including red, green, and blue may be exemplified as examples of the primary colors. FIG. 2 shows an example of the spatial division, in which each of the pixels PX includes a color filter **230** for displaying one of the primary colors in a region of the upper panel **200** corresponding to the pixel electrode **191**. Unlike the structure shown in FIG. 2, the color filter **230** may be formed on or beneath the pixel electrode **191** of the lower panel **100**.

[0050] At least one polarizer (not shown) for polarizing light is attached to the outer surface of the liquid crystal panel assembly **300**.

[0051] Referring to FIG. 1 again, the gray voltage generator **800** generates a plurality of gray voltages (or reference gray voltages) related to the light transmittance of the pixels PX . The gray voltage generator **800**, however, may generate only a given number of gray voltages (referred to as reference gray voltages) instead of generating all of the gray voltages.

[0052] The gate driver **400** is connected to the gate lines G_1 to G_n of the liquid crystal panel assembly **300** and applies gate signals, which are formed by a combination of a gate-on voltage V_{on} and a gate-off voltage V_{off} , to the gate lines G_1 to G_n .

[0053] The data driver **500** is connected to the data lines D_1 to D_m of the liquid crystal panel assembly **300** and applies data voltages V_d , which are selected from the gray voltages supplied from the gray voltage generator **800**, to the data lines, D_1 to D_m . When the gray voltage generator **800** does not provide voltages for all grayscales but provides only a predetermined number of reference gray voltages, however, the data driver **500** generates gray voltages for all

grayscales by dividing the reference gray voltages and selects a data signal among the gray voltages for all grayscales.

[0054] The signal controller **600** controls the gate driver **400**, the data driver **500**, and the other circuits of the liquid crystal display.

[0055] Each of the driving devices and the controller **400**, **500**, **600**, and **800** may be directly mounted on the liquid crystal panel assembly **300** in the form of at least one IC chip, or they may be mounted on a flexible printed circuit film (not shown) so as to be attached to the liquid crystal panel assembly **300** in the form of a TCP (tape carrier package), or they may be mounted on a separate printed circuit board (not shown). Unlike the above-mentioned structure, the driving devices **400**, **500**, **600**, and **800** also may be integrated on the liquid crystal panel assembly **300** along with the signal lines G_1 to G_n and D_1 to D_m and the thin film transistor switching elements Q . Furthermore, the driving devices and the controller **400**, **500**, **600**, and **800** may be integrated into a single chip. In this case, at least one of the drivers or at least one circuit element forming the drivers may be provided outside the single chip.

[0056] Hereinafter, an example of the liquid crystal panel assembly according to an exemplary embodiment of the present invention will be described in detail referring to FIGS. 3 to 7B.

[0057] FIG. 3 is a layout view of the liquid crystal display according to an exemplary embodiment of the present invention, and FIGS. 4 and 5 are cross-sectional views taken along the lines IV-IV and V-V, respectively, in the liquid crystal display shown in FIG. 3.

[0058] Referring to FIGS. 3 to 5, the liquid crystal display according to an exemplary embodiment of the present invention includes a lower panel **100** and an upper panel **200** that face each other, and a liquid crystal layer **3** that is interposed between the two display panels **100** and **200**.

[0059] First, the lower panel **100** will be described.

[0060] A plurality of gate lines **121** are formed on an insulation substrate **110** formed of transparent glass or plastic.

[0061] The gate lines **121** transmit gate signals, and extend in a transverse direction. Each of the gate lines **121** has a plurality of gate electrodes **124** that protrude upwardly, and an end portion **129** having a large area for connection with other layers and external driving circuits. When a gate driver **400** is integrated on the substrate **110**, the gate lines **121** may extend so as to be directly connected to the gate driver circuit.

[0062] Each of the gate lines **121** may be made of an aluminum-based metal, such as aluminum (Al) or an aluminum alloy, a silver-based metal, such as silver (Ag) or a silver alloy, a copper-based metal, such as copper (Cu) or a copper alloy, a molybdenum-based metal such as molybdenum (Mo) or a molybdenum alloy, chromium (Cr), tantalum (Ta), titanium (Ti), and the like. The gate conductor, however, may have a multilayer structure that has two conductive layers (not shown) with physical properties that are different from each other. In order to reduce signal delay or voltage drop, one of the two conductive layers is made of a metal having low resistivity, for example, an aluminum-

based metal, a silver-based metal, a copper-based metal, or the like. Different from the one conductive layer, the other conductive layer is made of materials with excellent physical, chemical, and electrical contact characteristics, particularly, ITO (indium tin oxide) and IZO (indium zinc oxide), molybdenum-based metal, chromium, tantalum, titanium, and the like. Preferable examples of material configurations of the two conductive layers may include a chromium lower layer and an aluminum (alloy) upper layer, and an aluminum (alloy) lower layer and a molybdenum (alloy) upper layer. Each of the gate lines **121**, however, may be made of not only the above-mentioned materials, but also of various other metals or conductors.

[0063] The side of each of the gate lines **121** is inclined relative to a surface of the substrate **110**, and the preferable inclination angle thereof ranges from about 30 degrees to about 80 degrees.

[0064] A gate insulating layer **140** preferably made of silicon nitride (SiNx) or silicon oxide (SiOx) is formed on the gate conductor **121**.

[0065] A plurality of semiconductor islands **154**, which are formed of hydrogenated amorphous silicon, amorphous silicon is hereinafter simply referred to as a-Si, or polysilicon, are formed above the gate insulating layer **140**. The semiconductor islands **154** are located above the gate electrodes **124**.

[0066] A pair of ohmic contact islands (ohmic contacts) **163** and **165** are formed above the semiconductor islands **154**. Each of the ohmic contacts **163** and **165** may be made of a material such as n+ hydrogenated amorphous silicon, in which n-type impurities, such as phosphor, are doped with a high concentration, or made of a material such as silicide.

[0067] The sides of the semiconductor **154** and the ohmic contacts **163** and **165** are inclined with respect to the surface of the substrate **110**, and the inclined angle is within a range of 30 to 80°.

[0068] A plurality of data conductors including a plurality of pairs of data lines **171** and a plurality of pairs of first and second drain electrodes **175** are formed on the ohmic contacts **163** and **165** and the gate insulating layer **140**.

[0069] The data lines **171** transmit data signals, and extend in a longitudinal direction to cross the gate lines **121**. Each of the data lines **171** includes a plurality of pairs of source electrodes **173** that extend to the gate electrodes **124**, and an end portion **179** having a large area for connection with the other layers or the data driver **500**. When the data driver **500** is integrated on the substrate **110**, the data line **171** may extend to be directly connected to the data driver **500**.

[0070] The drain electrodes **175** are separated from the data lines **171**, and face the source electrodes **173** are based on the gate electrodes **124**.

[0071] A single gate electrode **124**, a single source electrode **173**, and a single drain electrode **175** form a single thin film transistor (TFT) together with a semiconductor **154**, and a channel of the thin film transistor is formed in the semiconductor **154** between the source electrode **173** and the drain electrode **175**.

[0072] Each of the data conductors **171** and **175** is preferably made of refractory metals, such as molybdenum,

chromium, tantalum, and titanium, or an alloy thereof, or may have a multilayer structure that includes a refractory metal film (not shown) and a conductive layer (not shown) having low resistance. Examples of the multilayer structure include a double layer having a chromium or molybdenum (alloy) lower layer and an aluminum (alloy) upper layer, and a triple layer having a molybdenum (alloy) lower layer, an aluminum (alloy) intermediate layer, and a molybdenum (alloy) upper layer. The data conductors **171** and **175**, however, may be made of not only the above-mentioned materials, but also of various other metals or conductors.

[0073] The sides of the data conductors **171** and **175** are also preferably inclined to the surface of the substrate **110** at an angle of 30 to 80°.

[0074] The ohmic contacts **163** and **165** exist only between the semiconductor **154** below the ohmic contacts **163** and **165** and the data conductors **171** and **175** above the ohmic contacts **163** and **165**, so as to reduce the contact resistance between them. In the semiconductor **154**, exposed regions exist between the source electrodes **173** and the drain electrodes **175**, as well as exposed portions that are not covered with the data conductors **171** and **175**.

[0075] A passivation layer **180** is formed on the data conductors **171** and **175** and the exposed portions of the semiconductor **154**. The passivation layer **180** may be made of an inorganic insulator or an organic insulator and may have a flat surface. Preferably, the organic insulator has a dielectric constant of 4.0 or less, and may have photosensitivity. The passivation layer **180**, however, may have a dual-layer structure including a lower inorganic layer and an upper organic layer, so that it does not damage the exposed portions of the semiconductor **154**, while sufficiently employing the excellent insulating characteristic of an organic film.

[0076] In the passivation layer **180**, are formed a plurality of contact holes **182** and **185** to which an end **179** of the data line **171** and ends of the first and second drain electrodes **175** are exposed, and formed in the passivation layer **180** and the gate insulating layer **140** are a plurality of contact holes **181** to which ends **129** of the gate lines **121** are exposed.

[0077] On the passivation layer **180**, a plurality of pixel electrodes **191** and a plurality of contact assistants **81** and **82** are formed. Each of the pixel electrodes **191** and the contact assistants **81** and **82** may be made of a transparent conductive material such as ITO or IZO, or a reflective metal such as aluminum, silver, chromium, or an alloy thereof.

[0078] Hereinafter, shapes of the pixel electrodes **191** according to an exemplary embodiment of the present invention will be described referring to FIGS. **6A**, **6B**, **7A**, and **7B**.

[0079] FIG. **6A** is a layout view showing a pixel electrode and a common electrode of the liquid crystal display according to an exemplary embodiment of the present invention, FIG. **6B** is a cross-sectional view taken along the line VIb-VIb of FIG. **6A**, and FIGS. **7A** and **7B** are plan views illustrating electrode pieces as basic units of the pixel electrode in the liquid crystal display according to an exemplary embodiment of the present invention.

[0080] As shown in FIGS. **6A** and **6B**, each of the pixel electrodes of the liquid crystal panel assembly according to

an exemplary embodiment of the present invention includes first parts **191Ra**, **191Ga**, and **191Ba** formed on the left of the lengthwise center line, and second parts **191Rb**, **191Gb**, and **191Bb** formed on the right of the lengthwise center line. The common electrode **270** (see FIG. 2) has cutouts **71a**, **71b**, and **72** that face the pixel electrodes **191**.

[0081] Each of the first and the second parts **191Ra**, **191Ga**, **191Ba**, **191Rb**, **191Gb**, and **191Bb** of the pixel electrode **191** includes one parallelogram electrode piece **196** shown in FIG. 7A and one parallelogram electrode piece **197** shown in FIG. 7B.

[0082] As shown in FIGS. 7A and 7B, each of the electrode pieces **196** and **197** has a pair of oblique edges **196o** and **197o** and a pair of lengthwise edges **196t** and **197t**, and each of the electrode pieces **196** and **197** is substantially a parallelogram. Each oblique edge **196o** and **197o** forms an oblique angle with respect to the lengthwise edges **196t** and **197t**, and the oblique angle is preferably within a range of 45 to 135°. Hereinafter, for convenience sake, the shape of the electrode piece **196** and **197** is classified according to the direction of inclination (“inclination direction”) from a perpendicular state with respect to the lengthwise edges **196t** and **197t**, and it is referred to as “left-inclined” when the inclination direction is leftward as shown in FIG. 7A and as “right-inclined” when the inclination direction is rightward as shown in FIG. 7B.

[0083] The length between the lengthwise edges **196t** and **197t** of the electrode pieces **196** and **197**, that is, the width, and the distance between the oblique edges **196o** and **197o**, that is, the height, may be determined freely in accordance with the size of the LC panel assembly **300**. Also, the lengthwise edges **196t** and **197t** of each electrode piece **196** and **197** may be modified, for example, may be curved or projected, in consideration of the relationships with other parts, which modification may be included when referring to a parallelogram hereinafter.

[0084] In the pixel electrodes **191**, the parallelogram electrode pieces **196** and **197**, which have different inclinations, are partially connected to each other through connection bridges **193a** (see FIG. 3), **193R**, **193G** and **193B** in a row direction. The lengthwise edges **196t** and **197t** of the parallelogram electrode pieces **196** and **197** are in contact with each other. The oblique edges **196o** and **197o** of the parallelogram electrode pieces **196** and **197** are connected to each other to form an oblique angle, and the oblique angle is preferably about 90°. As such, the pixel electrodes **191** are bent once in a horizontal direction, and are bilaterally symmetrical with the lengthwise center line as the central figure.

[0085] The two pixel electrodes **191R** and **191G** that are adjacent each other in a column direction have lengthwise edges **196t** and **197t** on a straight line. That is, virtual lines that bisect the pixel electrodes **191R** and **191G** into left and right sides (hereinafter, referred to as “lengthwise center line”) are arranged in a straight line. Virtual lines that bisect the pixel electrodes **191R** and **191G** into upper and lower sides (hereinafter, referred to as “transverse center line”) are not located on the straight line in the two pixel electrodes **191R** and **191B** that are adjacent to each other in the row direction. An upper oblique edge of the pixel electrode **191B** is located at a middle portion of the lengthwise edge of the neighboring pixel electrode **191R**. That is, the pixel elec-

trodes **191R** and **191B** that are adjacent each other in the row direction are alternately arranged in the vertical direction.

[0086] In the common electrode **270**, cutouts **71a**, **71b**, and **72** are formed to face the electrode pieces **196** and **197**, and the electrode pieces **196** and **197** are divided into two sub-areas with the cutouts **71a**, **71b**, and **72** as the central figure. The cutouts **71a**, **71b**, and **72** include oblique lines **71a** and **71b** that are parallel to the oblique edges **196o** and **197o** of the electrode pieces **196** and **197**, and connection portions **72** that extend to meet the oblique lines **71a** and **71b** at an obtuse angle. The oblique lines **71a** and **71b** of the cutouts that are formed in the common electrodes **270** facing the pixel electrodes **191R** and **191B** that are adjacent in the row direction are connected through the connection portions **72**. That is, the cutouts **71a**, **71b**, and **72** of the common electrodes **270** are connected to each other in the single pixel row.

[0087] The connection portions **72** of the cutouts overlap the boundary line of the pixel electrodes **191R** and **191B** that are adjacent each other in the row direction, and the widths of the connection portions **72** are larger than those of the pixel electrodes **191R** and **191B** that are adjacent each other in the row direction.

[0088] In FIGS. 3 to 7B, the position and the angled direction of the pixel electrodes **191** may be changed, and the pixel electrodes **191** of FIGS. 3 to 7B may be symmetrically shifted in the horizontal or vertical direction or rotated to achieve the change in direction.

[0089] Each pixel electrode **191** is physically and electrically connected through the contact hole **185** to the drain electrode **175**, and the data voltage is applied from the drain electrode **175** to the pixel electrode. The pixel electrode **191** to which the data voltage is applied generates an electric field along with the common electrode **270** of the upper panel **200** to which the common voltage is applied, thereby determining the direction of liquid crystal molecules **30** of the liquid crystal layer **3** between the two electrodes **191** and **270**. The variation of the polarization of the light passing through the liquid crystal layer **3** is different according to the direction of the liquid crystal molecules **30** that is determined as described above. The pixel electrode **191** and the common electrode **270** form a capacitor, referred to above as the “liquid crystal capacitor”, and it holds an applied voltage even after the thin film transistor is turned off.

[0090] The contact assistants **81** and **82** are connected to the ends **129** of the gate lines **121** and ends **179** of the data lines **171** through the contact holes **181** and **182**. The contact assistants **81** and **82** complement connection between the ends **129** of the gate lines **121** and the ends **179** of the data lines **171** and an external device, and serve to protect them.

[0091] Next, the upper panel **200** will be described.

[0092] The light blocking member **220** is formed on an insulation substrate **210** that is made of transparent glass or plastic. The light blocking member **220** may have a bent portion (not shown) that corresponds to a bent edge of the pixel electrode **191** and a quadrangle portion (not shown) that corresponds to the thin film transistor. The light blocking member **220** prevents light leakage between the pixel electrodes **191** and defines an opening region that faces the pixel electrode **191**.

[0093] On the substrate **210** and the light blocking member **220**, a plurality of color filters **230** are formed. The color filters **230** mainly exist in a region surrounded by the light blocking member **220**, and may extend to be elongated along a column of the pixel electrodes **191**. Each of the color filters **230** may display one of three primary colors including red, green, and blue.

[0094] An overcoat **250** is formed on the color filter **230** and the light blocking member **220**. The overcoat **250** may be made of an organic insulator, prevents the color filter **230** from being exposed, and provides a flat surface. The overcoat **250** may be omitted if desired.

[0095] The common electrode **270** is formed on the overcoat **250**. The common electrode **270** is formed of a transparent conductor, such as ITO, IZO, or the like, and has a plurality of cutouts (not shown).

[0096] Alignment layers **11** and **21**, which may be vertical alignment layers, are formed on inner surfaces of the display panels **100** and **200** facing the liquid crystal layer **3**.

[0097] Polarizers **12** and **22** shown in FIG. 4 are provided on outer surfaces of the display panels **100** and **200**. Preferably, the polarization axes of the two polarizers are orthogonal to each other, and form an angle of about 45° with respect to the oblique edges of the pixel electrodes **191**. In a case of a reflective liquid crystal display, one of the two polarizers may be omitted.

[0098] The liquid crystal display may include a lighting unit or backlight unit (not shown) that supplies light to the polarizers **12** and **22**, a phase delay film, the display panels **100** and **200**, and the liquid crystal layer **3**.

[0099] The liquid crystal layer **3** has negative dielectric anisotropy, and long axis of the liquid crystal molecules of the liquid crystal layer **3** are perpendicular to the surfaces of the two display panels in the absence of an electric field.

[0100] The liquid crystal panel assembly including a plurality of pixel electrodes shown in FIG. 3 will be described in detail referring to FIGS 8 and 9.

[0101] FIG. 8 illustrates arrangement of the pixel electrode, the common electrode, and a signal line of the liquid crystal display according to the exemplary embodiment of the present invention.

[0102] In FIG. 8, virtual lines that bisect the pixel electrodes **191** of FIG. 3, which are adjacent each other in the row direction, into upper and lower sides (hereinafter, referred to as "transverse center line") are not located on the same straight line. The pixel electrodes **191** that are adjacent each other in the row direction are reversely symmetrical in the vertical direction. The shapes of the pixel electrodes **191** that are adjacent in the column direction are identical with each other, and the lengthwise center lines of the pixel electrodes **191** are on the same straight line.

[0103] Meanwhile, a portion of the gate lines **G1** and **G2** overlaps the pixel electrodes **191**, while another portion does not overlap the pixel electrodes **191**.

[0104] Further, a portion of the data lines **D1**, **D3**, **D5**, **D6**, and **D7** extends over the lengthwise center line of the pixel electrode **191** to bisect the pixel electrode, while another portion of the data line **D2**, **D4**, **D6**, and **D8** extends while

passing through the boundary line of the pixel electrodes **191** that are adjacent in the row direction.

[0105] Two color filters **230** shown in FIG. 2 of different colors alternately extend along that pixel electrodes **191** that are adjacent in the column direction. In FIG. 8, the pixels are designated by Rij, Gij, or Bij. R denotes the pixel having the red color filter **230**, G denotes the pixel having the green color filter **230**, B denotes the pixel having the blue color filter **230**, i means that the pixel is connected to the i-th gate line **121**, and j means that the pixel is connected to the j-th data line **171**. In the liquid crystal panel assembly of FIG. 8, the pixels R11 and R21 having the red color filter are sequentially connected to the first data line **D1**, the pixels G12 and G22 having the green color filter are sequentially connected to the second data line **D2**, and the pixels B13 and B23 having the blue color filter are sequentially connected to the third data line **D8**. This rule is repeated with respect to the data lines **D4**, **D5**, **D6**, **D7**, and **D8**.

[0106] An arrangement of the pixel electrodes of the liquid crystal panel assembly according to an exemplary embodiment of the present invention will be described referring to FIG. 9.

[0107] FIG. 9 illustrates arrangement of the pixel electrode, the common electrode, and the signal line of the liquid crystal display according to an exemplary embodiment of the present invention.

[0108] The pixel electrode **191** and the common electrode **270** shown in FIG. 2 of the liquid crystal panel assembly of FIG. 9 have the same shapes as those of the liquid crystal panel assembly of FIG. 8. Unlike what is shown in FIG. 8, since the gate line **121** is bent a few times so as to extend while passing through the boundary line of the pixel electrodes **191** that are adjacent in the column direction, the gate line **121** and the pixel electrode **191** do not overlap each other in the exemplary embodiment of FIG. 9. Accordingly, a parasitic capacitance is prevented from occurring between the gate line **121** and the pixel electrode **191**.

[0109] The operation of the liquid crystal display will now be described in detail referring back to FIG. 1.

[0110] The signal controller **600** receives input image signals R, G, and B from an external graphics controller (not shown), and input control signals for controlling the display of the input image signals R, G, and B. The input image signals R, G, and B have luminance information regarding the pixel PX, and the luminance has a predetermined number of grays, for example, the luminance has 1024 ($=2^{10}$), 256 ($=2^8$), or 64 ($=2^6$) grays. Examples of the input control signal include a vertical synchronization signal Vsync, a horizontal synchronizing signal Hsync, a main clock signal MCLK, and a data enable signal DE.

[0111] The signal controller **600** appropriately processes the input image signals R, G, and B and the input control signals, so that the input image signals R, G, and B correspond to operating conditions of the liquid crystal panel assembly **300** and the data driver **500**, and generates gate control signals CONT1, data control signals CONT2, and the like. Then, the signal controller **600** transmits the gate control signals CONT1 to the gate driver **400**, and transmits the data control signals CONT2 and the processed image signals DAT to the data driver **500**. An output image signal DAT has a predetermined number of values (or grays) formed as a digital signal.

[0112] Each of the gate control signals CONT1 includes a scanning start signal for instructing the start of scanning, and at least one clock signal for controlling the output period of the gate-on voltage Von. In addition, the gate control signal CONT1 may further include an output enable signal E for limiting the duration of the gate-on voltage Von.

[0113] Each of the data control signals CONT2 includes a horizontal synchronization start signal for directing the start of transmitting image data to a group of subpixels, and a load signal and a data clock signal for causing the data signals to be applied to the liquid crystal panel assembly 300. In addition, each of the data control signals CONT2 may further include an inversion signal for inverting the voltage polarity of the data signal for the common voltage Vcom, hereinafter, "the voltage polarity of the data signal for the common voltage" is briefly referred to as "the polarity of the data signal".

[0114] The data driver 500 converts the digital image signals DAT into analog data signals by receiving the digital image signals DAT for a group of subpixels, and selecting respective gray voltages corresponding to the digital image signals DAT on the basis of the data control signals CONT2 from the signal controller 600. Then, the data driver 500 applies the analog data signals to the corresponding data lines.

[0115] The gate driver 400 turns on the switching elements connected to the gate lines by applying the gate-on voltage V on to the gate lines on the basis of the gate control signal CONT1 from the signal controller 600. Accordingly, the data signals applied to the data lines are applied to the corresponding pixels through the switching elements that are turned on.

[0116] If a potential difference is generated across the liquid crystal capacitors Clc shown in FIG. 2, a primary electric field that is substantially perpendicular to the surfaces of the display panels 100 and 200 is generated in the liquid crystal layer 3. Hereinafter, all of the electrodes 191 and the common electrode 270 are referred to as "field generating electrodes". Then, long axes of the liquid crystal molecules of the liquid crystal layer 3 are perpendicular to a direction in which the electric field is applied in response to the applied electric field, and the variation of the polarization of the light incident on the liquid crystal layer 3 is different according to the inclination of the liquid crystal molecules. When the polarization varies, the light transmittance is changed by the polarizer and, thus, the liquid crystal display displays images.

[0117] Tilt directions of the liquid crystal molecules are primarily determined according to horizontal components obtained by distorting the primary electric field by the cutouts 71a, 71b, and 72 of the field generating electrodes 191 and 270 and the edges of the pixel electrodes 191. The horizontal components of this primary electric field are substantially perpendicular to the edges of the cutouts 71a, 71b, and 72 and the edges of the pixel electrodes 191.

[0118] The pixel electrodes 191 are divided into a plurality of sub-areas by the cutouts 71a, 71b, and 72, and each of the sub-areas has two major edges that are defined by oblique lines of the cutouts 71a, 71b, and 72 and oblique edges of the pixel electrodes 191. The liquid crystal molecules on each sub-area are tilted in directions perpendicular to the major edges, that is, in substantially four directions. As such, as the tilt directions of liquid crystal molecules are diversified, a reference viewing angle of the liquid crystal display is increased.

[0119] A direction of a secondary electric field that is secondarily generated by the voltage difference between the pixel electrodes 191 is perpendicular to the major edges of the sub-areas. Therefore, a direction of the secondary electric field is that of the direction of the horizontal component of the primary electric field. As a result, the secondary electric field between the pixel electrodes 191 determines the tilt direction of the liquid crystal molecules.

[0120] In the liquid crystal display according to an exemplary embodiment of the present invention, the electric field formed between the common electrode 270 and the pixel electrode 191 corresponds to a curved line of FIG. 6B. Accordingly, the liquid crystal molecules move substantially perpendicularly with respect to the curved line. As shown in FIGS. 6A and 6B, if the cutout 72 of the common electrode 270 overlaps the gap 197b between the pixel electrodes 191, and the cutout 72 of the common electrode 270 is larger than the gap 197b between the pixel electrodes 191, the liquid crystal molecules 30 are tilted in a predetermined direction. Furthermore, the liquid crystal molecules 30 are tilted in a predetermined direction due to the electric field formed between the gap 197a between the two electrode pieces 196 and 197 and the common electrode. Therefore, as shown in FIG. 6B, the liquid crystal molecules 30 are tilted in the same direction between the gap 197a between the two electrode pieces 196 and 197 of the pixel electrode 191 and the gap 197b between the pixel electrodes 191. That is, in a first region RA, the liquid crystal molecules 30 are tilted to the right, and, in a second region LA, the liquid crystal molecules 30 are tilted to the left. Accordingly, since the liquid crystal molecules 30 are unidirectionally tilted in one region, it is possible to prevent the occurrence of texture that is caused by disordered directions of the liquid crystal molecules.

[0121] Hereinafter, the liquid crystal panel assembly according to an exemplary embodiment of the present invention will be described in detail referring to FIG. 10.

[0122] FIG. 10 is a layout view showing the liquid crystal panel assembly according to an exemplary embodiment of the present invention.

[0123] In the liquid crystal panel assembly of FIG. 10, the arrangement of pixel electrodes 191 and common electrodes 270 is the same as that of FIG. 8. The liquid crystal panel assembly of FIG. 10, however, has different types of arrangements of the color filter 230, unlike what is shown in FIG. 8. That is, the three color filters having different colors of the color filter 230 alternately extend along the pixel electrodes 191 that are adjacent in the column direction. Like FIG. 8 in which the pixels are designated by Rij, Gij, or Bij, R denotes the pixel having the red color filter 230, G denotes the pixel having the green color filter 230, B denotes the pixel having the blue color filter 230, i means that the pixel is connected to the i-th gate line 121, and j means that the pixel is connected to the j-th data line 171. In the liquid crystal panel assembly of FIG. 10, the pixel R11 having the red color filter, the pixel B21 having the blue color filter, and the pixel R32 having the red color filter are sequentially connected to the first data line D1. The pixel G12 having the green color filter and the pixel G32 having the green color filter are sequentially connected to the second data line D1, and the pixel B13 having the blue color filter, the pixel G23 having the green color filter, the pixel B33 having the blue color filter, and the pixel G43 having the green color filter are sequentially connected to the third data line D3. That is, the pixels having the same color filter are not connected to

the single data line, but the pixels having the different color filters are connected to the single data line.

[0124] Accordingly, in the signal controller 600, it is necessary for image signals to be rearranged according to the order of the color filters connected to the single data line if the image signals are obtained by treating R, G, and B input image signals. When image signals are stored in a buffer part (not shown) in the signal controller 600, the image signals may be appropriately rearranged and outputted.

[0125] According to exemplary embodiments of the present invention, since disadvantages caused by texture of a liquid crystal display are avoided, it is possible to improve an aperture ratio and transmittance.

[0126] While this invention has been described in connection with what is presently considered to be exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments, but, on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the appended claims.

What is claimed is:

1. A liquid crystal display comprising:

a plurality of pixel electrodes formed in a matrix shape, each pixel electrode includes at least two parallelogram electrode pieces each having a pair of lengthwise edges and a pair of oblique edges adjacent to the lengthwise edges; and

a common electrode that faces the plurality pixel electrodes and has tilt direction determining members,

wherein transverse center lines of the respective pixel electrodes that are adjacent to each other in a row direction are alternate, and

the tilt direction determining members that correspond to the pixel electrodes that are adjacent to each other in the row direction are connected to each other in the row direction.

2. The liquid crystal display of claim 1, wherein the tilt direction determining members include cutouts having oblique lines that are substantially parallel to the oblique edges of the electrode pieces and connection portions that are bent from the oblique lines.

3. The liquid crystal display of claim 2, wherein the connection portions overlap boundary lines of the pixel electrodes that are adjacent to each other in the row direction.

4. The liquid crystal display of claim 1, wherein each of the two parallelogram electrode pieces that are adjacent to each other in the row direction and the two parallelogram electrode pieces are connected to each other.

5. The liquid crystal display of claim 4, wherein the two parallelogram electrode pieces are reversely symmetrical on a basis of a lengthwise center line of each of the plurality of pixel electrodes.

6. The liquid crystal display of claim 1, further comprising:

a plurality of thin film transistors respectively connected to the plurality of pixel electrodes;

a plurality of gate lines respectively connected to the plurality of thin film transistors; and

a plurality of data lines respectively connected to the plurality of thin film transistors and being arranged to intersect the plurality of gate lines.

7. The liquid crystal display of claim 5, wherein at least one of a plurality of data lines is extended while passing through a boundary line of the parallelogram electrode pieces.

8. The liquid crystal display of claim 6, wherein at least one of the plurality of data lines is extended while passing through a boundary line of the pixel electrodes that are adjacent to each other in the row direction.

9. The liquid crystal display of claim 6, wherein each of the plurality of gate lines include a first portion that does not overlap the pixel electrodes and a second portion that does overlap the pixel electrodes.

10. The liquid crystal display of claim 9, wherein the first portion is extended while passing through boundary lines of the plurality of pixel electrodes that are adjacent to each other in a column direction.

11. The liquid crystal display of claim 6, wherein the plurality of gate lines do not overlap the plurality of pixel electrodes, respectively.

12. The liquid crystal display of claim 6, further comprising an organic film formed between the plurality of data lines and the plurality of pixel electrodes.

13. The liquid crystal display of claim 1, further comprising a plurality of color filters respectively facing the plurality of pixel electrodes,

wherein the plurality of color filters that face the plurality of pixel electrodes are located in a same column direction and have two different colors that are alternately disposed.

14. The liquid crystal display of claim 1, further comprising a plurality of color filters respectively facing the plurality of pixel electrodes,

wherein the plurality of color filters that face the plurality of pixel electrodes are located in a same column direction and have three different colors that are alternately disposed.

15. The liquid crystal display of claim 13, wherein the plurality of color filters that respectively face the plurality of pixel electrodes adjacent to each other in a row direction display the two different colors.

16. The liquid crystal display of claim 6, further comprising:

a gate driver connected to the plurality of gate lines;

a data driver connected to the plurality of data lines, and

a signal controller controlling the gate driver and the data driver,

wherein the signal controller rearranges image signals obtained by treating input image signals to apply output image signals to the data driver.

* * * * *

专利名称(译)	液晶显示器		
公开(公告)号	US20070258031A1	公开(公告)日	2007-11-08
申请号	US11/567006	申请日	2006-12-05
[标]申请(专利权)人(译)	CHOI NAK CHO SOHN智 JUNG MEE HYE BYUN豪润达 CHO AH SEON		
申请(专利权)人(译)	崔NAK-CHO SOHN JI-WON JUNG MEE惠 BYUN HO-YUN CHO SEON-AH		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	CHOI NAK CHO SOHN JI WON JUNG MEE HYE BYUN HO YUN CHO SEON AH		
发明人	CHOI, NAK-CHO SOHN, JI-WON JUNG, MEE-HYE BYUN, HO-YUN CHO, SEON-AH		
IPC分类号	G02F1/1337		
CPC分类号	G02F1/133707 G02F2201/122 G02F1/1393 G02F1/134336		
优先权	1020050118535 2005-12-07 KR		
其他公开文献	US7671951		
外部链接	Espacenet USPTO		

摘要(译)

液晶显示器包括多个像素电极，所述多个像素电极形成为矩阵形状，并且每个像素电极包括至少两个平行四边形电极片，每个电极片具有一对纵向边缘和与纵向边缘相邻的一对倾斜边缘，以及公共电极面向像素电极并具有倾斜方向确定构件。在行方向上彼此相邻的像素电极的横向中心线交替，并且与在行方向上彼此相邻的像素电极对应的倾斜方向确定构件在行方向上彼此连接。

