



US008279376B2

(12) **United States Patent**
Chan et al.

(10) **Patent No.:** **US 8,279,376 B2**
(45) **Date of Patent:** **Oct. 2, 2012**

(54) **LIQUID CRYSTAL DISPLAY PANEL AND MANUFACTURING METHOD THEREOF**

(75) Inventors: **Te-Wei Chan**, Hsinchu County (TW);
Chieh-Wei Chen, Taichung County (TW); **Cheng-Han Tsao**, Taipei County (TW); **Chung-Yi Chiu**, Tainan County (TW)

(73) Assignee: **Au Optonics Corporation**, Hsinchu (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1004 days.

(21) Appl. No.: **12/199,808**

(22) Filed: **Aug. 28, 2008**

(65) **Prior Publication Data**

US 2009/0322659 A1 Dec. 31, 2009

(30) **Foreign Application Priority Data**

Jun. 27, 2008 (TW) 97124238 A

(51) **Int. Cl.**
G02F 1/1333 (2006.01)

(52) **U.S. Cl.** 349/86; 349/129; 349/90; 349/128

(58) **Field of Classification Search** 349/129,
349/128, 86-94
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,549,255 B2 * 4/2003 Stebler et al. 349/127
7,113,241 B2 * 9/2006 Hanaoka 349/139
7,304,691 B2 12/2007 Song et al.
7,733,430 B2 6/2010 Huang et al.
8,134,653 B2 3/2012 Huang et al.

2003/0002002 A1 * 1/2003 Kawachi et al. 349/143
2003/0043336 A1 * 3/2003 Sasaki et al. 349/187
2006/0061700 A1 3/2006 Chung et al.
2006/0146243 A1 * 7/2006 Nakanishi et al. 349/139
2008/0030636 A1 * 2/2008 Huang et al. 349/38
2008/0036931 A1 * 2/2008 Chan et al. 349/38
2008/0123038 A1 * 5/2008 Suwa et al. 349/129
2010/0201935 A1 8/2010 Huang et al.

FOREIGN PATENT DOCUMENTS

CN 1912699 2/2007
TW 200809349 2/2008
WO 2007135853 11/2007

OTHER PUBLICATIONS

"Office Action of Taiwan Counterpart Application", issued on Mar. 30, 2012, p. 1-p. 11, in which the listed references were cited.

* cited by examiner

Primary Examiner — Edward Glick



Assistant Examiner — Sang Nguyen

(74) *Attorney, Agent, or Firm* — Jianq Chyun IP Office

(57) **ABSTRACT**

A liquid crystal display panel including a first substrate, a liquid crystal layer, an alignment layer, a polymer layer, scan lines, data lines, pixel structures, first capacitor bottom electrodes and second capacitor bottom electrodes, and a manufacturing method thereof are provided. Each pixel structure has a first pixel electrode and a second pixel electrode. Each first capacitor bottom electrode is disposed between the first pixel electrode and the first substrate. Each second capacitor bottom electrode disposed between the second pixel electrode and the first substrate includes a first pattern and a plurality of second patterns. The first pattern extends from a first side to an opposite second side of the second pixel electrode. The second patterns connected to the first pattern are disposed on the first side and the second side. The second pattern at least partly overlaps a region between the second pixel electrode and the data line.

7 Claims, 15 Drawing Sheets






FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 1E




FIG. 1F





FIG. 2






FIG. 3B





FIG. 3C








FIG. 3E








FIG. 4

LIQUID CRYSTAL DISPLAY PANEL AND MANUFACTURING METHOD THEREOF

CROSS-REFERENCE TO RELATED APPLICATION

This application claims the priority benefit of Taiwan application serial no. 97124238, filed on Jun. 27, 2008. The entirety of the above-mentioned patent application is hereby incorporated by reference herein and made a part of specification.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a liquid crystal display panel and a manufacturing method thereof, and particularly to a polymer stabilized alignment liquid crystal display panel and a manufacturing method thereof.

2. Description of Related Art

As display technology advances, the use of displays makes our life much more convenient. Flat panel displays (FPD) have thus become the current trend for the characteristic of lightness and thinness. Among all flat panel displays, liquid crystal displays (LCD) are especially popular.

The demand for wider view angles of liquid crystal displays is growing. At present, multi-domain vertical alignment (MVA) liquid crystal display (LCD) panels are common application of wide view angle technology. A MVA-LCD panel utilizes an alignment structure to control liquid crystal molecules in different regions to tilt in different directions, and thereby achieves the effects of wide view angle. However, the tilt directions of the liquid crystal molecules around the alignment structure are usually not ideal so as to cause disclination, which may result in light leakage. Accordingly, an alignment method, which is formed by a polymer alignment together with a pixel electrode having a plurality of fine slits, is provided to improve the display effects of a MVA-LCD panel.

Polymer alignment technology is first to dope polymerizable molecules (monomers) with proper concentration into a liquid crystal material, wherein a liquid crystal mixture is called hereafter. Then, a voltage is applied to the liquid crystal mixture. When the liquid crystal molecules are stably arranged by the voltage, an ultraviolet light irradiation or a heating process is used to bond the polymerizable molecules (monomers) into a polymer layer, so as to complete the stabilized alignment process.

The voltage described above may be applied by a voltage of a capacitor electrode coupling to a pixel electrode. Conventionally, the capacitor electrode requires a higher voltage to enhance the capacitance coupling effect between the capacitor electrode and the pixel electrode, so as to control the arrangement of the liquid crystal molecules. Hence, during the polymer stabilized alignment process, a high voltage difference usually exists between the capacitor electrode not covered by the pixel electrode and an opposing electrode. If the area of the capacitor electrode not covered by the pixel electrode becomes larger, it will be more difficult to control the arrangement of liquid crystal molecules in certain areas. Accordingly, the problem of disclination therefore occurs.

SUMMARY OF THE INVENTION

The present invention provides a liquid crystal display panel for improving light leakage and non-uniform display when displaying images.

The present invention further provides a liquid crystal display panel having a favorable arrangement of liquid crystal molecules.

The present invention further provides a method for manufacturing the aforesaid liquid crystal display panel.

The present invention provides a liquid crystal display panel, comprising a first substrate, a second substrate, a liquid crystal layer, an opposing electrode, a plurality of scan lines, a plurality of data lines, a plurality of pixel structures, a plurality of first capacitor bottom electrodes, a plurality of second capacitor bottom electrodes, at least an alignment layer, and at least a polymer layer. The second substrate is opposite to the first substrate, and the liquid crystal layer is disposed between the first substrate and the second substrate. The opposing electrode is disposed between the second substrate and the liquid crystal layer. The scan lines and the data lines are disposed between the first substrate and the liquid crystal layer, and interlace each other. The pixel structures are disposed on the first substrate and electrically connected to the scan lines and the data lines, wherein each pixel structure has a first pixel electrode and a second pixel electrode. The first capacitor bottom electrodes are disposed between the first pixel electrodes and the first substrate, and the second capacitor bottom electrodes are disposed between the second pixel electrodes and the first substrate. In addition, each second capacitor bottom electrode comprises a first pattern and a plurality of second patterns connected to the first pattern. The first pattern extends from a first side of the corresponding second pixel electrode to an opposite second side thereof, and the second patterns are disposed on the first side and the second side. At least a portion of the second patterns overlaps a region between the second pixel electrode and the corresponding data lines. The alignment layer is disposed between the pixel structures and the opposing electrode, and the polymer layer is disposed between the alignment layer and the liquid crystal layer.

The present invention further provides a liquid crystal display panel, comprising a first substrate, a second substrate, a liquid crystal layer, an opposing electrode, a plurality of scan lines, a plurality of data lines, a plurality of pixel structures, a plurality of first capacitor bottom electrodes, a plurality of second capacitor bottom electrodes, at least an alignment layer, and at least a polymer layer. The second substrate is opposite to the first substrate, and the liquid crystal layer is disposed between the first substrate and the second substrate. The opposing electrode is arranged between the second substrate and the liquid crystal layer. The scan lines are disposed between the first substrate and the liquid crystal layer, and the data lines are disposed between the first substrate and the liquid crystal layer, wherein the scan lines and the data lines interlace one another. The pixel structures are disposed on the first substrate and electrically connected to the scan lines and the data lines, wherein each pixel structure comprises a first pixel electrode, a second pixel electrode, a first active device, and a second active device. The first active device and the second active device are electrically connected to one of the scan lines. The first active device and the second active device are respectively electrically connected to different data lines, and the first active device and the second active device are respectively electrically connected to the first pixel electrode and the second pixel electrode. The first capacitor bottom electrodes are disposed between the first pixel electrodes and the first substrate, and the second capacitor bottom electrodes are disposed between the second pixel electrodes and the first substrate. The alignment layer is disposed between the pixel

structures and the opposing electrode, and the polymer layer is disposed between the alignment layer and the liquid crystal layer.

The present invention further provides a method for manufacturing a liquid crystal display panel which comprises providing a semi-finished liquid crystal display panel first, wherein the semi-finished liquid crystal display panel includes a first substrate, a second substrate, a liquid crystal layer, an opposing electrode, a plurality of scan lines, a plurality of data lines, a plurality of polymerizable molecules, a plurality of pixel structures, a plurality of first capacitor bottom electrodes, a plurality of second capacitor bottom electrodes, and at least an alignment layer. The second substrate is opposite to the first substrate, and the liquid crystal layer is disposed between the first substrate and the second substrate. The opposing electrode is disposed between the second substrate and the liquid crystal layer. The scan lines and the data lines are disposed between the first substrate and the liquid crystal layer, and interlace each other. The pixel structures are disposed on the first substrate and electrically connected to the scan lines and the data lines, wherein each pixel structure has a first pixel electrode and a second pixel electrode, and the blocks of the liquid crystal layer corresponding to the first pixel electrodes and the second pixel electrodes are respectively a plurality of first blocks and a plurality of second blocks. The first capacitor bottom electrodes are disposed between the first pixel electrodes and the first substrate, and the second capacitor bottom electrodes are disposed between the second pixel electrodes and the first substrate. In addition, each second capacitor bottom electrode comprises a first pattern and a plurality of second patterns connected to the first pattern. The first pattern extends from a first side of the corresponding second pixel electrode to an opposite second side thereof, and the second patterns are disposed on the first side and the second side, wherein at least a portion of the second patterns overlaps a region between the second pixel electrode and the corresponding data lines. The alignment layer is disposed between the pixel structures and the opposing electrode, and the polymerizable molecules are doped into the liquid crystal layer. Then, a first voltage difference and a second voltage difference are respectively formed in the first blocks and the second blocks respectively, wherein the first voltage difference is different from the second voltage difference. Accordingly, the polymerizable molecules are polymerized to form a liquid crystal display panel.

The present invention further provides a method for manufacturing a liquid crystal display panel which comprises providing a semi-finished liquid crystal display panel, wherein the semi-finished liquid crystal display panel includes a first substrate, a second substrate, a liquid crystal layer, an opposing electrode, a plurality of scan lines, a plurality of data lines, a plurality of polymerizable molecules, a plurality of pixel structures, a plurality of first capacitor bottom electrodes, a plurality of second capacitor bottom electrodes, and at least an alignment layer. The second substrate is opposite to the first substrate, and the liquid crystal layer is disposed between the first substrate and the second substrate. The opposing electrode is disposed between the second substrate and the liquid crystal layer. The scan lines and the data lines are disposed between the first substrate and the liquid crystal layer, and interlace each other. The pixel structures are disposed on the first substrate and electrically connected to the scan lines and the data lines, wherein each pixel structure comprises a first pixel electrode, a second pixel electrode, a first active device, and a second active device. The first active device and the second active device are electrically connected to one of the scan lines. The first active device and the second

active device are respectively electrically connected to different data lines, and the first active device and the second active device are respectively electrically connected to the first pixel electrode and the second pixel electrode, wherein the blocks of the liquid crystal layer corresponding to the first pixel electrodes and the second pixel electrodes are respectively a plurality of first blocks and a plurality of second blocks. The first capacitor bottom electrodes are disposed between the first pixel electrodes and the first substrate, and the second capacitor bottom electrodes are disposed between the second pixel electrodes and the first substrate. The alignment layer is disposed between the pixel structures and the opposing electrode, and the polymerizable molecules are doped into the liquid crystal layer. Then, a first voltage difference and a second voltage difference are respectively formed in the first blocks and the second blocks for polymerizing the polymerizable molecules to form a liquid crystal display panel, wherein the first voltage difference is different from the second voltage difference.

In an embodiment of the present invention, the second pixel electrode comprises an intersection pattern and a plurality of stripe patterns, wherein the stripe pattern has a first end connected to the intersection pattern and a second end away from the intersection pattern, and the stripe patterns are apart from each other.

In an embodiment of the present invention, the second patterns of the second capacitor bottom electrodes are disposed under at least a portion of the second ends.

In an embodiment of the present invention, the intersection pattern comprises a first direction section and a second direction section, wherein the first direction section interlaces the second direction section, and the first patterns of the second capacitor bottom electrodes are substantially parallel to the first direction section. In an embodiment, the first direction section is substantially perpendicular to the second direction section.

In an embodiment of the present invention, the first patterns and the second patterns of the second capacitor bottom electrodes may be arranged in an H shape, a U shape, a reversed U shape, or an N shape.

In an embodiment of the present invention, a V-shaped main slit may be formed between the first pixel electrode and the second pixel electrode, wherein the V-shaped main slit includes a pointed end and two side sections connected to the pointed end. The pointed end is arranged toward the second pixel electrode, and an edge of the first pixel electrode and an edge of the second pixel electrode adjacent to each side section are substantially parallel to each other.

In an embodiment of the present invention, the first pixel electrode includes a first intersection pattern, a plurality of first stripe patterns, and a V-shaped connection pattern. An end of each first stripe pattern is connected to the first intersection pattern, and the other end of each first stripe pattern is away from the first intersection pattern. In addition, the first stripe patterns are apart from one another. The V-shaped connection pattern connects a portion of the first stripe patterns with the first intersection pattern, and the V-shaped main slit is disposed between the V-shaped connection pattern and the second pixel electrodes.

In an embodiment of the present invention, the second pixel electrode comprises a second intersection pattern and a plurality of second stripe patterns. The second stripe patterns are substantially apart from one another. An end of each second stripe pattern is connected to the second intersection pattern, and the other end of each second stripe pattern is away from the second intersection pattern, wherein two of the second stripe patterns are adjacent to the V-shaped main slit.

In an embodiment of the present invention, a liquid crystal display panel further comprises a plurality of first capacitor top electrodes and a plurality of coupling electrodes. The first capacitor top electrodes are disposed between the first pixel electrodes and the first capacitor bottom electrodes, and the first capacitor top electrodes are electrically connected to the first pixel electrodes. A portion of the coupling electrodes is arranged between the first capacitor bottom electrodes and the first pixel electrodes, and the coupling electrodes are electrically connected to the second pixel electrodes.

In an embodiment of the present invention, the opposing electrode may be electrically connected to the second capacitor bottom electrodes.

In an embodiment of the present invention, the pixel structure further comprises a first active device and a second active device, wherein the first active device and the second active device are electrically connected to one of the scan lines and one of the data lines, and the first active device and the second active device are respectively electrically connected to the first pixel electrode and the second pixel electrode.

In an embodiment of the present invention, the pixel structure further comprises a first active device and a second active device, wherein the first active device and the second active device are electrically connected to one of the scan lines. Additionally, the first active device and the second active device are respectively electrically connected to different data lines, and the first active device and the second active device are respectively electrically connected to the first pixel electrode and the second pixel electrode.

In an embodiment, the pixel structure further comprises a third pixel electrode electrically connected to the second pixel electrode. In an embodiment, the second capacitor bottom electrode further comprises a third pattern parallel to the first pattern. The third pattern is disposed between the third pixel electrode and the first substrate, and a portion of each second pattern further extends to a side of the third pixel electrode to connect the third pattern.

In an embodiment of the present invention, a method for forming the first voltage difference and the second voltage difference comprises respectively providing a first voltage, a second voltage, and a third voltage to the first capacitor bottom electrodes, the second capacitor bottom electrodes, and the opposing electrode. In an embodiment, the first voltage is substantially larger than the second voltage, wherein the second voltage is substantially equal to the third voltage.

In an embodiment of the present invention, the first pixel electrodes and the second pixel electrodes are electrically connected to different data lines, and a method for forming the first voltage difference and the second voltage difference comprises respectively providing a first voltage and a second voltage to the first pixel electrodes and the second pixel electrodes by the data lines, wherein the first voltage and the second voltage are different. Moreover, a third voltage is provided to the opposing electrode.

In an embodiment of the present invention, the first voltage is substantially equal to 0~80 volts, the second voltage is substantially equal to 0~80 volts, and the third voltage is substantially equal to 0~80 volts.

In an embodiment of the present invention, the polymerizable molecules are, for example, a plurality of photo-polymerizable molecules, and a method for polymerizing the polymerizable molecules comprises a light illuminating method. In an embodiment, the light illuminating method is, for example, to use an ultraviolet light.

In an embodiment of the present invention, the polymerizable molecules are polymerized on the first substrate to form the polymer layer between the alignment layer and the liquid crystal layer.

In the liquid crystal display panel of the present invention, a portion of the second capacitor bottom electrodes is arranged between the second pixel electrodes and neighboring data lines. Hence, the second capacitor bottom electrodes also help to reduce the crosstalk effect which occurs between the second pixel electrodes and the data lines. Additionally, in the manufacturing method of the present invention, a common voltage of the opposing electrode may be applied to the second capacitor electrodes or different voltages may be respectively applied to the pixel electrodes through different data lines during the polymer stabilized alignment process. Hence, the capacitor electrodes which are not covered by the pixel electrodes do not influence the arrangement direction of the liquid crystal molecules during the polymer stabilized alignment process. Consequently, the liquid crystal molecules in the liquid crystal display panel are tilted and arranged in a favorable way.

To make the above features and advantages of the present invention more comprehensible, several embodiments accompanied with figures are described in detail as follows.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings are included to provide a further understanding of the invention, and are incorporated in and constitute a part of this specification. The drawings illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention.

FIG. 1A illustrates a schematic view of a liquid crystal display panel according to the first embodiment of the present invention.

FIG. 1B illustrates a cross-sectional view along line L1-L1' in FIG. 1A.

FIGS. 1C and 1D illustrate a method for manufacturing the liquid crystal display panel along line L2-L2' in FIG. 1A.

FIGS. 1E and 1F illustrate a method for manufacturing the liquid crystal display panel along line L3-L3' in FIG. 1A.

FIG. 2 illustrates a partial top view of a liquid crystal display panel according to the second embodiment of the present invention.

FIG. 3A illustrates a partial top view of a liquid crystal display panel according to the third embodiment of the present invention.

FIG. 3B illustrates a cross-sectional view of the liquid crystal display panel in the third embodiment.

FIG. 3C illustrates another cross-sectional view of the liquid crystal display panel in the third embodiment.

FIG. 3D illustrates a top view of another liquid crystal display panel according to the third embodiment of the present invention.

FIG. 3E illustrates a top view of yet another liquid crystal display panel according to the third embodiment of the present invention.

FIGS. 3F and 3G illustrate the top views of another two liquid crystal display panels according to the third embodiment of the present invention.

FIG. 4 illustrates an equivalent circuit diagram of the liquid crystal display panel according to the third embodiment of the present invention.

DESCRIPTION OF EMBODIMENTS

First Embodiment

FIG. 1A illustrates a schematic view of a liquid crystal display panel according to the first embodiment of the present invention.

invention, and FIG. 1B illustrates a cross-sectional view along Line L1-L1' in FIG. 1A. Referring to FIGS. 1A and 1B, a liquid crystal display panel 100 comprises a first substrate 110, a second substrate 120, a liquid crystal layer 130, an opposing electrode 140, a plurality of scan lines 150, a plurality of data lines 160, a plurality of pixel structures 170, a plurality of first capacitor bottom electrodes 180, a plurality of second capacitor bottom electrodes 190, at least an alignment layer 200, and at least a polymer layer 210. The liquid crystal display panel 100 is substantially a polymer stabilized alignment liquid crystal display panel. Herein, FIGS. 1A and 1B merely illustrate a part of the elements in an area of one pixel structure 170.

Based on the above, the second substrate 120 is opposite to the first substrate 110, and the liquid crystal layer 130 is disposed between the first substrate 110 and the second substrate 120. The opposing electrode 140 is disposed between the second substrate 120 and the liquid crystal layer 130. The scan lines 150 and the data lines 160 are disposed between the first substrate 110 and the liquid crystal layer 130 and interlace each other. The alignment layer 200 is disposed between the pixel structures 170 and the opposing electrode 140, and the polymer layer 210 is disposed between the alignment layer 200 and the liquid crystal layer 130. The pixel structures 170 are disposed on the first substrate 110 and electrically connected to the scan lines 150 and the data lines 160. Each pixel structure 170 has a first pixel electrode 172 and a second pixel electrode 174.

The first capacitor bottom electrodes 180 are at least disposed between the first pixel electrodes 172 and the first substrate 110. Particularly, most portion of the area of the first capacitor bottom electrodes 180 is disposed in the area where the first pixel electrodes are located, and a portion thereof further extends to the area where the second pixel electrodes are located. In addition, the second capacitor bottom electrodes 190 are disposed between the second pixel electrodes 174 and the first substrate 110.

When the liquid crystal display panel 100 displays images, the first capacitor bottom electrodes 180 and the second capacitor bottom electrodes 190 may have the same potential as the opposing electrode 140. Further, a portion of the first capacitor bottom electrodes 180 overlaps the first pixel electrodes 172, and a portion of the second pixel electrodes 174 overlaps the second capacitor bottom electrodes 190. Hence, a capacitance effect provided by the first capacitor bottom electrodes 180 helps to maintain a voltage difference between the first pixel electrodes 172 and the opposing electrode 140. Similarly, the capacitance effect provided by the second capacitor bottom electrodes 190 also helps to maintain the voltage difference between the second pixel electrodes 174 and the opposing electrode 140.

To improve display quality, in practice, two active devices 176a and 176b respectively electrically connected to the first pixel electrodes 172 and the second pixel electrodes 174 may be disposed on the first substrate 110. The active devices 176a and 176b are respectively used for controlling the display voltages of the first pixel electrodes 172 and the second pixel electrodes 174. When the liquid crystal display panel 100 displays images, a potential difference between the first pixel electrodes 172 and the opposing electrode 140 is, for example, larger than or equal to the potential difference between the second pixel electrodes 174 and the opposing electrode 140, so as to achieve different display brightness. Consequently, the images of the liquid crystal display panel 100 are properly improved to achieve better display effects.

Generally speaking, the larger the areas of the first pixel electrodes 172 and the second pixel electrodes 174 are, the

better the aperture ratio (AR) of the liquid crystal display panel 100 becomes. However, as the aperture ratio excessively increases, the first pixel electrodes 172 and the second pixel electrodes 174 become closer to the data lines 160. Under this circumstance, crosstalk effect may occur in the liquid crystal display panel 100. For instance, as the second pixel electrodes 174 are closer to the data lines 160, the capacitance coupling effect between the second pixel electrodes 174 and the data lines 160 becomes more significant. In other words, the second pixel electrodes 174 and the signals of the data lines 160 interfere with each other.

To solve the aforesaid problem, the second capacitor bottom electrodes 190 in this embodiment are, for example, arranged in an H shape, so as to reduce the crosstalk effect between the data lines 160 and the second pixel electrodes 174. To be more specific, the second capacitor bottom electrode 190 in this embodiment comprises a first pattern 190a and a plurality of second patterns 190b connected to the first pattern 190a, wherein the first pattern 190a and the second patterns 190b of the second capacitor bottom electrode 190 may be arranged in an H shape. For instance, the first pattern 190a extends from a first side S1 of the second pixel electrode 174 to a second side S2 thereof, and the second patterns 190b are arranged on the first side S1 and the second side S2, wherein the first side S1 is opposite to the second side S2.

Moreover, at least a portion of the second patterns 190b overlaps a region between the second pixel electrode 174 and the data lines 160. When the liquid crystal display panel 100 displays images, the capacitance coupling effect between the second pixel electrode 174 and the data lines 160 can be effectively reduced to avoid crosstalk effect. In other words, the second patterns 190b of the second capacitor bottom electrode 190 provide favorable shielding effect to reduce the signal interference between the second pixel electrode 174 and the data lines 160.

In other embodiments, the first pattern 190a may be connected to two ends or one end of each second pattern 190b according to the designer's requirements. For example, the first pattern 190a and the second patterns 190b may be arranged in a U shape, a reversed U shape, or an N shape.

Additionally, the liquid crystal display panel 100 may further comprise a plurality of first capacitor top electrodes 220. The first capacitor top electrodes 220 are disposed between the first pixel electrodes 172 and the first capacitor bottom electrodes 180. In other words, the first capacitor top electrodes 220 are disposed in where the first pixel electrodes 172 are located. When the liquid crystal display panel 100 displays images, the storage capacitance formed between the first capacitor bottom electrodes 180 and the first capacitor top electrodes 220 also helps to maintain the voltage difference between the first pixel electrodes 172 and the opposing electrode 140. Certainly, the first capacitor top electrodes 220 may be selectively not disposed between the first pixel electrodes 172 and the first capacitor bottom electrodes 180 in other embodiments. In other words, in where the first pixel electrodes 172 are located, the storage capacitance may be formed only by the capacitance effect between the first pixel electrodes 172 and the first capacitor bottom electrodes 180.

Moreover, the liquid crystal display panel 100 further comprises a plurality of coupling electrodes 230 (FIG. 1B only illustrates one of the coupling electrodes in a single pixel structure), wherein the coupling electrodes 230 extend from where the first pixel electrodes 172 are located to where the second pixel electrodes 174 are located. In the pixel structure 170, the coupling electrode 230 is electrically connected to the active device 176b and the second pixel electrode 174. In other words, the display voltage of the second pixel electrode

174 may be transmitted to the second pixel electrode 174 through the active device 176b and the coupling electrode 230 by the data line 160. In addition, a portion of the area of the coupling electrode 230 overlaps a portion of the area of the second capacitor bottom electrode 190. When the liquid crystal display panel 100 displays images, the storage capacitance effect provided by the coupling electrodes 230 helps to maintain the voltage difference between the second pixel electrodes 174 and the opposing electrode 140.

As shown in FIG. 1A, in this embodiment, the second pixel electrode 174 comprises an intersection pattern 174a and a plurality of stripe patterns 174b apart from each other, wherein the intersection pattern 174a comprises a first direction section 274a and a second direction section 374a. Further, the first direction section 274a and the second direction section 374a interlace each other, wherein the first pattern 190a of the second capacitor bottom electrode 190 is, for example, parallel to the first direction section 274a, and the first direction section 274a is, for example, perpendicular to the second direction section 374a. Moreover, an end of each stripe pattern 174b is connected to the intersection pattern 174a, and the other end of each stripe pattern 174b is away from the intersection pattern 174a. The second patterns 190b of the second capacitor bottom electrodes 190 are, for example, arranged under the ends of a portion of the stripe patterns 174b, which are away from the intersection pattern 174a.

Based on the above, the intersection pattern 174a divides the area of the second pixel electrodes into four areas I, II, III, and IV. The stripe patterns 174b in the areas I, II, III, and IV respectively extend from the intersection pattern 174a toward the directions of 45°, 135°, 225°, and 315°. When the liquid crystal display panel 100 displays images, the electric field effect caused by the stripe patterns 174b makes the liquid crystal molecules in the areas I, II, III, and IV tilt toward the directions of 45°, 135°, 225°, and 315°, so as to achieve wide view angle.

It is noted that the first pixel electrodes 172 in this embodiment may also be formed by an intersection pattern (not shown) and a plurality of stripe patterns (not shown). In other words, when the liquid crystal display panel 100 displays images, the liquid crystal molecules above where the first pixel electrodes 172 are located may also be arranged in multi-domain alignment to achieve wide view angle. As a whole, the liquid crystal display panel 100 in this embodiment at least provides the display effects of wide view angle, high display aperture ratio, and high image quality.

FIGS. 1C and 1D illustrate a method for manufacturing the liquid crystal display panel along line L2-L2' in FIG. 1A, and FIGS. 1E and 1F illustrate a method for manufacturing the liquid crystal display panel along line L3-L3' in FIG. 1A. Referring to FIGS. 1C and 1E, a semi-finished liquid crystal display panel 100' is provided. The semi-finished liquid crystal display panel 100' comprises a first substrate 110, a second substrate 120, a liquid crystal layer 130, an opposing electrode 140, a plurality of scan lines 150, a plurality of data lines 160, a plurality of pixel structures 170, a plurality of first capacitor bottom electrodes 180, a plurality of second capacitor bottom electrodes 190, at least an alignment layer 200, and a plurality of polymerizable molecules (monomers) 210'. The blocks of the liquid crystal layer 130 corresponding to the first pixel electrodes 172 and the second pixel electrodes 174 are respectively the first blocks B172 and the second blocks B174.

The arrangement of the first substrate 110, the second substrate 120, the liquid crystal layer 130, the opposing electrode 140, the scan lines 150, the data lines 160, the pixel

structures 170, the first capacitor bottom electrodes 180, the second capacitor bottom electrodes 190, and the alignment layer 200 is similar to that in FIG. 1A. The arrangement of these elements may be referred to in FIG. 1A. Hence, the descriptions thereof are omitted here. It is noted that the polymerizable molecules 210' are doped into the liquid crystal layer 130. The polymerizable molecules 210' are a plurality of photo-polymerizable molecules, for example. Certainly, thermal polymerizable molecules or other molecules which can be polymerized under certain mechanisms may also serve as the polymerizable molecules 210'.

Then, referring to FIGS. 1D and 1F, a first voltage difference ΔV_1 and a second voltage difference ΔV_2 are respectively formed in the first blocks B172 and the second blocks B174, wherein the first voltage difference ΔV_1 is different from the second voltage difference ΔV_2 . At the same time, the first voltage difference ΔV_1 and the second voltage difference ΔV_2 make the liquid crystal molecules in the liquid crystal layer 130 to be arranged in a specific way. After the arrangement of the liquid crystal molecules becomes stable, the polymerizable molecules 210' are polymerized. In this embodiment, an ultraviolet light is used to perform a light illuminating method for polymerizing the polymerizable molecules 210' to form the polymer layer 210 on the first substrate 110 and the second substrate 120 respectively. Thereby, the fabrication of the liquid crystal display panel 100 in this embodiment is roughly completed. In other embodiments, the polymer layer 210 may be formed only on a side of the liquid crystal layer 130 by controlling the fabricating conditions.

In the polymer stabilized alignment process of this embodiment, a method for forming the first voltage difference ΔV_1 and the second voltage difference ΔV_2 is described as follows. Referring to FIG. 1D, in this embodiment, the method for forming the first voltage difference ΔV_1 is, for example, to respectively provide a first voltage V_1 and a third voltage V_3 to the first capacitor bottom electrodes 180 and the opposing electrode 140. Consequently, the first voltage difference ΔV_1 is formed in the first blocks B172 by the capacitance coupling effect between the first capacitor bottom electrodes 180 and the first capacitor top electrodes 220, the coupling electrodes 230, and the first pixel electrodes 172. In other words, a specific intensity of electric field is generated in the first blocks B172.

Additionally, a portion of the coupling electrodes 230 is disposed in where the first pixel electrodes 172 are located, and the other portion of the coupling electrodes 230 is disposed in where the second pixel electrodes 174 are located. Further, the coupling electrodes 230 are electrically connected to the second pixel electrodes 174. Hence, when the first voltage V_1 is provided to the first capacitor bottom electrodes 180, the capacitance coupling effect between the coupling electrodes 230 and the first capacitor bottom electrodes 180 also influences the potential of the second pixel electrodes 174.

Moreover, referring to FIG. 1F, a second voltage V_2 is provided to the second capacitor bottom electrodes 190 during the polymer stabilized alignment process. As a consequence, capacitance coupling effect also occurs between the second capacitor bottom electrodes 190 and the second pixel electrodes 174. The capacitance coupling effect in where the second pixel electrodes 174 are located is integrated to form the second voltage difference ΔV_2 in the second blocks B174. In other words, another specific intensity of electric field is generated in the second blocks B174.

In brief, the first voltage V_1 , the second voltage V_2 , and the third voltage V_3 are respectively provided to the first capacitor

bottom electrodes **180**, the second capacitor bottom electrodes **190**, and the opposing electrode **140**, wherein the first voltage V_1 is larger than or equal to the second voltage V_2 , and the first voltage difference ΔV_1 is formed in the first blocks **B172** and the second voltage difference ΔV_2 is formed in the second blocks **B174**. In the polymer stabilized alignment process, the first voltage difference ΔV_1 and the second voltage difference ΔV_2 are respectively conducive to polymerize the polymerizable molecules **210'** in the first blocks **B172** and the second blocks **B174** in different forms, so as to form the polymer layer **210**. Thereby, the liquid crystal molecules in different areas can be arranged in different pre-tilt angles, for example.

It is noted that, in the polymer stabilized alignment process of this embodiment, the first voltage V_1 is substantially larger than the second voltage V_2 , and the second voltage V_2 is substantially equal to the third voltage V_3 . The first voltage V_1 is substantially equal to 0~80 volts, the second voltage V_2 is substantially equal to 0~80 volts, and the third voltage V_3 is substantially equal to 0~80 volts. According to the top view in FIG. 1A, in where the second pixel electrodes **174** are located, a portion of the second patterns **190b** of the second capacitor bottom electrodes **190** is not covered by the second pixel electrodes **174**. Hence, if a large voltage is applied to the second capacitor bottom electrodes **190** during the polymer stabilized alignment process, the tilt directions of the liquid crystal molecules above the second patterns **190b** easily become indefinite and cause light leakage. Thus, in this embodiment, a smaller voltage, the second voltage V_2 , is applied to the second capacitor bottom electrodes **190** to avoid the problem of poorly arranged liquid crystal molecules above the second patterns **190b** caused by a large voltage.

In this embodiment, the second capacitor bottom electrodes **190** are, for example, arranged in an H shape. Such a design helps to reduce the capacitance coupling effect between the data lines **160** and the second pixel electrodes **174** without influencing the aperture ratio. Furthermore, the second capacitor bottom electrodes **190** are provided with a smaller voltage during the polymer stabilized alignment process, which helps to properly arrange the liquid crystal molecules above the second patterns **190b**.

In the polymer stabilized alignment process, the second capacitor bottom electrodes **190** and the opposing electrode **140** are, for example, applied with the same voltage. When the liquid crystal display panel **100** displays images, the first capacitor bottom electrodes **180** and the second capacitor bottom electrodes **190** are also applied with the same voltage as the opposing electrode **140**. Therefore, in this embodiment the second capacitor bottom electrodes **190** can be directly electrically connected to the opposing electrode **140**, or the second capacitor bottom electrodes **190** and the opposing electrode **140** can be connected to the same voltage source, for example.

Because the liquid crystal molecules in the liquid crystal display panel **100** are tilted and arranged properly, the problems of light leakage and non-uniform display which occur above the second patterns **190b** of the second capacitor bottom electrodes **190** are improved. Briefly, the liquid crystal display panel **100** in this embodiment has favorable display quality.

Second Embodiment

FIG. 2 illustrates a partial top view of a liquid crystal display panel according to the second embodiment of the present invention, and FIG. 2 only illustrates the area of one pixel structure. Referring to FIG. 2, a liquid crystal display

panel **400** in this embodiment is similar to the liquid crystal display panel **100** described in the first embodiment. It is to say that FIG. 2 which illustrates this embodiment is similar to FIG. 1A which illustrates the first embodiment, wherein the same elements are indicated by the same reference numbers. The descriptions thereof are therefore not repeated here.

As shown in FIG. 2, in this embodiment, a V-shaped main slit MS is formed between a first pixel electrode **472** and a second pixel electrode **474** of a pixel structure **470**, wherein the V-shaped main slit MS comprises a pointed end MS₁ and two side sections MS₂ connected to the pointed end MS₁. The pointed end MS₁ is pointed toward the second pixel electrode **474**, and an edge E1 of the first pixel electrode **472** and an edge E2 of the second pixel electrode **474** adjacent to each side section MS₂ are substantially parallel to each other.

Specifically, the first pixel electrode **472** in this embodiment comprises a first intersection pattern **472a**, a plurality of first stripe patterns **472b** apart from one another, and a V-shape connection pattern **472c**, wherein an end of each first stripe pattern **472b** is connected to the first intersection pattern **472a**, and the other end thereof is away from the first intersection pattern **472a**. The V-shaped connection pattern **472c** connects the ends of a portion of the first stripe patterns **472b** away from the first intersection pattern **472a** and an end of the first intersection pattern **472a** close to the V-shaped main slit MS. Additionally, the V-shaped main slit MS is arranged between the V-shaped connection pattern **472c** and the second pixel electrode **474**. In other words, the edge of the first pixel electrode **472** adjacent to the second pixel electrode **474** is enclosed.

In practice, the second pixel electrode **474** may be formed by a second intersection pattern **474a** and a plurality of second stripe patterns **474b** apart from one another, wherein two of the second stripe patterns **474b** are adjacent to the V-shaped main slit MS. Moreover, an end of each second stripe pattern **474b** is connected to the second intersection pattern **474a**, and the other end thereof is away from the second intersection pattern **474a**.

When the liquid crystal display panel **400** displays images, the liquid crystal molecules respectively tilt along the extended directions of the stripe patterns **472a** and **474b**, so as to achieve wide view angle. It is noted that the tilt direction of the liquid crystal molecules above one of the side sections MS₂ (MS₂ at the right side in FIG. 2) is, for example, from 315° to 45°. The tilt direction of the liquid crystal molecules above the other side section MS₂ (MS₂ at the left side in FIG. 2) is, for example, from 225° to 135°.

When viewing the images displayed by the liquid crystal display panel **400** in a horizontal direction, the liquid crystal molecules above the V-shaped main slit MS do not easily tilt along the directions of 90° or 270°, and thus a poor display area is avoided. Because of the design of the V-shaped main slit MS, color shift and color washout which occur when the liquid crystal display panel **400** is viewed in different angles can be improved.

The fabricating processes of the liquid crystal display panel **400** in this embodiment are similar to those of the liquid crystal display panel **100** in the first embodiment. Hence, persons with ordinary knowledge in this field may refer to FIGS. 1C to 1F and the relevant descriptions for the manufacturing method of the liquid crystal display panel **400** in this embodiment. Based on the above, this embodiment not only has the advantages which the first embodiment has but also further improves the display effects of the liquid crystal display panel **400**.

A Third Embodiment

FIG. 3A illustrates a partial top view of a liquid crystal display panel according to the third embodiment of the

present invention, and FIG. 3A only illustrates the area of one pixel structure. A liquid crystal display panel 700 in this embodiment is similar to the liquid crystal display panel 100 described in the first embodiment. It is to say that FIG. 3A which illustrates this embodiment is similar to FIG. 1A which illustrates the first embodiment, wherein the same or similar elements are indicated by the same or similar reference numbers. The descriptions thereof are therefore not repeated here.

Referring to FIG. 3A, the liquid crystal display panel 700 in this embodiment comprises a plurality of data lines 760, a plurality of pixel structures 770, a plurality of first capacitor bottom electrodes 780, and a plurality of second capacitor bottom electrodes 190 which are substantially different from those described in the first embodiment.

As shown in FIG. 3A, the pixel structure 770 further comprises a first active device 776a and a second active device 776b. In the pixel structure 770, the first active device 776a and the second active device 776b are electrically connected to the same scan line 150. However, the first active device 776a and the second active device 776b are respectively electrically connected to a data line 760a and a data line 760b. In addition, the first active device 776a and the second active device 776b are respectively electrically connected to a first pixel electrode 772 and a second pixel electrode 774. In other words, the first pixel electrode 772 and the second pixel electrode 774 respectively receive data signals from different data lines 760a and 760b.

It is noted that the first capacitor bottom electrode 780 in this embodiment also comprises a first pattern 780a and a plurality of second patterns 780b, wherein the first pattern 780a and the second patterns 780b may be arranged in an H shape. In other embodiments, the first pattern 780a and the second patterns 780b may also be arranged in a U shape, a reversed U shape, or an N shape. Certainly, the first capacitor bottom electrode 780 is not necessarily formed by the first pattern 780a and the second patterns 780b. According to the designer's requirements, the first capacitor bottom electrode 780 in this embodiment may be designed to be similar to the first capacitor bottom electrode 180 in the first or the second embodiment.

In the H-shaped first capacitor bottom electrodes 780 and the H-shaped second capacitor bottom electrodes 190 of this embodiment, the second patterns 780b and the second patterns 190b both provide proper shielding effect. Accordingly, the crosstalk effects between the data lines 760 and the first pixel electrodes 772 and between the data lines 760 and the second pixel electrodes 774 are improved. In other words, the liquid crystal display panel 700 provides favorable display quality. However, H-shaped first capacitor bottom electrodes 780 and straight-line type second capacitor bottom electrodes parallel to the scan lines 150, or straight-line type first capacitor bottom electrodes parallel to the scan lines 150 and H-shaped second capacitor bottom electrodes 190 may be also applied in this embodiment, but the present invention is not limited thereto.

Further, FIG. 3B is, for example, a cross-sectional view along Line L4-L4' in FIG. 3A, and FIG. 3C is, for example, a cross-sectional view along Line L5-L5' in FIG. 3A. Referring to the cross-sectional views in FIGS. 3B and 3C, the liquid crystal display panel 700 further comprises the alignment layer 200 and the polymer layer 210 disposed between the first substrate 110 and the second substrate 120. It is to say that the liquid crystal display panel 700 in this embodiment is a polymer stabilized alignment liquid crystal display panel.

The polymer stabilized alignment process requires respectively forming a voltage difference between the first pixel electrodes 772 and the opposing electrode 140 and between

the second pixel electrodes 774 and the opposing electrode 140. To form the voltage differences, conventionally a relative larger voltage is applied to the first capacitor bottom electrodes 780 and the second capacitor bottom electrodes 190, and a relative smaller voltage is applied to the opposing electrode 140. However, a portion of the areas of the H-shaped first capacitor bottom electrodes 780 and second capacitor bottom electrodes 190 in this embodiment is not covered by the corresponding pixel electrodes (772 and 774). When the larger voltage is applied to the first capacitor bottom electrodes 780 and the second capacitor bottom electrodes 190, the arrangement of the liquid crystal molecules may be disordered due to the exposure of the second patterns 780b and 190b.

Moreover, the scan lines 150 in this embodiment are arranged between the first pixel electrodes 772 and the second pixel electrodes 774. Consequently, when the data lines 760a and 760b are respectively electrically connected to the first pixel electrodes 772 and the second pixel electrodes 774 through the first active device 776a and the second active device 776b, the signals of the data line 760b are not required to be transmitted to the second pixel electrodes 774 through the first pixel electrodes 772. Hence, besides the methods mentioned in the aforesaid embodiments, the polymer stabilized alignment process in this embodiment can also utilize the data lines 760a and 760b to apply different voltages to the first pixel electrodes 772 and the second pixel electrodes 774.

To be more specific, the polymer stabilized alignment process in this embodiment uses the first and the second active devices 776a and 776b to respectively transmit a first voltage V_1' and a second voltage V_2' provided by the data lines 760a and 760b to the first pixel electrodes 772 and the second pixel electrodes 774, and provides a third voltage V_3' to the opposing electrode 140, wherein the first voltage V_1' and the second voltage V_2' are not equal. For instance, the first voltage V_1' is substantially equal to 0~80 volts, the second voltage V_2' is substantially equal to 0~80 volts, and the third voltage V_3' is substantially equal to 0~80 volts. Thereby, the first blocks B772 and the second blocks B774 have different voltage differences. It is to say that the first blocks B772 and the second blocks B774 have different intensity of electric field. In other words, this embodiment does not respectively apply large voltages to the first capacitor bottom electrodes 780 and the second capacitor bottom electrodes 190. Consequently, during the polymer stabilized alignment process, a high voltage difference does not exist between the opposing electrode 140 and the first and the second capacitor bottom electrodes 780 and 190 not covered by the first and the second pixel electrodes 772 and 774. Hence, the arrangement of the liquid crystal molecules above the second patterns 780b (belong to the first capacitor bottom electrodes 780) and the second patterns 190b (belong to the second capacitor bottom electrodes 190) is not disordered.

In addition, FIG. 3D illustrates a top view of another liquid crystal display panel according to the third embodiment of the present invention. Referring to a liquid crystal display panel 800 in FIG. 3D, a pixel structure 870 in this embodiment further comprises a third pixel electrode 876, wherein the third pixel electrode 876 is electrically connected to the second pixel electrode 774. Additionally, the second capacitor bottom electrode 890 further comprises a third pattern 890c, wherein the third pattern 890c is disposed between the third pixel electrode 876 and the first substrate 110 to be approximately parallel to the first pattern 190a. A portion of the second patterns 190b further extends to a side of the third pixel electrode 876 to connect the third pattern 890c. In addition to the advantages of the liquid crystal display panel 700,

the liquid crystal display panel **800** achieves the effect of alignment in more domains of the liquid crystal molecules.

Further, FIG. 3E illustrates a top view of yet another liquid crystal display panel according to the third embodiment of the present invention. Referring to FIG. 3E, a liquid crystal display panel **900** is substantially similar to the liquid crystal display panel **800**. The difference merely lies in that the liquid crystal display panel **900** further comprises a plurality of third active devices **776c** electrically connected to the third pixel electrode **876**. In addition, the third active devices **776c** are electrically coupled with the second active devices **776b**. In other words, the third active devices **776c** and the second active devices **776b** are electrically connected to the same scan lines **150** and data lines **760b**, and the third pixel electrode **876** is driven by the third active devices **776c**. In this embodiment, the designs of the third active devices **776c** and the second active devices **776b** are different, such that the second pixel electrode **774** and the third pixel electrode **876** can have different display voltages. Thereby, the display effects of the liquid crystal display panel **900** are further improved.

As shown in FIG. 3E, in this embodiment, the second pixel electrode **774** and the third pixel electrode **876** are respectively driven by the second active devices **776b** and the third active devices **776c**. To be more specific, during the polymer stabilized alignment process, the voltages applied by the data lines **760b** are respectively transmitted to the second and the third pixel electrodes **774** and **876** through the second and the third active devices **776b** and **776c**, so as to achieve different alignments of the liquid crystal molecules over the second and the third pixel electrodes **774** and **876**. In brief, besides the advantages of the liquid crystal display panel **800**, the liquid crystal display panel **900** achieves the effect of alignment in much more domains of the liquid crystal molecules.

Certainly, the present invention is not limited thereto. FIGS. 3F and 3G illustrate yet another two liquid crystal display panels according to the third embodiment of the present invention. Referring to FIG. 3F, a liquid crystal display panel **1000** is substantially similar to the aforesaid liquid crystal display panel **700**. However, in the liquid crystal display panel **1000**, the first capacitor bottom electrodes **1080** and the second capacitor bottom electrodes **1090** are designed to be straight-line type capacitor electrodes. On the other hand, referring to FIG. 3G, a liquid crystal display panel **1100** is substantially similar to the aforesaid liquid crystal display panel **800**, wherein the first capacitor bottom electrodes **1080**, the second capacitor bottom electrodes **1192**, and the third capacitor bottom electrodes **1194** in the liquid crystal display panel **1100** are straight-line design.

Specifically, the liquid crystal display panels **1000** and **1100** are both polymer stabilized alignment liquid crystal display panels, and each pixel structure is driven by two data lines **760a** and **760b** and one scan line **150**. In this embodiment, the first capacitor bottom electrodes **1080**, the second capacitor bottom electrodes **1090** and **1192**, and the third capacitor bottom electrodes **1194** are all straight-line design. The polymer stabilized alignment process is performed on the liquid crystal display panels **1000** and **1100** in two ways: one is to input signals to the aforesaid capacitor bottom electrodes **1080**, **1090**, **1192**, and **1194**, so as to form the voltage differences or electric field intensity required in the polymer stabilized alignment process between these pixel electrodes **772**, **774**, and **876** and the opposing electrode **140**; the other is to use different data lines **760a** and **760b** for inputting different signals to the corresponding pixel electrodes **772**, **774**, and **876**, so as to form the voltage differences required in the polymer stabilized alignment process between the pixel elec-

trodes **772**, **774**, and **876** and the opposing electrode **140**. In brief, the designs of the liquid crystal display panels **1000** and **1100** help to make the polymer stabilized alignment process more flexible.

To clearly explain the various liquid crystal display panels in the third embodiment of the present invention, FIG. 4 illustrates an equivalent circuit diagram of the liquid crystal display panel according to the third embodiment of the present invention. Referring to FIG. 4, a liquid crystal display panel **1200** in this embodiment comprises a plurality of scan lines **1250**, a plurality of data lines **1260a** and **1260b**, a plurality of pixel structures **1270**, a plurality of first capacitor bottom electrodes **1280**, and a plurality of second capacitor bottom electrodes **1290**.

Specifically, in this embodiment, the scan lines **1250** and the data lines **1260a** and **1260b** are arranged to define where a plurality of pixel structures **1270** is located, such that the pixel structures **1270** are arranged as an array. In addition, each pixel structure **1270** may be formed by a first pixel electrode **1272** and a second pixel electrode **1274**. The first pixel electrode **1272** and the second pixel electrode **1274** are electrically connected to the same scan line **1250**, and respectively electrically connected to different data lines **1260a** and **1260b**. Moreover, the first and the second capacitor bottom electrodes **1280** and **1290** are respectively electrically coupled to the first and the second pixel electrodes **1272** and **1274**. When the liquid crystal display panel **1200** displays images, the first and the second pixel electrodes **1272** and **1274** respectively receive the data signals transmitted by the data lines **1260a** and **1260b** through the first and the second active devices **1276a** and **1276b**, and voltages are applied to the first and the second capacitor bottom electrodes **1280** and **1290** to maintain the data signals in the first and the second pixel electrodes **1272** and **1274**. Herein, the first and the second capacitor bottom electrodes **1280** and **1290** are applied with the same voltage.

To conclude, in the design of the liquid crystal display panel of the present invention, the second capacitor bottom electrodes provide favorable shielding effect to prevent the crosstalk effect between the second pixel electrodes and the data lines. Further, during the polymer stabilized alignment process, the first and the second capacitor bottom electrodes may be selectively applied with different potentials or not applied with any voltages. Consequently, the liquid crystal molecules in each pixel structure of the liquid crystal display panel are tilted and arranged properly. The problems of light leakage and non-uniform display which occur when the liquid crystal display panel displays images are thereby improved. Additionally, when the V-shaped main slit is formed between the first and the second pixel electrodes, the liquid crystal molecules above the V-shaped main slit are tilted in a proper direction to enhance the display quality of the liquid crystal display panel. As a whole, the liquid crystal molecules in the liquid crystal display panel are arranged to achieve the effect of multi-domain alignment and further to improve the wide view angle effect of the liquid crystal display panel. In addition to the above, the liquid crystal display panel of the present invention has the advantages of high aperture ratio, low crosstalk effect, and so forth.

Although the present invention has been disclosed by the above embodiments, they are not intended to limit the present invention. Anybody with ordinary knowledge in the art may make some modifications and alterations without departing from the spirit and scope of the present invention. Therefore, the protection range of the present invention falls in the appended claims.

What is claimed is:

1. A manufacturing method of a liquid crystal display panel, comprising:
 - providing a semi-finished liquid crystal display panel, comprising:
 - a first substrate;
 - a second substrate opposite to the first substrate;
 - a liquid crystal layer disposed between the first substrate and the second substrate;
 - an opposing electrode arranged between the second substrate and the liquid crystal layer;
 - a plurality of scan lines disposed between the first substrate and the liquid crystal layer;
 - a plurality of data lines disposed between the first substrate and the liquid crystal layer, and the scan lines and the data lines interlacing each other;
 - a plurality of polymerizable molecules located in the liquid crystal layer; and
 - a plurality of pixel structures disposed on the first substrate and electrically connected to the scan lines and the data lines, each pixel structure comprising:
 - a first pixel electrode;
 - a second pixel electrode;
 - a first active device; and
 - a second active device, wherein the first active device and the second active device are electrically connected to one of the scan lines, the first active device and the second active device are respectively electrically connected to different data lines, and the first active device and the second active device are respectively electrically connected to the first pixel electrode and the second pixel electrode, wherein the blocks of the liquid crystal layer corresponding to the first pixel electrodes and the second pixel electrodes are respectively a plurality of first blocks and a plurality of second blocks; and
 - a plurality of first capacitor bottom electrodes disposed between the first pixel electrodes and the first substrate;
 - a plurality of second capacitor bottom electrodes disposed between the second pixel electrodes and the first substrate; and

at least an alignment layer disposed between the pixel structures and the opposing electrode; and
 providing a first voltage, a second voltage, and a third voltage to respectively forming a first voltage difference in the first blocks by the first voltage and the third voltage and forming a second voltage difference in the second blocks by the second voltage and the third voltage for polymerizing the polymerizable molecules to form the liquid crystal display panel, wherein the first voltage difference is different from the second voltage difference such that the liquid crystal molecules of the liquid crystal layer in different areas are arranged in different pre-tilt angles.

2. The manufacturing method as claimed in claim 1, wherein the step of forming the first voltage difference and the second voltage difference comprises respectively providing the first voltage, the second voltage, and the third voltage to the first capacitor bottom electrode, the second capacitor bottom electrode, and the opposing electrode.

3. The manufacturing method as claimed in claim 2, wherein the first voltage is larger than or equal to the second voltage.

4. The manufacturing method as claimed in claim 2, wherein the second voltage is equal to the third voltage.

5. The manufacturing method as claimed in claim 2, wherein the first voltage is substantially equal to 0~80 volts, the second voltage is substantially equal to 0~80 volts, and the third voltage is substantially equal to 0~80 volts.

6. The manufacturing method as claimed in claim 1, wherein the step of forming the first voltage difference and the second voltage difference comprises:

respectively providing the first voltage and the second voltage to the first pixel electrodes and the second pixel electrodes through the data lines; and

providing the third voltage to the opposing electrode.

7. The manufacturing method as claimed in claim 6, wherein the first voltage is substantially equal to 0~80 volts, the second voltage is substantially equal to 0~80 volts, and the third voltage is substantially equal to 0~80 volts.

* * * * *

专利名称(译)	液晶显示面板及其制造方法		
公开(公告)号	US8279376	公开(公告)日	2012-10-02
申请号	US12/199808	申请日	2008-08-28
[标]申请(专利权)人(译)	友达光电股份有限公司		
申请(专利权)人(译)	友达光电股份有限公司		
当前申请(专利权)人(译)	友达光电股份有限公司		
[标]发明人	CHAN TE WEI CHEN CHIEH WEI TSAO CHENG HAN CHIU CHUNG YI		
发明人	CHAN, TE-WEI CHEN, CHIEH-WEI TSAO, CHENG-HAN CHIU, CHUNG-YI		
IPC分类号	G02F1/1333		
CPC分类号	G02F1/136213 G02F1/133345 G02F2001/134345 G09G3/3607 G09G3/3648 G09G2300/0426 G09G2310/0205		
助理审查员(译)	阮桑		
优先权	097124238 2008-06-27 TW		
其他公开文献	US20090322659A1		
外部链接	Espacenet USPTO		

摘要(译)

本发明提供一种液晶显示面板及其制造方法，所述液晶显示面板包括第一基板，液晶层，取向层，聚合物层，扫描线，数据线，像素结构，第一电容器底电极和第二电容器底电极。每个像素结构具有第一像素电极和第二像素电极。每个第一电容器底电极设置在第一像素电极和第一基板之间。设置在第二像素电极和第一基板之间的每个第二电容器下电极包括第一图案和多个第二图案。第一图案从第二像素电极的第一侧延伸到相对的第二侧。连接到第一图案的第二图案设置在第一侧和第二侧上。第二图案至少部分地与第二像素电极和数据线之间的区域重叠。

