



US 20050099580A1

(19) **United States**(12) **Patent Application Publication****Lee et al.**(10) **Pub. No.: US 2005/0099580 A1**(43) **Pub. Date: May 12, 2005**(54) **LIQUID CRYSTAL DISPLAY DEVICE AND  
METHOD OF FABRICATING THE SAME****Related U.S. Application Data**

(62) Division of application No. 10/448,174, filed on May 30, 2003.

(75) Inventors: **Gue-Tai Lee**, Gyung-sangbuk-Do (KR);  
**Soo-Won Seok**, Gyung-sangbuk-Do  
(KR); **Ki-Bok Park**, Gyung-sangbuk-Do  
(KR)(30) **Foreign Application Priority Data**

Dec. 31, 2002 (KR)..... 88471/2002

**Publication Classification**(51) **Int. Cl.<sup>7</sup>** ..... **G02F 1/1339**(52) **U.S. Cl.** ..... **349/156**

Correspondence Address:

**MORGAN LEWIS & BOCKIUS LLP**  
**1111 PENNSYLVANIA AVENUE NW**  
**WASHINGTON, DC 20004 (US)**(57) **ABSTRACT**

A liquid crystal display device includes a substrate, a black matrix layer on the substrate and having a first plurality of openings, a color filter layer on the black matrix layer and having a second plurality of openings, and a plurality of column spacers each contacting the substrate through the first plurality and second plurality of openings.


(73) Assignee: **LG. PHILIPS LCD CO., LTD.**(21) Appl. No.: **11/006,579**(22) Filed: **Dec. 8, 2004**

FIG. 1  
RELATED ART




FIG. 2  
RELATED ART




FIG. 3A  
RELATED ART




FIG. 3B  
RELATED ART




FIG. 3C  
RELATED ART




FIG. 3D  
RELATED ART




FIG. 3E  
RELATED ART




FIG. 3F  
RELATED ART




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 4E




FIG. 4F




FIG. 4G




FIG. 5A




FIG. 5B





FIG. 5C



## LIQUID CRYSTAL DISPLAY DEVICE AND METHOD OF FABRICATING THE SAME

[0001] The present invention claims the benefit of Korean Patent Application No. 88471/2002 filed in Korea on Dec. 31, 2002, which is hereby incorporated by reference.

### BACKGROUND OF THE INVENTION

#### [0002] 1. Field of the Invention

[0003] The present invention relates to a color filter substrate structure of a liquid crystal display device, and more particularly, to a method of fabricating a color filter substrate having a spacer directly contacting a substrate.

#### [0004] 2. Description of the Related Art

[0005] Presently, liquid crystal display (LCD) devices are commonly used in various fields from image display devices, such as computer monitors, TV receivers, and portable telephones, to information display panels used for automobiles and airplanes, for example.

[0006] **FIG. 1** is a perspective view of an upper substrate and a lower substrate of an LCD device according to the related art. In **FIG. 1**, an LCD device includes a transparent substrate **21**, a color filter layer **8** including a black matrix **6** and a sub-color filter layer **7** of red, green, and blue on the transparent substrate **21**, a color filter substrate **1** having a transparent common electrode **18** on the color filter layer **8**, a TFT array substrate **2** including a plurality of switching devices **T** arranged on the substrate **3** in a matrix configuration, and a pixel electrode **5** corresponding to the respective switching devices **T**. In addition, a liquid crystal material **10** is injected between the color filter substrate **1** and the TFT array substrate **2**.

[0007] A plurality of gate lines **11** arranged in rows and a plurality of data lines **12** arranged in columns are formed on the TFT array substrate **2**, such that the gate and data lines intersect and cross each other. In addition, a thin film transistor **T** corresponding to the switching device is formed at the intersection points between the gate lines and the data lines in a matrix configuration.

[0008] A pixel region **4** is formed on the TFT array substrate **2** corresponding to the gate lines **11** and the data lines **12**, and the pixel electrode **5** is formed on the pixel region **4**. The pixel electrode **5** is formed of a transparent electrode material having excellent light transmittance, such as Indium Tin Oxide (ITO).

[0009] **FIG. 2** is a flow chart for a fabrication process of an LCD device according to the related art. In **FIG. 2**, the fabrication process includes steps of: preparing a lower (TFT) substrate; forming an alignment layer on the lower substrate; rubbing the alignment layer for alignment of liquid crystal material (not shown); forming a seal pattern; scattering spacers (not shown); bonding an upper substrate and the lower substrate together; cutting the bonded substrates into a plurality of unit cells; and injecting the liquid crystal material into the unit cell.

[0010] During the preparation of the lower substrate, a plurality of the gate lines horizontally arranged and a plurality of the data lines vertically arranged by crossing the gate lines are formed on the lower substrate. Then, a plurality of the thin film transistors are formed in a matrix

configuration at the intersection points of the gate lines and the data lines. Next, the pixel electrode corresponding to the switching device **T** is formed on the TFT array substrate.

[0011] During the formation of the alignment layer, a thin film of polymer material is uniformly coated on the lower substrate. It is essential that the alignment layer is uniformly formed so that the subsequent process of rubbing the alignment layer may be uniformly performed and alignment of the liquid crystal material may be uniform.

[0012] During the process of rubbing the alignment layer, a cloth is used to rub the alignment layer along a constant direction to uniformly align the liquid crystal material. The rubbing process is important to set the initial alignment direction of the liquid crystal material. When the rubbing process is properly performed, normal driving of the liquid crystal material is possible to provide uniform driving characteristics of the LCD device. Generally, the alignment layer is formed of polyimide-based organic materials.

[0013] The seal pattern forms a gap between the upper substrate and the lower substrate for the liquid crystal material injection, and prevents the injected liquid crystal material from leaking out from the bonded substrates. Accordingly, during the formation process of the seal pattern, a constant pattern is formed along a periphery of an active region of the lower substrate using a thermosetting resin during a screen printing method.

[0014] During the process of scattering the spacers, spacers of a predetermined size are used in order to maintain a constant cell gap between the upper and lower substrates. Accordingly, the spacers have to be scattered uniformly on the TFT array substrate. Scattering methods of the spacers include a wet scattering method for scattering the spacers within an alcohol carrier solution, and a dry scattering method for scattering only the spacers without using a carrier solution. In addition, the dry scattering method includes an electrostatic scattering method using static electricity, and a non-electrostatic scattering method using gas pressure. The non-electrostatic scattering method is commonly used in the liquid crystal cell structure having a low static electricity resistance.

[0015] During the bonding process, the upper and lower substrates are bonded together along the seal pattern. The bonding process is determined by a predetermined margin between the upper and lower substrates, which may be several microns. If the bonded substrates exceed the predetermined margin, light may leak from the liquid crystal display device, thereby reducing the picture quality of driving the liquid crystal display device.

[0016] Next, the bonded substrates are divided into a plurality of unit cells by cutting the upper and/or lower substrates. In previous processes for cutting the liquid crystal cells, the liquid crystal material was simultaneously injected into several unit cells and the cells were cut as a unit cell. However, as the area of the LCD devices increased, the liquid crystal cells were first cut into the unit cells and then injected with the liquid crystal material.

[0017] Finally, the liquid crystal material is injected into the cut unit liquid crystal cells. The unit liquid crystal cell has a cell gap of several microns and an area of several hundreds of square centimeters. Accordingly, a vacuum injection method for injecting the liquid crystal material

into the unit liquid crystal cells using a pressure difference between interior and exterior regions of the liquid crystal cells is commonly used.

[0018] FIGS. 3A to 3F are cross sectional views of a fabrication process of an upper substrate of an LCD device according to the related art. In FIG. 3A, a black matrix 32 is formed on a transparent glass substrate 31 at a region of an upper substrate that corresponds to gate and data lines and switching devices of the lower substrate. Generally, the black matrix 32 is formed between sub-color filter of red, green, and blue, and blocks light that passes through a reverse tilt domain formed at a peripheral portion of a pixel electrode of the lower substrate. A material for forming the black matrix 32 includes a metal thin film, such as Cr, having an optical density more than 3.5, or an organic material. In addition, a double layer, such as Cr/CrOx, may be used for low reflection. Accordingly, a proper material of the black matrix may be selected for a desired purpose.

[0019] In FIG. 3B, a color filter is formed using a pigment scattering method. However, several different methods may be used, such as dyeing, depositing, and printing. First, a red color resin is deposited on the substrate 31 upon which the black matrix 32 has been previously formed. Then, the red color resin is selectively exposed to light, thereby forming a red sub color filter 33a at a desired region.

[0020] Next, a green color resin is deposited on the substrate upon which the red sub-color filter has been previously formed, and selectively exposed to light, thereby patterning the green sub-color filter 33b at a desired region. Likewise, a blue sub-color filter 33c is formed by repeating the same process.

[0021] In FIG. 3C, a process for forming an overcoat layer 34 includes forming a transparent resin having an insulating characteristic on the substrate 31 upon which the sub-color filters 33a, 33b, and 33c have been previously formed, thereby forming an overcoat layer 34. The overcoat layer 34 is not necessarily formed and may be omitted. When a Cr-based metal is used as the black matrix 32, the overcoat layer 34 is not needed since a thickness of the black matrix 32 is as thin as a few thousands of angstroms. In addition, when a resin-based black matrix 32 is used, a thickness may be 1 to 1.5  $\mu\text{m}$ , thereby requiring the overcoat layer 34.

[0022] In FIG. 3D, a common electrode 35 is formed on the color filter substrate upon which the overcoat layer 34 has been previously formed. The common electrode is a transparent electrode and is commonly formed of indium tin oxide (ITO). A common voltage is supplied to the common electrode, so that an electric field is formed in combination with a pixel voltage applied to the pixel electrode on the array substrate, thereby driving the liquid crystal material.

[0023] In FIG. 3E, spacers 36 are formed in which a transparent organic film is formed on the substrate 31 upon which the common electrode 35 has been previously formed, and the spacers 36 are patterned with a specific shape by photolithographic and an etching processes. Both shape and height of the spacers 36 are determined by the photolithographic process that includes a chemical reaction by irradiation of light and cross linking. Accordingly, the construction of the spacers 36 is changed into a net structure and the spacers 36 are resistant to etching. Thus, the spacers 36 may be formed having a more minute pattern, thereby

increasing the mechanical strength of the spacers 36. Increasing the mechanical strength of the spacers 36 results in increasing mechanical deformation of the spacers. For example, in in-plane switching (IPS) mode LCD devices, an electric field is formed on the array substrate 31 and the metal-based black matrix may influence the electric field when the liquid crystal material is driven. Accordingly, carbon-based resins are used as the material of the black matrix 32. However, the carbon-based black matrix resins have a mechanical strength lower than that of the acrylic-based color resin and the overcoat layer 34 so that the black matrix resin 32 is mechanically deformed by external impact to the spacers 36. In addition, the spacers 36 can be formed on the overcoat layer 34 prior to formation of the common electrode 35. However, the same problems regarding mechanic deformation may be generated.

[0024] In FIG. 3F, a process for forming the alignment layer 37 includes forming an organic insulating film, such as polyimide, on the color filter substrate upon which the spacers have been previously formed. Then, a rubbing process is performed for forming a predetermined groove on the alignment layer 37 in order to provide an alignment of the liquid crystal material, thereby completing the upper substrate of the LCD device.

[0025] It is possible that the spacers 36 can be formed after forming the alignment layer 37. However, the alignment layer 37 is chemically damaged during the etching process. Thus, the alignment layer 37 is commonly formed after formation of the spacers 36.

[0026] However, during fabrication of the upper substrate of the LCD device and fabrication of the spacers 36, the spacers 36 are formed at a region corresponding to the black matrix 32. When external pressure is applied to the spacers 36, the carbon resin-based black matrix 32 corresponding to bottom portions of the spacers 36 are mechanically deformed such that the spacers 36 are deformed along a direction towards the black matrix 32. This is a significant problem in IPS-mode LCD devices that use the carbon resin-based black matrix. If the spacers are deformed, the cell gap is not uniformly maintained. Accordingly, differences in displayed image brightness are generated, thereby creating smear on the image screen. This phenomenon is also generated where the spacers 36 are formed at a color filter region of the upper substrate corresponding to the pixel region of the TFT array substrate of the LCD device.

#### SUMMARY OF THE INVENTION

[0027] Accordingly, the present invention is directed to a liquid crystal display device and method of fabricating a liquid crystal display device that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

[0028] An object of the present invention is to provide a liquid crystal display device having an improved a cell gap structure.

[0029] Another object of the present invention is to provide a liquid crystal display device having an improved spacer structure to prevent black matrix destruction.

[0030] Another object of the present invention is to provide a method of fabricating a liquid crystal display device having an improved a cell gap structure.

[0031] Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

[0032] To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described herein, a liquid crystal display device includes a substrate, a black matrix layer on the substrate and having a first plurality of openings, a color filter layer on the black matrix layer and having a second plurality of openings, and a plurality of column spacers each contacting the substrate through the first plurality and second plurality of openings.

[0033] In another aspect, a liquid crystal display device includes a substrate, a black matrix layer on the substrate and having a first plurality of openings, a color filter layer on the black matrix layer, a plurality of column spacers on the color filter layer, and an alignment layer on the substrate, wherein the plurality of column spacers are aligned with the first plurality of openings.

[0034] In another aspect, a method for fabricating a liquid crystal display device includes forming a black matrix layer on a substrate, forming a color filter layer on the black matrix layer, forming a first plurality of openings through the color filter layer and black matrix layer to expose a surface portion of the substrate, and forming a plurality of column spacers within the first plurality of openings.

[0035] In another aspect, a method for fabricating a liquid crystal display device includes forming a black matrix layer on a substrate, forming a first plurality of openings in the black matrix layer to expose surface portions of the substrate, forming a color filter layer on the black matrix layer, and forming a plurality of column spacers on the color filter layer.

[0036] In another aspect, a liquid crystal display device includes a substrate, a black matrix layer on the substrate and having a first plurality of openings, a first color filter layer on the black matrix layer, a second color filter layer on the black matrix layer and within the first plurality of openings, an overcoat layer on the first and second color filter layers, a common electrode layer on the overcoat layer, and a plurality of column spacers on the common electrode layer.

[0037] It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0038] The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention. In the drawings:

[0039] FIG. 1 is a perspective view of an upper substrate and a lower substrate of an LCD device according to the related art;

[0040] FIG. 2 is a flow chart for a fabrication process of an LCD device according to the related art;

[0041] FIGS. 3A to 3F are cross sectional views of a fabrication process of an upper substrate of an LCD device according to the related art;

[0042] FIGS. 4A to 4G are cross sectional views of an exemplary fabrication process of an upper substrate of an LCD device according to the present invention; and

[0043] FIGS. 5A to 5C are cross sectional views of another exemplary fabrication process of an upper substrate of an LCD device according to the present invention.

#### DETAILED DESCRIPTION OF THE EXEMPLARY EMBODIMENTS

[0044] Reference will now be made in detail to the exemplary embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

[0045] FIGS. 4A to 4G are cross sectional views of an exemplary fabrication process of an upper substrate of an LCD device according to the present invention. In FIG. 4A, a substrate 41 of an LCD device may be prepared to include, but not limited to, a plurality of gate and data lines, switching devices, and pixel electrodes. Then, a black matrix 42 may be formed on the substrate 41 for covering the gate lines, data lines, and switching devices. Alternatively, the gate lines, data lines, and switching devices may be formed on a lower substrate of the LCD device. The black matrix 42 may be formed between sub-color filters of red, green, and blue, thereby blocking light that may pass through a reverse tilt domain formed along a peripheral portion of a pixel electrode of the lower substrate.

[0046] The black matrix 42 may include a metal thin film, such as Cr, or an organic carbon resin may be used. The black matrix 42 made of a Cr material may be used in LCD devices of a) twisted nematic (TN) mode, wherein a common electrode may be located on the upper substrate and a pixel electrode may be formed on the lower substrate. In addition, in an IPS mode the common electrode and the pixel electrode may be formed on the same substrate, i.e., the lower substrate. Accordingly, since metallic materials used to make the black matrix 42 may influence an electric field generated by the common and pixel electrodes of the lower substrate a carbon resin black matrix material may be used. The present invention may improve the brightness of the LCD device using the carbon resin as a material of the black matrix 42. In addition, the carbon resin may also be used as a material of the black matrix 42 in the TN mode LCD device.

[0047] In FIG. 4B, a color filter having color resins of red, green, and blue may be formed on the substrate 41 and portions of the black matrix 42 using a pigment scattering method, for example. The color resin includes photosensitive color resins, such as monomers, and binder. Alternatively, several different methods may be used, such as dyeing, depositing, and printing.

[0048] First, the red color resin may be coated on an entire surface of the substrate 41 upon which the black matrix 42 may have previously been formed. Then, the red color resin may be selectively exposed to light, thereby forming a red

sub-color filter **43a** at desired regions of the substrate **41** and the portions of the black matrix **42**.

[0049] Next, the green color resin may be coated on the substrate **41** upon which the red sub-color filter **43a** may have previously been formed. Then, the green color resin may be selectively exposed to light, thereby forming the green sub-color filter **43b** at desired regions of the substrate **41** and the portions of the black matrix **42**.

[0050] Similarly, a blue sub-color filter **43c** may be formed by repeating the above process. A fabrication order of the red, green, and blue sub-color filters **43a**, **43b**, and **43c** may be rearranged.

[0051] In FIG. 4C, an overcoat layer **44** made of a transparent acryl resin may be formed to compensate for any stepped regions between the black matrix **42** and the red, green, and blue sub-color filters **43a**, **43b**, and **43c**.

[0052] In FIG. 4D, a common electrode **45** may be formed on the overcoat layer **44**. The common electrode **45**, together with a pixel electrode formed on another substrate, may be used for supplying an electric field to the liquid crystal material, which will be subsequently formed. However, in the IPS mode LCD device, the common electrode may not necessarily be required.

[0053] In FIG. 4E, portions of the common electrode **45**, the overcoat layer **44**, the sub-color filters **43a**, **43b**, and **43c** (collectively referred to as a color filter layer **43**), and the black matrix **42** on the substrate **41** may be partially removed by etching to expose a portion of the substrate **41** through opening **46**. Alternatively, the common electrode **45**, the overcoat layer **44**, the color filter layer **43**, and the black matrix **42** may be selectively formed to provide the opening **46** such that etching may not be necessary.

[0054] Since a portion of the black matrix **42** formed on the substrate **41** may be removed, light may leak from the lower substrate through the opening **46**. Accordingly, a spacer may be formed within the opening **46** that is formed of a material that can block the leaked light, such as a colored resin material.

[0055] In FIG. 4F, the black matrix **42** (in FIG. 4E) may be formed within a region of the blue sub-color resin **43c** since the blue sub-color resin **43c** may have the highest intensity among the red, green, and blue sub-color resins **43a**, **43b**, and **43c**. In addition, a size of the opening **46** may be approximately 10  $\mu\text{m}$  in diameter.

[0056] In FIG. 4G, the spacer **47** may be formed using a photosensitive resin and may be formed using photolithographic and etching processes so that the spacer **47** may be precisely aligned within the opening **46** (in FIG. 4F). Specifically, the column spacer **47** may include a matrix resin dissolved and swelled by alkaline aqueous solution, acryl monomer having ethylene unsaturated bonding number more than 2, or photo-polymerization initiator may be used. In addition, a width between sidewall portions of the opening **46** may be at least similar to a width of a bottom portion of the column spacer **47**.

[0057] Although not specifically shown, a single spacer may be distributed among three adjacent pixel regions, or more. In addition, the spacer may be formed to maintain a cell gap of about 3 to 7  $\mu\text{m}$  between the upper and lower substrates of the LCD device. Moreover, since the spacers

may be formed to directly contact the glass substrate **41**, the spacers may have a relatively larger size as compared to spacers according to the related art.

[0058] FIGS. 5A to 5C are cross sectional views of another exemplary fabrication process of an upper substrate of an LCD device according to the present invention. In FIG. 5A, a black matrix **52** may be formed on a substrate **51**.

[0059] In FIG. 5B, portions of the black matrix **52** located at a point where spacers may be subsequently formed on the substrate **51** may be removed by photolithographic and etching processes, thereby exposing surface portions of the substrate **51**. In addition, one opening **53** may be distributed among at least three adjacent pixel electrodes, or more. The opening **53** may be larger than the subsequently formed column spacer since the column spacer will be formed within the opening **53**. When the opening **53** is smaller than the column spacer, the black matrix **52** and the column spacer may overlap after arranging the column spacer within the opening **53**. Thus, when an external pressure is applied, the black matrix **52** may be mechanically deformed, as in the related art. Since a size of the column spacer is approximately 10  $\mu\text{m}$  in diameter, the opening **53** on the black matrix **52** should be larger than the 10  $\mu\text{m}$ , or may be the same.

[0060] After forming the opening **53** in the black matrix **52**, red, green, and blue sub-color resins (collectively called the color filter resin) may be applied by a pigment scattering method, for example, similar to the process shown in FIG. 4B. Then, as shown in FIG. 5C, an overcoat layer **55** and a common electrode **56** may be sequentially formed similar to the processes shown in FIGS. 4C and 4D.

[0061] FIG. 5C is a cross sectional view of the upper substrate of the LCD device when a dotted line **5L** is a cutting line in FIG. 5B. Since the color filter resin may be arranged as a stripe on the substrate where the black matrix **52** is arranged, the color filter resin **54** may be located within the opening **53** and on the black matrix **52**. In addition, column spacers **57** may be formed on the common electrode **56** aligned to the opening **53**.

[0062] It will be apparent to those skilled in the art that various modifications and variations can be made in the liquid crystal display device and method of fabricating the same of the present invention with departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

1-8. (canceled)

9. A liquid crystal display device, comprising:

a substrate;

a black matrix layer on the substrate and having a first plurality of openings;

a color filter layer on the black matrix layer;

a plurality of column spacers on the color filter layer; and

an alignment layer on the substrate,

wherein the plurality of column spacers are aligned with the first plurality of openings.

**10.** The device according to claim 9, wherein a width between sidewall portions of each of the first plurality of openings is at least similar to a width of bottom portions of each of the plurality of column spacers.

**11.** The device according to claim 9, further comprising an overcoat layer on the color filter layer.

**12.** The device according to claim 9, further comprising a common electrode on the color filter layer.

**13-18.** (canceled)

**19.** A method for fabricating a liquid crystal display device, comprising:

forming a black matrix layer on a substrate;

forming a first plurality of openings in the black matrix layer to expose surface portions of the substrate;

forming a color filter layer on the black matrix layer; and

forming a plurality of column spacers on the color filter layer.

**20.** The method according to claim 19, wherein the plurality of column spacers are integrally formed with the first plurality of openings.

**21.** The method according to claim 20, wherein a width between sidewall portions of each of the first plurality of openings is at least similar to a width of bottom portions of each of the plurality of column spacers.

**22.** A liquid crystal display device, comprising:

a substrate;

a black matrix layer on the substrate and having a first plurality of openings;

a first color filter layer on the black matrix layer;

a second color filter layer on the black matrix layer and within the first plurality of openings;

an overcoat layer on the first and second color filter layers;

a common electrode layer on the overcoat layer; and

a plurality of column spacers on the common electrode layer.

**23.** The device according to claim 22, wherein the plurality of column spacers are aligned with the first plurality of openings.

**24.** The device according to claim 22, wherein a width between sidewall portions of each of the first plurality of openings is at least similar to a width of bottom portions of each of the plurality of column spacers.

**25.** The device according to claim 24, wherein a diameter of the plurality of column spacers is approximately 10  $\mu\text{m}$ .

**26.** The device according to claim 22, wherein each of the first plurality of openings are distributed among at least three adjacent pixel electrodes.

**27.** The device according to claim 26, wherein each of the first plurality of openings are distributed among more than three adjacent pixel electrodes.

\* \* \* \* \*

|                |                                                 |         |            |
|----------------|-------------------------------------------------|---------|------------|
| 专利名称(译)        | 液晶显示装置及其制造方法                                    |         |            |
| 公开(公告)号        | <a href="#">US20050099580A1</a>                 | 公开(公告)日 | 2005-05-12 |
| 申请号            | US11/006579                                     | 申请日     | 2004-12-08 |
| [标]申请(专利权)人(译) | 乐金显示有限公司                                        |         |            |
| 申请(专利权)人(译)    | LG.飞利浦液晶CO. , LTD.                              |         |            |
| 当前申请(专利权)人(译)  | LG DISPLAY CO. , LTD.                           |         |            |
| [标]发明人         | LEE GUE TAI<br>SEOK SOO WON<br>PARK KI BOK      |         |            |
| 发明人            | LEE, GUE-TAI<br>SEOK, SOO-WON<br>PARK, KI-BOK   |         |            |
| IPC分类号         | G02F1/1335 G02F1/1339                           |         |            |
| CPC分类号         | G02F1/13394 G02F1/133512                        |         |            |
| 优先权            | 1020020088471 2002-12-31 KR                     |         |            |
| 其他公开文献         | US7342636                                       |         |            |
| 外部链接           | <a href="#">Espacenet</a> <a href="#">USPTO</a> |         |            |

#### 摘要(译)

一种液晶显示装置，包括：基板，基板上的黑矩阵层，具有第一多个开口；黑矩阵层上的滤色器层，具有第二多个开口；以及多个柱间隔物，每个开口接触所述开口。衬底通过第一多个和第二多个开口。

