



(12) **Patent Application Publication**
Kim

(43) **Pub. Date:** Dec. 28, 2006

Jun. 24, 2005 (KR) 10-2005-0054848

Publication Classification

(51) **Int. Cl.**
G02F 1/1335 (2006.01)

(52) **U.S. Cl.** **349/113**

(57) **ABSTRACT**

Disclosed is a liquid crystal display. In the LCD, a reflective polarizer and an optical retarder are provided between an absorbing polarizer and a backlight unit. This structure recycles light that would ordinarily be removed by absorption in conventional LCDs to be used for the display, so that light efficiency and display luminance of the LCD may be improved.

(22) Filed: **May 24, 2006**




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12





Fig. 13



LIQUID CRYSTAL DISPLAY

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to corresponding Korean Patent Application No. 10-2005-0054848 filed in the Korean Intellectual Property Office, Republic of Korea, on Jun. 24, 2005, the entire contents of which are incorporated by reference herein.

BACKGROUND OF THE INVENTION

[0002] (a) Field of the Invention

[0003] The present invention relates to a liquid crystal display (LCD).

[0004] (b) Description of the Related Art

[0005] Generally, an LCD includes a pair of panels each having electrodes on their inner surfaces, and a dielectric anisotropy liquid crystal (LC) layer interposed between the panels. In an LCD, a variation of the voltage difference between the field generating electrodes, i.e., the variation in the strength of an electric field generated by the electrodes, changes the transmittance of the light passing through the LCD, and thus desired images are obtained by controlling the voltage difference between the electrodes.

[0006] Depending on the type of light source used for image display, LCDs are divided into three types: transmissive, reflective, and transreflective. In transmissive LCDs, pixels are illuminated from behind using a backlight. In reflective LCDs, the pixels are illuminated from the front using incident light originating from the ambient environment. The transreflective LCDs combine transmissive and reflective characteristics. Under medium light conditions such as an indoor environment, or under complete darkness conditions, these LCDs are operated in a transmissive mode, while under very bright conditions, such as an outdoor environment, they are operated in a reflective mode.

[0007] The transmissive LCD and the transreflective LCD are often used since they provide relatively high display luminance compared to the reflective LCD type.

[0008] However, in these two types of LCDs, a polarizer attached to a lower surface of the LCD absorbs about 50% of light emitted from the backlight, and therefore only the remaining 50% is used for the display. As a result, light efficiency and display luminance of the LCD are less than optimal.

SUMMARY OF THE INVENTION

[0009] In accordance with the present invention, the display luminance of an LCD is improved by reducing an absorptive loss of light emitted from a backlight unit of the LCD.

[0010] According to an aspect of the present invention, there is provided an LCD including a display panel, a reflective polarizer that is provided under the display panel for transmitting light that is linearly polarized in a first direction and reflecting light that is linearly polarized in a second direction perpendicular to the first direction, an optical retarder that is provided under the reflective polar-

izer; and a backlight unit provided under the optical retarder, said backlight unit comprising a light source for supplying light to the display panel.

[0011] The LCD may further include a first absorbing polarizer that is provided between the display panel and the reflective polarizer, and a transmission axis of the first absorbing polarizer may be in the first direction.

[0012] The LCD may further include a second absorbing polarizer that is attached to an upper surface of the display panel, and a transmission axis of the second absorbing polarizer may be in the second direction.

[0013] The optical retarder has a slow axis and a fast axis, and a phase difference between the two axes may be a quarter-wave for converting circularly polarized light into linearly polarized light and linearly polarized light into circularly polarized light. The fast axis or the slow axis of the optical retarder may be formed at an angle of $\pm 45^\circ$ relative to the first direction or the second direction.

[0014] The reflective polarizer includes a substrate and a plurality of metal lines formed on a surface of the substrate, and an interval between the two adjacent metal lines may be narrower than a wavelength of visible light supplied by the backlight unit.

[0015] The metal lines of the reflective polarizer may be parallel to each other in the second direction.

[0016] The backlight unit may further include a reflective plate for reflecting light toward the display panel that is provided above the backlight unit.

[0017] According to another aspect, there is provided another LCD which includes a display panel, a reflective polarizer that is provided under the display panel to transmit light that is linearly polarized in a first direction and to reflect light that is linearly polarized in a second direction perpendicular to the first direction, and a backlight unit that is provided under the reflective polarizer, said backlight unit comprising a light source for supplying light to the display panel.

[0018] In this structure, the reflective polarizer includes a substrate, a plurality of metal lines, and an optical retardation film formed under the metal lines. The metal lines of the reflective polarizer are parallel to each other in the second direction, and an interval between the two adjacent metal lines is narrower than a wavelength of visible light supplied by the backlight unit.

[0019] The LCD may further include a first absorbing polarizer that is provided between the display panel and the reflective polarizer, and a transmission axis of the first absorbing polarizer may be in the first direction.

[0020] The LCD may further include a second absorbing polarizer that is attached to an upper surface of the display panel, and a transmission axis of the second absorbing polarizer may be in the second direction.

[0021] The optical retardation film has a slow axis and a fast axis, and a phase difference between the two axes may be a quarter-wave to convert circularly polarized light into linearly polarized light or linearly polarized light into circularly polarized light. The fast axis or the slow axis of the optical retardation film may be formed at $\pm 45^\circ$ to the first direction or the second direction.

[0022] The substrate of the reflective polarizer may be placed on the plurality of metal lines or under the optical retardation film.

[0023] The optical retardation film may be obtained by curing liquid crystal.

[0024] The backlight unit may further include a reflective plate for reflecting light toward the display panel that is provided above the backlight unit.

BRIEF DESCRIPTION OF THE DRAWINGS

[0025] The present invention will become more apparent by description of the preferred embodiments thereof with reference to the accompanying drawings.

[0026] **FIG. 1** is a layout view of a TFT array panel of an LCD according to an embodiment of the present invention.

[0027] **FIG. 2** is a layout view of a common electrode panel of an LCD according to an embodiment of the present invention.

[0028] **FIG. 3** is a layout view of an LCD incorporating the TFT array panel of **FIG. 1** and the common electrode panel of **FIG. 2**.

[0029] **FIG. 4** is a cross-sectional view cut along IV-IV' of **FIG. 3**.

[0030] **FIG. 5** shows cross-sections cut along V-V' and V'-V'' of **FIG. 3**, respectively.

[0031] **FIG. 6** shows a schematic cross-sectional view of an LCD according to an embodiment of the present invention.

[0032] **FIG. 7** is a view for comparing light efficiency and light paths between portions with and without a reflective polarizer and an optical retarder in an LCD according to the present invention.

[0033] **FIG. 8** shows the polarization states of light in the LCD of **FIG. 6**.

[0034] **FIG. 9** shows a schematic cross-sectional view of an LCD according to another embodiment of the present invention.

[0035] **FIG. 10** shows the polarization states of light in the LCD of **FIG. 9**.

[0036] **FIG. 11** is a perspective view of a reflective polarizer according to an embodiment of the present invention.

[0037] **FIG. 12** and **FIG. 13** are cross-sectional views of modified reflective polarizers according to other embodiments of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0038] Preferred embodiments of the present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. The present invention may, however, be embodied in different forms and should not be construed as being limited to the embodiments set forth herein. Rather, these embodiments are provided so that

this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art.

[0039] In the drawings, the thickness of the layers, films, and regions are exaggerated for clarity. Like numerals refer to like elements throughout. It will be understood that when an element such as a layer, film, region, or substrate is referred to as being "on" another element, it can be directly on the other element or intervening elements may also be present.

[0040] An LCD according to a preferred embodiment of the present invention will be described in detail below with reference to **FIG. 1** through **FIG. 5**.

[0041] **FIG. 1** is a layout view of a TFT array panel of an LCD according to an embodiment of the present invention, **FIG. 2** is a layout view of a common electrode panel of an LCD according to an embodiment of the present invention, **FIG. 3** is a layout view of an LCD incorporating the TFT array panel of **FIG. 1** and the common electrode panel of **FIG. 2**, **FIG. 4** is a cross-sectional view cut along IV-IV' of **FIG. 3**, and **FIG. 5** shows cross sections cut along V-V' and V'-V'' of **FIG. 3**, respectively.

[0042] Referring to **FIG. 1** through **FIG. 5**, an LCD according to an embodiment of the present invention comprises a TFT array panel **100** and a common electrode panel **200** facing each other, and an LC layer **3** interposed therebetween.

[0043] First, the basic structure of the TFT array panel **100** is described below with reference to **FIG. 1**, **FIG. 3**, and **FIG. 5**.

[0044] A plurality of gate lines **121** and a plurality of storage electrode lines **131** are formed on an insulating substrate **110** comprising transparent glass or plastic.

[0045] The gate lines **121** for transmitting gate signals extend substantially in a horizontal direction (as shown in **FIG. 1**). Each gate line **121** includes a plurality of gate electrodes **124** protruding downward and an end portion **129** having a relatively large surface area for connection with a different layer or an external device. Gate drivers (not shown) for generating the gate signals may be mounted on a flexible printed circuit film (not shown) attached to the substrate **110**, or directly on the substrate **110**. Alternatively, the gate drivers may be integrated into the substrate **110**. In this case, the gate lines **121** are directly connected to the gate drivers.

[0046] The storage electrode lines **131** receive a predetermined voltage. Each storage electrode line **131** comprises a stem line that is substantially parallel to the gate lines **121** and a plurality of pairs of storage electrodes **133a** and **133b** that extend from the stem line substantially in a vertical direction. Each storage electrode line **131** is provided between two adjacent gate lines **121**. In this embodiment, the stem line of the storage electrode line **131** is positioned closer to the lower-positioned gate line of the two adjacent gate lines **121** between which the storage electrode line **131** is provided. Each storage electrode **133a** has a fixed end that is connected to one of the stem lines and a free end. Each storage electrode **133b** has a fixed end with a relatively large width, which is connected to one of the stem lines, and two free ends including a straight free end and a crooked free

end. In other embodiments, the form and arrangement of the storage electrode lines 131 may be varied.

[0047] The gate lines 121 and the storage electrode lines 131 preferably comprise an aluminum—(Al) containing metal such as Al and an Al alloy, a silver—(Ag) containing metal such as Ag and a Ag alloy, a copper—(Cu) containing metal such as Cu and a Cu alloy, a molybdenum—(Mo) containing metal such as Mo and a Mo alloy, chrome (Cr), titanium (Ti), or tantalum (Ta). The gate lines 121 and the storage electrode lines 131 may be configured as a multi-layered structure, including at least two conductive layers (not shown) having different physical properties. In such a structure, one of the two conductive layers comprises a low resistivity metal, such as an Al-containing metal, an Ag-containing metal, a Cu-containing metal, or the like, in order to reduce signal delay or voltage drop in the gate lines 121 and the storage electrode lines 131. The other conductive layer comprises a material, such as indium tin oxide (ITO) and indium zinc oxide (IZO), which has desirable physical, chemical, and electrical contact properties with other materials. For example, a Mo-containing metal, Cr, Ta, Ti, etc., may be used for the formation of the conductive layer layer. Suitable examples of multi-layered structures include a lower Cr layer and an upper Al (or Al alloy) layer, and a lower Al (or Al alloy) layer and an upper Mo (or Mo alloy) layer. In addition to the above-listed materials, various other metals, conductors, and combinations thereof can be used for the formation of the gate lines 121 and the storage electrode lines 131.

[0048] All lateral sides of the gate lines 121 and the storage electrode lines 131 preferably form an angle in the range from about 30° to about 80° relative to the surface of the substrate 110.

[0049] A gate insulating layer 140 comprising silicon nitride (SiN_x) or silicon oxide (SiO₂) is formed on the gate lines 121 and the storage electrode lines 131.

[0050] A plurality of linear semiconductors 151 comprising hydrogenated amorphous silicon (abbreviated as “a-Si”) or polysilicon are formed on the gate insulating layer 140. Each linear semiconductor 151 extends substantially in a vertical direction, including a plurality of projections 154 that extend along the respective gate electrodes 124. The linear semiconductors 151 are enlarged in the vicinities of the gate lines 121 and the storage electrode lines 131 in order to provide a large surface area for overlap with the gate lines 121 and the storage electrode lines 131.

[0051] A plurality of linear ohmic contacts 161 and island-shaped ohmic contacts 165 are formed on the linear semiconductors 151. The ohmic contacts 161 and 165 may comprise N+ hydrogenated amorphous silicon that is highly doped with N-type impurities such as phosphorus (P) or silicide. The linear ohmic contacts 161 include a plurality of projections 163. A set of a projection 163 and an island-shaped ohmic contact 165 are placed on the projection 154 of the semiconductor 151.

[0052] All lateral sides of the linear semiconductors 151 and the ohmic contacts 161 and 165 preferably form an angle in the range from about 30° to about 80° relative to the surface of the substrate 110.

[0053] A plurality of data lines 171 and a plurality of drain electrodes 175 are formed on the ohmic contacts 161 and 165 and the gate insulating layer 140.

[0054] The data lines 171 for transmitting data signals extend substantially in a vertical direction to intersect with the gate lines 121 and the stem lines of the storage electrode lines 131. In this embodiment, each pair of the storage electrodes 133a and 133b is provided between two adjacent data lines 171. Each data line 171 includes a plurality of source electrodes 173 extending toward the respective gate electrodes 124, and an end portion 179 having a relatively large surface area for connection to a different layer or an external device. Data drivers (not shown) for generating the data signals may be mounted on a flexible printed circuit film (not shown) attached to the substrate 110, or directly on the substrate 110. Alternatively, the data drivers may be integrated into the substrate 110. In this case, the data lines 171 are directly connected to the gate drivers.

[0055] The drain electrodes 175 separated from the data lines 171 are opposite to the source electrodes 173, and are centered on the gate electrodes 124. Each drain electrode 175 includes an expansion having a relatively large width and a bar-shaped end portion that is partially surrounded with the curved source electrode 173.

[0056] A gate electrode 124, a source electrode 173, a drain electrode 175, and a projection 154 of the semiconductor 151 form a thin film transistor (TFT). A TFT channel is formed in the projection 154 provided between the source electrode 173 and the drain electrode 175.

[0057] The data lines 171 and the drain electrodes 175 preferably comprise a refractory metal such as Mo, Cr, Ta, or Ti, or alloys thereof, and may be configured as multi-layered structures including a refractory metal layer (not shown) and a low resistivity conductive layer (not shown). One example of a multi-layered structure includes a lower layer comprising one among Cr, Mo, and a Mo alloy, and an upper layer comprising Al or an Al alloy. Another example is a lower layer comprising Mo or a Mo alloy, an intermediate layer comprising Al or an Al alloy, and an upper layer comprising Mo or a Mo alloy. In addition to the above-listed materials, various other metals, conductors, and combinations thereof can be used for the formation of the data lines 171 and the drain electrodes 175.

[0058] All lateral sides of the data lines 171 and the drain electrodes 175 preferably form an angle in the range from about 30° to about 80° relative to the surface of the substrate 110.

[0059] The ohmic contacts 161 and 165 are provided only between the underlying semiconductors 151 and the overlying data lines 171 and between the overlying drain electrodes 175 and the underlying semiconductors 151, in order to reduce contact resistance therebetween. Most of the linear semiconductors 151 are formed more narrowly than the data lines 171, but partial portions thereof are enlarged in the vicinities of regions intersecting with the gate lines 121 or the storage electrode lines 131, as previously mentioned, in order to prevent the data lines 171 from being shorted. The linear semiconductors 151 are partially exposed in regions not covered by the data lines 171 and the drain electrodes 175, as well as between the source electrodes 173 and the drain electrodes 175.

[0060] A passivation layer 180 is formed on the data lines 171, the drain electrodes 175, and the exposed portions of the semiconductors 151. An upper surface of the passivation

layer **180** may be substantially flat. The passivation layer **180** may be configured as a single layer comprising an inorganic insulator, such as SiN_x or SiO_2 , or an organic insulator. In this case, a desirable organic insulator for the passivation layer **180** has a low dielectric constant of below 4.0 and/or photosensitivity. The passivation layer **180** may also be configured as a double-layered structure including a lower inorganic insulator layer and an upper organic insulator layer. This structure has a prominent insulating property, preventing damage to the exposed portions of the semiconductors **151**.

[0061] The passivation layer **180** is provided with a plurality of contact holes **182** and **185**, through which the end portions **179** of the data lines **171** and the expansions of the drain electrodes **175** are exposed, respectively. A plurality of contact holes **181** are formed in the passivation layer **180** and the gate insulating layer **140**, and the end portions **129** of the gate lines **121** are exposed therethrough.

[0062] A plurality of pixel electrodes **191**, a plurality of overpasses **83**, and a plurality of contact assistants **81** and **82** are formed on the passivation layer **180**. The pixel electrodes **191**, overpasses **83**, and contact assistants **81** and **82** may comprise a transparent conductor, such as ITO or IZO, or a reflective metal, such as Al, Ag, Cr, or their alloys.

[0063] The pixel electrodes **191** are physically and electrically connected to the drain electrodes **175** through the contact holes **185** in order to receive data voltages from the drain electrodes **175**. The pixel electrodes **191** supplied with the data voltages generate electric fields in cooperation with a common electrode **270** of the color filter panel **200**, thereby determining the orientations of LC molecules in the LC layer **3** interposed between the two electrodes **191** and **270**. The polarization of light passing through the LC layer **3** is controlled by varying the orientations of the LC molecules. Each set of the pixel electrode **191**, the corresponding common electrode **270**, and the LC layer **3** therebetween forms an LC capacitor capable of storing the applied voltage after the TFT is turned off.

[0064] To enhance the capacitance of the LC capacitors, storage capacitors are further provided. The pixel electrodes **191** and the expansions of the drain electrodes **175** that are connected to the pixel electrodes **191** through the contact holes **182** and **185** are overlapped with the storage electrodes **133a** and **133b** as well as the stem lines of storage electrodes **131**. Overlapping the pixel electrodes **191** and the drain electrodes **175** electrically connected thereto with the storage electrode lines **131** creates the storage capacitors.

[0065] The contact assistants **81** and **82** are connected to the end portions **129** of the gate lines **121** and the end portions **179** of the data lines **171** through the contact holes **181** and **182**, respectively. The contact assistants **81** and **82** supplement adhesion between the exposed end portions **129** and **179** and exterior devices, and protect them.

[0066] The overpasses **83** span the gate lines **121** and include a first portion extending upward and a second portion extending downward. The first portion of the overpass **83** is connected to the exposed stem line of the storage electrode line **131** through contact hole **183a**, and second portion of the overpass **83** is connected to the exposed straight free end of the storage electrode **133b** through contact hole **183b**. The overpasses **83** and the storage

electrode lines **131** having the storage electrodes **133a** and **133b** may be used for repairing any defect arising from the gate lines **121** and/or the data lines **171**.

[0067] The basic structure of the color filter panel **200** is described below with reference to FIG. 2 and FIG. 4.

[0068] A light-blocking member **220** called "a black matrix" is provided on an insulating substrate **210** comprising transparent glass or plastic. The light-blocking member **220** comprises portions corresponding to the gate lines **121**, the data lines **171**, and the TFTs, to prevent light from leaking out through barriers between the pixel electrodes **191**.

[0069] A plurality of color filters **230** are formed on the substrate **210** having the light-blocking member **220**. Most of them are placed within aperture regions delimited by the light-blocking member **220**. The color filters **230** may extend along the pixel electrodes **191** in a vertical direction. Each color filter **230** may exhibit either red, green, and blue colors.

[0070] An overcoat layer **250** is formed on the light-blocking member **220** and the color filters **230** to prevent the color filters **230** from being exposed and to offer a substantially flat surface. The overcoat layer **250** may comprise an organic insulator. In other embodiments, the overcoat layer **250** may be omitted.

[0071] A common electrode **270** comprising a transparent conductor such as ITO or IZO, is formed on the overcoat layer **250**.

[0072] Alignment layers **11** and **21** are individually coated on the inner surfaces of the panels **100** and **200**, respectively. The alignment layers **11** and **21** may comprise vertical alignment layers.

[0073] Polarizers **12** and **22** are provided on the outer surfaces of the panels **100** and **200**, respectively. Their transmission axes are oriented to form a right angle relative to each other. In this embodiment, one of the transmission axes is preferably parallel to the gate lines **121**.

[0074] The LC molecules in the LC layer **3** have negative dielectric anisotropy. In the absence of an electric field, they are aligned substantially perpendicular to the surfaces of the two panels **100** and **200**. In this case, incident light cannot pass through the polarizers **12** and **22** because the directions of polarization of the polarizers **12** and **22** are perpendicular.

[0075] When the common electrode **270** is supplied with a common voltage and the pixel electrode **191** is supplied with a data voltage, an electric field, which is perpendicular to the surfaces of the two panels **100** and **200**, is generated in the LC layer **3**. In response to the electric field, the LC molecules in the LC layer **3** begin to change their orientation to be perpendicular to the direction of the electric field.

[0076] FIG. 6 shows a schematic cross-sectional view of an LCD according to an embodiment of the present invention.

[0077] In this embodiment, the polarizer **12** comprises an absorbing polarizer **12**, and the LCD further comprises a reflective polarizer **13**, an optical retarder **14**, and a backlight unit **500**, in addition to the TFT array panel **100**, the common electrode panel **200**, and the LC layer **3** shown in FIG. 1 through FIG. 5.

[0078] Referring to FIG. 6, the absorbing polarizer 12 is attached to a lower surface of the TFT array panel 100, and the reflective polarizer 13 and the optical retarder 14 in this order are disposed under the absorbing polarizer 12. The backlight unit 500 is disposed under the optical retarder 14, and a reflective plate 510 is provided on a lower surface of the backlight unit 500.

[0079] As shown in FIG. 7, the reflective polarizer 13 transmits incident light that is linearly polarized in the X direction ($\leftrightarrow$) and reflects incident light that is linearly polarized in the Y direction ($\odot$), which is perpendicular to the X direction ($\leftrightarrow$). The structure of the reflective polarizer 13 is shown in FIG. 11 and will be described in greater detail below. In addition, the absorbing polarizer 12 transmits incident light that is linearly polarized in the X direction ($\leftrightarrow$) and absorbs incident light that is linearly polarized in the Y direction ($\odot$). Accordingly, light passing through the reflective polarizer 13 can also pass through the absorbing polarizer 12.

[0080] The optical retarder 14, which is disposed under the reflective polarizer 13, has a slow axis and a fast axis. Accordingly, light passing through the fast axis obtains a faster phase than that of light passing through the slow axis. In this embodiment, a phase difference between the two axes is a quarter-wave to convert circularly polarized light into linearly polarized light or linearly polarized light into circularly polarized light. In this embodiment, it is preferable that the two axes are perpendicular to each other and are formed at $\pm 45^\circ$ relative to transmission axes of the polarizers 12, 22, and 13, respectively.

[0081] FIG. 7 is a view for comparing light efficiency and light paths between portions with and without a reflective polarizer and an optical retarder in an LCD according to the present invention.

[0082] The left half of FIG. 7 shows a portion of the LCD with only the absorbing polarizer 12 without the reflective polarizer 13 and the optical retarder 14. In this case, only light in the X direction ($\leftrightarrow$) can be used for the display. Whereas, in the case that the polarizers 12 and 13 and the optical retarder 14 are all provided between the panel 100 and backlight unit 500 as shown in the right half of FIG. 7, light in the Y direction ($\odot$) can also be used for the display together with the light in the X direction ($\leftrightarrow$) by using a light recycling process.

[0083] FIG. 8 shows the polarization states of light in the LCD of FIG. 6. This figure shows only primary components that have influence on the polarization of light so that the light emitted from the backlight unit 500 is incident onto the TFT array panel 100.

[0084] Referring to FIG. 8, light (T) emitted from the backlight unit 500 is incident onto the optical retarder 14. This light (T) is unpolarized and includes all components. The optical retarder 14 transmits all incident light (T) without polarization. The light is then incident onto the reflective polarizer 13. The reflective polarizer 13 only transmits the X direction ($\leftrightarrow$) component of the incident light (T), and reflects the Y direction ($\odot$) component of the light (T). Hereinafter, successive paths of the light (T1) passing through the reflective polarizer 13 and the light (T2) reflected by the reflective polarizer 13 are separately described.

[0085] The transmitted light (T1) is incident onto the absorbing polarizer 12. This transmitted light (T1) through the polarizer 12 since a transmission axis of the polarizer 12 is in the X direction ($\leftrightarrow$). The light (T1) is then incident onto the TFT array panel 100.

[0086] On the other hand, the light reflected (T2) by the reflective polarizer 13 is incident onto the optical retarder 14 again. The light (T2) then passes through the optical retarder 14. At this time, the light (T2) is converted to left-handed circularly polarized light by the optical retarder 14. The left-handed circularly polarized light is incident onto the reflective plate 510 of the backlight unit 500, and then reflected by the reflective plate 510. With the reflection, the left-circularly polarized light is converted to right-circularly polarized light. Then, the right-circularly polarized light passes through the optical retarder 14. As the right-circularly polarized light passes through the optical retarder 14, the right-circularly polarized light is converted to linearly polarized light in the X direction ($\leftrightarrow$).

[0087] Since the reflected light (T2) is converted to linearly polarized light in the X direction in this manner, the reflected light (T2) can pass through the reflective polarizer 13 and the absorbing polarizer 12 to be incident upon the TFT array panel 100. In this way, the light that would ordinarily be removed by absorption in conventional LCDs is recycled for the display, thereby improving light efficiency and display luminance of the LCD.

[0088] FIG. 9 shows a schematic cross-sectional view of an LCD according to another embodiment of the present invention.

[0089] In this embodiment, the absorbing polarizer 12 of FIG. 6 is omitted. This is possible because the transmission axes of the reflective polarizer 13 and the absorbing polarizer 12 are in the same direction ($\leftrightarrow$). Therefore, the two polarizers 12 and 13 serve similar functions.

[0090] An LCD without the absorbing polarizer 12 may have some advantages and disadvantages, as described below.

[0091] Generally, absorbing polarizers show higher polarization efficiency than reflective polarizers. Therefore, an LCD incorporating an absorbing polarizer 12 can display images more vividly than the LCD without the absorbing polarizer 12. However, omitting the absorbing polarizer 12 may simplify the manufacturing process and reduce manufacturing cost.

[0092] Therefore, it may be preferable to employ the absorbing polarizer 12 in LCDs requiring higher display quality, and to omit the absorbing polarizer 12 in LCDs requiring lower manufacturing cost.

[0093] FIG. 10 shows the polarization states of light in the LCD of FIG. 9. The polarization states of light shown in FIG. 10 are equivalent to that of FIG. 8, except that the absorbing polarizer 12 is omitted.

[0094] FIG. 11 is a perspective view of an exemplary reflective polarizer according to an embodiment of the present invention.

[0095] Referring to FIG. 11, a reflective polarizer 13 comprises a substrate 13-1 and a plurality of metal lines 13-2 that are formed on a surface of the substrate 13-1 to be

substantially parallel to each other. An interval between the two adjacent metal lines **13-2** is significantly narrower than a wavelength of the visible light generated by the backlight unit **500**. In this case, the reflective polarizer **13** reflects light that is parallel to the metal lines **13-2** (i.e., light in the Y direction) and transmits light that is perpendicular to the metal lines **13-2** (i.e., light in the X direction). The substrate **13-1** comprises glass or plastic, and the metal lines **13-2** comprise a reflective metal such as Al.

[0096] In this embodiment, the optical retarder **14** is disposed under the reflective polarizer **13** even though it is not shown in **FIG. 11**. Alternatively, the reflective polarizer and optical retarder can be integrally formed as shown in **FIG. 12** and **FIG. 13**.

[0097] **FIG. 12** and **FIG. 13** are cross-sectional views of modified reflective polarizers according to other embodiments of the present invention.

[0098] Referring to **FIG. 12**, a reflective polarizer **15** comprises a substrate **15-1**, a plurality of metal lines **15-2** formed on a surface of the substrate **15-1**, and an optical retardation film **15-3** formed on the metal lines **15-2**. In this structure, the metal lines **15-2** and the optical retardation film **15-3** are preferably configured in the same pattern. In this example, the metal lines **15-2** and the optical retardation film **15-3** can be simultaneously patterned in a single process in order to simplify the manufacturing process. The optical retardation film **15-3** may be obtained by curing LC molecules. A photosensitive alignment layer may be coated on the substrate **15-1** and then exposed to light to form an alignment axis. After the formation of the alignment axis, LC molecules are coated thereon and then cured, so that an optical retardation film **15-3** is completed on the reflected polarizer. A thickness of the optical retardation film **15-3** thus formed does not exceed 1 μm . In contrast with the film **15-3**, a thickness of a separate optical retarder **14**, as shown in **FIG. 9**, is in the range from 60 μm to 80 μm including a thickness of an adhesive used. Accordingly, the optical retardation film **15-3** may be significantly thinner than the optical retarder **14**. The optical retardation film **15-3** has a slow axis and a fast axis. In this embodiment, it is preferable that either of the two axes is formed at $\pm 45^\circ$ to the metal lines **15-2**.

[0099] **FIG. 13** shows another reflective polarizer **15**. This reflective polarizer **15** comprises a substrate **15-1**, an optical retardation film **15-3** formed on a surface of the substrate **15-1**, and a plurality of metal lines **15-2** formed on the optical retardation film **15-3**.

[0100] In the above-illustrated embodiments of the present invention, the common electrode **270** is formed in the common electrode panel **200**. However, the present invention is also applicable to other embodiments in which the common electrode and pixel electrodes are formed in the same panel.

[0101] In accordance with the present invention, the reflective polarizer and optical retarder are provided between the absorbing polarizer and the backlight unit, as described above. This structure can recycle light that would ordinarily be absorbed by the absorbing polarizer in the conventional LCDs to be used for the display. As a result, light efficiency and display luminance of the LCD may be improved.

[0102] The present invention should not be considered limited to the particular examples described above, but rather should be understood to cover all aspects of the invention as set out in the attached claims. Various modifications, equivalent processes, as well as numerous structures to which the present invention may be applicable will be readily apparent to those of skill in the art to which the present invention is directed upon review of the instant specification.

What is claimed is:

1. A liquid crystal display comprising:

a display panel;

a reflective polarizer provided under the display panel transmitting light that is linearly polarized in a first direction and reflecting light that is linearly polarized in a second direction perpendicular to the first direction;

an optical retarder provided under the reflective polarizer; and

a backlight unit provided under the optical retarder, said backlight unit comprising a light source for supplying light to the display panel, wherein the reflective polarizer includes a substrate and a plurality of metal lines formed on a surface of the substrate, and an interval between two adjacent metal lines is narrower than a wavelength of visible light supplied by the backlight unit, and

the metal lines of the reflective polarizer are parallel to each other in the second direction.

2. The liquid crystal display of claim 1, further comprising a first absorbing polarizer provided between the display panel and the reflective polarizer.

3. The liquid crystal display of claim 2, wherein a transmission axis of the first absorbing polarizer is in the first direction.

4. The liquid crystal display of claim 3, further comprising a second absorbing polarizer coupled to an upper surface of the display panel.

5. The liquid crystal display of claim 4, wherein a transmission axis of the second absorbing polarizer is in the second direction.

6. The liquid crystal display of claim 1, wherein the optical retarder has a slow axis and a fast axis, and a phase difference between the two axes is a quarter-wave for converting circularly polarized light into linearly polarized light or linearly polarized light into circularly polarized light.

7. The liquid crystal display of claim 6, wherein the fast axis or the slow axis of the optical retarder is formed at angle of $\pm 45^\circ$ relative to the first direction or the second direction.

8. The liquid crystal display of claim 1, wherein the backlight unit includes a reflective plate for reflecting light toward the display panel.

9. A liquid crystal display comprising:

a display panel;

a reflective polarizer provided under the display panel transmitting light that is linearly polarized in a first direction and reflecting light that is linearly polarized in a second direction perpendicular to the first direction; and

a backlight unit provided under the reflective polarizer, said backlight unit comprising a light source for supplying light to the display panel,

wherein the reflective polarizer includes a substrate, a plurality of metal lines, and an optical retardation film formed under the metal lines, and

wherein the metal lines are parallel to each other in the second direction, and an interval between two adjacent metal lines is narrower than a wavelength of visible light supplied by the backlight unit.

10. The liquid crystal display of claim 9, further comprising a first absorbing polarizer provided between the display panel and the reflective polarizer.

11. The liquid crystal display of claim 10, wherein a transmission axis of the first absorbing polarizer is in the first direction.

12. The liquid crystal display of claim 11, further comprising a second absorbing polarizer coupled to an upper surface of the display panel.

13. The liquid crystal display of claim 12, wherein a transmission axis of the second absorbing polarizer is in the second direction.

14. The liquid crystal display of claim 9, wherein the optical retardation film has a slow axis and a fast axis, and a phase difference between the two axes is a quarter-wave for converting circularly polarized light into linearly polarized light or linearly polarized light into circularly polarized light.

15. The liquid crystal display of claim 14, wherein the fast axis or the slow axis of the optical retardation film is formed at an angle of $\pm 45^\circ$ relative to the first direction or the second direction.

16. The liquid crystal display of claim 15, wherein the substrate of the reflective polarizer is placed on the plurality of metal lines or under the optical retardation film.

17. The liquid crystal display of claim 9, wherein the optical retardation film is obtained by curing liquid crystal.

18. The liquid crystal display of claim 9, wherein the backlight unit further includes a reflective plate for reflecting light toward the display panel.

* * * * *

专利名称(译)	液晶显示器		
公开(公告)号	US20060290846A1	公开(公告)日	2006-12-28
申请号	US11/440601	申请日	2006-05-24
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	KIM JAE HYUN		
发明人	KIM, JAE-HYUN		
IPC分类号	G02F1/1335		
CPC分类号	G02F1/13362 G02F2203/09 G02F2203/01 G02F2001/133541		
优先权	1020050054848 2005-06-24 KR		
其他公开文献	US7750995		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种液晶显示器。在LCD中，反射偏振器和光学延迟器设置在吸收偏振器和背光单元之间。该结构回收通常在常规LCD中通过吸收去除的光以用于显示器，从而可以提高LCD的光效率和显示亮度。

