



US 20030048403A1

(19) **United States**

(12) **Patent Application Publication**
Satoh

(10) **Pub. No.: US 2003/0048403 A1**

(43) **Pub. Date: Mar. 13, 2003**

(54) **LIQUID CRYSTAL DISPLAY CELL WITH
IMPROVED SPACER STRUCTURE**

Publication Classification

(75) Inventor: **Hiroki Satoh, Akita (JP)**

(51) **Int. Cl. 7** **G02F 1/1339**

(52) **U.S. Cl.** **349/156**

Correspondence Address:

**YOUNG & THOMPSON
745 SOUTH 23RD STREET 2ND FLOOR
ARLINGTON, VA 22202**

(57) **ABSTRACT**

(73) Assignee: **NEC CORPORATION, TOKYO (JP)**

(21) Appl. No.: **10/242,604**

(22) Filed: **Sep. 13, 2002**

(30) **Foreign Application Priority Data**

Sep. 13, 2001 (JP) 2001-278590

A liquid crystal display cell includes: a first substrate; a second substrate; a liquid crystal layer interposed between the first and second substrates; and a spacer structure on the second substrate. The spacer structure further includes: at least a first type spacer having a first height and at least a second type spacer having a second height which is smaller than the first height.




FIG. 1A prior art




FIG. 1B prior art




FIG. 2A prior art




FIG. 2B prior art




FIG. 3A prior art




FIG. 3B prior art




FIG. 4A prior art




FIG. 4B prior art




FIG. 5A prior art




FIG. 5B prior art




FIG. 6A prior art




FIG. 6B prior art




FIG. 7A prior art




FIG. 7B prior art




FIG. 7C prior art




FIG. 8A prior art




FIG. 8B prior art




FIG. 8C prior art




FIG. 9A




FIG. 9B




FIG. 10




FIG. 11




FIG. 12A




FIG. 12B




FIG. 13A





FIG. 13B



LIQUID CRYSTAL DISPLAY CELL WITH IMPROVED SPACER STRUCTURE

BACKGROUND OF THE INVENTION

[0001] 1. Field of the Invention

[0002] The present invention relates to a liquid crystal display, and more particularly to a color filter substrate with an improved spacer structure for a liquid crystal display.

[0003] All of patents, patent applications, patent publications, scientific articles and the like, which will hereinafter be cited or identified in the present application, will, hereby, be incorporated by references in their entirety in order to describe more fully the state of the art, to which the present invention pertains.

[0004] 2. Description of the Related Art

[0005] A conventional structure of a liquid crystal display with a color filter substrate including column-shaped spacers will be described with reference to the drawings. **FIG. 1A** is a fragmentary schematic plan view of a conventional structure of a color filter substrate included in a conventional liquid crystal display. **FIG. 1B** is a fragmentary schematic cross sectional elevation view, taken along an X-X' line in **FIG. 1A**, illustrative of the conventional structure of the conventional liquid crystal display.

[0006] The liquid crystal display includes a color filter substrate 111 and a thin film transistor substrate 131 as well as a liquid crystal layer 113 filling in an inter-space between the color filter substrate 111 and the thin film transistor substrate 131.

[0007] The thin film transistor substrate 131 has a normal structure which includes a glass substrate, an insulating film, a matrix array of thin film transistors, interconnections and an orientation film which are not illustrated.

[0008] The color filter substrate 111 has a matrix array of pixels, each of which includes a set of primary-three-color filters 123, 124 and 125 which extend in parallel to each other and in a horizontal direction perpendicular to the X-X' line in **FIG. 1A**. The each pixel is represented by a broken line in **FIG. 1A** and has a rectangle shape in plan view which has a longitudinal direction along the X-X' line in **FIG. 1A**.

[0009] With reference to **FIG. 1B**, the color filter substrate 111 includes a glass substrate 101, a black matrix layer 102, color filter layers 123, 124 and 125, a common electrode layer 106, a column-shaped spacer 143, and an orientation film 107. The black matrix layer 102 extends over the glass substrate 101. The color filter layers 123, 124 and 125 extend over the black matrix layer 102 in the horizontal direction perpendicular to the X-X' line. The color filter layers 123, 124 and 125 are aligned in the direction along the X-X' line at a constant pitch and a constant gap, so that parts of the top surface of the black matrix layer 102 are exposed. Each of the color filter layers 123, 124 and 125 has a ridge shape in sectioned view, so that each of the color filter layers 123, 124 and 125 has a top plat surface and two sloped side-walls. The common electrode layer 106 extends on the top plat surface and the two sloped side-walls of the color filter layers 123, 124 and 125 and also on the exposed surface of the black matrix layer 102. The common electrode 106 may typically comprise an indium tin oxide film.

[0010] The column-shaped spacer 143 is provided in a gap between adjacent two of the pixels. The column-shaped spacer 143 is provided on the common electrode layer 106 over the top plat surface of the color filter layer 123. The orientation film 107 extends on the top surface and the side walls of the column-shaped spacer 143 as well as on the common electrode layer 106. The orientation film 107 is exposed to the liquid crystal layer 113. The orientation film 107 over the top surface of the column-shaped spacer 143 is in contact with the thin film transistor substrate 131. As described above, the column-shaped spacer 143 is provided in the gap between adjacent two of the pixels. Namely, the plural column-shaped spacers 143 are provided over the color filter substrate 111, so that the column-shaped spacers 143 form the inter-space defined between the color filter substrate 111 and the thin film transistor substrate 131, so as to allow the liquid crystal layer 113 fills the inter-space.

[0011] Another conventional structure of the liquid crystal display with the color filter substrate including column-shaped spacers will be described with reference to the drawings. **FIG. 2A** is a fragmentary schematic plan view of another conventional structure of the color filter substrate included in the conventional liquid crystal display. **FIG. 2B** is a fragmentary schematic cross sectional elevation view, taken along an X-X' line in **FIG. 2A**, illustrative of the conventional structure of the conventional liquid crystal display.

[0012] A difference of this other conventional structure of **FIGS. 2A and 2B** from the above-described conventional structure of **FIGS. 1A and 1B** is only in that not only the column-shaped spacer 143 is provided over the top surface of the color filter layer 123 but further column-shaped spacers 144 and 145 are also provided over the top surfaces of the color filter layers 124 and 125. Namely, in accordance with the conventional structure of **FIGS. 2A and 2B**, a set of the three column-shaped spacers 143, 144 and 145 is provided in the gap between the adjacent two of the pixels.

[0013] The above-described conventional structure of **FIGS. 1A and 1B** has the following programs with temperature variation. **FIG. 3A** is a fragmentary schematic cross sectional elevation view illustrative of the conventional structure of the liquid crystal display shown in **FIGS. 1A and 1B**, wherein the display is placed at a normal temperature of, for example, 20° C. **FIG. 3B** is a fragmentary schematic cross sectional elevation view illustrative of the conventional structure of the liquid crystal display shown in **FIGS. 1A and 1B**, wherein the display is placed at a high temperature of, for example, 60° C.

[0014] The variation in temperature causes a variation in cell gap of the display. The cell gap is defined to be a distance in vertical direction between the bottom surface of the thin film transistor substrate 131 and the top surface of the orientation film 107 in the gap between the adjacent two of the color filter layers 123, 124 and 125. Namely, the cell gap corresponds to a maximum gap in vertical direction of the inter-space between the thin film transistor substrate 131 and the color filter substrate 111.

[0015] As shown in **FIG. 3A**, if the display is placed in the normal temperature environment, for example, at 20° C., a cell gap "T1" is given by a spacer 103 which is defined between the top surface of the orientation film 107 over the top surface of the column-shaped spacer 143 and the top

surface of the orientation film 107 in the gap between the adjacent two of the color filter layers 123, 124 and 125. Namely, the height of the spacer 103 corresponds to a sum of a height of the column-shaped spacer 143 and a height of the color filter layer 123. Accordingly, in the normal temperature environment, the cell gap "T1" is given by the total height of the column-shaped spacer 143 and the color filter layer 123.

[0016] As shown in **FIG. 3B**, if the display is placed in the high temperature environment, for example, at 60° C., a cell gap "T2" is formed which is larger than the cell gap "T1", because the top surface of the orientation film 107 over the top surface of the column-shaped spacer 143 is distanced from the bottom surface of the thin film transistor substrate 131. Namely, the temperature increase causes an expansion of the liquid crystal layer 113. This expansion of the liquid crystal increases the cell gap and distances the top surface of the orientation film 107 over the top surface of the column-shaped spacer 143 from the bottom surface of the thin film transistor substrate 131, whereby the thin film transistor substrate 131 is floated by the expanded liquid crystal layer 113 from the column-shaped spacer 143. Therefore, the cell gap "T2" is unstable and variable.

[0017] In order to avoid the last-described problem, it was proposed that in the normal temperature environment, the column-shaped spacer 143 be compressed in the vertical direction, so that in the high temperature environment, the column-shaped spacer 143 is allowed to be free of the vertical compression and returned to the original shape by the expansion of the liquid crystal layer 113, whereby the compression-free column-shaped spacer 143, however, still supports the thin film transistor substrate 131. The description of this alternative proposal will be made in detail with reference to the drawings.

[0018] **FIG. 4A** is a fragmentary schematic cross sectional elevation view illustrative of the conventional structure of the liquid crystal display shown in **FIGS. 1A and 1B**, wherein the display is placed at the normal temperature of, for example, 20° C., and the column-shaped spacer is compressed in the vertical direction. **FIG. 4B** is a fragmentary schematic cross sectional elevation view illustrative of the conventional structure of the liquid crystal display shown in **FIGS. 1A and 1B**, wherein the display is placed at a high temperature of, for example, 60° C., and the column-shaped spacer is free from any vertical compression.

[0019] In the normal temperature environment, as shown in **FIG. 4A**, the column-shaped spacer 143 is compressed in the vertical direction, so that a smaller cell gap "t1" is formed, which is smaller than the above cell gap "T1" shown in **FIG. 3A**. The column-shaped spacer 143 has an elasticity.

[0020] If the display is placed into the high temperature environment as shown in **FIG. 4B**, then the liquid crystal layer 113 is expanded to press the color filter substrate 111 and the thin film transistor substrate 131 outwardly, so that the vertical compression to the column-shaped spacer 143 is reduced, and thus a larger cell gap "t2" is formed which is larger than the above cell gap "t1" in the normal temperature environment. However, in the high temperature environment as shown in **FIG. 4B**, the compression-reduced column-shaped spacer 143 still supports the thin film transistor substrate 131, whereby the thin film transistor substrate 131

is securely and stably supported by the compression-reduced column-shaped spacer 143. The cell gap "t2" is also stable and not variable. This technique is to utilize the elasticity of the column-shaped spacer 143.

[0021] **FIG. 5A** is a fragmentary schematic cross sectional elevation view illustrative of the conventional structure of the liquid crystal display shown in **FIGS. 1A and 1B**, wherein the display is placed at the normal temperature of, for example, 20° C. **FIG. 5B** is a fragmentary schematic cross sectional elevation view illustrative of the conventional structure of the liquid crystal display shown in **FIGS. 1A and 1B**, wherein the display is placed at a low temperature of, for example, -20° C.

[0022] As shown in **FIG. 5A**, if the display is placed in the normal temperature environment, for example, at 20° C., a cell gap "L1" is given by the spacer which is defined between the top surface of the orientation film 107 over the top surface of the column-shaped spacer 143 and the top surface of the orientation film 107 in the gap between the adjacent two of the color filter layers 123, 124 and 125. The column n-shaped spacer 143 is free of any substantive vertical compression. Namely, the height of the spacer 103 corresponds to a sum of the height of the column-shaped spacer 143 and the height of the color filter layer 123. Accordingly, in the normal temperature environment, the cell gap "L1" is given by the total height of the compression-free column-shaped spacer 143 and the color filter layer 123.

[0023] As shown in **FIG. 5B**, if the display is placed in the low temperature environment, for example, at -20° C., then a cell gap "L2" is formed which is smaller than the cell gap "L1", because the liquid crystal layer 113 is contracted and reduced in volume and thus the column-shaped spacer 143 is thus compressed in the vertical direction. The column-shaped spacer 143 is provided for the gap between the adjacent two of the pixels. Since the number of the column-shaped spacer 143 is small, then the total elastic force of the plural column-shaped spacers 143 is still smaller than the contracting force of the liquid crystal layer 113.

[0024] **FIG. 6A** is a fragmentary schematic cross sectional elevation view illustrative of the conventional structure of the liquid crystal display shown in **FIGS. 2A and 2B**, wherein the display is placed at the normal temperature of, for example, 20° C. **FIG. 6B** is a fragmentary schematic cross sectional elevation view illustrative of the conventional structure of the liquid crystal display shown in **FIGS. 2A and 2B**, wherein the display is placed at a low temperature of, for example, -20° C.

[0025] As shown in **FIG. 6A**, if the display is placed in the normal temperature environment, for example, at 20° C., a cell gap "L1" is given by the spacer which is defined between the top surface of the orientation film 107 over the top surface of the column-shaped spacers 143, 144 and 145 and the top surface of the orientation film 107 in the gap between the adjacent two of the color filter layers 123, 124 and 125. The column-shaped spacers 143, 144 and 145 are free of any substantive vertical compression. Namely, the height of the spacer 103 corresponds to a sum of the height of each of the column-shaped spacers 143, 144 and 145 and the height of each of the color filter layers 123, 124 and 125. Accordingly, in the normal temperature environment, the cell gap "L1" is given by the total height of each of the compression-free column-shaped spacers 143, 144 and 145 and each of the color filter layers 123, 124 and 125.

[0026] As shown in **FIG. 6B**, if the display is placed in the low temperature environment, for example, at -20°C , then a cell gap “L2” is formed which is nearly equal to the cell gap “L1”, because the liquid crystal layer 113 has a contracting force but not reduced in volume and thus the column-shaped spacers 143, 144 and 145 are not compressed in the vertical direction. The column-shaped spacers 143, 144 and 145 are provided for the gap between the adjacent two of the pixels. Since the number of the column-shaped spacers 143, 144 and 145 is large, then the total elastic force of the plural column-shaped spacers 143, 144 and 145 is larger than the contracting force of the liquid crystal layer 113. For this reason, the cell gap is not varied substantially. However, the liquid crystal layer 113 causes an evaporation of chemically unstable low molecular materials therein, whereby undesired bubbles or foams are formed in the liquid crystal layer 113. These bubbles or foams, cause display defective of the display device. Consequently, the small number of the column-shaped spacers is preferable for avoiding the undesired formation of the bubbles or foams in the liquid crystal layer 113.

[0027] The following descriptions will focus on how the status of the display device is changed upon application of an external load and after released from the load. **FIG. 7A** is a fragmentary schematic cross sectional elevation view of the liquid crystal display device shown in **FIGS. 1A and 1B**, prior to any application of external load. **FIG. 7B** is a fragmentary schematic cross sectional elevation view of the liquid crystal display device shown in **FIGS. 1A and 1B**, upon application of an external load in the vertical direction to the surface of the thin film transistor substrate. **FIG. 7C** is a fragmentary schematic cross sectional elevation view of the liquid crystal display device shown in **FIGS. 1A and 1B**, after released from the applied external load.

[0028] As shown in **FIG. 7A**, the liquid crystal display device before application of any external load is placed in the same state as that shown in **FIGS. 1A and 1B**, wherein the column-shaped spacer 143 is free of any compression, and the device has the originally designed cell gap “L1”.

[0029] As shown in **FIG. 7B**, the liquid crystal display device is applied with the external load in the direction vertical to the surface of the thin film transistor substrate 111, so that the column-shaped spacer 143 is compressed and largely deformed, and the device has a reduced cell gap “L2” which is smaller than the originally designed cell gap “L1”.

[0030] As shown in **FIG. 7C**, even after the liquid crystal display device is released from the external load, the column-shaped spacer 143 still remains in the deformed or compressed state, but not returned to the original shape, and thus the device remains having the reduced cell gap “L2”.

[0031] **FIG. 8A** is a fragmentary schematic cross sectional elevation view of the liquid crystal display device shown in **FIGS. 2A and 2B**, prior to any application of external load. **FIG. 8B** is a fragmentary schematic cross sectional elevation view of the liquid crystal display device shown in **FIGS. 2A and 2B**, upon application of an external load in the vertical direction to the surface of the thin film transistor substrate. **FIG. 8C** is a fragmentary schematic cross sectional elevation view of the liquid crystal display device shown in **FIGS. 2A and 2B**, after released from the applied external load. As a result, the cell gap variation is caused, and the display defect may be caused.

[0032] As shown in **FIG. 8A**, the liquid crystal display device before application of any external load is placed in the same state as that shown in **FIGS. 2A and 2B**, wherein the column-shaped spacers 143, 144 and 145 are free of any compression, and the device has the originally designed cell gap “L1”.

[0033] As shown in **FIG. 8B**, the liquid crystal display device is applied with the external load in the direction vertical to the surface of the thin film transistor substrate 111, so that the column-shaped spacers 143, 144 and 145 are compressed and slightly deformed, and the device has a reduced cell gap “L2” which is smaller than the originally designed cell gap “L1”.

[0034] As shown in **FIG. 8C**, after the liquid crystal display device is released from the external load, the column-shaped spacers 143, 144 and 145 become free from the deformed or compressed state, and are returned to the original shape, so that the device has again the originally designed cell gap “L1”. As a result, no cell gap variation is caused, nor display defect may be caused.

[0035] Consequently, increasing the density or the number of the column-shaped spacers may increase the mechanical resistivity to the externally applied load, while may allow undesired formation of bubbles or foams in the liquid crystal layer upon the temperature drop.

[0036] In the above circumstances, the development of a novel liquid crystal display with an improved spacer structure free from the above problems is desirable.

SUMMARY OF THE INVENTION

[0037] Accordingly, it is an object of the present invention to provide a novel liquid crystal display with an improved spacer structure free from the above problems.

[0038] The present invention provides a liquid crystal display cell including: a first substrate; a second substrate; a liquid crystal layer interposed between the first and second substrates; and a spacer structure on the second substrate. The spacer structure further includes: at least a first type spacer having a first height; and at least a second type spacer having a second height which is smaller than the first height.

[0039] The above and other objects, features and advantages of the present invention will be apparent from the following descriptions.

BRIEF DESCRIPTION OF THE DRAWINGS

[0040] Preferred embodiments according to the present invention will be described in detail with reference to the accompanying drawings.

[0041] **FIG. 1A** is a fragmentary schematic plan view of a conventional structure of a color filter substrate included in a conventional liquid crystal display.

[0042] **FIG. 1B** is a fragmentary schematic cross sectional elevation view, taken along an X-X' line in **FIG. 1A**, illustrative of the conventional structure of the conventional liquid crystal display.

[0043] **FIG. 2A** is a fragmentary schematic plan view of another conventional structure of the color filter substrate included in the conventional liquid crystal display.

[0044] **FIG. 2B** is a fragmentary schematic cross sectional elevation view, taken along an X-X' line in **FIG. 2A**, illustrative of the conventional structure of the conventional liquid crystal display.

[0045] **FIG. 3A** is a fragmentary schematic cross sectional elevation view illustrative of the conventional structure of the liquid crystal display shown in **FIGS. 1A and 1B**, wherein the display is placed at a normal temperature of, for example, 20° C.

[0046] **FIG. 3B** is a fragmentary schematic cross sectional elevation view illustrative of the conventional structure of the liquid crystal display shown in **FIGS. 1A and 1B**, wherein the display is placed at a high temperature of, for example, 60° C.

[0047] **FIG. 4A** is a fragmentary schematic cross sectional elevation view illustrative of the conventional structure of the liquid crystal display shown in **FIGS. 1A and 1B**, wherein the display is placed at the normal temperature of, for example, 20° C., and the column-shaped spacer is compressed in the vertical direction.

[0048] **FIG. 4B** is a fragmentary schematic cross sectional elevation view illustrative of the conventional structure of the liquid crystal display shown in **FIGS. 1A and 1B**, wherein the display is placed at a high temperature of, for example, 60° C., and the column-shaped spacer is free from any vertical compression.

[0049] **FIG. 5A** is a fragmentary schematic cross sectional elevation view illustrative of the conventional structure of the liquid crystal display shown in **FIGS. 1A and 1B**, wherein the display is placed at the normal temperature of, for example, 20° C.

[0050] **FIG. 5B** is a fragmentary schematic cross sectional elevation view illustrative of the conventional structure of the liquid crystal display shown in **FIGS. 1A and 1B**, wherein the display is placed at a low temperature of, for example, -20° C.

[0051] **FIG. 6A** is a fragmentary schematic cross sectional elevation view illustrative of the conventional structure of the liquid crystal display shown in **FIGS. 2A and 2B**, wherein the display is placed at the normal temperature of, for example, 20° C.

[0052] **FIG. 6B** is a fragmentary schematic cross sectional elevation view illustrative of the conventional structure of the liquid crystal display shown in **FIGS. 2A and 2B**, wherein the display is placed at a low temperature of, for example, -20° C.

[0053] **FIG. 7A** is a fragmentary schematic cross sectional elevation view of the liquid crystal display device shown in **FIGS. 1A and 1B**, prior to any application of external load.

[0054] **FIG. 7B** is a fragmentary schematic cross sectional elevation view of the liquid crystal display device shown in **FIGS. 1A and 1B**, upon application of an external load in the vertical direction to the surface of the thin film transistor substrate.

[0055] **FIG. 7C** is a fragmentary schematic cross sectional elevation view of the liquid crystal display device shown in **FIGS. 1A and 1B**, after released from the applied external load.

[0056] **FIG. 8A** is a fragmentary schematic cross sectional elevation view of the liquid crystal display device shown in **FIGS. 2A and 2B**, prior to any application of external load.

[0057] **FIG. 8B** is a fragmentary schematic cross sectional elevation view of the liquid crystal display device shown in **FIGS. 2A and 2B**, upon application of an external load in the vertical direction to the surface of the thin film transistor substrate.

[0058] **FIG. 8C** is a fragmentary schematic cross sectional elevation view of the liquid crystal display device shown in **FIGS. 2A and 2B**, after released from the applied external load.

[0059] **FIG. 9A** is a fragmentary schematic plan view of a color filter substrate included in a novel liquid crystal display in a first embodiment in accordance with the present invention.

[0060] **FIG. 9B** is a fragmentary schematic cross sectional elevation view, taken along an X-X' line in **FIG. 9A**, illustrative of a novel spacer structure of the color filter substrate included in the novel liquid crystal display.

[0061] **FIG. 10** is a fragmentary cross sectional elevation view of a novel liquid crystal display including a thin film transistor substrate and the color filter substrate of **FIGS. 9A and 9B** in the first embodiment in accordance with the present invention.

[0062] **FIG. 11** is a fragmentary schematic plane view of one example of an arrangement pattern of spacers over a matrix array of pixels of the color filter substrate included in the liquid crystal display of **FIG. 10**.

[0063] **FIG. 12A** is a fragmentary schematic plan view of a color filter substrate included in a novel liquid crystal display in a modified embodiment in accordance with the present invention.

[0064] **FIG. 12B** is a fragmentary schematic cross sectional elevation view, taken along an X-X' line in **FIG. 12A**, illustrative of a novel spacer structure of the color filter substrate included in the novel liquid crystal display.

[0065] **FIG. 13A** is a fragmentary schematic plan view of a color filter substrate included in a novel liquid crystal display in a further modified embodiment in accordance with the present invention.

[0066] **FIG. 13B** is a fragmentary schematic cross sectional elevation view, taken along an X-X' line in **FIG. 13A**, illustrative of a novel spacer structure of the color filter substrate included in the novel liquid crystal display.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0067] A primary aspect of the present invention is a liquid crystal display cell including: a first substrate; a second substrate; a liquid crystal layer interposed between the first and second substrates; and a spacer structure on the second substrate. The spacer structure further includes: at least a first type spacer having a first height; and at least a second type spacer having a second height which is smaller than the first height.

[0068] It is preferable that the first height provides an original cell gap, and a difference between the first and

second heights is smaller than an elastic deformation limit of the first spacer, provided that the elastic deformation limit is a transitional compressive deformation amount, over which a compressive deformation is a plastic deformation and under which the compressive deformation is an elastic deformation.

[0069] It is also preferable that the first height provides an original cell gap, and the second height is larger than a subtraction of an elastic deformation limit of the first spacer from the first height, provided that the elastic deformation limit is a transitional compressive deformation amount, over which a compressive deformation is a plastic deformation and under which the compressive deformation is an elastic deformation.

[0070] It is also preferable that the first type spacer comprises a first color filter layer over the second substrate, and a first column-shaped spacer over the first color filter layer, and the second type spacer comprises a second color filter layer over the second substrate, and a second column-shaped spacer over the second color filter layer. In one example, the first and second color filter layers may have the same thickness or height, while the first column-shaped spacer may be larger in height than the second column-shaped spacer. In another example, the first and second column-shaped spacers may have the same height, while the first color filter layer may be larger in thickness or height than the second color filter layer.

[0071] It is preferable that the spacer structure further includes: at least a third type spacer having a third height which is smaller than the second height. Preferably, the third type spacer may comprise a third color filter layer over the second substrate, and a third column-shaped spacer over the third color filter layer. In one example, the first, second and third color filter layers may have the same thickness or height, while the first column-shaped spacer may be larger in height than the second column-shaped spacer, and the second column-shaped spacer may be larger in height than the third column-shaped spacer. In another example, the first, second and third column-shaped spacers may have the same height, while the first color filter layer may be larger in height than the second color filter layer, and the second color filter layer may be larger in thickness or height than the third color filter layer.

[0072] The following embodiments are typical examples for practicing the foregoing aspects of the present invention. Although the subject matters of the present invention have been described in details, the following additional descriptions in one or more typical preferred embodiments or examples will be made with reference to the drawings for making it easy to understand the typical modes for practicing the foregoing aspects of the present invention.

[0073] First Embodiment:

[0074] A first embodiment according to the present invention will be described in detail with reference to the drawings. **FIG. 9A** is a fragmentary schematic plan view of a color filter substrate included in a novel liquid crystal display in a first embodiment in accordance with the present invention. **FIG. 9B** is a fragmentary schematic cross sectional elevation view, taken along an X-X' line in **FIG. 9A**, illustrative of a novel spacer structure of the color filter substrate included in the novel liquid crystal display.

[0075] The color filter substrate **10** has a matrix array of pixels, each of which includes a set of primary-three-color filters **23**, **24** and **25** which extend in parallel to each other and in a horizontal direction perpendicular to the X-X' line in **FIG. 9A**. The each pixel is represented by a broken line in **FIG. 9A** and has a rectangle shape in plan view which has a longitudinal direction along the X-X' line in **FIG. 9A**.

[0076] With reference to **FIG. 9B**, the color filter substrate **10** includes a glass substrate **1**, a black matrix layer **2**, first, second and third color filter layers **23**, **24** and **25**, a common electrode layer **6**, first and second column-shaped spacers **43** and **44**, and an orientation film **7**. The black matrix layer **2** extends over the glass substrate **1**. The black matrix layer **2** may comprise Cr or a resin.

[0077] The first, second and third color filter layers **23**, **24** and **25** may be formed by a pigment-dispersion method. The first, second and third color filter layers **23**, **24** and **25** correspond primary-three colors, for example, red, green and blue. The first, second and third color filter layers **23**, **24** and **25** extend over the black matrix layer **2** in the horizontal direction perpendicular to the X-X' line. The first, second and third color filter layers **23**, **24** and **25** are aligned in the direction along the X-X' line at a constant pitch and a constant gap, so that parts of the top surface of the black matrix layer **2** are exposed. Each of the first, second and third color filter layers **23**, **24** and **25** has a ridge shape in sectioned view, so that each of the first, second and third color filter layers **23**, **24** and **25** has a top plat surface and two sloped side-walls. The first, second and third color filter layers **23**, **24** and **25** are, however, different in height, wherein the top levels of the first, second and third color filter layers **23**, **24** and **25** are different from each other, but the bottom levels thereof are identical with each other. For example, the top level of the first color filter layer **23** is highest, while the top level of the third color filter layer **25** is lowest, and the top level of the second color filter layer **24** is middle between the first and third color filter layers **23** and **25**. The differentiation in thickness or height among the first, second and third color filter layers **23**, **24** and **25** need to adjust color-material concentrations of the first, second and third color filter layers **23**, **24** and **25** in order to realize originally designed color tones.

[0078] The common electrode layer **6** extends on the respective top plat surface and the respective two sloped side-walls of the first, second and third color filter layers **23**, **24** and **25** and also on the exposed surface of the black matrix layer **2**. The common electrode layer **6** may typically comprise an indium tin oxide film.

[0079] The first and second column-shaped spacers **43** and **44** are provided in a gap between adjacent two of the pixels. The first and second column-shaped spacers **43** and **44** may optionally and advantageously comprise a photo-sensitive transparent acrylic resin. The first column-shaped spacer **43** is provided on the common electrode layer **6** over the top plat surface of the first color filter layer **23**. The second column-shaped spacer **44** is provided on the common electrode layer **6** over the top plat surface of the second color filter layer **24**. The first and second column-shaped spacers **43** and **44** have the same height as each other. However, the respective levels of the first and second column-shaped spacers **43** and **44** are different from each other, wherein the first column-shaped spacer **43** is higher in level than the

second column-shaped spacer **44**, because the respective levels of the first and second column-shaped spacers **43** and **44** depend on the respective top levels of the first and second color filter layers **23** and **24**. Since the top level of the first color filter layer **23** is higher than the top level of the second color filter layer **24**, then the first column-shaped spacer **43** is higher in level than the second column-shaped spacer **44**, even the respective heights of the first and second column-shaped spacers **43** and **44** are identical with each other.

[0080] A difference in level between the first and second column-shaped spacers **43** and **44** is caused by the difference in height of the first and second color filter layers **23** and **24**. A first combination of the first color filter layer **23** and the first column-shaped spacer **43** forms a first spacer **3**. A second combination of the second color filter layer **24** and the second column-shaped spacer **44** forms a second spacer **4**. The first spacer **3** is greater in height than the second spacer **4**. A difference in height between the first and second spacers **3** and **4** is caused by the difference in height of the first and second color filter layers **23** and **24**.

[0081] The orientation film **7** extends on the top surface and the side walls of the first and second column-shaped spacers **43** and **44** as well as on the common electrode layer **6**. The orientation film **7** is exposed to a liquid crystal layer.

[0082] FIG. 10 is a fragmentary cross sectional elevation view of a novel liquid crystal display including a thin film transistor substrate and the color filter substrate of FIGS. 9A and 9B in the first embodiment in accordance with the present invention. The liquid crystal display includes the color filter substrate **10** as described with reference to FIGS. 9A and 9B and a thin film transistor substrate **20** as well as a liquid crystal layer **13** filling in an inter-space between the color filter substrate **10** and the thin film transistor substrate **20**. The thin film transistor substrate **20** has a normal structure which includes a glass substrate, an insulating film, a matrix array of thin film transistors, interconnections and an orientation film which are not illustrated. The color filter substrate **10** is as described above with reference to FIGS. 9A and 9B.

[0083] As described above, the first column-shaped spacer **43** is higher in top level than the second column-shaped spacer **44**, provided that the first and second column-shaped spacers **43** and **44** have the same height as each other, but the first color filter layer **23** has a larger height than the second color filter layer **24**. When the thin film transistor substrate **20** receives an application of an external pressure or an external load in a vertical direction to the surface of the thin film transistor substrate **20**, then the first column-shaped spacer **43** is first compressed by the applied load. In one typical example, the first and second column-shaped spacers **43** and **44** may be so designed as follows. In case that the cell gap is 4.0 micrometers, as the compressive deformation of the first spacer **3** becomes larger than 0.4 micrometers or one tenth of the cell gap of 4.0 micrometers, then the compressive deformation becomes plastic deformation from elastic deformation. Namely, if the compressive deformation of the first spacer **3** is smaller than one tenth of the cell gap, then the compressive deformation is elastic deformation, wherein after the device is released from the application of the external load, then the compressed first spacer **3** providing the reduced cell gap will be returned to the original shape providing the original cell gap. If the compressive deformation

of the first spacer **3** is larger than one tenth of the cell gap, then the compressive deformation is plastic deformation, wherein even after the device is released from the application of the external load, then the compressed first spacer **3** providing the reduced cell gap will remain in the compressed or deformed state providing the reduced cell gap.

[0084] If a difference in level between the first and second column-shaped spacers **43** and **44** is defined to be "d", then the difference "d" is designed larger than a variation in cell gap between the normal temperature, for example, 20° C. and the low temperature, for example, -20° C., so that the elastic deformation of the first column-shaped spacer **43** completely absorbs the reduction in the cell gap caused by the temperature change from the normal temperature to the low temperature, whereby the first column-shaped spacer **43** shows no plastic deformation. Further, as the difference "d" is designed larger than a variation in cell gap between the normal temperature and the low temperature, the second column-shaped spacer **44** at the low temperature still remains distanced from the thin film transistor substrate **20** and thus the first column-shaped spacer **43** only remains mechanically supporting the thin film transistor substrate **20**, whereby no bubbles nor foams are formed in the liquid crystal layer **13** at the low temperature.

[0085] A distance "h" appearing in FIG. 10 represents a limitation of the elastic deformation of the first column-shaped spacer **43**. If the compressive deformation of the first column-shaped spacer **43** becomes larger than the elastic deformation limit "h", then the deformation is the plastic deformation or the first column-shaped spacer **43** may be broken. A further mechanical support to the thin film transistor substrate **20** by the second spacer **4** is necessary for preventing the first column-shaped spacer **43** from showing the larger compressive deformation than the elastic deformation limit "h". Therefore, the difference "d" in the top level between the first and second spacers **3** and **4** is smaller than the elastic deformation limit "h" of the first column-shaped spacer **43**.

[0086] It is, hereby, assumed that the cell gap corresponding to the first height of the first spacer **3** is 4.0 micrometers, and the elastic deformation limitation of the first column-shaped spacer **43** is 0.4 micrometers as one tenth of the cell gap. Namely, 0.4 micrometers is the transitional value from the elastic deformation to the plastic deformation. The second spacer **4** is designed to have a second height which satisfies the condition that the difference "d" in the top level between the first and second spacers **3** and **4** is smaller than 0.4 micrometers of the elastic deformation limit "h" of the first column-shaped spacer **43**. Namely, the second height is smaller than the first height of 4.0 micrometers of the first spacer **3**, but larger than 3.6 micrometers which corresponds to the subtraction of the elastic deformation limit "h" from the first height of the first spacer **3**.

[0087] FIG. 11 is a fragmentary schematic plane view of one example of an arrangement pattern of spacers over a matrix array of pixels of the color filter substrate included in the liquid crystal display of FIG. 10. Each squared block represents the pixel. Each circle represents the spacer. The spacers **3** and **4** are arranged in checkered pattern. In pixels **110**, **111**, **112**, **113** and **114**, the spacers are provided. The above arrangement pattern is only one example. It is also

possible to provide a plurality of the column-shaped spacers over the color filters in the single pixel. It is also possible to vary the density in arrangement of the spacers.

[0088] Adjustment in the area of the top of the column-shaped spacers provides substantially the same effect as adjustment to the density in arrangement of the column-shaped spacers. In this embodiment, the arrangement of the spacers is made by taking into account only the spacer arrangement density.

[0089] The above embodiment of the present invention may realize that the design of the spacers be made to avoid the gap variation at the high temperature condition and also the formation of bubbles or foams in the low temperature condition, and also to provide a sufficient mechanical supporting strength to the external load. Namely, the difference in top level of the spacers allows that the first spacer only absorbs the compressive deformation of the cell as long as the compressive deformation of the first column-shaped spacer is in the elastic deformation, while as the compressive deformation of the first column-shaped spacer reaches the elastic deformation limit, then the second spacer also absorbs the compressive deformation of the cell in addition to the first spacer. After the cell is released from the external load, then only the first spacer mechanically supports the thin film transistor substrate. This structure may allow a reduction of the cell gap, thereby making it difficult to form bubbles or foams.

[0090] For numerical comparison of the withstand load strength of the liquid crystal cell, it is assumed that the withstand load strength is 1.0 if the spacers are provided in all of the pixels. If the spacers are provided in one half of all the pixels, then the withstand load strength is approximately 0.5.

[0091] Under the low temperature condition, a half arrangement of the spacers in one half of all the pixels allows a larger compression or a larger reduction in the cell gap than a full arrangement of the spacers in all the pixels, for which reason the half arrangement of the spacers in one half of all the pixels is suitable for avoiding the undesired formation of bubbles and foams in the liquid crystal layer, and thus avoiding the display defect.

[0092] If the above described novel liquid crystal display needs substantially the same withstand load strength of the spacers as of the conventional display with the full spacer arrangement, and if the above described novel liquid crystal display needs substantially the same display defective rate as of the conventional display with the half spacer arrangement, then this display may be realized by arrangement of a pair of the first and second spacers in each pixel.

[0093] As a modification to the above embodiment, first, second and third column-shaped spacers having the same height are provided over the first, second and third color filter layers having different heights, respectively. **FIG. 12A** is a fragmentary schematic plan view of a color filter substrate included in a novel liquid crystal display in a modified embodiment in accordance with the present invention. **FIG. 12B** is a fragmentary schematic cross sectional elevation view, taken along an X-X' line in **FIG. 12A**, illustrative of a novel spacer structure of the color filter substrate included in the novel liquid crystal display.

[0094] The color filter substrate **10** has a matrix array of pixels, each of which includes a set of primary-three-color

filters **23**, **24** and **25** which extend in parallel to each other and in a horizontal direction perpendicular to the X-X' line in **FIG. 12A**. The each pixel is represented by a broken line in **FIG. 12A** and has a rectangle shape in plan view which has a longitudinal direction along the X-X' line in **FIG. 12A**.

[0095] With reference to **FIG. 12B**, the color filter substrate **10** includes a glass substrate **1**, a black matrix layer **2**, first, second and third color filter layers **23**, **24** and **25**, a common electrode layer **6**, first, second and third column-shaped spacers **63**, **64** and **65**, and an orientation film **7**.

[0096] The first, second and third color filter layers **23**, **24** and **25** may be formed by a pigment-dispersion method. The first, second and third color filter layers **23**, **24** and **25** correspond primary-three colors, for example, red, green and blue. The first, second and third color filter layers **23**, **24** and **25** extend over the black matrix layer **2** in the horizontal direction perpendicular to the X-X' line. The first, second and third color filter layers **23**, **24** and **25** are aligned in the direction along the X-X' line at a constant pitch and a constant gap, so that parts of the top surface of the black matrix layer **2** are exposed. Each of the first, second and third color filter layers **23**, **24** and **25** has a ridge shape in sectioned view, so that each of the first, second and third color filter layers **23**, **24** and **25** has a top plat surface and two sloped side-walls. The first, second and third color filter layers **23**, **24** and **25** are, however, different in height, wherein the top levels of the first, second and third color filter layers **23**, **24** and **25** are different from each other, but the bottom levels thereof are identical with each other. For example, the top level of the first color filter layer **23** is highest, while the top level of the third color filter layer **25** is lowest, and the top level of the second color filter layer **24** is middle between the first and third color filter layers **23** and **25**. The differentiation in thickness or height among the first, second and third color filter layers **23**, **24** and **25** need to adjust color-material concentrations of the first, second and third color filter layers **23**, **24** and **25** in order to realize originally designed color tones.

[0097] The common electrode layer **6** extends on the respective top plat surface and the respective two sloped side-walls of the first, second and third color filter layers **23**, **24** and **25** and also on the exposed surface of the black matrix layer **2**. The common electrode layer **6** may typically comprise an indium tin oxide film.

[0098] The first, second and third column-shaped spacers **63**, **64** and **65** are provided in a gap between adjacent two of the pixels. The first, second and third column-shaped spacers **63**, **64** and **65** may optionally and advantageously comprise a photo-sensitive transparent acrylic resin. The first column-shaped spacer **63** is provided on the common electrode layer **6** over the top plat surface of the first color filter layer **23**. The second column-shaped spacer **64** is provided on the common electrode layer **6** over the top plat surface of the second color filter layer **24**. The third column-shaped spacer **65** is provided on the common electrode layer **6** over the top plat surface of the third color filter layer **25**. The first, second and third column-shaped spacers **63**, **64** and **65** have the same height as each other. However, the respective levels of the first, second and third column-shaped spacers **63**, **64** and **65** are different from each other, wherein the first column-shaped spacer **63** is higher in level than the second column-shaped spacer **64** which is higher in level than the third

column-shaped spacer 65, because the respective levels of the first, second and third column-shaped spacers 63, 64 and 65 depend on the respective top levels of the first, second and third color filter layers 23, 24 and 25. Since the top level of the first color filter layer 23 is higher than the top level of the second color filter layer 24, then the first column-shaped spacer 63 is higher in level than the second column-shaped spacer 64, even the respective heights of the first and second column-shaped spacers 63 and 64 are identical with each other. Since the top level of the second color filter layer 24 is higher than the top level of the third color filter layer 25, then the second column-shaped spacer 64 is higher in level than the third column-shaped spacer 65, even the respective heights of the second and third column-shaped spacers 64 and 65 are identical with each other.

[0099] Respective differences in level among the first, second and third column-shaped spacers 63, 64 and 65 are caused by the differences in height of the first, second and third color filter layers 23, 24 and 25. A first combination of the first color filter layer 23 and the first column-shaped spacer 63 forms a first spacer 3. A second combination of the second color filter layer 24 and the second column-shaped spacer 64 forms a second spacer 4. A third combination of the third color filter layer 25 and the third column-shaped spacer 65 forms a third spacer 5. The first spacer 3 is greater in height than the second spacer 4. A difference in height between the first and second spacers 3 and 4 is caused by the difference in height of the first and second color filter layers 23 and 24. The second spacer 4 is greater in height than the third spacer 5. A difference in height between the second and third spacers 4 and 5 is caused by the difference in height of the second and third color filter layers 24 and 25.

[0100] The above modified spacer structure also provide substantially the same functions and effects as described in the first embodiment.

[0101] As a further modification to the above embodiment, first, second and third column-shaped spacers having the same height are provided over the first, second and third color filter layers having different heights, respectively. **FIG. 13A** is a fragmentary schematic plan view of a color filter substrate included in a novel liquid crystal display in a further modified embodiment in accordance with the present invention. **FIG. 13B** is a fragmentary schematic cross sectional elevation view, taken along an X-X' line in **FIG. 13A**, illustrative of a novel spacer structure of the color filter substrate included in the novel liquid crystal display.

[0102] The color filter substrate 10 has a matrix array of pixels, each of which includes a set of primary-three-color filters 23, 24 and 25 which extend in parallel to each other and in a horizontal direction perpendicular to the X-X' line in **FIG. 13A**. The each pixel is represented by a broken line in **FIG. 13A** and has a rectangle shape in plan view which has a longitudinal direction along the X-X' line in **FIG. 13A**.

[0103] With reference to **FIG. 13B**, the color filter substrate 10 includes a glass substrate 1, a black matrix layer 2, first, second and third color filter layers 23, 24 and 25, a common electrode layer 6, first and second column-shaped spacers 83 and 84, and an orientation film 7.

[0104] The first, second and third color filter layers 23, 24 and 25 may be formed by a pigment-dispersion method. The first, second and third color filter layers 23, 24 and 25

correspond primary-three colors, for example, red, green and blue. The first, second and third color filter layers 23, 24 and 25 extend over the black matrix layer 2 in the horizontal direction perpendicular to the X-X' line. The first, second and third color filter layers 23, 24 and 25 are aligned in the direction along the X-X' line at a constant pitch and a constant gap, so that parts of the top surface of the black matrix layer 2 are exposed. Each of the first, second and third color filter layers 23, 24 and 25 has a ridge shape in sectioned view, so that each of the first, second and third color filter layers 23, 24 and 25 has a top plat surface and two sloped side-walls. The first, second and third color filter layers 23, 24 and 25 have a uniform height.

[0105] The common electrode layer 6 extends on the respective top plat surface and the respective two sloped side-walls of the first, second and third color filter layers 23, 24 and 25 and also on the exposed surface of the black matrix layer 2. The common electrode layer 6 may typically comprise an indium tin oxide film.

[0106] The first and second column-shaped spacers 83 and 84 are provided in a gap between adjacent two of the pixels. The first and second column-shaped spacers 83 and 84 may optionally and advantageously comprise a photo-sensitive transparent acrylic resin. The first column-shaped spacer 83 is provided on the common electrode layer 6 over the top plat surface of the first color filter layer 23. The second column-shaped spacer 84 is provided on the common electrode layer 6 over the top plat surface of the second color filter layer 24. The first and second column-shaped spacers 83 and 84 are different in height from each other, wherein the first column-shaped spacer 83 is higher than the second column-shaped spacer 83, so that the respective top levels of the first and second column-shaped spacers 83 and 84 are different from each other, wherein the first column-shaped spacer 83 is higher in top level than the second column-shaped spacer 84.

[0107] A difference in top level between the first and second column-shaped spacers 83 and 84 is caused by the difference in height thereof. A first combination of the first color filter layer 23 and the first column-shaped spacer 83 forms a first spacer 3. A second combination of the second color filter layer 24 and the second column-shaped spacer 84 forms a second spacer 4. The first spacer 3 is greater in height than the second spacer 4. A difference in height between the first and second spacers 3 and 4 is caused by the difference in height of the first and second color filter layers 23 and 24.

[0108] The above modified spacer structure also provide substantially the same functions and effects as described in the first embodiment.

[0109] Although the invention has been described above in connection with several preferred embodiments therefor, it will be appreciated that those embodiments have been provided solely for illustrating the invention, and not in a limiting sense. Numerous modifications and substitutions of equivalent materials and techniques will be readily apparent to those skilled in the art after reading the present application, and all such modifications and substitutions are expressly understood to fall within the true scope and spirit of the appended claims.

What is claimed is:

1. A liquid crystal display cell including:
 - a first substrate;
 - a second substrate;
 - a liquid crystal layer interposed between said first and second substrates; and
 - a spacer structure on said second substrate, and said spacer structure further including:
 - at least a first type spacer having a first height; and
 - at least a second type spacer having a second height which is smaller than said first height.
2. The liquid crystal display cell as claimed in claim 1, wherein said first height provides an original cell gap, and a difference between said first and second heights is smaller than an elastic deformation limit of said first spacer, provided that said elastic deformation limit is a transitional compressive deformation amount, over which a compressive deformation is a plastic deformation and under which said compressive deformation is an elastic deformation.
3. The liquid crystal display cell as claimed in claim 1, wherein said first height provides an original cell gap, and said second height is larger than a subtraction of an elastic deformation limit of said first spacer from said first height, provided that said elastic deformation limit is a transitional compressive deformation amount, over which a compressive deformation is a plastic deformation and under which said compressive deformation is an elastic deformation.
4. The liquid crystal display cell as claimed in claim 1, wherein said first type spacer comprises a first color filter layer over said substrate, and a first column-shaped spacer over said first color filter layer, and said second type spacer comprises a second color filter layer over said second substrate, and a second column-shaped spacer over said second color filter layer.
5. The liquid crystal display cell as claimed in claim 4, wherein said first and second color filter layers have the same thickness or height, while said first column-shaped spacer is larger in height than said second column-shaped spacer.
6. The liquid crystal display cell as claimed in claim 4, wherein said first and second column-shaped spacers have the same height, while said first color filter layer is larger in thickness or height than said second color filter layer.
7. The liquid crystal display cell as claimed in claim 1, wherein said spacer structure further includes:
 - at least a third type spacer having a third height which is smaller than said second height.
8. The liquid crystal display cell as claimed in claim 7, wherein said third type spacer comprises a third color filter layer over said second substrate, and a third column-shaped spacer over said third color filter layer.
9. The liquid crystal display cell as claimed in claim 8, wherein said first, second and third color filter layers have the same thickness or height, while said first column-shaped spacer is larger in height than said second column-shaped spacer, and said second column-shaped spacer is larger in height than said third column-shaped spacer.
10. The liquid crystal display cell as claimed in claim 8, wherein said first, second and third column-shaped spacers have the same height, while said first color filter layer is larger in thickness or height than said second color filter layer, and said second color filter layer is larger in thickness or height than said third color filter layer.
11. A spacer structure over a substrate for a liquid crystal display cell, said spacer structure including:
 - at least a first type spacer having a first height; and
 - at least a second type spacer having a second height which is smaller than said first height.
12. The spacer structure as claimed in claim 11, wherein said first height provides an original cell gap, and a difference between said first and second heights is smaller than an elastic deformation limit of said first spacer, provided that said elastic deformation limit is a transitional compressive deformation amount, over which a compressive deformation is a plastic deformation and under which said compressive deformation is an elastic deformation.
13. The spacer structure as claimed in claim 11, wherein said first height provides an original cell gap, and said second height is larger than a subtraction of an elastic deformation limit of said first spacer from said first height, provided that said elastic deformation limit is a transitional compressive deformation amount, over which a compressive deformation is a plastic deformation and under which said compressive deformation is an elastic deformation.
14. The spacer structure as claimed in claim 11, wherein said first type spacer comprises a first color filter layer over said second substrate, and a first column-shaped spacer over said first color filter layer, and said second type spacer comprises a second color filter layer over said second substrate, and a second column-shaped spacer over said second color filter layer.
15. The spacer structure as claimed in claim 14, wherein said first and second color filter layers have the same thickness or height, while said first column-shaped spacer is larger in height than said second column-shaped spacer.
16. The spacer structure as claimed in claim 14, wherein said first and second column-shaped spacers have the same height, while said first color filter layer is larger in thickness or height than said second color filter layer.
17. The spacer structure as claimed in claim 11, wherein said spacer structure further includes:
 - at least a third type spacer having a third height which is smaller than said second height.
18. The spacer structure as claimed in claim 17, wherein said third type spacer comprises a third color filter layer over said second substrate, and a third column-shaped spacer over said third color filter layer.
19. The spacer structure as claimed in claim 18, wherein said first, second and third color filter layers have the same thickness or height, while said first column-shaped spacer is larger in height than said second column-shaped spacer, and said second column-shaped spacer is larger in height than said third column-shaped spacer.
20. The spacer structure as claimed in claim 18, wherein said first, second and third column-shaped spacers have the same height, while said first color filter layer is larger in height than said second color filter layer, and said second color filter layer is larger in thickness or height than said third color filter layer.

* * * * *

专利名称(译)	具有改进的间隔结构的液晶显示器单元		
公开(公告)号	US20030048403A1	公开(公告)日	2003-03-13
申请号	US10/242604	申请日	2002-09-13
申请(专利权)人(译)	NEC公司		
当前申请(专利权)人(译)	NEC公司		
[标]发明人	SATOH HIROKI		
发明人	SATOH, HIROKI		
IPC分类号	G02F1/1339		
CPC分类号	G02F1/13394 G02F2001/13396		
优先权	2001278590 2001-09-13 JP		
其他公开文献	US6870593		
外部链接	Espacenet USPTO		

摘要(译)

一种液晶显示单元，包括：第一基板；第二基板；介于第一和第二基板之间的液晶层；以及第二基板上的间隔物结构。间隔物结构还包括：至少第一类型间隔物和第二类型间隔物，第一类型间隔物具有第一高度，第二类型间隔物具有小于第一高度的第二高度。

