



US 20050146661A1

(19) **United States**(12) **Patent Application Publication****Song et al.**(10) **Pub. No.: US 2005/0146661 A1**(43) **Pub. Date:****Jul. 7, 2005**(54) **UPPER SUBSTRATE AND LIQUID CRYSTAL
DISPLAY APPARATUS HAVING THE SAME****Publication Classification**(51) **Int. Cl.⁷** **G02F 1/1337**(52) **U.S. Cl.** **349/126**(76) **Inventors:** **Jun-Ho Song**, Seongnam-si (KR);
Yong-Ho Yang, Seoul (KR); **Ji-Hye Moon**, Seoul (KR); **Jin-Suk Park**,
Seoul (KR); **Kyo-Seop Choo**, Suwon-si (KR)(57) **ABSTRACT**

To improve reliability of a liquid crystal display apparatus using an upper substrate, the upper substrate to be combined with a lower substrate includes a transparent electrode and a first spacer. The lower substrate includes a display region and a driving region surrounding the display region to provide a drive signal to the display region. A liquid crystal layer is interposed between the upper substrate and the lower substrate. The first spacer is formed on the transparent electrode corresponding to the driving region to protect the driving region. The first spacer is disposed such that a rubbing having a rubbing direction of the upper substrate does not end at the first spacer. Thus, a corner white phenomenon that is caused by impurities stacked at a side portion of the first spacer may be reduced.

Correspondence Address:

DLA PIPER RUDNICK GRAY CARY US, LLP
2000 UNIVERSITY AVENUE
E. PALO ALTO, CA 94303-2248 (US)

(21) **Appl. No.:** **11/031,122**(22) **Filed:** **Jan. 5, 2005**(30) **Foreign Application Priority Data**

Jan. 6, 2004 (KR) 2004-524




FIG. 1
(PRIOR ART)




FIG.2
(PRIOR ART)




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG.9





FIG.10



UPPER SUBSTRATE AND LIQUID CRYSTAL DISPLAY APPARATUS HAVING THE SAME

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application relies for priority upon Korean Patent Application No. 2004-524 filed on Jan. 6, 2004, the contents of which are herein incorporated by reference in its entirety.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The present invention relates to an upper substrate and a liquid crystal display apparatus having the upper substrate. More particularly, the present invention relates to an upper substrate with improved reliability and a liquid crystal display apparatus having the upper substrate.

[0004] 2. Description of the Related Art

[0005] Generally, liquid crystal display apparatuses are classified into a transmissive type liquid crystal display apparatus, a reflective type liquid crystal display apparatus and a transmissive and reflective type liquid crystal display apparatus according to light sources used for the apparatuses. The transmissive type liquid crystal display apparatus displays an image using a backlight disposed in a rear face of a liquid crystal cell. The reflective type liquid crystal display apparatus uses natural light as the light source. The transmissive and reflective type liquid crystal display apparatus is operated either by a transmissive display mode or by a reflective display mode. An image is displayed using a light source built in the liquid crystal display apparatus in the transmissive display mode under indoor or dark conditions where no external light source exists. When illumination is sufficient, external light is reflected on a reflective electrode in the liquid crystal display apparatus to display the image in the reflective display mode.

[0006] A liquid crystal display apparatus usually controls an arrangement of liquid crystal molecules in accordance with a voltage applied to a liquid crystal layer. The liquid crystal display apparatus is generally classified into a passive matrix type liquid crystal display apparatus and an active matrix type liquid crystal display apparatus according to a method of operation. In the passive matrix type liquid crystal display apparatus, pixels are operated using a root-mean-square value of a voltage difference between a signal line and a scanning line while applying a signal voltage to all the pixels connected to the scanning line. In the active matrix type liquid crystal display apparatus, each pixel is operated by a switching device such as a thin film transistor or a metal-insulator-metal device.

[0007] A process for manufacturing an active matrix type and a transmissive type liquid crystal display apparatus using the thin film transistor includes forming a lower substrate having the thin film transistor and a pixel electrode arranged thereon, forming an upper substrate including a color filter and a common electrode, and forming a liquid crystal layer between the lower and upper substrates.

[0008] FIG. 1 is a plan view illustrating a conventional transmissive and reflective type liquid crystal display apparatus.

[0009] Referring to FIG. 1, the transmissive and reflective type liquid crystal display apparatus operates in a twisted nematic mode in which a first rubbing direction of an upper substrate (or a color filter substrate) 10 is substantially perpendicular to a second rubbing direction of a lower substrate (or a thin film transistor substrate) 20. Conducting a high temperature reliability test at a temperature of about 50 to 60° C. causes inferiority such as a corner white phenomenon. The corner white phenomenon refers to a gray scale changing from medium or black to partially white at a tip of corner of display region DA of the lower substrate 20 along the second rubbing direction.

[0010] In a conventional liquid crystal display apparatus, an aperture ratio is increased by superposing a pixel electrode on the data line and on the gate line using an organic insulation layer having a low dielectric constant. The corner white phenomenon may be generated due to impurities caused by the organic insulation layer formed on the lower substrate 20 during rubbing the lower substrate 20. The corner white phenomenon shown at the tip of the lower substrate 20 along the rubbing direction may be prevented by forming a dummy pixel region near the display region DA, thereby shifting a position of a corner white CW toward the black matrix 30.

[0011] A conventional transmissive and reflective type liquid crystal display apparatus usually has constant cell gaps in the transmissive mode and in the reflective mode. Since the cell gap is determined based on either the transmissive mode or the reflective mode, a significant difference in image characteristics such as color reproduction may be generated due to an optical path difference between the transmitting light and the reflecting light when the apparatus is used. Thus, a liquid crystal display apparatus having a double cell gap has been developed. A thickness of liquid crystal layer in the transmissive mode is thicker than that of liquid crystal layer in the reflective mode to compensate a transmissivity difference between the reflective mode and the transmissive mode.

[0012] Furthermore, technologies of integrating a gate driver circuit and/or a data driver circuit on the lower substrate of the liquid crystal display apparatus have been developed to simplify assembly processes and to reduce size and volume of the liquid crystal display apparatus.

[0013] FIG. 2 is a plan view illustrating a liquid crystal display apparatus having a double cell gap with driver circuits integrated thereon. FIG. 3 is a cross-sectional view taken along a line I-I' of FIG. 2.

[0014] Referring to FIGS. 2 and 3, a lower substrate 60 has a display region DA and a driving region DR. Thin film transistors are formed in the display region DA, and a gate driver circuit 68 and/or a data driver circuit (not shown) that operates the thin film transistors is/are formed in the driving region DR. In FIGS. 2 and 3, the thin film transistors, the pixel electrode and other elements formed in the display region of the lower substrate 60 are represented by a reference numeral 64 and positions thereof are omitted.

[0015] A spacer (not shown) that separates the upper substrate 50 from the lower substrate 60 by a specific distance to maintain a cell gap is formed on a common electrode 55 corresponding to the display region DA of the upper substrate 50. A capping spacer 90 is formed on the

common electrode **55** corresponding to the driving region DR of the upper substrate **50** to improve the reliability of the gate driver circuit **68**.

[0016] Molecules of liquid crystal is homogeneously arranged in the transmissive and reflective type liquid crystal display apparatus having a double cell gap to set a twist angle of the liquid crystal to be zero. To set the twist angle of the liquid crystal to be zero, the upper substrate **50** is rubbed along a first rubbing direction and the lower substrate **60** is preferably rubbed along a second rubbing direction that is anti-parallel to the first rubbing direction.

[0017] A high temperature reliability test conducted at a temperature of about 50 to 60° C. on the transmissive and reflective type liquid crystal display apparatus corresponding to an electrically controlled birefringence mode, in which the first rubbing direction of the upper substrate **50** is anti-parallel with the second rubbing direction of the lower substrate **60**, induces a corner white phenomenon CW1 at the tip of corner of the display region DA along the second rubbing direction as well as a corner white phenomenon CW2 at the tip of corner of the upper substrate **250** along the first rubbing direction.

[0018] The corner white phenomenon CW2 at the tip of corner of the upper substrate **50** along the first rubbing direction is caused by the capping spacer **90** formed on the upper substrate **50**. Impurities 'B' caused by rubbing are stacked at side portion of the capping spacer **90** while the capping spacer **90** that improves the reliability of the gate driver circuit **68** formed on the lower substrate **60** makes contact with the upper substrate **50** along the first rubbing direction. The impurities 'B' cause the corner white phenomenon CW2 to deteriorate the reliability of the liquid crystal display apparatus.

SUMMARY OF THE INVENTION

[0019] Accordingly, the present invention is provided to substantially obviate one or more problems due to limitations and disadvantages of the related art.

[0020] The present invention provides an upper substrate used in a liquid crystal display apparatus with increased reliability.

[0021] The present invention also provides a liquid crystal display apparatus with increased reliability and reduced corner white phenomena.

[0022] In an exemplary upper substrate according to the present invention, the upper substrate to be combined with a lower substrate includes a transparent electrode and a first spacer. The lower substrate includes a display region and a driving region surrounding the display region to provide a drive signal to the display region. A liquid crystal layer is interposed between the upper substrate and the lower substrate. The first spacer is disposed such that a rubbing having a rubbing direction of the upper substrate does not end at the first spacer. The rubbing direction of the upper substrate is substantially perpendicular to a rubbing direction of the lower substrate. Alternatively, the rubbing direction of the upper substrate is opposite to a rubbing direction of the lower substrate.

[0023] In an exemplary liquid crystal display apparatus according to the present invention, the liquid crystal display

apparatus includes a lower substrate, an upper substrate and a liquid crystal layer interposed between the upper substrate and the lower substrate. The lower substrate includes a display region and a driving region. The driving region surrounds the display region to provide a drive signal to the display region. The upper substrate includes a common electrode and a first spacer.

[0024] The first spacer is disposed such that a rubbing having a rubbing direction of the upper substrate does not end at the first spacer.

[0025] In a transmissive and reflective type liquid crystal display apparatus according to the present invention, the transmissive and reflective type liquid crystal display apparatus includes a lower substrate, an upper substrate and a liquid crystal layer interposed between the upper substrate and the lower substrate. The lower substrate includes a display region and a driving region. The display region has a transmission window and a reflection window. The driving region surrounds the display region to provide a drive signal to the display region. The upper substrate includes a common electrode and a first spacer. The first spacer is disposed such that a rubbing having a rubbing direction of the upper substrate does not end at the first spacer.

[0026] According to the present invention, a first spacer is disposed such that a rubbing having a rubbing direction of an upper substrate does not end at the first spacer.

[0027] Thus, a corner white phenomenon that is caused by impurities stacked at side portion of the first spacer in the display region may be reduced, and the reliability of the liquid crystal display apparatus may be increased.

BRIEF DESCRIPTION OF THE DRAWINGS

[0028] The above and other features and advantages of the invention will become more apparent by describing in detailed exemplary embodiments thereof with reference to the accompanying drawings, in which:

[0029] FIG. 1 is a plan view illustrating a conventional transmissive and reflective type liquid crystal display apparatus;

[0030] FIG. 2 is a plan view illustrating a liquid crystal display apparatus having a double cell gap with driver circuits integrated thereon;

[0031] FIG. 3 is a cross-sectional view taken along a line I-I' of FIG. 2;

[0032] FIG. 4 is a plan view illustrating a liquid crystal display apparatus according to an exemplary embodiment of the present invention;

[0033] FIG. 5 is a cross-sectional view taken along a line II-II' of FIG. 4;

[0034] FIG. 6 is a schematic plan view respectively illustrating the upper substrate and the lower substrate shown in FIG. 5;

[0035] FIG. 7 is a plan view illustrating a liquid crystal display apparatus according to another exemplary embodiment of the present invention;

[0036] FIG. 8 is a plan view illustrating a liquid crystal display apparatus according to still another exemplary embodiment of the present invention;

[0037] FIG. 9 is a plan view illustrating a liquid crystal display apparatus according to still another exemplary embodiment of the present invention; and

[0038] FIG. 10 is a plan view illustrating a liquid crystal display apparatus according to still another exemplary embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0039] Hereinafter, the preferred embodiment of the invention will be described in detail with reference to the accompanying drawings.

[0040] FIG. 4 is a plan view illustrating a liquid crystal display apparatus according to an exemplary embodiment of the present invention. FIG. 5 is a cross-sectional view taken along a line II-II' of FIG. 4. FIG. 6 is a schematic plan view respectively illustrating the upper substrate and the lower substrate shown in FIG. 5.

[0041] Referring to FIGS. 4 to 6, the liquid crystal display apparatus includes an upper substrate 100, a lower substrate 200 and a liquid crystal layer 300 interposed between the upper substrate 100 and the lower substrate 200. A display region DA and a driving region DR are defined on the lower substrate 200. The driving region DR surrounds the display region DA, and provides a drive signal to the display region DA.

[0042] The upper substrate 100 includes a first insulation plate 110, a color filter 120, a black matrix 130 and a common electrode 140.

[0043] Each color filter 120 has a red, green or blue color pixel. Each color pixel shows a red, green or blue color by light. The black matrix 130 distinguishes each color pixel. The black matrix 130 prevents a light leakage occurring at near boundaries of color pixels. The black matrix 130 also blocks unnecessary light from another region other than the display region DA. The common electrode 140 includes a transparent material such as indium tin oxide (ITO), indium zinc oxide (IZO), etc.

[0044] The lower substrate 200 includes a second insulation plate 210, a plurality of pixels 225, a gate driver circuit 230 and a data driver circuit 250. The pixels 225 are formed in the display region DA in a shape of matrix, and the gate driver circuit 230 and the data driver circuit 250 are formed in the driving region DR.

[0045] Each of the pixels 225 includes a gate line 231, a data line 251 that is substantially perpendicular to the gate line 231, a thin film transistor 220 connected to the gate line 231 and the data line 251 as a switching device, and a pixel electrode 240 connected to the thin film transistor 220.

[0046] A gate electrode 221 of the thin film transistor 220 is connected to the gate line 231, and a source electrode 222 of the thin film transistor 220 is connected to the data line 251. A drain electrode 223 of the thin film transistor 220 is connected to the pixel electrode 240.

[0047] When electrical signals are externally provided to the gate driver circuit 230 and the data driver circuit 250, the gate driver circuit 230 sequentially applies a gate driving voltage that is suitable for driving the thin film transistor 220 to each of the gate lines 231. When the gate driving voltage

sequentially drives each of the thin film transistors 220, an image signal outputted from the data driver circuit 250 is provided to the data line 251. The image signal is then provided to the pixel electrode 240 connected to the thin film transistor 220 driven by the gate driving voltage. Accordingly, an electric field is generated between the common electrode 140 on the upper substrate 100 and the pixel electrode 240 on the lower substrate 200.

[0048] A member that maintains a cell gap (hereinafter, referred to as spacers) is formed between the upper substrate 100 and the lower substrate 200.

[0049] The spacers maintain the cell gap to prevent the liquid crystal between the upper and lower substrates 100 and 200 from deformation in shape and property. In addition, the spacers prevent deterioration of the display quality of the liquid crystal display apparatus. The spacers are preferably formed on a position corresponding to a non-effective display region so that the aperture ratio that indicates an effective display region/total region is not affected. In this embodiment, the non-effective display region corresponds to the driving region DR as well as a region having the thin film transistor 220, the gate line 231 and the data line 251.

[0050] The spacers are classified into a ball spacer and a rigid spacer. The ball spacer has a shape of ball, and a plurality of the ball spacers is scattered on the upper substrate 100 or the lower substrate 200. The rigid spacer is formed by forming an organic layer on the upper substrate 100 or the lower substrate 200 and then patterning the organic layer.

[0051] Since the ball spacers tend to be randomly scattered, the ball spacers may be formed on an effective display region of the liquid crystal display apparatus, thereby reducing the aperture ratio. The ball spacer also has an irregular size, thereby failing in maintaining a constant cell gap.

[0052] The rigid spacer is formed on the non-effective display region by selectively removing the organic layer on the other region other than the non-effective display region. In addition, use of the rigid spacer may not decrease the aperture ratio while maintaining a constant cell gap.

[0053] In the present embodiment, spacers include a first spacer 150 and a second spacer 152. The first spacer 150 is formed on the common electrode 140 of the upper substrate 100 corresponding to the driving region DR. The second spacer 152 is formed on a region corresponding to the non-effective display region in the display region DA. The second spacer 152 is formed from a layer forming the first spacer. The second spacer 152 maintains a distance between the upper substrate 100 and the lower substrate 200.

[0054] When only the second spacer 152 is formed, a parasitic capacitance may be generated between the gate driver circuit 230 and the common electrode 140. Hence, the signal outputted from the gate driver circuit 230 is possibly distorted or delayed to deteriorate the display quality of the liquid crystal display apparatus. Additionally, when an external impact is applied to the liquid crystal display apparatus, the common electrode 140 formed on the upper substrate 100 may be contacted with the gate driver circuit 230 formed on the lower substrate 200 to cause an electrical short between the upper substrate 100 and the lower substrate 200. The first spacer 150 formed on a position corresponding to the driving region DR may protect the gate driver circuit 230

from the external impact. Moreover, the parasitic capacitance between the common electrode **140** and the gate driver circuit **230** may be reduced to improve the reliability of the gate driver circuit **230**.

[0055] The first spacer **150** preferably has a bar-shape that corresponds to the shape of the gate driver circuit **230**. The second spacer **152** is formed in a bar-shape that corresponds to the black matrix **130** formed on the display region DA of the upper substrate **100**. Alternatively, the first and second spacers **150** and **152** may have a dot shape such as cylinder, rectangular prism or triangular prism.

[0056] In this embodiment, the position of the first spacer **150** is controlled so that a rubbing having the first rubbing direction of the upper substrate **100** does not end at the first spacer **150**.

[0057] The first rubbing direction that corresponds to the rubbing direction of the upper substrate **100** is required to be substantially perpendicular to the second rubbing direction that corresponds to the rubbing direction of the lower substrate **200** in order to arrange the liquid crystal to have a twist angle. The first spacer **150** is preferably disposed on a left side of the upper substrate **100** in a plan view thereof such that the rubbing having the first rubbing direction of the upper substrate **100** does not end at the first spacer **150**. When the rubbing having the first rubbing direction of the upper substrate **100** ends at the first spacer **150**, impurities caused by the rubbing may be stacked at the side portion of the first spacer **150** toward the black matrix **130**. Thus, when the rubbing having the first rubbing direction of the upper substrate **100** does not end at the first spacer **150**, the impurities may not be stacked at the side portion of the first spacer **150** toward the display region DA, thereby preventing the corner white phenomenon.

[0058] Hereinafter, processes of manufacturing the above described upper substrate **100** and the lower substrate **200** will be described in detail.

[0059] A first photoresist layer (not shown) including a red pigment or dye is coated on a first insulation plate **110**. A first mask (not shown) is disposed over the first photoresist layer. The first mask has patterns corresponding to a shape of a red color pixel on the first insulation plate **110**.

[0060] The first photoresist layer is exposed and then developed to remove the exposed photoresist layer.

[0061] A second photoresist layer (not shown) including a green pigment or dye is coated on a region other than the region having the red color pixel of the first insulation plate **110**. A procedure of preparing the red color pixel is repeated to form a green color pixel. A third photoresist layer (not shown) including a blue pigment or dye is coated on a region other than the region having the red color pixel and the green color pixel of the first insulation plate **110**. A procedure of preparing the red color pixel or the green color pixel is repeated to form a blue color pixel. As a result, a color filter **120** having red, green and blue color pixels is formed on the first insulation plate **110**.

[0062] A black matrix **130** is formed on the first insulation plate **110** having the color filter **120** formed thereon. The black matrix **130** is formed between two of the red, green and blue color pixels. The black matrix **130** blocks light leaked from the red, green and blue color pixels to improve

a contrast ratio. The black matrix **130** is formed in the driving region DR as well as in the display region DA to prevent the gate driver circuit **230** and the data driver circuit **250** from being projected in a screen of the liquid crystal display apparatus. The black matrix **130** includes chromium oxide or an organic material.

[0063] The common electrode **140** including ITO or IZO is formed on the first insulation plate **110** having the color filter **120** and the black matrix **130** formed thereon. An organic layer is then formed on the first insulation plate **110** having the common electrode **140**.

[0064] A second mask (not shown) having patterns corresponding to a shape of a second spacer **152** is disposed over the organic layer. The organic layer is exposed and then developed to form a first spacer **150** in the driving region DR, and the second spacer **152** in the display region DA. The first spacer **150** preferably has a height less than that of the second spacer **152**, wherein the height is measured from the bottom of the first insulation plate **110**.

[0065] A plurality of pixels **225** including a thin film transistor **220** and a pixel electrode **240** is formed in the display region DA of the lower substrate **200**. During a formation of the thin film transistor **220**, a plurality of gate lines **231** is formed along a row direction, and a plurality of data lines **251** is formed along a column direction. A gate driver circuit **230** and a data driver circuit **250** are formed in the driving region DA to drive the thin film transistor **220** during the formation of the thin film transistor **220**.

[0066] An organic insulation layer (not shown) is formed on the second insulation plate **210** having the thin film transistor **220**, the gate driver circuit **230** and the data driver circuit **250** formed thereon. The organic insulation layer formed on a position corresponding to a drain electrode **223** is removed to form a contact hole (not shown). A transparent conductive layer including ITO or IZO and a reflective layer including chromium (Cr), molybdenum (Mo), aluminum neodymium (AlNd), copper (Cu) or alloys thereof are sequentially formed on the organic insulation layer and in the contact hole. The transparent conductive layer and the reflective layer are patterned by a photolithography process to form a pixel electrode **240** that is electrically connected to the drain electrode **223** of the thin film transistor **220** through the contact hole. The pixel electrode **240** includes a transparent electrode and a reflective electrode. Portions of the reflective electrode are superposed on the transparent electrode to form a transmission window and a reflection window.

[0067] The upper substrate **100** is combined with the lower substrate **200** so that the common electrode **140** faces to the pixel electrode **240**. In particular, a sealant is formed near the display region DA to firmly combine the upper substrate **100** with the lower substrate **200**.

[0068] The first spacer **150** formed on the upper substrate **100** protects the gate driver circuit **230** formed on the lower substrate **200**. The second spacer **152** is contacted with the lower substrate **200** to maintain the cell gap between the upper substrate **100** and the lower substrate **200**.

[0069] Liquid crystal is interposed between the upper and lower substrates **100** and **200** to form a liquid crystal layer **300**, thereby completing a liquid crystal display apparatus.

[0070] FIG. 7 is a plan view illustrating a liquid crystal display apparatus according to another exemplary embodiment of the present invention. Directions in this embodiment will be described in the plan view.

[0071] Referring to FIG. 7, when a transmissive and reflective type liquid crystal display apparatus employs a homogenous liquid crystal alignment mode instead of a twisted liquid crystal alignment mode to improve transmissivity, a cell gap in the reflection region is preferably different from the cell gap in the transmitting region. Accordingly, in the homogenous liquid crystal alignment mode, the liquid crystal layer between the upper and lower substrates 100 and 200 in the reflection region preferably has a thickness different from that of the transmitting region.

[0072] The upper substrate 100 is preferably rubbed along a first rubbing direction and the lower substrate 200 is preferably rubbed along a second rubbing direction that is opposite to the first rubbing direction to set a twisted angle at zero.

[0073] When the upper substrate 100 is rubbed along a first rubbing direction that corresponds to a four o'clock direction and the lower substrate 200 is rubbed along a ten o'clock direction that is opposite to the first rubbing direction, the first spacer 150 that is to be formed on the upper substrate 100 corresponding to the driving region DR of the lower substrate 200 is placed on a left side of the upper substrate 100 so that a rubbing having the first rubbing direction of the upper substrate 100 does not end at the first spacer 150. Thus, impurities may not be stacked at a side portion of the first spacer 150 toward the display region DA to prevent a corner white phenomenon,

[0074] FIG. 8 is a plan view illustrating a liquid crystal display apparatus according to still another exemplary embodiment of the present invention. Directions in this embodiment will be described in terms of the plan view.

[0075] Referring to FIG. 8, the upper substrate 100 is rubbed along a first rubbing direction, and the lower substrate 200 is rubbed along a second rubbing direction that is opposite to the first rubbing direction to set the twist angle of liquid crystal at zero in a transmissive and reflective type liquid crystal display apparatus having a double cell gap. To reduce a rubbing effect, it is advantageous to employ a viewing angle in a twelve o'clock direction or six o'clock direction.

[0076] For example, when the lower substrate 200 is rubbed along the second rubbing direction that is a twelve o'clock direction, and the upper substrate 100 is rubbed along the first rubbing direction that is a six o'clock direction opposite to the second rubbing direction, a rubbing having the first rubbing direction of the upper substrate 100 does not end at the first spacer 150 on the upper substrate 100 corresponding to the driving region DA of the lower substrate. Therefore, the spacer 150 may be placed at any position on the upper substrate 100.

[0077] FIG. 9 is a plan view illustrating a liquid crystal display apparatus according to still another exemplary embodiment of the present invention. Directions in this embodiment will be described in terms of the plan view.

[0078] Referring to FIG. 9, the lower substrate 200 is rubbed along a second rubbing direction that is a three

o'clock direction, and the upper substrate 100 is rubbed along a first rubbing direction that is a nine o'clock direction, to set a main viewing angle in a three o'clock direction. The first spacer 150 corresponding to the position of the driving region DA of the lower substrate 200 is disposed on a right side of the upper substrate 100 such that a rubbing having the first rubbing direction of the upper substrate 100 does not end at the first spacer 150.

[0079] Since the rubbing having the first rubbing direction of the upper substrate 100 is performed as in contact with the first spacer 150 toward the black matrix 130, impurities caused by the rubbing may be stacked at the side portion of the first spacer 150 toward the black matrix 130, for example at the right side in the plan view. The impurities are not stacked at the left side portion of the first spacer 150 toward the display region DA, thereby preventing the corner white phenomenon.

[0080] FIG. 10 is a plan view illustrating a liquid crystal display apparatus according to still another exemplary embodiment of the present invention. Directions in this embodiment will be described in terms of the plan view.

[0081] Referring to FIG. 10, the lower substrate 200 is rubbed along a second rubbing direction that is a nine o'clock direction, and the upper substrate 100 is rubbed along a first rubbing direction that is a three o'clock direction, to set a main viewing angle in a nine o'clock direction. The first spacer 150 corresponding to the position of the driving region DA of the lower substrate 200 is disposed on a left side of the upper substrate 100 so that a rubbing having the first rubbing direction of the upper substrate 100 does not end at the first spacer 150.

[0082] Since the rubbing having the first rubbing direction of the upper substrate 100 is performed as in contact with the first spacer 150 toward the black matrix 130, impurities caused by the rubbing may be stacked at the side portion of the first spacer 150 toward the black matrix 130, for example at a left side in the plan view. The impurities are not stacked at a right side portion of the first spacer 150 toward the display region DA, thereby preventing the corner white phenomenon.

[0083] As described above, the first spacer 150 is disposed on the upper substrate 100 so that the rubbing having the first rubbing direction of the upper substrate 100 does not end at the first spacer 150.

[0084] Thus, a corner white phenomenon that is caused by impurities stacked at the side portion of the first spacer in the display region DA may be reduced, and the reliability of the liquid crystal display apparatus may be increased.

[0085] Having described the exemplary embodiments of the invention and its advantages, it is noted that various changes, substitutions and alterations can be made herein without departing from the spirit and scope of the invention as defined by appended claims.

What is claimed is:

1. An upper substrate to be combined with a lower substrate including a display region and a driving region surrounding the display region to provide a drive signal to the display region, a liquid crystal layer being interposed between the upper substrate and the lower substrate, comprising:

- a transparent electrode; and
- a first spacer disposed such that a rubbing having a rubbing direction of the upper substrate does not end at the first spacer.
- 2. The upper substrate of claim 1, wherein the first spacer is formed on the transparent electrode corresponding to the driving region.
- 3. The upper substrate of claim 1, wherein the first spacer has a bar-shape.
- 4. The upper substrate of claim 1, further comprising a second spacer formed on the transparent electrode corresponding to the display region to maintain a distance between the upper substrate and the lower substrate, the first and second spacers being formed by patterning a same layer.
- 5. The upper substrate of claim 1, wherein the rubbing direction of the upper substrate is substantially perpendicular to a rubbing direction of the lower substrate.
- 6. The upper substrate of claim 1, wherein the rubbing direction of the upper substrate is opposite to the rubbing direction of the lower substrate.
- 7. A liquid crystal display apparatus comprising:
 - a lower substrate including a display region and a driving region that surrounds the display region to provide a drive signal to the display region;
 - an upper substrate including a common electrode and a first spacer disposed such that a rubbing having a rubbing direction of the upper substrate does not end at the first spacer; and
 - a liquid crystal layer interposed between the upper substrate and the lower substrate.
- 8. The liquid crystal display apparatus of claim 7, wherein the first spacer is formed on the common electrode corresponding to the driving region.
- 9. The liquid crystal display apparatus of claim 7, wherein the first spacer has a bar-shape.
- 10. The liquid crystal display apparatus of claim 7, further comprising a second spacer formed on a transparent electrode corresponding to the display region to maintain a distance between the upper substrate and the lower substrate, the first and second spacers being formed by patterning a same layer.
- 11. The liquid crystal display apparatus of claim 7, wherein the rubbing direction of the upper substrate is substantially perpendicular to a rubbing direction of the lower substrate.
- 12. The liquid crystal display apparatus of claim 7, wherein the rubbing direction of the upper substrate is opposite to the rubbing direction of the lower substrate.
- 13. The liquid crystal display apparatus of claim 7, wherein when the rubbing direction of the lower substrate corresponds to a twelve o'clock or six o'clock direction and the rubbing direction of the upper substrate is opposite to the rubbing direction of the lower substrate, the first spacer is disposed at a right or left side in the display region of the upper substrate.
- 14. The liquid crystal display apparatus of claim 7, wherein the lower substrate comprises:
 - a gate line;
 - a data line that is substantially perpendicular to the gate line;

a switching device connected to the gate line and the data line;

a pixel electrode connected to the switching device.

15. The liquid crystal display apparatus of claim 14, wherein the pixel electrode includes a transparent electrode and a reflective electrode, the reflective electrode being superposed on the transparent electrode to form a transmission window and a reflection window.

16. The liquid crystal display apparatus of claim 15, wherein the liquid crystal layer has a different thickness on the transmission window and on the reflection window, respectively.

17. A transmissive and reflective type liquid crystal display apparatus comprising:

a lower substrate including a display region that has a transmission window and a reflection window, and a driving region that surrounds the display region to provide a drive signal to the display region;

an upper substrate including a common electrode and a first spacer that is disposed such that a rubbing having a rubbing direction of the upper substrate does not end at the first spacer; and

a liquid crystal layer interposed between the upper substrate and the lower substrate.

18. The transmissive and reflective type liquid crystal display apparatus of claim 17, wherein the first spacer is formed on the common electrode corresponding to the driving region.

19. The transmissive and reflective type liquid crystal display apparatus of claim 17, wherein the first spacer has a bar-shape.

20. The transmissive and reflective type liquid crystal display apparatus of claim 17, further comprising a second spacer formed on a transparent electrode corresponding to the display region to maintain a distance between the upper substrate and the lower substrate, the first and second spacers being formed by patterning a same layer.

21. The transmissive and reflective type liquid crystal display apparatus of claim 17, wherein the rubbing direction of the upper substrate is substantially perpendicular to a rubbing direction of the lower substrate.

22. The transmissive and reflective type liquid crystal display apparatus of claim 17, wherein the rubbing direction of the upper substrate is opposite to the rubbing direction of the lower substrate.

23. The transmissive and reflective type liquid crystal display apparatus of claim 17, wherein when the rubbing direction of the lower substrate corresponds to a twelve o'clock or six o'clock direction and the rubbing direction of the upper substrate is opposite to the rubbing direction of the lower substrate, the first spacer is disposed at a right or left side in the display region of the upper substrate.

24. The transmissive and reflective type liquid crystal display apparatus of claim 17, wherein the liquid crystal layer has a different thickness on the transmission window and on the reflection window, respectively.

专利名称(译)	上基板和具有该上基板的液晶显示装置		
公开(公告)号	US20050146661A1	公开(公告)日	2005-07-07
申请号	US11/031122	申请日	2005-01-05
[标]申请(专利权)人(译)	宋军HO 杨勇HO MOON JI HYE 朴真SUK CHOO京燮		
申请(专利权)人(译)	宋军-HO 杨永HO MOON JI-HYE 公园jin-suk CHOO京燮		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	SONG JUN HO YANG YONG HO MOON JI HYE PARK JIN SUK CHOO KYO SEOP		
发明人	SONG, JUN-HO YANG, YONG-HO MOON, JI-HYE PARK, JIN-SUK CHOO, KYO-SEOP		
IPC分类号	G02F1/1339 G02F1/1335 G02F1/1337 G02F1/1368		
CPC分类号	G02F1/13394 G02F1/133784		
优先权	1020040000524 2004-01-06 KR		
其他公开文献	US7746441		
外部链接	Espacenet USPTO		

摘要(译)

为了提高使用上基板的液晶显示装置的可靠性，。与下基板组合的上基板包括透明电极和第一间隔物。下基板包括显示区域和围绕显示区域的驱动区域，以向显示区域提供驱动信号。液晶层介于上基板和下基板之间。第一间隔物形成在对应于驱动区域的透明电极上，以保护驱动区域。设置第一间隔物使得具有上基板的摩擦方向的摩擦不在第一间隔物处终止。因此，可以减少由堆叠在第一间隔物的侧部的杂质引起的角白现象。

