



US008013951B2

(12) **United States Patent**
Hsu et al.

(10) **Patent No.:** **US 8,013,951 B2**
(45) **Date of Patent:** **Sep. 6, 2011**

(54) **MULTI-VIEW LIQUID CRYSTAL DISPLAY
AND THE DRIVING METHOD THEREOF**

(75) Inventors: **Shih-Chia Hsu**, Kaohsiung (TW);
Chih-Jen Hu, Hsinchu (TW)

(73) Assignee: **Au Optonics Corporation**, Hsinchu
(TW)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 243 days.

(21) Appl. No.: **12/220,860**

(22) Filed: **Jul. 28, 2008**

(65) **Prior Publication Data**
US 2009/0251638 A1 Oct. 8, 2009

(30) **Foreign Application Priority Data**
Apr. 8, 2008 (TW) 97112689 A

(51) **Int. Cl.**
G02F 1/1335 (2006.01)

(52) **U.S. Cl.** **349/68; 349/61**

(58) **Field of Classification Search** None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,357,277	A *	10/1994	Nakayoshi et al.	348/55
5,956,107	A	9/1999	Hashimoto et al.	
6,115,058	A *	9/2000	Omori et al.	348/45
6,496,236	B1 *	12/2002	Cole et al.	349/61
7,671,935	B2 *	3/2010	Mather et al.	349/65

2003/0210540	A1 *	11/2003	Yamada et al.	362/31
2004/0183960	A1 *	9/2004	Kim et al.	349/61
2006/0132474	A1 *	6/2006	Lam	345/204
2006/0164862	A1 *	7/2006	Chien et al.	362/619
2007/0058127	A1	3/2007	Mather et al.	
2007/0081111	A1 *	4/2007	Chang et al.	349/62
2007/0206137	A1 *	9/2007	Akiyama	349/113
2008/0218657	A1 *	9/2008	Hwang et al.	349/62

FOREIGN PATENT DOCUMENTS

CN	1973239	5/2007
TW	I263845	10/2006

* cited by examiner


Primary Examiner — Tina M Wong

(74) *Attorney, Agent, or Firm* — J.C. Patents

(57) **ABSTRACT**

A multi-view liquid crystal display for different users to watch different images from different viewing angles is provided. The multi-view liquid crystal display includes a liquid crystal display panel, a first backlight module and a second backlight module. The first backlight module is disposed below the liquid crystal display panel. The second backlight module is disposed between the first backlight module and the liquid crystal display panel. Furthermore, the first backlight module provides a first plane light source and the second backlight module provides a second plane light source. An included angle α formed between transmitting directions of the first and the second plane light sources ranges from 6 degrees to 176 degrees. Therefore, when different users watch the multi-view liquid crystal display which displays different images from different viewing angles, the resolutions of the images are the same as the resolution of the multi-view liquid crystal display panel.

12 Claims, 3 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4



FIG. 5c



FIG. 5b




FIG. 5a

MULTI-VIEW LIQUID CRYSTAL DISPLAY AND THE DRIVING METHOD THEREOF

CROSS-REFERENCE TO RELATED APPLICATION

This application claims the priority benefit of Taiwan application serial no. 97112689, filed on Apr. 8, 2008. The entirety of the above-mentioned patent application is hereby incorporated by reference herein and made a part of specification.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a liquid crystal display and a driving method thereof, and particularly relates to a multi-view liquid crystal display and a driving method thereof.

2. Description of Related Art

With the advancement of technology, display devices have helped increase the convenience of modern life. Flat Panel Displays (FPDs) are the main stream for its lightness and thinness, with Liquid Crystal Display (LCD) being the most popular. However, in order for users to be able to view display images of the display devices from different viewing angles, a multi-view LCD is developed.

In general, the multi-view LCD is achieved by disposing a barrier, a lenticular plate, or a prism. The multi-view effect can be achieved by disposing the barrier on the exterior of an upper polarizing plate and using the barrier to control transmitting directions of backlight sources. Also, the multi-view effect can be achieved by disposing the lenticular plate or the prism in a backlight module and using the lenticular plate or the prism to control transmitting directions of backlight sources. It matters not which of the barrier, the lenticular plate, or the prism is used to control the transmitting directions of the backlight sources, users will only see images whose resolution is only half of that of the LCD panel. The images that users see are not good enough.

SUMMARY OF THE INVENTION

The present invention provides a multi-view LCD which enables different users to view different images from different viewing angles. The resolutions of these images are the same as the real resolution of the LCD panel of the multi-view LCD.

The present invention provides a driving method suitable for driving a multi-view LCD. The driving method ensures that the resolutions of the images displayed by the multi-view LCD from various viewing angles do not decrease.

The present invention provides a driving method for a multi-view LCD suitable for driving a multi-view LCD. The method ensures that the resolutions of the images displayed by the multi-view LCD from different viewing angles are the same and the resolutions of these images do not decrease.

The present invention provides a multi-view LCD enabling different users to view different images from different viewing angles. The multi-view LCD comprises an LCD panel, a first backlight module, and a second backlight module. The first backlight module is disposed below the LCD panel. The second backlight module is disposed between the first backlight module and the LCD panel. Furthermore, the first backlight module provides a first plane light source and the second backlight module provides a second plane light source. An

included angle α formed between the transmitting directions of the first and the second plane light sources ranges from 6 degrees to 176 degrees.

In one embodiment of the present invention, the above LCD panel comprises a transmissive LCD panel or a trans-
flective LCD panel.

In one embodiment of the present invention, the above first backlight module or the second backlight module comprises a direct type backlight module or an edge type backlight module.

In one embodiment of the present invention, the above LCD panel comprises a normal vector. The transmitting direction of the first plane light source forms an included angle α_1 with the normal vector, and the transmitting direction of the second plane light source forms an included angle α_2 with the normal vector.

In one embodiment of the present invention, $\alpha_1 = \alpha_2$ and, α_1 and α_2 are approximately in the range from 3 degrees to 88 degrees. In another embodiment, $\alpha_1 \neq \alpha_2$ and, α_1 and α_2 are approximately in the range from 3 degrees to 88 degrees.

In one embodiment of the present invention, a normal vector, a transmitting direction of a first plane light source, and a transmitting direction of a second plane light source are on the same plane.

The present invention provides another multi-view LCD which comprises an LCD panel, a first backlight module, and a second backlight module. The first backlight module is disposed below the LCD panel. The second backlight module is disposed between the first backlight module and the LCD panel. Furthermore, the first backlight module provides a first plane light source and the second backlight module provides a second plane light source to the LCD panel to respectively display a first program image and a second program image independent from the first program image at the same time.

In one embodiment of the present invention, an included angle α formed between the transmitting directions of the first and the second plane light sources ranges from 6 degrees to 176 degrees. In one embodiment of the present invention, a first backlight module and a second backlight module are turned on alternately.

In one embodiment of the present invention, an LCD panel has a normal vector. A transmitting direction of a first plane light source forms an included angle α_1 with the normal vector, and a transmitting direction of a second plane light source forms an included angle α_2 with the normal vector. In one embodiment of the present invention, $\alpha_1 = \alpha_2$ and, α_1 and α_2 are approximately in the range from 3 degrees to 88 degrees. In another embodiment, $\alpha_1 \neq \alpha_2$ and, α_1 and α_2 are approximately in the range from 3 degrees to 88 degrees.

The present invention provides a driving method suitable for driving a multi-view LCD which enables different users to view different images from different viewing angles. The multi-view LCD comprises an LCD panel, a first backlight module, and a second backlight module. The first backlight module is disposed below the LCD panel. The second backlight module is disposed between the first backlight module and the LCD panel. Furthermore, the first backlight module provides a first plane light source and the second backlight module provides a second plane light source. An included angle α formed between the transmitting directions of the first and the second plane light sources ranges from 6 degrees to 176 degrees. In addition, the driving method comprises alternately turning on the first backlight module and the second backlight module and alternately displaying a first program image and a second program image through the LCD panel. The turn-on time of the first backlight module corresponds to the time when the first program image is provided and the

turn-on time of the second backlight module corresponds to the time when the second program image is provided.

In one embodiment of the present invention, a brightness of a first plane light source provided by a first backlight module is substantially equal to a brightness of a second plane light source provided by a second backlight module. In another embodiment, a brightness of a first plane light source provided by a first backlight module is not equal to a brightness of a second plane light source provided by a second backlight module.

In one embodiment of the present invention, the turn-on time of the first backlight module and the turn-on time of the second backlight module are substantially the same in the same frame time in the above driving method.

The present invention provides a method for driving a multi-view LCD. The multi-view LCD comprises an LCD panel, a first backlight module, and a second backlight module. The first backlight module is disposed below the LCD panel. The second backlight module is disposed between the first backlight module and the LCD panel. Furthermore, the first backlight module provides a first plane light source and the second backlight module provides a second plane light source to the LCD panel. Furthermore, the driving method for driving the multi-view LCD comprises providing the multi-view LCD, alternately turning on the first backlight module and the second backlight module, and alternately displaying a first program image and a second program image through the LCD panel. The first program image and the second program image are completely independent from each other at the same time.

In one embodiment of the present invention, a brightness of a first plane light source provided by a first backlight module is substantially equal to that of a second plane light source provided by a second backlight module. In another embodiment, a brightness of a first plane light source provided by a first backlight module is not equal to that of a second plane light source provided by a second backlight module.

In one embodiment of the present invention, a time difference between a turn-on time of a first backlight module and a turn-off time of a second backlight module within a frame time that a first program image and a second program image overlap is larger than about 0 ms and smaller than or equal to about 8.3 ms. In another embodiment, a time difference between a turn-on time of a first backlight module and a turn-off time of a second backlight module is larger than about 0 ms and smaller than or equal to about 1 ms.

The multi-view LCD display of the present invention uses a structure comprising a first backlight module, a second backlight module, and an LCD panel to alternately display a first program image and a second program image such that when the first backlight module is turned on, the LCD panel displays the first program image and when the second backlight module is turned on, the LCD panel displays the second program image. Thus, the resolutions of images that different users see from different viewing angles are the same as the real resolution of the multi-view LCD display.

In order to make the aforementioned and other objects, features and advantages of the present invention more comprehensible, several embodiments accompanied with figures are described in detail below.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings are included to provide a further understanding of the invention, and are incorporated in and constitute a part of this specification. The drawings

illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention.

FIG. 1 is a structural view of a multi-view LCD according to one embodiment of the present invention.

FIG. 2 is a schematic view of the multi-view LCD in FIG. 1.

FIG. 3 is a waveform diagram of image signals received by an LCD panel of a multi-view LCD in one embodiment of the present invention.

FIG. 4 is a flow chart illustrating a driving method according to another embodiment of the present invention.

FIG. 5a is an image picture viewed from a left side of an LCD panel from a non-right angle in one embodiment of the present invention.

FIG. 5b is an image picture viewed from a right angle to an LCD panel in one embodiment of the present invention.

FIG. 5c is an image picture viewed from a right side of an LCD panel from a non-right angle in one embodiment of the present invention.

DESCRIPTION OF EMBODIMENTS

FIG. 1 is a structural view of a multi-view LCD according to one embodiment of the present invention. Referring to FIG. 1, the present invention provides a multi-view LCD 100 which enables different users to view different images from different viewing angles. As shown in FIG. 1, the multi-view LCD 100 comprises an LCD panel 102, a first backlight module 104, and a second backlight module 106. The first backlight module 104 is disposed below the LCD panel 102. The second backlight module 106 is disposed between the first backlight module 104 and the LCD panel 102.

FIG. 2 is a schematic view of the multi-view LCD in FIG. 1. Referring to FIG. 2, a multi-view LCD 200 comprises an LCD panel 202, a first backlight module 204, and a second backlight module 206. In general, the LCD panel 202 relies on the first backlight module 204 and the second backlight module 206 to provide the main backlight source. Therefore, the LCD panel 202 at least has transmissive pixels. For example, the LCD panel 202 may be a transmissive LCD panel or a transreflective LCD panel. In the present embodiment, the first backlight module 204 and the second backlight module 206 are both edge type backlight modules and the LCD panel 202 is a transmissive LCD panel, for example. The first backlight module 204 comprises a first light source LS1 and a first light conducting substrate (not shown). The second backlight module 206 comprises a second light source LS2 and a second light conducting substrate (not shown).

Specifically, FIG. 5a-FIG. 5c are display images on the LCD panel from three viewing angles in one embodiment of the present invention. When the first backlight module 204 is turned on, the second backlight module 206 is off. At this time, only the first light source LS1 forms a first plane light source L1 through the light conducting substrate (not shown) in the first backlight module 204. Thus, the first backlight module 204 may provide the first plane light source L1 to the LCD panel 202. At the same time, the LCD panel 202 provides a first program image I1 which is navigation information as shown in FIG. 5c, for example. This view is from the right side of the LCD panel 202 in a non-right angle and is the view from the position of the user P1.

For the same reason, when the second backlight module 206 is on and the first backlight module 204 is off, the second light source LS2 forms a second plane light source L2 through the light conducting substrate (not shown) in the second backlight module 206. Thus, the second backlight module 206 may provide the second plane light source L2 to the LCD

panel **202**. At the same time, the LCD panel **202** provides a second program image **I2** which is a cartoon program as shown in FIG. **5a**, for example. This view is from the left side of the LCD panel **202** in a non-right angle and is the view from the position of the user **P2**.

It should be noted that FIG. **5b** is a view of the LCD panel from a right angle and is an overlapping image of the views from the right and left sides of the LCD panel by the users **P1** and **P2**.

In light of the above, the user **P1** is on the transmitting direction of the first light plane light source **L1** so the user **P1** sees that the image displayed on the multi-view LCD **200** is the first program image **I1**. Similarly, when the user **P2** is on the transmitting direction of the second light plane light source **L2**, the user **P2** sees the second program image **I2**. It should be noted that the transmitting directions of the first plane light source **L1** and the second plane light source **L2** form an included angle α where α ranges from 6 degrees to 176 degrees.

Referring to FIG. **2**, the first backlight module **204** and the second backlight module **206** provide a first plane light source **L1** and a second plane light source **L2**, respectively, to the LCD panel **202**. Therefore, the LCD panel **202** may display the first program image **I1** and the second program image **I2** which is independent from the first program image **I1** at the same time. In other words, the first program image **I1** viewed by the user **P1** and the second program image **I2** viewed by the user **P2** are completely different and not related.

If the multi-view LCD **200** in the present embodiment is used in a system inside an automobile, from the position of the driver (i.e. the user **P1**), the first program image **I1** (i.e. navigation information) may be viewed. When the automobile is on the road, it may reach its destination according to the content of the first program image **I1** while from the position of the passenger (i.e. the user **P2**), the second program image **I2** (i.e. cartoon or other entertainment programs) may be viewed. Furthermore, the contents of the first program image **I1** and the second program image **I2** may be adjusted accordingly. In other words, the second program image **I2** may be navigation information. The present invention is not limited hereby.

What is more special is that when the user **P1** and the user **P2** view images that are the first program image **I1** and the second program image **I2**, respectively, the resolutions of the first program image **I1** and the second program image **I2** are the same as the resolution of the LCD panel **202**.

In addition, the distance between the first backlight module **204** and the LCD panel **202** is longer than the distance between the second backlight module **206** and the LCD panel **202** so if the brightness of the first light source **LS1** is the same as the brightness of the second light source **LS2**, the image that the user **P1** sees displayed by the multi-view LCD **200** is darker than the image that the user **P2** sees displayed by the multi-view LCD **200**. In order for the user **P1** and the user **P2** to see images of the same brightness, the brightness of the first plane light source **L1** provided by the first backlight module **204** may substantially equal to the brightness of the second plane light source **L2** provided by the second backlight module **206**.

However, those skilled in the art may also set the images viewed by the user **P1** and the user **P2** to be at different brightness. Thus, the brightness of the first plane light source **L1** provided by the first backlight module **204** may substantially not equal to the brightness of the second plane light source **L2** provided by the second backlight module **206**.

Certainly, in other embodiments, designers may design the first backlight module **204** or the second backlight module

206 as a direct type backlight module. Furthermore, the first backlight module **204** and the second backlight module **206** may be any type that respectively provides light surface sources of different angles. The present invention does not limit the type of the first backlight module **204** or the second backlight module **206**.

It should be noted that the LCD panel **200** comprises a normal vector **N**. The transmitting direction of the first plane light source **L1** forms an included angle α_1 with the normal vector **N**, and the transmitting direction of the second plane light source **L2** forms an included angle α_2 with the normal vector **N**. Therefore, the directions from which the user **P1** and the user **P2** view the multi-view LCD **200** form angles α_1 and α_2 , respectively, with the normal vector **N**. Furthermore, the normal vector **N**, the transmitting direction of the first plane light source **L1**, and the transmitting direction of the second plane light source **L2** are on the same plane.

What is special is that in one embodiment, when α_1 and α_2 are equal and both in the range of 3 degrees to 88 degrees, the user **P1** and the user **P2** will be able to view better display images on the multi-view LCD **200** at angles α_1 and α_2 , respectively.

However, in another embodiment, when α_1 and α_2 are not equal and are both in the range of 3 degrees to 88 degrees, the user **P1** and the user **P2** may also be able to view better display images on the multi-view LCD **200** at angles α_1 and α_2 , respectively.

In practice, a driving circuit in the multi-view LCD **200** (not shown) may make the LCD panel **202** alternately display the first program image **I1** and the second program image **I2**. FIG. **3** is a waveform diagram of image signals received by the LCD panel of the multi-view LCD in one embodiment of the present invention. Referring to FIG. **2** and FIG. **3** at the same time, from the waveform diagram, the LCD panel **202** alternately receives a first image signal **SI1** and a second image signal **SI2**. Specifically, the time period **t1** that the LCD panel **202** receives the first image signal **SI1** corresponds to the turn-on time of the first backlight module **204**, during which the user **P1** may view the first program image **I1**. In another aspect, the time period **t2** that the LCD panel **202** receives the second image signal **SI2** corresponds to the turn-on time of the second backlight module **206**, during which the user **P2** may view the second program image **I2**.

Similarly, the method of transmitting images in time period **t1** may be applicable in time periods **t3** etc. . . . and the method of transmitting images in time period **t2** may be applicable in time periods **t4** etc. . . . In other words, the first program images **I1** generated in time periods **t1**, **t3**, . . . have a closer relationship, while the second program images **I2** generated in time periods **t2**, **t4**, . . . have a closer relationship. The first program image **I1** and the second program image **I2** are generated alternately. Therefore, the LCD **200** alternately displays the first program image **I1** and the second program image **I2**.

From the above, the user **P1** is in the transmitting direction of the first plane light source **L1** so the user **P1** only sees the first program image **I1** when viewing the multi-view LCD **200**. For the same reason, the user **P2** only sees the second program image **I2**. The fact that the LCD panel **202** alternately receives the image signals **SI1** and **SI2** makes the user **P1** and the user **P2** alternately view the first program image **I1** and the second program image **I2**. However, the vision reaction speeds of the user **P1** and the user **P2** are lower than the switching speed between the first image signal **SI1** and the second image signal **SI2** so the first program image **I1** viewed by the user **P1** and the second program image **I2** viewed by the user **P2** are serial display images.

It should be mentioned that in a same frame time t_f the turn-on time of the first backlight module **204** (e.g. $t_1, t_3, \dots$) and the turn-on time of the second backlight module **206** (e.g. $t_2, t_4, \dots$) may substantially be equal. However, those skilled in the art may design a turn-on time of the first backlight module **204** to be different from the turn-on time of the second backlight module **206**, according to design requirements.

Referring to FIG. 3 again, a time difference between the turn-on time of the first backlight module **204** (e.g. t_a) and the turn-off time of the second backlight module **206** (e.g. t_b) within a frame time t_f that the first program image **I1** and the second program image **I2** overlap is approximately larger than 0 ms and smaller than or equal to 8.3 ms. Take an Optically Compensated Birefringence Liquid Crystal Display (OCB LCD) for example, the time difference between the turn-on time of the first backlight module **204** (e.g. t_a) and the turn-off time of the second backlight module **206** (e.g. t_b) is approximately larger than 0 ms and smaller than or equal to 1 ms.

The above FIG. 1 and FIG. 2 showing the structure of the multi-view LCD **200** may be used to further illustrate the multi-view LCD **200** in connection with the driving method in FIG. 4. FIG. 4 is a flow chart illustrating a driving method in one embodiment of the present invention. The driving method is suitable for driving the multi-view LCD **100** and the multi-view LCD **200** (shown in FIG. 1 and FIG. 2). Referring to FIG. 4, the driving method comprises the following steps. First, provide the multi-view LCD **200** which comprises an LCD panel **202**, a first backlight module **204** and a second backlight module **206** as shown in FIG. 1 or FIG. 2, wherein the first backlight module **204** provides a first plane light source **L1** and the second backlight module **206** provides a second plane light source **L2** to the LCD panel **202**, and then, in step **S402**, a multi-view LCD alternately turns on a first backlight module and a second backlight module. In step **S404**, the multi-view LCD alternately displays a first program image **I1** and a second program image **I2** through an LCD panel. The turn-on time of the first backlight module corresponds to the time when the first program image is provided and the turn-on time of the second backlight module corresponds to the time when the second program image is provided.

Specifically, during the time when the first backlight module is turned on, the first backlight module works in connection with the LCD panel to display an image on the LCD. In another aspect, during the time when the second backlight module is turned on, the second backlight module works in connection with the LCD panel to display an image on the LCD. Other details of the present driving method have been included in the above embodiment, which will not be further explained herein.

In summary, the present invention provides a multi-view LCD which enables different users to view different images from different viewing angles. The resolutions of these images are the same as the real resolution of the LCD panel of the multi-view LCD. Thus, the multi-view LCD of the present invention provides simultaneous viewing to multiple users from multiple viewing angles without reducing resolution.

It will be apparent to those of ordinary skills in the technical field that various modifications and variations can be made to the structure of the present invention without departing from the scope or spirit of the invention. In view of the foregoing, it is intended that the present invention covers modifications and variations of this invention provided they fall within the scope of the following claims and their equivalents.

What is claimed is:

1. A method for driving a multi-view liquid crystal display (LCD), the multi-view LCD comprising an LCD panel; a first backlight module disposed below the LCD panel; and a second backlight module disposed between the first backlight module and the LCD panel, wherein the first backlight module provides a first plane light source, the second backlight module provides a second plane light source, and an included angle α formed between transmitting directions of the first and the second plane light sources ranges from 6 degrees to 176 degrees, the method comprising:

alternately turning on the first backlight module and the second backlight module; and

alternately displaying a first program image and a second program image through the LCD panel, wherein the turn-on time of the first backlight module corresponds to the time when the first program image is displayed and the turn-on time of the second backlight module corresponds to the time when the second program image is displayed, and wherein the first program image and the second program image are completely different and not related.

2. The method according to claim 1, wherein a brightness of the first plane light source provided by the first backlight module is substantially equal to a brightness of the second plane light source provided by the second backlight module.

3. The method according to claim 1, wherein a brightness of the first plane light source provided by the first backlight module is not equal to a brightness of the second plane light source provided by the second backlight module.

4. The method according to claim 1, wherein the turn-on time of the first backlight module and the turn-on time of the second backlight module are substantially the same in the same frame time.

5. A method for driving a multi-view LCD, comprising: providing the multi-view LCD, wherein the multi-view LCD comprises:

an LCD panel;

a first backlight module disposed below the LCD panel; and

a second backlight module disposed between the first backlight module and the LCD panel, wherein the first backlight module provides a first plane light source and the second backlight module provides a second plane light source to the LCD panel;

alternately turning on the first backlight module and the second backlight module; and

alternately displaying a first program image and a second program image through the LCD panel, wherein the first program image and the second program image are completely independent from each other at the same time, and the first program image and the second program image are completely different and not related.

6. The method according to claim 5, wherein a brightness of the first plane light source provided by the first backlight module is substantially equal to a brightness of the second plane light source provided by the second backlight module.

7. The method according to claim 5, wherein a brightness of the first plane light source provided by the first backlight module is not equal to a brightness of the second plane light source provided by the second backlight module.

8. The method according to claim 5, wherein a time difference between a turn-on time of the first backlight module and a turn-off time of the second backlight module within a frame time that the first program image and the second program image overlap is approximately larger than 0 ms and smaller than or equal to 8.3 ms.

9

9. The method according to claim 5, wherein a time difference between a turn-on time of the first backlight module and a turn-off time of the second backlight module is approximately larger than 0 ms and smaller than or equal to 1 ms.

10. A method for driving a multi-view LCD, comprising: 5
 providing the multi-view LCD, wherein the multi-view LCD comprises:
 an LCD panel;
 a first backlight module disposed below the LCD panel; and
 a second backlight module disposed between the first back- 10
 light module and the LCD panel, wherein the first back-
 light module provides a first plane light source and the

10

second backlight module provides a second plane light source to the LCD panel; and
 alternately displaying a first program image and a second program image through the LCD panel to a first user and a second user, respectively, wherein the first program image and the second program image are different.

11. The method according to claim 10, wherein the first program image and the second program image are completely different and not related.

12. The method according to claim 10, wherein the first user and the second user are located in different directions with respect to the multi-view LCD.

* * * * *

专利名称(译)	多视图液晶显示器及其驱动方法		
公开(公告)号	US8013951	公开(公告)日	2011-09-06
申请号	US12/220860	申请日	2008-07-28
[标]申请(专利权)人(译)	友达光电股份有限公司		
申请(专利权)人(译)	友达光电股份有限公司		
当前申请(专利权)人(译)	友达光电股份有限公司		
[标]发明人	HSU SHIH CHIA HU CHIH JEN		
发明人	HSU, SHIH-CHIA HU, CHIH-JEN		
IPC分类号	G02F1/1335		
CPC分类号	G02F1/1336 G09G3/3406 G09G2310/0237		
优先权	097112689 2008-04-08 TW		
其他公开文献	US20090251638A1		
外部链接	Espacenet USPTO		

摘要(译)

提供了一种用于不同用户的多视图液晶显示器，用于观看来自不同视角的不同图像。多视点液晶显示器包括液晶显示面板，第一背光模块和第二背光模块。第一背光模块设置在液晶显示面板下方。第二背光模块设置于第一背光模块与液晶显示面板之间。此外，第一背光模块提供第一平面光源，第二背光模块提供第二平面光源。在第一平面光源和第二平面光源的透射方向之间形成的夹角 α 的范围为6度至176度。因此，当不同的用户观看从不同视角显示不同图像的多视图液晶显示器时，图像的分辨率与多视图液晶显示面板的分辨率相同。

