



(19) **United States**

(12) **Patent Application Publication**
Song et al.

(10) **Pub. No.: US 2006/0244705 A1**
(43) **Pub. Date: Nov. 2, 2006**

(54) **LIQUID CRYSTAL DISPLAY AND DRIVING METHOD THEREOF**

Publication Classification

(76) Inventors: **Jang-Kun Song**, Seoul (KR);
Chang-Hun Lee, Suwon-city (KR);
Hak-Sun Chang, Seoul (KR)

(51) **Int. Cl.**
G09G 3/36 (2006.01)
(52) **U.S. Cl.** **345/98**

(57) **ABSTRACT**

The present invention relates a liquid crystal display. The liquid crystal display includes a liquid crystal panel assembly including a plurality of pixels arranged in a matrix, a gate driver applying gate signals to the pixels for application of data signals to the pixels, a data driver selecting gray voltages corresponding to gray signals and applying the selected gray voltages to the pixels as the data signals, and a signal controller providing the gray signals and control signals for controlling the gray signals for the gate driver and the data driver. The data signals include normal data signals and a black data signal. The data driver alternately applies the normal data signals and the black data signal to the pixels under control of the signal controller. A scanning direction of the normal data signals is opposite in adjacent frames. Accordingly, respective holding periods of all the pixels for the normal data signals and the black data signals are uniform, and then image quality of the LCD is uniformed to be improved.

Correspondence Address:
F. CHAU & ASSOCIATES, LLC
130 WOODBURY ROAD
WOODBURY, NY 11797 (US)

(21) Appl. No.: **10/520,352**

(22) PCT Filed: **Sep. 17, 2002**

(86) PCT No.: **PCT/KR02/01743**

(30) **Foreign Application Priority Data**

Jul. 5, 2002 (KR) 2002/38920




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4




FIG. 6




FIG. 7





FIG. 8



LIQUID CRYSTAL DISPLAY AND DRIVING METHOD THEREOF

BACKGROUND OF THE INVENTION

[0001] (a) Field of the Invention

[0002] The present invention relates to a liquid crystal display and a driving method thereof.

[0003] (b) Description of the Related Art

[0004] A typical liquid crystal display ("LCD") includes a pair of panels and a liquid crystal layer with dielectric anisotropy, which is disposed between the two panels. The liquid crystal layer is applied with electric field, and the transmittance of light passing through the liquid crystal layer is adjusted by controlling the electric field, thereby obtaining desired images. The LCD is the most commonly used one of flat panel displays ("FPDs") handy to carry. Among the various types of LCDs, a thin film transistor liquid crystal display ("TFT-LCD") employing the thin film transistors as switching elements is most widely used.

[0005] In a conventional TFT-LCD, because liquid crystal molecules have slow response time, images may be unclear and blurred. To solve the problem, an impulsive driving inserting block images has been adopted.

[0006] The impulsive driving includes an impulsive emission type and a cyclic resetting type, the former regularly turning on/off a backlight to darken a screen and the latter regularly applying black data signals.

[0007] However, these driving techniques have a problem of deteriorated image quality due to afterimage or flicker since response time of the liquid crystal molecules or the backlight is slow. More specifically, the latter technique has a problem of reduced application time of the data signals in a frame.

SUMMARY OF THE INVENTION

[0008] A motivation of the present invention is to solve the problems of the conventional art such that the application times of data signals to all pixels are uniform to improve image quality.

[0009] A liquid crystal display according to an aspect of the present invention includes: a liquid crystal panel assembly including a plurality of pixels arranged in a matrix; a gate driver applying gate signals to the pixels; a data driver selecting gray voltages corresponding to gray signals and applying the selected gray voltages to the pixels as data signals; and a signal controller providing the gray signals and control signals for controlling the gray signals for the gate driver and the data driver, wherein the data signals include normal data signals and a black data signal, the data driver alternately applies the normal data signals and the black data signal to the pixels under control of the signal controller, and a scanning direction of the normal data signals is opposite in adjacent frames.

[0010] The black data signal is simultaneously applied to the pixels.

[0011] A liquid crystal display according to another aspect of the present invention includes: a liquid crystal panel assembly including a plurality of scanning areas including a plurality of pixels arranged in a matrix and including respec-

tive switching elements connected to a plurality of gate lines and a plurality of data lines; a gate driver applying a voltage for turning on the switching elements to the gate lines; a data driver selecting gray voltages corresponding to gray signals and applying the selected gray voltages to the pixels via the data lines as data signals; and a signal controller providing the gray signals and control signals for controlling the gray signals for the gate driver and the data driver, wherein the gate driver includes a plurality of gate driving devices; the gate driving devices are connected to the gate lines; the pixels in different scanning areas are connected to different gate driving devices through the gate lines; the data signals include normal data signals and a black data signal; the normal data signals and the black data signal are alternately applied to each scanning area; the normal data signals are applied to one of the scanning areas, and then the black data signal is applied to one of remaining scanning areas except for one of the scanning areas; and scanning of the scanning areas for a previous frame is completed, and then scanning directions within the scanning areas for a next frame are opposite to scanning directions of the previous frame.

[0012] The black data signal is simultaneously applied to the pixels in one of the scanning areas.

[0013] Preferably, the black data signal applied in a previous step is held on at least one of the scanning areas during scanning of one of the scanning areas.

[0014] Moreover, polarity of the normal data signals on adjacent frames is preferably opposite.

[0015] The liquid crystal display may be in OCB mode.

[0016] A method of driving a liquid crystal display including a plurality of pixels arranged in a matrix, each pixel including a liquid capacitor filled with liquid material, according to another aspect of the present invention includes: a first data voltage application step applying normal data voltages to the pixels in a first direction; a second data voltage application step applying a black data voltage to the pixels; a third data voltage application step applying normal data voltages to the pixels in a second direction; and a fourth data voltage application step applying the black data voltage to the pixels.

[0017] Preferably, polarity of the normal data voltages applied in the first data voltage application step is opposite to polarity of the normal data voltage applied in the third data voltage application step, and polarity of the black data voltage applied in the second data voltage application step is opposite to polarity of the black data voltage applied in the fourth data voltage application step.

[0018] A method of driving a liquid crystal display including a plurality of pixels arranged in a matrix, each pixel including a liquid capacitor filled with liquid material and including a plurality of areas provided with the pixels, according to another aspect of the present invention includes: a first data voltage application step applying normal data voltages to a first area of the plurality of areas in a first direction; a second data voltage application step applying a black data voltage to a second area following the first area; a third data voltage application step applying normal data voltages to the second area in the first direction; a first repeating step repeating the first data voltage application step to the third data voltage application step for the plurality of areas; a fourth data voltage application step

applying normal data voltages to the first area in a second direction; a fifth data voltage application step applying the black data voltage to the second area; a sixth data voltage application step applying normal data voltages to the second area in the second direction; and a second repeating step repeating the fourth data voltage application step to the sixth data voltage application step for the plurality of areas.

[0019] Preferably, the first direction is opposite to the second direction.

[0020] A liquid crystal display according to the other aspect to the present invention includes including a plurality of pixels, wherein normal data signals and a black data signal are alternately applied to the pixels, and normal data holding periods of the pixels averaged over adjacent two frames is uniform.

[0021] Preferably, scanning directions for the adjacent two frames are opposite each other.

BRIEF DESCRIPTION OF THE DRAWINGS

[0022] FIG. 1 is a block diagram of an LCD according to an embodiment of the present invention;

[0023] FIG. 2 is an equivalent circuit diagram of a pixel of an LCD according to an embodiment of the present invention;

[0024] FIG. 3A is a detailed block diagram of a gate driver according to an embodiment of the present invention;

[0025] FIG. 3B shows a connection between a gate driving integrated circuit (IC) and a liquid crystal panel assembly according to an embodiment of the present invention;

[0026] FIG. 4 illustrates an impulsive driving according to an embodiment of the present invention;

[0027] FIG. 5 shows waveforms of gate signals and data signals being applied in the impulsive driving shown in FIG. 4;

[0028] FIG. 6 shows scanning for a first frame in a driving method of an LCD according to another embodiment of the present invention;

[0029] FIG. 7 shows waveforms of gate signals and data signals in the first frame shown in FIG. 6;

[0030] FIG. 8 shows scanning for a second frame in a driving method of an LCD according to another embodiment of the present invention; and

[0031] FIG. 9 shows waveforms of gate signals and data signals in the second frame shown in FIG. 8.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0032] The present invention now will be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Like numerals refer to like elements throughout.

[0033] Then, liquid crystal displays according to embodiments of the present invention will be described.

[0034] FIG. 1 is a block diagram of an LCD according to an embodiment of the present invention, and FIG. 2 is an equivalent circuit diagram of a pixel of an LCD according to an embodiment of the present invention.

[0035] Referring to FIG. 1, an LCD according to an embodiment of the present invention includes a liquid crystal panel assembly 300, a gate driver 420 and a data driver 430 which are connected to the panel assembly 300, a driving voltage generator 560 connected to the gate driver 420, a gray voltage generator 570 connected to the data driver 430, and a signal controller 550 controlling the above elements.

[0036] In view of an equivalent circuit, the panel assembly 300 includes a plurality of signal lines G_1 - G_n and D_1 - D_m and a plurality of pixels connected thereto. Each pixel includes a switching element Q connected to the signal lines G_1 - G_n and D_1 - D_m , and a liquid crystal capacitor C_{lc} and a storage capacitor C_{st} that are connected to the switching element Q. The signal lines G_1 - G_n and D_1 - D_m include a plurality of scanning lines or gate lines G_1 - G_n extending in a row direction and transmitting scanning signals or gate signals, and a plurality of data lines D_1 - D_m extending in a column direction and transmitting image signals or data signals. The switching element Q has three terminals, a control terminal connected to one of the gate lines G_1 - G_n , an input terminal connected to one of the data lines D_1 - D_m , and an output terminal connected to both the liquid crystal capacitor C_{lc} and the storage capacitor C_{st} .

[0037] The liquid crystal capacitor C_{lc} is connected between the output terminal of the switching element Q and a reference voltage or a common voltage V_{com} . The other terminal of the storage capacitor C_{st} is connected a predetermined voltage such as the reference voltage. However, the other terminal of the storage capacitor C_{st} may be connected to a gate line located just above (referred to as a "previous gate line" hereinafter). The former is referred to as a separate wire type, and the latter is referred to as a previous gate type.

[0038] Meanwhile, FIG. 2 schematically shows a structure of a panel assembly 300 according to an embodiment of the present invention. For easy explanation, only a pixel is illustrated in FIG. 2.

[0039] As shown in FIG. 2, a panel assembly 300 includes a lower panel 100, an upper panel 200 opposite the lower panel 100, and a liquid crystal layer 3 interposed therebetween. Gate lines G_i and G_{i-1} , a data line D_j , a switching element Q, and a storage capacitor C_{st} are provided on the lower panel 100. A pixel electrode 190 on the lower panel 100 and a common electrode 270 on the upper panel 200 form two terminals of a liquid crystal capacitor C_{lc} . The liquid crystal layer 3 disposed between the two electrodes 190 and 270 functions as dielectric of the liquid crystal capacitor C_{lc} . The liquid crystal layer 3 according to this embodiment, for example, may have an optically compensated bend (OCB) type orientation. In this case, the liquid crystal molecules are aligned in a bend mode, where liquid crystal molecules are symmetrically aligned with respect to a mid-plane located between the lower panel 100 and the upper panel 200. The OCB LCD improves response time and view angle, uses the bend orientation of the liquid crystal molecules, which is easily broken upon application of a voltage lower than a predetermined voltage, and may be driven with voltages higher than a threshold voltage (V_c), which do not break the bend alignment.

[0040] The pixel electrode **190** is connected to the switching element **Q** and the common electrode **270** is connected to the common voltage V_{com} and covers entire surface of the upper panel **200**.

[0041] The orientations of liquid crystal molecules in the liquid crystal layer **3** are changed by the change of electric field generated by the pixel electrode **190** and the common electrode **270**. The change of the molecular orientations changes the polarization of light passing through the liquid crystal layer **3**, which in turn causes the variation of the transmittance of the light by a polarizer or polarizers (not shown) attached to at least one of the panels **100** and **200**.

[0042] A separate wire provided on the lower panel **100** and supplied with the reference voltage overlaps the pixel electrode **190** to form a storage capacitor Cst . In the previous gate type, the pixel electrode **190** overlaps its previous gate line G_{i-1} via an insulator such that the pixel electrode **190** and the previous gate line G_{i-1} form two terminals of the storage capacitor Cst .

[0043] **FIG. 2** shows a MOS transistor as a switching element, and the MOS transistor is implemented as a thin film transistor ("TFT") including an amorphous silicon or polysilicon channel layer in practical manufacturing process.

[0044] Different from **FIG. 2**, the common electrode **270** may be provided on the lower panel **100**. In this case, both the electrodes **190** and **270** have shapes of stripes.

[0045] For realizing color display, each pixel can represent a color by providing one of a plurality of red, green and blue color filters **230** in an area corresponding to the pixel electrode **190**. The color filter **230** shown in **FIG. 2** is provided in the corresponding area of the upper panel **200**. Alternatively, the color filter **230** is provided on or under the pixel electrode **190** on the lower panel **100**.

[0046] Referring to **FIG. 1** again, the gate driver **420** and the data driver **430**, which are often called a scanning driver and a source driver, respectively, may include a plurality of gate driving integrated circuits (ICs) and a plurality of data driving ICs, respectively. The ICs are separately placed external to the panel assembly **300** or mounted on the panel assembly **300**. Alternatively, the ICs are formed on the panel assembly **300** like the signal lines G_1-G_n and D_1-D_m and the TFTs **Q**. In **FIG. 3A**, the gate driver **420** includes four gate driving ICs **421-424** which are chips mounted on a flexible printed circuit film. Also, each gate driving IC **421-424** is connected to the gate lines via a plurality of wires **500**, and the four gate driving ICs **421-424** are connected to all gate lines G_1-G_n through wires **500**.

[0047] Each gate driving IC **421-424** of the gate driver **420** is connected to the gate lines G_1-G_n of the panel assembly **300** and applies gate signals to the gate lines G_1-G_n , each gate signal being a combination of a gate-on voltage V_{on} and a gate off voltage V_{off} from the driving voltage generator **560**. In this embodiment of the present invention, the gate signals are applied through the gate lines G_1-G_n connected to each gate driving IC **421-424** of the gate driver **420**.

[0048] The data driver **430** is connected to the data lines D_1-D_n of the panel assembly **300** and selects gray voltages from the gray voltage generator **570** to be applied as data signals to the data lines D_1-D_n .

[0049] The gate driver **420**, the data driver **430** and the driving voltage generator **560** are controlled by the signal controller **400** connected thereto and located external to the panel assembly **300**. The operation will be described in detail.

[0050] The signal controller **550** is supplied from an external graphic controller (not shown) with RGB gray signals R , G and B and input control signals controlling the display thereof, for example, a vertical synchronization signal V_{sync} , a horizontal synchronization signal H_{sync} , a main clock CLK , a data enable signal DE , etc. After generating gate control signals and data control signals on the basis of the input control signals and processing the gray signals R , G and B suitable for the operation of the panel assembly **300**, the signal controller **550** provides the gate control signals for the gate driver **420**, and the processed gray signals R' , G' and B' and the data control signals for the data driver **430**.

[0051] The gate control signals include a vertical synchronization start signal STV for instructing to begin outputting gate-on pulses (i.e., high sections of the gate signals), a gate clock signal CPV for controlling the output period of the gate-on pulses and an output enable signal OE for defining the widths of the gate-on pulses. Among the gate control signals, the output enable signal OE and the gate clock signal CPV are provided for the driving voltage generator **560**. The data control signals include a horizontal synchronization start signal STH for instructing to begin outputting the gray signals, a load signal $LOAD$ or TP for instructing to apply the appropriate data voltages to the data lines, an inversion control signal RVS for reversing polarity of the data voltages, and a data clock signal $HCLK$.

[0052] Responsive to the gate control signals from the signals controller **550**, the gate driver **420** sequentially applies the gate-on pulses to the gate lines G_1-G_n , thereby sequentially turning on the switching elements **Q** connected thereto. In response to the data control signals from the signal controller **550**, the data driver **430** supplies analog voltages from the gray voltage generator **570** corresponding to the entering gray signals R' , G' and B' to the corresponding data lines D_1-D_m as the data signals. Then, the data signals in turn are applied to the corresponding pixels via the turned-on switching elements **Q**. By performing this procedure, all gate lines G_1-G_n are supplied with the gate-on pulses in a frame such that all pixel rows are supplied with the data signals. At that time, if the data signals for a frame are applied to the pixels in all rows and then the inversion control signal RVS makes the polarity of data signals for a next frame, which are applied to all rows, changed. Moreover, according to this embodiment of the present invention, normal data signals N and black data signals B are alternately applied to each pixel.

[0053] Then, an impulsive driving according to an embodiment of the present invention will be described in detail with reference to **FIGS. 4** and **5**.

[0054] **FIG. 4** illustrates an impulsive driving according to an embodiment of the present invention, and **FIG. 5** shows waveforms of gate signals and data signals in the impulsive driving shown in **FIG. 4**.

[0055] The impulsive driving method in accordance with an embodiment of the present invention applies a gate-on

voltage V_{on} to all gate lines G_1 - G_n to turn on switching elements Q and applies a black data B to all pixels for a predetermined time after applying normal data signals N of a frame to the pixels. Scanning directions are changed alternately every frame, that is, from top to bottom, and then from bottom to top.

[0056] As shown in (a) of FIG. 4, in a first frame, the gate-on voltage V_{on} is sequentially applied from the first gate line $G1$ to the last gate line G_n such that the normal data signals N corresponding to gray signals R' , G' and B' are supplied for all pixels. Then, as shown in (b) of FIG. 4, the gate-on voltage V_{on} is applied to all gate lines $G1$ - G_n at the same time and the black data signal B is applied to the data lines $D1$ - D_n to display a black image on the panel assembly 300. Since the normal data signals N are held until the black data signals B are applied, the normal data holding time becomes to gradually decrease from the first row to the last row.

[0057] In a second frame, the normal data signals N are sequentially applied from the last row to the first row, in a direction opposite in the first frame (as shown in (c) of FIG. 4). Then, the gate-on voltage V_{on} is applied to all gate lines $G1$ - G_n at the same time and the black data signal B is applied to all pixels via the data lines $D1$ - D_n (as shown in (d) of FIG. 4). Thereby, the data holding time becomes to gradually increase from the first row to the last row.

[0058] Accordingly, the data holding times of the pixels averaged over the two frames are equal.

[0059] As shown in (e) and (f) of FIG. 4, the alternate application of the normal data signals N and the black data signals B are repeated, in the same manner as (a) and (b) of FIG. 4.

[0060] According to an embodiment of the present invention, the polarity of the normal data signals N and the black data signals B are reversed every frame. For example, if the applied normal data signals in (a) of FIG. 4 have positive polarity, the applied normal data signals N in (c) of FIG. 4 have negative polarity and then the applied normal data signals N in (e) of FIG. 4 have positive polarity again. Similarly, if the black data signal B having positive polarity is applied in (b) of FIG. 4, the black data signal B having negative polarity is applied in (d) of FIG. 4 and then the black data signal B having positive polarity is applied in (f) of FIG. 4.

[0061] Referring to FIGS. 6-9, an impulsive driving of an LCD in accordance with an embodiment of the present invention will be described in detail.

[0062] FIG. 6 shows scanning for a first frame in a driving method of an LCD according to another embodiment of the present invention, and FIG. 7 shows waveforms of gate signals and data signals in the first frame shown in FIG. 6.

[0063] FIG. 8 shows scanning for a second frame in a driving method of an LCD according to another embodiment of the present invention, and FIG. 9 shows waveforms of gate signals and data signals in the second frame shown in FIG. 8.

[0064] For convenience, all gate lines $G1$ - G_n are grouped into four groups $G11$ - $G1i$, $G21$ - $G2i$, $G31$ - $G3i$ and $G41$ - $G4i$ based on the connection to the gate driving ICs 421-424 shown in FIG. 3. That is, the gate lines of each gate line

group $G11$ - $G1i$, $G21$ - $G2i$, $G31$ - $G3i$ or $G41$ - $G4i$ are connected only to a corresponding gate driving IC 421-424. Furthermore, the pixels are partitioned into four imaginary areas 3001-3004 based on the connection to the four gate line groups $G11$ - $G1i$, $G21$ - $G2i$, $G31$ - $G3i$ and $G41$ - $G4i$. That is, the pixels in different imaginary areas 3001-3004 are connected to different gate line groups $G11$ - $G1i$, $G21$ - $G2i$, $G31$ - $G3i$ and $G41$ - $G4i$, and connected to different gate driving ICs 421-424.

[0065] As shown in (a) of FIG. 6, the gate-on voltage V_{on} is applied to all gate lines $G21$ - $G2i$ for the second area 3002 at the same time and the black data signal B is applied to the data lines $D1$ - D_m . At this time, the pixels in the remaining areas hold previously applied data signals.

[0066] Subsequently, as shown in (b) of FIG. 6, the first area 3001 is scanned from top to bottom for application of the normal data signals N . The second area 3002 holds the previously applied black data signal.

[0067] Next, as shown in (c) of FIG. 6, the gate-on voltage V_{on} is applied to all gate lines $G31$ - $G3i$ connected to the third gate driving IC 423 at the same time, and then the black data signal B is applied to the third area 3003. At this time, the first area 3001 holds the normal data signals N and the second area 3002 holds the black data signal B .

[0068] As shown in (d) of FIG. 6, the second area 3002 connected to the second gate driving IC 422 is scanned from top to bottom for application of the normal data signals N . The pixels in the first area 3001 hold the normal data signal N and those of the third area 3003 hold the black data signal B .

[0069] As shown in (e) of FIG. 6, the gate-on voltage V_{on} is applied to the gate lines $G41$ - $G4i$ of the fourth area 3004 connected to the fourth gate driving IC 424 at the same time and the black data signal B is applied to the pixels of thereof such that the fourth area 3004 is in a black state. At this time, the first and the second areas 3001 and 3002 hold the normal data signals N , and the third area 3003 holds the black data signal B .

[0070] As shown in (f) of FIG. 6, the third area 3003 connected to the third gate driving IC 423 and thus connected to the gate lines $G31$ - $G3i$ is scanned from top to bottom for application of the normal data signals N . The first and the second areas 3001 and 3002 hold the normal data signals N and the fourth area 3004 holds the black data signal B .

[0071] As shown in (g) of FIG. 6, the gate-on voltage V_{on} is applied to gate lines $G11$ - $G1i$ for the first area 3001 connected to the first gate driving IC 421 at the same time and the black data signal B is applied to the first area 3001 to be in a black state. At this time, the second and the third areas 3002 and 3003 hold the normal data signals N and the fourth area 3004 holds the black data signal B .

[0072] Finally, as shown in (h) of FIG. 6, the fourth area 3004 connected to the fourth gate driving IC 424 and thus connected to the gate lines $G41$ - $G4i$ is scanned from top to bottom for application of the normal data signals N . The first area 3001 holds the black data signal B and the second and the third areas 3002 and 3003 hold the normal data signals N .

[0073] In this manner, when a frame is completed, a next frame starts. A scanning direction within each area **3001-3004** is opposite to a scanning direction in the previous frame, that is, from bottom to top.

[0074] At that time, the inverse control signal RVS is applied to the data driver **430** such that the polarity of the normal and the black data signals N and B are reversed.

[0075] Now, referring to **FIGS. 8 and 9**, the scanning of the next frame will be described.

[0076] The scanning of the next frame proceeds from the first area **3001** to the fourth area **3004** as the previous frame, but a scanning direction in each area **3001-3004** is from bottom to top. Except for the scanning direction, the scanning is similar to that described with reference to **FIG. 6** and the detailed description thereof is omitted.

[0077] In this embodiment of the present invention, the number of the areas holding the black data signal B is two to enhance the effect of the impulsive driving, but the number may be one or three. However, it is preferable to hold the black data signal on an area equal to or larger than 50% of the total display area.

[0078] In addition, the gate driver **420** according to this embodiment of the present invention has the four gate driving ICs **421-424**, but also the number of the gate driving ICs may be varied. Moreover, the areal partition is made such that one area corresponds to one gate driving IC, but may be made such that one area corresponds to two or more gate driving ICs.

[0079] As described above, the impulsive driving using a black data signal reverses the scanning direction for a frame compared with a previous frame such that holding times of the normal data signals and the black data signals for all pixels are uniform. Therefore, image quality of an LCD panel becomes uniform to be improved.

[0080] Furthermore, the LCD panel assembly is partitioned into a plurality of imaginary areas, and the scanning in each area proceeds in opposition to the scanning of the previous frame. As a result, it is possible to decrease the difference in the normal data holding time and the black data holding time between the pixels near the center and near the edges of the panel assembly, thereby preventing flicker and improving image quality of the panel assembly.

[0081] Although preferred embodiments of the present invention have been described in detail hereinabove, it should be clearly understood that many variations and/or modifications of the basic inventive concepts herein taught which may appear to those skilled in the present art will still fall within the spirit and scope of the present invention, as defined in the appended claims.

What is claimed is:

1. A liquid crystal display comprising:

a liquid crystal panel assembly including a plurality of pixels arranged in a matrix;

a gate driver applying gate signals to the pixels;

a data driver selecting gray voltages corresponding to gray signals and applying the selected gray voltages to the pixels as data signals; and

a signal controller providing the gray signals and control signals for controlling the gray signals for the gate driver and the data driver,

wherein the data signals include normal data signals and a black data signal, the data driver alternately applies the normal data signals and the black data signal to the pixels under control of the signal controller, and a scanning direction of the normal data signals is opposite in adjacent frames.

2. The liquid crystal display of claim 1, wherein the black data signal is simultaneously applied to the pixels.

3. A liquid crystal display comprising:

a liquid crystal panel assembly including a plurality of scanning areas including a plurality of pixels arranged in a matrix and including respective switching elements connected to a plurality of gate lines and a plurality of data lines;

a gate driver applying a voltage for turning on the switching elements to the gate lines;

a data driver selecting gray voltages corresponding to gray signals and applying the selected gray voltages to the pixels via the data lines as data signals; and

a signal controller providing the gray signals and control signals for controlling the gray signals for the gate driver and the data driver,

wherein

the gate driver includes a plurality of gate driving devices;

the gate driving devices are connected to the gate lines;

the pixels in different scanning areas are connected to different gate driving devices through the gate lines;

the data signals include normal data signals and a black data signal;

the normal data signals and the black data signal are alternately applied to each scanning area;

the normal data signals are applied to one of the scanning areas, and then the black data signal is applied to one of remaining scanning areas except for the one of the scanning areas; and

scanning of the scanning areas for a previous frame is completed, and then scanning directions within the scanning areas for a next frame are opposite to scanning directions of the previous frame.

4. The liquid crystal display of claim 3, wherein the black data signal is simultaneously applied to the pixels in one of the scanning areas.

5. The liquid crystal display of claim 3, wherein the black data signal applied in a previous step are held on at least one of the scanning areas during scanning of one of the scanning areas.

6. The liquid crystal display of claim 1 or 3, wherein polarity of the normal data signals on adjacent frames is opposite.

7. The liquid crystal display of claim 1 or 3, wherein the liquid crystal display is in an OCB mode.

8. A method of driving a liquid crystal display including a plurality of pixels arranged in a matrix, each pixel including a liquid capacitor filled liquid material, the method comprising:

- a first data voltage application step applying normal data voltages to the pixels in a first direction;
- a second data voltage application step applying a black data voltage to the pixels;
- a third data voltage application step applying normal data voltages to the pixels in a second direction; and
- a fourth data voltage application step applying the black data voltage to the pixels.

9. The method of claim 8, wherein polarity of the normal data voltages applied in the first data voltage application step is opposite to polarity of the normal data voltage applied in the third data voltage application step.

10. The method of claim 8, wherein polarity of the black data voltage applied in the second data voltage application step is opposite to polarity of the black data voltage applied in the fourth data voltage application step.

11. A method of driving a liquid crystal display including a plurality of pixels arranged in a matrix, each pixel including a liquid capacitor filled with liquid material and including a plurality of areas provided with the pixels, the method comprising:

- a first data voltage application step applying normal data voltages to a first area of the plurality of areas in a first direction;
- a second data voltage application step applying a black data voltage to a second area following the first area;

a third data voltage application step applying normal data voltages to the second area in the first direction;

a first repeating step repeating the first data voltage application step to the third data voltage application step for the plurality of areas;

a fourth data voltage application step applying normal data voltages to the first area in a second direction;

a fifth data voltage application step applying the black data voltage to the second area;

a sixth data voltage application step applying normal data voltages to the second area in the second direction; and

a second repeating step repeating the fourth data voltage application step to the sixth data voltage application step for the plurality of areas.

12. The method of claim 8 or 11, wherein the first direction is opposite to the second direction.

13. A liquid crystal display comprising:

a plurality of pixels,

wherein normal data signals and a black data signal are alternately applied to the pixels, and normal data holding period of the pixels averaged over adjacent two frames is uniform.

14. The liquid crystal display, wherein scanning directions for the adjacent two frames are opposite each other.

* * * * *

专利名称(译)	液晶显示器及其驱动方法		
公开(公告)号	US20060244705A1	公开(公告)日	2006-11-02
申请号	US10/520352	申请日	2002-09-17
[标]申请(专利权)人(译)	SONG JANG KUN 李沧HUN 常金学顺		
申请(专利权)人(译)	SONG JANG-KUN 李沧HUN 常HAK-SUN		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	SONG JANG KUN LEE CHANG HUN CHANG HAK SUN		
发明人	SONG, JANG-KUN LEE, CHANG-HUN CHANG, HAK-SUN		
IPC分类号	G09G3/36 G02F1/133 G02F1/1362 G09G3/20		
CPC分类号	G02F1/1362 G09G3/3648 G09G3/3666 G09G2320/0252 G09G2310/062 G09G2310/063 G09G2310/0283		
优先权	1020020038920 2002-07-05 KR		
其他公开文献	US8184080		
外部链接	Espacenet USPTO		

摘要(译)

液晶显示器本发明涉及一种液晶显示器。液晶显示器包括：液晶面板组件，包括以矩阵排列的多个像素；栅极驱动器，向像素施加栅极信号，用于向像素施加数据信号；数据驱动器，选择对应于灰度信号的灰度电压，以及应用作为数据信号的像素的所选灰度电压，以及提供灰度信号和控制信号的信号控制器，用于控制栅极驱动器和数据驱动器的灰度信号。数据信号包括正常数据信号和黑色数据信号。数据驱动器在信号控制器的控制下交替地将正常数据信号和黑色数据信号施加到像素。正常数据信号的扫描方向在相邻帧中相反。因此，正常数据信号和黑色数据信号的所有像素的各个保持周期是均匀的，然后LCD的图像质量均匀以提高。

