



US007336332B2

(12) **United States Patent**
Yang et al.

(10) **Patent No.:** **US 7,336,332 B2**
(45) **Date of Patent:** **Feb. 26, 2008**

(54) **REFLECTIVE TYPE CONTINUOUS DOMAIN
IN-PLANE SWITCHING LIQUID CRYSTAL
DISPLAY**

(75) Inventors: **Chiu-Lien Yang**, Miao-Li (TW);
Jia-Pang Pang, Miao-Li (TW);
Chueh-Ju Chen, Miao-Li (TW)

(73) Assignee: **Innolux Display Corp.**, Miao-Li (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 238 days.

(21) Appl. No.: **11/028,127**

(22) Filed: **Dec. 31, 2004**

(65) **Prior Publication Data**

US 2005/0212999 A1 Sep. 29, 2005

(30) **Foreign Application Priority Data**

Mar. 26, 2004 (TW) 93108255 A

(51) **Int. Cl.**
G02F 1/1343 (2006.01)

(52) **U.S. Cl.** 349/141; 349/145; 349/146

(58) **Field of Classification Search** 349/141,
349/145, 146

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,177,628 A * 1/1993 Moddel 349/28
5,977,562 A * 11/1999 Hirakata et al. 257/72
6,618,109 B2 * 9/2003 Hidehira et al. 349/141

6,741,311 B1 * 5/2004 Hong et al. 349/141
6,791,644 B2 9/2004 Toda
6,803,980 B2 10/2004 Funahata et al.
6,859,248 B2 * 2/2005 Matsumoto et al. 349/141
6,972,824 B2 * 12/2005 Masutani et al. 349/192
2001/0008693 A1 * 7/2001 Fink et al. 428/421
2004/0041742 A1 * 3/2004 Fink et al. 343/912
2005/0206826 A1 * 9/2005 Yang et al. 349/143
2006/0209243 A1 * 9/2006 Chen et al. 349/145
2007/0030432 A1 * 2/2007 Chen et al. 349/141
2007/0046867 A1 * 3/2007 Yang et al. 349/106

* cited by examiner

Primary Examiner—David Nelms


Assistant Examiner—David Y. Chung

(74) *Attorney, Agent, or Firm*—Wei Te Chung

(57) **ABSTRACT**

A reflective type IPS LCD includes a transparent upper substrate (100) and a lower substrate (200), and liquid crystal molecules (300) interposed between the substrates. A reflection layer (250) is disposed on the lower substrate. A plurality of gate lines (170) and a plurality of data lines (180) are formed on the upper substrate, thereby defining a plurality of pixel regions arranged in a matrix. Each pixel region includes pixel electrodes (210) and common electrodes (220). The pixel electrodes and the common electrodes have a bent configuration, and are spaced apart from each other. Therefore the electric field generated by them is along two directions, and the LCD exhibits a two-domain display effect. When viewing the LCD display from any oblique angle, the color shifts generated by the two domains counteract, and thus the overall color shift of the display is small.

5 Claims, 5 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8
(PRIOR ART)




FIG. 9
(PRIOR ART)

REFLECTIVE TYPE CONTINUOUS DOMAIN IN-PLANE SWITCHING LIQUID CRYSTAL DISPLAY

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a reflective type IPS (in-plane switching) mode LCD (liquid crystal display), and the control of liquid crystal molecules therein.

2. Description of Prior Art

A liquid crystal display utilizes the optical and electrical anisotropy of liquid crystal molecules thereof in order to produce an image. The liquid crystal molecules have a particular passive orientation when no voltage is applied thereto. However, in a driven state, the liquid crystal molecules change their orientation according to the strength and direction of the driving electric field. A polarization state of incident light changes when the light transmits through the liquid crystal molecules, due to the optical anisotropy of the liquid crystal molecules. The extent of the change depends on the orientation of the liquid crystal molecules. Thus, by properly controlling the driving electric field, an orientation of the liquid crystal molecules is changed and a desired image can be produced.

The TN (twisted nematic) mode LCD was the first main type of LCD developed. Even though TN mode LCDs have been put into use in many applications, they have an inherent drawback that cannot be eliminated; namely, a very narrow viewing angle. By adding compensation films on TN mode LCDs, this problem can be ameliorated to some extent. However, the cost of the TN mode LCD is increased. Therefore, a totally different driving means called IPS (in-plane switching) was proposed as early as in 1974. Then in 1993, Hitachi Corporation filed its first US patent application concerning IPS, in which an IPS mode LCD was disclosed.

A conventional IPS mode LCD has an upper substrate, a lower substrate, and a liquid crystal layer interposed therebetween. The liquid crystal layer has a plurality of liquid crystal molecules which have a same orientation when not driven, this orientation being parallel to the substrates. Pixel electrodes and common electrodes are disposed on the lower substrate. When a voltage is applied to the electrodes, an electric field is generated between the electrodes. The electric field drives the liquid crystal molecules to rotate in a plane parallel to the substrates. This rotation results in a change in light transmission. In other words, the operation of the IPS mode LCD is such that the liquid crystal molecules rotate in a plane parallel with the substrates in order to fulfill optical switching. The IPS LCD has the important advantage of a wide viewing angle. In basic IPS mode LCDs, the pixel electrodes and common electrodes are each comb-shaped. The electric field of these LCDs in a driven state is along a certain direction. Thus these LCDs are referred to as single domain IPS LCDs. When the displayed image is viewed at different oblique angles, a viewer may notice a quite large color shift. When this single domain IPS technology is applied in a reflective type liquid crystal display, color shift is likewise a problem.

Referring to FIG. 8 and FIG. 9, these are schematic plan representations of a conventional reflective type IPS liquid crystal display disclosed in U.S. Pat. No. 6,577,368 issued on Jun. 10, 2003. The liquid crystal display comprises an upper substrate (not shown), a lower substrate 80, and liquid crystal molecules (not shown) interposed between the substrates. A plurality of gate lines 10 and data lines 70 are

formed on the lower substrate 80, for transmitting a gate signal and a data signal respectively. TFTs (thin film transistors) are positioned at the intersections of the gate lines 10 and data lines 70. Each TFT comprises a gate electrode 11, a source electrode 71, and a drain electrode 72. Pixel electrodes 75 and common electrodes 20 are formed on the lower substrate 80, for generating a driving electric field. A lower alignment film 4 is disposed at the lower substrate 80, to control the alignment of the liquid crystal molecules.

Each of the pixel electrodes 75 and the common electrodes 20 is comb-shaped. Therefore when a voltage is applied to the pixel and common electrodes 75, 20, a parallel electric field mainly along a single direction is generated. The pixel electrodes 75 and the common electrodes 20 are made of an opaque material having high reflectance.

When the voltage is applied, the liquid crystal display is said to be in a driven state. The liquid crystal molecules have the same orientation due to the electric field. When the LCD display is viewed from an oblique angle, a color shift is seen. That is, the viewer sees a yellowish or a bluish image.

It is desired to provide a multi-domain reflective type IPS liquid crystal display which overcomes the above-described deficiencies.

SUMMARY OF THE INVENTION

An object of the present invention is to provide a multi-domain reflective type IPS liquid crystal display which has a relatively small color shift.

A preferred kind of reflective type IPS liquid crystal display of the present invention comprises a transparent upper substrate and a lower substrate, and liquid crystal molecules interposed between the substrates. A reflection layer is disposed on the lower substrate. A plurality of gate lines and a plurality of data lines are formed on one of the substrates, thereby defining a plurality of pixel regions arranged in a matrix. Each pixel region comprises a plurality of pixel electrodes and a plurality of common electrodes. The pixel electrodes and the common electrodes have a bent configuration, and are uniformly spaced apart from each other.

Because the pixel and common electrodes have the bent configuration, the electric field generated by them is along various different directions in a pixel region. The pixel region forms multi-domains. Therefore the color shift of each pixel region at oblique viewing angles is counteracted and the whole liquid crystal display has a small color shift.

Other objects, advantages, and novel features of the present invention will become more apparent from the following detailed description when taken in conjunction with the accompanying drawings, in which:

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic, side cross-sectional view of part of a reflective type IPS LCD according to a first embodiment of the present invention;

FIG. 2 is a schematic, top elevation of parts of a pixel region of the reflective type IPS LCD of FIG. 1, showing a configuration of pixel electrodes and common electrodes;

FIG. 3 is a schematic, side cross-sectional view of part of a reflective type IPS LCD according to a second embodiment of the present invention;

FIG. 4 is a schematic, top elevation of parts of a pixel region of the reflective type IPS LCD of FIG. 3, showing a configuration of pixel electrodes and common electrodes;

FIG. 5 is a schematic, side cross-sectional view of part of a reflective type IPS LCD according to a third embodiment of the present invention;

FIG. 6 is a schematic, top elevation of parts of a pixel region of the reflective type IPS LCD of FIG. 5, showing a configuration of pixel electrodes and common electrodes;

FIG. 7 is a schematic, inverted, side cross-sectional view of a reflection layer and a lower substrate of the reflective type IPS LCD of FIG. 5;

FIG. 8 is a schematic, top elevation of a pixel region of a conventional IPS LCD; and

FIG. 9 is a schematic, cross-sectional view taken along line of IX-IX of FIG. 8.

DETAILED DESCRIPTION OF THE INVENTION

Referring to FIG. 1 and FIG. 2, these are respectively a side cross-sectional view of a reflective type in-plane switching liquid crystal display (IPS LCD) according to a first embodiment of the present invention and a plan view of a pixel region of the IPS LCD. This IPS LCD comprises a transparent upper substrate **100**, a lower substrate **200**, and positive liquid crystal molecules **300** interposed between the upper and lower substrates **100**, **200**. An upper polarizer **160** is disposed on the outer side of the upper substrate **100**, a color filter **140** is disposed on an underside of the upper substrate **100**, and an upper alignment film **130** is disposed on an underside of the color filter **140**. A reflection layer **250** is formed on the lower substrate **200**. A plurality of gate lines **170** and data lines **180** are disposed on the lower substrate **200**, and define a plurality of pixel regions arranged in a matrix. Each pixel region comprises a plurality of pixel electrodes **210** and a plurality of common electrodes **220**. The pixel electrodes **210** and the common electrodes **220** have a similar zigzagged configuration, and are uniformly spaced apart from each other. A lower alignment film **230** is disposed on the reflection layer **250** and the electrodes **210**, **220**.

When a voltage is applied, because the pixel and common electrodes **210**, **220** have zigzagged configurations, the electric field (not shown) generated is mainly along two directions, and the IPS LCD exhibits a two-domain display effect. When viewing the IPS LCD display from any oblique angle, the color shifts generated by the two domains counteract each other, and thus the overall color shift of the display is small.

Referring to FIG. 3 and FIG. 4, a reflective type in-plane switching liquid crystal display (IPS LCD) according to the second embodiment of the present invention comprises a transparent upper substrate **101**, a lower substrate **201**, and positive liquid crystal molecules **301** interposed between the upper and lower substrates **101**, **201**. A lower alignment film **231**, a color filter **241** and a reflection layer **251** are stacked on the lower substrate **201** in that order from top to bottom. An upper polarizer **161** is disposed on an outer side of the upper substrate **101**. A plurality of gate lines **171** and data lines **181** are disposed on the upper substrate **101**, and define a plurality of pixel regions arranged in a matrix. Each pixel region comprises a plurality of pixel electrodes **111** and a plurality of common electrodes **121**. The pixel electrodes **111** and the common electrodes **121** have a similar arcuate configuration, and are uniformly spaced apart from each other. An upper alignment film **131** is disposed on the electrodes **111**, **121** and the upper substrate **101**.

Because the pixel and common electrodes **111**, **121** have arcuate configurations, the electric field generated by them

is a smooth continuum of multiple domains. The IPS LCD provides equally fine visual performance at various different viewing angles, and has a smaller color shift compared to the IPS LCD of the first embodiment.

Referring to FIG. 5 and FIG. 6, a reflective type in-plane switching liquid crystal display (IPS LCD) according to the third embodiment of the present invention comprises a transparent upper substrate **102**, a lower substrate **202**, and positive liquid crystal molecules **302** interposed between the upper and lower substrates **102**, **202**. An upper polarizer **162** and a lower polarizer **262** are disposed on outer sides of the substrates **102**, **202** respectively. A color filter **142** is disposed on an underside of the upper substrate **102**, and an alignment film **132** is disposed on an underside of the color filter **142**. A reflection layer **252** is disposed on an outer side of the lower alignment film **262**. The lower substrate **202** is transparent, so as to let light beams pass through and reach the reflection layer **252**. A plurality of gate lines **172** and data lines **182** are formed on the lower substrate **202**, and define a plurality of pixel regions arranged in a matrix. Each pixel region comprises a plurality of pixel electrodes **212** and a plurality of common electrode **222**. The pixel electrodes **212** and the common electrodes **222** have a similar wavy configuration, and are uniformly spaced apart from each other. A lower alignment film **232** is disposed on the electrodes **212**, **222** and the lower substrate **202**.

The electric field generated by the pixel and common electrodes **212**, **222** is a smooth continuum of multiple domains. The IPS LCD provides equally fine visual performance at various different viewing angles, and has a smaller color shift compared to the IPS LCD of the first embodiment. Moreover, the configuration of the data lines **182** is similar to that of the electrodes **212**, **222**. Because there is no driving electric field at the margins between the data lines and the electrodes **212**, **222**, the pixel region has a smaller non-driven portion. That is, the IPS LCD has a higher display efficiency compared to the IPS LCDs of the first and second embodiments.

Referring to FIG. 7, this is an inverted, cross-sectional view of the reflection layer **252** and the lower substrate **202**, not showing the lower polarizer **262**. The reflection layer **252** is multi-layer stack of dielectric materials. In particular, there are two dielectric materials: low refractive index polystyrene and high refractive index tellurium. The reflection layer **252** has a plurality of bumps **2521** for reflecting the light beams uniformly. In manufacturing the reflection layer **252**, small particles are disposed on the lower substrate **202**. Then the stack of dielectric materials is formed on the particles and the substrate **202**. In this way, the bumps **2521** of the reflection layer **252** are obtained.

In an alternative embodiment, the pixel electrodes and common electrodes may have different configurations. For example, the pixel electrodes may have a zigzagged configuration and the common electrodes may have a wavy configuration. Peaks of the pixel electrodes are spaced from peaks of the common electrodes, and troughs of the pixel electrodes are spaced from troughs of the common electrodes.

It is also to be generally understood that even though numerous characteristics and advantages of the present invention have been set out in the foregoing description, together with details of the structure and function of the invention, the disclosure is illustrative only, and changes may be made in detail, especially in matters of shape, size, and arrangement of parts within the principles of the invention to the full extent indicated by the broad general meaning of the terms in which the appended claims are expressed.

5

The invention claimed is:

1. A reflective type IPS (in-plane switching) liquid crystal display, comprising:

a transparent upper substrate;

a lower substrate;

liquid crystal molecules interposed between the substrates;

a reflection layer disposed at the lower substrate; and

a plurality of gate lines and a plurality of data lines disposed at one of the substrates, thereby defining a plurality of pixel regions arranged in a matrix;

wherein each pixel region comprises a plurality of pixel electrodes and a plurality of common electrode, the pixel electrodes and the common electrodes and the data lines each have an arcuate or wavy configuration, and the pixel electrodes and the common electrodes are uniformly spaced apart from each other.

6

2. The reflective type IPS liquid crystal display as claimed in claim 1, wherein the pixel electrodes and the common electrodes each have a zigzagged configuration.

3. The reflective type IPS liquid crystal display as claimed in claim 1, wherein the bent configuration of the pixel electrodes is different from the bent configuration of the common electrodes.

4. The reflective type IPS liquid crystal display as claimed in claim 1, wherein the reflection layer comprises a multilayer stack comprising a low refractive index material and a high refractive index material.

5. The reflective type IPS liquid crystal display as claimed in claim 4, wherein the low refractive index material is polystyrene and the high refractive index material is tellurium.

* * * * *

专利名称(译)	反射型连续域面内切换液晶显示器		
公开(公告)号	US7336332	公开(公告)日	2008-02-26
申请号	US11/028127	申请日	2004-12-31
[标]申请(专利权)人(译)	杨秋兴留置权 庞贾庞 陈觉JU		
申请(专利权)人(译)	杨秋兴留置权 庞贾鹏 陈觉-JU		
当前申请(专利权)人(译)	群创光电		
[标]发明人	YANG CHIU LIEN PANG JIA PANG CHEN CHUEH JU		
发明人	YANG, CHIU-LIEN PANG, JIA-PANG CHEN, CHUEH-JU		
IPC分类号	G02F1/1343 G02F1/1335		
CPC分类号	G02F1/134363		
审查员(译)	内尔姆斯, DAVID		
助理审查员(译)	CHUNG, DAVID Y.		
优先权	093108255 2004-03-26 TW		
其他公开文献	US20050212999A1		
外部链接	Espacenet USPTO		

摘要(译)

反射型IPS LCD包括透明上基板(100)和下基板(200),以及插入在基板之间的液晶分子(300)。反射层(250)设置在下基板上。在上基板上形成多条栅极线(170)和多条数据线(180),从而限定以矩阵排列的多个像素区域。每个像素区域包括像素电极(210)和公共电极(220)。像素电极和公共电极具有弯曲配置,并且彼此间隔开。因此,由它们产生的电场沿着两个方向,并且LCD表现出双域显示效果。当从任何倾斜角度观看LCD显示器时,由两个域产生的色移抵消,因此显示器的整体色移很小。

