



US008194198B2

(12) **United States Patent**
Wu et al.

(10) **Patent No.:** **US 8,194,198 B2**
(45) **Date of Patent:** **Jun. 5, 2012**

(54) **LIQUID CRYSTAL PANEL HAVING NOTCHES FOR REPAIR**

(75) Inventors: **Hong-Gi Wu**, Miao-Li (TW);
Chien-Ting Lai, Miao-Li (TW)

(73) Assignee: **Chimei Innolux Corporation**, Miaoli County (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 291 days.

(21) Appl. No.: **12/231,805**

(22) Filed: **Sep. 5, 2008**

(65) **Prior Publication Data**

US 2009/0066869 A1 Mar. 12, 2009

(30) **Foreign Application Priority Data**

Sep. 7, 2007 (CN) 2007 1 0077013

(51) **Int. Cl.**
G02F 1/1343 (2006.01)

(52) **U.S. Cl.** **349/39; 349/38**

(58) **Field of Classification Search** **349/38, 349/39**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,247,289 A * 9/1993 Matsueda 345/98
6,441,401 B1 * 8/2002 Jung et al. 257/72
6,657,231 B2 * 12/2003 Jung et al. 257/72

6,809,335 B2 * 10/2004 Park 257/59
7,116,393 B2 * 10/2006 Lee 349/192
7,291,860 B2 * 11/2007 Jung et al. 257/59
7,576,823 B2 * 8/2009 Kang et al. 349/141
7,733,456 B2 * 6/2010 Lee et al. 349/152
7,787,068 B2 * 8/2010 Choi et al. 349/54
2002/0149020 A1 * 10/2002 Jung et al. 257/72
2003/0107039 A1 * 6/2003 Jung et al. 257/72
2004/0090566 A1 * 5/2004 Jung et al. 349/43
2004/0174484 A1 * 9/2004 Matsumoto 349/139
2004/0257509 A1 * 12/2004 Lee et al. 349/139
2007/0002251 A1 * 1/2007 Chang et al. 349/141
2008/0158465 A1 * 7/2008 Choi et al. 349/54

FOREIGN PATENT DOCUMENTS

JP 2007-199436 A 8/2007
TW 200538833 A 12/2005

* cited by examiner


Primary Examiner — K. Cyrus Kianni

(74) *Attorney, Agent, or Firm* — Li & Cai Intellectual Property (USA) Office

(57) **ABSTRACT**

A liquid crystal panel of the present disclosure includes a first common electrode defining a plurality of first common electrode portions, a plurality of second common electrode portions connected to the first common electrode, and a plurality of pixel electrodes. Each pixel electrode overlaps one of the first common electrode portions and a corresponding one of the second common electrode portions, thereby forming storage capacitors therebetween. Each second common electrode portion defines a first notch adjacent to the pixel electrode. There is no overlap between the pixel electrode and the second common electrode portion at the first notch.

6 Claims, 3 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

1

LIQUID CRYSTAL PANEL HAVING NOTCHES FOR REPAIR

BACKGROUND

1. Field of the Invention

Embodiments of the present disclosure relate to a liquid crystal panel.

2. General Background

A typical liquid crystal display (LCD) is capable of displaying a clear and sharp image through thousands or even millions of pixels that make up the complete image. The liquid crystal display has thus been applied to various electronic equipment in which messages or pictures need to be displayed, such as mobile phones and notebook computers. A liquid crystal display generally includes a liquid crystal panel for displaying images, and a backlight for illuminating the liquid crystal panel.

In a process of fabricating the liquid crystal panel of the LCD, if an active substrate of the liquid crystal panel is not even enough, or when a heating or etching step is performed, a short circuit is liable to occur between a common electrode and a pixel electrode. In order to increase yield, the short circuit needs to be repaired.

However, when cutting one of the common and pixel electrodes to repair the short circuit therebetween, the common and pixel electrodes may both be inadvertently cut at the same time, thus creating another short circuit between the common and pixel electrodes. That is, the success rate of the repair process is apt to be low.

From the foregoing, it should be appreciated that there is a need for a liquid crystal display panel having an improved rate of success of repair.

SUMMARY

In one aspect, a liquid crystal panel includes a first common electrode defining a plurality of first common electrode portions, a plurality of second common electrode portions connected to the first common electrode, and a plurality of pixel electrodes. Each pixel electrode overlaps one of the first common electrode portions and a corresponding one of the second common electrode portions, thereby forming storage capacitors therebetween. Each second common electrode portion defines a first notch adjacent to the pixel electrode. There is no overlap between the pixel electrode and the second common electrode portion at the first notch.

In another aspect, a liquid crystal panel includes a first common electrode, a plurality of second common electrodes connected to the first common electrode, and a plurality of pixel electrodes. The pixel electrodes overlap respective portions of the first common electrode and the second common electrodes respectively, thereby forming storage capacitors therebetween. Each pixel electrode defines a first notch adjacent to a corresponding second common electrode with there being no overlap between the pixel electrode and the second common electrode at the first notch.

These and other objects and advantages of the present disclosure will become more apparent from the following description of certain inventive embodiments taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic of two adjacent pixels of a liquid crystal panel according to a first embodiment of the present disclosure.

2

FIG. 2 is a schematic of two adjacent pixels of a liquid crystal panel according to a second embodiment of the present disclosure.

FIG. 3 is a schematic of two adjacent pixels of a liquid crystal panel according to a third embodiment of the present disclosure.

FIG. 4 is a schematic of two adjacent pixels of a liquid crystal panel according to a fourth embodiment of the present disclosure.

FIG. 5 is a schematic of two adjacent pixels of a liquid crystal panel according to a fifth embodiment of the present disclosure.

FIG. 6 is a schematic of two adjacent pixels of a liquid crystal panel according to a sixth embodiment of the present disclosure.

DETAILED DESCRIPTION

FIG. 1 is a schematic of two adjacent pixels of a liquid crystal panel **20** according to a first embodiment of the present disclosure. In this embodiment, the liquid crystal panel **20** may include a plurality of parallel gate lines **201**, a plurality of parallel data lines **202** that are orthogonal to the gate lines **201**, a plurality of common electrodes **203**, and a plurality of pixel electrodes **204**. The plurality of gate lines **201** and the plurality of data lines **202** define a plurality of pixels (not labeled). The plurality of pixel electrodes **204** are positioned in the pixels, respectively. In each pixel, the common electrode **203** may include a first common electrode portion **2031** and a second common electrode portion **2032** perpendicular to the first common electrode portion **2031**. The first common electrode portion **2031** is parallel to the gate lines **201**, and the second common electrode portion **2032** is parallel to the data lines **202**. In each row of pixels, the first common electrode portions **2031** cooperatively form a single first common electrode (not labeled), which runs through the row of pixels. The second common electrode portions **2032** are electrically connected with the first common electrode at connection points **208**, respectively.

In each pixel, the pixel electrode **204** partially overlaps the first common electrode portion **2031** and the second common electrode portion **2032**, thereby forming a storage capacitor therebetween. The second common electrode portion **2032** defines a notch **205** adjacent to the connection point **208** and the pixel electrode **204**. Thus, there is no overlap between the pixel electrode **204** and the second common electrode portion **2032** at the notch **205**. In the illustrated embodiment, the notch **205** is semicircular or in the shape of a segment on a chord.

When a first short circuit point **2033** between the pixel electrode **204** and the first common electrode portion **2031** is detected, the pixel electrode **204** and the first common electrode portion **2031** can be disconnected by means of cutting the pixel electrode **204** along a cutting line **1** which corresponds to the notch **205**.

When a second short circuit point **2034** between the pixel electrode **204** and the second common electrode portion **2032** is detected, the pixel electrode **204** and the second common electrode portion **2032** can be disconnected by means of cutting the second common electrode portion **2032** along a cutting line **2** which corresponds to the notch **205**.

In summary, in each pixel, there is no overlap between the pixel electrode **204** and the second common electrode portion **2032** at the notch **205**, and the cutting lines **1**, **2** both correspond to the notch **205**. When cutting the pixel electrode **204** or the second common electrode portion **2032** along the cutting line **1** or **2** to solve the respective short circuit problem,

3

only one of the pixel electrode **204** and the second common electrode portion **2032** is cut. Therefore, there is little or no risk of another short circuit being created. Therefore, the rate of success of repair of the liquid crystal panel **20** is improved.

FIG. **2** is a schematic of two adjacent pixels of a liquid crystal panel **30** according to a second embodiment of the present disclosure. In this embodiment, the liquid crystal panel **30** may include a plurality of parallel gate lines **301**, a plurality of parallel data lines **302** that are orthogonal to the gate lines **301**, a plurality of common electrodes **303**, and a plurality of pixel electrodes **304**. The plurality of gate lines **301** and the plurality of data lines **302** define a plurality of pixels (not labeled). The plurality of pixel electrodes **304** are positioned in the pixels, respectively. In each pixel, the common electrode **203** may include a first common electrode portion **3031**, and a second common electrode portion **3032** perpendicular to the first common electrode portion **3031**. The first common electrode portion **3031** is parallel to the gate lines **301**, and the second common electrode portion **3032** is parallel to the data lines **302**. In each row of pixels, the first common electrode portions **3031** cooperatively form a single first common electrode (not labeled), which runs through the row of pixels. The second common electrode portions **3032** are electrically connected with the first common electrode at connection points **308**, respectively.

In each pixel, the pixel electrode **304** partially overlaps the first common electrode portion **3031** and the second common electrode portion **2032**, thereby respectively forming a storage capacitor therebetween. The pixel electrode **304** defines a notch **305** adjacent to the connection point **308** and the second common electrode portion **3032**. Thus, there is no overlap between the pixel electrode **304** and the second common electrode portion **3032** at the notch **305**. In the illustrated embodiment, the notch **305** is semicircular or in the shape of a segment on a chord.

FIG. **3** is a schematic of two adjacent pixels of a liquid crystal panel **40** according to a third embodiment of the present disclosure. The liquid crystal panel **40** is similar to the liquid crystal panel **20** of the first embodiment. However, a common electrode **403** in each pixel of the liquid crystal panel **40** further includes a third common electrode portion **4033**. In each pixel, the third common electrode portion **4033** is electrically connected with a first common electrode portion **4031** of a common electrode **403** at a connection point **408**. The pixel electrode **404** partially overlaps the third common electrode portion **4033**, thereby forming a storage capacitor therebetween. The third common electrode portion **4033** defines a notch **405** adjacent to the connection point **408** and the pixel electrode **404**. Thus, there is no overlap between the pixel electrode **404** and the third common electrode portion **4033** at the notch **405**. The third common electrode portion **4033** and the second common electrode portion **4032** are symmetrically opposite each other across a width of the pixel. In the illustrated embodiment, the notch **405** is semicircular or in the shape of a segment on a chord.

FIG. **4** is a schematic of two adjacent pixels of a liquid crystal panel **50** according to a fourth embodiment of the present disclosure. The liquid crystal panel **50** is similar to the liquid crystal panel **20** of the first embodiment. However, a pixel electrode **504** in each pixel of the liquid crystal panel **50** includes a notch **506** corresponding to a notch **505** of a corresponding second common electrode portion **5032**. In the illustrated embodiment, each of the notches **505**, **506** is semicircular or in the shape of a segment on a chord.

FIG. **5** is a schematic of two adjacent pixels of a liquid crystal panel **60** according to a fifth embodiment of the present disclosure. The liquid crystal panel **60** is similar to the

4

liquid crystal panel **40** of the third embodiment. However, a pixel electrode **604** in each pixel of the liquid crystal panel **60** defines two notches **606**, **608** at two opposite sides adjacent to a second common electrode portion **6032** and a third common electrode portion **6033**, respectively. The notches **606**, **608** respectively correspond to notches **605**, **607** of the second and third common electrode portions **6032**, **6033**. In the illustrated embodiment, each of the notches **605**, **606**, **607**, **608** is semicircular or in the shape of a segment on a chord. In one alternative embodiment, the notch **608** of the pixel electrode **604** may be omitted.

FIG. **6** is a schematic of two adjacent pixels of a liquid crystal panel **70** according to a sixth embodiment of the present disclosure. In this embodiment, the liquid crystal panel **70** may include a plurality of parallel gate lines **701**, a plurality of parallel data lines **702** that are orthogonal to the gate lines **701**, a plurality of common electrodes **703**, and a plurality of pixel electrodes **704**. The plurality of gate lines **701** and the plurality of data lines **702** define a plurality of pixels (not labeled). The plurality of pixel electrodes **704** are positioned in the pixels, respectively. In each pixel, the common electrode **703** may include a first common electrode portion **7031**, and a second common electrode portion **7032** perpendicular to the first common electrode portion **7031**. The first common electrode portion **7031** is parallel to the gate lines **701**, and the second common electrode portion **7032** is parallel to the data lines **702**. In each row of pixels, the first common electrode portions **7031** cooperatively form a single first common electrode (not labeled), which runs through the row of pixels. The second common electrode portions **7032** are electrically connected with the first common electrode at connection points **709**, respectively.

In each pixel, the pixel electrode **704** partially overlaps the first common electrode portion **7031** and the second common electrode portion **7032**, thereby respectively forming a storage capacitor therebetween. The second common electrode portion **7032** defines a notch **705** adjacent to the connection point **709** and the pixel electrode **704**. Thus, there is no overlap between the pixel electrode **704** and the second common electrode portion **7032** at the notch **705**. The second common electrode portion **7032** further includes two protrusions **7033** perpendicularly extending in a same direction to an underside of the nearest adjacent data line **702**. One of the protrusions **7033** is relatively near the connection point **709**, and the other protrusion **7033** is far away from the connection point **709**.

When a break **708** in the data line **702** is detected, the two protrusions **7033** are connected to the data line **702** respectively by a welding method, and the second common electrode portion **7032** is cut along a cutting line **1** at the notch **709**. Accordingly, the two separated parts of the data line **702** are reconnected through a portion of the second common electrode portion **7032**, and therefore the data line **702** can work normally.

It is to be further understood that even though numerous characteristics and advantages of the present embodiments have been set out in the foregoing description, together with details of the structures and functions of the embodiments, the disclosure is illustrative only; and that changes may be made in detail, especially in matters of shape, size and arrangement of parts within the principles of the invention to the full extent indicated by the broad general meaning of the terms in which the appended claims are expressed.

What is claimed is:

1. A liquid crystal panel comprising:
 - a plurality of gate lines parallel to each other; and

5

a plurality of data lines parallel to each other and extending perpendicular to the gate lines, the gate lines and data lines thereby defining a plurality of pixel regions, each pixel region comprising:

a common electrode comprising a first common electrode portion substantially parallel to the gate lines and a second common electrode portion substantially parallel to the data lines, the second common electrode portion electrically connected to the first common electrode portion; and

a pixel electrode; wherein the second common electrode portion comprises a first inner boundary adjacent to a corresponding data line and a first outer boundary opposite to the first inner boundary and adjacent to the pixel electrode, a portion of the first outer boundary is convex towards the first inner boundary such that a distance between the first inner boundary and the first outer boundary is at its narrowest at the convex portion, the pixel electrode overlaps the first common electrode portion and the second common electrode portion, thereby forming storage capacitors therebetween, and there is no overlap between the pixel electrode and the convex portion of the first outer boundary of the second common electrode portion.

2. The liquid crystal panel in claim 1, wherein the pixel electrode comprises a second inner boundary adjacent to the second common electrode portion and a second outer boundary opposite to the second inner boundary, a portion of the second inner boundary is convex towards the second outer boundary to allow the pixel electrode to have a narrower distance between the second inner boundary and the second outer boundary at the convex portion of the second inner boundary than a distance between the second inner boundary and the second outer boundary at other portions of the second inner boundary, the convex portion of the second inner boundary corresponding to the convex portion of the first outer boundary.

6

3. The liquid crystal panel in claim 2, wherein the second common electrode portion is connected with the first common electrode portion at a first connection point, the first convex portion being adjacent to the first connection point.

4. The liquid crystal panel in claim 3, wherein in each pixel, the common electrode further comprises a third common electrode portion, the third common electrode portion being connected with the first common electrode portion at a second connection point, the third common electrode portion and the second common electrode portion being symmetrically opposite each other across a width of the pixel, the pixel electrode overlapping the third common electrode portion thereby forming a storage capacitor therebetween.

5. The liquid crystal panel in claim 4, wherein the third common electrode portion comprises a third inner boundary adjacent to the second common electrode portion and a third outer boundary opposite to the third inner boundary, a portion of the third inner boundary is convex towards the third outer boundary to allow the third common electrode portion to have a narrower distance between the third inner boundary and the third outer boundary at the convex portion of the third inner boundary than a distance between the third inner boundary and the third outer boundary at other portions of the third inner boundary, with there being no overlap between the pixel electrode and the convex portion of the third inner boundary of the third common electrode portion.

6. The liquid crystal panel in claim 5, wherein a portion of the second outer boundary is convex towards the second inner boundary to allow the pixel electrode to have a narrower distance between the second inner boundary and the second outer boundary at the convex portion of the second outer boundary than a distance between the second inner boundary and the second outer boundary at other portions of the second outer boundary without the convex portion, the convex portion of the second outer boundary corresponding to the convex portion of the third inner boundary.

* * * * *

专利名称(译)	具有用于修复的凹口的液晶面板		
公开(公告)号	US8194198	公开(公告)日	2012-06-05
申请号	US12/231805	申请日	2008-09-05
[标]申请(专利权)人(译)	群创光电股份有限公司		
申请(专利权)人(译)	群创光电股份有限公司.		
当前申请(专利权)人(译)	群创光电		
[标]发明人	WU HONG GI LAI CHIEN TING		
发明人	WU, HONG-GI LAI, CHIEN-TING		
IPC分类号	G02F1/1343		
CPC分类号	G02F1/136259 G02F2001/136268		
优先权	200710077013.9 2007-09-07 CN		
其他公开文献	US20090066869A1		
外部链接	Espacenet USPTO		

摘要(译)

本公开的液晶面板包括：第一公共电极，限定多个第一公共电极部分；多个第二公共电极部分，连接到第一公共电极；以及多个像素电极。每个像素电极与第一公共电极部分中的一个和第二公共电极部分中的相应一个重叠，从而在它们之间形成存储电容器。每个第二公共电极部分限定与像素电极相邻的第一凹口。在第一凹口处的像素电极和第二公共电极部分之间没有重叠。

