



US 20020109809A1

(19) **United States**(12) **Patent Application Publication**

Utsumi et al.

(10) **Pub. No.: US 2002/0109809 A1**(43) **Pub. Date: Aug. 15, 2002**(54) **LIQUID CRYSTAL DISPLAY****Publication Classification**

(76) Inventors: **Yuka Utsumi**, Hitachi (JP); **Ikuo Hiyama**, Hitachinaka (JP); **Shinichi Komura**, Hitachi (JP); **Katsumi Kondo**, Mito (JP)

(51) **Int. Cl.⁷** **G02F 1/1335**(52) **U.S. Cl.** **349/105**

Correspondence Address:

**ANTONELLI TERRY STOUT AND KRAUS
SUITE 1800****1300 NORTH SEVENTEENTH STREET
ARLINGTON, VA 22209**(21) Appl. No.: **09/956,138**(22) Filed: **Sep. 20, 2001**(30) **Foreign Application Priority Data**

Feb. 9, 2001 (JP) 2001-034014

(57) **ABSTRACT**

A liquid crystal display for displaying an image to be visible for a viewer, has a liquid crystal, a pair of electrodes for controlling an orientation of at least a part of the liquid crystal in accordance with an electric field between the electrodes, a light source for generating a light to be transmitted through the liquid crystal to the viewer, a pair of first and second polarizer plates, the first polarizer plate being arranged between the liquid crystal and the light source, and the second polarizer plate being arranged between the liquid crystal and the viewer, and a band-pass filter for absorbing a component of the light, a wave-length of which component is not more than 440 nm, and the band-pass filter being arranged between the light source and the viewer.




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 4A

FIG. 4B




FIG. 4C

FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18





FIG. 19



LIQUID CRYSTAL DISPLAY

BACKGROUND OF THE INVENTION AND RELATED ART STATEMENT

[0001] The present invention relates to a liquid crystal display for displaying an image to be visible for a viewer.

[0002] JP-A-8-015697 discloses that a color toner adjuster for adjusting a color tone of a light as a back light generated by a fluorescent light source is arranged between the fluorescent light source and a light guide for distributing constantly the back light over a liquid crystal display panel in a STN type liquid crystal display unit.

[0003] JP-A-2000-206544 discloses that an unevenness in an image to be displayed is restrained by preventing a liquid crystal from being contaminated by a liquid crystal cell sealing resin before being cured, in an active matrix in-plane switching mode liquid crystal display in which a pair of comb-shaped electrodes is used.

[0004] JP-A-2000-19543 discloses a method for restraining an unevenness in an image caused by an error in dimension of electrodes.

[0005] JP-A-10-170923 discloses that a twisted connection between a liquid crystal molecule and a directing layer surface at the interface therebetween is made weak to decrease the unevenness in the image caused by an error in distance between substrates between which the liquid crystal is arranged.

OBJECT AND SUMMARY OF THE INVENTION

[0006] An object of the present invention is to provide a liquid crystal display for displaying an image to be visible for a viewer, in which a so-called blue fog phenomenon is restrained even when a brightness of the image is low. The lower a voltage for controlling an orientation of a liquid crystal is, the higher a permeability of the liquid crystal for a blue color light is. When the voltage for controlling the orientation of the liquid crystal is close to a threshold voltage of the liquid crystal so that a transmittance of the liquid crystal for the light is low, that is, a brightness of the display is low, a light of wave-length 400-440 nm as a blue color light is more effectively transmitted through the liquid crystal in comparison with another light of wave-length not less than 440 nm, and a difference in brightness and a difference in color can be clearly visible. Therefore, the so-called blue fog phenomenon occurs.

[0007] According to the invention, a liquid crystal display for displaying an image to be visible for a viewer, comprises, a liquid crystal, a pair of electrodes for controlling a molecular orientation of at least a part of the liquid crystal in accordance with an electric field between the electrodes, a light source for generating a light to be transmitted through the liquid crystal to the viewer, a pair of first and second polarizer plates, the first polarizer plate being arranged between the liquid crystal and the light source, and the second polarizer plate being arranged between the liquid crystal and the viewer, and a band-pass filter for absorbing a component of the light, a wave-length of which component is not more than 440 nm, and the band-pass filter being arranged between the light source and the viewer.

[0008] Since the band-pass filter for absorbing the component of the light, a wave-length of which component is not

more than 440 nm, is arranged between the light source and the viewer, when the voltage for controlling the molecular orientation of the liquid crystal is close to a threshold voltage of the liquid crystal so that a transmittance of the liquid crystal for the light is low, that is, a brightness of the display is low, and a light of wave-length 400-440 nm as a blue color light is more effectively transmitted through the liquid crystal in comparison with another light of wave-length not less than 440 nm, the light of wave-length 400-440 nm as the blue color light is restrained from reaching the viewer, so that the so-called blue fog phenomenon is prevented.

[0009] In order to generate correctly another color visible for the viewer while the so-called blue fog phenomenon is prevented, it is preferable that a transmittance of the band-pass filter for the component of wave-length not more than 440 nm is smaller than a transmittance of the band-pass filter for another component of the light, a wave-length of which another component is not less than 450 nm, that a transmittance of the band-pass filter for the component of wave-length 400-440 nm is smaller than a transmittance of the band-pass filter for another component of the light, a wave-length of which another component is not less than 450 nm, that a transmittance of the band-pass filter decreases in accordance with a decrease of a wave-length of a light to be transmitted through the band-pass filter when the wave-length of the light to be transmitted through the band-pass filter is less than 450 nm, and/or that a transmittance of the band-pass filter decreases in accordance with a decrease of a wave-length of a light to be transmitted through the band-pass filter when the wave-length of the light to be transmitted through the band-pass filter is 400-440 nm.

[0010] The band-pass filter may be arranged between the light source and a light guide for guiding the light from the light source to the liquid crystal to distribute the light evenly over the liquid crystal. When a diffusing plate for distributing constantly the light over the liquid crystal is arranged between the light guide and the liquid crystal, and the band-pass filter may be arranged between the diffusing plate and the light guide. The band-pass filter may be arranged on the light source. The band-pass filter may be arranged on the light guide. When the liquid crystal display comprises a pair of first and second substrates being at least partially transparent and the liquid crystal is arranged between the first and second substrates, the band-pass filter may be arranged on at least one of the first and second substrates. The band-pass filter may be arranged on at least one of the first and second polarizer plates. The band-pass filter is preferably arranged between the light source and the liquid crystal.

[0011] When the liquid crystal display comprises a color filter including a portion for transmitting therethrough a blue light, the portion includes an agent for absorbing the component of the light as the band-pass filter.

[0012] The band-pass filter may be a stack of layers. The band-pass filter may be a polymer for absorbing the component of the light. The band-pass filter may be a resin including an agent for absorbing the component of the light.

[0013] The light source may include a fluorescent substance for generating the light. The liquid crystal and the pair of first and second polarizer plates may form a normally close type liquid crystal display unit. A direction in which the light is transmitted in the liquid crystal may be prevented from being parallel to a direction in which the electric field

is generated or may be transverse with respect to the direction in which the electric field is generated. The liquid crystal and the pair of first and second polarizer plates may form a super twisted nematic type liquid crystal display unit.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] **FIG. 1** is a cross-sectional view showing a liquid crystal display of in-plane switching mode of the invention.

[0015] **FIG. 2** is a schematic view showing an angular relationship among an alignment direction of long axis of liquid crystal molecule, a direction of electric field and a polarized light transmitted axis of a polarizer plate.

[0016] **FIGS. 3a-3d** are views showing a change of the alignment direction of long axis of liquid crystal molecule by the electric field.

[0017] **FIGS. 4a-4c** are detailed views showing electrodes, insulating layers, and alignment layers.

[0018] **FIG. 5** is a diagram showing a crystal liquid driving circuit.

[0019] **FIG. 6** is a diagram showing a spectrum generated by a cold cathode of narrow band light emitting type.

[0020] **FIG. 7** is a diagram showing a relationship between a wave length of a light and a band-pass filter therefor of the invention.

[0021] **FIG. 8** is a chromaticity diagram according to CIE1931 of the international illumination committee, showing differences in color.

[0022] **FIG. 9** is an oblique projection view showing the liquid crystal display of in-plane switching mode liquid crystal display apparatus of the invention.

[0023] **FIG. 10** is a diagram showing a spectral characteristic of the normally-close in-plane switching mode liquid crystal display.

[0024] **FIG. 11** is a chromaticity diagram according to CIE1931 of the international illumination committee, showing differences in color.

[0025] **FIG. 12** is a chromaticity diagram according to CIE1931 of the international illumination committee, showing differences in color.

[0026] **FIG. 13** is a cross-sectional view showing a STN liquid crystal display of normally close type of the invention.

[0027] **FIG. 14** is a chromaticity diagram according to CIE1931 of the international illumination committee, showing differences in color.

[0028] **FIG. 15** is a cross-sectional view showing another STN liquid crystal display of reflection and transmission combination type of the invention.

[0029] **FIG. 16** is a cross-sectional view showing another arrangement of a light guide, a band-pass filter and a diffusion plate.

[0030] **FIG. 17** is a diagram showing a relationship between a brightness and a wave length in red, green and blue light emitting LEDs.

[0031] **FIG. 18** is a diagram showing a relationship between a brightness and a spectrum in STN liquid crystal display.

[0032] **FIG. 19** is a diagram showing a relationship between a brightness feeling and an actual brightness or luminous intensity.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0033] In a liquid crystal display of in-plane switching mode, as shown in **FIG. 1**, a back-light light source unit has a light source **1**, a cover **2**, a light guide **3**, a diffusing plate **4**, and a reflection plate **5**. An adhesive layer (not shown) adheres to the light guide **3** and the diffusing plate **4** to prevent a loss of light through an air between the light guide **3** and the diffusing plate **4**. A light collector sheet may be arranged between the diffusing plate **4** and a polarizer plate **12**. In this embodiment, a spectrum absorber **40** is arranged between the light source **1** and the light guide **3**. The spectrum absorber **40** is a band-pass filter including a plurality of stacks of layers for absorbing a visible light of wavelength 400-440 nm. A liquid crystal display panel of in-plan switching mode in which an electric field applied to a liquid crystal layer **10** is substantially parallel to a substrate is used as a normally-close type liquid crystal display utilizing birefringence of the first embodiment. In the liquid crystal display panel, the liquid crystal layer **10** is arranged between substrates **13** and **14**, and the substrates **13** and **14** are arranged between the polarizer plates **11** and **12**.

[0034] An inner surface of the substrate **14** has stripe-shaped electrodes **22** and **23**, and an alignment layer **15** covering the electrodes **22** and **23**. The electrode **22** is a common electrode to which a voltage of predetermined wave form other than an image signal voltage is applied, and the electrode **23** is an image pixel electrode to which a wave form of voltage changeable in accordance with the image signal is applied. An image signal electrode **24** is arranged at the same height as the image pixel electrode **23**. An insulating layer **21** of silicon-nitride is formed between the electrodes. The substrate **13** has a color filter **16** for multi-color display. The color filter **16** may be formed on the substrate **14** with the electrodes. The alignment layer **15** is formed by coating the substrate with a solution of 3% concentration poly-amicacid, baking the poly-amicacid under 200° C. for 30 minutes to be changed to a polyimide layer, and rubbing a surface of the polyimide layer. The alignment layer **15** may be formed by being irradiated with a polarized ultraviolet rays.

[0035] **FIG. 2** shows a relationship in angle among the electric field **93**, a long axis **91** of liquid crystal molecule, and a polarized light transmitted axis **92** of the polarizer plate. The polarizing directions of the polarizer plates **11** and **12** are perpendicular to each other to form the normally-close type liquid crystal display utilizing birefringence. A luminous intensity of the transmitted light is calculated by the following formula wherein Δn is an anisotropy in refractive index, θ is an angle between the polarized light permeable axis and the long or effective axis **91** of liquid crystal molecule, d_{eff} is a thickness of the liquid crystal layer, T_0 is a coefficient determined in accordance with a permeability of light of the polarizer plate, and λ is a wave length of the light to be transmitted.

$$T = T_0 \cdot \sin^2 2\theta \cdot \sin^2 [(\pi \cdot d_{\text{eff}} \cdot \Delta n) / \lambda]$$

[0036] The liquid crystal layer **10** is a nematic liquid crystal of positive anisotropy in dielectric constant, the

anisotropy in dielectric constant is 10.2, and the anisotropy in refractive index Δn is 0.073.

[0037] A permeability of light of the liquid crystal layer **10** is changed as shown in **FIG. 3**. Areas (a) and (b) show a non-energized condition, and areas (b) and (d) show an energized condition in which the angle θ between the long or effective axis **91** of liquid crystal molecule and the polarized light permeable axis **92** of the polarizer plate is changed by the electric field **93**.

[0038] As shown in **FIG. 4**, The inner surface of the substrate **14** has the stripe-shaped electrodes **22** and **23**, and the image signal electrodes **24** is arranged at the same height as the electrode **23** on the inner surface of the substrate **14**. A scanning electrode (gate wiring electrode) **25** extends perpendicularly to the image signal electrodes **24**. The alignment layer **15** is formed on the electrodes. An area on the substrate includes both an amorphous-silicon area **101** and a TFT element **102**.

[0039] As shown in **FIG. 5**, a liquid crystal display driver includes, for example, a common electrode driver circuit **103**, a vertical scanning signal circuit **104**, an image signal circuit **105** and an electric source and controller circuit **106**.

[0040] **FIG. 6** shows a spectrum generated by a cold cathode of narrow band light emitting type having a spectrum characteristic of a three band fluorescent light source. A peak in the spectrum is generated at a wave-length of 435 nm when this type fluorescent light source including mercury for energizing phosphor is used. In order to restrain a blue fog phenomenon in the liquid crystal display, the peak in the spectrum needs to be absorbed. Therefore, the band-pass filter **40** is arranged between the cold cathode of narrow band light emitting type **1** and the light guide **3**. A plurality of sets each including a low refractive index dielectric layer such as magnesium-fluoride, silicon-oxide or the like, and a high refractive index dielectric layer such as zirconium-oxide, titanium-oxide or the like are stacked by a vapor deposition process until a number of layers reaches 6-20.

[0041] As shown in **FIG. 7**, the band-pass filter **40** absorbs effectively a light of wave-length not more than 440 nm, so that the blue fog phenomenon is restrained.

[0042] In a chromaticity diagram as shown in **FIG. 8** according to CIE1931 of the international illumination committee, a point A indicates to a chromaticity obtained by the prior art normally-close transverse electric field type liquid crystal display when a dark color is generated, and a point B indicates to a chromaticity obtained by the in-plane switching mode type liquid crystal display of the invention with the band-pass filter **40** when the dark color is generated. A point A' indicates to a chromaticity obtained by the prior art normally-close in-plane switching mode liquid crystal display when a bright color is generated, and a point B' indicates to a chromaticity obtained by the in-plane switching mode liquid crystal display of the invention with the band-pass filter **40** when the bright color is generated. A point X indicates to a chromaticity of sun-light. An area of relatively small values of x and y corresponds to a relatively blue color, and an area of relatively large values of x and y corresponds to a relatively yellow color. The point A shows that the prior art normally-close transverse electric field type liquid crystal display emphasizes strongly the blue color, and the point B shows that the invention restrains the blue

color from being emphasized. The points A' and B' show that the chromaticities by the transverse electric field type liquid crystal display of the invention and the prior art normally-close in-plane switching mode type liquid crystal display are not different largely from each other when the bright color is generated. Therefore, the transverse electric field type liquid crystal display of the invention with the band-pass filter **40** restrains only the blue fog phenomenon, but does not have a large influence for the bright color indication. The band-pass filter **40** absorbs strongly the light of wave-length not more than 440 nm, but restrains the light of wave-length preferably more than 440 nm or practically not less than 450 nm from being absorbed strongly by the band-pass filter **40**.

[0043] As shown in **FIG. 9**, the light sources **1** are arranged at respective sides of a lower case **63** with an inverter drive circuit **64**. The reflecting plate **5**, the light guide **4**, the diffusion plate **4** and the liquid crystal display panel **70** are mounted on the lower case **63**. An upper side of the lower case **63** is covered by a shield case **61** having a display window.

[0044] The light of wave-length not more than 440 nm does not have a large influence for brightness. On the other hand, a permeability of the light of wave-length 400-440 nm is high when a brightness of the normally-close in-plane switching mode liquid crystal display is low, and is low when a brightness of the normally-close in-plane switching mode liquid crystal display is high. Therefore, the blue fog phenomenon occurs and the brightness of display is not changed largely by the light of wave-length not more than 440 nm when brightness of the normally-close in-plane switching mode liquid crystal display is low, and the brightness of display is not changed largely by the light of wave-length not more than 440 nm when brightness of the normally-close in-plane switching mode liquid crystal display is high.

[0045] In **FIG. 10** showing a spectral characteristic of the normally-close transverse electric field type liquid crystal display, a thick line **81** shows that a permeability of the light of wave-length not more than 440 nm is high and the permeability of the light decreases in accordance with an increase of the wave-length when the brightness is small, and a thin line **82** shows that a permeability of the light of wave-length not more than 440 nm is low and the permeability of the light increases in accordance with an increase of the wave-length when the brightness is high.

[0046] In a chromaticity diagram according to CIE1931 of the international illumination committee, as shown in **FIG. 11**, a point Ha indicating a chromaticity obtained by the normally-close in-plane switching mode liquid crystal display including the band-pass filter **40** absorbing strongly the light of wave-length not more than 430 nm when the dark color is generated is not different largely from the point A indicating the chromaticity obtained by the prior art normally-close transverse electric field type liquid crystal display when the dark color is generated. Therefore, the normally-close transverse electric field type liquid crystal display including the band-pass filter **40** absorbing strongly the light of wave-length not more than 430 nm cannot restrain effectively the blue fog phenomenon. A point Hb indicating a chromaticity obtained by the normally-close transverse electric field type liquid crystal display including the band-pass filter **40** absorbing strongly the light of

wave-length not more than 430 nm when the bright color is generated is not different largely from the point A' indicating the chromaticity obtained by the prior art normally-close transverse electric field type liquid crystal display when the bright color is generated.

[0047] In a chromaticity diagram according to CIE1931 of the international illumination committee, as shown in FIG. 12, a point Hc indicating a chromaticity obtained by the normally-close transverse electric field type liquid crystal display including the band-pass filter 40 absorbing strongly the light of wave-length not more than 450 nm when the dark color is generated is different largely from the point A indicating the chromaticity obtained by the prior art normally-close transverse electric field type liquid crystal display when the dark color is generated. Therefore, the normally-close transverse electric field type liquid crystal display including the band-pass filter 40 absorbing strongly the light of wave-length not more than 450 nm can restrain effectively the blue fog phenomenon. On the other hand, a point Hd indicating a chromaticity obtained by the normally-close transverse electric field type liquid crystal display including the band-pass filter 40 absorbing strongly the light of wave-length not more than 450 nm when the bright color is generated is different largely from the point A' indicating the chromaticity obtained by the prior art normally-close transverse electric field type liquid crystal display when the bright color is generated. Therefore, yellow is emphasized in the bright color.

[0048] As shown in FIG. 13, a normally close STN type liquid crystal display has a transparent Y electrode on the transparent substrate 13, a transparent X electrode on the transparent substrate 14, the color filter 16, a black matrix 17 and a flattening layer 18. Each of the transparent substrates 13 and 14 between which the liquid crystal 10 is arranged has the directing layer 15 of polyimide whose surface is treated by rubbing. The X and Y electrodes are energized by a driver (not shown). The polarizer plate 11 and a phase plate 33 of polycarbonate are arranged at an outside of the transparent substrate 13, and the polarizer plate 12 and a phase plate 34 of polycarbonate are arranged at an outside of the transparent substrate 14. The phase plate 34 may be arranged between the polarizer plate 11 and the phase plate 33 or between the substrate 13 and the phase plate 33. The liquid crystal layer 10 of thickness 6.2 μm is a nematic liquid crystal of positive anisotropy in dielectric constant, and the anisotropy in refractive index Δn is 0.144. The nematic liquid crystal includes a chiral agent (such as S811 of Merc Inc.,) to have a twist angle of 240 degrees.

[0049] In this case, an azimuth angle of the polarizing axis of the lower polarizer plate 12 is 10 degrees, an azimuth angle of the polarizing axis of the upper polarizer plate 11 is 80 degrees, an azimuth angle of slow axis of the lower phase plate 34 is 110 degrees, an azimuth angle of slow axis of the upper phase plate 33 is 70 degrees, and retardations of the phase plates 33 and 34 are 400 nm. The azimuth angles are set in such a manner that the twist angle is 240 degrees, and rubbed angles of the upper and lower directing layers are ± 30 degrees with respect to a longitudinal direction of the liquid crystal display panel. The arrangement of the light source unit and the band-pass filter 40 is the same as the embodiment shown in FIG. 1.

[0050] In a chromaticity diagram according to CIE1931 of the international illumination committee, as shown in FIG.

14, the band-pass filter 40 restrains the blue fog phenomenon in the normally close STN type liquid crystal display.

[0051] As shown in FIG. 15, a reflection and transmission combination STN type liquid crystal display panel has a transmission area formed by a transparent electrode 31 of, for example, ITO, and a reflection area formed by a reflection electrode 51 of, for example, aluminum in each pixel on the substrate 14. When the electrodes are formed on the substrate, a transparent electrode layer of, for example, ITO is deposited by sputtering process on the transparent substrate 14, and a part of the transparent electrode layer is removed to form a pattern of the transparent electrode layer as the transparent electrode 31. Subsequently, a reflection electrode layer of, for example, aluminum is deposited thereon, and a part of the reflection electrode layer is removed to form a pattern of the reflection electrode layer as the reflection electrode 52. The color filter (not shown) is formed on the substrate.

[0052] When this reflection and transmission combination STN type liquid crystal display panel is used with the light source unit and the band-pass filter 40 as described above, the blue fog phenomenon is also restrained effectively. The reflection electrode may be formed on the transparent electrode. The transparent electrode and the reflection electrode may be driven electrically independently of each other.

[0053] As shown in FIG. 16, a band-pass filter 41 having the same absorption characteristic for the light as the band-pass filter 40 may be arranged between the light guide 3 and the diffusing plate 4. The fluorescent light source 1 may be arranged under the light guide 3.

[0054] An acrylic type polymer layer including cyano-acrylate absorbent may be used as the band-pass filters 40 and 41. The acrylic type polymer layer including cyano-acrylate absorbent may be formed on the light guide 3 by coating a rotated surface of the light guide 3 with the acrylic type polymer layer of monomer condition including cyano-acrylate absorbent, and polymerizing the acrylic type polymer layer of monomer condition including cyano-acrylate absorbent on the surface of the light guide 3. The cyano-acrylate absorbent absorbs effectively the light of wave-length 400-440 nm. The acrylic type polymer layer including cyano-acrylate absorbent may be arranged directly on the three band fluorescent light source 1 or LED. The band-pass filters 40 or 41 may be arranged directly on the three band fluorescent light source 1 or LED. The light source may be formed by a combination of monochromatic red, green blue LEDs.

[0055] As shown in FIG. 17, the blue LED generates the light of wave-length 450-480 nm, the green LED generates the light of wave-length 520-570 nm, and the red LED generates the light of wave-length 600-660 nm. An extremely small amount of light of wave-length not more than 440 nm is absorbed by the band-pass filters 40 and 41 between the light guide 3 and the diffusing plate 4 to restrain the blue fog phenomenon.

[0056] The cyano-acrylate absorbent absorbing effectively the light of wave-length 400-440 nm may be included by the adhesive between the polarizer plate 12 and the phase plate 51 shown in FIG. 15. In this case, the diffusing plate 4 is not necessary.

[0057] The acrylic type polymer layer including cyano-acrylate absorbent absorbing effectively the light of wave-

length 400-440 nm may be arranged on the substrate **13**. The band-pass filters **40** or **41** or the absorbent absorbing effectively the light of wave-length 400-440 nm may be arranged between the liquid crystal display panel and a viewer of the liquid crystal display. The color filter may include the absorbent absorbing effectively the light of wave-length 400-440 nm. The absorbent absorbing effectively the light of wave-length may be included by a blue color filter or an overcoat layer of the color filter.

What is claimed is:

1. A liquid crystal display for displaying an image to be visible for a viewer, comprising,

a liquid crystal,

a pair of electrodes for controlling an orientation of at least a part of the liquid crystal in accordance with an electric field between the electrodes,

a light source for generating a light to be transmitted through the liquid crystal to the viewer,

a pair of first and second polarizer plates, the first polarizer plate being arranged between the liquid crystal and the light source, and the second polarizer plate being arranged between the liquid crystal and the viewer, and

a band-pass filter for absorbing a component of the light, a wave-length of which component is not more than 440 nm, and the band-pass filter being arranged between the light source and the viewer.

2. A liquid crystal display according to claim 1, wherein a permeability of the band-pass filter for the component of wave-length not more than 440 nm is smaller than a permeability of the band-pass filter for another component of the light, a wave-length of which another component is not less than 450 nm.

3. A liquid crystal display according to claim 1, wherein a permeability of the band-pass filter for the component of wave-length 400-440 nm is smaller than a permeability of the band-pass filter for another component of the light, a wave-length of which another component is not less than 450 nm.

4. A liquid crystal display according to claim 1, wherein a permeability of the band-pass filter decreases in accordance with a decrease of a wave-length of a light to be transmitted through the band-pass filter when the wave-length of the light to be transmitted through the band-pass filter is less than 450 nm.

5. A liquid crystal display according to claim 1, wherein a permeability of the band-pass filter decreases in accordance with a decrease of a wave-length of a light to be transmitted through the band-pass filter when the wave-length of the light to be transmitted through the band-pass filter is 400-440 nm.

6. A liquid crystal display according to claim 1, further comprising a light guide for guiding the light from the light source to the liquid crystal, wherein the band-pass filter is arranged between the light source and the light guide.

7. A liquid crystal display according to claim 1, further comprising a light guide for guiding the light from the light source, and a diffusing plate for distributing constantly the light over the liquid crystal, wherein the diffusing plate is arranged between the light guide and the liquid crystal, and the band-pass filter is arranged between the diffusing plate and the light guide.

8. A liquid crystal display according to claim 1, wherein the band-pass filter is arranged on the light source.

9. A liquid crystal display according to claim 1, further comprising a light guide for guiding the light from the light source to the liquid crystal, wherein the band-pass filter is arranged on the light guide.

10. A liquid crystal display according to claim 1, further comprising a pair of a first substrate being transparent and a second substrate being at least partially transparent, wherein the liquid crystal is arranged between the first and second substrates, the band-pass filter is arranged on at least one of the first and second substrates.

11. A liquid crystal display according to claim 1, further comprising a color filter including a portion for transmitting therethrough a blue light, wherein the portion includes an agent for absorbing the component of the light as the band-pass filter.

12. A liquid crystal display according to claim 1, wherein the band-pass filter is arranged on at least one of the first and second polarizer plates.

13. A liquid crystal display according to claim 1, wherein the band-pass filter is a stack of layers.

14. A liquid crystal display according to claim 1, wherein the band-pass filter is a polymer for absorbing the component of the light.

15. A liquid crystal display according to claim 1, wherein the band-pass filter is a resin including an agent for absorbing the component of the light.

16. A liquid crystal display according to claim 1, wherein the light source includes a fluorescent substance for generating the light.

17. A liquid crystal display according to claim 1, wherein the liquid crystal and the pair of first and second polarizer plates forms a normally close type liquid crystal display unit.

18. A liquid crystal display according to claim 1, wherein a direction in which the light is transmitted in the liquid crystal is transverse with respect to a direction in which the electric field is generated.

19. A liquid crystal display according to claim 1, wherein the liquid crystal and the pair of first and second polarizer plates forms a super twisted nematic type liquid crystal display unit.

20. A liquid crystal display according to claim 1, wherein the band-pass filter is arranged between the light source and the liquid crystal.

* * * * *

专利名称(译)	液晶显示器		
公开(公告)号	US20020109809A1	公开(公告)日	2002-08-15
申请号	US09/956138	申请日	2001-09-20
[标]申请(专利权)人(译)	Utsumi Yuka 桧山郁夫 高村正彦SHINICHI 近藤克己		
申请(专利权)人(译)	Utsumi Yuka 桧山郁夫 高村正彦SHINICHI 近藤克己		
当前申请(专利权)人(译)	Utsumi Yuka 桧山郁夫 高村正彦SHINICHI 近藤克己		
[标]发明人	UTSUMI YUKA HIYAMA IKUO KOMURA SHINICHI KONDO KATSUMI		
发明人	UTSUMI, YUKA HIYAMA, IKUO KOMURA, SHINICHI KONDO, KATSUMI		
IPC分类号	G02F1/133 G02F1/1335 G02F1/13357 G02F1/1368 G09F9/00		
CPC分类号	G02F1/133509 G02F1/133514		
优先权	2001034014 2001-02-09 JP		
其他公开文献	US6646699		
外部链接	Espacenet USPTO		

摘要(译)

一种用于显示对于观看者可见的图像的液晶显示器，具有液晶，用于根据电极之间的电场控制至少一部分液晶的取向的一对电极，光源用于产生通过液晶传输到观察者的光，一对第一和第二偏振片，第一偏振片设置在液晶和光源之间，第二偏振片设置在液晶之间观察器和用于吸收光的分量的带通滤波器，其波长的分量不大于440nm，并且带通滤波器设置在光源和观察者之间。

