



US 20040233358A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2004/0233358 A1****Wu et al.**(43) **Pub. Date: Nov. 25, 2004**

(54) **TRANSFLECTIVE LIQUID CRYSTAL
DISPLAY DEVICE CAPABLE OF
BALANCING COLOR DIFFERENCE
BETWEEN REFLECTIVE AND
TRANSMISSIVE REGIONS**

(30) **Foreign Application Priority Data**

May 23, 2003 (TW)..... 92113955


Publication Classification(51) **Int. Cl.⁷** G02F 1/1335(52) **U.S. Cl.** 349/114

(76) **Inventors: Yang-En Wu, Taipei (TW); Po-Lun
Chen, Chiayi City (TW)**

Correspondence Address:

**THOMAS, KAYDEN, HORSTEMEYER &
RISLEY, LLP****100 GALLERIA PARKWAY, NW****STE 1750****ATLANTA, GA 30339-5948 (US)**(57) **ABSTRACT**

A transfective liquid crystal device capable of balancing a color difference between a reflective region and a transmissive region. The arrangement conditions of optical elements in the transfective LCD are as follows. The twist angle of the liquid crystal is about 40°~80°. The angles β_{up} , β_{down} , θ_{up} and θ_{down} are about -20°~-60°, -20°~20°, 60°~110°, -30°~20° respectively. The angle between the retardation axes of the upper $\lambda/2$ plate and the upper $\lambda/4$ plate is about 30°~100°, and the angle between the retardation axes of the lower $\lambda/2$ plate and the lower $\lambda/4$ plate is about 30°~80°.

(21) **Appl. No.: 10/798,942**(22) **Filed: Mar. 11, 2004**




FIG. 1 (RELATED ART)




FIG. 2 (RELATED ART)




FIG. 3A




FIG. 3B




FIG. 4

TRANSFLECTIVE LIQUID CRYSTAL DISPLAY DEVICE CAPABLE OF BALANCING COLOR DIFFERENCE BETWEEN REFLECTIVE AND TRANSMISSIVE REGIONS

BACKGROUND OF THE INVENTION

[0001] b 1. Field of the Invention

[0002] This invention relates in general to a transmissive liquid crystal display (LCD). More particularly, this invention relates to a transmissive liquid crystal display (LCD) with a single gap type and capable of balancing a color difference between the reflective and transmissive regions.

[0003] 2. Description of the Related Art

[0004] Due to the characteristics of thin profile and low power consumption, liquid crystal displays (LCDs) have been widely used in electronic products, such as portable personal computers, digital cameras, projectors, etc.

[0005] Unlike CRTs (cathode ray tubes) and EL (electroluminescent) devices, LCDs do not emit light themselves, hence, transmissive LCDs require a backlight module. The backlight usually consumes 50% or more of the total power consumed by the LCD device. Therefore, power consumption is increased due to the use of backlight.

[0006] For solving the aforementioned problem, a reflective type LCD is thus developed for people who rely primarily on an LCD device or use the LCD device outdoors. A reflective type LCD comprises a reflector, instead of a backlight, to reflect ambient light. Reflective LCD devices, generally, include TN (twisted nematic) mode devices and STN (super twisted nematic) mode devices.

[0007] The reflective type LCD has the drawback of low visibility when ambient light decreases. In contrast, the drawback of the transmissive type LCD is that the visibility is very low when the ambient light is very bright. Since the display is darker than the ambient light, the quality of color reproduction suffers. In order to improve the image quality of the display in a brightly lit environment, it is necessary to enhance the light intensity of the backlight. However, enhancing the light intensity of the backlight increases power consumption. Moreover, when the LCD is exposed to sunlight or another light source, the image quality of the display decreases considerably. For example, when the sunlight or another light source is directly incident to the LCD monitor, it is difficult to view the displayed image due to reflection.

[0008] In order to solve the above problems, both the transmissive type display and the reflective type display are constructed as a single LCD, which is a so-called transmissive type LCD. **FIG. 1** is a top view of an active array substrate of a transmissive type LCD, disclosed in U.S. Pat. No. 6,295,109 and issued to Sharp Corp. **FIG. 2** is a cross section cut along the line II-II' of the transmissive type LCD in **FIG. 1**.

[0009] As shown in **FIGS. 1 and 2**, gate lines **53** and source lines **59a** are perpendicular to each other and arranged on a transparent substrate. Thin film transistors (TFTs) **57** are respectively disposed in the vicinity of the intersection of each gate line **53** and each source line **59a**. The drain electrode **59c** of the TFT **57** is connected to a transmissive electrode **58a**, used as a portion of a pixel

electrode, for providing voltage to the liquid crystal material in the transmissive region T. In the reflective region R, an interlayer insulating layer **60** and a reflective electrode **61** are disposed on the transmissive electrode **58a**. The reflective electrode **61** is connected to the drain electrode **59c** via a contact hole **63**, and used as a portion of the pixel electrode. Therefore, when viewing the above described LCD, the transmissive region T possesses a considerably high light transmission ratio, while the reflective region R possesses a considerably high light reflection ratio.

[0010] As shown, the TFT **57** comprises a gate insulating layer **54**, a semiconductor layer **55**, semiconductor contact layers **56a** and **56b**, a source electrode **59b**, a drain electrode **59c** and a gate electrode **52**. The gate electrode **52** is branched from the gate line **53**.

[0011] The light in the transmissive region T will pass through the liquid crystal layer with a thickness of dt once, while the light in the reflective region R will pass through the liquid crystal layer with a thickness of dr twice. In order to match retardation caused by the liquid crystal layer in the reflective region R and retardation caused by the liquid crystal layer in the transmissive region T, a thickness relationship of $dt=2 \times dr$ must be satisfied. The thickness dr of the liquid crystal layer in the reflective region R and the thickness dt of the liquid crystal layer in the transmissive region T can be adjusted by varying the thickness of the interlayer insulating layer **60**.

[0012] The aforementioned transmissive type LCD has two gaps, i.e., dt and dr . Although the color difference between the reflective region R and the transmissive region T is almost the same, a height difference between the reflective region R and the transmissive region T hinders formation of an alignment film by rubbing during the manufacturing process.

SUMMARY OF THE INVENTION

[0013] According to the foregoing description, an object of this invention is to provide a transmissive liquid crystal display (LCD) with a single gap. By accurately controlling relative positions of each optical element in the LCD, color difference between a reflective region and a transmissive region, caused by the transmissive LCD with a single gap, can be prevented.

[0014] According to the object(s) mentioned above, the present invention provides a transmissive liquid crystal device capable of balancing a color difference between a reflective region and a transmissive region. The arrangement conditions of optical elements in the transmissive LCD are described in the following.

[0015] The twist angle of the liquid crystal is between about 40° and about 80° , and the retardation $(\Delta n \times d)_{LC}$ (i.e., the phase difference) of the liquid crystal is between about 200 and 300 nm.

[0016] The optical axes of the first alignment film, the first quarter wavelength ($\lambda/4$) plate, the first half-wavelength ($\lambda/2$) plate, and the first polarization plate, which are arranged downwards above the liquid crystal layer near the viewing side, have the following relationships. An angle (β_{up}) between a rubbing direction of the first alignment film and a transmissive axis of the first polarization plate is -20° to -60° . An angle (θ_{up}) between the transmissive axis of the

first polarization plate and a retardation axis of the first half-wavelength ($\lambda/2$) plate is 60° to 110° . An angle between the retardation axis of the first half-wavelength ($\lambda/2$) plate and a retardation axis of the first quarter wavelength ($\lambda/4$) plate is 30° to 100° .

[0017] The optical axes of the second alignment film, the second quarter wavelength ($\lambda/4$) plate, the second half-wavelength ($\lambda/2$) plate, and the second polarization plate, which are arranged downwards under the liquid crystal layer near the backlight side, have the following relationships. An angle (β_{down}) between a rubbing direction of the second alignment film and a transmissive axis of the second polarization plate is -20° to 20° . An angle (θ_{down}) between the transmissive axis of the second polarization plate and a retardation axis of the second half-wavelength ($\lambda/2$) plate is -30° to 20° . An angle between the retardation axis of the second half-wavelength ($\lambda/2$) plate and a retardation axis of the second quarter wavelength ($\lambda/4$) plate is 30° to 80° .

[0018] The retardation (i.e., the phase difference) conditions of the first half-wavelength ($\lambda/2$) plate and the first quarter wavelength ($\lambda/4$) plate near the viewing side are as follows. The retardation of the first and the second half-wavelength ($\lambda/2$) plates is between about 220 nm and about 280 nm. The retardation of the first and the second quarter wavelength ($\lambda/4$) plates is between about 110 nm and about 150 nm.

[0019] In the above transfective LCD, a reflective electrode and a transparent electrode can be further arranged on the same plane between the second alignment film and the second quarter wavelength ($\lambda/4$) plate.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] The preferred embodiment of the invention is hereinafter described with reference to the accompanying drawings in which:

[0021] FIG. 1 is a top view of a conventional active array substrate of a transmissive type LCD;

[0022] FIG. 2 is a cross section cut along the line II-II' of the transmissive type LCD in FIG. 1;

[0023] FIG. 3A shows a transmissive mode and a reflective mode of a transfective type LCD with a single gap without applying voltage to the liquid crystal layer according to one embodiment of the present invention.

[0024] FIG. 3B shows a transmissive mode and a reflective mode of a transfective type LCD with a single gap with applying voltage to the liquid crystal layer according to one embodiment of the present invention.

[0025] FIG. 4 schematically shows relative positions of optical elements of the LCD in Example 1.

DETAILED DESCRIPTION OF THE INVENTION

[0026] FIGS. 3A and 3B are cross sections of a transfective LCD with a single gap. In FIGS. 3A and 3B, only one pixel area is depicted, and each pixel area includes a transmissive region T and a reflective region R.

[0027] At the viewing side of the transfective LCD, a half-wavelength ($\lambda/2$) plate 12 and a quarter wavelength ($\lambda/4$) plate 14 are included between an upper substrate 16

and an upper polarization plate 20. Additionally, opposite the viewing side of the transfective LCD, a half-wavelength ($\lambda/2$) plate 34 and a quarter wavelength ($\lambda/4$) plate 32 are also included between a lower substrate 30 and a lower polarization plate 36.

[0028] A reflective electrode 26R with a high reflection coefficient, whose material can be aluminum (Al), or tantalum (Ta), is arranged in a reflective region R on the lower substrate 30. A transmissive electrode 26T with a high transmission coefficient, whose material can be indium tin oxide (ITO), is arranged in a transmissive region T on the lower substrate 30. The reflective electrode 26R and the transmissive electrode 26T form a pixel electrode. According to the present invention, the reflective electrode 26R and the transmissive electrode 26T are arranged on the same plane and provide the advantage of forming an alignment film 24.

[0029] An interlayer insulating layer 28, for covering a thin film transistor (TFT, not shown), a gate line (not shown) and a source (not shown), etc., are further included between the lower substrate 30 and the pixel electrode including the reflective electrode 26R and the transmissive electrode 26T. In addition, a transparent counter electrode 18 is arranged on the surface of the upper substrate 16. A liquid electrode layer 22 is disposed between the counter electrode 18 and the pixel electrode including the reflective electrode 26R and the transmissive electrode 26T.

[0030] Furthermore, alignment films 24 and 20 are respectively arranged on the pixel electrode (the reflective electrode 26R and the transmissive electrode 26T) and the counter electrode 18 for aligning liquid crystal molecules in the liquid crystal layer 22.

[0031] A backlight 40 is arranged on the surface of the polarization plate 36 away from the lower substrate 30.

[0032] For balancing a color difference between the reflective region R and the transmissive region T of the transfective LCD with a single gap, the aforementioned optical elements have to satisfy following conditions according to the present inventors' elaborate research.

[0033] A twist angle of the above liquid crystal layer 22 is about 40° to about 80° , and a retardation (Δn_{xd})LC (i.e., a phase difference) of the liquid crystal layer 22 is about 0.2 to $0.3 \mu\text{m}$. The twist angle can be controlled by the rubbing directions of the upper alignment film 20 and the lower alignment film 24.

[0034] An angle β_{up} between a rubbing direction of the upper alignment film 20 and a transmission axis of the upper polarization plate 10 near the upper substrate 16 is set between -20° and -60° .

[0035] An angle β_{down} between a rubbing direction of the lower alignment film 24 and a transmission axis of the lower polarization plate 36 near the upper substrate 16 is set between -20° and 20° .

[0036] An angle θ_{up} between a transmission axis of the upper polarization plate 10 and a retardation axis of the upper half-wavelength ($\lambda/2$) plate 12 is set between -60° and 110° .

[0037] An angle θ_{down} between a transmission axis of the lower polarization plate 36 and a retardation axis of the lower half-wavelength ($\lambda/2$) plate 34 is set between -30° and 20° .

[0038] An angle between a retardation axis of the upper half-wavelength ($\lambda/2$) plate **12** and a retardation axis of the upper quarter wavelength ($\lambda/4$) plate **14** is set between 30° and 100° .

[0039] An angle between a retardation axis of the lower half-wavelength ($\lambda/2$) plate **34** and a retardation axis of the lower quarter wavelength ($\lambda/4$) plate **32** is set between 30° and 80° .

[0040] According to the above constraints for the optical elements, a transmissive LCD with a single gap can be made for balancing the color difference between the reflective region R and the transmissive region T. In addition, conditions of following parameters for the aforementioned optical elements can be further controlled.

[0041] The retardation of the upper $\lambda/2$ plate **12** is 220 nm to 280 nm.

[0042] The retardation of the lower $\lambda/2$ plate **34** is 220 nm to 280 nm.

[0043] The retardation of the upper $\lambda/4$ plate **14** is 110 nm to 150 nm.

[0044] The retardation of the lower $\lambda/4$ plate **32** is 110 nm to 150 nm.

[0045] The manner of display in the single gap transmissive LCD will be described in conjunction with FIGS. **3A** and **3B**.

[0046] FIG. **3A** shows a transmissive mode and a reflective mode of a transmissive type LCD with single gap without applying voltages to the liquid crystal layer **22** according to the present invention. At the reflective region R, the ambient light is incident and passes through the polarization plate **10**, the $\lambda/2$ plate **12**, the $\lambda/4$ plate **14** and the liquid crystal layer **22** sequentially. After being reflected by the reflective electrode **26R**, the reflected light passes through the liquid crystal layer **22**, the $\lambda/4$ plate **14**, the $\lambda/2$ plate **12**, and the polarization plate **10** sequentially. At the transmissive region T, the light from the backlight **40** passes through the polarization plate **36**, the $\lambda/2$ plate **34**, the $\lambda/4$ plate **32**, the liquid crystal layer **22**, the $\lambda/4$ plate **14**, the $\lambda/2$ plate **12**, and the polarization plate **10** sequentially. Therefore, the pixel becomes bright.

[0047] FIG. **3B** shows a transmissive mode and a reflective mode of a transmissive type LCD with a single gap with voltage applied to the liquid crystal layer **22** according to the present invention. At the reflective region R, the ambient light is incident and passes through the polarization plate **10**, the $\lambda/2$ plate **12**, the $\lambda/4$ plate **14** and the liquid crystal layer **22** sequentially. After reflected by the reflective electrode **26R**, the reflected light passes through the liquid crystal layer **22**, the $\lambda/4$ plate **14** and the $\lambda/2$ plate **12** sequentially, and then becomes a linearly polarized light. However, in this situation, since the linear polarization angle of the linearly polarized light is not parallel with the transmissive axis of the polarization plate **10**, the linearly polarized light will be absorbed by the polarization plate **10**. At the transmissive region T, the light from the backlight **40** passes through the polarization plate **36**, the $\lambda/2$ plate **34**, the $\lambda/4$ plate **32**, the liquid crystal layer **22**, the $\lambda/4$ plate **14** and the $\lambda/2$ plate **12** sequentially, and then becomes a linearly polarized light. However, in this situation, since the linear polarization angle of the linearly polarized light is not parallel with the trans-

missive axis of the polarization plate **10**, the linearly polarized light will be absorbed by the polarization plate **10**. Therefore, the pixel becomes dark.

EXAMPLE 1

[0048] Example 1 is described in detail according to FIG. **4**. In Example 1, the twist angle of the liquid crystal layer **22** is 50° , the thickness d of the liquid crystal layer **22** is $35\ \mu\text{m}$, Δn of the liquid crystal molecules of the liquid crystal layer **22** is $n_e - n_o = 0.064$, wherein n_e is the refraction index of the liquid crystal molecules with respect to the extraordinary light and n_o is the refraction index of the liquid crystal molecules with respect to the ordinary light. The retardation $(\Delta n d)_{LC}$ of the liquid crystal cell is $0.064 \times 0.35\ \mu\text{m} = 224\ \text{nm}$.

[0049] The rubbing direction **20a** of the alignment film **20** above the liquid crystal layer **22** and a horizontal reference line H forms an angle of -115° , and the rubbing direction **20a** is from the upside down to the left side. The rubbing direction **24a** of the alignment film **24** under the liquid crystal layer **22** and the horizontal reference line H forms an angle of 115° , and the rubbing direction **24a** is from the downside up to the left side.

[0050] The angle between the horizontal reference line H and the retardation axis **14a** of the $\lambda/4$ plate **14** above the liquid crystal layer **22** is 90° , and the angle between the horizontal reference line H and the retardation axis **32a** of the $\lambda/4$ plate **32** under the liquid crystal layer **22** is 27° .

[0051] In addition, the retardation of the upper $\lambda/4$ plate **14** is 120 nm, and the retardation of the lower $\lambda/4$ plate **32** is 140 nm.

[0052] The angle between the horizontal reference line H and the retardation axis **12a** of the upper $\lambda/2$ plate **12** is 30° , and the angle between the horizontal reference line H and the retardation axis **34a** of the lower $\lambda/2$ plate **34** is 90° .

[0053] Therefore, the angle θ_{up} (i.e., the angle between the transmissive axis **10a** and the retardation axis **12a**) is 75° . The angle θ_{down} (i.e., the angle between the transmissive axis **36a** and the retardation axis **34a**) is 75° .

[0054] The retardation of the upper $\lambda/2$ plate **12** is 265 nm, and the retardation of the lower $\lambda/2$ plate **34** is 270 nm.

[0055] The angle between the horizontal reference line H and the transmissive axis **10a** of the upper polarization plate **10** is 105° , and the angle between the horizontal reference line H and the transmissive axis **36a** of the lower polarization plate **36** is 106° .

[0056] Therefore, the angle β_{up} (i.e., the angle between the rubbing direction **20a** and the transmission axis **10a**) is -40° . The angle β_{down} (i.e., the angle between the rubbing direction **24a** and the transmission axis **36a**) is 9° .

[0057] The LCD constructed under above conditions of the aforementioned optical elements has a reflection rate of 41% and a reflective contrast ratio of **34**.

[0058] The foregoing description of the preferred embodiments of this invention has been presented for purposes of illustration and description. Obvious modifications or variations are possible in light of the above teaching. The embodiments were chosen and described to provide the best illustration of the principles of this invention and its prac-

tical application to thereby enable those skilled in the art to utilize the invention in various embodiments and with various modifications as are suited to the particular use contemplated. All such modifications and variations are within the scope of the present invention as determined by the appended claims when interpreted in accordance with the breadth to which they are fairly, legally, and equitably entitled.

What is claimed is:

1. A transreflective liquid crystal display device capable of balancing color difference between a reflective region and a transmissive region, comprising:

- a first substrate;
- a second substrate;
- a liquid crystal layer disposed between the first and the second substrates;
- a first polarization plate arranged on the first substrate and opposite to the liquid crystal layer;
- a second polarization plate arranged on the second substrate and opposite to the liquid crystal layer;
- a first half-wavelength ($\lambda/2$) plate arranged between the first polarization plate and the liquid crystal layer;
- a first quarter wavelength ($\lambda/4$) plate arranged between the first half-wavelength plate and the liquid crystal layer;
- a first alignment film arranged between the first quarter wavelength plate and the liquid crystal layer;
- a second half-wavelength ($\lambda/2$) plate arranged between the second polarization plate and the liquid crystal layer;
- a second quarter wavelength ($\lambda/4$) plate arranged between the second half-wavelength plate and the liquid crystal layer;
- a second alignment film arranged between the second quarter wavelength plate and the liquid crystal layer;

a reflective electrode and a transparent electrode arranged in-plane between the second alignment film and the second substrate; and

a backlight arranged on a surface of the second polarization plate and opposite to the second substrate,

wherein

a twist angle of the liquid crystal is 40° to 80° , a retardation $(\Delta n d)_{LC}$ of the liquid crystal is 200 to 300 nm,

an angle (β_{up}) between a rubbing direction of the first alignment film and a transmissive axis of the first polarization plate is -20° to -60° ,

an angle (β_{down}) between a rubbing direction of the second alignment film and a transmissive axis of the second polarization plate is -20° to 20° ,

an angle (θ_{up}) between the transmissive axis of the first polarization plate and a retardation axis of the first half-wavelength ($\lambda/2$) plate is 60° to 110° ,

an angle (θ_{down}) between the transmissive axis of the second polarization plate and a retardation axis of the second half-wavelength ($\lambda/2$) plate is -30° to 20° ,

an angle between the retardation axis of the first half-wavelength ($\lambda/2$) plate and a retardation axis of the first quarter wavelength ($\lambda/4$) plate is 30° to 100° , and

an angle between the retardation axis of the second half-wavelength ($\lambda/2$) plate and a retardation axis of the second quarter wavelength ($\lambda/4$) plate is 30° to 80° .

2. The transreflective liquid crystal display device of claim 1, wherein a retardation of the first and the second half-wavelength ($\lambda/2$) plates is 220 nm to 280 nm.

3. The transreflective liquid crystal display device of claim 1, wherein a retardation of the first and the second quarter wavelength ($\lambda/4$) plates is 110 nm to 150 nm.

* * * * *

专利名称(译)	透反液晶显示装置，能够平衡反射区域和透射区域之间的色差		
公开(公告)号	US20040233358A1	公开(公告)日	2004-11-25
申请号	US10/798942	申请日	2004-03-11
[标]申请(专利权)人(译)	吴洋EN 陈宝轮		
申请(专利权)人(译)	吴仰恩 陈伦宝		
当前申请(专利权)人(译)	吴仰恩 陈伦宝		
[标]发明人	WU YANG EN CHEN PO LUN		
发明人	WU, YANG-EN CHEN, PO-LUN		
IPC分类号	G02F1/1335 G02F1/13363		
CPC分类号	G02F1/133555 G02F1/13363 G02F2413/08 G02F2001/1398 G02F2413/04 G02F2001/133638		
优先权	092113955 2003-05-23 TW		
其他公开文献	US6999144		
外部链接	Espacenet USPTO		

摘要(译)

一种透反液晶装置，能够平衡反射区域和透射区域之间的色差。透反射LCD中光学元件的排列条件如下。液晶的扭曲角约为 40° ~ 80° 。 β_{up} ， β_{down} ， θ_{up} 和 θ_{down} 的角度分别为 -20° ~ -60° ， -20° ~ 20° ， 60° ~ 110° ， -30° ~ 20° 。上M 2板和上M 4板的延迟轴之间的角度约为 30° ~ 100° ，下M 2板和下M 4板的延迟轴之间的角度为约 30° ~ 80° 。

