



US 20050184939A1

(19) **United States**(12) **Patent Application Publication** (10) **Pub. No.: US 2005/0184939 A1**
Ueda et al. (43) **Pub. Date: Aug. 25, 2005**(54) **LIQUID CRYSTAL DISPLAY**(52) **U.S. Cl. 345/87**(75) **Inventors: Kazuya Ueda, Kawasaki (JP); Tsuyoshi Kamada, Kawasaki (JP); Hidefumi Yoshida, Kawasaki (JP); Yoshio Koike, Kawasaki (JP); Kenji Okamoto, Kawasaki (JP)**

Correspondence Address:
Patrick G. Burns, Esq.
GREER, BURNS & CRAIN, LTD.
Suite 2500
300 South Wacker Dr.
Chicago, IL 60606 (US)

(73) **Assignees: FUJITSU DISPLAY TECHNOLOGIES CORPORATION; AU OPTRONICS CORPORATION**(21) **Appl. No.: 10/890,977**(22) **Filed: Jul. 14, 2004**(30) **Foreign Application Priority Data**

Feb. 24, 2004 (JP) 2004-047677

Publication Classification(51) **Int. Cl.⁷ G09G 3/36**(57) **ABSTRACT**

The liquid crystal display comprises a first substrate 2 including a first pixel electrode 12a and a second pixel electrode 12b, a second substrate 4 with an opposed electrode 22 formed on, and a liquid crystal layer 6 sealed between the first substrate 2 and the second substrate 4. The thickness d_1 of the liquid crystal layer 6 on the first pixel electrode 12a in the first pixel region 8R, 8G is larger than the thickness d_2 of the liquid crystal layer 6 on the second pixel electrode 12b in the second pixel region 8B. The first pixel region 8R, 8G includes a first partial region 11a, and a second partial region 13a where the threshold voltage is higher than in the first partial region 11a. The second pixel region 8B includes a third partial region 11b, and a fourth partial region 13b where the threshold voltage is higher than in the third partial region 11b. The threshold voltage in the first partial region 11a and the threshold voltage in the third partial region 11b are equal to each other, and the threshold voltage in the second partial region 13a and the threshold voltage in the fourth partial region 13b are equal to each other. Thus, it is possible to prevent large changes in the chromaticity due to gradation and visual angle changes, which lead to the prevention of the occurrence of the coloring. Thus, it is possible to provide a liquid crystal display having good display quality.




FIG. 2




FIG. 3




FIG. 4




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14





FIG. 15



LIQUID CRYSTAL DISPLAY

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application is based upon and claims priority of Japanese Patent Application No. 2004-47677, filed on Feb. 24, 2004, the contents being incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0002] The present invention relates to a liquid crystal display, more specifically a liquid crystal display which can have display quality improved.

[0003] MVA (Multi-domain Vertical Alignment) type liquid crystal displays combine the vertical alignment technique, which realizes high contrast and high-speed response and the multi-domain technique, which realizes large viewing angle.

[0004] In the MVA type liquid crystal display, alignment control blank patterns or alignment control structures are disposed respectively on a TFT substrate and a CF substrate. Alignment directions of the liquid crystal molecules are controlled by the alignment control blank pattern or alignment control structure. The MVA type liquid crystal display does not require rubbing, which is a large factor for lowering the productivity, and can attain high productivity.

[0005] Following references disclose the background art of the present invention.

[0006] [Patent Reference 1]

[0007] Specification of Japanese Patent No. 2947350

[0008] [Patent Reference 2]

[0009] Specification of Japanese Patent Application Unexamined Publication No. 2002-107730

[0010] [Patent Reference 3]

[0011] Specification of Japanese Patent Application Unexamined Publication No. 2003-43489

SUMMARY OF THE INVENTION

[0012] According to one aspect of the present invention, there is provided a liquid crystal display comprising: a first substrate including a first pixel electrode and a second pixel electrode; a second substrate with an opposed electrode formed on, the opposed electrode opposing to the first pixel electrode and the second pixel electrode; and a liquid crystal layer sealed between the first substrate and the second substrate, a thickness of the liquid crystal layer in a first pixel region on the first pixel electrode being larger than a thickness of the liquid crystal layer in a second pixel region on the second pixel electrode; the first pixel region including a first partial region, and a second partial region where a threshold voltage is higher than in the first partial region, and the second pixel region including a third partial region and a fourth partial region where a threshold voltage is higher than in the third partial region, and the threshold voltage in the first partial region and the threshold voltage in the third partial region being equal to each other, and the threshold voltage in the second partial region and the threshold voltage in the fourth partial region being equal to each other.

[0013] According to the present invention, a lower threshold region and a higher threshold region are present between the alignment control blank pattern and the alignment control structure, whereby changes of the transmittivity for applied voltage changes can be gentle. Thus, the present invention can prevent the transmittivity given when the screen is observed obliquely from being higher than the transmittivity given when the screen is observed at the front, whereby the brightness given when the screen is observed obliquely from being higher than the brightness given when the screen is observed at the front. Furthermore, according to the present invention, the parameters of the alignment control structure, the alignment control blank pattern and the electric field control structures are set to be proportional with the respective cell-gaps, whereby although the cell-gap in the first pixel region and the cell-gap in the second pixel region are different from each other, the threshold voltage in the higher threshold region of the first pixel region and the threshold voltage in the higher threshold region of the second pixel region can be made substantially equal to each other, and the threshold voltage in the lower threshold region of the first pixel region and the threshold voltage in the lower threshold region of the second pixel region can be made substantially equal to each other. Thus, the present invention can prevent large changes in the chromaticity due to gradation and visual angle changes, which lead to the prevention of the occurrence of the coloring. Thus, the present invention can provide a liquid crystal display having good display quality.

[0014] According to the present invention, the parameters of the electric field control blank pattern are suitably set in accordance with the cell-gaps, whereby although the cell-gap differs between the first pixel region and the second pixel region, the threshold voltage in the higher threshold region of the first pixel region and the threshold voltage in the higher threshold region of the second pixel region can be made substantially equal to each other, and the threshold voltage in the lower threshold region of the first pixel region and the threshold voltage in the lower threshold region of the second pixel region can be made substantially equal to each other. Thus, the present invention can prevent the occurrence of the phenomena that the brightness given when observed obliquely is higher than the brightness given when observed at the front while preventing the occurrence of the coloring phenomena.

[0015] According to the present invention, the parameters of the electric field control blank pattern is suitably set in accordance with the cell-gap, whereby even in the case that the parameters of the electric field control blank pattern, the electric field control structure and the alignment control structure are set to be equal to one another in the respective pixel regions, the threshold voltages in the higher threshold regions of the respective pixel regions can be made substantially equal to each other. Thus, the present invention can prevent the brightness given when observed obliquely higher than the brightness given when observed at the front while preventing the occurrence of the coloring phenomena. According to the present invention, the parameters of the electric field control structure, the alignment control structure, etc. are set to be equal to one another among the respective pixel regions, whereby the fabrication process can be simplified. According to the present invention, the parameters of the electric field control structure, the alignment control structure, etc. are set to be equal to one another

among the respective pixel regions, whereby the response speed is prevented from varying among the respective pixel regions.

[0016] According to the present invention, in a pixel region where the electric field control blank pattern must be formed narrow, the electric field control blank pattern is not intentionally formed, whereby the occurrence of disuniform displays, etc. can be prevented.

[0017] According to the present invention, the cell-gap in the first pixel region and the cell-gap in the third pixel region are set to be equal to each other, whereby the structure can be simplified. Thus, the present invention can provide a liquid crystal display of good display quality at low cost.

BRIEF DESCRIPTION OF THE DRAWINGS

[0018] FIG. 1 is a sectional view of the liquid crystal display according to a first embodiment of the present invention.

[0019] FIG. 2 is a plan view of the liquid crystal display according to the first embodiment of the present invention.

[0020] FIG. 3 is a graph of the T-V characteristics of the liquid crystal display according to the first embodiment of the present invention.

[0021] FIG. 4 is a graph of the gradation chromaticity change characteristics of the liquid crystal display according to the first embodiment of the present invention.

[0022] FIG. 5 is a perspective view of the liquid crystal displaying to a second embodiment of the present invention.

[0023] FIG. 6 is a perspective view of the liquid crystal display according to a third embodiment of the present invention.

[0024] FIG. 7 is a perspective view of the liquid crystal display according to a fourth embodiment of the present invention.

[0025] FIG. 8 is a perspective view of the liquid crystal display according to a fifth embodiment of the present invention.

[0026] FIG. 9 is a sectional view of the proposed liquid crystal display.

[0027] FIG. 10 is a graph of the T-V characteristics of the proposed liquid crystal display.

[0028] FIG. 11 is a graph of gradation chromaticity change characteristics of the proposed liquid crystal display.

[0029] FIG. 12 is a sectional view of another proposed liquid crystal display.

[0030] FIG. 13 is a graph of the T-V characteristics of said another proposed liquid crystal display.

[0031] FIG. 14 is a graph of the gradation chromaticity change characteristics of said another proposed liquid crystal display.

[0032] FIG. 15 is a perspective view of the liquid crystal display according to Control 1.

[0033] FIG. 16 is a perspective view of the liquid crystal display according to Control 2.

DETAILED DESCRIPTION OF THE INVENTION

[0034] A proposed MVA type liquid crystal display will be explained with reference to FIG. 9. FIG. 9 is a sectional view of the proposed liquid crystal display. On the left side of the drawing, an R (red color) pixel region 108R and a G (green color) pixel region 108G are illustrated, and a B (blue color) pixel region 108B is illustrated on the right side of the drawings.

[0035] First, a TFT substrate 102 will be explained. As illustrated in FIG. 9, pixel electrodes 112a, 112b are formed on a glass substrate 110. Alignment control blank patterns (blank of the electrodes) 114a, 114b are formed in the pixel electrodes 112a, 112b. The widths w_{12} , w_{22} of the alignment control blank patterns 114a, 114b are both set at $10\text{ }\mu\text{m}$. An alignment film (not shown) is formed on the glass substrate 110a with the pixel electrodes 112a, 112b formed on. Thus, the TFT substrate 102 is formed.

[0036] Next, a CF substrate 104 will be explained. A color filter layer 120a, 120b is formed on the underside of the glass substrate 118. The thickness of the color filter layer 120a, 120b is set uniform in all the R, G and B pixel regions 108R, 108G, 108B. Alignment control structures 124a, 124b are formed on the underside of the color filter layer 120a, 120b. The widths w_{11} , w_{21} of the alignment control structures 124a, 124b are both set at $10\text{ }\mu\text{m}$. The heights h_{11} , h_{21} of the alignment control structures 124a, 124b are both set at, e.g., $1.2\text{ }\mu\text{m}$.

[0037] A liquid crystal 106 is sealed between the TFT substrate 102 and the CF substrate 104. The liquid crystal 106 is a nematic liquid crystal, which has negative dielectric anisotropy. The thickness of the liquid crystal layer 106, i.e., the cell-gap d_1 , d_2 is set at, e.g., $4.0\text{ }\mu\text{m}$ uniformly in all the R, the G and the B pixel regions 108R, 108G, 108B.

[0038] Thus, the proposed MVA type liquid crystal display is constituted.

[0039] In the MVA type liquid crystal display, the alignment control blank pattern 114 and the alignment control structure 124 disposed respectively on the TFT substrate 102 and the CF substrate 104 control the alignment direction of the liquid crystal molecules 126. The MVA type liquid crystal display does not require rubbing, which is a large factor for lowering the productivity, and can attain high productivity.

[0040] However, in the proposed MVA type liquid crystal display illustrated in FIG. 9, it has been often that the brightness of images observed obliquely is higher than the brightness of the images observed at the front. Thus, the proposed liquid crystal display does not have always good display quality.

[0041] An object of the present invention is to provide a liquid crystal display which can have the display quality improved.

A First Embodiment

[0042] Before the liquid crystal display according to a first embodiment of the present invention is explained, another proposed liquid crystal display will be explained. FIG. 12 is a sectional view of said another proposed liquid crystal display. In FIG. 12, an R pixel region 208R and a G pixel

region **208G** are illustrated on the left side of the drawing, and the right side of the drawing, a B pixel region **208B** is illustrated. The R pixel region **208R** and the G pixel region **208G** have the same constitution except that a color filter layer **220** is different in color between the R pixel region **208R** and the G pixel region **208G**, and are not separately illustrated but illustrated in one and the same drawing.

[0043] First, a TFT substrate **202** will be explained. Pixel electrodes **212a**, **212b** are formed on a glass substrate **210**. Alignment control blank patterns **214a**, **214b**, i.e., slits are formed respectively in the pixel electrodes **212a**, **212b**, the alignment control blank pattern being a region where ITO is not formed in the pixel electrode. The widths w_{12} , w_{22} of the alignment control blank patterns **214a**, **214b** are both set at $10\ \mu\text{m}$. Electric field control structures **216a**, **216b** of, e.g., a dielectric layer are formed on the pixel electrodes **212a**, **212b** with the alignment control blank patterns **214a**, **214b** formed in. The heights h_{11} , h_{12} of the electric field control structures **216a**, **216b** are both set at $1.0\ \mu\text{m}$. An alignment film (not shown) is formed on the glass substrate **210** with the electric field control structures **216a**, **216b**, etc. formed on. Thus, the TFT substrate **202** is formed.

[0044] Then, a CF substrate **204** will be explained. A color filter layer **220a**, **220b** is formed on the underside of the glass substrate **218**. The thickness of the color filter layer **220a** in the R and the G pixel regions is smaller by $1.0\ \mu\text{m}$ than the thickness of the color filter layer **220b** in the B pixel region. An opposed electrode **222** is formed on the underside of the color filter layer **220**. Respective alignment control structures **224a**, **224b** are formed on the underside of the opposed electrode **222**. The widths w_{11} , w_{21} of the alignment control structures **224a**, **224b** are both set at $10\ \mu\text{m}$. The height h_{11} , h_{12} of the alignment control structures **224a**, **224b** are both set at $1.5\ \mu\text{m}$.

[0045] A liquid crystal **206** is sealed between the TFT substrate **202** and the CF substrate **204**. The thickness of the liquid crystal layer **206** in the R and the G pixel regions **208R**, **208G**, i.e., the cell-gap d_1 is set at $5.0\ \mu\text{m}$. The cell-gap d_2 in the B pixel region **208B** is set at $4.0\ \mu\text{m}$. The cell-gap d_1 in the R and the G pixel regions **208R**, **208G** and the cell-gap d_2 in the B pixel region **208B** are different from each other so that the difference in $\Delta n \cdot d / \lambda$ among the respective R, the G and the B pixel regions **208R**, **208G**, **208B** is made small. Δn indicates a diffractive index anisotropy, d indicates a cell-gap, and λ indicates a wavelength of light. In order to make the difference in $\Delta n \cdot d / \lambda$ among the respective R, the G and the B pixel regions **208R**, **208G**, **208B** small, it is preferable to set the cell-gap in the R pixel region **208G**, the cell-gap in the G pixel region **208G** and the cell-gap in the B pixel region **208B** at optimum values. Here, to simplify the structure, the cell-gap in the R pixel region **208R** and the cell-gap in the G pixel region **208G** are set to be the same.

[0046] Thus, said another proposed liquid crystal display is constituted.

[0047] In said another proposed liquid crystal display, regions **211a**, **211b** where the electric field control structures **216a**, **216b** are not formed and regions **213a**, **213b** where the electric field control structures **216a**, **216b** are not formed are present between the alignment control blank patterns **214a**, **214b** and the alignment control structures **224a**, **224b**. The threshold voltage of in the regions **213a**, **213b**, where

the alignment control structures **216a**, **216b** are formed is higher than the threshold voltage in the regions **211a**, **211b** where the alignment control structures **216a**, **216b** are not formed. The T-V characteristics differ between the regions (higher threshold regions) **213a**, **213b**, where the threshold voltage is relatively high and the regions (lower threshold regions) **211a**, **211b**, where the threshold voltage is relatively lower. The threshold voltage means a voltage at which the liquid crystal molecules start to tilt while a voltage applied between the pixel electrode **12** and the opposed electrode **22** is being gradually increased.

[0048] FIG. 10 is a graph of the T-V characteristics (voltage-transmittivity characteristics) of the proposed liquid crystal display. FIG. 13 is a graph of the T-V characteristics of said another proposed liquid crystal display. In FIGS. 10 and 13, the applied voltages are taken on the horizontal axis, and on the vertical axis the transmittivities are taken. The $\diamond$ marks indicate the case where the screen was observed at the front, and the Δ marks indicate the case where the screen was observed obliquely. When the screen was observed obliquely, the polar angle of the view point was 60 degrees, and the screen was observed from above the screen. The polar angle means an angle to a normal to the substrate surface.

[0049] As seen in FIG. 10, the proposed liquid crystal display has a voltage range where the transmittivity is higher when observed obliquely than at the front. Accordingly, the proposed liquid crystal display, the brightness of images observed obliquely is higher than the brightness of the images observed at the front.

[0050] The reason for the brightness being higher when observed obliquely than when observed at the front will be as follows. That is, a liquid crystal having negative dielectric anisotropy does not transmit light when a direction of a view point agrees with an angle of the longitudinal direction of the liquid crystal molecules, and as the angle of the direction of the view point to the longitudinal direction of the liquid crystal molecules is increased, the transmittivity increases. There are conditions under which θ' is larger than θ when an angle of a view point direction to a longitudinal direction of the liquid crystal molecules formed when the tilted liquid crystal molecules are observed at the front is θ , and an angle of a view point direction to a longitudinal direction of the liquid crystal molecules formed when the tilted liquid crystal molecules are observed obliquely is θ' . Under such conditions, the transmittivity given when observed obliquely is higher than the transmittivity given when observed at the front. A resultant phenomena is that the brightness given observed obliquely is higher than the brightness given when observed at the front.

[0051] In said another proposed liquid crystal display, however, as seen in FIG. 13, the transmittivity given when observed obliquely is prevented from being higher than the transmittivity given when observed at the front. Accordingly, in said another proposed liquid crystal display, the phenomena that the brightness given when observed obliquely is higher than the brightness given when observed at the front can be prevented.

[0052] The reason for said another proposed liquid crystal display being able to suppress the phenomena that the brightness given when observed obliquely is higher than the brightness given when observed at the front will be as

follows. That is, the voltage applied between the pixel electrode **212** and the opposed electrode **222** is gradually increased, and when the voltage applied between the pixel electrode **212** and the opposed electrode **222** exceeds the threshold voltage of the lower threshold region **211**, the liquid crystal molecules **226** in the lower threshold region **211** start to tilt. At this time, since the liquid crystal molecules **226** in the higher threshold region **213** do not tilt, the transmittivity increase for the applied voltage increase is relatively gentle. Then, when the voltage applied between the pixel electrode **212** and the opposed electrode **222** exceeds the threshold voltage of the higher threshold region **213**, the liquid crystal molecules **226** in the higher threshold region **213** also start to tilt. Thus, in said another proposed liquid crystal display, in comparison with the proposed liquid crystal display, the transmittivity increase for the applied voltage increase can be gentle. Thus, the transmittivity increase for the applied voltage increase can be gentle both when observed at the front and when observed obliquely. Accordingly, much more increase of the transmittivity given when observed obliquely than given when observed at the front can be prevented, whereby the phenomena that the brightness given when observed obliquely is higher than the brightness given when observed at the front can be prevented.

[0053] However, in said another proposed liquid crystal display, the color balance among R, G and B has been often disturbed.

[0054] FIG. 14 is a graph of the gradation chromaticity change characteristics of said another proposed liquid crystal display. The $\diamond$ marks indicate the case where the screen was observed at the front, and the A marks indicate the case where the screen was observed obliquely. In measuring the gradation chromaticity change characteristics, the gradation was changed gradually from black to white, and the xy chromaticities (x,y) at each gradation were given. When the screen was observed, the polar angle of the view point was 60 degrees, and the screen was observed from above.

[0055] As seen in FIG. 14, in said another proposed liquid crystal display, the chromaticity is largely changed as the gradation changes, and the color balance is much disturbed. The differences in the chromaticity between the case where the screen was obliquely observed and the case where the screen was observed at the front are considerably large.

[0056] Accordingly, said another proposed liquid crystal display has the phenomena that a display which is originally to be displayed in an achromatic color is displayed in a chromatic color. Such phenomena is called coloring.

[0057] The coloring taking place in said another proposed liquid crystal display will be because the parameters of the alignment control structures **224a**, **224b**, the alignment control blank patterns **214a**, **214b** and the electric field control structures **216a**, **216b** are set to be equal to one another although the pixel regions **208R**, **208G** and region **208B** have the cell-gaps d_1 , d_2 which are different from each other. That is, in said another proposed liquid crystal display, the cell-gap d_1 in the pixel regions **208R**, **208G** is larger than the cell-gap d_2 in the pixel region **208B**, but the heights h_{12} , h_{22} of the electric field control structures **216a**, **216b** are equal to each other. This makes a voltage applied to the liquid crystal **206** in the higher threshold region **213a** higher than the voltage applied to the liquid crystal **206** in the

higher threshold region **213b** in said another proposed liquid crystal display. This is a factor for making the threshold voltages in the higher threshold regions **213a**, **213b** of each pixel regions **208** different from each other. In said another proposed liquid crystal display, although the cell-gap d_1 in the pixel regions **208R**, **208G** is larger than the cell-gap d_2 in the pixel region **208B**, the heights h_{11} , h_{21} and the widths w_{11} , w_{21} of the alignment control structure **224** and the widths w_{12} , w_{22} , etc. of the alignment control blank pattern **214** are equal to each other. Accordingly, the alignment control force to be applied to the liquid crystal molecules **226** varies among the respective pixel regions **208**. This is also a factor for the threshold voltages in the respective pixel regions **208** differ from one another.

[0058] The inventors of the present application have made earnest studies and had an idea that the parameters of the alignment control structures **224a**, **224b**, the alignment control blank patterns **214a**, **214b**, the electric field control structures **216a**, **216b**, etc. are set in accordance with the cell-gaps d in the respective pixel regions **208**. The parameters of the alignment control structures **224a**, **224b**, the alignment control blank patterns **214a**, **214b**, the electric field control structures **216a**, **216b**, etc. are set in accordance with the cell-gaps d in the respective pixel regions **208**, whereby a threshold voltage is prevented from varying among the respective pixel regions **208**, and accordingly, the color balance is kept from being disturbed with a result that the coloring phenomena is prevented.

[0059] The liquid crystal display according to a first embodiment of the present invention will be explained with reference to FIGS. 1 to 4. FIG. 1 is a sectional view of the liquid crystal display according to the present embodiment. FIG. 2 is a plan view of the liquid crystal display according to the present embodiment.

[0060] The liquid crystal display according to the present embodiment comprises a TFT substrate **2** with pixel electrodes, etc. formed on, a CF substrate **4** with an opposed electrode opposed to the pixel electrodes, etc., and a liquid crystal **6** sealed between the TFT substrate **2** and the CF substrate **4**.

[0061] In FIG. 1, on the left side of the drawing, an R (red color) pixel region and a G (green color) pixel region (a first pixel region) **8R**, **8G** are illustrated, and a B (blue color) pixel region (a second pixel region) **8B** is illustrated on the right side of the drawing. The R pixel region **8R** and the G pixel region **8G** have the same constitution except that they are different in the color of a color filter layer **20**, and they will be explained with reference to the drawing which does not illustrate them separately but illustrates together. In the R and the G pixel regions **8R**, **8G**, the thickness of the liquid crystal layer **6**, i.e., the cell-gap d_1 is set at, e.g., $5.0\ \mu\text{m}$. In the B pixel region **8B**, the cell-gap d_2 is set at, e.g., $4.0\ \mu\text{m}$.

[0062] The cell-gap d_1 in the R and the G pixel regions **8R**, **8G** is larger than the cell-gap d_2 in the B pixel region **8B**, because the difference in $\Delta n \cdot d / \lambda$ among the R, the G and the B pixel regions **8** can be small.

[0063] To make smaller the difference in $\Delta n \cdot d / \lambda$ among the R, the G and the B pixel regions **8R**, **8G**, **8B**, it is preferable the cell-gap in the R pixel region **8R**, the cell-gap in the G pixel region **8G** and the cell-gap in the B pixel region **8B** are respectively set at optimum values. In the

present embodiment, the cell-gap in the R pixel region **8R** and the cell-gap in the G pixel region **8G** are set to be equal to each other so as to make the structure simple.

[0064] First the TFT substrate **2** will be explained.

[0065] On the glass substrate **10** there are formed a plurality of gate bus lines **28** substantially in parallel with each other (see **FIG. 2**). A gate insulation film (not shown) is formed on the glass substrate **10** with the gate bus lines **28** formed on. On the glass substrate **10** with the gate insulation film, etc. formed on, a plurality of data bus lines **30** are formed, substantially orthogonally crossing the gate bus lines **28**. TFTs (Thin-Film Transistors) **32** are formed near the intersections between the gate bus lines **28** and the data bus lines **30**. The gate bus lines **28** functions as the gate electrodes of the TFTs **32**. The source electrodes **34** of the TFT **32** are electrically connected to the data bus lines **30**. The drain electrodes **36** of the TFTs **32** are connected to pixel electrodes **12a**, **12b** of ITO (Indium-Tin Oxide).

[0066] In the pixel electrodes **12a**, **12b**, respective alignment control blank patterns **14a**, **14b**, i.e., slits are formed. The alignment control blank patterns **14** are arranged generally zigzag (see **FIG. 2**). The alignment control blank patterns **14a**, **14b** are for controlling the alignment direction of the liquid crystal molecules **26** of the liquid crystal layer **6**.

[0067] The width w_{12} of the alignment control blank pattern **14a** in the R and the G pixel regions **8R**, **8G** is set at, e.g., $12\ \mu\text{m}$. The width w_{22} of the alignment control blank pattern **14b** in the B pixel region **8B** is set at, e.g., $10\ \mu\text{m}$. The ratio (w_{12}/d_1) of the width w_{12} of the alignment control blank pattern in the R and the G pixel regions to the cell-gap d_1 therein is set to be substantially equal to the ratio (w_{22}/d_2) of the width w_{22} of the alignment control blank pattern in the B pixel region to the cell-gap d_2 therein.

[0068] In the claims of the present application, to be equal contains not only to be perfectly equal, but also to be substantially equal.

[0069] The ratio (w_{12}/d_1) of the width w_{12} of the alignment control blank pattern in the R and the G pixel regions and the ratio (w_{22}/d_2) of the width w_{22} of the alignment control blank pattern in the B pixel region to the cell-gap d_2 therein are set to be substantially equal to each other for the following reason. That is, as the cell-gaps d_1 , d_2 are larger, the alignment control force of the alignment control blank patterns **14a**, **14b** is more hindered from acting to the liquid crystal molecules **26**. Accordingly, in the case that the cell-gap d_1 in the pixel regions **8R**, **8G** is larger than the cell-gap d_2 in the pixel region **8B**, but the width w_{12} of the alignment control blank pattern **14a** and width w_{22} of the alignment control blank pattern **14b** are set to be equal to each other, the alignment of the liquid crystal molecules **26** are not easily controlled in the pixel regions **8R**, **8G**, where the cell-gap d_1 is larger, and on the other hand, in the pixel region **8B**, where the cell-gap d_2 is smaller, the alignment of the liquid crystal molecules **26** is easily controlled. Then, a large difference in the threshold voltage between the R and the G pixel regions **8R**, **8G** and the B pixel region **8B** is made, which leads to deterioration of the display quality. In the present embodiment, however, the width w_{12} of the alignment control blank pattern **14a** in the R and the G pixel regions **8R**, **8G** and the width w_{22} of the alignment control

blank pattern **14b** in the B pixel region **8B** are set to be proportional the cell-gaps d_1 , d_2 . The alignment control force of the alignment control blank patterns **14a**, **14b** is larger as the widths w_{12} , w_{22} are larger. In the present embodiment, the widths w_{12} , w_{22} of the alignment control blank patterns **14a**, **14b** are set corresponding to the cell-gaps d_1 , d_2 , whereby even when the cell-gap d_1 in the pixel regions **8R**, **8G** is set to be larger than the cell-gap d_2 in the pixel region **8B**, it can be prevented that the liquid crystal molecules **26** in the pixel regions **8R**, **8B**, where the cell-gap d_1 is larger, are not easily aligned. Thus, according to the present embodiment, even when the cell-gap d is different among the respective pixel regions **8**, the threshold voltages can be substantially equal to one another.

[0070] Electric field control structures **16a**, **16b** of, e.g., a dielectric layer is formed on the glass substrate **10** with the pixel electrodes **12a**, **12b** formed on. The electric field control structure **16b** is arranged zigzag (see **FIG. 2**). The center line of the electric field control structures **16** substantially agrees with the center line of the alignment control blank patterns **14**. The electric field control structures **16** control the electric fields applied to the liquid crystal molecules **26** to thereby control the threshold voltage. Of the regions between the alignment control blank patterns **14a**, **14b** and the alignment control structures **24a**, **24b**, the regions **13a**, **13b** where the electric field control structures **16a**, **16b** are formed are regions where the threshold voltage is relatively higher, i.e., higher threshold regions. Of the regions between the alignment control blank patterns **14a**, **14b** and the alignment control structures **24a**, **24b**, the regions **11a**, **11b** where the electric field control structures **16a**, **16b** are not formed, are region where the threshold voltage is relative low, i.e., lower threshold regions.

[0071] The height h_{12} of the electric field control structure **16a** in the B and the G pixel regions **8B**, **8G** is set at, e.g., $1\ \mu\text{m}$. The height h_{22} of the electric field control structure **16b** in the B pixel region **8B** is set at, e.g., $0.8\ \mu\text{m}$. The ratio (h_{12}/d_1) of the height h_{12} of the electric field control structure to the cell-gap d_1 in the R and the G pixel regions **8R**, **8G** and the ratio (h_{22}/d_2) of the height h_{22} of the electric field control structure **16b** to the cell-gap d_2 in the B pixel region **8B** are set to be substantially equal to each other. The width of all the electric field control structures **16a**, **16b** is set at, e.g., $50\ \mu\text{m}$. The pitch of the electric field control structures **16a**, **16b** is set at, e.g., $70\ \mu\text{m}$.

[0072] The ratio of the height h_{12} of the electric field control structure **16a** to the cell-gap d_1 in the R and the G pixel regions and the ratio of the height h_{22} of the electric field control structure **16b** to the cell-gap d_2 in the B pixel region are set to be substantially equal to each other for the following reason. That is, in the regions where the electric field control structures **16a**, **16b** formed in, a voltage applied to the liquid crystal layer **6** is decreased by the electric field control structures **16a**, **16b**. Accordingly, in the case that the cell-gap d_1 in the pixel regions **8R**, **8G** is larger than the cell-gap d_2 in the pixel region **8B**, but the height h_{12} of the electric field control structure and the height h_{22} of the electric field control structure are set to be equal to each other, a voltage applied to the liquid crystal layer **6** in the pixel regions **8R**, **8G**, where the cell-gap d_1 is larger, becomes higher than the voltage applied to the liquid crystal layer **6** in the pixel region **8B**, where the cell-gap d_2 is smaller. The electric field control structures **16a**, **16b** also

function as the alignment control means for controlling the alignment direction of the liquid crystal molecules **26**. Accordingly, in the case that the cell-gap d_1 in the pixel regions **8R**, **8G** is larger than the cell-gap d_2 in the pixel region **8B**, but the height h_{12} of the electric field control structure and the height h_{22} of the electric field control structure are set to be equal to each other, the alignment control force does not easily act on the liquid crystal molecules **26** in the pixel regions **8R**, **8G**, where the cell-gap d_1 is larger, and on the other hand, the alignment control force easily acts on the liquid crystal molecules **26** in the pixel region **8B**, where the cell-gap d_2 is smaller. Resultantly, a large difference in the threshold voltage takes place between the pixel regions **8** having different cell-gaps d , which leads to deterioration of the display quality. However, in the present embodiment, the heights h_{12} , h_{22} of the electric field control structures **16a**, **16b** are set to be proportional to the cell-gaps d_1 , d_2 , whereby although the cell-gap d_1 in the pixel regions **8R**, **8G** is larger than the cell-gap d_2 in the pixel region **8B**, the electric field intensity to be applied to the liquid crystal molecules **26** can be made substantially equal to each other. Because of the heights h_{12} , h_{22} of the electric field control structures **16a**, **16b** set to be proportional to the cell-gaps d_1 , d_2 , the alignment control force applied to the liquid crystal molecules **26** in the pixel regions **8R**, **8G** and the alignment control force applied to the liquid crystal molecules **26** in the pixel region **8B** can be made substantially equal to each other although the cell-gap d_1 in the pixel regions **8R**, **8G** is larger than the cell-gap d_2 in the pixel regions **8B**. Thus, according to the present embodiment, even in the case that the cell-gap d_1 in the pixel regions **8R**, **8G** and the cell-gap d_2 in the pixel region **8B** are different from each other, the threshold voltage in the pixel region **8R**, **8G** and the threshold voltage in the pixel region **8B** can be made substantially equal to each other.

[0073] Thus, the TFT substrate **2** is constituted.

[0074] Then, the CF substrate **4** will be explained.

[0075] A color filter layer **20a**, **20b** is formed on the underside of the glass substrate **18**. The thickness of the color filter layer **20a** in the R and the G pixel regions **8R**, **8G** are set at, e.g., $2.0\ \mu\text{m}$. In the B pixel region **8B**, the thickness of the color filter layer **20b** is set at, e.g., $3.0\ \mu\text{m}$. The thickness of the color filter layer **20b** in the B pixel region **8B** is larger by, e.g., $1.0\ \mu\text{m}$ than the thickness of the color filter layer **20a** in the R and the G pixel regions **8R**, **8G**.

[0076] An opposed electrode **22** of ITO is formed on the underside of the color filter layer **20a**, **20b**.

[0077] Alignment control structures **24a**, **24b** are formed on the underside of the opposed electrode **22**. The alignment control structures **24** are formed zigzag (see FIG. 2). The alignment control structures **24** are arranged, offset from the alignment control blank patterns **14** by a half pitch. The height h_{11} of the alignment control structure **16a** formed in the R and the G pixel regions **8R**, **8G** are set at, e.g., $1.4\ \mu\text{m}$. The height h_{21} of the alignment control structure formed in the B pixel region **8B** is set at, e.g., $1.2\ \mu\text{m}$. The ratio (h_{11}/d_1) of the height h_{11} of the alignment control structure **24a** to the cell-gap d_1 in the R and G pixel regions and the ratio (h_{21}/d_2) of the height h_{21} of the alignment control structure **24b** to the cell-gap d_2 in the B pixel region are set to be substantially equal to each other.

[0078] The ratio of the height h_{11} of the alignment control structure **24a** to the cell-gap d_1 in the R and G pixel regions

and the ratio of the height h_{21} of the alignment control structure to the cell-gap d_2 in the B pixel region are set to be substantially equal to each other for the following reason. That is, the alignment control force of the alignment control structures **24a**, **24b** does not act easily on the liquid crystal molecules **26** as the cell-gap d is larger. Accordingly, in the case that the alignment control structures **24** are formed in the same height in the pixel regions **8** where the cell-gap d is different, the liquid crystal molecules **26** do not easily align in the pixel regions **8R**, **8G**, where the cell-gap d_1 is larger, and in the pixel region **8B**, where the cell-gap d_2 is smaller, the liquid crystal molecules **26** do not easily align. Then, a large difference is made in the threshold voltage between the pixel regions **8** where the cell-gap d differs, which leads to deterioration of the display quality. However, in the present embodiment, the height of the alignment control structures **24** is increased in proportion with the cell-gap d , where by the difficult alignment of the liquid crystal molecules **26** in the pixel regions **8R**, **8G**, where the cell-gap d_1 is larger, can be prevented. Thus, according to the present embodiment, even with different cell-gaps d_1 , d_2 , the threshold voltages in the respective pixel regions **8** can be made substantially equal to each other.

[0079] In the R and the G pixel regions **8R**, **8G**, the width w_{11} of the alignment control structure **24a** is set at, e.g., $12\ \mu\text{m}$. In the B pixel region **8B**, the width w_{21} of the alignment control structure **24b** is set at, e.g., $10\ \mu\text{m}$. The ratio of the width w_{11} of the alignment control structure **24a** to the cell-gap d_1 of the R and the G pixel regions and the ratio of the width w_{21} of the alignment control structure **24b** to the cell-gap d_2 of the B pixel region are set to be substantially equal to each other.

[0080] The ratio of the width w_{11} of the alignment control structure **24a** to the cell-gap d_1 of the R and the G pixel regions and the ratio of the width w_{21} of the alignment control structure **24b** to the cell-gap d_2 of the B pixel region are set to be substantially equal to each other for the following reason. That is, as described above, as the cell-gap d is larger, the alignment control force of the alignment control structures **24** does not easily act on the liquid crystal molecules **26**. Accordingly, in the case that the alignment control structures **24** are formed in the same width in the pixel regions **8**, where the cell-gap d differ, the liquid crystal molecules **26** do not easily align in the pixel regions **8R**, **8G**, where the cell-gap d_1 is larger, but in the pixel region **8B**, where the cell-gap d_2 is smaller, the liquid crystal molecules **26** easily align. Then, a large difference is made in the threshold voltage between the pixel regions **8**, where the cell-gap d differs, which leads to deterioration of the display quality. However, in the present embodiment, the width of the alignment control structures **24** is larger in proportion with the cell-gap d , whereby the difficult alignment of the liquid crystal molecules **26** in the pixel regions **8R**, **8G**, where the cell-gap d_1 is larger, can be prevented. Thus, according to the present embodiment, even in the case that the cell-gap d differs, the threshold voltages in the respective pixel regions **8** can be made substantially equal to each other.

[0081] Thus, the CF substrate **4** is constituted.

[0082] A pole-shaped spacer (not shown), for example, is formed in the B pixel region **8B**. The spacer retains the thickness of the liquid crystal layer **6**.

[0083] Vertical alignment films (not shown) for vertically aligning the liquid crystal molecules **26** are formed respec-

tively on the TFT substrate **2** and the CF substrate **4**. The vertical alignment film can be, e.g., the vertical alignment film made by, JSR Corporation.

[0084] The liquid crystal **6** is sealed between the TFT substrate **2** and the CF substrate **4**. The liquid crystal **6** can be a nematic liquid crystal, which is a liquid crystal having negative dielectric anisotropy. The refractive index anisotropy An of the liquid crystal **6** is, e.g., about 0.1.

[0085] In the liquid crystal display according to the present embodiment, in which the alignment control structures **24** and the alignment control blank patterns **14** are arranged zigzag, roughly 4 directional domains are realized. The alignment directions of the liquid crystal molecules are 45 degrees, 135 degrees, 225 degrees and 315 degrees with 0 degree set on the right side of the display screen. The areas of the respective display domains for the alignment division are substantially uniform in one pixel.

[0086] Thus, the liquid crystal display according to the present embodiment is constituted.

[0087] Next, the result of evaluating the liquid crystal display according to the present embodiment will be explained.

[0088] First, the T-V characteristics of the evaluation result will be explained with reference to FIG. 3. FIG. 3 is a graph of the T-V characteristics of the liquid crystal display according to the present embodiment. In FIG. 3, the $\diamond$ marks indicate the case that the screen was observed at the front. The Δ marks indicate the case that the screen was observed obliquely. In measuring the T-V characteristics, the voltage applied between the pixel electrodes and the opposed electrode was gradually changed, and transmittivities were measured for the applied voltages. In measuring the transmittivity given when observed obliquely, the polar angle of the view point was 60 degrees, and the screen was observed from above.

[0089] As illustrated in FIG. 3, in the liquid crystal display according to the present embodiment, as in said another proposed liquid crystal display, the transmittivity given when observed obliquely is prevented from becoming higher than the transmittivity given when observed at the front (see FIG. 13).

[0090] Based on this, according to the present embodiment, as in said another proposed liquid crystal display, it can be prevented that images are observed more brightly when observed obliquely than when observed at the front.

[0091] Next, the result of comparing the transmittivity will be explained.

[0092] When the transmittivity of the proposed liquid crystal display was 1.0, the transmittivity of said another proposed liquid crystal display was 0.92. The transmittivity of the liquid crystal display according to the present embodiment was 0.93.

[0093] Based on this, the present embodiment can have good transmittivity, as do the proposed liquid crystal display and said another proposed liquid crystal display.

[0094] Next, it was visually observed whether or not the phenomena that the bright of images is higher when observed obliquely than when observed at the front took place.

[0095] This phenomena took place in the proposed liquid crystal display.

[0096] This phenomena did not take place in said another proposed liquid crystal display and the liquid crystal display according to the present embodiment.

[0097] Based on this, it can be seen that the present embodiment can prevent the brightness given when observed obliquely from being higher than the brightness given when observed at the front.

[0098] Next, the result of measuring the gradation chromaticity change characteristics will be explained with reference to FIG. 4. FIG. 4 is a graph of gradation chromaticity change characteristics of the liquid crystal display according to the present embodiment. FIG. 11 is a graph of the gradation chromaticity change characteristics of the proposed liquid crystal display. In measuring the gradation chromaticity change characteristics, the gradation was changed gradually from black to white. The xy chromaticities (x, y) at the respective gradations were measured. In FIGS. 4 and 11, the $\diamond$ marks indicate the case that the screen was observed at the front, and the Δ marks indicate the case that the screen was observed obliquely. In observing the screen obliquely, the polar angle of the view point was 60 degrees, and the screen was observed from above.

[0099] As seen in FIG. 11, in the proposed liquid crystal display, the chromaticity relatively largely changes in accordance with the gradation changes. The differences in the chromaticity between when observed at the front and when obliquely observed are relatively large.

[0100] As described above with reference to FIG. 14, in said another proposed liquid crystal display, the chromaticity largely changes in accordance with the gradation changes. The differences in the chromaticity between when observed at the front and when obliquely observed are relatively large.

[0101] However, in the liquid crystal display according to the present embodiment, as seen in FIG. 4, the chromaticity changes in accordance with the gradation changes are depressed. The differences in the chromaticity between when observed at the front and when obliquely observed are relatively small.

[0102] Based on this, it can be seen that the present embodiment can depress the chromaticity change in accordance with the gradation change and visual angle changes can be depressed, whereby the disturbance of the color balance can be prevented.

[0103] Next, amounts of chromaticity changes given when black color was gradated to white color will be explained.

[0104] In the proposed liquid crystal display, when the screen was observed at the front, the chromaticity change amount given when black color was gradated to white color was 0.102.

[0105] In said another proposed liquid crystal display, when the screen was observed at the front, the amount of the chromaticity change given when black color was gradated to white color was 0.056.

[0106] However, in the liquid crystal display according to the present embodiment, when the screen was observed at

the front, the amount of the chromaticity change given when black color was gradated to white color was 0.046.

[0107] In the proposed liquid crystal display, when observed obliquely, the chromaticity change amount given when black color was gradated to white color was 0.141.

[0108] In said another proposed liquid crystal display, when observed obliquely, the chromaticity change amount given when black color was gradated to white color was 0.168.

[0109] In the liquid crystal display according to the present embodiment, when observed obliquely, the chromaticity change amount given when black color was graded to white color was 0.089.

[0110] In all the cases, in the oblique observation, the polar angle of the view point was 60 degrees, and the screen was observed from above.

[0111] Based on this, the liquid crystal display according to the present embodiment can depress the chromaticity change amount given when black color is gradated to white color both when observed obliquely and when observed at the front.

[0112] Next, whether or not the coloring takes place when black color was gradated to white color was visually observed.

[0113] In the proposed liquid crystal display, the color balance was much disturbed, and the coloring was conspicuous.

[0114] In said another proposed liquid crystal display, the color balance was disturbed, and the coloring took place.

[0115] However, in the liquid crystal display according to the present embodiment, the coloring was not found.

[0116] Based on this, it is found that the present embodiment can depress the disturbance of the color balance, and the coloring can be prevented.

[0117] The liquid crystal display according to the present embodiment is characterized mainly in that the lower threshold regions 11a, 11b and the higher threshold regions 13a, 13b are present in the regions between the alignment control blank patterns 14a, 14b and the alignment control structures 24a, 24b, and the parameters of the alignment control structures 24a, 24b, the alignment control blank patterns 14a, 14b and the electric field control structures 16a, 16b are set corresponding to the cell-gaps d_1 , d_2 .

[0118] In the present embodiment, in which the lower threshold regions 11a, 11b and the higher threshold regions 13a, 13b are present in the regions between the alignment control blank patterns 14a, 14b and the alignment control structures 24a, 24b, the transmittivity corresponding to the applied voltage increase can be slow. Accordingly, the present embodiment can depress much increase of the transmittivity given when observed obliquely in comparison with the transmittivity given when observed at the front, whereby the brightness given when observed obliquely is prevented from becoming higher than the brightness given when observed at the front. Furthermore, according to the present embodiment, the parameters of the alignment control structures 24a, 24b, the alignment control blank patterns 14a, 14b and the electric field control structures 16a, 16b are

set to be proportional to the respective cell-gaps d_1 , d_2 , whereby although the cell-gaps d_1 , d_2 are different from each other, the threshold voltages in the respective pixel regions 8 can be made substantially equal to each other. Accordingly, the present embodiment can prevent large chromaticity changes due to changes in the gradation and the visual angle, which leads to the prevention of the coloring. Thus, the liquid crystal display according to the present embodiment can have good display quality.

Second Embodiment

[0119] The liquid crystal display according to a second embodiment of the present invention will be explained with reference to FIG. 5. FIG. 5 is a perspective view of the liquid crystal display according to the present embodiment. The same members of the present embodiment as those of the liquid crystal display according to the first embodiment illustrated in FIGS. 1 to 4 are represented by the same reference numbers not to repeat or to simplify their explanation.

[0120] The liquid crystal display according to the present embodiment is characterized mainly in that electric field control blank patterns 38a, 38b form higher threshold regions 13a, 13b, and the parameters of the electric field control blank patterns 38a, 38b are different from each other in accordance with the cell-gaps d_1 , d_2 .

[0121] First, a TFT substrate 2a will be explained.

[0122] As illustrated in FIG. 5, in pixel electrodes 12a, 12b, a plurality of electric field control blank patterns 38a, 38b are formed, substantially perpendicularly crossing alignment control blank patterns 14a, 14b. The electric field control blank pattern is a region where ITO is not formed in the pixel electrode. The electric field control blank patterns 38a, 38b are for controlling electric fields to be applied to the liquid crystal molecules 26 to thereby control the threshold voltage. Of the regions between the alignment control structures 24a, 24b and the alignment control blank patterns 14a, 14b, the regions 13a, 13b where the electric field control blank patterns 38a, 38b are formed are higher threshold regions where the threshold voltage is relative higher. Of the regions between the alignment control structures 24a, 24b and the alignment control blank patterns 14a, 14b, the regions 11a, 11b where the electric field control blank patterns 38a, 38b are not formed are lower threshold regions where the threshold voltage is relatively lower. In R and G pixel regions 8R, 8G, the width S_1 of the electric field control blank pattern 38a is set at, e.g., 5 μm . The distance L_1 between the adjacent electric field control blank patterns 38a is set at, e.g., 5 μm . In B pixel region 8B, the width S_2 of the electric field control blank pattern 38b is set at, e.g., 3 μm . The distance L_2 between the adjacent electric field control blank patterns 38b is set at, e.g., 7 μm .

[0123] The width S_2 of the electric field control blank pattern 38b in the B pixel region 8B is set to be smaller than the width S_1 of the electric field control blank pattern 38b in the R and the G pixel regions 8R, 8G for the following reason.

[0124] That is, in the case that the cell-gap d_2 in the B pixel region 8B is smaller than the cell-gap d_1 in the R and the G pixel regions 8R, 8G, but the widths S_1 , S_2 of the electric field control blank patterns 38a, 38b are set to be equal to

each other, and the distances L_1 , L_2 between the adjacent electric field control blank patterns **38a**, **38b** are set to be substantially equal to each other in the respective pixel regions **8**, the strain of the electric fields in the higher threshold region **13b** of the pixel region **8B** becomes larger than the strain of the electric fields in the higher threshold region **13a** of the pixel regions **8R**, **8G**. Accordingly, the threshold voltage in the higher threshold region **13b** of the B pixel region **8B** becomes higher than the threshold voltage in the higher threshold region **13a** of the R and the G pixel regions **8R**, **8G**. However, in the present embodiment, in which the width S_2 of the electric field control blank pattern **38b** in the B pixel region **8B** is set to be smaller, the strain of the electric field due to the electric field control blank pattern **38b** can be mitigated. Thus, According to the present embodiment, the cell-gap d_2 in the B pixel region **8B** is smaller than the cell-gap d_1 in the R and the G pixel regions **8R**, **8G**, but the threshold voltage in the higher threshold region **13b** of the B pixel region **8B** can be made substantially equal to the threshold voltage in the higher threshold region **13a** of the R and the G pixel regions **8R**, **8G**.

[0125] The width w_{12} of the alignment control blank patterns **14a**, **14b** in the R and the G pixel regions **8R**, **8G** are set at, e.g., $12\ \mu\text{m}$, as in the liquid crystal display according to the first embodiment. The width w_{22} of the alignment control blank pattern **14b** in the B pixel region **8B** is set at, e.g., $10\ \mu\text{m}$, as in the liquid crystal display according to the first embodiment.

[0126] Thus, the TFT substrate **2a** is constituted.

[0127] A CF substrate **4** is the same as the CF substrate of the liquid crystal display according to the first embodiment, and the explanation of the CF substrate **4** is omitted.

[0128] A liquid crystal **6** is sealed between the TFT substrate **2a** and the CF substrate **4**, as in the liquid crystal display according to the first embodiment.

[0129] Thus, the liquid crystal display according to the present embodiment is constituted.

[0130] The change of the threshold voltage due to the presence of the electric field control blank patterns **38a**, **38b** is smaller than the change of the threshold voltage due to the presence of the electric field control structures **16a**, **16b**. In term of setting the threshold voltage in the higher threshold regions **13a**, **13b** to be higher, the presence of the electric field control structures **16a**, **16b** is more advantageous than the presence of the electric field control blank patterns **38a**, **38b**. In preventing the phenomena that the brightness given when observed obliquely is higher than the brightness given when observed at the front, the liquid crystal display according to the present embodiment is superior to the liquid crystal display according to the present embodiment.

[0131] However, in the liquid crystal display according to the present embodiment, when the electric field control blank patterns **14a**, **14b** are formed in the pixel electrodes **12a**, **12b**, the electric field control structures **38a**, **38b** can be formed, and it is not necessary to form the electric field control structures **16a**, **16b** separately. Accordingly, the present embodiment can have lower costs than the liquid crystal display according to the first embodiment.

[0132] The liquid crystal display according to the present embodiment is characterized mainly in that, as described

above, the higher threshold regions **13a**, **13b** are formed by the electric field control blank patterns **38a**, **38b**, and the parameters of the electric field control blank patterns **38a**, **38b** are made different in accordance with the cell-gaps d_1 , d_2 .

[0133] According to the present embodiment, in which the parameters of the electric field control blank patterns **38a**, **38b** are made different in accordance with the cell-gaps d_1 , d_2 , as in the liquid crystal display according to the first embodiment, the cell-gap d_2 in the B pixel region **8B** is smaller than the cell-gap d_1 in the R and the G pixel regions **8R**, **8G**, but the threshold voltage in the higher threshold voltage region **13a** of the R and the G pixel regions **8R**, **8G** and the threshold voltage in the higher threshold region **13b** of the B pixel region **8B** can be made substantially equal to each other. Thus, as does the liquid crystal display according to the first embodiment, the present embodiment can prevent the phenomena that the brightness given when obliquely observed from becomes higher than the brightness given when observed at the front while preventing the phenomena of the coloring.

A Third Embodiment

[0134] The liquid crystal display according to a third embodiment of the present invention will be explained with reference to FIG. 6. FIG. 6 is a perspective view of the liquid crystal display according to the present embodiment. The same members of the present embodiment as those of the liquid crystal display according to the first embodiment illustrated in FIGS. 1 to 5 are represented by the same reference numbers not to repeat or to simplify their explanation.

[0135] In FIG. 6, an R pixel region (a third pixel region) **8R** is illustrated on the left side of the drawing, a G pixel region (a first pixel region) **8G** is illustrated at the center of the drawing, and a B pixel region (a second pixel region) **8B** is illustrated on the right side of the drawing.

[0136] In the R pixel region **8R**, the thickness of the liquid crystal layer **6**, the cell-gap d_R is set at $5.5\ \mu\text{m}$. In the G pixel region **8G**, the cell-gap d_G is set at, e.g., $5.0\ \mu\text{m}$. In the B pixel region **8B**, the cell-gap d_B is set at, e.g., $4.0\ \mu\text{m}$.

[0137] The cell-gaps d_R , d_G , d_B of the R, the G, the B pixel regions **8** are different from one another, because the difference in $\Delta n \cdot d / \lambda$, among the respective R, G and B pixel regions **8**. An indicates a refraction index anisotropy, d indicates a cell-gap, and λ indicates a wavelength of light.

[0138] First, a TFT substrate **2b** will be explained.

[0139] Pixel electrodes **12R**, **12G**, **12B** of ITO are formed on a glass substrate **10** (see FIG. 1).

[0140] Respective alignment control blank patterns **14** are formed in the pixel electrodes **12R**, **12G**, **12B**. The width of the alignment control blank patterns **14** is set at, e.g., $12\ \mu\text{m}$.

[0141] In the respective pixel regions **8**, a plurality of electric field control blank patterns **38R**, **38G**, **38B** are formed, substantially perpendicularly crossing the alignment control blank patterns **14**. The electric field control blank patterns **38** are for suitably adjusting the electric field intensity and controlling the threshold voltage.

[0142] In the R pixel region **8R**, the width S_R of the electric field control blank pattern **38R** is set at, e.g., $4.0\ \mu\text{m}$.

The distance L_R between the adjacent electric field control blank patterns **38R** is set at, e.g., $2.0\ \mu\text{m}$.

[0143] In the G pixel region **8G**, the width S_G of the electric field control blank pattern **38G** is set at, e.g., $3.0\ \mu\text{m}$. In the G pixel region **8G**, the distance L_G between the adjacent electric field control blank patterns **38G** is set at, e.g., $3.0\ \mu\text{m}$.

[0144] In the B pixel region **8B**, the width S_B of the electric field control blank pattern **38B** is set at, e.g., $5.0\ \mu\text{m}$. The distance L_B between the adjacent electric field control blank pattern **38B** is set at, e.g., $1.0\ \mu\text{m}$.

[0145] Respective electric field control structures **16** of a dielectric layer are formed on the pixel electrodes **12a**, **12b**. The height of the electric field control structures **16** was set at, e.g., $1.0\ \mu\text{m}$. The width of the electric field control structures **16** is set at, e.g., $50\ \mu\text{m}$. The pitch of the electric field control structures **16** is set at, e.g., $70\ \mu\text{m}$.

[0146] Of the regions between the alignment control blank patterns **14** and the electric field structures **24**, the regions where the electric field control structures **16** are formed are higher threshold regions **13R**, **13G**, **13B**. Of the regions between the alignment control blank patterns **14** and the electric field control structures **24**, the region where the electric field control structures **16** are not formed are lower threshold regions **11R**, **11G**, **11B**.

[0147] In the present embodiment, the widths S and the distances L of the electric field control blank patterns **38R**, **38G**, **38B** are made different from one another in accordance with the cell-gap d_R , d_G , d_B for the following reason.

[0148] That is, in the case that the cell-gaps d of the R, the G and the B pixel regions **8** are different from one another, but the heights, etc. of the electric field control structures **16** are set to be the same in the respective pixel regions **8**, the threshold voltages in the higher threshold regions **13** are made different from one another. Then, the color balance is disturbed, and the phenomena of the coloring takes place.

[0149] However, in the present embodiment, the electric field control blank patterns **38** are formed below the electric field control structures **16**, and the widths S and the distances L of the electric field control blank patterns **38** are suitably set in accordance with the cell-gaps d , whereby even in the case that the heights of the electric field control structures **16** are made the same in the respective pixel regions **8**, the threshold voltages in the higher threshold regions **13R**, **13G**, **13B** in the respective pixel regions **8R**, **8G**, **8B** can be made substantially equal to one another. Thus, the present embodiment can prevent the disturbance of the color balance and the phenomena of the coloring.

[0150] Thus, the TFT substrate **2b** is constituted.

[0151] Next, a CF substrate **4a** will be explained.

[0152] A color filter layer **20R**, **20G**, **20B** is formed on the underside of a glass substrate **18** (see FIG. 1). In the R pixel region **8R**, the thickness of the color filter layer **20R** is set at, e.g., $1.5\ \mu\text{m}$. In the G pixel region **20G**, the thickness of the color filter layer **20G** is set at, e.g., $2.0\ \mu\text{m}$. In the B pixel region **8B**, the thickness of the color filter layer **20B** is set at, e.g., $3.0\ \mu\text{m}$. The thickness of the color filter layer **20B** in the B pixel region **8B** is larger by $1.5\ \mu\text{m}$ than the thickness of the color filter layer **20R** in the R pixel region

8R. The thickness of the color filter layer **20G** in the G pixel region **8G** is larger by $0.5\ \mu\text{m}$ than the thickness of the color filter layer **20R** in the R pixel region **8R**.

[0153] An opposed electrode **22** (see FIG. 1) of ITO is formed on the underside of the color filter layer **20**.

[0154] On the underside of the opposed electrode **22**, alignment control structures **24** are formed. The heights of the alignment control structures **24** are all set at, e.g., $1.5\ \mu\text{m}$. The widths of the alignment control structures **24** are all set at, e.g., $12\ \mu\text{m}$. The pitch of the alignment control structures **24** are all set at, e.g., $70\ \mu\text{m}$.

[0155] Thus, the CF substrate **4a** is constituted.

[0156] A liquid crystal **6** is sealed between the TFT substrate **2b** and the CF substrate **4a**.

[0157] Thus, the liquid crystal display according to the present embodiment is constituted.

[0158] Then, the result of evaluating the liquid crystal display according to the present embodiment will be explained.

[0159] First, change amounts of the chromaticity given when black color was gradated to white color will be explained.

[0160] FIG. 15 is a perspective view of the liquid crystal display according to Control 1. In the liquid crystal display according to Control 1, the widths S_R , S_G , S_B of the electric field control blank patterns **38R**, **38G**, **38B** are all set at $3.0\ \mu\text{m}$. The distances L_R , L_G , L_B between the adjacent electric field control blank patterns **38R**, **38G**, **38B** are all set at $3.0\ \mu\text{m}$.

[0161] In the liquid crystal display according to Control 1, change amounts of the chromaticities given when black color was gradated to white color were 0.048 when observed at the front and 0.143 when observed obliquely.

[0162] In contrast to this, in the liquid crystal display according to the present embodiment, the change amounts of the chromaticities given when black color was gradated to white color were 0.032 when observed at the front and 0.068 when observed obliquely.

[0163] In all the cases, for the oblique observation, the polar angle of the visual angle was 60 degrees, and the screen was observed from above.

[0164] Based on this, it is found that the liquid crystal display according to the present embodiment can suppress the chromaticity change amount given when black color is gradated to white color both when observed at the front and when observed obliquely.

[0165] Next, it was visually observed whether or not the phenomena that images are observed dark when observed at the front but bright when observed obliquely takes place.

[0166] Such phenomena took place neither in the liquid crystal display according to Control 1 nor in the liquid crystal display according to the present embodiment.

[0167] Based on this, it can be seen that the present embodiment can prevent the brightness given when observed obliquely from being higher than the brightness given when observed at the front.

[0168] Then, it was observed visually whether or not the phenomena that the color balance is disturbed when black color is gradated to white color takes place.

[0169] In the liquid crystal display according to Control 1, the phenomena that the color balance is disturbed, and the coloring takes place. More specifically, yellowish coloring took place at specific half tones.

[0170] In contrast to this, in the liquid crystal display according to the present embodiment, the coloring phenomena was not confirmed at all the tones.

[0171] Based on this, the liquid crystal display according to the present embodiment can prevent the occurrence of the coloring phenomena, whereby the liquid crystal display can have good display quality.

[0172] The liquid crystal display according to the present embodiment is characterized mainly in that the width and distance of the electric field control blank patterns 38 can be set suitably in accordance with the cell-gaps d .

[0173] In the present embodiment, the parameters of the electric field control blank patterns 38, such as the width, the distance, etc., are set suitably in accordance with the cell-gaps d , whereby even in the case that the parameters of the electric field control blank patterns 14, the electric field control structures 16 and the alignment control structures 24 are set the same among the respective pixel regions 8, the threshold voltages in the higher threshold regions 13 can be made substantially the same. Thus, the present embodiment can prevent the occurrence of the phenomena that the brightness given when observed obliquely than the brightness given when observed at the front while preventing the occurrence of the coloring.

[0174] According to the present embodiment, the parameters of the electric field control structures 16, since the alignment control structures 24, etc. are set to be the same among the respective pixel regions 8, it is possible to simply the fabrication process of the liquid crystal display.

[0175] According to the present embodiment, the parameters of the electric field control structures 16, the alignment control structures 24, etc. are set to be the same among the respective pixel regions 8, whereby the response speed is prevented from varying among the respective regions 8.

A Fourth Embodiment

[0176] The liquid crystal display according to a fourth embodiment of the present invention will be explained with reference to FIG. 7. FIG. 7 is a perspective view of the liquid crystal display according to the present embodiment. The same members of the present embodiment as those of the liquid crystal display according to the first to the third embodiments illustrated in FIGS. 1 to 6 are represented by the same reference numbers not to repeat or to simplify their explanation.

[0177] The liquid crystal display according to the present embodiment is characterized mainly in that an electric field control blank pattern 16B (see FIG. 6B) is not formed in the higher threshold region 13B of a B pixel region 8B.

[0178] First, a TFT substrate 2c will be explained.

[0179] As illustrated in FIG. 7, as in the liquid crystal display according to the third embodiment, an electric field

control blank pattern 38R is formed in the higher threshold region 13R of an R pixel region 8R. The parameters of the electric field control blank pattern 38R are set to be the same as those in the liquid crystal display according to the third embodiment.

[0180] As in the liquid crystal display according to the third embodiment, an electric field control blank pattern 38G is formed in a G pixel region 8G. The parameters of the electric field control blank pattern 38G are set to be the same as those in the liquid crystal display according to the third embodiment.

[0181] In the B pixel region 8B, however, the electric field control blank pattern 38B is not formed (see FIG. 6). In the present embodiment, the electric field control blank pattern 38B is not formed in the B pixel region 8B for the following reason. That is, as described above in the third embodiment, it is preferable that in the B pixel region 8B, the width S_B of the electric field control blank pattern 38B is set at about $1.0 \mu\text{m}$. In terms of the fabrication process, however, it is not easy to form the electric field control blank pattern 38B having a width of $3.0 \mu\text{m}$ or below $3.0 \mu\text{m}$. When the electric field control blank pattern 38B of an about $1.0 \mu\text{m}$ -width is formed, the width S_B of the electric field control blank pattern 38B is varied, which is a factor for disuniform display, etc. Then, in the present embodiment, the electric field control blank pattern 38B is not formed in the B pixel region 8B. The electric field control blank pattern 38B having such an extremely small width is not effective in reducing the electric field intensity, and the absence of the electric field control blank pattern 38B never affect the display characteristics.

[0182] Thus, the TFT substrate 2c is constituted.

[0183] The CF substrate 4a is the same as that of the liquid crystal display according to the third embodiment described above with reference to FIG. 6, and the description of the CF substrate 4a will be omitted.

[0184] A liquid crystal 6 is sealed between the TFT substrate 2c and the CF substrate 4.

[0185] Thus, the liquid crystal display according to the present embodiment is constituted.

[0186] Next, the result of evaluating the liquid crystal display according to the present embodiment will be explained.

[0187] First, change amounts of chromaticities given when black color was gradated to white color will be explained.

[0188] In the liquid crystal display according to the present embodiment, the change amounts of chromaticities given when black color was gradated to white color were 0.040 when observed at the front and was 0.081 when observed obliquely. For the oblique observation, the polar angle of the view point was 60 degrees, and the screen was observed from above.

[0189] Based on this, it is seen that the liquid crystal display according to the present embodiment can more decrease the change amount of the chromaticity given when black color is graded to white color in comparison with the liquid crystal display according to Control 1 described above.

[0190] However, in the liquid crystal display according to the present embodiment, the change amount of the chromaticity given when black color is gradated to white color is larger in comparison with that in the liquid crystal display according to the third embodiment described above.

[0191] Next, whether or not the phenomena that the brightness given when observed obliquely is higher than the brightness given when observed at the front takes place was visually observed.

[0192] In the liquid crystal display according to the present embodiment, this phenomena did not take place. Based on this, the present embodiment as well can prevent the brightness given when observed obliquely from being higher than the brightness given when observed at the front.

[0193] Next, whether or not the coloring phenomena takes place when black color is gradated to white color was visually observed.

[0194] In the liquid crystal display according to the present embodiment, the so-called coloring was not confirmed. Based on this, the present embodiment can prevent the coloring phenomena.

[0195] As described above, the liquid crystal display according to the present embodiment is characterized mainly in that the electric field control blank pattern 38B is not formed in the higher threshold region 13B of the B pixel region 8B.

[0196] As described above, in terms of the fabrication process, it is not easy to form the electric field control blank pattern 38B of an extremely small width. When the electric field control blank pattern 38B of an extremely small width is formed, the width of the electric field control blank pattern 38B is varied, which is a factor for disuniform display, etc. However, in the present embodiment, the electric field control blank pattern 38B is not formed in the B pixel region 8B intentionally, where the electric field control blank pattern 38B must be formed in a narrow width, whereby the occurrences of disuniform displays, etc. can be prevented.

A Fifth Embodiment

[0197] The liquid crystal display according to a fifth embodiment of the present invention will be explained with reference to FIG. 8. FIG. 8 is a perspective view of the liquid crystal display according to the present embodiment. The same members of the present embodiment as those of the liquid crystal display according to the first to the fourth embodiments illustrated in FIGS. 1 to 7 are represented by the same reference numbers not to repeat to simplify their explanation.

[0198] The liquid crystal display according to the present embodiment is characterized mainly in that the cell-gap d_R in an R pixel region 8R and the cell-gap d_G in a G pixel region 8G are set to be equal to each other.

[0199] First, a TFT substrate 2d will be explained.

[0200] As illustrated in FIG. 8, an electric field control blank pattern 38R is formed in a pixel electrode 12R in the R pixel region 8R. The width S_R of the electric field control blank pattern 38R is set at, e.g., $3.0\ \mu\text{m}$. The distance L_R of the adjacent electric field control blank patterns 38R is set at, e.g., $3.0\ \mu\text{m}$.

[0201] An electric field control blank pattern 38G is formed in the pixel electrode 12G in a G pixel region 8G, as in the liquid crystal display according to the third embodiment. The parameters of the electric field control blank pattern 38G are set to be the same as those of the liquid crystal display according to the third embodiment.

[0202] The parameters of the electric field control blank pattern 38R in the R pixel region 8R and the parameter of the electric field control blank pattern 38G in the G pixel region 8G are set to be equal to each other. In the present embodiment, the parameters of the electric field control blank pattern 38R in the R pixel region 8R and the parameters of the electric field control blank pattern 38G in the G pixel region 8G are set to be equal to each other, because, as will be described later, the cell-gap d_R in the R pixel region 8R and the cell-gap d_G in the G pixel region 8G are set to be equal to each other.

[0203] An electric field control blank pattern 38B (see FIG. 6) is not formed in the B pixel region 8B, as is not in the liquid crystal display according to the fourth embodiment.

[0204] Thus, the TFT substrate 2d is constituted.

[0205] Next, a CF substrate 4b will be explained.

[0206] A color filter layer 20R, 20G, 20B is formed on the underside of a glass substrate 18 (see FIG. 1). The thickness of the color filter layer 20R, 20G in the R and the G pixel region 8R, 8G is set at, e.g., $2.0\ \mu\text{m}$. The thickness of the color filter layer 20B in the B pixel region 8B is set at, e.g., $3.0\ \mu\text{m}$. The thickness of the color filter layer 20B in the B pixel region 8B is set to be larger by $1.0\ \mu\text{m}$ than the thickness of the color filter layer 20R, 20G in the R and the G pixel regions 8R, 8G.

[0207] An opposed electrode 22 (see FIG. 1) of ITO is formed on the underside of the color filter layer 20.

[0208] Alignment control structures 24 are formed on the underside of the opposed electrode 22. The height of the alignment control structures 24 is all set at, e.g., $1.5\ \mu\text{m}$, as is in the liquid crystal display according to the third and the fourth embodiments. The width of the alignment control structures 24 is all set at, e.g., $12\ \mu\text{m}$ as is in the liquid crystal display according to the third and the fourth embodiments. The pitch (period) of the alignment control structures 24 is set at, e.g., $70\ \mu\text{m}$.

[0209] Thus, the CF substrate 4b is constituted.

[0210] A liquid crystal 6 is sealed between the TFT substrate 2d and the CF substrate 4b.

[0211] The cell-gap d_R in the R pixel region 8R and the cell-gap d_G in the G pixel region 8G are both set at, e.g., $5.0\ \mu\text{m}$. The cell-gap d_B in the B pixel region 8B is set at, e.g., $4.0\ \mu\text{m}$.

[0212] In the present embodiment, the cell-gap d_R in the R pixel region 8R and the cell-gap d_G in the G pixel region 8G are set to be equal to each other so as to simplify the structure and reduce the cost.

[0213] For the following reason, the cell-gap d_G in the G pixel region 8G and the cell-gap d_B in the B pixel region 8B are not set to be equal to each other, but the cell-gap d_R in the R pixel region 8R and the cell-gap d_G in the G pixel

region **8G** are set to be equal to each other. That is, when the cell-gap d is set to be larger than an idealistic value, the alignment control of the liquid crystal molecules **26** (see **FIG. 1**) is difficult, and resultantly defective displays, such as rough displays, etc., tend to occur. Accordingly, it is more preferable that the cell-gap d is smaller than an idealistic value than larger than the idealistic value. The difference in $\Delta n \cdot d / \lambda$ is smaller with the cell-gap d_R in the R pixel region **8R** set to be equal to the cell-gap d_G in the G pixel region **8G** than with the cell-gap d_G in the G pixel region set to be equal to the cell-gap d_B in the B pixel region **8B**. For such reason, in the present embodiment, the cell-gap d_G in the G pixel region **8G** and the cell-gap d_B in the B pixel region **8B** are not set to be equal to each other, but the cell-gap d_R in the R pixel region **8R** and the cell-gap d_G in the G pixel region **8G** are set to be equal to each other.

[0214] Thus, the liquid crystal display according to the present embodiment is constituted.

[0215] Then, the result of evaluating the liquid crystal display according to the present embodiment will be explained.

[0216] Change amounts of the chromaticities given when black color was gradated to white color will be explained.

[0217] **FIG. 16** is a perspective view of the liquid crystal display according to Control **2**. In the liquid crystal display according to Control **2**, the widths S_R , S_G , S_B of the electric field control blank patterns **38R**, **38G**, **38B** were all set at $3.0 \mu\text{m}$. The distances L_R , L_G , L_B of the electric field control blank patterns **38R**, **38G**, **38B** were all set at $3.0 \mu\text{m}$. The cell-gap d_R in the R pixel region **8R** and the cell-gap d_G in the G pixel region **8G** are set to be equal to each other. Specifically, the cell-gap d_R in the R pixel region **8R** and the cell-gap d_G in the G pixel region **8G** were set at $5.0 \mu\text{m}$. The cell-gap in the B pixel region **8B** was set at $4.0 \mu\text{m}$, as is in the liquid crystal display according to the present embodiment.

[0218] In the liquid crystal display according to Control **2**, the chromaticity change amount given when black color was gradated to white color is 0.056 when observed at the front and was 0.168 when obliquely observed.

[0219] In contrast to this, in the liquid crystal display according to the present embodiment, the chromaticity change amount given when black color was gradated to white color was 0.053 when observed at the front and was 0.092 when obliquely observed.

[0220] For the oblique observation, the polar angle of the view point was 60 degrees, and the screen was observed from above.

[0221] Based on this, it is seen that the liquid crystal display according to the present embodiment can more reduce the chromaticity change amount given when black color is gradated to white color than the liquid crystal display according to Control **2**.

[0222] However, in comparison with the chromaticity change amount of the liquid crystal display according to the third and the fourth embodiments given when black color is gradated to white color, the chromaticity change amount of the liquid crystal display according to the present embodiment is larger.

[0223] Next, whether or not the phenomena that the brightness given when observed obliquely is higher than the brightness given when observed at the front takes place was visually observed.

[0224] In the liquid crystal display according to the present embodiment as well, such phenomena did not take place. Based on this, it is seen that the present embodiment can prevent the brightness given when observed obliquely from being higher than the brightness given when observed at the front.

[0225] Next, whether or not the coloring phenomena takes place when black color is gradated to white color was visually observed.

[0226] In the liquid crystal display according to the present embodiment, the coloring phenomena was not confirmed. Based on this, it is seen that the present embodiment can prevent the occurrence of the coloring phenomena.

[0227] The liquid crystal display according to the present embodiment is characterized mainly in that, as described above, the cell-gap d_R in the R pixel region **8R** and the cell-gap d_G in the G pixel region **8G** are set to be equal to each other.

[0228] According to the present embodiment, the cell-gap d_R in the R pixel region **8R** and the cell-gap d_G in the G pixel region **8G** are set to be equal to each other, whereby the structure can be simple. Accordingly, the liquid crystal display according to the present embodiment can have good display quality at low cost.

Modified Embodiments

[0229] The present invention is not limited to the above-described embodiments and can cover other various modifications.

[0230] In the above-described embodiments, the present invention is applied to, e.g., MVA type liquid crystal displays, but the principle of the present invention is applicable not only to MVA type liquid crystal displays, but also to any other liquid crystal displays.

[0231] In the above-described embodiments, the alignment control blank patterns are formed as the alignment control means formed on the TFT substrate. However, the alignment control means formed on the TFT substrate is not limited to the alignment control blank pattern, and alignment control structures may be formed as the alignment control means formed on the TFT substrate.

[0232] In the above-described embodiments, the alignment control structure is formed as the alignment control means formed on the CF substrate. However, the alignment control means formed on the CF substrate is not limited to the alignment control structure. For example, alignment control blank pattern may be formed as the alignment control means formed on the CF substrate.

[0233] In the above-described embodiments, the alignment control blank pattern is formed on the TFT substrate, and on the CF substrate the alignment control structure is formed. However, the alignment control structure may be formed on the TFT substrate, and the alignment control blank pattern may be formed on the CF substrate.

[0234] In the above-described embodiments, the electric field control structure is formed on the TFT substrate but may be formed on the CF substrate.

[0235] In the above-described embodiments, the electric field control blank pattern is formed in the pixel electrode on the TFT substrate but may be formed in the opposed electrode on the CF substrate.

[0236] In the above-described embodiments, the width and the distance of the electric field control blank pattern are suitably set, but the pitch of the electric field control blank pattern may be suitably set.

[0237] In the above-described embodiments, the electric field control blank pattern is formed in stripes but may be formed in a mesh.

[0238] In the above-described embodiments, the alignment control structure and the electric field control structure are formed of dielectrics, but the materials of the alignment control structure and the electric field control structure are not limited to dielectrics. A conductor may be suitably used as a material of the alignment control structure and electric field control structure.

[0239] In the above-described embodiments, the layout is made with the center line of the alignment control blank pattern and that of the electric field control structure in agreement with each other. However, the layout is not limited to the layout described above. However, the electric field control structure functions as alignment control means, and it is preferable to arrange the electric field control structure suitably to align the liquid crystal molecules in a desired direction.

[0240] In the above-described embodiments, the electric field control blank pattern has a rectangular shape. However, the shape of the electric field control blank pattern is not limited to the rectangular shape. The electric field control blank pattern may be, e.g., wedge-shaped.

What is claimed is:

1. A liquid crystal display comprising:

- a first substrate including a first pixel electrode and a second pixel electrode;
- a second substrate with an opposed electrode formed on, the opposed electrode opposing to the first pixel electrode and the second pixel electrode; and
- a liquid crystal layer sealed between the first substrate and the second substrate,
- a thickness of the liquid crystal layer in a first pixel region on the first pixel electrode being larger than a thickness of the liquid crystal layer in a second pixel region on the second pixel electrode;
- the first pixel region including a first partial region, and a second partial region where a threshold voltage is higher than in the first partial region, and the second pixel region including a third partial region and a fourth partial region where a threshold voltage is higher than in the third partial region, and
- the threshold voltage in the first partial region and the threshold voltage in the third partial region being equal to each other, and the threshold voltage in the second

partial region and the threshold voltage in the fourth partial region being equal to each other.

2. A liquid crystal display according to claim 1, wherein

- a first electric field control structure for controlling an electric field to be applied to a liquid crystal molecule of the liquid crystal layer being formed on the first substrate or the second substrate in the second partial region,
- a second electric field control structure for controlling an electric field to be applied to a liquid crystal molecule of the liquid crystal layer being formed on the first substrate or the second substrate in the fourth partial region, and
- a height of the first electric field control structure being larger than a height of the second electric field control structure.

3. A liquid crystal display according to claim 2, wherein

- a ratio of the height of the first electric field control structure to the thickness of the liquid crystal layer in the first pixel region, and a ratio of the height of the second electric field control structure to the thickness of the liquid crystal layer in the second pixel region are equal to each other.

4. A liquid crystal display according to claim 2, wherein

- a first alignment control structure for controlling an alignment direction of the liquid crystal molecule of the liquid crystal layer is formed on the first substrate or the second substrate in the first pixel region,
- a second alignment control structure for controlling an alignment direction of the liquid crystal molecule of the liquid crystal layer on the first substrate or the second substrate in the second pixel region, and
- a height of the first alignment control structure is larger than a height of the second alignment control structure.

5. A liquid crystal display according to claim 4, wherein

- a ratio of the height of the first alignment control structure to the thickness of the liquid crystal layer in the first pixel region, and a ratio of the height of the second alignment control structure to the thickness of the liquid crystal layer in the second pixel region are equal to each other.

6. A liquid crystal display according to claim 2, wherein

- a first alignment control structure for controlling an alignment direction of the liquid crystal molecule of the liquid crystal layer is formed on the first substrate or the second substrate in the first pixel region,
- a second alignment control structure for controlling an alignment direction of the liquid crystal molecule of the liquid crystal layer is formed on the first substrate or the second substrate in the second pixel region, and
- a width of the first alignment control structure is larger than a width of the second alignment control structure.

7. A liquid crystal display according to claim 6, wherein

- a ratio of the width of the first alignment control structure to the thickness of the liquid crystal layer in the first pixel region, and a ratio of the width of the second

- alignment control structure to the thickness of the liquid crystal layer in the second pixel region are equal to each other.
- 8.** A liquid crystal display according to claim 2, wherein
- a first alignment control blank pattern for controlling an alignment direction of a liquid crystal molecule of the liquid crystal layer is formed on the first pixel electrode or the opposed electrode in the first pixel region,
 - a second alignment control blank pattern for controlling an alignment direction of a liquid crystal molecule of the liquid crystal layer is formed on the second pixel electrode or the opposed electrode in the second pixel region, and
 - a width of the first alignment control blank pattern is larger than a width of the second alignment control blank pattern.
- 9.** A liquid crystal display according to claim 8, wherein
- a ratio of the width of the first alignment control blank pattern to the thickness of the liquid crystal layer in the first pixel region, and a ratio of the width of the second alignment control blank pattern to the thickness of the liquid crystal layer in the second pixel region are equal to each other.
- 10.** A liquid crystal display according to claim 1, wherein
- a plurality of electric field control blank patterns for controlling an electric field to be applied to a liquid crystal molecule of the liquid crystal layer are formed on the first pixel electrode or the opposed electrode in the second partial region,
 - a plurality of second electric field control blank patterns for controlling an electric field to be applied to a liquid crystal molecule of the liquid crystal layer are formed in the second pixel electrode or the opposed electrode in the fourth partial region, and
 - a width or a pitch of the first electric field control blank patterns is different from a width or a pitch of the second electric field control blank patterns.
- 11.** A liquid crystal display according to claim 2, wherein
- the first pixel region is a pixel region for displaying red color or green color, and
 - the second pixel region is a pixel region for displaying blue color.
- 12.** A liquid crystal display according to claim 1, wherein
- the first substrate further includes a third pixel electrode,
 - a thickness of the liquid crystal layer in a third pixel region on the third pixel electrode is larger than a thickness of the liquid crystal layer in the first pixel region,
 - the third pixel region includes a fifth partial region, and a sixth partial region where a threshold voltage is higher than in the fifth partial region, and
 - a threshold voltage in the first partial region, a threshold voltage in the third partial region and a threshold voltage in the fifth partial region are equal to each other, and a threshold voltage in the second partial region, a threshold voltage in the fourth partial region and a threshold voltage in the sixth partial region are equal to each other.
- 13.** A liquid crystal display according to claim 12, wherein
- the first pixel region is a pixel region for displaying green color,
 - the second pixel region is a pixel region for displaying blue color, and
 - the third pixel region is a pixel region for displaying red color.
- 14.** A liquid crystal display according to claim 1, wherein
- a first electric field control structure for controlling an electric field to be applied to a liquid crystal molecule of the liquid crystal layer is formed on the first substrate or the second substrate in the second partial region, and a second electric field control structure for controlling an electric field to be applied to a liquid crystal molecule of the liquid crystal layer is formed on the first substrate or the second substrate in the fourth partial region,
 - a plurality of the first electric field control blank patterns for controlling an electric field to be applied to a liquid crystal molecule of the liquid crystal layer are formed on the first pixel electrode or the opposed electrode in the second partial region, and a plurality of the second electric field control blank patterns for controlling an electric field to be applied to a liquid crystal molecule of the liquid crystal layer are formed on the second pixel electrode or the opposed electrode in the fourth partial region, and
 - a width or a pitch of the first electric field control blank pattern is different from a width or a pitch of the second electric field control blank pattern.
- 15.** A liquid crystal display according to claim 14, wherein
- a first alignment control blank pattern for controlling an alignment direction of a liquid crystal molecule of the liquid crystal layer is formed on the first pixel electrode or the opposed electrode in the second partial region,
 - a second alignment control blank pattern for controlling an alignment direction of a liquid crystal molecule of the liquid crystal layer is formed on the second pixel electrode or the opposed electrode in the fourth partial region,
 - the first electric field control blank pattern is formed, crossing the first alignment control blank pattern vertically, and
 - the second electric field control blank pattern is formed, crossing the second alignment control blank pattern vertically.
- 16.** A liquid crystal display according to claim 15, wherein
- the first substrate further includes a third pixel electrode,
 - a thickness of the liquid crystal layer in a third pixel region on the third pixel electrode is larger than a thickness of the liquid crystal layer in the first pixel region,
 - the third pixel region includes a fifth partial region, and a sixth partial region where a threshold voltage is higher than in the fifth partial region,
 - a third electric field control structure for controlling an electric field to be applied to a liquid crystal molecule

- of the liquid crystal layer is formed on the first substrate or the second substrate in the sixth partial region,
- a plurality of the third electric field control blank patterns for controlling an electric field to be applied to a liquid crystal molecule of the liquid crystal layer are formed on the third pixel electrode or the opposed electrode in the sixth partial region, and
- a width or a pitch of the third electric field control blank pattern is different from a width or a pitch of the first and the second electric field control blank pattern.
- 17.** A liquid crystal display according to claim 1, wherein
- a first electric field control structure for controlling an electric field to be applied to a liquid crystal molecule of the liquid crystal layer is formed on the first substrate or the second substrate in the second partial region, and a second electric field control structure for controlling an electric field to be applied to a liquid crystal molecule of the liquid crystal layer is formed on the first substrate or the second substrate in the fourth partial region, and
- a plurality of electric field control blank patterns for controlling an electric field to be applied to a liquid crystal molecule of the liquid crystal layer are formed on the first pixel electrode or the opposed electrode in the second partial region, and the electric field control blank pattern is not formed on the second pixel electrode and the opposed electrode in the fourth partial region.
- 18.** A liquid crystal display according to claim 17, wherein
- a first alignment control blank pattern for controlling an alignment direction of a liquid crystal molecule of the liquid crystal layer is formed on the first pixel electrode or the opposed electrode in the second partial region,
- a second alignment control blank pattern for controlling an alignment direction of a liquid crystal molecule of the liquid crystal layer is formed on the second pixel electrode or the opposed electrode in the fourth partial region, and
- said plurality of electric field control blank patterns are formed, crossing the first alignment control blank pattern vertically.
- 19.** A liquid crystal display according to claim 17, wherein the first substrate further includes a third pixel electrode,
- a thickness of the liquid crystal layer on the third pixel electrode in the third pixel region is larger than a thickness of the liquid crystal layer in the first pixel region,
- the third pixel region includes a fifth partial region, and a sixth partial region where a threshold voltage is higher than in the fifth partial region,
- a third electric field control structure for controlling an electric field to be applied to a liquid crystal molecule of the liquid crystal layer is formed on the first substrate or the second substrate in the sixth partial region,
- a plurality of other electric field control blank patterns for controlling an electric field to be applied to a liquid crystal molecule of the liquid crystal layer are formed on the third pixel electrode or the opposed electrode in the sixth partial region, and
- a width or a pitch of said other electric field control blank pattern is equal to a width or a pitch of said electric field control blank pattern.
- 20.** A liquid crystal display according to claim 17, wherein the first substrate further includes a third pixel electrode,
- a thickness of the liquid crystal layer in a third pixel region on the third pixel electrode is equal to a thickness of the liquid crystal layer in the first pixel region,
- the third pixel region includes a fifth partial region, and a sixth partial region where a threshold voltage is higher than in the fifth partial region,
- a third electric field control structure for controlling an electric field to be applied to a liquid crystal molecule of the liquid crystal layer is formed on the first substrate or the second substrate in the sixth partial region,
- a plurality of other electric field control blank patterns for controlling an electric field to be applied to a liquid crystal molecule of the liquid crystal layer are formed on the third pixel electrode or the opposed electrode in the sixth partial region, and
- a width or a pitch of said other electric field control blank pattern is equal to a width or a pitch of said electric field control blank pattern.
- 21.** A liquid crystal display according to claim 16, wherein the first pixel region is a pixel region for displaying green color,
- the second pixel region is a pixel region for displaying blue color, and
- the third pixel region is a pixel region for displaying red color.
- 22.** A liquid crystal display according to claim 19, wherein the first pixel region is a pixel region for displaying green color,
- the second pixel region is a pixel region for displaying blue color, and
- the third pixel region is a pixel region for displaying red color.
- 23.** A liquid crystal display according to claim 20, wherein the first pixel region is a pixel region for displaying green color,
- the second pixel region is a pixel region for displaying blue color, and
- the third pixel region is a pixel region for displaying red color.
- 24.** A liquid crystal display according to claim 1, wherein the liquid crystal layer is formed of a liquid crystal having negative dielectric anisotropy.

专利名称(译)	液晶显示器		
公开(公告)号	US20050184939A1	公开(公告)日	2005-08-25
申请号	US10/890977	申请日	2004-07-14
[标]申请(专利权)人(译)	富士通显示技术股份有限公司 友达光电股份有限公司		
申请(专利权)人(译)	富士通显示器科技股份有限公司 友达光电股份有限公司		
当前申请(专利权)人(译)	友达光电股份有限公司		
[标]发明人	UEDA KAZUYA KAMADA TSUYOSHI YOSHIDA HIDEFUMI KOIKE YOSHIO OKAMOTO KENJI		
发明人	UEDA, KAZUYA KAMADA, TSUYOSHI YOSHIDA, HIDEFUMI KOIKE, YOSHIO OKAMOTO, KENJI		
IPC分类号	G02F1/1333 G02F1/133 G02F1/1337 G02F1/1343 G09G3/36		
CPC分类号	G02F1/133371 G02F1/1393 G02F1/133707		
优先权	2004047677 2004-02-24 JP		
其他公开文献	US7466295		
外部链接	Espacenet USPTO		

摘要(译)

液晶显示器包括：第一基板2，包括第一像素电极12a和第二像素电极12b；第二基板4，其上形成有对置电极22；以及液晶层6，密封在第一基板2和第二基板之间第一像素区域8R，8G中的第一像素电极12a上的液晶层6的厚度d1大于第二像素区域8B中的第二像素电极12b上的液晶层6的厚度d2。第一像素区域8R，8G包括第一部分区域11a和第二部分区域13a，其中阈值电压高于第一部分区域11a中的阈值电压。第二像素区域8B包括第三部分区域11b和第四部分区域13b，其中阈值电压高于第三部分区域11b中的阈值电压。第一部分区域11a中的阈值电压和第三部分区域11b中的阈值电压彼此相等，并且第二部分区域13a中的阈值电压和第四部分区域13b中的阈值电压彼此相等。因此，可以防止由于灰度和视角变化引起的色度的大的变化，这导致防止着色的发生。因此，可以提供具有良好显示质量的液晶显示器。

