



US006657607B1

(12) **United States Patent**
Evanicky et al.

(10) **Patent No.: US 6,657,607 B1**
(45) **Date of Patent: *Dec. 2, 2003**

(54) **LIQUID CRYSTAL FLAT PANEL DISPLAY
WITH ENHANCED BACKLIGHT
BRIGHTNESS AND SPECIALLY SELECTED
LIGHT SOURCES**

5,931,555 A	8/1999	Akahane et al.
5,982,542 A	11/1999	Hannon et al.
6,184,940 B1	2/2001	Sano
6,201,893 B1	3/2001	Shiraiwa et al.
6,238,827 B1	5/2001	Nakazawa et al.

(75) Inventors: **Daniel E. Evanicky**, San Jose, CA
(US); **Sun Lu**, San Jose, CA (US)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Silicon Graphics, Inc.**, Mountain View,
CA (US)

DE	3331724 A1	3/1985
WO	95/17699	6/1995
WO	97/20238	6/1997

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 310 days.

This patent is subject to a terminal dis-
claimer.

OTHER PUBLICATIONS

Patent Abstract of Japan, vol. 097, No. 009, Sep. 30, 1997
& JP 09113871A (SONY) May 2, 1997.

"White Balance Control Methods of Liquid Crystal Dis-
play", IBM Technical Disclosure Bulletin, vol. 37, No. 11,
Nov. 1, 1994, pp. 425/426.

Primary Examiner—Kent Chang

(74) *Attorney, Agent, or Firm*—Baker Botts L.L.P.

(21) Appl. No.: **09/811,988**

(22) Filed: **Mar. 19, 2001**

(57) **ABSTRACT**

Related U.S. Application Data

(63) Continuation of application No. 09/087,280, filed on May
29, 1998, now Pat. No. 6,243,068.

(51) **Int. Cl.**⁷ **G09G 3/36**

(52) **U.S. Cl.** **345/88; 345/87; 345/102**

(58) **Field of Search** 345/87, 88, 102,
345/589, 591, 593; 348/61, 69, 70-72;
362/26, 31, 62; 349/61, 62


(56) **References Cited**

U.S. PATENT DOCUMENTS

5,202,950 A	4/1993	Arego et al.
5,593,221 A	1/1997	Evanicky et al.
5,696,529 A	12/1997	Evanicky et al.
5,696,567 A	12/1997	Wada et al.
5,710,607 A	1/1998	Iwamoto et al.
5,815,204 A	9/1998	Abe et al.
5,867,239 A	2/1999	Sahouani et al.

Brightness in the LCD is enhanced by polarization recycling
using a pre-polarizing film to pre-polarize light, and a
special reflector for recycling light reflected by the pre-
polarizing film. In one embodiment, the pre-polarizing film
comprises a layer of DBEF brightness enhancement film,
and the rear reflector is made of a PTFE material. In another
embodiment, the rear reflector is covered with a film com-
prising barium sulfate. The multiple light sources are
selected such that, at any color temperature within a prede-
termined range, the brightness of the LCD is not reduced
below a given threshold minimum (e.g., 70 percent of the
maximum brightness). Another constraint for selecting the
light sources is that within the predetermined color tempera-
ture range, the color temperature is held close to the black
body curve of the CIE chromaticity diagram. The light
sources are also selected so that their maximum brightness
point is set to be near the middle of the predetermined color
temperature range.

25 Claims, 32 Drawing Sheets






FIG. 1A




FIG. 1B




FIG. 1C

36




FIG. 1D




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 4




FIG. 5




FIG. 6

FIG. 7A




FIG. 7B

CCFL Emission Spectrum




FIG. 7C

226

CCFL Emission Spectrum




FIG. 8A





FIG. 8B

232

CCFL Emission Spectrum



240

Color Temperature Adjustment

Case #29: CCFL1 - 11670 K, CCFL2 - 3623 K




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 9D




FIG. 10A




FIG. 10B




FIG. 11




FIG. 12




FIG. 13A




FIG. 13B




FIG. 13C




FIGURE 14

Figure 15




Figure 16





Figure 17






FIG. 18A




FIG. 18B


930

FIG. 18C

LIQUID CRYSTAL FLAT PANEL DISPLAY WITH ENHANCED BACKLIGHT BRIGHTNESS AND SPECIALLY SELECTED LIGHT SOURCES

This is a continuation of application(s) Ser. No. 09/087,280 filed on May 29, 1998, now U.S. Pat. No. 6,243,068.

BACKGROUND OF THE INVENTION

(1) Field of the Invention

The present invention relates to the field of display devices. More specifically, the present invention relates to the field of flat panel display devices utilizing liquid crystal display (LCD) technology.

(2) Prior Art

Flat panel displays or liquid crystal displays (LCDs) are popular display devices for conveying information generated by a computer system. The decreased weight and size of a flat panel display greatly increases its versatility over a cathode ray tube (CRT) display. High quality flat panel displays are typically back-lit. That is, a source of illumination is placed behind the LCD layers to facilitate visualization of the resultant image. Flat panel LCD units are used today in many applications including the computer industry where flat panel LCD units are an excellent display choice for lap-top computers and other portable electronic devices. However, because the technology of flat panel LCD units is improving, they are being used more and more in other mainstream applications, such as desktop computers, high-end graphics computers, and as television and other multimedia monitors.

In the field of flat panel LCD unit devices, much like conventional cathode ray tube (CRT) displays, a white pixel is composed of a red, a green and a blue color point or "spot." When each color point of the pixel is illuminated simultaneously, white can be perceived by the viewer at the pixel's screen position. To produce different colors at the pixel, the intensities (e.g., brightness) to which the red, green and blue points are driven are altered in well known fashions. The separate red, green and blue data that corresponds to the color intensities of a particular pixel is called the pixel's color data. Color data is often called gray scale data. The degree to which different colors can be achieved by a pixel is referred to as gray scale resolution. Gray scale resolution is directly related to the amount of different intensities to which each red, green and blue point can be driven.

The method of altering the relative color intensities of the color points across a display screen is called white balance adjustment (also referred to as color balance adjustment, color temperature adjustment, white adjustment, or color balancing). In other words, the appearance of "white" is a combination of red, green and blue intensities in various contributions of each color. "Color temperature" attempts to correlate the temperature of an object with the apparent color of that object. It is the temperature of the light source that illuminates the object. Ideally, that source is a perfect black body emitter, e.g., a thermally radiating object that absorbs all incident radiation and re-radiates that energy with complete efficiency. A theoretical model of such a black body was derived by Max Planck and is the standard to which any the source is compared.

But real life radiators are not so efficient but still tend to follow Planks equation in a relative sense and are known as "gray body" emitters. A tungsten filament is a very good approximation to a gray body and the user of a tungsten

filament as a substitute for a black body reference is wide spread. Therefore, the term "color temperature" refers to the emission spectra of a tungsten filament at a given temperature as expressed in degrees Kelvin. In a display, the "color temperature" of white correlates to the relative percentage contributions of its red, green and blue intensity components. Relatively high degree K color temperatures represent "white" having a larger blue contribution (e.g., a "cooler" look). Relatively small degrees K color temperatures represent "white" having a larger red contribution (e.g., a "warmer" look). Generally, the color temperature of a display screen is adjusted from blue to red while avoiding any yellow-ish or green-ish variations within the CIE chromaticity diagram.

The white balance adjustment for a display is important because many users want the ability to alter the display's color temperature for a variety of different reasons. For instance, the color temperature might be varied based on a viewer's personal taste. In other situations, color temperature adjustment may be needed to perform color matching (e.g., from screen-to-screen or from screen-to-paper or screen-to-film). In some situations, color temperature adjustment can correct for the effects of aging in some displays. Therefore, it is important for a flat panel LCD unit to provide the user with a color balancing adjustment option.

One method for correcting or altering the color balance within an LCD unit screen is to alter, on-the-fly, the color data used to render an image on the screen. For instance, instead of sending a particular color point a color value of X, the color value of X is first passed through a function that has a gain and an offset. The output of the function, Y, is then sent to the color point. The function is specifically selected for a particular color temperature result. The values of the above function can be altered as the color temperature needs to be increased or decreased in value. Although offering dynamic color balance adjustment, this prior art mechanism for altering the color balance is disadvantageous because it requires relatively complex circuitry for altering a very large volume of color data. The circuitry adds to the overall cost of production and can increase image generation latency. Secondly, this prior art mechanism may degrade the quality of the image by reducing, e.g., narrowing, the gray-scale range and therefore the gray-scale resolution of the flat panel display. Therefore, it is desirable to provide a color balance adjustment mechanism for a flat panel display screen that does not alter the image data nor compromise the gray-scale resolution of the image.

Another method of correcting for color balance within a flat panel display screen is used in active matrix flat panel display screens (AMLCD). This method pertains to altering the physical color filters used to generate the red, green and blue color points. By altering the color the filters, the color temperature of the AMLCD screen can be adjusted. However, this adjustment is not dynamic because the color filters need to be physically (e.g., manually) replaced each time adjustment is required. Therefore, it would be advantageous to provide a color balancing mechanism for a flat panel display screen that can respond, dynamically, to required changes in the color temperature of the display.

Within CRT devices, color balancing is performed by independently altering the voltages of the primary electron guns (e.g., red, green and blue guns) depending on the color temperature desired. However, like the prior art mechanism that alters the color data on-the-fly, this prior art color balancing technique reduces the gray-scale's dynamic range and therefore the gray-scale resolution of the display. Also, this technique for color balancing is not relevant for flat panel LCD units because they do not have primary electron guns.

Accordingly, the present invention offers a mechanism and method for providing color balancing within a display that does not require a large amount of complex circuitry and does not reduce the gray-scale resolution of the display. Further, the present invention offers a mechanism and method that dynamically alters the color balance of a display and is particularly well suited for application with flat panel LCD units. These and other advantages of the present invention not specifically described above will become clear within discussions of the present invention herein.

SUMMARY OF THE INVENTION

Multiple light source systems are described herein for color balancing within a liquid crystal flat panel display unit. The present invention includes a method and system for altering the brightness of two or more light sources, having differing color temperatures, thereby providing color balancing of a liquid crystal display (LCD) unit within a given color temperature range. The embodiments operate for both edge and backlighting systems. In one embodiment, two planar light pipes are positioned, a first over a second, with an air gap between. The light pipes distribute light uniformly and independently of each other. The first light pipe is optically coupled along one edge to receive light from a first light source having an overall color temperature above the predetermined range (e.g., the "blue" light) and the second light pipe is optically coupled along one edge to receive light from a second light source having an overall color temperature below the predetermined range (e.g., the "red" light).

In the above embodiment, the color temperatures of the first and second light sources are selected such that the overall color temperature of the LCD can vary within the predetermined range by altering the driving voltages of the first and second light sources. In effect, the LCD color temperature is altered by selectively dimming the brightness of one or the other of the light sources so that the overall contribution matches the desired LCD color temperature. In the selection of the light sources, a constraint is maintained that at any color temperature the brightness of the LCD is not reduced below a given threshold minimum (e.g., 70 percent of the maximum brightness). In the selection of the light sources, a second constraint is maintained that within the predetermined color temperature range, the color temperature is held close to the black body curve of the CIE chromaticity diagram. In a third constraint, the light sources are selected so that their maximum brightness point is set to be near the middle of the predetermined color temperature range.

In furtherance of one embodiment of the present invention, the light sources selection process may be implemented in computer readable instructions executable by a computer system and stored in computer readable memory such that a large number of number of light sources candidates may be simulated to obtain their luminance, chromaticity, and color temperature data. Candidates that satisfy the above constraints are selected. In one embodiment, the selection process includes the step of analyzing high-resolution spectral files of R, G, and B phosphors, varying a percentage composition of the R, G, B phosphors to generate multiple sets of light source candidates, matching up the light source candidates to generate a pool of candidate pairs, calculating a color temperature-luminance relationship for each candidate pair, and rejecting the candidate pair unless the color temperature-luminance relationship satisfies the above pre-defined selection constraints.

In another embodiment of the present invention, the selection process specifically includes the steps of calculat-

ing a chromaticity relationship for each candidate pair and rejecting the candidate pair if the chromaticity relationship deviates significantly from the black body curve. In yet another embodiment of the present invention, the selection process further includes the steps of examining the color temperature-luminance relationship to determine whether a peak brightness point occurs at the middle of the given color temperature range.

One embodiment of the present invention includes a color balancing system within a flat panel display for providing color balancing within a color temperature range, the color balancing system having: a first planar light pipe disposed to provide backlight to a liquid crystal display (LCD) layer; a first light source optically coupled to provide light to the first planar light pipe, the first light source having a color temperature that is below the minimum color temperature of the color temperature range; a second planar light pipe disposed parallel to the first planar light pipe such that an air gap exists between the first and the second planar light pipes, the second planar light pipe also for providing backlight to the LCD layer; a second light source optically coupled to provide light to the second planar light pipe, the second light source having a color temperature that is above the maximum color temperature of the color temperature range; a pre-polarizing film disposed between the light pipes and a rear polarizer of an LCD; and a rear reflector positioned on the other side of the light pipes. The system also has a circuit coupled to the first and the second light sources for setting a color temperature of the flat panel display by selectively and independently varying the brightness of the first light source and the brightness of the second light source. The circuit decreases the brightness of the first light source to increase the color temperature of the flat panel display and decreases the brightness of the second light source to decrease the color temperature of the flat panel display.

Significantly, in the present embodiment, brightness in the LCD is enhanced by polarization recycling. According to the present embodiment, the pre-polarizing film first pre-polarizes light emitted from the light pipes to a predetermined orientation that matches the polarization orientation of the rear polarizer of an LCD. Light that is not polarized in the predetermined orientation is reflected by the pre-polarizing film to the reflector where it is rephased to the predetermined orientation. Consequently, brightness of the LCD screen is significantly improved by the recycling. In one embodiment, the pre-polarizing film comprises a layer of DBEF brightness enhancement film, and the rear reflector is made of a PTFE material. In another embodiment, the rear reflector is covered with a film comprising barium sulfate. Brightness may also be significantly enhanced by the addition of a crossed BEF layer between the rear polarizer of the LCD and the light pipes.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A illustrates a perspective front view of a display device in accordance with one embodiment of the present invention having a removable backlighting assembly partially inserted.

FIG. 1B illustrates a perspective back view of a display device in accordance with one embodiment of the present invention having a removable backlighting assembly removed.

FIG. 1C illustrates a front view of a desk top display device in accordance with an embodiment of the present invention having a fixed in place backlighting assembly or module.

5

FIG. 1D illustrates a back perspective view of the desk top display device of FIG. 1C.

FIG. 2A is a cross sectional view of a dual light source and dual light pipe embodiment of an LCD flat panel display in accordance with the present invention.

FIG. 2B is a cross sectional view of another implementation of the dual light source and dual light pipe embodiment of FIG. 2A.

FIG. 3A illustrates an extraction pattern disposed on the bottom side of a light pipe in accordance with embodiments of the present invention that use a single edge-disposed light source per light pipe.

FIG. 3B illustrates a portion of the LCD panel embodiment of FIG. 2A with oriented extraction patterns in accordance with the present invention.

FIG. 3C illustrates a portion of the LCD panel embodiment of FIG. 2B with oriented extraction patterns in accordance with the present invention.

FIG. 3D illustrates variation of the embodiment of FIG. 3C having two variable intensity light sources and a single light pipe for both.

FIG. 4 is a schematic diagram of the inverter circuitry used to independently control the brightness of light sources within an LCD flat panel display within the embodiments of the present invention.

FIG. 5 illustrates the CIE chromaticity diagram including the black body curve from blue to red.

FIG. 6 is a graph illustrating the color temperatures achieved by one implementation of the dual light source and dual light pipe embodiment of the present invention for a given color temperature range.

FIG. 7A, FIG. 7B and FIG. 7C are spectrum graphs of the energy distributions over a range of wavelengths representing the color temperature distributions of three exemplary blue light sources selected in accordance with the present invention.

FIG. 8A and FIG. 8B are spectrum graphs of the energy distributions over a range of wavelengths representing the color temperature distributions of two exemplary red light sources selected in accordance with the present invention.

FIG. 9A is a graph of color temperature and luminance for one implementation of the dual light source and dual light pipe embodiment of the present invention having a blue source at 11,670 K and a red source at 3,623 K.

FIG. 9B is a graph of color temperature versus luminance for one implementation of the dual light source and dual light pipe embodiment of the present invention for a blue source at 15,599 K and a red source at 3,221 K with 2.6 mm cold cathode fluorescent tubes (CCFL).

FIG. 9C is a graph of color temperature versus luminance for one implementation of the dual light source and dual light pipe embodiment of the present invention for a blue source at 15,599 K and a red source at 3221 K with 2.4 mm CCFL.

FIG. 9D is a graph of color temperature versus luminance for one implementation of the dual light source and dual light pipe embodiment of the present invention for a blue source at 15,005 K and a red source at 3,561 K with 2.6 mm CCFL.

FIG. 10A is a cross sectional diagram of an embodiment of the present invention having dual light pipes and four light sources, two blue sources and two red sources.

FIG. 10B is a cross sectional diagram of an embodiment of the present invention having a single light pipe and four light sources, two blue sources and two red sources.

6

FIG. 11 is a cross sectional diagram of an embodiment of the present invention having dual light pipes and three light sources, two blue sources associated with one light pipe and one red light source that is adjusted for color balancing.

FIG. 12 is a cross sectional diagram of an embodiment of the present invention having two wedge-shaped cross-nested light pipes and two light sources.

FIG. 13A illustrates a cross sectional diagram of another embodiment of the present invention in which backlight is recycled to increase luminance of the LCD.

FIG. 13B illustrates a cross section of another embodiment of a rear reflector where the reflection material is applied to a plastic substrate or carrier.

FIG. 13C illustrates a cross section of a PTFE film reflector according to one embodiment of the present invention.

FIG. 14 illustrates an exemplary computer system in which the process of selecting appropriate light sources according to one embodiment of the present invention.

FIG. 15 is a flow diagram illustrating the process of selecting appropriate light source candidates according to one selection criterion in furtherance of one embodiment of the present invention.

FIG. 16 is a flow diagram illustrating the process of selecting appropriate light source candidates according to another selection criterion in furtherance of one embodiment of the present invention.

FIG. 17 is a flow diagram illustrating a process of selecting appropriate light source candidates according to yet another selection criterion in furtherance of one embodiment of the present invention.

FIG. 18A illustrates a backlighting embodiment of the present invention having an array of CCF light sources.

FIG. 18B illustrates a backlighting embodiment of the present invention having an array of CCF light sources and a scallop-shaped rear reflector.

FIG. 18C illustrates a backlighting embodiment of the present invention having an array of CCF light sources and a scallop-shaped rear reflector where each scallop has a light source pair.

DETAILED DESCRIPTION OF THE INVENTION

In the following detailed description of the present invention, a color balancing system for a flat panel LCD unit applying variable brightness to multiple light sources of varying color temperature, numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will be obvious to one skilled in the art that the present invention may be practiced without these specific details or with certain alternative equivalent circuits and methods to those described herein. In other instances, well known methods, procedures, components, and circuits have not been described in detail as not to unnecessarily obscure aspects of the present invention.

Exemplary Display Systems

FIG. 1A and FIG. 1B illustrate front and back perspective views of a display system 5 in which embodiments of the present invention can be implemented. Although exemplary display system 5 utilizes a removable backlighting unit 14 that makes use of edge lighting technology, the color temperature balancing embodiments of the present invention are equally applicable to display systems that use fixed-in-place

edge lit backlighting units and/or direct backlighting technology (FIG. 1C and FIG. 1D). The color temperature balancing embodiments of the present invention are equally applicable to direct backlighting applications as well as edge lighting applications. As described more fully in U.S. Pat. No. 5,696,529, issued Dec. 9, 1997, by Evanicky et al., and U.S. Pat. No. 5,593,221, issued Jan. 14, 1997, by Evanicky et al, both of which are assigned to the assignee of the present invention and incorporated herein by reference, the high resolution color flat panel display 5 has a backlighting door assembly ("backlighting assembly") 14 for direct viewing. This backlighting assembly 14 can be removed to expose the transparent active LCD unit screen. Once removed, the transparent active LCD unit screen can be positioned on top of an overhead projector in order to project the displayed image in an enlarged fashion onto a receiving screen.

With reference to FIG. 1A, a perspective view of the display subsystem 5 is illustrated with the display side facing toward the viewer. This is the direct viewing configuration. The display system 5 comprises three major assemblies. The base assembly 12 which is coupled to a display assembly 10 via a hinge in order to allow the display assembly 10 to adjust to different angles for direct monitoring or allows the display assembly to lay flat for overhead projection configurations and for storage and transportation. The base assembly 12 supports the display 10 for direct viewing configurations and also contains several electronic circuit systems for providing the display unit with power, audio information, and video information (see FIG. 4). Herein, the door assembly 14 is also called a backlighting assembly or a liquid crystal flat panel layer.

The display assembly 10 contains two stereo speakers 8a and 8b as well as an active matrix LCD color screen 20. Although many different resolutions can be utilized within the scope of the present invention, an implementation utilizes an LCD screen 20 having 1280 pixels by 1024 pixels by RGB color and utilizes amorphous silicon thin film transistors (TFT). The LCD screen 20 is composed of color TFT-LCD panel, driver ICs, control circuitry, and power supply circuitry all contained in a rigid bezel. LCD screen 20 is capable of displaying 2¹⁸ true colors without frame rate modulation in text or graphics mode. Various flat panel LCD screens and screen technologies can be used within the scope of the present invention with proper configuration.

As shown in FIG. 1A, the display assembly 10 is back-lit via a separate assembly or removable backlighting assembly 14. In this view, the door is partially removed from the display assembly 10. The backlighting assembly 14 is removed so that the display 20 can become transparent for overhead projection configurations. While inserted, the backlighting assembly 14 provides backlighting for the LCD screen 20 for direct viewing configurations. Although a number of lamps can be utilized, one embodiment utilizes cold cathode fluorescent (CCF) tubes which are located within the display assembly to illuminate along the top and bottom edges of one or more light pipes located within the backlighting assembly 14 (as will be discussed further below) when the backlighting assembly 14 is inserted within the display assembly 10. Hot cathode tubes (HCF) can also be used. Also shown is a snap fit clip 34 which is used to secure the backlighting assembly 14 to the display assembly 10.

FIG. 1B illustrates the back side of the display subsystem 5 with the backlighting assembly 14 completely removed to expose inner components of the display assembly 10. In this view, with the backlighting assembly 14 removed, the back

side of the LCD screen 20 is exposed. Located on the base assembly 12 are inputs for AC power 44 and an audio/video input connector 48. Power supplied to the subsystem, back-light brightness and audio volume are controlled by the computer system's software through the audio/video input connector 48. In an alternative embodiment, in addition to computer control these features can be manually adjusted. For instance, also located on the display subsystem 5 can be (optionally) a power on switch 2a, a color temperature adjustment knob 2b and a volume adjustment knob 2c for the stereo speakers 8a and 8b. The audio/video input connector 48 is coupled to the digital audio/video output of a computer system.

Located within the display assembly 10 are two lamp assemblies or housings. One lamp housing 40 is shown. Each lamp housing can contain one or more CCF lamps 52, depending on the particular embodiment of white balancing utilized (described further below). The CCF lamps can optionally be mounted within their respective lamp housing using two rubber shock mounts, as shown, 50a and 50b to secure lamps 52. An identical configuration is employed for the top lamp housing (obscured). A reflective film 42 is applied to the inner portions of the lamp housings and this tape extends outside, beyond the positions of the lamps 52, for providing an optical coupling with components of the backlighting assembly 14 when inserted. The same is true for the upper lamp housing.

Also shown in FIG. 1B are two receiving holes 32 located on the right and left sides of the display assembly 10. These receiving holes 32 fasten to corresponding latches (34 not shown) located on the backlighting assembly 14. There is also a recess associated with these latch holes 32 for removal of the backlighting assembly 14. Also located within this region of the display assembly 10 is a magnetic reed switch 22 that is responsive to the presence of a magnet 140 (not shown) that is located along the mating edge of the backlighting assembly 14. Using this switch 22, the display subsystem 5 determines whether or not the backlighting assembly 14 is inserted or removed from the display assembly 10 and responds accordingly. It is appreciated that the reed switch 22 and sensor, in lieu of being magnetically operated, can also be implemented using and optical sensor (or switch, such as using a LED or fiber-optic device) or a mechanical sensor (or switch, such as a toggle or spring switch).

There are also two notches 95a and 95b located on the top of the display assembly 10. These notches 95a and 95b are for mating with corresponding latches located on an overhead projector of the present invention for securing the display subsystem properly over an illuminating screen of the projector. When used in a projector configuration, the display subsystem 5 is extended so that the base assembly 12 and the display assembly 10 are flat and the facing side of the display subsystem, as shown in FIG. 1B, is placed facing down on top of the illuminating screen of the projector. In this way, light is projected through the back side of the LCD screen 20.

As discussed above, the color temperature balancing embodiments of the present invention are equally applicable to display systems that use fixed-in-place edge lit backlighting units and/or direct backlighting technology. FIG. 1C illustrates a front view of a desk top display unit ("monitor") 36 having installed therein an LCD flat panel display assembly 38 having the color balancing system of the present invention. In this embodiment, the LCD flat panel display assembly 38 is fixed-in-place and edge lit with light sources along the top horizontal edge 38a and bottom horizontal edge 38b.

FIG. 1D illustrates a back perspective view of the desk top display unit **36**. This desk top display unit **36** includes a mounting bracket **39** for mounting on a wall, a mechanical arm or for mounting with a base.

Color Balancing Systems of the Present Invention

FIG. 2A illustrates a liquid crystal flat panel display (herein "flat panel display") **110a** in accordance with one embodiment of the present invention. This flat panel display **110a** can be used within a flat panel display device having a fixed-in-place backlighting unit or can be used within a flat panel display system **5** (FIG. 1A) using a removable backlighting assembly **14**. The flat panel display **110a**, in accordance with the present invention, provides white balance adjustment by independently varying the brightness of a pair of light sources (e.g., CCF tubes) **132** and **136**. For a predetermined range of color temperatures, having a minimum temperature (e.g., 5,000 K) and a maximum temperature (e.g., 6,500 K), a first light source **132** is provided that has a wavelength spectrum with an overall color temperature less than the minimum temperature of the predetermined range; herein, a light source **132** with this characteristic is called the "red" light source for convenience. Also, a second light source **136** is provided that has a wavelength spectrum with an overall color temperature that is greater than the maximum temperature of the predetermined range; herein, a light source **136** with this characteristic is called the "blue" light source for convenience.

As shown in FIG. 2A, the red light source **132** is optically coupled to provide light to a first planar light pipe **130**. The red light source **132** is positioned along an edge of the light pipe **130**. In FIG. 2A, only cross sections of this planar light pipe **130** and the light source **132** are shown. Likewise, the blue light source **136** is optically coupled to provide light to a second planar light pipe **134**. The blue light source **136** is positioned along an edge of the light pipe **134**. Only cross sections of this planar light pipe **134** and the light source **136** are shown. In the embodiment **110a** of FIG. 2A, the light sources **132** and **136** are long thin tubes which are positioned on opposite sides of the planar light pipes **134** and **130**. The light sources **132** and **136** are positioned to be substantially parallel with each other. The power supply for each light source **132** and **136** receives a separate voltage signal for independently controlling its brightness with respect to the other light source. It is appreciated that the positions of the red tube **132** and the blue tube **136** can be switched without departing from the scope of the invention.

In order to maintain independence of the light distribution between the first **130** and second **134** light pipes, an air gap **133** is maintained between the two light pipes. This air gap **133** prevents light from light source **132** being extracted within light pipe **134** and prevents light from light source **136** from being extracted within light pipe **130**. The air gap **133** is particularly important for embodiment **110a** because each light pipe is illuminated from one edge, and the extraction dot pattern (e.g., a pattern of bumps disposed on the surface of the light pipes) corresponding to that light pipe is specifically tailored for light originating from that edge. On the edges and surrounding the light pipes are reflection tapes **131** and **135**.

Within embodiment **110a**, a rear reflector layer **138** is positioned on one side of the light pipes. On the other side of the light pipes a diffuser layer **128** (mylar) is followed by one or more brightness enhancement layers (BEFs) **126**, followed by a double BEF (DBEF) layer **124** which is followed by a cover layer **122** for protection. The DBEF

layer **124** redirects light not of the proper polarization to the rear reflector layer **138** for recycling. The LCD panel includes a first polarizer layer **120** followed by a back glass layer **121** followed by the selectively energized transistor layer **119** and an LCD layer **118**, followed by red/green/blue color filter layers **114**, a front glass layer **115** followed by a second polarizer layer **116**. A glass or acrylic protection layer **112** is then used. These layers are described in more detail further below.

The white balance or color temperature of the embodiment **110a** is maintained and adjusted using the two independently controlled light sources **132** and **136**. The white balance is adjusted by altering the brightness of the light sources **132** and **136** independently. The phosphor mix (e.g., contribution of red, green and blue phosphor) of the two light sources **132** and **136** is selected so that the white balance can be adjusted by varying the brightness of the light sources. The light pipes **130** and **134** are acrylic and each contain an extraction system that uniformly and independently distributes the light from each light source across the viewing area of the display.

In one implementation, the light pipes **130** and **134** are mounted to address a removable backlight assembly (e.g., assembly **14**). In another implementation, the light sources are located behind a diffusing system **128** to directly backlight the display rather than "edge" light the light pipe. In one embodiment, the light sources **132** and **136** are cold cathode fluorescent (CCF) tubes and, in another embodiment, hot cathode fluorescent (HCF) tubes are used. Constraints are placed on the amount of brightness variation tolerated during white adjustment such that the overall brightness of the display never decreases below a percentage of the maximum brightness output by the light sources **132** and **136**. In one implementation, this percentage is selected at 70 percent.

FIG. 2B illustrates another embodiment **110b** that is analogous to embodiment **110a** except for the differences pointed out below. In the embodiment **110b** of FIG. 2B, the light sources **132** and **136** are long thin tubes which are positioned on the same side of the planar light pipes **134** and **130**. The light sources **132** and **136** are positioned to be substantially parallel with each other. Because the light sources **132** and **136** are positioned on the same side of the planar light pipes **134** and **130**, the position of the reflection element **131** is shifted. It is appreciated that the positions of the red tube **132** and the blue tube **136** can be switched without departing from the scope of the invention.

Extraction Pattern Orientation

FIG. 3A illustrates a top view of an exemplary extraction pattern **144a** that can be applied to the bottom of light pipe **130** within embodiment **110a**. The extraction pattern **144a** is designed to uniformly illuminate the LCD layer **118**, at any brightness, taking into consideration that the red tube **132** is positioned along one edge of the light pipe **130**. To accomplish this uniform distribution of light, extraction dots increase in size in a proportion to their distance from the light source **132** as shown in direction **146**. Extraction dots **150a** are smaller since they are relatively close to the light source **132**. Extraction dots **150b** are slightly larger since they are relatively farther from the light source **132** than dots **150a**. Extraction dots **150c** are the largest because they are the farthest from light source **132**. It is appreciated that extraction pattern **144a** also includes larger sized dots **150d** at the corners near the light source **132** because the tube **132** is not as bright at the ends as in the middle sections of the tube.

FIG. 3B illustrates a configuration 160 of light pipes and light sources (of embodiment 110a of FIG. 2A) taking into consideration the orientation of the light extraction patterns. Within embodiments 110a and 110b, each light extraction pattern is designed to operate with its own light pipe (e.g., pipe 130) independently of the other light pipe (e.g., pipe 134). In other words, extraction pattern 144a is designed to uniformly distribute light to the LCD layer 118, independently of light pipe 132, as the brightness of light source 132 varies. Extraction pattern 144b is designed to uniformly distribute light to the LCD layer 118, independently of light pipe 130, as the brightness of light source 136 varies. Light extraction pattern 144a is shown in FIG. 3B in cross section as a thin line applied to the underside of light pipe 130. As shown, the dot sizes increase within pattern 144a from left to right because the light source 132 is positioned on the left edge of the light pipe 130. However, the light extraction pattern 144b applied to the underside of light pipe 134 is the flipped image of pattern 144a with the dot sizes increasing from right to left because light source 136 is positioned along the right edge of the light pipe 134.

Considering the provision of the air gap 133 and that each light extraction pattern 144a and 144b is tailored for its own light pipe, the light pipes 130 and 134 effectively operate separately and independently to uniformly distribute light over the LCD layer. One function of the light extraction patterns 144a and 144b is to uniformly distribute light over their associated light pipes even if one lamp is dimmed (or brightened) unilaterally. It is appreciated that the brightness of light source 136 is increased slightly to compensate for the fact that extraction pattern 144a resides between the light pipe 134 and any LCD layer and thereby slightly obstructs the light emitted from light pipe 134. An alternative approach adjusts the sizes of the dots of the relative dot extraction patterns to compensate for the obstruction.

FIG. 3C illustrates a configuration 165 of light pipes and light sources (of embodiment 110b of FIG. 2B) taking into consideration the orientation of the light extraction patterns. Within embodiments 110a and 110b, each light extraction pattern is designed to operate with their light pipe (e.g., pipe 130) independently of the other light pipe (e.g., pipe 134). Light extraction pattern 144b is shown in FIG. 3C in cross section as a thin line applied to the underside of light pipe 130. As shown, the dot sizes increase within pattern 144b from right to left because the light source 132 is positioned on the right edge of the light pipe 130. The same light extraction pattern, 144b, is also applied to the underside of light pipe 134. As discussed above, extraction pattern 144b is the mirror image of pattern 144a with the dot sizes increasing from right to left because light source 136 is positioned along the right edge of the light pipe 134.

FIG. 3D illustrates a variation of the embodiment 165 of FIG. 3C. Alternatively, as shown in FIG. 3D, this embodiment 167 uses both controls for the first 132 and second 136 light sources together to change the display brightness without altering the white balance setting where both the first and second light sources are positioned on the same side of a single light pipe layer 130' and optically coupled to it. A rear reflector 138 is also used. This embodiment 167 can also be used for color temperature balancing.

Dual Inverters for Independently Driving Light Sources

FIG. 4 is a logical block diagram of electronics 170 of the display subsystem 5. Although some electrical components are shown (in dashed lines) to be associated with the base

assembly 12 or the display assembly 10, it is appreciated that their locations are exemplary. Apart from the LCD screen 20, the actual location of the circuits could be in either the display assembly 10 or the base assembly 12. It is appreciated that circuit 170 includes the provision of separate inverter circuits 175a and 175b for separately and independently controlling light sources 132 and 136. A color temperature adjustment knob 2b (FIG. 1B) is coupled to circuit 187 which controls the voltages supplied by the inverters 175a and 175b to the lamps 132 and 136 over bus 180 to separately control their brightness. Another implementation adjusts the brightness through software control by means of a digital potentiometer. Inverter 175a controls light source 132 and inverter 175b controls light source 136.

In one implementation, within the base assembly, as shown in FIG. 4, are a power supply unit 184 for coupling with an alternating current source 44. This power supply 184 supplies power via line 182 to an audio board 178 and a video board 176. The audio board 178 is coupled to the video board 176 via bus 186. Audio and video information are sent to the display subsystem via input interconnect 48. It is appreciated that a variety of audio/video information transfer formats and standards can be used within the scope of the present invention, including an IBM compatible standard, a UNIX standard, or Apple Computer standard.

Video board 176 is coupled to a bus 185 for communicating and controlling elements of the display assembly 20. It is appreciated that portions of bus 185 are composed of flex circuits so that base assembly 12 and display assembly 10 can move freely about their common hinge. Among other signals, this bus 185 carries power, control signals and audio and video data signals. The video board 176 is coupled to supply audio signals over bus 185 to stereo speakers 8a and 8b. Video board 176 also supplies a control signal and power over line 185 to a circuit 187 which in turn independently controls two AC to DC inverters 175a and 175b. Each inverter contains a transformer for supplying a high voltage signal, over bus 180, to the light sources 132 and 136 and also contains a switch circuit for turning the tubes off. Light sources 132 and 136 are separately coupled to power supply lines 180a and 180b, respectively, which are within bus 180. Return bus 189 contains a separate return lines from source 132 to inverter 175a and from source 136 to inverter 175b. Bus 185 is also coupled to reed switch 22 which carries a digital signal indicating when the backlighting assembly 14 is inserted into the display assembly 10 or not present.

Bus 185 of FIG. 4 is coupled to supply video information to column driver circuits 171. The column driver circuits 171 control information flow to the columns of each of the rows of transistors of the LCD screen 20 to generate an image in the well-known fashion. (There are also separate row driver circuits that are not illustrated but operate in the well-known fashion.)

Blackbody Chromaticity Curve

FIG. 5 illustrates a CIE chromaticity diagram illustrating chromaticity coordinates along the horizontal and vertical. Within the diagram 190, the green portion 194 is toward the top with yellow 192 between green 194 and red 198. Blue 196 is toward the left. A black body curve 200 represents the chromaticity displayed by a tungsten filament heated to various degrees kelvin. For instance, from point D to point A along curve 200, the curve represents the color emitted from the tungsten filament from 6,500 degrees K to 2856 degrees K. As shown, the blackbody curve 200 traverses from blue 196 to the red 198 without straying much into the yellow 192 or green 194 regions.

The light sources **132** and **136** selected in accordance with the present invention are those that illuminate with a color temperature that is near the blackbody curve **200** when their brightness is adjusted within a predetermined color temperature range (e.g., 5,000 to 6,500 K). That is, the color balancing system of the present invention allows adjustments to the color temperature of the flat panel display screen that remain close to the blackbody curve.

In addition to following the CIE black body curve ("locus"), light sources **132** and **136** selected in accordance with the present invention follow the daylight color temperature locus when color temperature of the display is adjusted. One advantage of following the daylight color temperature locus during white balancing is that the resulting color temperature tends to be brighter (e.g. having a greater lumen value, Y), and tends to model daylight more accurately. Furthermore, the resulting color temperature tends to be more "green," giving the display a more natural appeal.

FIG. **6** illustrates one exemplary case where the "blue" light source **136** is a CCFL tube having a color temperature of 11,670 K and the "red" light source **132** is a CCFL tube having a color temperature of 3,623 K within a flat panel display having a color balancing system **160** as shown in FIG. **3B**. FIG. **6** illustrates that by independently varying the brightness of the light sources **132** and **136**, the resultant color temperature of the flat panel display can be altered in accordance with line **212**. Line **200** is the same blackbody curve as shown in FIG. **5**. In this case, curve **212** is substantially similar to curve **200** within the predetermined color temperature range of 5,000 K to 6,500 K. In one embodiment, the brightness is varied by holding one light source (e.g., **132**) at maximum brightness and dimming the other light source (e.g., **136**) until a minimum brightness threshold is met. This steers the color temperature from a mid range value (e.g., 5500 K) into progressively warmer (e.g. smaller) values. To increase the color temperature from the mid range value, light source **136** is held constant and light source **132** is dimmed down until the minimum threshold brightness is reached.

Example Red and Blue Light Sources

Within the present invention, the light sources **132** and **136** are selected such that their color temperature allows the white balancing within a predetermined range (e.g., 5,000 to 6,500) that (1) follows the blackbody curve **200**, (2) where the overall brightness of the display does not drop below a predetermined threshold over the color temperature range and (3) having a peak brightness (both light sources on) near the middle of the color temperature range. There are many combinations of blue and red tubes that meet the above constraints. Processes described further below illustrate the manner in which light sources **132** and **136** can be selected that meet the above constraints. The following description illustrates some exemplary blue light sources and exemplary red light sources that can be paired (in blue-red combinations) to meet the above constraints.

FIG. **7A** illustrates a blue light source **136** having percentages of red, green and blue phosphors such that the CCFL tube exhibits the emission spectrum **220** within the 375–775 nm wavelength range. The overall color temperature for the light source of FIG. **7A** is very high at 15,600 K. FIG. **7B** illustrates a blue light source **136** having percentages of red, green and blue phosphors such that the CCFL tube exhibits the spectrum **224** within the 375–775 nm wavelength range. The overall color temperature for the

light source of FIG. **7B** is high at 15,000 K. FIG. **7C** illustrates a blue light source **136** having percentages of red, green and blue phosphors such that the CCFL tube exhibits the spectrum **226** within the 375–775 nm wavelength range. The overall color temperature for the light source of FIG. **7C** is 10,600 K.

FIG. **8A** illustrates a red light source **132** having percentages of red, green and blue phosphors such that the CCFL tube exhibits the spectrum **230** within the 375–775 nm wavelength range. The overall color temperature for the light source of FIG. **8A** is low at 3,560 K. FIG. **8B** illustrates a red light source **132** having percentages of red, green and blue phosphors such that the CCFL tube exhibits the spectrum **232** within the 375–775 nm wavelength range. The overall color temperature for the light source of FIG. **8B** is low at 3,220 K.

Exemplary combinations of the above red and blue light sources that can be used within embodiment **160** of FIG. **3B** are shown in Table I below.

TABLE I

Pair	Red Tube	Blue Tube	Ctemp @ Max Lumin
1	3,560	15,600	5,893
2	3,220	15,600	5,635
3	3,560	10,600	5,468
4	3,560	15,000	5,635
5	3,220	15,000	5,367

Where Ctemp @ Max Lumin is the color temperature of the pair at maximum luminance.

FIG. **9A** illustrates a color temperature and luminance diagram **240** for various brightness configurations of a color balancing embodiment **160** of FIG. **3B** within the color temperature range of 5,000 to 6,500 K. In this example, a blue tube **136** having a color temperature of 11,670 K is used with a red tube **132** having a color temperature of 3,623 K and corresponds to the same configuration described with respect to FIG. **6**. Mid point **246c** of FIG. **9A** represents maximum luminance when both tubes are at their full brightness and a color temperature near 5,500 K is reached. This is roughly in the middle of the color temperature range 5,000 to 6,500 K.

The following describes color temperature variations from the mid point **246c** achieved by dimming one or the other tube. Region **246a** represents the white balance adjustment where the red tube **132** is left fully on and the blue tube **136** is dimmed down in a range from 5 to 25 percent (of the original full) luminance. Within region **246a**, curve **242** represents the luminance ratio and this value decreases (from 1.0 to 0.8) as the blue tube **136** is dimmed down. Also within region **246a**, the color temperature as shown by curve **248** decreases as the blue tube **136** is dimmed down. Region **246b** represents the white balance adjustment where the blue tube **136** is left fully on and the red tube **132** is dimmed down from 5 to 25 percent of the original full luminance. Within region **246b**, curve **242** represents the luminance ratio and this value decreases (from 1.0 to 0.8) as the red tube **132** is dimmed down. Also within region **246b**, the color temperature as shown by curve **248** increases as the red tube **132** is dimmed down.

FIG. **9B** illustrates a color temperature and luminance diagram **260** for various brightness configurations of a color balancing embodiment **160** of FIG. **3B** within the color temperature range of 3,400 to 8,250 K using CCFL tubes of 2.6 mm in size. In this example, a blue tube **136** having a color temperature of 15,599 K (FIG. **7A**) is used with a red

tube **132** having a color temperature of 3,221 K (FIG. 8B). Curve **262** represents the luminance in Cd/sq m over the given range of color temperatures and curve **264** represents the luminance ratio (from 0 to 1.0). Peak luminance point **266** represents the maximum brightness condition (4,600 K) when both lamps **136** and **132** are fully on. That portion of the curves to the right of point **266** represents the condition when tube **136** is fully on and tube **132** is dimmed down to increase the color temperature. That portion of the curves to the left of point **266** represents the condition when tube **132** is fully on and tube **136** is dimmed down to decrease the color temperature.

FIG. 9C illustrates a color temperature and luminance diagram **270** for various brightness configurations of a color balancing embodiment **160** of FIG. 3B within the color temperature range of 3,400 to 8,250 K using CCFL tubes of 2.4 mm in size. In this example, a blue tube **136** having a color temperature of 15,599 K (FIG. 7A) is used with a red tube **132** having a color temperature of 3,221 K (FIG. 8B). Curve **272** represents the luminance in Cd/sq m over the given range of color temperatures. Peak luminance point **276** represents the maximum brightness condition (5,000 K) when both lamps **136** and **132** are fully on. That portion of the curves to the right of point **276** represents the condition when tube **136** is fully on and tube **132** is dimmed down to increase the color temperature. That portion of the curves to the left of point **276** represents the condition when tube **132** is fully on and tube **136** is dimmed down to decrease the color temperature.

FIG. 9D illustrates a color temperature and luminance diagram **280** for various brightness configurations of a color balancing embodiment **160** of FIG. 3B within the color temperature range of 3,400 to 8,250 K using CCFL tubes of 2.6 mm in size. In this example, a blue tube **136** having a color temperature of 15,599 K (FIG. 7A) is used with a red tube **132** having a color temperature of 3,221 K (FIG. 8B). Curve **282** represents the luminance in Cd/sq m over the given range of color temperatures. Peak luminance point **286** represents the maximum brightness condition (4,800 K) when both lamps **136** and **132** are fully on. That portion of the curves to the right of point **286** represents the condition when tube **136** is fully on and tube **132** is dimmed down to increase the color temperature. That portion of the curves to the left of point **286** represents the condition when tube **132** is fully on and tube **136** is dimmed down to decrease the color temperature.

It is appreciated that many of the layers within an LCD flat panel display system tend to "yellow" shift light passing there through, e.g., the acrylic in the light pipes, the ultra-violet cured extraction patterns, the DBEF and BEF films, the polarizers, the LCD layer and the color filters. Therefore, to compensate for this yellow shift, the red and/or blue light sources **132** and **136** selected can be slightly blue shifted.

Additional Multi-Light Source Embodiments

FIG. 10A illustrates a cross section of an alternate embodiment **310** of a color balancing system in accordance with the present invention that utilizes four light sources. Two red light sources **312** and **314** are positioned on opposite sides of a planar light pipe **130** and are parallel with each other. The brightness of these two red light sources **312** and **314** are varied in tandem. Two blue light sources **316** and **318** are positioned on opposite sides of a planar light pipe **134** and are parallel with each other. The brightness of these two blue light sources **316** and **318** are varied in tandem independently of the red light sources **312** and **314**.

It is appreciated that the positions of the blue and red light sources can be switched in accordance with the present invention. Light pipe **134** is positioned under light pipe **130**. An air gap **133** is positioned between the light pipes **130** and **134** but is optional in this embodiment because the locations of the red and blue light source pairs are symmetrical with respect to both light pipes **130** and **134**. As with embodiment **160**, CCFL tubes or HCL tubes can be used as the light sources with particular red, green, blue phosphor contributions to differentiate the blue from the red light sources.

Within embodiment **310**, because the brightness of the light sources that are on opposite sides of a same light pipe are varied in tandem, there is a uniform decrease or increase in brightness on both sides of the light pipe (e.g., light pipe **130** or **134**). In this case, the extraction pattern **144c** applied to the underside of each light pipe **130** and **134** utilizes extraction dots that vary in size with respect to their closest distance from the two light sources. That is, along the sides having the light sources, the extraction dots are smaller and they increase in size (from both sides) toward the middle. An extraction pattern **144c** fitting this description is described in U.S. Pat. No. 5,696,529, issued Dec. 9, 1997 by Evanicky, et al., and assigned to the assignee of the present invention.

In accordance with the embodiment **310** of FIG. 10A, to vary the color temperature of the display, the voltage driving the red light sources **312** and **314** is varied to vary their brightness. With the blue light sources **316** and **318** at maximum brightness, the color temperature can be increased from mid-range by dimming down the red light sources **312** and **314** in tandem. Conversely, to vary the color temperature of the display, the voltage of the inverter supply driving the blue light sources **316** and **318** is varied to vary their brightness. With the red light sources **312** and **314** at maximum brightness, the color temperature can be decreased from mid-range by dimming down the blue light sources **316** and **318** in tandem.

Embodiment **310** provides increased brightness through the color temperature variation because more light sources are utilized. Therefore, this embodiment **310** has a larger pool of red/blue light source candidates which allow good color temperature range variation while also providing adequate brightness through the color temperature range. However, since more light sources are used in embodiment **310** over the dual light pipe embodiment **160**, embodiment **310** consumes more power.

FIG. 10B illustrates a cross section of an embodiment **330** of a color balancing system in accordance with the present invention that is a variation of embodiment **310**. Embodiment **330** includes a single planar light pipe **340** having a red/blue pair of light sources located on two opposite sides. On the left are located a red light source **312** and a blue light source **316** and on the right are located a red light source **314** and a blue light source **318**. Like embodiment **310**, the red light sources **312** and **314** of embodiment **330** are varied in tandem and the blue light sources **316** and **318** are varied in tandem, independently from the red light sources **312** and **314**. An extraction pattern **144c**, as described above, is applied to the underside of light pipe **340**.

Color temperature variation is performed for embodiment **330** in the same manner as described with respect to embodiment **310**. The advantage of embodiment **330** is that a single light pipe **340** can be used. Since the brightness of the red and blue light sources are varied in tandem (for a given color), only two inverters **175a** and **175b** (FIG. 4) are required for embodiment **310** and for embodiment **330**. In other words, the voltage signal on line **180a** of FIG. 4 can

be coupled to control both red light sources **312** and **314** and the voltage signal on line **180b** can be coupled to control both blue light sources **316** and **318**.

FIG. **11** illustrates a cross section of another embodiment **350** of a color balancing system in accordance with the present invention that utilizes two blue light sources **316** and **318** and a single red light source **314**. The blue light sources **316** and **318** are positioned along opposite edges of a first light pipe **130**. An extraction pattern **144c**, as described above, is applied to the underside of light pipe **130**. Positioned under light pipe **130** (with an air gap **133** in between) a second light pipe **134**. A single red light source **314** is positioned along one edge of light pipe **134** (e.g., on the right or left side). When light source **314** is positioned on the right side, as shown, extraction pattern **144b** is used with light pipe **134** and when light source **314** is positioned on the left side, extraction pattern **144a** is used.

In operation, the blue light sources **316** and **318** are maintained at (or slightly above) a color temperature above a predetermined color temperature range (e.g., at or above 6,500 K). The blue light sources **316** and **318** are maintained at or near their full brightness to provide the required luminance for the display and the red light source **314** is adjusted in brightness to provide a varying degree of down-shifted color temperature. Embodiment **350** provides the advantage that the color temperature of the display can effectively be adjusted without affecting the backlight luminance. That is to say, if the emission spectra of the red lamp is in the deep red region (e.g., 658 nm), then even at its full brightness it would only contribute about 5 percent of the backlight luminance because of the human eye's insensitivity to that color region. It is appreciated that two inverters **175a** and **175b** are required for embodiment **350** even though the brightness of light sources **316** and **318** is held constant. Power consumption for the red light source **314** is within the region of 0.5 watt.

FIG. **12** illustrates a cross section of an embodiment **370** of a color balancing system in accordance with the present invention. Embodiment **370** is similar to embodiment **160** except the planar light tubes **372** and **374** are wedge-shaped in cross section. The light tubes **372** and **374** are positioned as shown in FIG. **12** so that they have a lower profile in cross section. That is, the light pipes **130** and **134** of embodiment **160**, in one implementation, are roughly 3 mm thick so their total width is just over 6 mm when stacked with an air gap **133** in between. However, because the wedge-shaped light pipes **372** and **374** can be positioned as shown in FIG. **12**, the overall height of light pipes **372** and **374** is only 3 mm since they are inter-crossed (e.g., cross-nested) together. As shown, a modification of extraction pattern **144a** is applied to the underside of light pipe **372** and a modification of extraction pattern **144b** is applied to the underside of light pipe **374**. The functionality of embodiment **370** similar to embodiment **160** however embodiment **370** offers a much lower profile and reduced weight. A modification of the extraction pattern is necessary to compensate for the influence on extraction resulting from the angle of the wedge of each light pipe **372 374**.

Color Balancing User Interface

There are several mechanisms in which the user can adjust the color balance of the display in accordance with the present invention. In one embodiment, the user can adjust a slider between two extreme mechanical positions in which the position of the slider (or knob **2b**) represents a particular color temperature within the predetermined color tempera-

ture range. The particular color temperature selected is then translated into a dimming configuration by which one or more tubes are dimmed to achieve the color temperature.

In another embodiment, the slider is provided but the display also contains a chromaticity measuring device (e.g., a calorimeter) which gives the user immediate feedback as to the color temperature of the display. The user then monitors the measuring device while adjusting the slider mechanism until the desired color temperature is reached. Alternatively, the white balance can be set via a feedback loop from a colorimeter positioned so that it analyzes the color temperature of the display and feeds that information to the host computer through a serial port and the host computer then automatically adjusts the white balance.

Improved Light Pipe Assembly Construction for Enhanced Display Brightness

In prior art flat panel LCD systems, almost 50% of the luminance from the backlight is lost. This is due to the fact that the rear polarizer film of the LCD only accepts light with a specific orientation and rejects the rest. The present invention recognizes that, if this rejected light could somehow be "recycled," the net display brightness could be increased. FIG. **13A** illustrates an embodiment of the present invention in which backlight is recycled to increase luminance of the LCD.

Particularly, as illustrated in FIG. **13A**, portions of a flat panel LCD **410** including a backlight distributor **430**, which may comprise various configurations of light pipes and light sources, such as the embodiments of the dual light pipes illustrated in FIGS. **2A-2B** and FIGS. **3B-3C**. In addition, according to the present embodiment, flat panel LCD **410** further includes a rear reflector layer **438** positioned on the back side of the backlight distributor **430** for recycling light. On the other side of the backlight distributor **430**, a diffuser layer **428** is followed by one or more brightness enhancement layers (BEFS) **426**, followed by a dual brightness enhancement film (DBEF) layer **424** which is followed by a special cover layer **422**. The LCD panel includes a first (rear) polarizer layer **120** followed by a selectively energized transistor-layer **110** and a LCD layer **118**, followed by red/green/blue color filter layers **114**, a front glass layer **115** followed by a second polarizer layer **116**. A glass or acrylic protection layer **112** is then used.

According to the present embodiment, DBEF layer **424** of FIG. **13A**, in combination with the rear reflector **438**, increases brightness of flat panel LCD **410** by first "pre-polarizing" the light emitted from the backlight distributor **430** to the same orientation as the rear polarizer **120**. Any light having the wrong orientation is reflected by DBEF layer **424** to the rear reflector **438** where much of it is rephased and reflected back to the display or lost through absorption. A large portion of the rephased and reflected light from the reflector **438** can then pass through the rear polarizer layer **120**.

Naturally, the amount of light that can be recycled depends upon the reflectivity of rear reflector **438**. Conventional reflective materials currently employed by the industry only reflect about 92% of the light. According to one embodiment of the present invention, a white rear reflector **438** made of a Teflon-like material developed by W.I. Gore and Associates, Inc., and sold under the name of PTFE, is used. In this embodiment, a near 100% increase in luminance is attainable. In one embodiment, rear reflector **438** comprises a layer of PTFE **437** coated onto plastic film substrate **441**, and is illustrated in FIG. **13C**. It should be

apparent to those ordinarily skilled in the art, upon reading the present disclosure, that other materials displaying similar light-rephasing and reflectivity properties may also be used.

LCD brightness may be further enhanced by the using a brightness enhancement film (BEF) in between the backlight distributor **430** and the DBEF layer **424**. As illustrated in FIG. 13A, flat panel LCD **410** includes optional BEF layer(s) **426**. In one embodiment where a single layer of BEF is used, LCD brightness may be increased by 50%. An even higher luminance gain may be attained when two layers of BEF are aligned at an angle of 90 to each other, a forming a "crossed BEF" layer. In some systems, a luminance gain of 75% may be attained when crossed BEFs are used. An additional benefit of the crossed BEF is that the viewing angle of the LCD is significantly increased.

However, one drawback of the DBEF is that off-axis visual artifacts such as color pattern or color stripes, may appear on the LCD screen if viewed at large angles from the normal direction. In furtherance of one embodiment of the present invention, a special cover sheet **422** may be used to eliminate such off-axis visual artifacts. According to the present embodiment, special cover sheet **422** comprises a thin light diffusing film placed between the DBEF and the rear polarizer of the LCD such that a small portion of the backlight is scattered at large off-axis angles. As a result, the contrast of the color stripe pattern is greatly reduced. However, it should be noted that special cover sheet **422** should not cause significant de-polarization because excess de-polarization would reduce the efficiency of the light-recycling process. In the present embodiment, special cover sheet **422** is made of an Lexan **8A35** material available from General Electric. Further, in the present embodiment, the special cover sheet **422** is cut with its optical axis matching the transmission axis of the polarizer and the DBEF.

In furtherance of the present invention, FIG. 13B illustrates another embodiment of a rear reflector **440** that may be used in place of rear reflector **438** of FIG. 13A. As shown, rear reflector **440** comprises a layer of barium sulfate **439** deposited on substrate **441** such as white plastic film(s). According to the present embodiment, barium sulfate layer **439** may be deposited on substrate **441** by first mixing barium sulfate powder with an organic binder to form a paste, and then screen printing the paste on the substrate **441**. Significantly, barium sulfate layer **439** should be at least 0.01" thick. It should be apparent to those of ordinary skill in the art, upon reading the present disclosure, that numerous well known organic binders and coating techniques may also be used to manufacture rear reflector **440**.

Selecting Appropriate Percentage Composition of Phosphors for Use in Cold Cathode Fluorescent Tubes

Portions of the present invention comprise computer-readable and computer-executable instructions which reside in, for example, computer-usable media of a computer system. FIG. 14 illustrates an exemplary computer system **500** upon which one embodiment of the present invention may be practiced. It is appreciated that system **500** of FIG. 14 is exemplary only and that the present invention can operate within a number of different computer systems and/or electronic device platforms.

System **500** of FIG. 14 includes an address/data-bus **510** for communicating information and a central processor unit **520** coupled to bus **510** for processing information and instructions. System **500** also includes data storage features such as computer-usable volatile memory **530**, e.g. random

access memory (RAM), coupled to bus **510** for storing information and instructions for central processor unit **520**; computer usable non-volatile memory **540**, e.g. read only memory (ROM), coupled to bus **510** for storing static information and instructions for the central processor unit **520**; a data storage unit **550** (e.g., a magnetic or optical disk and disk drive) coupled to bus **510** for storing information and instructions; and a network interface unit **590** (e.g. ethernet adapter card, modem, etc.) for receiving data from and transmitting data to a computer network. System **500** also includes optional devices such as an optional alphanumeric input device **570** coupled to bus **510** for communicating information and command selections to central processor unit **520**; an optional cursor control device **580** coupled to bus **510** for communicating user input information and command selections to central processor unit **520**; and an optional display device **560** coupled to bus **510** for displaying information.

Unless specifically stated otherwise as apparent from the following discussions, it is appreciated that throughout the present invention, discussions utilizing terms such as "receiving," "determining," "indicating," "transmitting," "repeating," or the like, refer to the actions and processes of a computer system or similar electronic computing device. The computer system or similar electronic device manipulates and transforms data, represented as physical (electronic) quantities within the computer system's registers and memories, into other data, similarly represented as physical quantities within the computer system memories, into other data similarly represented as physical quantities within the computer system memories, registers, or other such information storage, transmission, or display devices.

In the embodiments described above, LCD color temperature is altered by selectively dimming the brightness of one or the other of the light sources so that their overall contribution matches the desired LCD color temperature. LCD color temperature is also dependent upon the percentages of different phosphors that are used within the CCFLs. For instance, a CCFL tube that includes 33% of R-phosphor, 33% of G-phosphor, and 33% of B-phosphor will have different color temperature, chromaticity, and brightness than another one that includes 40% R-phosphor, 40% G-phosphor, and 20% B-phosphor. Therefore, it is necessary to select an appropriate percentage composition of R, G, and B phosphors such that the color temperature, luminance, and chromaticity of the LCD may be accurately controlled.

According to one embodiment of the present invention, an appropriate percentage composition of phosphors is selected such that, within a predetermined range of color temperature, the brightness of the LCD is not reduced below a given threshold minimum (e.g., 70 percent of the maximum brightness). In addition, in the present embodiment, the appropriate mix of R, G, B phosphors is selected such that, within the predetermined color temperature range, the color temperature of the display is held close to the black body curve **200** of the CIE chromaticity diagram **190** (FIG. 5). Finally, in the present embodiment, the appropriate mix of R, G, B phosphors in the light sources is selected such that their maximum brightness point is set to be near the middle of the predetermined color temperature range.

FIG. 15 is a flow diagram **600** illustrating a process (executed on system **500**) of selecting appropriate light source candidates such that, within a predetermined range of color temperature, the brightness of the LCD is not reduced below a given threshold minimum (e.g., 70 percent of the maximum brightness). For simplicity, in the present embodiment, the selection is made for a "blue" light source

136, and a “red” light source 132 of a color balancing embodiment 160 of FIG. 3B. Further, a target color temperature range is predetermined to be between 3,400 K to 8,250 K.

At step 610, high-resolution (1 nm) spectral files for particular types of R, G, and B phosphors are input into computer system 500 and stored at RAM 530 or data storage unit 550. The high-resolution spectral files for R, G, and B phosphors may be obtained from manufacturers of the phosphors. Particularly, each spectral file contains energy data of the emission spectrum of one type of phosphor (e.g. R-phosphors, G-phosphors or B-phosphors). Then, the energy data of the emission spectra of the R, G, and B phosphors are converted to luminance (brightness) data using the human eye sensitivity data over the visible emission spectrum. For simplicity, in the following discussion, the luminance data for R, G, and B phosphors are labeled $R(\lambda)$, $G(\lambda)$ and $B(\lambda)$, respectively. Significantly, each light source candidate is essentially represented by the percentages of R-phosphors, G-phosphors, and B-phosphors present in the light source candidate.

At step 620, a pool of light source candidates are generated by varying the amount of different phosphor types. According to the present embodiment, a 5%-increment scheme in the relative amounts of different phosphor types is adopted. For example, one light source candidate may have a percentage composition of 25% R-phosphors, 35% G-phosphors, and 40% B-phosphors. Another light source candidate may have a percentage composition of 40% R-phosphors, 40% G-phosphors, and 20% B-phosphors. Further, in the present embodiment, 400 (20×20) light source candidates are available.

At step 630, the luminance spectrum $W(\lambda)$ of each of the light source candidates is computed. According to the present embodiment, a “bluish” luminance spectrum $W1(\lambda)$ for “blue” light source 136 is calculated according to the following equation:

$$W1(\lambda)=a1*R(\lambda)+b1*G(\lambda)+c1*B(\lambda),$$

where $a1$, $b1$, $c1$ correspond to the percentages of red phosphors, green phosphors, and blue phosphors, respectively, selected for the “blue” light source 136, and where $a1+b1+c1=1$. According to the present embodiment, a total number of 400 calculations have to be made for each of the 400 light source candidates.

Similarly, a “reddish” luminance spectrum $W2(\lambda)$ for “red” light source 132 is calculated according to the following equation:

$$W2(\lambda)=a2*R(\lambda)+b2*G(\lambda)+c2*B(\lambda),$$

where $a2$, $b2$, $c2$ correspond to the percentages of red phosphors, green phosphors, and blue phosphors selected for the “red” light source 132, and where $a2+b2+c2=1$.

At step 640, a light source candidate is matched up with another light source candidate to form a candidate pair. In the present embodiment, the total number of light source candidate is 20 for each of the two light sources 132 and 136. Therefore, a total number of possible candidate pairs is 400.

At step 650, a combined luminance spectrum, $W3(\lambda)$, is computed for the selected candidate pair. The combined luminance spectrum results from contributions from “blue” light source candidate and from “red” light source candidate, and can be calculated according to the equation:

$$W3(\lambda)=L1*W1(\lambda)+L2*W2(\lambda),$$

where $L1$ and $L2$ represent brightness levels of “blue” light source 136, and “red” light source 132, respectively. Accord-

ing to the present embodiment, the brightness level $L1$ of the “blue” light source 136, and the brightness level $L2$ of the “red” light source 132 may be selectively and independently adjusted to modify the color temperature of the LCD. Further, according to the present embodiment, a 5% increment/decrement scheme in the intensity levels $L1$ and $L2$ is adopted. Thus, in the present embodiment, after discarding redundancy, a total number of 200 combined luminance spectrums are calculated for the selected candidate pair.

At step 660, for each of the combined luminance spectrums generated at step 650 for the selected candidate pair, a luminance value and a color temperature is calculated. Methods for calculating luminance values and color temperatures from luminance spectrums are well known in the art. Therefore, details of such methods are not described herein to avoid obscuring aspects of the present invention. In one embodiment, a maximum luminance value, L_{max} , corresponding to the maximum brightness levels ($L1=L2=100\%$) of the “blue” light source candidate and the “red” light source candidate, is also calculated.

At step 670, a table for storing the luminance values and color temperatures associated with the selected candidate pair is constructed, thus forming a color temperature-luminance relationship for the selected candidate pair.

At step 680, candidate pairs having luminance values (L) smaller than a minimum luminance threshold (e.g. 70% of L_{max}) between the predetermined color temperature range (e.g. between 3,400 K to 8,250 K) are rejected. In this way, a significant number of candidate pairs are rejected and the simulation time for any subsequent steps is reduced.

At step 690, it is determined whether all the possible combinations of candidate light sources have been processed. If it is determined that all possible combinations of the candidate light sources have been processed, candidate pairs that do not meet the requisite criterion are rejected, and the processed ends. However, if there are possible combinations of candidate light sources that have not been processed, steps 610 through 690 are repeated.

FIG. 16 is a flow diagram 700 illustrating a process of selecting appropriate light source candidates such that within the predetermined color temperature range, the color temperature is held close to the black body curve 200 of the CIE chromaticity diagram 190.

At step 710, a candidate pair is selected from the pool of candidate pairs that have not been rejected. According to the one embodiment, the process illustrated in flow diagram 700 is performed after candidate pairs that do not meet the luminance requirement are rejected.

At step 720, the chromaticity values (x , y) for a candidate pair is determined from the combined luminance spectrums calculated in step 660. In one embodiment, a different chromaticity value (x , y) is calculated for each luminance spectrum for each candidate pair. Methods for calculating chromaticities from luminance spectrums are well known in the art. Therefore, details of such methods are not described herein to avoid obscuring aspects of the present invention.

At step 730, the chromaticity values over the luminance spectrums for a candidate pair are compared to the black body curve 200 of chromaticity diagram 190. In one embodiment, a relationship of color temperature and chromaticity is built, and the relationship is compared to the black body radiation curve. Methods for performing statistical comparison for two set of data are well known in the art. Therefore, it would be apparent to those of ordinary skill in the art, upon reading the present disclosure, that numerous statistical analysis algorithms may be implemented herein.

In one embodiment, the sum of the derivatives are computed and compared to other sums of other candidate pairs.

At step **740**, if it is determined that the chromaticity values of the candidate pair is significantly deviated from the black body curve **200**, then the candidate pair is rejected.

At step **750**, if it is determined that the chromaticity does not significantly deviate from the black body curve **200**, then the candidate pair remains in the pool.

At step **760**, a new candidate pair is selected from the remaining pool of candidate pairs, and steps **710–750** are repeated until all the candidate pairs have been processed. Thereafter, at step **770**, when all candidate pairs have been processed, the process returns, and the number of candidate pairs is further reduced.

FIG. **17** is a flow diagram **800** illustrating a process of selecting appropriate light source candidates such that a maximum luminance occurs approximately in the middle of a given color temperature range.

At step **810**, a pair of light source candidates are selected from the pool of candidate pairs that have passed the luminance threshold requirement and that closely follow the black body curve **200**.

At step **820** of FIG. **17**, color temperature values of the selected candidate pair are plotted against luminance values of the selected candidate pair to provide a color temperature and luminance diagram. Exemplary color temperature and luminance diagrams are illustrated in FIGS. **9B** and **9C**.

At step **830**, it is determined whether a peak luminance point, or maximum luminance point, i.e. when both “blue” and “red” light source candidates are turned on at a maximum intensity, occurs approximately at the middle of the given color temperature range. In the exemplary color temperature and luminance diagram of FIG. **9B**, peak luminance point **266** occurs at roughly 4700 K. In FIG. **9C**, the peak luminance point **276** occurs at roughly 5050 K.

At step **840**, if it is determined that the peak luminance point does not occur approximately at the middle of the given color temperature range, then the candidate pair is rejected. For instance, in the example as illustrated in FIG. **9B**, for a predetermined range of color temperature between 3,400 K to 8,250 K, the peak luminance point should occur at approximately 5825 K. The peak luminance point, however, occurs at approximately 4700 K for the example as illustrated in FIG. **9B**. Therefore, the example as illustrated in FIG. **9B** does not satisfy this requirement, and will be rejected.

At step **850**, if it is determined that the maximum luminance occurs roughly in the middle of the predetermined color temperature range, then the candidate pair remains in the pool of potential candidates. Thereafter, the process returns.

At step **860**, a new candidate pair is selected from the remaining pool of candidate pairs, and steps **810–850** are repeated until all the candidate pairs have been processed. Thereafter, at step **870**, when all candidate pairs have been processed, the process returns, and the number of candidate pairs is further reduced.

According to one embodiment of the present invention, an offset value may be added to the luminance spectrum so as to compensate for the yellow shift caused by many of the layers, e.g., the acrylic in the light pipes, the ultra-violet cured extraction patterns, the DBEF and BEF films, the polarizers, the LCD layer and the color filters, within an LCD flat panel display system. The offset value, however, is largely determined by the experience and skill of the light tube designer, and by empirical experimentation. In addition, light tube designers may adjust the values of the

percentage compositions of the R-phosphors, G-phosphors, and B-phosphors to produce a pair of CCFL tubes that have the ideal “look and feel.”

Rear Backlighting Embodiments

FIG. **18A** illustrates a backlighting embodiment **910** of the present invention that positions an array of light sources **132a–132b** and **136a–136b** directly under the display layer **912** thereby obviating the need for any light pipes. A diffuser layer **914** is used to diffuse the light emitted from the light sources to promote light uniformity. If the light sources are placed near the diffuser layer **914** (e.g., less than one inch away), then hiding lines may be required. These hiding lines are typically etched on the diffuser layer and are more numerous near the body of the light sources. The relative intensities of the light sources (red and blue) can be controlled to perform color temperature balancing as described above in the numerous edge lit embodiments. A rear reflector layer **138** is also used in embodiment **910**.

The information display layer **912** (“display layer **912**”) is generally a non-emissive modulated display layer. The layer **912** is non-emissive meaning that it does not generate any original light but rather modules the light of another light source (e.g., sources **132a–b** and **136a–b**). The display layer **912** modules light that layer **912** does not generate. Modulation is used to form images on layer **912** thereby conveying information. In one embodiment, display layer **912** is a liquid crystal display layer of the technology shown in FIG. **2A** including the layers between layer **126** and layer **112**. Alternatively, the display layer **912** an electrophoretic display layer using ion migration for modulation. Layer **912** can also be a reflective display layer or a layer having a fixed modulated design printed or otherwise laid thereon. Layer **912** can also be an electromechanical display using shuttered pixels (“windows”) for modulation. Layer **912** can also be a ferroelectric display.

FIG. **18B** illustrates another backlighting embodiment **922** similar to embodiment **910** except the rear reflector **920** contains scallops cut therein and each light source **132a–132b** and **136a–136b** is positioned with its own scallop to increase directed reflection. FIG. **18C** illustrates another backlighting embodiment **930** that is similar to embodiment **922** except that within the reflector layer **936** a pair of light sources **132a** and **136** can be positioned within a single scallop.

Conclusion

The preferred embodiment of the present invention, a color balancing system for a flat panel LCD unit applying variable brightness to multiple light sources of varying color temperature, is thus described. While the present invention has been described in particular embodiments, it should be appreciated that the present invention should not be construed as limited by such embodiments, but rather construed according to the below claims.

What is claimed is:

1. A flat panel display comprising:

- a planar light pipe disposed to provide backlight to a liquid crystal display layer;
- a first light source optically coupled to provide a first spectral component of light to said planar light pipe, said first spectral component having a first color temperature and wherein said first color temperature is below a predefined minimum color temperature;
- a second light source optically coupled to provide a second spectral component of light to said planar light

25

pipe, said second spectral component having a second color temperature and wherein said second color temperature is above a predefined maximum color temperature; and

wherein said first and second light sources are stacked parallel to each other and positioned along a same edge of said planar light pipe.

2. The flat panel display according to claim 1 wherein a color temperature of said backlight of said flat panel display is adjustable by selectively and independently varying brightness of said first light source and said second light source.

3. The flat panel display according to claim 2 wherein said first color temperature is approximately 3,560 K.

4. The flat panel display according to claim 2 wherein said second color temperature is approximately 15,000 K.

5. The flat panel display according to claim 2 and further comprising:

a rear polarizer of said flat panel display for polarizing light in a predetermined orientation, said rear polarizer receiving light from said planar light pipe;

a pre-polarizer interposed between said planar light pipe and said rear polarizer and on a first side of said planar light pipe for allowing a first portion of light polarized in said predetermined orientation to pass, wherein a second portion of light is reflected toward a second side of said planar light pipe; and

a reflector for increasing brightness of said flat panel display, said reflector being positioned on said second side of said planar light pipe to receive said second portion of light, said reflector further having a layer of light rephasing material for rephasing said second portion of light into said predetermined orientation such that a part of second portion of light is allowed to pass through said pre-polarizer and said rear polarizer.

6. The flat panel display according to claim 5 wherein said light rephasing material comprises a PTFE material.

7. The flat panel display according to claim 5 wherein said pre-polarizer comprises a layer of dual brightness enhancement film (DBEF).

8. The flat panel display according to claim 5 further comprising:

a light diffusing film disposed between said pre-polarizer and said rear polarizer for eliminating off-axis defects.

9. The flat panel display according to claim 8 wherein said light diffusing film comprises a LEXAN film.

10. The flat panel display according to claim 5 further comprising a crossed brightness enhancement film (BEF) interposed between said planar light pipe and said rear polarizer of said liquid crystal display screen for expanding a view angle of said liquid crystal display screen.

11. The flat panel display according to claim 5 wherein said light rephasing material comprises a material including barium sulfate.

12. A flat panel display comprising:

a planar light pipe for providing backlight to a liquid crystal display layer;

a bi-directional light extraction pattern on one surface of said planar light pipe for uniformly distributing light over said planar light pipe;

a first light source optically coupled to provide a first spectral component of light to said planar light pipe, said first spectral component having a first color temperature that is below a predefined minimum color temperature;

26

a second light source optically coupled to provide a second spectral component of light to said planar light pipe, said second spectral component having a second color temperature that is above a predefined maximum color temperature; and

wherein said first and second light sources are stacked parallel to each other and positioned along a same edge of said planar light pipe.

13. The flat panel display according to claim 12 wherein a color temperature of said backlight of said flat panel display is adjustable between said minimum and said maximum color temperature by selectively and independently varying brightness of said first light source and said second light source.

14. The flat panel display according to claim 12 wherein said first color temperature is approximately 3,560 K.

15. The flat panel display according to claim 12 wherein said second color temperature is approximately 15,000 K.

16. The flat panel display according to claim 12 and further comprising:

a rear polarizer of said flat panel display for polarizing light in a predetermined orientation, said rear polarizer receiving light from said planar light pipe;

a pre-polarizer interposed between said planar light pipe and said rear polarizer and on a first side of said planar light pipe for allowing a first portion of light polarized in said predetermined orientation to pass, wherein a second portion of light is reflected toward a second side of said planar light pipe; and

a reflector for increasing brightness of said flat panel display, said reflector being positioned on said second side of said planar light pipe to receive said second portion of light, said reflector further having a layer of light rephasing material for rephasing said second portion of light into said predetermined orientation such that a part of second portion of light is allowed to pass through said pre-polarizer and said rear polarizer.

17. The flat panel display according to claim 16 wherein said light rephasing material comprises a PTFE material.

18. The flat panel display according to claim 16 wherein said pre-polarizer comprises a layer of dual brightness enhancement film (DBEF).

19. The flat panel display according to claim 16 further comprising:

a light diffusing film disposed between said pre-polarizer and said rear polarizer for eliminating off-axis defects.

20. The flat panel display according to claim 19 wherein said light diffusing film comprises a LEXAN film.

21. The flat panel display according to claim 16 further comprising a crossed brightness enhancement film (BEF) interposed between said planar light pipe and said rear polarizer of said liquid crystal display screen for expanding a view angle of said liquid crystal display screen.

22. The flat panel display according to claim 16 wherein said light rephasing material comprises a material including barium sulfate.

23. The flat panel display according to claim 12 wherein said bidirectional light extraction pattern comprises:

a plurality of extraction dots that increase in size as a function of their distance away from said light sources; and

a plurality of relatively larger extraction dots positioned at corners of said extraction pattern.

24. A flat panel display comprising:

a planar light pipe for providing backlight to a liquid crystal display layer,

27

- a bidirectional light extraction pattern on one surface of said planar light pipe for uniformly distributing light over said planar light pipe;
- a first light source optically coupled to provide a first spectral component of light to said planar light pipe, said first spectral component having a first color temperature;
- a second light source optically coupled to provide a second spectral component of light to said planar light pipe, said second spectral component having a second color temperature; and

28

wherein said first and second light sources are stacked parallel to each other and positioned along a same edge of said planar light pipe.

25. The flat panel display according to claim **24** wherein a color temperature of said backlight of said flat panel display is adjustable between a minimum and said maximum color temperature by selectively and independently varying brightness of said first light source and said second light source.

* * * * *

专利名称(译)	液晶平板显示器，具有增强的背光亮度和特别选择的光源		
公开(公告)号	US6657607	公开(公告)日	2003-12-02
申请号	US09/811988	申请日	2001-03-19
申请(专利权)人(译)	SILICON GRAPHICS, INC.		
当前申请(专利权)人(译)	RPX CORPORATION		
[标]发明人	EVANICKY DANIEL E LU SUN		
发明人	EVANICKY, DANIEL E. LU, SUN		
IPC分类号	G02F1/13 G02F1/1335 G02F1/13357 G09G3/36		
CPC分类号	G02F1/133609 G02F1/13362 G02B6/0068 G02B6/0046 G02B6/0051 G02B6/0055 G02B6/0056 G02F2001/133507 G02B6/0076		
代理机构(译)	贝克博茨L.L.P.		
审查员(译)	常, KENT		
外部链接	Espacenet USPTO		

摘要(译)

通过使用预偏振膜进行偏振再循环以使光预偏振，以及用于回收由预偏振膜反射的光的特殊反射器，增强了LCD中的亮度。在一个实施例中，预偏振膜包括一层DBEF亮度增强膜，后反射器由PTFF材料制成。在另一个实施例中，后反射器覆盖有包含硫酸钡的膜。选择多个光源，使得在预定范围内的任何色温下，LCD的亮度不会降低到给定的阈值最小值以下（例如，最大亮度的70%）。选择光源的另一个限制是在预定色温范围内，色温保持接近CIE色度图的黑体曲线。还选择光源，使得它们的最大亮度点被设置为接近预定色温范围的中间。

