



US007583343B2

(12) **United States Patent**
Sekime

(10) **Patent No.:** **US 7,583,343 B2**
(45) **Date of Patent:** **Sep. 1, 2009**

(54) **LIQUID CRYSTAL DISPLAY DEVICE AND ELECTRONIC APPARATUS**

2006/0114385 A1* 6/2006 Ito et al. 349/119

(75) Inventor: **Tomoaki Sekime**, Suwa (JP)

(73) Assignee: **Seiko Epson Corporation** (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 554 days.

FOREIGN PATENT DOCUMENTS

CN	1053302	7/1991
CN	1281157	1/2001
CN	1392964	1/2003

(21) Appl. No.: **11/065,749**

(22) Filed: **Feb. 25, 2005**

(Continued)

(65) **Prior Publication Data**

US 2005/0190328 A1 Sep. 1, 2005

OTHER PUBLICATIONS

Communication from Japanese Patent Office regarding related application.

(30) **Foreign Application Priority Data**

Feb. 26, 2004	(JP)		2004-051667
Nov. 9, 2004	(JP)		2004-324748

Primary Examiner—David Nelms

Assistant Examiner—Thanh-Nhan P Nguyen

(74) *Attorney, Agent, or Firm*—Harness, Dickey & Pierce, P.L.C.

(51) **Int. Cl.**

G02F 1/1335 (2006.01)

(52) **U.S. Cl.** **349/119; 349/117; 349/118**

(58) **Field of Classification Search** 349/114, 349/117–119

See application file for complete search history.

(57)

ABSTRACT


The liquid crystal display device includes a liquid crystal cell having a nematic liquid crystal layer, upper and lower retardation plates sandwiching the liquid crystal cell, an upper polarizer above the upper retardation plate, and a lower polarizer below the lower retardation plate. The nematic liquid crystal layer is arranged at the upper and lower substrates with the twist angle set in a range of 0° to 70° which is subjected to a rubbing process at a predetermined angle relative to a reference direction. The lower retardation plate has a first lower retardation plate of a discotic liquid crystal film with hybrid alignment, and a second lower retardation plate of a polymer film having a three-dimensional refractive index anisotropy. The three-dimensional refractive index of the second lower retardation plate is set in a range of −0.7 to 0.7.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,139,340 A	8/1992	Okumura	
6,307,608 B1	10/2001	Sakamoto	
6,411,355 B1*	6/2002	Manabe et al.	349/120
6,771,334 B2	8/2004	Kubota	
6,801,283 B2*	10/2004	Koyama et al.	349/119
6,816,217 B2*	11/2004	Sone	349/114
2001/0030726 A1*	10/2001	Yoshida et al.	349/117
2004/0233362 A1*	11/2004	Kashima	349/117
2005/0041180 A1*	2/2005	Ozawa	349/98
2005/0057704 A1*	3/2005	Ootake et al.	349/69
2005/0087704 A1	4/2005	Funakoshi et al.	
2006/0072054 A1*	4/2006	Ito	349/96

9 Claims, 14 Drawing Sheets



US 7,583,343 B2

Page 2

FOREIGN PATENT DOCUMENTS

JP	05-100114	4/1993	JP	10-206637	8/1998
JP	9-203895	8/1997	JP	2002-182036	6/2002
JP	10-033314	2/1998	JP	2003-090914	3/2003
JP	10-186356	7/1998	JP	2003-322855	11/2003
			WO	03/085949	10/2003
			* cited by examiner		

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B





FIG. 8






FIG. 10




FIG. 11A

		PREFERRED RANGE		MORE PREFERRED RANGE	
		ANGLE	PHASE DIFFERENCE VALUE	ANGLE	PHASE DIFFERENCE VALUE
UPPER POLARIZING PLATE 2		-80 DEG.< ϕ _{pu} <80 DEG.	—	15 DEG.	—
UPPER RETARDATION PLATE 3a		-60 DEG.< ϕ _{F1} <60 DEG.	220nm<RF3a<290nm	30 DEG.	260nm
UPPER RETARDATION PLATE 3b		45 DEG.< ϕ _{F2} <35 DEG.	50nm<RF3b<140nm	90 DEG.	90nm
LIQUID CRYSTAL LAYER	UPPER	80 DEG.< ϕ _{LCu} <130 DEG.	220nm< Δ nd<350nm	90 DEG.	REFLECTED 163nm
	LOWER	230 DEG.< ϕ _{LCd} <270 DEG.		270 DEG.	TRANSMITTED 325nm
LOWER RETARDATION PLATE 5a		85 DEG.< ϕ _{F3} <95 DEG.	10nm<RF5a<40nm	90 DEG.	26nm
LOWER RETARDATION PLATE 5b		85 DEG.< ϕ _{F4} <95 DEG.	80nm<RF5b<150nm	90 DEG.	130nm
LOWER RETARDATION PLATE 5c		-60 DEG.< ϕ _{F5} <60 DEG.	220nm<RF5c<290nm	150 DEG. (-30 DEG.)	270nm
LOWER POLARIZING PLATE 7		45 DEG.< ϕ _{pd} <135 DEG.	—	75 DEG.	—

FIG. 11B

	PREFERRED RANGE		MORE PREFERRED RANGE	
	ANGLE	PHASE DIFFERENCE VALUE	ANGLE	PHASE DIFFERENCE VALUE
UPPER POLARIZING PLATE 2	-80 DEG.< ϕ_{pu} <80 DEG.	—	15 DEG.	—
UPPER RETARDATION PLATE 3c	-60 DEG.< ϕ_{F6} <60 DEG.	100nm<RF3c<200nm	50 DEG.	170nm
LIQUID CRYSTAL LAYER	UPPER 80 DEG.< ϕ_{LCu} <130 DEG.	220nm< Δn_d <350nm	90 DEG.	REFLECTED 163nm
	LOWER 230 DEG.< ϕ_{LCd} <270 DEG.		270 DEG.	TRANSMITTED 325nm
LOWER RETARDATION PLATE 5a	85 DEG.< ϕ_{F3} <95 DEG.	10nm<RF5a<40nm	90 DEG.	26nm
LOWER RETARDATION PLATE 5b	85 DEG.< ϕ_{F4} <95 DEG.	80nm<RF5b<150nm	90 DEG.	130nm
LOWER RETARDATION PLATE 5c	-60 DEG.< ϕ_{F5} <60 DEG.	220nm<RF5c<290nm	150 DEG. (-30 DEG.)	270nm
LOWER POLARIZING PLATE 7	45 DEG.< ϕ_{pd} <135 DEG.	—	75 DEG.	—

FIG. 11C

	PREFERRED RANGE		MORE PREFERRED RANGE	
	ANGLE	PHASE DIFFERENCE VALUE	ANGLE	PHASE DIFFERENCE VALUE
UPPER POLARIZING PLATE 2	-80 DEG.< ϕ _{pu} <80 DEG.	—	15 DEG.	—
UPPER RETARDATION PLATE 3d	-60 DEG.< ϕ _{F7} <60 DEG.	220nm<RF3d<290nm	30 DEG.	265nm
UPPER RETARDATION PLATE 3e	45 DEG.< ϕ _{F8} <135 DEG.	50nm<RF3e<140nm	90 DEG.	130nm
UPPER RETARDATION PLATE 3f	45 DEG.< ϕ _{F9} <135 DEG.	10nm<RF3f<40nm	90 DEG.	30nm
LIQUID CRYSTAL LAYER	UPPER	80 DEG.< ϕ _{LCu} <130 DEG.	90 DEG.	REFLECTED 163nm
	LOWER	230 DEG.< ϕ _{LCd} <270 DEG.	270 DEG.	TRANSMITTED 325nm
LOWER RETARDATION PLATE 5a	85 DEG.< ϕ _{F3} <95 DEG.	10nm<RF5a<40nm	90 DEG.	26nm
LOWER RETARDATION PLATE 5b	85 DEG.< ϕ _{F4} <95 DEG.	80nm<RF5b<150nm	90 DEG.	130nm
LOWER RETARDATION PLATE 5c	-60 DEG.< ϕ _{F5} <60 DEG.	220nm<RF5c<290nm	150 DEG. (-30 DEG.)	270nm
LOWER POLARIZING PLATE 7	45 DEG.< ϕ _{pd} <135 DEG.	—	75 DEG.	—

FIG. 12A




FIG. 12B




FIG. 12C




FIG. 12D





FIG. 13



LIQUID CRYSTAL DISPLAY DEVICE AND ELECTRONIC APPARATUS

RELATED APPLICATIONS

This application claims priority to Japanese Patent Application Nos. 2004-051667 filed Feb. 26, 2004 and 2004-324748 filed Nov. 9, 2004 which are hereby expressly incorporated by reference herein in their entirety.

BACKGROUND

1. Technical Field

The present invention relates to a transmissive liquid crystal display device capable of performing display in a transmitting mode and a reflecting mode, and an electronic apparatus using the same.

2. Related Art

An active driven twisted nematic (TN) liquid crystal display device has several advantages of thin size, light-weight, and low power consumption, so that it is widely employed as a display device of a portable telephone, a notebook computer, a portable television, a portable digital assistant (PDA), etc.

However, in the conventional twisted nematic liquid crystal display device, there exists a problem in a viewing angle that causes a display color to be changed or a display contrast to be degraded when the liquid crystal display device is viewed in a tilted angle due to a refractive index anisotropy of the liquid crystal molecule. That is, when a voltage is applied to a liquid crystal layer, the liquid crystal molecule is almost vertically aligned to show a positive one axial property, but a twisted angle has an S-shaped distribution, and the liquid crystal molecule is not significantly tilted near each surface of upper and lower substrates due to an effect of the alignment regulating force of the substrate surface. As a result, the configuration of the liquid crystal molecule when a voltage is applied thereto is differently shown depending on the angle of viewing the liquid crystal display device and its azimuth.

This is why improvement of the viewing angle problem is strongly desired in the liquid crystal display device, and various attempts are made for the improvement. As a representative method thereof, a method is disclosed which does not change the structure of the liquid crystal display device at all, but has an optical compensation film as a retardation plate incorporated into the conventional twisted nematic liquid crystal display device so as to increase the viewing angle.

A method of fabricating an optical compensation film used as the above-mentioned optical compensation film has been proposed, wherein the film is formed of a liquid crystalline polymer representing a positive one axial property optically and has fixed a nematic hybrid alignment which was formed in a liquid crystal state. This method has an advantage of cost effective production because it does not require fabrication equipment for the liquid crystal display device to be improved or additionally.

However, among various liquid crystal display devices, in a transmissive liquid crystal display device in which a partially reflecting layer is interposed between a nematic liquid crystal layer and a lower polarizer, there occurs a problem that the amount of display light or contrast is not sufficient in a transmitting mode even though an optical compensation film functioning as the retardation plate is disposed. Thus, there exists a case that a plurality of retardation plates more than four is employed, however, which causes the cost to be

increased and the display performance to be degraded due to a variation of the phase retardation axis of each retardation plate.

Accordingly, the present invention has been made in consideration of the above circumstances, and it is an object of the present invention to provide a liquid crystal display device capable of improving the contrast or the amount of display light in a transmitting mode by using an optimized optical compensation film, and an electronic apparatus using the same.

SUMMARY

In one aspect of the present invention, a liquid crystal display device includes: a lower polarizer; a lower retardation plate formed above the lower polarizer, the lower retardation plate having a first lower retardation plate made of a discotic liquid crystal film with hybrid alignment and a second lower retardation plate made of a polymer film having a three-dimensional refractive index anisotropy, the second lower retardation plate being disposed below the first lower retardation plate and having a three-dimensional refractive index in a range of -0.7 to 0.7 ; a liquid crystal cell formed above the lower retardation plate, the liquid crystal cell having a nematic liquid crystal layer, the nematic liquid crystal layer having a twist angle set in a range of 0° to 70° ; an upper retardation plate formed above the liquid crystal cell; and an upper polarizer formed above the upper retardation plate.

The above-described liquid crystal display device is suitably applied to a transmissive liquid crystal display device, and is configured to have a first lower retardation plate made of a discotic liquid crystal film with hybrid alignment disposed between the lower polarizer and the liquid crystal cell where the twist angle of the liquid crystal is set to 0° to 70° , and a second lower retardation plate made of a polymer film having a three-dimensional refractive index anisotropy disposed below the first lower retardation plate. The tilt of the liquid crystal layer is compensated by the first lower retardation plate made of the discotic liquid crystal film with hybrid alignment, and a phase difference is given in a thickness direction of the liquid crystal cell by the second lower retardation plate made of the polymer film having the three-dimensional refractive index anisotropy, so that the refractive index of a whole structure of these layers can be made uniform in a three-dimensional manner, which allows the viewing angle dependency to be decreased. Accordingly, the liquid crystal display device may allow a wide viewing angle to be implemented, which leads to an increase in the amount of display light and the enhancement of the contrast in the transmissive display mode.

In a preferable example of the above-described liquid crystal display device, the first lower retardation plate has a hybrid alignment axis in a range of 85° to 95° in a counterclockwise direction with respect to a reference direction when the first lower retardation plate is seen from the top. In addition, the second lower retardation plate has a phase retardation axis in a range of 85° to 95° in a counterclockwise direction with respect to the reference direction when the second lower retardation plate is seen from the top.

In one aspect of the above-described liquid crystal display device, the upper retardation plate has first and second upper retardation plates whose phase retardation axes are different in their direction from each other as seen from the top and which are made of a low dispersion film. In another aspect, a single retardation plate made of a reverse wavelength dispersion film may be employed instead of the two retardation plates made of a low dispersion film. Accordingly, the number

of the retardation plate can be reduced, which allows the liquid crystal display device to be thinly fabricated.

In still another aspect of the above-described liquid crystal display device, the upper retardation plate has a first upper retardation plate made of a discotic liquid crystal film with hybrid alignment, and a second upper retardation plate made of a polymer film having a three-dimensional refractive index anisotropy, and the second upper retardation plate is disposed above the first retardation plate. In this aspect, a combination of the retardation plate made of a discotic liquid crystal film with hybrid alignment and the retardation plate made of polymer film having a three-dimensional refractive index anisotropy is disposed not only below the liquid crystal cell but also above the liquid crystal cell, so that the viewing angle can be further improved.

In a preferable example of the above-described liquid crystal display device, the liquid crystal cell is a transmissive liquid crystal cell having a partially reflecting layer, and the thickness of the nematic liquid crystal layer in a reflecting portion corresponding to the partially reflecting layer is smaller than that of the nematic liquid crystal layer in a transmitting portion other than the reflecting portion. By employing such a so-called multi gap structure, the retardation between the reflecting display portion and the transmissive display portion can be optimized in the transmissive liquid crystal display device, which allows the display quality to be enhanced in the transmitting mode.

The liquid crystal display device according to the present invention may be suitably applied to an electronic apparatus having a display unit, such as a portable telephone, a notebook computer, a portable television, a portable digital assistant (PDA), and so forth.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram illustrating an electrical configuration of a liquid crystal display to which the present invention is applied.

FIG. 2 is an exploded perspective view illustrating a configuration of the liquid crystal display device shown in FIG. 1.

FIG. 3 is an enlarged cross-sectional view illustrating a portion of the liquid crystal display device shown in FIG. 1.

FIG. 4 is a plan view illustrating the layout of several pixels of the liquid crystal display device shown in FIG. 1.

FIG. 5 is a cross-sectional view taken along the A-A' line of FIG. 4.

FIGS. 6A and 6B are views for explaining the principle of viewing angle compensation.

FIGS. 7A and 7B are view for explaining the principle of viewing angle compensation.

FIG. 8 is a view illustrating a laminated configuration of optical components in accordance with a first embodiment of the present invention.

FIG. 9 is a view illustrating a laminated configuration of optical components in accordance with a second embodiment of the present invention.

FIG. 10 is a view illustrating a laminated configuration of optical components in accordance with a third embodiment of the present invention.

FIGS. 11A, 11B, and 11C are tables illustrating an axial direction and so forth of each optical component in accordance with the first to third embodiments.

FIGS. 12A, 12B, 12C, and 12D are graphs illustrating a viewing angle characteristic as compared to the related art.

FIG. 13 is a perspective view illustrating an example of an electronic apparatus using the liquid crystal display device of the present invention.

DETAILED DESCRIPTION

Hereinafter, preferred embodiments of the present invention will be described with reference to the accompanying drawings.

Overall Configuration of Liquid Crystal Display Device

FIG. 1 is a block diagram illustrating an electrical configuration of the liquid crystal display device to which the present invention is applied. FIGS. 2 and 3 are an exploded perspective view of the configuration of the liquid crystal display device shown in FIG. 1, and a partially enlarged cross-sectional view thereof, respectively. FIG. 4 is a plan view illustrating the layout of several pixels including a thin film diode (TFD) in the liquid crystal display device, and FIG. 5 is a cross-sectional view taken along the line A-A' of FIG. 4.

The liquid crystal display to which the present invention is applied is an active matrix type transmissive liquid crystal display device using nematic liquid crystal, wherein a plurality of scanning lines **31** is arranged in a row direction (x-direction) and a plurality of data lines **21** is arranged in a column direction (y-direction) as shown in FIG. 1. In addition, a pixel **11** is formed at each intersection of the scanning line **31** and the data line **21**. A liquid crystal layer **12** formed of nematic liquid crystal and a thin film diode (TFD) element **40** as a two-terminal type active element are serially connected to each other in each pixel **11**. In the present example, the liquid crystal layer **12** is connected to the scanning line **31**, and the TFD element **40** is connected to the data line **21**. Each scanning line **31** is driven by the scanning line driving circuit **350**, and each data line **21** is driven by the data line driving circuit **250**.

In the liquid crystal display device **1** as shown in FIG. 2, a driving liquid crystal cell **10** having a pair of transmitting substrates bonded to each other with predetermined spacing is used, while an upper polarizer **2**, at least one upper retardation plate **3**, a driving liquid crystal cell **10**, a plurality of lower retardation plates **5**, a lower polarizer **7**, and a backlight **9** are arranged to overlap each other downward from the upper side in this order. In addition, the number of the upper retardation plate **3** is different from each other in each embodiment to be described later.

In the driving liquid crystal cell **10**, the transmitting substrate on one side is an element substrate **20** where active elements are formed, and the transmitting substrate on the other side is a counter substrate **30** opposed to the element substrate **20**. The element substrate **20** and the counter substrate **30** are bonded by a seal **34** including a spacer (not shown) while maintaining a predetermined gap therebetween, and a liquid crystal layer to be described layer is enclosed within the gap to be retained.

In the liquid crystal display device **1**, an integrated circuit (IC) driver for driving the liquid crystal which constitutes the data line driving circuit **250** is directly mounted on a surface of the element substrate **20** by means of a chip on glass (COG) technique, and an IC (driver) for driving the liquid crystal which constitutes the scanning line driving circuit **350** is also directly mounted on a surface of the counter substrate **30**. In addition, other techniques may be employed to have a connected configuration of the IC chip and the liquid crystal display device instead of the COG technique. For example, a tape automated bonding (TAB) technique may be employed to have a tape carrier package (TCP) where an IC chip is bonded on a flexible printed circuit (FPC) to be electrically

connected to the liquid crystal display device. In addition, a technique of bonding the IC chip onto a hard substrate (i.e. chip on board (COB)) may be employed.

As shown in FIGS. 3 and 4, a plurality of data lines 21, a plurality of TFDs 40 connected to the data lines 21, and a pixel electrode 23 connected to each of the TFD element 40 in one-to-one manner on an inner surface of the element substrate 20. This pixel electrode 23 is formed of a transparent metal film such as an indium tin oxide (ITO). Each data line 21 extends in a straight line, and the TFD element 40 and the pixel electrode 23 are arranged in a dot matrix. An alignment film 24 is formed on the surface of the pixel electrode 23 which has been subjected to a rubbing process as one axial alignment process having conditions to be described later. This alignment film 24 is generally formed of a polyimide resin or the like.

In the meantime, a layer-thickness adjusting film for adjusting the thickness of the liquid crystal layer 12 in the transmissive display region 14 and the thickness of the liquid crystal layer 12 in the reflective display region 13, a partially reflecting layer 33 formed of a single layer or a multi-layer made of aluminum, aluminum alloy, silver, silver alloy, etc. or laminated layers thereof, a color filter 34, an overcoat layer 35, a belt-shaped counter electrode 36 formed of a transparent metal film such as ITO or the like, and an alignment film 37 are formed on an inner surface of the counter substrate 30.

Among these layers, the layer-thickness adjusting film 32 and the partially reflecting layer 33 are selectively formed in the reflective display region 13 of the pixel 11, and are not formed in the transmissive display region 14.

The color filter 34 has three colored layers of red (R), green (G), and blue (B) colors. A black matrix 38 is formed in a gap between each colored layer, and is configured to block lights incident from the gaps of the colored layers. The overcoat layer 35 is formed for the purpose of increasing the smoothness of the black matrix 38 and the color filter 34 in the surface of the black matrix 38 and the color filter 34 to thereby prevent disconnection of the counter electrode 36. In this case, the counter electrode 36 functions as a scanning line 31, and is formed in a direction orthogonal to the data line 21.

The alignment film 37 which has been subjected to a rubbing process such as one axial rubbing process is formed in the surface of the counter electrode 36 using conditions to be described later. This alignment film 37 is generally formed of polyimide resin or the like.

As shown in FIGS. 4 and 5, on an insulating film 25 formed on the surface of the element substrate 20, the TFD element 40 has a first TFD element 40a and a second TFD element 40b, and is formed of a first metal film 42, an oxide film 44 as an insulator formed by anodization on the surface of the first metal film 42, and second metal films 46a and 46b formed on the surface and spaced from each other. In addition, the second metal film 46a functions as the data line 21 while the second metal film 46b is connected to the pixel electrode 23 formed of an ITO film or the like.

The first TFD element 40a is formed of the second metal film 46a, the oxide film 44, and the first metal film 42 in the order as seen from the side of data line 21, and has a sandwiched structure of:

metal(conductor)/insulator/metal(conductor),

so that it has a bi-directional diode switching characteristic of positive and negative polarities. In the meantime, the second TFD element 40b is formed of the first metal film 42, the oxide film 44, and the second metal film 46b in the order as seen from the side of data line 21, and has a diode switching characteristic opposite to that of the first TFD element 40a. Accordingly, the TFD element 40 has

a symmetrically nonlinear characteristic of current-voltage in the positive and negative polarities as compared to the case of using one diode. Alternatively, when such a nonlinear characteristic is not strictly required to be symmetrical, only one TFD element 40 may be employed.

In addition, the TFD element 40 is one example of the diode element, and a zinc oxide (ZnO) varistor, an element using a metal semi-insulator (MSI) or the like, a single body thereof, a serial connection thereof in a reverse direction, or a parallel connection thereof in a reverse direction may also be employed for the same.

In the liquid crystal display device 1 of the present embodiment, the layer-thickness adjusting film 32 is configured so as to meet the relationship as follows: $dh < dt$, wherein dh denotes the thickness of the liquid crystal layer 12 (nematic liquid crystal layer) corresponding to the reflective display region 13, and dt denotes the thickness of the liquid crystal layer 12 corresponding to the transmissive display region 14.

For example, the thickness dh of the liquid crystal layer 12 of the reflective display region 13 is set to 3.0 μm , and the thickness dt of the liquid crystal layer 12 corresponding to the transmissive display region 14 is set to 5.0 μm . Accordingly, when the birefringence of the liquid crystal molecule is 0.05, the retardation value Δnd of the reflective display region 13 is 150 nm while the retardation value Δnd of the transmissive display region 14 is 250 nm.

In the liquid crystal display device 1 configured as described above, when the reflective display is performed, external light incident from the outside of the device (i.e. the element substrate 20) are used, which are incident on the liquid crystal layer 12 from the element substrate 20 and reflected by the partially reflecting layer 33 (reflective display region 13), which are then transmitted again through the liquid crystal layer 12 and exited from the element substrate 20, thereby performing the color display in the reflecting mode. In this case, the liquid crystal of the liquid crystal layer 12 between the pixel electrode 23 and the counter electrode 36 is controlled in its alignment, so that the bright and dark display is performed.

In addition, in order to perform the transmissive display, light emitted from the backlight 9 are transmitted through the transmissive display region 14 from the counter substrate 30 to be incident on the liquid crystal layer 12, which are exited from the element substrate 20, so that the color display is performed in the transmitting mode. In this case, the liquid crystal of the liquid crystal layer 12 between the pixel electrode 23 and the counter electrode 36 is also controlled in its alignment, so that the bright and dark display is performed.

Accordingly, in the reflecting mode of these display modes, the incident light is transmitted through the liquid crystal layer 12 two times, while the transmitted light emitted from the backlight 9 is transmitted through the liquid crystal layer 12 only one time. Therefore, in consideration of the retardation of the liquid crystal layer 12, this retardation of the liquid crystal layer causes a difference in transmittance of the liquid crystal. However, according to the present embodiment, a predetermined magnitude relation is given to the thickness dh of the liquid crystal layer 12 corresponding to the reflective display region 13 and the thickness dt of the liquid crystal layer 12 corresponding to the transmissive display region 14, so that a retardation value Δnd in the reflective display region 13 is set to be higher than the retardation value Δnd in the transmissive display region 14.

In adjusting the layer thickness as described above, according to the present embodiment, a layer-thickness adjusting layer 35 formed of a photosensitive resin is selectively formed

on an inner surface of the counter substrate **30**, however, it is also possible to selectively etch the surface of the counter substrate **30** to form a concave portion, and to adjust the thickness of the liquid crystal layer **12** in the reflective display region **13** and the thickness of the liquid crystal layer **12** in the transmissive display region **14** by means of the concave portion.

Principle of Compensation of Viewing Angle

Next, the principle of compensating for the viewing angle will be described with reference to FIGS. **6** and **7**. As shown in FIG. **6A**, the liquid crystal molecule **50** of the nematic liquid crystal has a birefringence property, so that the refractive index of the axial direction (x direction) of the liquid crystal molecule **50** is different from that vertical to the direction (y direction). Accordingly, the optical path length of light is different from each other depending on the observation direction of the observer, which leads to a difference in contrast or brightness (that is, the viewing angle dependency is said to be high). This is the fundamental reason why the viewing angle is decreased. Accordingly, in order to improve the viewing angle, it is theoretically preferable to have the same refractive index of the liquid crystal molecule as that of the sphere **52** as schematically shown in FIG. **6B**. That is, when the refractive index is constant while the observer sees the liquid crystal display device in any directions, the viewing angle dependency problem may be overcome.

Accordingly, a viewing angle compensation film is used in a pseudo manner in the present invention to thereby make the refractive index characteristic closer to that of the sphere shown in FIG. **6B**. That is, a liquid crystal film and a polymer film are laminated with respect to the liquid crystal layer **12** of the liquid crystal display device **1**, so that the refractive index characteristic of the whole laminate is made closer to that of the sphere in a three-dimensional manner.

Specifically, a liquid crystal film **54** aligned in a discotic hybrid manner is first used to compensate for the tilt of the liquid crystal layer **12** of the liquid crystal display device **1** as shown in FIG. **7A**. That is, the tilt of the liquid crystal layer **12** is compensated by the discotic liquid crystal constituting the liquid crystal film **54** as shown in FIG. **7B**. In actual, as shown in FIG. **7B**, when the laminated structure of the liquid crystal layer **12** and the liquid crystal film **54** are observed from the side, the tilt direction of the nematic liquid crystal within the liquid crystal layer **12** is made to cross the tilt direction of the discotic liquid crystal within the liquid crystal film **54**, so that the tilt of the liquid crystal layer **12** is compensated.

The discotic liquid crystal constituting the liquid crystal film **54** does not have a refractive index difference within its plane (i.e. $n_x=n_y$), which thus does not have the phase differences generated at all in a z-axis direction. Accordingly, by using a polymer film **59** having a three-dimensional refractive index anisotropy as shown in FIG. **7B**, the phase difference may also be generated in the z-axis direction. As such, the tilt of the liquid crystal layer **12** is compensated by the liquid crystal **54** and the phase difference is generated in the z-axis direction by the polymer film **59**, so that the refractive index may be made closer to that of the sphere by the laminate of the liquid crystal **12**, the liquid crystal film **54**, and the polymer film **59** in a pseudo manner, which allows the viewing angle dependency to be suppressed.

FIRST EMBODIMENT

Next, a first embodiment of the present invention will be described. FIG. **8** is a view for explaining an axial direction and so forth of each optical component used for the liquid crystal display device to which the present invention is

applied. When the liquid crystal display device **1** is configured using the driving liquid crystal cell **10** of the present embodiment, an upper polarizer **2**, upper retardation plates **3a** and **3c**, a driving liquid crystal cell **10**, lower retardation plates **5a** to **5c**, a lower polarizer **7**, and a backlight **9** are arranged to overlap each other in this order downward from the upper side as shown in FIGS. **2** and **8**.

A low dispersion film is used for the upper retardation plates **3a** and **3b** and the lower retardation plate **5c**. In addition, a discotic liquid crystal film as the above-described liquid crystal film **54** is used for the lower retardation plate **5a**. In addition, a polymer film having a three-dimensional refractive index anisotropy as the above-described polymer film **59** is used for the lower retardation plate **5b**.

The axial angle of each member shown in FIG. **8** and a phase difference value obtained by the axial angle are shown in FIG. **11A**. As shown in FIG. **8**, rubbing is performed on the nematic liquid crystal layer **12** in a direction in which a predetermined angle is formed with respect to the three o'clock direction shown as a broken line with respect to the element substrate **20** and the counter substrate **30**, so that the twist angle Ω_{LC} is set to 0° to 70° . Specifically, the rubbing direction of the element substrate **20** (upper substrate) of the liquid crystal cell **10** is set to an angle ϕ_{LCu} in a counterclockwise direction from the reference direction, and the rubbing direction of the counter substrate **30** (lower substrate) is set to an angle ϕ_{LCd} in a counterclockwise direction from the reference direction. As shown in FIG. **11A**, the angle ϕ_{LCu} is in a preferable range of 80° to 130° , and particularly preferably about 90° . In addition, the angle ϕ_{LCd} is in a preferable range of 230° to 270° , and particularly preferably about 270° .

In addition, all angles are indicated in a counterclockwise direction from the reference directions shown as broken lines in the following description.

The polarizer **2** where the absorbing axis **201** has an angle ϕ_{pu} with respect to the reference direction as seen from the top, is employed. The angle ϕ_{pu} is in a preferable range of -80° to 80° , and particularly preferably about 15° .

A low dispersion film where a phase retardation axis **301a** has an angle ϕ_{F1} with respect to the reference direction as seen from the top, is used as the upper retardation plate **3a**. The angle ϕ_{F1} is in a preferable range of -60° to 60° , and particularly preferably about 30° . In addition, the phase difference $RF3a$ due to the lower retardation plate **3a** is in a preferable range of 220 nm to 290 nm , and particularly preferably about 260 nm . The low dispersion film has a lower refractive index when the measured wavelength becomes shorter. In addition, the same configuration is applied to the upper retardation plate **3b** and the lower retardation plate **5c**.

A low dispersion film where a phase retardation axis **301b** has an angle ϕ_{F2} with respect to the reference direction as seen from the top, is used as the upper retardation plate **3b**. The angle ϕ_{F2} is in a preferable range of 45° to 135° , and particularly preferably about 90° . In addition, the phase difference $RF3b$ due to the lower retardation plate **3b** is in a preferable range of 50 nm to 140 nm , and particularly preferably about 90 nm .

A discotic liquid crystal film with hybrid alignment where a hybrid alignment axis **501a** has an angle ϕ_{F3} with respect to the reference direction is used as the lower retardation plate **5a**. The angle ϕ_{F3} is in a preferable range of 85° to 95° , and particularly preferably about 90° . The phase difference $RF5a$ due to the lower retardation plate **5a** is in a preferable range of 10 nm to 40 nm , and particularly preferably about 26 nm .

A polymer film where the phase retardation axis **501b** has an angle ϕ_{F4} with respect to the reference direction is used as the lower retardation plate **5b**. The angle ϕ_{F4} is in a preferable

range of 85° to 95°, and particularly preferably about 90°. The phase difference RF5b due to the lower retardation plate 5b is in a preferable range of 80 nm to 150 nm, and particularly preferably about 130 nm. In addition, the lower retardation plate 5b preferably has a three-dimensional refractive index N_z set as $-0.7 < N_z = (n_x - n_z) / (n_x - n_y) < 0.7$.

A low dispersion film wherein the phase retardation axis 501c has an angle $\phi F5$ with respect to the reference direction is used as the lower retardation plate 5c. The angle $\phi F5$ is in a preferable range of -60° to 60°, and particularly preferably about 150° (= -30°). The phase difference RF5c due to the lower retardation plate 5c is in a preferable range of 220 nm to 290 nm, and particularly preferably about 270 nm.

The lower polarizer 7 is preferably used wherein the absorbing axis 701 has an angle ϕpd with respect to the reference direction. The angle ϕpd is in a preferable range of 45° to 135°, and particularly preferably about 75°.

It was found that the viewing angle characteristic was improved two times or more in the transmitting mode when the display performance was measured with respect to the liquid crystal display device 1 having the above-mentioned configuration. In addition, the color variation due to the viewing angle was reduced, which allowed the contrast to be increased two times or more.

SECOND EMBODIMENT

Next, a third embodiment will be described. FIG. 9 is a view for explaining an axial direction or the like of each optical component using a liquid crystal display device according to the second embodiment. In order to fabricate the liquid crystal display device 1 using the driving liquid crystal cell 10 of the present embodiment, an upper polarizer 2, an upper retardation plate 3c, a driving liquid crystal cell 10, lower retardation plates 5a to 5c, a lower polarizer 7, and a backlight 9 are arranged to overlap each other in this order downward from the upper side as shown in FIG. 9. Compared with the configuration of the first embodiment, the upper retardation plate 3c is used in the second embodiment instead of the upper retardation plates 3a and 3b in the first embodiment. The other configuration is same as that of the first embodiment. That is, the configuration of the upper polarizer 2, the liquid crystal 10, the lower retardation plates 5a to 5c, and the lower polarizer 7 is same as that of the first embodiment, so that its description will be skipped. The axial angle of each member shown in FIG. 9 and a phase difference value obtained therefrom are shown in FIG. 11B.

A retardation plate of a reverse wavelength diffusion type, which shows a lower phase difference value in the shorter wavelength in a measurement wavelength range of 400 nm to 700 nm, is used as the upper retardation plate 3c in the second embodiment. By means of this configuration, the upper retardation plate may be configured with one sheet. A reverse wavelength diffusion film wherein the phase retardation axis 301c has an angle $\phi F6$ with respect to the reference direction as seen from the top, is used as the upper retardation plate 3c. The angle $\phi F6$ is in a preferable range of -60° to 60°, and particularly preferably about 50°. In addition, the phase difference RF3c due to the upper retardation plate 3c is in a preferable range of 100 nm to 200 nm, and particularly preferably about 170 nm.

As such, according to the second embodiment, the lower retardation plate 5a to 5c and the lower polarizer 7 which are disposed below the liquid crystal cell 10 are same as that of the first embodiment, so that the same effect of improving the viewing angle is obtained as the first embodiment. In addition, a reverse wavelength diffusion film is used in the second

embodiment to allow one sheet of the upper retardation plate to be employed, which may lead to the thin liquid crystal display device 1 by its reduced thickness.

THIRD EMBODIMENT

Next, a third embodiment will be described. FIG. 10 is a view for explaining an axial direction or the like of each optical component using a liquid crystal display device according to the third embodiment. In order to fabricate the liquid crystal display device 1 using the driving liquid crystal cell 10 of the present embodiment, an upper polarizer 2, upper retardation plates 3d to 3f, a driving liquid crystal cell 10, lower retardation plates 5a to 5c, a lower polarizer 7, and a backlight 9 are arranged to overlap each other in this order downward from the upper side as shown in FIG. 10. Compared with the configuration of the first embodiment, the upper retardation plates 3d to 3f are used in the third embodiment instead of the upper retardation plates 3a and 3b in the first embodiment. The other configuration is same as that of the first embodiment. That is, the configuration of the upper polarizer 2, the liquid crystal 10, the lower retardation plates 5a to 5c, and the lower polarizer 7 is same as that of the first embodiment, so that its description will be skipped. The axial angle of each member shown in FIG. 10 and a phase difference value obtained therefrom are shown in FIG. 11C.

In the present embodiment, a configuration improving the viewing angle by using a discotic liquid crystal film with hybrid alignment and a polymer film having a three-dimensional refractive index anisotropy, namely, the same configuration as that of the lower retardation plates 5a to 5c is also employed for upper retardation plates. However, the laminating order is symmetric with the liquid crystal cell 10 being a reference. Specifically, the upper retardation plate 3f uses a discotic liquid crystal film with hybrid alignment which is same as that of the lower retardation plate 5a, and the upper retardation plate 3e uses a polymer film having a three-dimensional refractive index anisotropy which is same as that of the lower retardation plate 5b, and the upper retardation plate 3d uses a low dispersion film which is same as that of the upper retardation plate 3d.

A low dispersion film wherein the phase retardation axis 301d has an angle $\phi F7$ with respect to the reference direction is used as the upper retardation plate 3d. The angle $\phi F7$ is in a preferable range of -60° to 60°, and particularly preferably about 30°. The phase difference RF3d due to the upper retardation plate 3d is in a preferable range of 220 nm to 290 nm, and particularly preferably about 265 nm.

A polymer film having the three-dimensional refractive index anisotropy is used as the upper retardation plate 3e wherein the phase retardation axis 301e has an angle $\phi F8$ with respect to the reference direction. The angle $\phi F8$ is in a preferable range of 45° to 135°, and particularly preferably about 90°. The phase difference RF3e due to the upper retardation plate 3e is in a preferable range of 50 nm to 140 nm, and particularly preferably about 130 nm.

A discotic liquid crystal film with hybrid alignment is used as the upper retardation plate 3f wherein the hybrid alignment axis 301f has an angle $\phi F9$ with respect to the reference direction. The angle $\phi F9$ is in a preferable range of 45° to 135°, and particularly preferably about 90°. The phase difference RF3f due to the upper retardation plate 3f is in a preferable range of 10 nm to 40 nm, and particularly preferably about 30 nm.

According to the present embodiment, a combination of the discotic liquid crystal film with hybrid alignment and a polymer film having a three-dimensional refractive index

anisotropy is provided in both of the upper and lower positions of the liquid crystal cell 10, so that the viewing angle characteristic may be further improved in the transmitting mode. Specifically, it was found that the viewing angle characteristic was improved two and a half times or more in the transmitting mode when the display performance was measured with respect to the liquid crystal display device 1 having the above-mentioned configuration. In addition, the color variation due to the viewing angle was reduced, which allowed the contrast to be increased two times or more.

Comparison of Viewing Angle with Conventional Configuration

FIG. 12 shows the viewing angle characteristics of the configuration according to the above-mentioned embodiment and the conventional configuration. FIG. 12A shows the viewing angle characteristic of the liquid crystal display device 1 according to the first embodiment. In addition, FIG. 12B shows the viewing angle characteristic of the liquid crystal display device using the optical compensation film substantially formed of a liquid crystalline polymer representing a positive one axial property optically wherein the liquid crystalline polymer has fixed the nematic hybrid alignment formed in the liquid crystal state.

In addition, referring to FIGS. 12A and 12B, a circle graph representing the viewing angle characteristic has an azimuth angle α in a circumferential direction and an elevation angle β in a radial direction. Specifically, the right (three o'clock) direction of the circle graph is set to a reference direction (i.e. the azimuth angle $\alpha=0$), and the azimuth angle α is indicated in a counterclockwise direction from the reference. The azimuth angle α indicates the angle of deviation in up, down, left and right directions of an observer as shown in FIG. 12C. In addition, the elevation angle β indicates an angle where the line of sight of the observer is formed with respect to the normal line NL of the liquid crystal display device 1 as shown in FIG. 12D. Referring to FIGS. 12A and 12B, the length of the circle in the radial direction indicates the elevation angle β . Specifically, concentric circles denoted by broken lines in the circle graph of FIG. 12A indicate elevation angles corresponding to 20°, 40°, 60°, and 80° from an inner circumferential side of the broken line. In addition, referring back to FIGS. 12A and 12B, a white area has a contrast not less than 10, and a black area has a contrast less than 10. In general, when the viewing angle is evaluated, the contrast of 10 often becomes a reference for determining the visibility as a good state, and the circle graphs shown in FIGS. 12A and 12B are also classified into the white area and the black area by color with the contrast of 10 being a boundary thereof.

As can be seen from the comparison of FIG. 12A and FIG. 12B, the white area spreads toward the outer circumferential side of the circle in the viewing angle characteristic of the liquid crystal display device 1 of the first embodiment shown in FIG. 12A as compared to the viewing angle characteristic of the conventional configuration shown in FIG. 12B. That is, it can be understood that the viewing angle is improved in all directions. Specifically, the contrast becomes 10 or more till the elevation angle of about 40° in almost all directions in the viewing angle characteristic of the conventional configuration shown in FIG. 12B, whereas the contrast is degraded to less than 10 when the elevation angle exceeds 40°. On the contrary, the azimuth is increased which maintains the contrast not less than 10 till the elevation angle of about 50° in the viewing angle characteristic of the first embodiment shown in FIG. 12A. As such, the viewing angle is improved in all directions according to the liquid crystal display device of the present embodiments.

In addition, FIG. 12 shows only the viewing angle characteristic of the liquid crystal display device 1 according to the first embodiment, however, the viewing angle is also improved in the liquid crystal display device according to the second and third embodiments.

OTHER EMBODIMENT

In addition, the TFD element 40 is used as the active element in the above-mentioned embodiments, the present invention may also be applied to the liquid crystal display device using a thin film transistor (TFT) instead of the TFD.

In addition, the liquid crystal is twisted by the alignment film which has been rubbed in the above-mentioned embodiment, however, the liquid crystal may be twisted by other method. For example, the alignment film may be fabricated depositing a silicon oxide or the like on the surface of the substrate obliquely. In addition, after a photo-curable resin is coated on the substrate, the intensity of light may be adjusted in a stripe to use the photo-curable resin layer which has been exposed and cured as an alignment film.

Electronic Apparatus

FIG. 13 is a perspective view illustrating a configuration of a portable telephone as an example of an electronic apparatus to which the liquid crystal display device 1 of the present invention is mounted.

Referring to FIG. 13, a portable telephone 1400 has an earpiece 1404, a mouthpiece 1406, and a liquid crystal display 1 as well as a plurality of operation buttons 1402. A backlight is also mounted on the back of the liquid crystal display 1 if necessary.

In addition to the portable telephone, a mobile computer, a liquid crystal television, a view finder type or monitor direct-view type video tape recorder, a car navigation apparatus, an electronic note, an electronic calculator, a word processor, a workstation, a picture phone, a point-of-sale (POS) terminal, or an apparatus having a touch panel may employed as the electronic apparatus which may mount the liquid crystal display device of the present embodiment.

What is claimed is:

1. A liquid crystal display device comprising:

a lower polarizer;

a lower retardation plate formed above the lower polarizer, the lower retardation plate having a first lower retardation plate made of a discotic liquid crystal film with hybrid alignment and a second lower retardation plate made of a polymer film having a three-dimensional refractive index anisotropy, the second lower retardation plate being disposed below the first lower retardation plate and having a three-dimensional refractive index in a range of -0.7 to 0.7 ;

a liquid crystal cell formed above the lower retardation plate, the liquid crystal cell having a nematic liquid crystal layer, the nematic liquid crystal layer having a twist angle set in a range of 0° to 70° ;

an upper retardation plate formed above the liquid crystal cell; and

an upper polarizer formed above the upper retardation plate,

wherein the user retardation plate has first and second upper retardation plates whose phase retardation axes are different in their direction from each other as seen from the top and which are made of a low dispersion film.

2. The liquid crystal display device according to claim 1, wherein the first lower retardation plate has a hybrid alignment axis in a range of 85° to 95° in a counterclockwise

direction with respect to a reference direction when the first lower retardation plate is seen from the top.

3. The liquid crystal display device according to claim 2, wherein the second lower retardation plate has a phase retardation axis in a range of 85° to 95° in a counterclockwise direction with respect to the reference direction when the second lower retardation plate is seen from the top.

4. The liquid crystal display device according to claim 1, wherein the upper retardation plate has a first upper retardation plate made of a discotic liquid crystal film with hybrid alignment, and a second upper retardation plate made of a polymer film having a three-dimensional refractive index anisotropy, and the second upper retardation plate is disposed above the first upper retardation plate.

5. The liquid crystal display device according to claim 1, wherein the liquid crystal cell is a transmissive liquid crystal cell having a partially reflecting layer, and the thickness of the nematic liquid crystal layer in a reflecting portion corresponding to the partially reflecting layer is smaller than that of the nematic liquid crystal layer in a transmitting portion other than the reflecting portion.

6. An electronic apparatus comprising the liquid crystal display device according to claim 1.

7. A liquid crystal display device comprising:

a lower polarizer;

a lower retardation plate formed above the lower polarizer, the lower retardation plate having a first lower retardation plate made of a discotic liquid crystal film with hybrid alignment and a second lower retardation plate made of a polymer film having a three-dimensional refractive index anisotropy, the second lower retardation plate being disposed below the first lower retardation plate and having a three-dimensional refractive index in a range of -0.7 to 0.7 , the first lower retardation plate having a hybrid alignment axis in a range of 85° to 95° in a counterclockwise direction with respect to a three o'clock direction when the first lower retardation plate is seen from the top, the second lower retardation plate having a phase retardation axis in a range of 85° to 95° in a counterclockwise direction with respect to the three o'clock direction when the second lower retardation plate is seen from the top;

a liquid crystal cell formed above the lower retardation plate, the liquid crystal cell having a nematic liquid crystal layer, the nematic liquid crystal layer having a twist angle set in a range of 0° to 70° , the liquid crystal cell including a first substrate and a second substrate in opposition with each other with the nematic liquid crystal layer disposed therebetween, the nematic liquid crystal layer having a phase difference value $\Delta n d$ from 220nm to 350nm , wherein Δn is a birefringence of the

liquid crystal and d is a thickness of the liquid crystal layer corresponding to a transmissive display region, the absolute value of $\phi_{\text{Lcd}} - 180^\circ - \phi_{\text{Lcu}}$ is 0° to 70° , wherein ϕ_{Lcu} is an angle of rubbing direction of the first substrate with respect to the three o'clock direction, the angle ϕ_{Lcu} being 80° to 130° , and ϕ_{Lcd} is an angle of the rubbing direction of the second substrate with respect to the three o'clock direction;

an upper retardation plate formed above the liquid crystal cell;

an upper polarizer formed above the upper retardation plate,

wherein the upper retardation plate has first and second upper retardation plates whose phase retardation axes are different in their direction from each other as seen from the top and which are made of a low dispersion film; and

a backlight disposed to the outside of the lower polarizer so that the backlight, the lower polarizer, the lower retardation plate, the liquid crystal cell, the upper retardation plate, and the upper polarizer are juxtaposed in this order.

8. The liquid crystal display device according to claim 7, wherein the liquid crystal cell is a transmissive liquid crystal cell having a partially reflecting layer, and the thickness of the nematic liquid crystal layer in a reflecting portion corresponding to the partially reflecting layer is smaller than that of the nematic liquid crystal layer in a transmitting portion other than the reflecting portion.

9. A liquid crystal display device comprising:

a lower polarizer;

a lower retardation plate formed above the lower polarizer, the lower retardation plate having a first lower retardation plate made of a discotic liquid crystal film with hybrid alignment and a second lower retardation plate made of a polymer film having a three-dimensional refractive index anisotropy, the second lower retardation plate being disposed below the first lower retardation plate and having a three-dimensional refractive index in a range of -0.7 to 0.7 ;

a liquid crystal cell formed above the lower retardation plate, the liquid crystal cell having a nematic liquid crystal layer, the nematic liquid crystal layer having a twist angle set in a range of 0° to 70° ;

an upper retardation plate formed above the liquid crystal cell; and an upper polarizer formed above the upper retardation plate,

wherein the upper retardation plate is a single retardation plate made of a reverse wavelength dispersion film.

* * * * *

专利名称(译)	液晶显示装置和电子设备		
公开(公告)号	US7583343	公开(公告)日	2009-09-01
申请号	US11/065749	申请日	2005-02-25
[标]申请(专利权)人(译)	关目智明		
申请(专利权)人(译)	关目智明		
当前申请(专利权)人(译)	京东方科技集团股份有限公司.		
[标]发明人	SEKIME TOMOAKI		
发明人	SEKIME, TOMOAKI		
IPC分类号	G02F1/1335 G02B5/30 G02B27/52 G02F1/1333 G02F1/13363 G02F1/1365		
CPC分类号	G02F1/133632 G02F1/133634 G02F1/133555 G02F2413/105 G02F1/1365 G02F2001/1398		
审查员(译)	内尔姆斯, DAVID		
优先权	2004051667 2004-02-26 JP 2004324748 2004-11-09 JP		
其他公开文献	US20050190328A1		
外部链接	Espacenet USPTO		

摘要(译)

该液晶显示装置包括具有向列液晶层的液晶单元，夹着液晶单元的上和下延迟板，在上延迟板上方的上偏振器，和在下延迟板下方的下偏振器。向列型液晶层设置在上基板和下基板上，扭转角设定在0°至70°的范围内，其相对于参考方向以预定角度进行摩擦处理。下延迟板具有第一下部延迟板，其具有混合排列的盘状液晶膜，以及具有三维折射率各向异性的聚合物膜的第二下延迟板。第二下延迟板的三维折射率设定在-0.7至0.7的范围内。

