



US008009261B2

(12) **United States Patent**  
**Onishi et al.**

(10) **Patent No.:** **US 8,009,261 B2**  
(45) **Date of Patent:** **Aug. 30, 2011**

(54) **LIQUID CRYSTAL DISPLAY DEVICE  
COMPRISING A PLURALITY OF FIRST AND  
SECOND SUPPORTS**

(75) Inventors: **Noriaki Onishi**, Nara (JP); **Naohisa  
Sonku**, Nara (JP); **Yusuke Tsuda**,  
Kizugawa (JP); **Hiroaki Kojima**,  
Kashiba (JP); **Yasunobu Tagusa**, Ikoma  
(JP)

(73) Assignee: **Sharp Kabushiki Kaisha**, Osaka (JP)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 750 days.

(21) Appl. No.: **12/064,678**

(22) PCT Filed: **Jul. 24, 2006**

(86) PCT No.: **PCT/JP2006/314560**

§ 371 (c)(1),  
(2), (4) Date: **Feb. 25, 2008**

(87) PCT Pub. No.: **WO2007/034622**

PCT Pub. Date: **Mar. 29, 2007**

(65) **Prior Publication Data**

US 2009/0244457 A1 Oct. 1, 2009

(30) **Foreign Application Priority Data**

Sep. 22, 2005 (JP) ..... 2005-276610

(51) **Int. Cl.**  
**G02F 1/1339** (2006.01)  
**G02F 1/1335** (2006.01)

(52) **U.S. Cl.** ..... **349/155; 349/114; 349/157**

(58) **Field of Classification Search** ..... **349/155-157**  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

5,643,471	A	7/1997	Onishi et al.	
5,978,061	A	11/1999	Miyazaki et al.	
6,445,437	B1	9/2002	Miyazaki et al.	
6,493,057	B1 *	12/2002	Sato et al.	349/153
6,836,308	B2	12/2004	Sawasaki et al.	
6,888,608	B2	5/2005	Miyazaki et al.	
7,245,345	B2	7/2007	Sawasaki et al.	
7,359,021	B2	4/2008	Ota et al.	
7,649,601	B2 *	1/2010	Ikeda et al.	349/129
2004/0141141	A1	7/2004	Ota et al.	
2005/0116915	A1	6/2005	Nakajima et al.	

(Continued)

**FOREIGN PATENT DOCUMENTS**

CN 1279460 A 1/2001

(Continued)

**OTHER PUBLICATIONS**

Official communication issued in the International Application No.  
PCT/JP2006/314560, mailed on Oct. 10, 2006.

(Continued)

*Primary Examiner* — Mark Robinson


*Assistant Examiner* — Charles Chang

(74) *Attorney, Agent, or Firm* — Keating & Bennett, LLP

(57) **ABSTRACT**

A liquid crystal display device includes a TFT substrate and a CF substrate arranged to face each other and a liquid crystal layer sandwiched therebetween, wherein a plurality of first supports are arranged to extend from one of the substrates to reach the other substrate and a plurality of second supports, which are shorter than the first supports, are arranged to extend from one of the substrates to the other substrate.

**18 Claims, 9 Drawing Sheets**



# US 8,009,261 B2

Page 2

## U.S. PATENT DOCUMENTS

2005/0179853 A1 8/2005 Chen et al.  
2005/0185129 A1 8/2005 Kim et al.  
2005/0200799 A1 9/2005 Murai  
2005/0206812 A1 9/2005 Tsubata  
2005/0237459 A1 10/2005 Ikeda et al.  
2006/0055863 A1 3/2006 Sawasaki et al.  
2007/0103635 A1 5/2007 Tawaraya et al.  
2008/0160871 A1 7/2008 Ota et al.

## FOREIGN PATENT DOCUMENTS

CN 1512216 A 7/2004  
EP 1 067 423 A2 10/2001  
JP 59-9326 U 1/1984  
JP 09-073093 A 3/1997  
JP 2002-341354 A 11/2002  
JP 2003-043501 A 2/2003  
JP 2003-121857 A 4/2003  
JP 2003-195273 A 7/2003

JP 2003-216068 A 7/2003  
JP 2003-270640 A 9/2003  
JP 2003-279936 A 10/2003  
JP 2003-295162 A 10/2003  
JP 2004-005516 A 1/2004  
JP 2004-198847 A 7/2004  
JP 2004-279812 A 10/2004  
JP 2005-049561 A 2/2005  
JP 2005-106856 A 4/2005  
JP 2005-122150 A 5/2005  
JP 2005-165280 A 6/2005  
JP 2005-241856 A 9/2005  
JP 2005-309239 A 11/2005

## OTHER PUBLICATIONS

Onishi et al., "Liquid Crystal Display Device", U.S. Appl. No. 13/040,307, filed on Mar. 4, 2011.

\* cited by examiner



FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14  
PRIOR ART




FIG. 15  
PRIOR ART





FIG. 16  
PRIOR ART



# LIQUID CRYSTAL DISPLAY DEVICE COMPRISING A PLURALITY OF FIRST AND SECOND SUPPORTS

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

The present invention relates to a liquid crystal display device.

### 2. Description of the Related Art

In recent years, liquid crystal display devices have widely been used as flat panel displays for communication tools. This is because the application of the liquid crystal display devices has rapidly been spread in the field of not only OA equipment but also mobile devices due to their enhanced definition, high display quality and increasing lightness and thinness. Under these circumstances, reduction in thickness and weight is still demanded in particular for liquid crystal display panels. A conventional pair of glass substrates of about 1.1 mm in thickness has now been replaced with a pair of glass substrates of about 0.7 mm in thickness. A pair of substrates of smaller thickness has also been considered.

Reduction of the thickness of the glass substrates of the liquid crystal display panel is accompanied by the following drawbacks.

If a pressure higher than a certain level is applied to the surface of the liquid crystal display panel, unevenness in display occurs (stain remains) in a display region. This phenomenon becomes remarkable as the substrate is thinned down. The thinner the substrate is, the more significantly a spacer near the surface which receives a point load is crushed. As a result, a gap between the substrates is reduced near the spacer to a further extent.

For specific explanation of this drawback, as shown in FIG. 14, a pair of glass substrates are arranged to face each other with a plurality of spacers interposed therebetween to leave a gap of 5  $\mu\text{m}$  and a liquid crystal layer is disposed between the substrates. Then, a point load is applied to the middle of one of the substrates. One of the paired substrates is 0.5 mm in thickness, while the thickness of the other substrate is selected from 0.05, 0.1, 0.2, 0.3 and 0.5 mm. As indicated in FIG. 15, the thinner the glass substrate which receives the point load is, the more the glass substrate is warped. Further, as shown in FIG. 16, a 0.05 mm thick glass substrate is warped by 4  $\mu\text{m}$  by a load of only about one-twenty of a load that warps a 0.5 mm thick glass substrate by 4  $\mu\text{m}$ . This indicates that the thinning of the glass substrate easily causes the warpage of the substrate in response to even just a small load.

As a countermeasure against the warpage of the glass substrate, Japanese Unexamined Patent Publication No. 09-073093, discloses a liquid crystal display device including first and second substrates sandwiching liquid crystal therebetween. The first substrate carries a plurality of columnar spacers for leaving a gap between the first and second substrates and a first transparent electrode for applying a voltage to the liquid crystal. The second substrate carries a second transparent electrode for applying a voltage to the liquid crystal. The liquid crystal display device has a peripheral region which does not contribute to the display and a display region enclosed with the peripheral region. As a feature of the liquid crystal display device, the density of the columnar spacers formed on the peripheral region is higher than the density of those formed on the display region. Japanese Unexamined Patent Publication No. 09-073093 describes that this feature reduces display failure due to cell gap failure of the liquid crystal display device.

The technique of Japanese Unexamined Patent Publication No. 09-073093 is directed to restrain the warpage by increasing the number of the spacers to prevent the crush of the spacers and maintain the gap between the substrates. The problem of warpage may possibly be solved by this technique, but another problem of the occurrence of vacuum bubbles in a low temperature environment may arise (bubbles induced by shock at low temperature). At low temperature, the liquid crystal shows particularly significant volumetric shrinkage as compared with other components. Therefore, the spacers cannot follow the shrinkage of the liquid crystal layer and the vacuum bubbles are generated.

Solutions to the problem of the occurrence of bubbles caused by shock at low temperature have been proposed. For example, Japanese Unexamined Patent Publication No. 2002-341354 discloses a liquid crystal display element including liquid crystal sandwiched between two substrates opposing each other with a sealant arranged on the periphery thereof. First columnar spacers are formed on a light blocking region of at least one of the substrates to be in contact with the counter substrate, thereby determining a gap between the substrates. Second columnar spacers are also formed on the same region to have a clearance of 0.2  $\mu\text{m}$  or less between their heads and the counter substrate. With this configuration, the bubbles are not formed by shock at low temperature and unevenness in display caused by a load applied in the production process or an external load is prevented from occurring.

Japanese Unexamined Patent Publication No. 2003-121857 discloses a color filter for a liquid crystal display device provided with columnar spacers including first columnar spacers and second columnar spacers. The first columnar spacers are configured to have a height and a cross-sectional area that make it possible to follow deformation caused by a load applied in a panel assembly process or shrinkage of liquid crystal in a low temperature environment. The second columnar spacers are configured to have a height and a cross-sectional area that make it possible to keep the gap between the substrates even if the liquid crystal is shrunk by a locally applied excessive load or in a low temperature environment. The columnar spacers are adapted to maintain the suitable gap between the substrates in the panel assembly process and are deformed when an excessive load is locally applied or the liquid crystal is shrunk in a low temperature environment, thereby keeping the gap between the substrates uniform. With this configuration, the panel assembly is carried out while keeping the suitable gap. Further, when the excessive load is locally applied or the liquid crystal is shrunk in the low temperature environment, the gap is reduced and kept uniform. Therefore, the liquid crystal display device is achieved without unevenness in color and vacuum bubbles (bubbles formed by shock at low temperature).

According to Japanese Unexamined Patent Publication No. 2002-341354 and Japanese Unexamined Patent Publication No. 2003-121857, a portion that follows the elastic deformation of the gap between the substrates is provided together with the first spacers for keeping the gap between the substrates to prevent the occurrence of bubbles caused by shock at low temperature. Further, the second spacers, which are shorter than the first supports, are provided in parallel with the first spacers. Since a thin liquid crystal display panel is less resistant against a local load and therefore greatly warped, a larger number of spacers must be provided. However, the increase of the first spacers for keeping the gap between the substrates raises the probability of occurrence of bubbles caused by shock at low temperature.

That is, it has been difficult to solve both of the problems involved in the thin liquid crystal display panel such as the

warpage caused by the application of local load and the local occurrence of bubbles caused by shock at low temperature.

### SUMMARY OF THE INVENTION

In order to solve the problems described above, preferred embodiments of the present invention provide a liquid crystal display device that prevents the occurrence of unevenness in display caused by a load applied generally or locally to the display region as well as the occurrence of bubbles induced by shock at low temperature.

A liquid crystal display device according to a preferred embodiment of the present invention includes a first substrate and a second substrate arranged to face each other and a liquid crystal layer sandwiched therebetween, wherein a plurality of first supports are arranged to extend from one of the first and second substrates to reach the other substrate and a plurality of second supports that are shorter than the first supports are arranged to extend from one of the first and second substrates to the other substrate.

With this configuration, the first supports are arranged to extend from one of the first and second substrates to reach the other substrate and the second supports that are shorter than the first supports are arranged to extend from one of the first and second substrates to the other substrate between the first and second substrates of the liquid crystal display device facing each other. Therefore, a load generally applied to the substrate is received by the first and second supports. With the provision of the second supports that are shorter than the first supports, the first and second substrates relatively move to follow the displacement of the liquid crystal layer. Accordingly, the occurrence of bubbles caused by shock at low temperature is prevented.

According to the liquid crystal display device of a preferred embodiment of the present invention, the number of the second supports may be larger than the number of the first supports.

With this configuration, the number of the first supports is minimized and the number of the second supports shorter than the first supports is increased. As a result, when a local load is applied, the first and second substrates follow the displacement of the liquid crystal layer with more flexibility. Therefore, the local occurrence of bubbles caused by shock at low temperature, which has been frequent in such a case, is prevented with high reliability.

According to the liquid crystal display device of a preferred embodiment of the present invention, the second supports may be provided in a display region.

If the second supports are provided in the display region, local display failure in the display region is prevented.

According to the liquid crystal display device of a preferred embodiment of the present invention, the number of the second supports provided in a unit pixel area of the display region may be larger than the number of first supports provided in the same area.

If the number of the second supports provided in the unit pixel area of the display region is larger than the number of the first supports in the same area, local display failure in the display region is prevented with high reliability.

According to the liquid crystal display device of a preferred embodiment of the present invention, the density of the second supports provided in the unit pixel area may be approximately 1.2 or more times the density of the first supports provided in the same area, for example.

The second supports according to a preferred embodiment of the present invention are adapted to prevent the occurrence of bubbles caused by shock at low temperature and to con-

tribute to reduce the unevenness in display caused by pressure applied to the surface of the thinned substrate. From this point of view, the density of the second supports, which is determined by [(the number of the supports/mm<sup>2</sup>)×the cross-sectional area of the supports], is preferably higher than that of the first supports. If the density of the second supports is approximately 1.2 or more times the density of the first supports, for example, the effect of the second supports is exhibited more significantly.

According to the liquid crystal display device of a preferred embodiment of the present invention, the second supports may be arranged in the same pattern in each of the unit pixel areas.

With this configuration, the second supports arranged in the uniform pattern equally receive the load applied locally to the substrate. As a result, the local substrate warpage is effectively prevented and the display function of the liquid crystal display device is made stable and is greatly improved.

According to the liquid crystal display device of a preferred embodiment of the present invention, a gap between the second supports and the opposing substrate may be about 0.05 or more times and about 0.2 or less times the thickness of the liquid crystal layer, for example.

If the gap between the second supports and the opposing substrate is about 0.2 or less times the thickness of the liquid crystal layer, the thin liquid crystal display device effectively prevents the unevenness in display caused by pressure applied to the liquid crystal display panel. Further, if the gap between the second supports and the counter substrate is about 0.05 or more times the thickness of the liquid crystal layer, the occurrence of bubbles caused by shock at low temperature and the occurrence of failed domains are prevented with high effectiveness and efficiency.

According to the liquid crystal display device of a preferred embodiment of the present invention, at least one of the first and second substrates may have a thickness of about 0.5 mm or less, for example.

With this configuration, in the case where the glass substrates have to be thinned down to reduce the thickness or the weight of the panel, the first and second substrates may be designed to have the same thickness or different thicknesses.

According to the liquid crystal display device of a preferred embodiment of the present invention, the first and second supports may have different thicknesses.

With this configuration, the first and second substrates, e.g., a TFT array substrate and a counter substrate, are relatively thinned down. This makes it possible to prevent the TFT array substrate whose thickness has been reduced to a size smaller than the predetermined level from breaking upon local application of heat or pressure to the periphery of the substrate in the process of directly mounting connection terminals and drivers on the TFT array substrate. Further, in the process of forming thin multilayers such as TFT terminals and wires, the TFT array substrate is affected or warped by changes in temperature or pressure. Even in such a case, the reduction of mechanical strength of the thinned TFT array substrate is prevented.

According to the liquid crystal display device of a preferred embodiment of the present invention, each of the unit pixel areas may include a light transmissive region and a light reflective region.

With this configuration, the first and second supports preferably are simultaneously formed in the light transmissive region and the light reflective region higher than the other region by the thickness of a reflective layer. That is, the first

and second supports having different heights are provided efficiently. Therefore, production efficiency of the device is improved.

According to the liquid crystal display device of a preferred embodiment of the present invention, the second supports may be provided in a light blocking region of the display region.

If the second supports are provided in the light blocking region of the display region, leakage of light at the places of the second supports is prevented. Further, if the second supports are provided in the light blocking region in the light reflective region of the pixel, such as a storage capacitor line, the reduction of effective aperture ratio is prevented.

According to the liquid crystal display device of a preferred embodiment of the present invention, the first and second supports may have different cross-sectional areas.

In general, the larger the cross-sectional area of the supports (an area of a cross section taken in the direction perpendicular to the direction of extension of the supports) is, the higher resistance to pressure the glass substrate is likely to have. The supports prevent leakage of light if they are formed at certain positions on the lines. On the other hand, if the supports are designed to have a larger cross-sectional area than the certain level, the display characteristics such as contrast ratio are adversely affected. In particular, in the case of a preferred embodiment of the present invention where a larger number of the second supports than the first supports are provided, the first and second supports having different cross-sectional areas are arranged in asymmetric patterns. Therefore, the reduction of aperture ratio and contrast ratio of the panel is effectively prevented. The first and second supports may be made of the same or different materials in the different processes. However, it is more effective to form the first and second supports at one time by the same photolithography and patterning from the viewpoints of reduction of production process and cost. In this way, the first and second supports may be formed at one time to have different heights and different cross-sectional areas.

According to the liquid crystal display device of a preferred embodiment of the present invention, the cross-sectional area of the second supports may be smaller than the cross-sectional area of the first supports.

If the cross-sectional area of the second supports to be formed at certain positions and certain density with respect to the first supports is designed to be smaller than the cross-sectional area of the first supports, the second supports are provided by the steps of the same number as the conventional steps of providing the first supports for keeping the gap between the substrates.

According to the liquid crystal display device of a preferred embodiment of the present invention, vertical alignment films for vertically aligning liquid crystal molecules when no voltage is applied may be provided on the surfaces of the first and second substrates facing the liquid crystal layer, respectively, and alignment controllers for radially aligning the liquid crystal molecules when a voltage is applied may be provided on at least one of the surfaces of the first and second substrates facing the liquid crystal layer.

With this configuration, in the liquid crystal layer sandwiched between the substrates that are less likely to cause local warpage, the vertical alignment under no application of load and the radial alignment under application of load are not disturbed even if a local load is applied. Therefore, excellent display quality is maintained.

According to the liquid crystal display device of a preferred embodiment of the present invention, the second supports may also function as the alignment controllers.

If the second supports also function as the alignment controllers, the required number of the second supports is reduced. Therefore, the production efficiency of the device is improved.

According to the liquid crystal display device of a preferred embodiment of the present invention, an alignment film subjected to a certain alignment treatment may be provided on at least one of the surfaces of the first and second substrates facing the liquid crystal layer.

With this configuration, in the liquid crystal layer sandwiched between the substrates that are less likely to cause local warpage, the alignment given by the certain alignment treatment is not disturbed even if a local load is applied. Therefore, excellent display quality is maintained.

According to various preferred embodiments of the present invention, as described above, a liquid crystal display device is obtained which prevents the unevenness in display and the occurrence of bubbles caused by shock at low temperature even if a load is applied entirely or locally to the display region.

Other features, elements, processes, steps, characteristics and advantages of the present invention will become more apparent from the following detailed description of preferred embodiments of the present invention with reference to the attached drawings.

#### BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a plan view of a liquid crystal display device according to first preferred embodiment of the present invention.

FIG. 2 is a sectional view of the liquid crystal display device taken along the line II-II of FIG. 1.

FIG. 3 is a plan view of the liquid crystal display device with first supports formed in reflective regions.

FIG. 4 is a sectional view of the liquid crystal display device taken along the line IV-IV of FIG. 3.

FIG. 5 is a sectional view of a liquid crystal display device according to a second preferred embodiment of the present invention.

FIG. 6 is a plan view of a pixel pattern of the liquid crystal display device.

FIG. 7 is a plan view of the pixel pattern of the liquid crystal display device in which second supports are arranged on diagonal lines intersecting at a first support as the center.

FIG. 8 is a plan view of the pixel pattern of the liquid crystal display device in which the second supports are arranged on lines extending laterally and longitudinally from the first support as the center.

FIG. 9 is a plan view of the pixel pattern of the liquid crystal display device in which the second supports are arranged in subpixels, respectively.

FIG. 10 is a graph illustrating the relationship between a load applied to the substrate and the degree of warpage of the substrate.

FIG. 11 is a graph illustrating the relationship between the thickness of a CF glass substrate and the upper limit value of applied pressure that does not cause unevenness in display when the density of the first supports is fixed (about 25 pieces/mm<sup>2</sup>, diameter: about 12 μm).

FIG. 12 is a graph illustrating the relationship between the diameter of the first supports and the upper limit value of applied pressure that does not cause unevenness in display when the CF substrate and the TFT substrate are about 0.05 mm and about 0.5 mm in thickness, respectively.

FIG. 13 is a graph illustrating the relationship between the diameter of the first support and the upper limit value of

applied pressure that does not cause unevenness in display when the CF substrate and the TFT substrate are about 0.1 mm and about 0.5 mm in thickness, respectively.

FIG. 14 is a view illustrating how a point load is applied to the substrate surface.

FIG. 15 is a graph illustrating the relationship between the thickness of the substrate that receives a load and the warpage of the substrate when the load is fixed.

FIG. 16 is a graph illustrating the relationship between a load that warps the substrate by about 4  $\mu\text{m}$  and the thickness of the substrate.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Hereinafter, liquid crystal display devices according to first and second preferred embodiments will be explained in detail with reference to the drawings. The preferred embodiments are not intended to limit the present invention.

First and second preferred embodiments of the present invention are directed to a thin liquid crystal display device used for mobile equipment such as mobile phones.

##### First Preferred Embodiment

##### Structure of Liquid Crystal Display Device 10

FIG. 1 is a plan view illustrating a display surface of a liquid crystal display device 10 and FIG. 2 is a sectional view of the liquid crystal display device 10 taken along a broken line II-II shown in FIG. 1. The liquid crystal display device 10 preferably is a semi-transmissive liquid crystal display device that allows display in both of a transmissive mode and a reflective mode.

The liquid crystal display device 10 includes a TFT substrate 20 and a color filter substrate (CF substrate) 30 arranged to face each other, a liquid crystal layer 40 provided between the substrates and first supports 50, second supports 51 and alignment controllers 52 provided between the opposing substrates 20 and 30.

The TFT substrate 20 includes a glass substrate 21 provided with active elements (not shown) formed on the surface thereof and circuit elements (not shown) such as gate lines and source lines connected to the active elements. A reflective layer 23 having a corrugated surface is formed on a reflective region 22 of a pixel region of the TFT substrate 20 and a transparent insulating layer 24 is formed to cover the reflective layer 23 and planarize the corrugated surface of the reflective layer 23. On the flat surface of the transparent insulating layer 24, transparent pixel electrodes (not shown) and a vertical alignment film 25 are formed in this order.

The pixel electrodes are divided in the form of a plurality of subpixels 31 as shown in FIG. 1 by a cutout portion (not shown) of a predetermined pattern. When a certain voltage is applied to the liquid crystal layer 40, an oblique electric field is generated around the pixel electrode or near the cutout portion and radially aligned liquid crystal domains are formed in the subpixels 31, respectively. As shown in FIG. 1, a unit of four parallel subpixels 31 partitioned by a black matrix 54 described later is referred to as a pixel pattern 49 (unit pixel area). In the present preferred embodiment, a set of four parallel subpixels 31 partitioned by the black matrix 54 is regarded as the pixel pattern 49. However, the number and the arrangement of the subpixels 31 of the pixel pattern 49 may be varied depending on the type of the display device.

The CF substrate 30 includes a glass substrate 32 thinner than the glass substrate 21 of the TFT substrate 20. A CF layer

including red (R), green (G) and blue (B) subpixels 31 and a vertical alignment film 33 are formed on the thin glass substrate 32 in this order. Each of the subpixels 31 is rimmed with a black matrix 54 for obtaining contrast. That is, the black matrix 54 separates the subpixels 31. The R, G and B subpixels 31 may be replaced with those of complementary colors, i.e., cyan, magenta and yellow.

The thickness of the glass substrate 32 of the CF substrate 30 and the thickness of the glass substrate 21 of the TFT substrate 20 are not particularly limited. The glass substrate of the TFT substrate 20 may be thinner than that of the CF substrate 30 or they may have the same thickness.

Each of the first supports 50 is formed to extend from the TFT substrate 20 to reach the CF substrate 30. The first support 50 is formed on the black matrix 54 of the CF substrate 30. The first support 50 is adapted to keep the thickness of the liquid crystal layer 40, i.e., its height defines the thickness of the liquid crystal layer 40. The shape of the first support 50 is not particularly limited. For example, it may be shaped in the form of a cylinder, a prism, a tapered cylinder or a tapered prism. The first support 50 of the present preferred embodiment is preferably made of a resin material. However, the material for the first support is not particularly limited as long as it is resistant to pressure applied to the substrate. For example, the first support may be made of ceramic or metal.

Unlike the present preferred embodiment, the first support 50 may be formed on other light blocking region than the black matrix 54 (e.g., on a storage capacitor line in the display region). As shown in FIGS. 3 and 4, the first support 50 may be formed on a transparent dielectric layer 57. Also in this case, the first support 50 is formed to extend from the transparent dielectric layer 57 to reach the TFT substrate 20.

The alignment controller 52 is formed on a portion of the CF substrate 30 in a transmissive region 26. The alignment controller 52 is formed on the surface of the vertical alignment film 33 facing the liquid crystal layer 40 and shaped into a truncated cone extending toward the TFT substrate 20. The alignment controller 52 is formed in each of the subpixels 31 such that the alignment is stabilized in each of the subpixels 31.

The transparent dielectric layer 57 is formed on a portion of the CF substrate 30 in a reflective region 22. The transparent dielectric layer 57 has a certain thickness and is formed on the surface of the vertical alignment film 33 facing the liquid crystal layer 40. The thickness of the transparent dielectric layer 57 is preferably almost half the thickness of the liquid crystal layer 40. In a reflective display mode, light used for the display passes the liquid crystal layer 40 twice. In the transmissive mode, on the other hand, light used for the display passes the liquid crystal layer 40 only once. Therefore, excellent display is achieved in both of the display modes if the thickness of part of the liquid crystal layer 40 in the transmissive region 26 is preferably about twice the thickness of part of the liquid crystal layer 40 in the reflective region 22.

Each of the second supports 51 is formed on the transparent dielectric layer 57 formed on a portion of the CF substrate 30 in the reflective region 22. Therefore, the first and second supports having different heights can simultaneously be formed with efficiency in the transmissive region 26 and the reflective region 22 higher than the other region due to the presence of the reflective layer 23. The second support 51 of the present preferred embodiment is preferably made of a resin material. However, the material for the second support is not particularly limited as long as it is resistant against pressure applied to the substrate. For example, the second support may be made of ceramic or metal. The second support 51

preferably is in the form of a truncated cone extending toward the TFT substrate **20** and a gap **58** is provided between the head of the second support and the TFT substrate **20**. Therefore, a load applied to the substrate is received by the first and second supports **50** and **51**. Since the second supports are preferably shorter than the first supports **50** and the gap **58** is generated between the heads of the second supports **51** and the TFT substrate **20**, the substrates **20** and **30** are relatively moved to follow the displacement of the liquid crystal layer **40**. As a result, the occurrence of bubbles induced by shock at low temperature is prevented.

If the gap **58**, i.e., a clearance between the head of the second support **51** and the opposing TFT substrate **20**, is about 0.2 or less times the thickness of the liquid crystal layer **40**, for example, unevenness in display caused by pressure applied to a liquid crystal display panel of a thin liquid crystal display device is prevented in an effective manner. Further, if the clearance between the head of the second support **51** and the opposing TFT substrate **20** is about 0.05 or more times the thickness of the liquid crystal layer **40**, for example, the occurrence of bubbles caused by shock at low temperature and the occurrence of failed domains are effectively prevented.

Since the second support **51** is formed in the display region, display failure is prevented from occurring locally in the display region. However, the second support **51** may be formed in other region than the display region, e.g., on the black matrix **54**. The second support **51** may also be formed on a light blocking region in the display region such that leakage of light at the location of the second support **51** is prevented. If the second support is formed on the light blocking region such as a storage capacity line in the reflective region **22**, the effective aperture ratio is less likely to decrease.

The second support **51** is provided in each of the subpixels **31**. Therefore, the number of the second supports **51** is larger than the number of the first supports **50** formed on the black matrix **54** in correspondence with every other subpixel **31**. With this configuration, the number of the first supports **50** is minimized and the number of the second supports **51** shorter than the first supports **50** is increased. As a result, when a local load is applied, the substrates **20** and **30** are allowed to follow the displacement of the liquid crystal layer **40** with more flexibility. Therefore, the local occurrence of bubbles caused by shock at low temperature that has been frequent in such a case is prevented with high reliability. The second supports **51** preferably are arranged in the same pattern in each of the subpixels **31**. To be more specific, as shown in FIG. 1, every second support **51** is provided on the transparent dielectric layer **57** to be positioned substantially in the middle of the reflective region **22** in the subpixel **31**. Therefore, when a local load is applied to the substrate, the uniformly aligned second supports **51** equally receive the load. As a result, local warpage of the substrate is effectively prevented and the display function of the liquid crystal display device **10** is stabilized and improved to a higher degree.

The arrangement of the second supports **51** is not limited. The density of the second supports **51** may be about 1.2 or more times the density of the first supports **50**. The second supports **51** of the present preferred embodiment make it possible to prevent the occurrence of bubbles induced by shock at low temperature and contribute to reduce unevenness in display caused by pressure applied to the substrate of reduced thickness. From this aspect, the density of the second supports, which is determined by [(the number of the supports/mm<sup>2</sup>)×the cross-sectional area of the supports], is preferably higher than the density of the first supports, more

preferably about 1.2 or more times the density of the first supports to exhibit the above-described effects to a higher degree.

According to the present preferred embodiment, the supports are arranged such that the density of the second supports **51** is about 1.2 or more times the density of the first supports **50**. For example, one or more first supports **50** and **51** are preferably provided in a display unit, i.e., a picture element (consists of a set of R, G and B pixels). From the aspect of preventing the occurrence of bubbles caused by shock at low temperature, it is difficult to provide three or more first supports **50** for keeping the gap to be filled with the liquid crystal in a single picture element. If the first support **50** is subjected to an alignment treatment such as rubbing, the alignment may be disturbed near the support and display quality may possibly be decreased, e.g., light leakage may occur. Therefore, for example, it is preferable to provide the first support adjacent to the B (blue) pixel having relatively low luminosity. In particular, in a normally black mode liquid crystal display device which makes use of vertical alignment just like the device of the present preferred embodiment, it is also effective to provide the second support not only on a certain signal line outside the effective display region but also in a portion of the display region in substantially the middle of an alignment axis, for example.

Each of the second supports **51** makes use of its shape to stabilize the alignment of the liquid crystal layer **40** in each of the subpixels **31**. The center of the alignment is fixed to substantially the middle of the reflective region **22** of the subpixel **31** such that the liquid crystal molecules aligned in the radial directions are almost uniformly dispersed. Thus, uniform display is achieved. In this way, the second support **51** also serves as an alignment controller in the reflective region **22**. Therefore, the number of required second supports **51** or alignment controllers is reduced and the production efficiency of the device is improved.

In the present preferred embodiment, the first and second supports **50** and **51** are formed on the CF substrate **30**. However, they may be formed on the TFT substrate **20** or separately formed on different substrates.

## Second Preferred Embodiment

### Structure of Liquid Crystal Display Device **60**

A liquid crystal display device **60** according to a second preferred embodiment of the present invention will be explained with reference to the drawings.

FIG. 5 shows the liquid crystal display device **60**. The liquid crystal display device **60** preferably is a twisted nematic (TN) liquid crystal display device in which the opposing substrates have been subjected to an alignment treatment, respectively.

The liquid crystal display device **60** includes a TFT substrate **70** and a color filter substrate (CF substrate) **80** arranged to face each other, a liquid crystal layer **90** sandwiched therebetween and first supports **100** and second supports **101** arranged between the opposing substrates **70** and **80**.

The TFT substrate **70** includes a glass substrate **71**, switching elements **72** including signal lines and scanning lines formed on the glass substrate **71** and pixel electrodes **73**. An alignment film **75** is formed to cover their surfaces facing the liquid crystal layer **90**. The alignment film **75** has been subjected to an alignment treatment.

The CF substrate **80** includes a glass substrate **81** thinner than the glass substrate **71** of the TFT substrate **70** and a CF layer **82** including red (R), green (G) and blue (B) subpixels

**84** formed on the glass substrate **81**. Each of the subpixels **84** is rimmed with a black matrix **91** for obtaining contrast. That is, the black matrix **91** separates the subpixels **84** as shown in FIG. 6. The R, G and B subpixels **84** may be replaced with those of complementary colors, i.e., cyan, magenta and yellow. As shown in FIG. 6, in the CF layer **82**, a unit pixel area including six subpixels **84** arranged in a 2×3 matrix pattern is referred to as a pixel pattern **85**. The pixel pattern **85** is varied depending on the size of the liquid crystal display device **60**. For example, the pixel pattern **85** including six subpixels **84** according to the present preferred embodiment may be replaced with a pixel pattern including nine subpixels arranged in a 3×3 matrix pattern.

The CF substrate **80** further carries a transparent electrode **86** on the surface of the CF layer **82** facing the liquid crystal layer **90**. An alignment film **87** having a surface that has gone through an alignment treatment is formed on the surface of the transparent electrode **86** facing the liquid crystal layer **90**. The alignment film **87** has been subjected to an alignment treatment such that it has an alignment direction perpendicular to the alignment direction given to the alignment film **75** formed on the TFT substrate **70**.

The thickness of the glass substrate **81** of the CF substrate **80** and the thickness of the glass substrate **71** of the TFT substrate **70** are not particularly limited. The glass substrate of the TFT substrate **70** may be thinner than that of the CF substrate **80** or they may have the same thickness.

Each of the first supports **100** is formed to extend from the TFT substrate **70** to reach the CF substrate **80**. The first support **100** is formed on the black matrix **91** of the CF substrate **80**. The first support **100** is adapted to keep the thickness of the liquid crystal layer **90**, i.e., its height defines the thickness of the liquid crystal layer **90**. The shape of the first support **100** is not particularly limited. For example, it may be shaped in the form of a cylinder, a prism, a tapered cylinder or a tapered prism. The first support **100** of the present preferred embodiment is preferably made of a resin material. However, the material for the first support is not particularly limited as long as it is resistant to pressure applied to the substrate. For example, the first support may be made of ceramic or metal.

Unlike the present preferred embodiment, the first support **100** may be formed on other light blocking region than the black matrix **91** (e.g., on a storage capacitor line in the display region).

Each of the second supports **101** is formed on the black matrix **91** of the CF layer **82**. The second support **101** preferably has a truncated cone shape extending toward the opposing TFT substrate **70** and a gap **58** is generated between the head of the second support and the TFT substrate **70**. Therefore, when a load is applied to the substrate, the first and second supports **100** and **101** bear the load. Since the second support is shorter than the first support **100** and the gap **58** is formed between the head of the second support **101** and the TFT substrate **70**, the substrates **70** and **80** are relatively moved to follow the displacement of the liquid crystal layer **90**. As a result, the occurrence of bubbles induced by shock at low temperature is prevented.

If the gap **58**, i.e., a clearance between the head of the second support **101** and the opposing TFT substrate **70**, is about 0.2 or less times the thickness of the liquid crystal layer **90**, unevenness in display caused by pressure applied to a liquid crystal display panel of a thin liquid crystal display device is prevented in an effective manner. Further, if the clearance between the head of the second support **101** and the opposing TFT substrate **70** is about 0.05 or more times the thickness of the liquid crystal layer **90**, the occurrence of

bubbles caused by shock at low temperature and the occurrence of failed domains are efficiently prevented.

The second support **101** of the present preferred embodiment is preferably made of a resin material. However, the material for the second support is not particularly limited as long as it is resistant to pressure applied to the substrate. For example, the second support may be made of ceramic or metal.

As shown in FIG. 6, eight second supports **101**, for example, are preferably arranged on the black matrix **91** dividing the subpixels **84** in a uniform pattern with the first support **100** as the center of them. That is, the number of the second supports **101** is preferably larger than the number of the first supports **100**. In this way, the number of the first supports **100** is minimized and the number of the second supports **101** shorter than the first supports is increased such that the substrates **70** and **80** are allowed to follow the displacement of the liquid crystal layer **90** with more flexibility when a local load is applied. Therefore, the local occurrence of bubbles caused by shock at low temperature that has been frequent in such a case is prevented with high reliability. The second supports **101** are preferably arranged in the same pattern in each of the pixel patterns **85**. To be more specific, just like the eight second supports **101** arranged in the pixel pattern **85** including six subpixels **84** shown in FIG. 6, eight second supports are arranged to surround the first support **100** in the other pixel patterns **85** of the liquid crystal display device **60**. Therefore, a local load applied to the substrate is equally received by the second supports **101** arranged in a uniform pattern. As a result, local warpage of the substrate is effectively prevented and the display function of the liquid crystal display device **60** is stabilized and improved to a higher degree.

The arrangement of the second supports **101** is not limited to the above. As shown in FIG. 7, four second supports may be arranged on four portions of the black matrix **91** in the pixel pattern **85** corresponding to diagonal lines intersecting at the first support **100**. As shown in FIG. 8, four second supports may be arranged on four portions of the black matrix **91** in the pixel pattern **85** corresponding to lines extending longitudinally and laterally from the first support **100**. Further, as shown in FIG. 9, six second supports may be arranged on storage capacity lines (not shown) positioned in the middle of the subpixels **84**, respectively.

The density of the second supports **101** may be about 1.2 or more times the density of the first supports **100**. The second supports **101** of the present preferred embodiment make it possible to prevent the occurrence of bubbles induced by shock at low temperature and contribute to reduce unevenness in display caused by pressure applied to the substrate of reduced thickness. From this aspect, the density of the second supports, which is determined by [(the number of supports/mm<sup>2</sup>)×the cross-sectional area of the supports], is preferably higher than that of the first supports, more preferably about 1.2 or more times the density of the first supports to exhibit the above-described effects to a higher degree.

According to the present preferred embodiment, the supports are arranged such that the density of the second supports **101** is about 1.2 or more times the density of the first supports **100**. For example, as shown in FIGS. 6 to 9, one or more first and second supports **100** and **101** are preferably provided in a display unit, i.e., a picture element (consists of a set of R, G, and B pixels). From the aspect of preventing the occurrence of bubbles caused by shock at low temperature, it is difficult to provide three or more first supports **100** for keeping the gap to be filled with the liquid crystal in a single picture element. If the first support **100** is subjected to an alignment treatment

such as rubbing, the alignment may be disturbed near the support and display quality may possibly be decreased, e.g., light leakage may occur. Therefore, for example, it is preferable to provide the first support adjacent to the B (blue) pixel having relatively low luminosity.

In the present preferred embodiment, the first and second supports **100** and **101** are formed on the CF substrate **80**. However, they may be formed on the TFT substrate **70** or separately formed on different substrates.

The present preferred embodiment is preferably directed to the TN liquid crystal display device **60**. However, it is not limitative and a super twisted nematic liquid crystal display device or an electrically controlled birefringence (ECB) liquid crystal display device may be used as the liquid crystal display device **60**.

In the first and second preferred embodiments, it is particularly effective to provide the supports at certain locations in the panel by photolithography. The supports may be made of material which shows excellent resolution and development properties in the patterning process and is mechanically strong, less polluting and highly transparent to liquid crystal.

To be more specific, a negative photosensitive material which cures as it is exposed to light and a positive photosensitive material in which a bond is released by exposure to light and selective dissolution proceeds in the development process are available. For example, from the viewpoint of maintaining transparency and mechanical strength, a photosensitive resin based on acrylate, urethane acrylate, epoxy acrylate or methacrylate is preferably used for the patterning.

EXAMPLES

Inspection of the liquid crystal display devices according to preferred embodiments of the present invention was made to examine the influence of various loads on display function of the devices.

Evaluation Test 1

An evaluation test was performed on liquid crystal display devices configured according to the first preferred embodiment to examine the relationship among the thicknesses of the substrates, the densities of the first and second supports and unevenness in display due to load applied to the display device.

Liquid Crystal Display Device for Evaluation Test

Liquid crystal display devices were prepared each including a combination of a 0.5 mm thick first substrate and a 0.05 mm thick second substrate or a combination of a 0.5 mm first substrate and a 0.1 mm thick second substrate and first and second supports each arranged at a predetermined density (pieces per unit area) and having a predetermined cross-sectional area (diameter). A pair of certain polarizers were bonded to the outer surfaces of the substrates of the liquid crystal display panel.

Evaluation Method

For evaluation of unevenness in display caused by pressure, a load application test was performed on the liquid crystal display devices for evaluation using Instron Universal Testing Machine model 5543.

First, the liquid crystal display device was placed on a cylindrical table with the CF substrate facing upward.

Then, a load was applied to the surface of the CF substrate of the liquid crystal display device at the rate of 1 mm/min using a cylindrical pressing jig as shown in FIG. **11**. Three kinds of cylindrical pressing jigs of the Instron Universal Testing Machine were used for the test.

Cylindrical rubber jig: a 10 mm diameter brass rod with a rubber film attached to the end (means to apply most ideal surface load)

Cylindrical jig: a 10 mm diameter brass rod without a rubber film at the end (means to simulate the case where the display device is likely to be damaged by a local load which is often applied in a durability test for a display device assembled into a cell phone)

Spherical jig: a 10 mm diameter brass rod with a spherical end (R5) not covered with a rubber film (means to simulate the case where the display is likely to be damaged by a load applied to a smaller area, e.g., the case where a load is applied by something pointed or the case where a cell-phone strap or the like is sandwiched in a clamshell phone)

When the pressing load was increased up to a predetermined value, the cylindrical pressing jig of the Instron Universal Testing Machine was maintained for 5 seconds. Then, the load on the substrate was withdrawn at the rate of 1 mm/min.

In this manner, the load application test was carried out at several portions of the substrate surface.

After a lapse of 5 minutes from the load application test, the liquid crystal display devices showing a white image and a halftone image on the entire screen were visually checked in the direction perpendicular to the panel (substrate) surface and in directions tilted about 45° from the perpendicular direction as to the presence of unevenness and the degree of the unevenness, if any.

Evaluation Results

Table 1 shows the results of the load application test for examining the unevenness in display caused by pressure. In Table 1, symbol © indicates that excellent results were obtained in all the tests using the cylindrical rubber jig, the cylindrical jig and the spherical jig. Likewise, symbol ○ indicates that the results of two of the tests were excellent, symbol Δ indicates that the results of one of the tests were excellent and symbol x indicates that excellent results were not obtained in all the tests.

TABLE 1

Structure of 1 <sup>st</sup> support	Density	Piece/mm <sup>2</sup>	25	25	25	25	25	25	25	50
	Area	Diameter (μm)	12	17	21	24	12	17	12	12
		Multiple	1	2	3	4	1	2	1	1
Structure of 2 <sup>nd</sup> support	Density	Piece/mm <sup>2</sup>	125	125	125	125	50	100	125	100
	Area	Diameter (μm)	5	5	5	5	2	4	5	4
		Multiple	6	6	6	6	6	6	12	6
Ratio of density of support (2 <sup>nd</sup> /1 <sup>st</sup> )			0.5	0.5	0.5	0.5	0.5	0.5	1	0.5
Substrate thickness			2.5	1.25	0.83	0.63	1	1	5	1
							0.5/0.05			

TABLE 1-continued

(1 <sup>st</sup> /2 <sup>nd</sup> ) (mm)										
Pressure test for examining unevenness in display/	(1) Cylindrical rubber jig	Result (kgf)	16	28	40	50	11	18	18	20
		Result (N)	157	274	392	490	108	176	176	196
		Judgment	○	○	○	○	X	○	○	○
Load capacity: kgf(N)	(2) Cylindrical jig	Result (kgf)	10	16	20	24	7	9	13	15
		Result (N)	98	157	196	235	69	88	127	147
		Judgment	○	○	○	○	X	X	○	○
	(3) Spherical jig	Result (kgf)	10	16	18	20	6	7	12	14
		Result (N)	98	157	176	196	59	69	118	137
		Judgment	○	○	○	○	X	X	○	○
General judgment			◎	◎	◎	◎	X	△	◎	◎
Test for occurrence of bubbles caused by shock at low temperature (-30° C.)			○	○	○	○	○	○	○	△
Structure of 1 <sup>st</sup> support	Density	Piece/mm <sup>2</sup>	75	25	25	25	25	25	25	25
		Multiple	3	1	1	1	1	1	1	1
		Diameter (μm)	12	12	17	21	24	24	12	12
Structure of 2 <sup>nd</sup> support	Density	Piece/mm <sup>2</sup>	75	125	125	125	125	50	75	
		Multiple	3	5	5	5	5	2	3	
		Diameter (μm)	6	6	6	6	6	6	6	
		Multiple	0.5	0.5	0.5	0.5	0.5	0.5	0.5	
Ratio of density of support (2 <sup>nd</sup> /1 <sup>st</sup> )			0.5	2.5	1.25	0.83	0.63	1	1.5	
Substrate thickness (1 <sup>st</sup> /2 <sup>nd</sup> ) (mm)			0.5/0.05			0.5/0.1				
Pressure test for examining unevenness in display/	(1) Cylindrical rubber jig	Result (kgf)	25	18	28	40	52	14	15	
		Result (N)	245	176	274	392	510	137	147	
		Judgment	○	○	○	○	○	X	○	
Load capacity: kgf(N)	(2) Cylindrical jig	Result (kgf)	18	10	18	24	28	9	10	
		Result (N)	176	98	176	235	274	88	98	
		Judgment	○	○	○	○	○	X	○	
	(3) Spherical jig	Result (kgf)	17	10	16	18	20	8	8	
		Result (N)	167	98	157	176	196	78	78	
		Judgment	○	○	○	○	○	○	○	
General judgment			◎	◎	◎	◎	◎	△	◎	
Test for occurrence of bubbles caused by shock at low temperature (-30° C.)			X	○	○	○	○	○	○	

(Standard support structure) 1<sup>st</sup> support; density: 25 pieces/mm<sup>2</sup>, area (diameter): 12 μm 2<sup>nd</sup> support; density: 25 pieces/mm<sup>2</sup>, area (diameter): 12 μm  
 (Target value of load capacity in pressure test) (1) Cylindrical rubber jig: ≥15 kgf (147N), (2) Cylindrical jig: ≥10 kgf (98N), (3) Spherical jig: ≥8 kgf (78N)  
 General judgment . . . ◎: Excellent with 3 jigs, ○: Excellent with 2 of 3 jigs, △: Excellent with 1 of 3 jigs, X: Poor with all jigs  
 (Test for occurrence of bubbles caused by shock at low temperature) ○: No display failure, △: Some panels caused display failure, X: All panels caused display failure

For explanation of the principle of the occurrence of unevenness in display caused by pressure, FIG. 10 shows a graph illustrating the deformation of the support when a load is applied to the support itself or a local area.

In the first process, the support is pressed at the rate of 1 mm/min. In the second process, the support is kept pressed for 5 seconds at a given maximum load. In the third process, the load is withdrawn at the rate of 1 mm/min. Then, in the fourth process, the deformation of the support was shifted to elastic deformation to plastic deformation (a), i.e., the support was no longer able to return to the original state.

When load A which is below the limit is applied, the degree of plastic deformation (α) is almost 0 even after the load is withdrawn. However, when load Amax exceeding the limit is applied, the support shows plastic deformation (α). Due to the plastic deformation (α) of the support, the thickness of the cell is locally changed. This is considered as a main cause of the unevenness in display caused by pressure.

Table 1 indicates that most of the liquid crystal display devices showed excellent results in the pressure test. In these liquid crystal display devices, substrates not thicker than 0.5 mm were used. Accordingly, it is indicated that excellent effect was obtained on the thin liquid crystal display devices in which the first or the second substrate is at least 0.5 mm or less in thickness. Referring to the results shown in Table 1, display failure was observed in two of the liquid crystal dis-

play devices in which the density ratio between the first and second supports, which is determined by [(the density of the second supports×the diameter of the traverse plane of the second supports)/(the density of the first supports×the diameter of the traverse plane of the first supports)], was 1. That is, if the density ratio between the supports is about 1.2 or more, the display device prevents the unevenness in display caused by pressure with high reliability.

FIG. 11 shows the upper limit value of the pressure below which the unevenness in display was not observed. In this examination, the density of the first supports was fixed (25 pieces/mm<sup>2</sup>, diameter: 12 μm) and the pressure was applied using a rod with a spherical end in view of local deformation. Particularly when the substrate thickness was small, the provision of the second supports in addition to the first supports exhibited significant effect.

FIGS. 12 and 13 are graphs illustrating the relationship between the diameter of the first supports and the upper limit value of the pressure below which the unevenness in display was not observed. In this examination, the substrates of 0.05/0.5 mm or 0.1/0.5 mm in thickness were used and the pressure was applied using a rod with a spherical end in view of local deformation.

The larger the diameter of the first supports is, i.e., the larger the cross-sectional area is, the more excellent resistance to pressure is exhibited. However, when the supports

having a larger diameter are formed by patterning, the effective aperture ratio may possibly be decreased in connection with the width of bus lines (light blocking portions). That is, from the viewpoint of design rule, the diameter of the supports is preferably 20 μm or less in order to provide the supports on the bus lines. If the supports with a larger diameter are provided, it is difficult to prevent leakage of light from the vicinity of the supports and the contrast ratio of the display is greatly reduced. Further, the aperture ratio is also reduced significantly and the transmittance of the panel may possibly be reduced. It is also confirmed that the effective aperture ratio is reduced by about 10% or more when the ratio of the density of the second supports, which is determined by [(the number of the supports/mm<sup>2</sup>)×the cross-sectional area of the supports] to the density of the first supports is more than 10. Evaluation Test 2

An evaluation test was performed on liquid crystal display devices configured according to the first preferred embodiment to examine the relationship among the thicknesses of the substrates, the densities of the first and second supports and the occurrence of bubbles caused by shock at low temperature.

Liquid Crystal Display Device for Evaluation

Liquid crystal display devices were prepared each including a combination of a 0.5 mm thick first substrate and a 0.05 mm thick second substrate or a combination of a 0.5 mm first substrate and a 0.1 mm thick second substrate and first and second supports each arranged at a predetermined density (pieces per unit area) and having a predetermined cross-sectional area (diameter). A pair of certain polarizers were bonded to the outer surfaces of the substrates of the liquid crystal display panel.

Evaluation Method

A test was performed on the liquid crystal display devices for evaluation to examine the occurrence of bubbles induced by shock at low temperature.

First, each of the liquid crystal display devices was left stand in a thermostat in an environment of -30° C. for 3 hours. Then, a pachinko ball was free-dropped onto the surface of the CF substrate from a height of 10 cm.

The liquid crystal display device was taken out of the thermostat and visually and microscopically checked as to the presence of unevenness in display due to bubbles and the degree of unevenness, if any, using a panel lighting device.

Evaluation Results

The results of the test for the occurrence of bubbles caused by load application at low temperature are shown in Table 1. Symbol ○ shown in Table 1 indicates that display failure was not observed and Δ indicates that some of the display panels showed display failure.

As shown in Table 1, display failure due to the occurrence of bubbles caused by shock at low temperature was observed in one of the liquid crystal display devices in which the density ratio between the first and second supports [(the density of the second supports×the diameter of the traverse plane of the second supports)/(the density of the first supports×the diameter of the traverse plane of the first supports)] was 1 or less. On the other hand, sufficiently excellent results were exhibited by the liquid crystal display devices in which the density ratio is higher than 1, such as 1.25 closest to 1. Therefore, if the density ratio between the first and second supports is 1.2 or more, the liquid crystal display device shows particularly excellent characteristic of preventing the occurrence of bubbles caused by shock at low temperature.

Evaluation Test 3

The tests for examining the unevenness in display caused by pressure and the occurrence of bubbles caused by shock at low temperature were performed on the liquid crystal display devices for evaluation in the same manner as described above. The gap between the second supports and the counter substrate was varied to examine the influence of the relationship between the gap and the thickness of the liquid crystal layer on the unevenness in display and the occurrence of bubbles.

Liquid Crystal Display Device for Examination

The liquid crystal display devices used were configured to have different gaps between the second supports and the counter substrate.

Test conditions were as follows. The first and second substrates were 0.5/0.05 mm in thickness, respectively. The density and the diameter of the first supports were 25 pieces/mm<sup>2</sup> and 17 μm. The density and the diameter of the second supports were 125 pieces/mm<sup>2</sup> and 6 μm.

Evaluation Result

Evaluation results are shown in Table 2. According to Table 2, the liquid crystal display devices in which the gap between the second supports and the counter substrate was 0.06 to 0.19 times the thickness of the liquid crystal layer (3.40 μm), as well as those in which the gap was 0.10 to 0.20 times the thickness of the liquid crystal layer (5.10 μm), were judged excellent as to prevention of the display failure caused by pressure and prevention of the occurrence of bubbles caused by shock at low temperature. The results indicate that if the gap between the second supports and the counter substrate is 0.05 or more times and 0.20 or less times the thickness of the liquid crystal layer, the unevenness in display caused by pressure and the occurrence of bubbles caused by shock at low temperature are effectively prevented.

TABLE 2

			3.40					5.10			
Structure of 2 <sup>nd</sup> support	(1) Thickness of liquid crystal layer (μm)		0.80	0.65	0.40	0.20	0.15	1.10	1.00	0.50	0.20
	(2) Gap from the counter substrate (μm)										
	Gap ratio ((2)/(1))		0.24	0.19	0.12	0.06	0.04	0.22	0.20	0.10	0.04
Pressure test for examining unevenness in display/	Cylindrical	Result (kgf)	16	19	28	31	32	15	16	25	28
	rubber	Result (N)	157	186	274	304	314	147	157	245	274
Load capacity: kgf(N)	jig	Judgment	○	○	○	○	○	○	○	○	○
	Cylindrical	Result (kgf)	9	10	16	18	20	9	12	17	19
	jig	Result (N)	88	98	157	176	196	88	118	167	186
		Judgment	X	○	○	○	○	X	○	○	○
	Spherical	Result (kgf)	7	8	16	18	19	6	10	14	16
	jig	Result (N)	69	78	157	176	186	59	98	137	157
		Judgment	X	○	○	○	○	X	○	○	○
	General judgment		Δ	⊗	⊗	⊗	⊗	Δ	⊗	⊗	⊗
Test for occurrence of bubbles caused by shock at low temperature (-30° C.)			○	○	○	○	X	○	○	○	Δ

TABLE 2-continued

(Pressure test for examining unevenness in display) Target value . . . Cylindrical rubber jig:  $\geq 15$  kgf (147N), Cylindrical jig:  $\geq 10$  kgf (98N), Spherical jig:  $\geq 8$  kgf (78N)  
 General judgment . . . ◎: Excellent with 3 jigs, ○: Excellent with 2 of 3 jigs, Δ: Excellent with 1 of 3 jigs, X: Poor with all jigs  
 (Test for occurrence of bubble by shock at low temperature) ○: No display failure, Δ: Some panels caused display failure, X: All panels caused display failure  
 Test conditions . . . 1<sup>st</sup>/2<sup>nd</sup> substrate thickness: 0.5/0.05 (mm), 1<sup>st</sup> support: 25 pieces/mm<sup>2</sup>, 17 μm in diameter, 2<sup>nd</sup> support: 125 pieces/mm<sup>2</sup>, 6 μm in diameter

Evaluation Test 4

In order to prevent the occurrence of local stains caused by pressure (display failure) and the occurrence of bubbles caused by shock at low temperature that have been unsolved problems involved in the liquid crystal display device having a thinned substrate, it is also effective to optimize the structure and density of the first supports (cross-sectional shape and area) for controlling the gap between the substrates.

Evaluation Results

Table 3 shows the results. The results indicate that the optimization of the single kind of supports (the supports for keeping the gap between the substrates) makes it possible to solve the problem of panel strength to a certain degree. In this regard, the above-described problem seems to be solved to a certain degree by optimizing the density and cross-sectional area of the supports.

TABLE 3

Structure of support	Density	Piece/mm <sup>2</sup>	25	50	75	150	25	25	25	25	25	25
	Area	Diameter (μm)	12	12	12	12	17	21	24	12	12	12
Substrate thickness (1 <sup>st</sup> /2 <sup>nd</sup> ) (mm)		Multiple	1	1	1	1	2	3	4	1	1	1
			0.5/0.05						0.5/0.1			
Pressure test for examining unevenness in display/Load capacity: kgf(N)	(1)	Result (kgf)	10	16	24	42	16	28	36	10	16	16
	Cylindrical rubber jig	Result (N)	98	157	235	412	157	274	353	98	157	157
unevenness in display/Load capacity: kgf(N)	(2)	Result (kgf)	2	4	8	16	4	14	20	6	6	6
	Cylindrical jig	Result (N)	20	39	78	157	39	137	196	59	59	59
(3)	Spherical jig	Result (kgf)	2	2	4	10	4	12	16	6	6	6
	Spherical jig	Result (N)	20	20	39	98	39	118	157	59	59	59
General judgment		Judgment	X	X	X	○	X	○	○	X	X	X
		General judgment	X	X	X	○	X	○	○	X	X	X
Test for occurrence of bubbles caused by shock at low temperature (-30° C.)			○	Δ	X	X	○	X	X	○	Δ	Δ
Structure of support	Density	Piece/mm	75	150	25	25	25	25	25	25	25	25
	Area	Diameter (μm)	12	12	17	21	24	12	12	12	12	12
Substrate thickness (1 <sup>st</sup> /2 <sup>nd</sup> ) (mm)		Multiple	3	6	1	1	1	1	1	1	1	1
			12	12	17	21	24	12	12	12	12	12
Pressure test for examining unevenness in display/Load capacity: kgf(N)	(1)	Result (kgf)	28	45	18	30	40	12	12	12	16	16
	Cylindrical rubber jig	Result (N)	274	441	176	294	392	118	118	157	157	157
unevenness in display/Load capacity: kgf(N)	(2)	Result (kgf)	12	20	12	14	24	6	8	10	10	10
	Cylindrical jig	Result (N)	118	196	118	137	235	59	78	98	98	98
(3)	Spherical jig	Result (kgf)	10	14	12	14	18	6	8	8	8	8
	Spherical jig	Result (N)	98	137	118	137	176	59	78	78	78	78
General judgment		Judgment	○	○	○	○	○	X	○	○	○	○
		General judgment	○	○	○	○	○	X	X	X	○	○
Test for occurrence of bubbles caused by shock at low temperature (-30° C.)			X	X	Δ	X	X	○	○	○	○	○

50

Accordingly, a test was performed on liquid crystal display devices including the first supports only to examine the relationship of the density of the first supports and the unevenness in display caused by pressure and the occurrence of bubbles caused by shock at low temperature.

Evaluation Method

Liquid crystal display panels were prepared while the thickness of the thinned substrate was varied in the range of 0.5 mm to 0.05 mm and the density and cross-sectional area of the supports were varied. After certain phase different polarizers were bonded to both surfaces of the panel, a test for examining the unevenness in display caused by pressure and a test for examining the occurrence of bubbles caused by shock at -30° C. were carried out in the same manner as examination tests 1 and 2. Five liquid crystal display panels were subjected to each of the tests.

With the use of the single kind of the supports only, however, it is difficult to thin down the panel or increase the strength to a further degree. In order to thin down the panel to a further degree, it is effective to apply the technique disclosed by preferred embodiments of the present invention. Effects and Advantages

The effects and advantages of various preferred embodiments of the present invention will be explained below. The liquid crystal display device 10 or 60 according to the first or second preferred embodiments preferably includes the TFT substrate 20 or 70 and the CF substrate 30 or 80 arranged to face each other and the liquid crystal layer 40 or 90 sandwiched therebetween, wherein a plurality of first supports 50 or 100 are provided to extend from one of the TFT substrate 20 or 70 and the CF substrate 30 or 80 to reach the other substrate and a plurality of second supports 51 or 101, which

are shorter than the first supports **50** or **100**, are arranged to extend from one of the TFT substrate **20** or **70** and the CF substrate **30** or **80** to the other substrate.

With this configuration, a load generally applied to the substrate is received by the first supports **50** or **100** and the second supports **51** or **101**. With the provision of the second supports **51** or **101** that are shorter than the first supports **50** or **100**, the TFT substrate **20** or **70** and the CF substrate **30** or **80** relatively move to follow the displacement of the liquid crystal layer **40** or **90**. Accordingly, the occurrence of bubbles caused by shock at low temperature is prevented.

According to the liquid crystal display device **10** or **60** of preferred embodiments of the present invention, the number of the second supports **51** or **101** may be larger than the number of the first supports **50** or **100**.

With this configuration, the number of the first supports **50** or **100** is minimized and the number of the second supports **51** or **101** shorter than the first supports is increased. As a result, when a local load is applied, the TFT substrate **20** or **70** and the CF substrate **30** or **80** follow the displacement of the liquid crystal layer **40** or **90** with more flexibility. Therefore, the local occurrence of bubbles caused by shock at low temperature, which has been frequent in such a case, is prevented with high reliability.

According to the liquid crystal display device **10** or **60** of preferred embodiments of the present invention, the second supports **51** or **101** may be provided in a display region.

If the second supports **51** or **101** are provided in the display region, local display failure in the display region is prevented.

According to the liquid crystal display device **10** or **60** of preferred embodiments of the present invention, the number of the second supports **51** or **101** provided in a pixel pattern **49** or **85** of the display region may be larger than the number of the first supports **50** or **100** in the same pixel pattern.

If the number of the second supports **51** or **101** is larger than the number of the first supports **50** or **100** in the pixel pattern **49** or **85** of the display region, local display failure in the display region is prevented with high reliability.

According to the liquid crystal display device **10** or **60** of preferred embodiments of the present invention, the density of the second supports **51** or **101** may be about 1.2 or more times the density of the first supports **50** or **100** in the pixel pattern **49** or **85**.

The second supports **51** or **101** according to preferred embodiments of the present invention are adapted to prevent the occurrence of bubbles caused by shock at low temperature and contribute to reduce the unevenness in display caused by pressure applied to the surface of the thinned substrate. From this point of view, the density of the second supports **51** or **101**, which is determined by [(the number of the supports/mm<sup>2</sup>)×the cross-sectional area of the supports], is preferably higher than that of the first supports **50** or **100**. If the density of the second supports is about 1.2 or more times the density of the first supports, the effect of the second supports is exhibited more significantly.

According to the liquid crystal display device **10** or **60** of preferred embodiments of the present invention, the second supports **51** or **101** may be arranged in the same pattern in each of the pixel patterns **49** or **85**.

With this configuration, the second supports **51** or **101** arranged in the uniform pattern equally receive the load applied locally to the substrate. As a result, the local substrate warpage is effectively prevented and the display function of the liquid crystal display device **10** or **60** is made very stable and greatly improved.

According to the liquid crystal display device **10** or **60** of preferred embodiments of the present invention, a gap

between the second supports **51** or **101** and the TFT substrate **20** or **70** preferably is about 0.05 or more times and about 0.2 or less times the thickness of the liquid crystal layer **40** or **90**.

If the gap between the second supports **51** or **101** and the TFT substrate **20** or **70** is about 0.2 or less times the thickness of the liquid crystal layer **40** or **90**, the thin liquid crystal display device effectively prevents the unevenness in display caused by pressure applied to the liquid crystal display panel. Further, if the gap between the second supports **51** or **101** and the TFT substrate **20** or **70** is about 0.05 or more times the thickness of the liquid crystal layer **40** or **90**, the occurrence of bubbles caused by shock at low temperature and the occurrence of failed domains are prevented with high efficiency.

According to the liquid crystal display device **10** or **60** of preferred embodiments of the present invention, at least one of the TFT substrate **20** or **70** and the CF substrate **30** or **80** may have a thickness of about 0.5 mm or less.

With this configuration, in the case where the glass substrates have to be thinned down to reduce the thickness or weight of the panel of the liquid crystal display device **10** or **60**, the TFT substrate **20** or **70** and the CF substrate **30** or **80** may be equally thinned down or designed to have different thicknesses.

According to the liquid crystal display device **10** or **60** of preferred embodiments of the present invention, the TFT substrate **20** or **70** and the CF substrate **30** or **80** may have different thicknesses.

With this configuration, the first and second substrates, i.e., the TFT substrate **20** or **70** and the CF substrate **30** or **80**, are relatively thinned down. This makes it possible to prevent the TFT substrate **20** or **70** whose thickness has been reduced smaller than the predetermined level from breaking upon local application of heat or pressure to the periphery of the substrate in the process of directly mounting connection terminals and drivers on the TFT substrate **20** or **70**. Further, in the process of forming thin multilayers such as TFT terminals and wires, the TFT substrate **20** or **70** is affected or warped by change in temperature or pressure. Even in such a case, the reduction of mechanical strength of the thinned TFT substrate **20** or **70** is prevented.

According to the liquid crystal display device **10** of preferred embodiments of the present invention, each of the pixel patterns **49** may include a light transmissive region **26** and a light reflective region **22**.

With this configuration, the first and second supports **51** or **101** are simultaneously formed in the light transmissive region **26** and the light reflective region higher than the other region by the thickness of a reflective layer **23**. That is, the first and second supports **51** or **101** having different heights are efficiently provided. Therefore, production efficiency of the device is improved.

According to the liquid crystal display device **10** or **60** of preferred embodiments of the present invention, the second supports **51** or **101** may be provided in a light blocking region of the display region.

If the second supports **51** or **101** are provided in the light blocking region of the display region, leakage of light at the places of the second support **51** or **101** is prevented. Further, in the liquid crystal display device **10**, if the second supports are provided in the light blocking region in the light reflective region **22** of the pixel, such as a storage capacitor line, the reduction of effective aperture ratio is prevented.

According to the liquid crystal display device **10** or **60** of preferred embodiments of the present invention, the first supports **50** or **100** and the second supports **51** or **101** may have different cross-sectional areas.

In general, the larger the cross-sectional area of the support (an area of a cross section taken in the direction perpendicular to the direction of extension of the support) is, the higher resistance to pressure the glass substrate is likely to have. The supports prevent leakage of light if they are formed at certain positions on the lines. On the other hand, if the supports are designed to have a larger cross-sectional area than the certain level, the display characteristic such as contrast ratio is adversely affected. In particular, in the case of preferred embodiments of the present invention where a larger number of the second supports **51** or **101** than the first supports are provided, the first supports **50** or **100** and the second supports **51** or **101** having different cross-sectional areas are arranged in asymmetric patterns. Therefore, reduction of the aperture ratio and the contrast ratio of the panel is effectively prevented. The first supports **50** or **100** and the second supports **51** or **101** may be made of the same or different materials in the different processes. However, it is more effective to form the first supports **50** or **100** and the second supports **51** or **101** at one time by the same photolithography and patterning from the viewpoints of reduction of production process and cost. In this way, the first and second supports may be formed at one time to have different heights and different cross-sectional areas.

According to the liquid crystal display device **10** or **60** of preferred embodiments of the present invention, the cross-sectional area of the second supports **51** or **101** may be smaller than the cross-sectional area of the first supports **50** or **100**.

If the cross-sectional area of the second supports **51** or **101** to be formed at certain positions and certain density with respect to the first supports is designed to be smaller than the cross-sectional area of the first supports **50** or **100**, the second supports are provided by the steps of the same number as the conventional steps of providing the first supports **50** or **100** for keeping the gap between the substrates.

According to the liquid crystal display device **10** of preferred embodiments of the present invention, vertical alignment films **25** and **33** for vertically aligning liquid crystal molecules when no voltage is applied may be provided on the surfaces of the TFT substrate **20** and the CF substrate **30** facing the liquid crystal layer **40** and alignment controllers **52** for radially aligning the liquid crystal molecules when a voltage is applied may be provided on at least one of the surfaces of the TFT substrate **20** or **70** and the CF substrate **30** or **80** facing the liquid crystal layer **40** or **90**.

With this configuration, in the liquid crystal layer **40** sandwiched between the substrates that are less likely to cause local warpage, the vertical alignment under no application of load and the radial alignment under application of load are not disturbed even if a local load is applied. Therefore, excellent display quality is maintained.

According to the liquid crystal display device **10** of preferred embodiments of the present invention, the second supports **51** may also function as the alignment controllers.

If the second supports **51** also function as the alignment controllers, the required number of the second supports **51** is reduced. Therefore, the production efficiency of the device is improved.

According to the liquid crystal display device **60** of preferred embodiments of the present invention, an alignment film **75** or **87** subjected to a certain alignment treatment may be provided on at least one of the surfaces of the TFT substrate **70** and the CF substrate **80** facing the liquid crystal layer **90**.

With this configuration, in the liquid crystal layer sandwiched between the substrates less likely to cause local warpage, the alignment given by the certain alignment treat-

ment is not disturbed even if a local load is applied. Therefore, excellent display quality is maintained.

As described above, various preferred embodiments of the present invention are useful for liquid crystal display devices.

While preferred embodiments of the present invention have been described above, it is to be understood that variations and modifications will be apparent to those skilled in the art without departing the scope and spirit of the present invention. The scope of the present invention, therefore, is to be determined solely by the following claims.

The invention claimed is:

1. A liquid crystal display device comprising:

a first substrate;

a second substrate arranged to face the first substrate;

a liquid crystal layer sandwiched between the first substrate and the second substrates;

a plurality of first supports arranged to extend from one of the first substrate and the second substrates to reach the other one of the first substrate and the second substrate; and

a plurality of second supports, which are shorter than the plurality of first supports, arranged to extend from one of the first substrate and the second substrates to the other of the first substrate and the second substrates; wherein a number of the plurality of second supports is larger than a number of the plurality of the first supports; a gap between the plurality of second supports and an opposing one of the first substrate and the second substrate is about 0.06 or more times and about 0.2 or less times a thickness of the liquid crystal layer; and at least one of the first substrate and the second substrate has a thickness of about 0.5 mm or less.

2. The liquid crystal display device of claim 1, wherein the plurality of second supports is provided in a display region.

3. The liquid crystal display device of claim 1 wherein the number of the plurality of second supports provided in a unit pixel area of the display region is larger than the number of the plurality of first supports provided in the same area.

4. The liquid crystal display device of claim 3, wherein the density of the plurality of second supports provided in the unit pixel area is at least about 1.2 times the density of the plurality of first supports provided in the same area.

5. The liquid crystal display device of claim 4, wherein the plurality of second supports is arranged in the same pattern in each of the unit pixel areas.

6. The liquid crystal display device of claim 1, wherein the first substrate and the second substrate have different thicknesses.

7. The liquid crystal display device of claim 6, wherein a thinner one of the first substrate and the second substrate is a CF substrate, and a thicker one of the first substrate and the second substrate is a TFT substrate.

8. The liquid crystal display device of claim 7, wherein the plurality of first supports and the plurality of second supports are provided on the thinner one of the first substrate and the second substrate.

9. The liquid crystal display device of claim 1, wherein each of the unit pixel areas includes a light transmissive region and a light reflective region.

10. The liquid crystal display device of claim 1, wherein the plurality of second supports is provided in a light blocking region of the display region.

11. The liquid crystal display device of claim 1, wherein the plurality of first supports and the plurality of second supports have different cross-sectional areas.

25

12. The liquid crystal display device of claim 11, wherein a cross-sectional area of the plurality of second supports is smaller than a cross-sectional area of the plurality of first supports.

13. The liquid crystal display device of claim 1, wherein vertical alignment films arranged to vertically align liquid crystal molecules when no voltage is applied are provided on surfaces of the first substrate and the second substrates facing the liquid crystal layer, respectively, and alignment controllers arranged to radially align the liquid crystal molecules when a voltage is applied are provided on at least one of the surfaces of the first substrate and the second substrates facing the liquid crystal layer.

14. The liquid crystal display device of claim 13, wherein the plurality of second supports also define alignment controllers.

26

15. The liquid crystal display device of claim 1, wherein an alignment film subjected to alignment treatment is provided on at least one of a surface of the first substrate and the second substrates facing the liquid crystal layer.

16. The liquid crystal display device of claim 1, wherein both of the first substrate and the second substrate have a thickness of about 0.5 mm or less.

17. The liquid crystal display device of claim 1, wherein the plurality of second supports is arranged around the plurality of first supports in each of the unit pixel areas which define a display region.

18. The liquid crystal display device of claim 1, wherein the plurality of first supports is provided adjacent to a blue pixel in each of the unit pixel areas which define a display region.

\* \* \* \* \*

专利名称(译)	液晶显示装置包括多个第一和第二支撑物		
公开(公告)号	<a href="#">US8009261</a>	公开(公告)日	2011-08-30
申请号	US12/064678	申请日	2006-07-24
[标]申请(专利权)人(译)	夏普株式会社		
申请(专利权)人(译)	夏普株式会社		
当前申请(专利权)人(译)	夏普株式会社		
[标]发明人	ONISHI NORIAKI SONKU NAOHISA TSUDA YUSUKE KOJIMA HIROAKI TAGUSA YASUNOBU		
发明人	ONISHI, NORIAKI SONKU, NAOHISA TSUDA, YUSUKE KOJIMA, HIROAKI TAGUSA, YASUNOBU		
IPC分类号	G02F1/1339 G02F1/1335		
CPC分类号	G02F1/133555 G02F1/13394 G02F1/133707 G02F2001/13396		
审查员(译)	ROBINSON , MARK		
助理审查员(译)	常 , CHARLES		
优先权	2005276610 2005-09-22 JP		
其他公开文献	US20090244457A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

一种液晶显示装置，包括：TFT基板和CF基板，布置成彼此面对，并且夹在其间的液晶层，其中，多个第一支撑件布置成从一个基板延伸到另一个基板，并且多个比第一支撑件短的第二支撑件布置成从一个基板延伸到另一个基板。

