



US008004643B2

(12) **United States Patent**
Kobayashi

(10) **Patent No.:** **US 8,004,643 B2**
(45) **Date of Patent:** **Aug. 23, 2011**

(54) **LIQUID CRYSTAL DISPLAY DEVICE**

(75) Inventor: **Kunpei Kobayashi**, Tachikawa (JP)

(73) Assignee: **Casio Computer Co., Ltd.**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 243 days.

(21) Appl. No.: **12/400,267**

(22) Filed: **Mar. 9, 2009**

(65) **Prior Publication Data**

US 2009/0244464 A1 Oct. 1, 2009

(30) **Foreign Application Priority Data**

Mar. 26, 2008 (JP) 2008-081256

(51) **Int. Cl.**
G02F 1/1343 (2006.01)
G02F 1/1335 (2006.01)

(52) **U.S. Cl.** **349/141**; 349/114

(58) **Field of Classification Search** None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,950,167 B2	9/2005	Matsumoto et al.	
7,177,002 B2	2/2007	Matsumoto et al.	
7,492,431 B2 *	2/2009	Matsumoto et al.	349/146
7,675,579 B2	3/2010	Suzuki	
2007/0177090 A1	8/2007	Shimomaki	
2008/0018840 A1 *	1/2008	Uehara et al.	349/114
2008/0074602 A1	3/2008	Arai et al.	

FOREIGN PATENT DOCUMENTS

JP	2002-82357 A	3/2002
JP	2002-182230 A	6/2002
JP	2004-109794 A	4/2004
JP	2007-003877 A	1/2007
JP	2008-83395 A	4/2008
KR	2004-107648 A	12/2004
KR	2006-135537 A	12/2006

OTHER PUBLICATIONS

Korean Office Action dated Aug. 25, 2010 (and English translation thereof) in counterpart Korean Application No. 10-2009-0023716.
Japanese Office Action dated Mar. 9, 2010 and English translation thereof in counterpart Japanese Application No. 2008-081256.

* cited by examiner

Primary Examiner — Tina M Wong

(74) *Attorney, Agent, or Firm* — Holtz, Holtz, Goodman & Chick PC

(57) **ABSTRACT**

A liquid crystal display device includes first and second substrates which have opposed surfaces respectively provided with aligning films and have undergone aligning treatments such that aligning treatment directions are parallel and opposite between the films, and a liquid crystal layer made of a liquid crystal having a negative dielectric anisotropy and placed between the substrates such that molecular long axes of the liquid crystal are oriented parallel to surfaces of the substrates. The first substrate includes a first conductive layer in which elongated slits obliquely crossing the aligning treatment direction are formed parallel to each other, and a second conductive layer formed on a layer different from the first layer through an insulating layer so as to overlap the slits and overlap at least part of the first layer. Each slit includes first and second linear portions extending in different directions at angles line-symmetrical to the aligning treatment direction.

20 Claims, 7 Drawing Sheets




FIG. 1




FIG.2




FIG.3





FIG. 4

FIG. 6




FIG.7




FIG. 8





FIG. 9



LIQUID CRYSTAL DISPLAY DEVICE**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is based upon and claims the benefit of priority from prior Japanese Patent Application No. 2008-081256, filed Mar. 26, 2008, the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION**1. Field of the Invention**

The present invention relates to a lateral electric field control liquid crystal display device.

2. Description of the Related Art

As a liquid crystal display device, there is available a lateral electric field control liquid crystal display device which performs display by changing the molecular long axis direction of liquid crystal molecules within a plane almost parallel to a substrate surface (Jpn. Pat. Appln. KOKAI Publication Nos. 2002-082357 and 2002-182230).

In a conventional lateral electric field control liquid crystal display device, disclination occurs at a portion corresponding to an edge of an electrode for generating a lateral electric field. In addition, when an observation surface is pressed with a finger or the like (this operation will be referred to as surface pressing hereinafter), disclination occurs at the pressed portion.

Disclination occurring at a portion corresponding to the edge of the electrode is display irregularity which occurs when the liquid crystal molecules in a portion corresponding to the edge of the electrode behave so as to rise upright relative to a substrate surface upon application of a strong electric field.

The above disclination due to surface pressing is display irregularity which occurs when an observation surface is partly pressed while the above lateral electric field is applied, the alignment of liquid crystal molecules is disturbed by the surface pressing force, and the disturbed alignment state of the liquid crystal molecules is maintained and is not restored to the initial alignment state even after the surface pressing force is released.

BRIEF SUMMARY OF THE INVENTION

It is an object of the present invention to provide a lateral electric field control liquid crystal display device which can suppress the occurrence of display irregularity.

According to a preferred embodiment of the present invention, there is provided a liquid crystal display device including a first substrate and a second substrate which have opposed surfaces respectively provided with aligning films and have undergone aligning treatments such that aligning treatment directions are parallel and opposite between the aligning films, and a liquid crystal layer which comprises a liquid crystal having a negative dielectric anisotropy and is placed between the first substrate and the second substrate such that molecular long axes of the liquid crystal are oriented substantially parallel to surfaces of the substrates. The first substrate includes a first conductive layer on which elongated electrode portions obliquely crossing the aligning treatment direction are formed parallel to each other so as to form slit portions between the adjacent electrode portions, and a second conductive layer which is formed on a layer different from the first conductive layer through an insulating layer so as to overlap the slit portions and overlap at least part of the

first conductive layer. The elongated electrode portions each include a first linear portion and a second linear portion which extend in different directions at angles line-symmetrical with respect to the aligning treatment direction.

According to a preferred embodiment of the present invention, there is provided a liquid crystal display device including a first substrate and a second substrate which have opposed surfaces respectively provided with aligning films and have undergone aligning treatments such that aligning treatment directions are parallel and opposite between the aligning films, and a liquid crystal layer which comprises a liquid crystal having a negative dielectric anisotropy and is placed between the first substrate and the second substrate such that molecular long axes of the liquid crystal are oriented substantially parallel to surfaces of the substrates. The first substrate includes a first conductive layer in which elongated slit portions obliquely crossing the aligning treatment direction are formed parallel to each other, and a second conductive layer which is formed on a layer different from the first conductive layer through an insulating layer so as to overlap the slit portions and overlap at least part of the first conductive layer. The elongated slit portions each includes a first linear portion and a second linear portion which extend in different directions at angles line symmetrical with respect to the aligning treatment direction.

According to the liquid crystal display device of the present invention, the occurrence of display irregularity can be suppressed.

Advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. Advantages of the invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the invention, and together with the general description given above and the detailed description of the embodiments given below, serve to explain the principles of the invention.

FIG. 1 is a plan view of part of one substrate of a liquid crystal display device according to the first embodiment;

FIG. 2 is a sectional view taken along a line II-II of the liquid crystal display device in FIG. 1;

FIG. 3 is a sectional view taken along a line III-III of the liquid crystal display device in FIG. 1;

FIG. 4 is an enlarged plan view of one slit portion of a common electrode in the liquid crystal display device;

FIG. 5 is a plan view showing the molecular long axis direction of liquid crystal molecules in each portion in one pixel when no lateral electric field is generated in the liquid crystal display device;

FIG. 6 is a plan view showing the molecular long axis direction of liquid crystal molecules in each portion in one pixel when a lateral electric field is generated in the liquid crystal display device;

FIG. 7 is an enlarged sectional view taken along a line VII-VII in FIG. 6;

FIG. 8 is a plan view of part of one substrate of a liquid crystal display device according to the second embodiment; and

FIG. 9 is an enlarged sectional view of part of one pixel of the liquid crystal display device according to the second embodiment.

DETAILED DESCRIPTION OF THE INVENTION

The best mode for carrying out the present invention will be described below with reference to the views of the accompanying drawing.

First Embodiment

FIGS. 1 to 7 show the first embodiment of the present invention. FIG. 1 is a plan view of part of one substrate of a liquid crystal display device. FIG. 2 is a sectional view taken along a line II-II of the liquid crystal display device in FIG. 1. FIG. 3 is a sectional view taken along a line III-III of the liquid crystal display device in FIG. 1.

As shown in FIGS. 1 to 3, this liquid crystal display device includes a pair of transparent substrates 1 and 2, a liquid crystal layer 3, a first transparent electrode 4, and second electrodes 5. The substrates 1 and 2 are arranged to face each other through a predetermined gap. Aligning films 18 and 19 are provided on the inner surfaces of the respective substrates which face each other. The substrate on the observation side (the upper side in FIGS. 2 and 3) and the substrate on the opposite side respectively have undergone aligning treatments in parallel and opposite directions 1a and 2a. The liquid crystal layer 3 is sealed in the gap between the pair of substrates 1 and 2, and the molecular long axes of liquid crystal molecules 3a are oriented almost parallel to the surfaces of the substrates 1 and 2 so as to be aligned with the aligning treatment directions 1a and 2a of the pair of substrates 1 and 2. The first transparent electrode 4 is provided on one of the inner surfaces of the pair of substrates 1 and 2 which face each other, e.g., the inner surface of the substrate 2 on the opposite side (to be referred to as a rear substrate hereinafter) to the observation side, at a position closer to the substrate 2 than the aligning film 19. The second electrodes 5 are provided on the inner surface of the rear substrate 2 at a position closer to the rear substrate 2 than the aligning film 19 so as to be insulated from the first electrode 4. The second electrode 5 is to generate a lateral electric field between itself and the first electrode 4 to change the molecular long axis direction of the liquid crystal molecules 3a within a plane almost parallel to the surfaces of the pair of substrates 1 and 2.

This liquid crystal display device is an active matrix liquid crystal display device. Of the first and second electrodes 4 and 5 provided on the inner surface of the rear substrate 2 so as to be insulated from each other, the second electrodes 5 are pixel electrodes arranged in a matrix form in the row direction (the horizontal direction of the screen) and the column direction (the vertical direction of the screen), and the first electrode 4 is a common electrode corresponding to the pixel electrodes 5.

The inner surface of the rear substrate 2 is provided with thin-film transistors (to be referred to as TFTs hereinafter) 6 which are arranged in the row and column directions and to which display signals corresponding to display data are supplied, and interconnections which are provided between the rows and columns of the TFTs 6 arranged in the above manner and include scanning lines 13 which supply scanning signals to the TFTs 6 of the respective rows and signal lines 14 which supply display signals to the TFTs 6 of the respective columns.

The TFT 6 includes a gate electrode 7 formed on the substrate surface of the rear substrate 2, a transparent gate insulating film 8 formed on almost the entire surface of the rear substrate 2 so as to cover the gate electrode 7, an i-type semiconductor film 9 formed on the gate insulating film 8 so as to face the gate electrode 7, and drain and source electrodes 11 and 12 formed on two side portions of the i-type semiconductor film 9 through n-type semiconductor films 10.

The scanning lines 13 are formed on the substrate surface of the rear substrate 2 so as to extend along one side (the lower side in FIG. 1) of each pixel 100 of each row, and are respectively connected to the gate electrodes 7 of the TFTs 6 of each row. The signal lines 14 are formed on the gate insulating film 8 so as to extend along one side (the left side in FIG. 1) of each pixel 100 of each column, and are respectively connected to the drain electrodes 11 of the TFTs 6 of each column.

The pixel electrodes 5 are formed on the gate insulating film 8 so as to be respectively connected to the source electrodes 12 of the TFTs 6 for each predetermined region for the formation of one pixel 100. That is, the pixel electrodes 5 are isolated for each pixel region and respectively connected to the different TFTs 6.

The common electrode 4 is formed on a transparent insulating film 15 formed on almost the entire surface of the rear substrate 2 so as to cover the TFTs 6 and the signal lines 14. That is, the common electrode 4 is placed between the pixel electrodes 5 and the aligning film 19 formed on the inner surface of the rear substrate 2 so as to be insulated from the pixel electrodes 5 by the insulating film 15 and cover the scanning lines 13 and the signal lines 14. The common electrode 4 is electrically connected among the respective pixel regions to be set at the same potential among the pixel regions.

Note that a terminal array portion (not shown) is formed on an edge portion of the rear substrate 2 so as to protrude outside the substrate 1 on the observation side. The scanning lines 13 and the signal lines 14 are connected to scanning line terminals and signal line terminals provided on the terminal array portion. The common electrode 4 is connected to a common electrode terminal provided on the terminal array portion.

Light-shielding films 16 are formed on the inner surface of the substrate 1 on the observation side so as to correspond to regions among the pixels 100 and the disposition regions of the TFTs 6. Color filters 17R, 17G, and 17B of three colors, i.e., red, green, and blue, are provided on the light-shielding films 16 so as to correspond to the respective pixels 100.

The aligning films 18 and 19 are homogeneous alignment films made of polyimide films or the like, and are respectively formed on the inner surfaces of the pair of substrates 1 and 2 so as to cover the color filters 17R, 17G, and 17B and the common electrode 4.

The inner surfaces of the pair of substrates 1 and 2 are subjected to aligning treatments by rubbing the film surfaces of the aligning films 18 and 19 in parallel and opposite directions. In this embodiment, an aligning treatment is performed on the inner surface of the observation-side substrate 1 from the right to the left on the screen in a direction parallel to the horizontal direction of the screen, and an aligning treatment is performed on the inner surface of the rear substrate 2 from the left to the right on the screen in a direction parallel to the horizontal direction of the screen.

The pair of substrates 1 and 2 are joined to each other through a frame-like seal member (not shown). The liquid crystal layer 3 is sealed in the region surrounded by the seal member in the gap between the pair of substrates 1 and 2.

In addition, polarizing plates 20 and 21 are respectively arranged on the outer surfaces of the pair of substrates 1 and

2. A transparent static electricity blocking conductive film 22 for blocking external static electricity is placed between the observation-side substrate 1 and the observation-side polarizing plate 20 placed on the outer surface of the observation-side substrate 1.

The common electrode 4 and pixel electrodes 5 which are formed on the inner surface of the rear substrate 2 will be described in detail below. The pixel electrodes 5 each comprise a transparent conductive film 50 such as an ITO film formed into a shape corresponding to a predetermined region for the formation of one pixel 100 described above, e.g., a rectangular region which is longer than wide, that is, the vertical width along the vertical direction of the screen is larger than the horizontal width along the horizontal direction of the screen.

The common electrode 4 is formed on the entire region in which the pixel electrodes 5 are arranged in a matrix form so as to cover the scanning lines 13 and the signal lines 14. The common electrode 4 is provided with slits 41 which are formed at intervals, for each predetermined region for the formation of one pixel 100, to form edges crossing the aligning treatment directions 1a and 2a of the pair of substrates 1 and 2 in an oblique direction other than directions perpendicular and parallel to the aligning treatment directions 1a and 2a.

The slits 41 of the common electrode 4 each are formed into an almost doglegged shape having a length almost equal to or slightly smaller than the length of the pixel electrode 5 in a direction perpendicular to the aligning treatment directions 1a and 2a and having two linear portions 41a respectively extending from a middle portion in the lengthwise direction to one end and the other end in directions tilting toward one side relative to directions perpendicular to the aligning treatment directions 1a and 2a of the pair of the substrates 1 and 2, i.e., directions crossing the aligning treatment directions 1a and 2a at a predetermined angle.

The crossing angle of one and the other linear portions 41a of each of the slits 41 of the common electrode 4 with respect to the respective aligning treatment directions is set to an angle smaller than 90° and larger than 70°.

The common electrode 4 comprises a transparent conductive film 40 made of an ITO film or the like in which the slits 41 are formed parallel at intervals so as to obliquely cross the aligning treatment directions 1a and 2a. Each of the slits 41 is formed into a continuous shape constituted by one and the other linear portions 41a which extend from the middle portion in the lengthwise direction of the slit toward one end and the other end in directions tilting to one side (the right side in FIG. 1) relative to directions perpendicular to the aligning treatment directions 1a and 2a and crossing the aligning treatment directions 1a and 2a at a predetermined angle, bent portions 41b which are respectively formed at the adjacent ends of one and the other linear portions 41a and extend in directions crossing the aligning treatment directions 1a and 2a at an angle smaller than the crossing angle of the linear portions 41a with respect to the aligning treatment directions 1a and 2a, and a joint portion 41c between the bent portions 41b.

In addition, the slits 41 of the common electrode 4 each have bent end portions 41d which are respectively formed at the ends, of one and the other linear portions 41a, which are located on the opposite side to their adjacent ends and extend in directions crossing the aligning treatment directions 1a and 2a at an angle smaller than the crossing angle of the linear portions 41a with respect to the aligning treatment directions 1a and 2a.

The connecting portions between the linear portions 41a and the bent portions 41b of each of the slits 41 each are formed into an arcuated shape such that the two side edges of the linear portion 41a and the bent portion 41b are smoothly continuous. The joint portion 41c between the two bent portions 41b is formed into an arcuated shape such that the two side edges of the joint portion 41c and the bent portion 41b are smoothly continuous. Furthermore, the connecting portions between the linear portions 41a and the bent end portions 41d each are formed into an arcuated shape such that the two side edges of the linear portion 41a and the bent end portion 41d are smoothly continuous.

The common electrode 4 is an electrode having elongated electrode portions 42, each including a portion between the adjacent slits 41 and portions located outside the slits 41 on the two sides, formed side by side at intervals corresponding to the width of the slit 41 for each predetermined region for the formation of one pixel 100 described above. The elongated electrode portions 42 conform to the shape of the slit 41.

Each of the elongated electrode portions 42 of the common electrode 4 is formed into a smoothly continuous shape constituted by one and the other linear portions 42a which extend from the middle portion in the lengthwise direction of the slit toward one end and the other end in directions tilting to one side relative to directions perpendicular to the aligning treatment directions 1a and 2a and crossing the aligning treatment directions 1a and 2a at a predetermined angle, bent portions 42b which are respectively formed at the adjacent ends of one and the other linear portions 42a and extend in directions crossing the aligning treatment directions 1a and 2a at an angle smaller than the crossing angle of the linear portions 42a with respect to the aligning treatment directions 1a and 2a, a joint portion 42c between the bent portions 42b, and bent end portions 42d which are respectively formed at ends, of one and the other linear portions 42a, which are located on the opposite side to their adjacent ends and extend in directions crossing the aligning treatment directions 1a and 2a at an angle smaller than the crossing angle of the linear portions 42a with respect to the aligning treatment directions 1a and 2a.

One and the other linear portions 41a of each of the slits 41 of the common electrode 4 have almost the same width, and one and the other linear portions 42a of the elongated electrode portions 42, which include portions between the adjacent slits 41 and portions located outside the slits 41 on the two sides, have almost the same width. In addition, a ratio D/W between a width D of the linear portion 41a of the slit 41 and a width W (see FIG. 5) of the elongated electrode portion 42 is set to 1/3 to 3/1, preferably 1/1.

FIG. 4 is an enlarged plan view of part of one slit 41 of the common electrode 4. Letting θ_a be the crossing angle of one and the other linear portions 41a of each of the slits 41 with respect to the aligning treatment directions 1a and 2a, the crossing angle is set to

$$70^\circ < \theta_a < 90^\circ.$$

The crossing angle of one and the other linear portions 42a of each of the elongated electrode portion 42 with respect to the aligning treatment directions 1a and 2a is almost the same as the above value.

Letting θ_b be the crossing angle of the bent portions 41b provided at the adjacent ends of one and the other linear portions 41a of each of the slits 41 with respect to the aligning treatment directions 1a and 2a, the crossing angle is set to

$$50^\circ < \theta_b < 70^\circ.$$

The crossing angle of the bent portions **42b** of each of the elongated electrode portions **42** with respect to the aligning treatment directions **1a** and **2a** is almost the same as the above value.

Letting L_a be the length of one and the other linear portions **41a** of each of the slits **41**, and L_b be the length of the bent portions **41b** provided at the adjacent ends of one and the other linear portions **41a**, the length L_a of the linear portions **41a** and the length L_b of the bent portions **41b** are set to

$$L_a > nL_b \text{ (n: 3-5) or}$$

$$10L_b > L_a > 4L_b.$$

The length relationship between one and the other linear portions **42a** of the elongated electrode portions **42** and the bent portions **42b** of the elongated electrode portions **42** is almost the same as that described above.

Letting θ_c be the crossing angle of the bent end portions **41d** of the slits **41** with respect to the aligning treatment directions **1a** and **2a**, the crossing angle is set to

$$50^\circ < \theta_c < 70^\circ.$$

The crossing angle of the bent end portions **42d** of the elongated electrode portions **42** with respect to the aligning treatment directions **1a** and **2a** is almost the same as the above value.

Letting L_c be the length of the bent end portions **41d** at the two ends of each of the slits **41**, the relationship between the length L_a of one and the other linear portions **41a** and the length L_b of the bent portions **41b** is set to satisfy

$$L_a > nL_c \text{ (n: 3-5) or}$$

$$10L_c > L_a > 4L_c.$$

The length relationship between one and the other linear portions **42a** of each of the elongated electrode portions **42** and the bent end portions **42d** of each of the elongated electrode portions **42** is almost the same as that described above.

That is, the bent end portions **41d** of the slits **41** are formed to have almost the same tilt angle and length as those of the bent portions **41b** which joint one and the other linear portions **41a**.

The crossing angle θ_a of one and the other linear portions **41a** of each of the slits **41** with respect to the aligning treatment directions **1a** and **2a** is preferably set to $80^\circ \pm 5^\circ$, more desirably $80^\circ \pm 2^\circ$. The crossing angles θ_b and θ_c of the bent portion **41b** and bent end portion **41d** with respect to the aligning treatment directions **1a** and **2a** are preferably set to $60^\circ \pm 5^\circ$, more desirably $60^\circ \pm 2^\circ$.

Note that the linear portion **41a**, of one and the other linear portions **41a** of each of the slits **41**, which extends toward the location of the TFTs **6** is formed to have a length that does not overlap the disposition portion of the TFTs **6**.

The liquid crystal layer **3** comprises a nematic liquid crystal having a negative dielectric anisotropy. The liquid crystal molecules **3a** of the liquid crystal layer **3** are oriented almost parallel to the surfaces of the substrates **1** and **2** while the molecular long axes are aligned with the aligning treatment directions **1a** and **2a** and are uniformly pre-tilted, relative to one of the substrate surfaces, e.g., the surface of the rear substrate **2**, in a direction away from the rear substrate **2** toward the aligning treatment direction **2a** of the inner surface of the rear substrate **2**.

This liquid crystal display device generates a lateral electric field, which changes the molecular long axis direction of the liquid crystal molecules **3a** to a direction almost parallel to the surfaces of the substrates **1** and **2**, between the edges of the slits **41** of the common electrode **4**, i.e., the edge portions of

the elongated electrode portions **42**, and the pixel electrodes **5** by applying a driving voltage corresponding to a display signal between the common electrode **4** of the pixels **100** and the pixel electrodes **5**. This lateral electric field controls the molecular long axis direction of the liquid crystal molecules **3a** of the pixels **100** within a plane almost parallel to the surfaces of the substrates **1** and **2**, thereby displaying an image.

FIG. **5** is a plan view showing the molecular long axis direction of the liquid crystal molecules **3a** in each portion in one pixel **100** when the above lateral electric field is not generated. FIG. **6** is a plan view showing the molecular long axis direction of the liquid crystal molecules **3a** in each portion in one pixel **100** when the above lateral electric field is generated.

FIG. **7** is an enlarged sectional view taken along a line VII-VII in FIG. **6**.

The driving voltage to be applied between the common electrode **4** and the pixel electrode **5** is controlled in accordance with the above display signal within the range from a minimum value of almost 0 V which does not generate the above lateral electric field to a maximum value which generates the lateral electric field having a strength that orients the molecular long axes of the liquid crystal molecules **3a** in regions along the edges of one and the other linear portions **41a** of each of the slits **41** of the elongated electrode portions **42** of the common electrode **4** (the edge portions to one and the other linear portions **42a** of each of the elongated electrode portions **42**) in directions at an angle of almost 45° with respect to the aligning treatment directions **1a** and **2a**.

Note that the liquid crystal display device of this embodiment is of a normally dark display type (to be referred to as a normally black type hereinafter) in which the transmission axis of one of the observation-side polarizing plate **20** and the rear-side polarizing plate **21** is set to be almost parallel or perpendicular to the aligning treatment directions **1a** and **2a**, while the transmission axis of the other polarizing plate is set to be almost perpendicular to the transmission axis of one polarizing plate. In the non-electric field mode in which the lateral electric field is not generated between the common electrode **4** and the pixel electrode **5**, i.e., when the molecular long axes of the liquid crystal molecules **3a** are oriented along the aligning treatment directions **1a** and **2a** as shown in FIG. **5a**, the pixel **100** provides black display. When a lateral electric field E having a strength that orients the molecular long axes of the liquid crystal molecules **3a** in regions along the edges of one and the other linear portions **41a** of each of the slits **41** of the elongated electrode portions **42** of the common electrode **4** in directions at an angle of almost 45° with respect to the aligning treatment directions **1a** and **2a** as shown in FIGS. **6** and **7** is generated between the common electrode **4** and the pixel electrode **5**, the pixel **100** provides brightest display.

As shown in FIGS. **6** and **7**, the lateral electric field E is generated between one side edge and the other side edge of each of the slits **41** of the common electrode **4** and portions, of the pixel electrode **5**, which are adjacent to one side edge and the other side edge of each of the slits **41** of the common electrode **4**.

The lateral electric field E is an electric field in a direction perpendicular to an edge of each of the slits **41** of the common electrode **4**. When the lateral electric field E is generated, the direction of the molecular long axes of the liquid crystal molecules **3a** is changed to a direction perpendicular to the direction of the lateral electric field in accordance with the strength of the lateral electric field E .

In this liquid crystal display device, the slits **41** of the common electrode **4** each are formed into the shape having one and the other linear portions **41a** extending from the middle portion in the lengthwise direction of the slit toward one end and the other end in directions tilting to one side relative to directions perpendicular to the aligning treatment directions **1a** and **2a** at a predetermined angle, with one and the other linear portions **41a** crossing the aligning treatment directions **1a** and **2a** at almost the same angle θ_a . With this shape, as shown in FIG. 6, the direction of the lateral electric field E generated between the edge of one linear portion **41a** of each of the slits **41** of the common electrode **4** and the pixel electrode **5** is made to differ from the direction of the lateral electric field E generated between the edge of the other linear portion **41a** of the slit **41** and the pixel electrode **5** to orient the liquid crystal molecules **3a** in the two different directions in each pixel **100**, thereby performing display with a wide viewing angle with low viewing angle dependence on contrast, brightness, display color, and the like.

In addition, in this liquid crystal display device, the slits **41** of the common electrode **4** each are formed into the continuous shape constituted by one and the other linear portions **41a**, the bent portions **41b** which are formed at the adjacent ends of one and the other linear portions **41a** and extend in the directions crossing the aligning treatment directions **1a** and **2a** at the angle θ_b smaller than the crossing angle θ_a of the linear portions **41a** with respect to the aligning treatment directions **1a** and **2a**, and the joint portion **41c** between the bent portions **41b**. With this shape, even if the strong lateral electric field E that orients the molecular long axes of the liquid crystal molecules **3a** in regions along the edges of one and the other linear portions **41a** of each of the slits **41** of the common electrode **4** in directions at an angle of almost 45° or an angle close to it relative to the aligning treatment directions **1a** and **2a** is generated between the common electrode **4** and the pixel electrode **5**, the liquid crystal molecules **3a** do not tilt at an angle opposite to the pre-tilt angle set by the above aligning treatment.

That is, in the liquid crystal display device of the above embodiment, the slits **41** of the common electrode **4** each are formed into the shape having the bent portions **41b** which are provided at the adjacent ends of one and the other linear portions **41a** and extend in directions crossing the aligning treatment directions **1a** and **2a** at the angle θ_b smaller than the crossing angle θ_a of the linear portions **41a** with respect to the aligning treatment directions **1a** and **2a**, with the bent portions **41b** being made continuous through the joint portion **41c**. With this shape, of the lateral electric fields E generated between the common electrode **4** and the pixel electrode **5**, the lateral electric field generated between one side edge and the other side edge of the bent portions **41b** of each of the slits **41** of the common electrode **4** and the pixel electrode **5** is the lateral electric field (the electric field in a direction perpendicular to the edges of the bent portions **41b**) E in a direction at a crossing angle with respect to the aligning treatment directions **1a** and **2a** which is larger than that of the lateral electric field E generated between the pixel electrode **5** and one side edge and the other side edge of one and the other linear portions **41a** of the slit **41**, as shown in FIG. 6.

For this reason, a change angle ψ_b of the molecular long axis direction of the liquid crystal molecules **3a** in regions along one side edge and the other side edge of the bent portions **41b** of each of the slits **41** of the common electrode **4** relative to the aligning treatment directions **1a** and **2a** at the time of generation of the lateral electric field E is smaller than a change angle ψ_a of the molecular long axis direction of the

liquid crystal molecules **3a** in regions along one side edge and the other side edge of the one and the other linear portions **41a** of the slit **41** relative to the aligning treatment directions **1a** and **2a**. In addition, the above liquid crystal molecules **3a** are strongly influenced by the anchoring force from the aligning film, and the alignment discontinuity of the liquid crystal molecules **3a** at the joint portion **41c** decreases. As a consequence, the intermolecular force between the adjacent liquid crystal molecules **3a** strongly acts on the liquid crystal molecules **3a** in regions along one side edge and the other side edge of the bent portions **41b** to suppress a change in the tilt angle of the liquid crystal molecules **3a** relative to the lateral, electric field E. When a strong electric field is applied between the common electrode **4** and the pixel electrode **5**, since the long axes of the liquid crystal molecules **3a** in regions along one side edge and the other side edge of the slit **41** are oriented in a direction along one side edge and the other side edge of the slit **41**, an electric field component is generated in a direction perpendicular to the substrate at one side edge and the other side edge of the slit **41** by the electric field applied between the common electrode **4** and the pixel electrode **5**. However, since this electric field is an electric field in a direction perpendicular to the long axes of the liquid crystal molecules **3a**, no force acts to increase the tilt angle of the liquid crystal molecules **3a** with respect to the substrate, but a force acts to orient the liquid crystal molecules **3a** parallel to the substrate surface.

For this reason, even when the strong lateral electric field E that orients the molecular long axes of the liquid crystal molecules **3a** in regions along one and the other linear portions **41a** of each of the slits **41** of the common electrode **4** in a direction at an angle of almost 45° or an angle close to it relative to the aligning treatment directions **1a** and **2a** is generated between the common electrode **4** and the pixel electrode **5**, the tilt of the liquid crystal molecules **3a** near the bent portions **41b** of the slit **41** does not change and remains stable. This maintains the state in which the liquid crystal molecules **3a** along one side edge and the other side edge of the bent portions **41b** are tilted at the pre-tilt angle set by the aligning treatment.

The liquid crystal display device of this embodiment is therefore free from alignment irregularity such as the inversion of the tilt angle of the liquid crystal molecules **3a** in regions along one side edge and the other side edge of one and the other linear portions **41a** of the slit **41** relative to a portion corresponding to the inflection point of the slit **41** as a starting point as in a case in which the slits **41** of the common electrode **4** each are shaped into a simple doglegged shape with one and the other linear portions **41a** being directly joined to each other.

The connecting portions between one and the other linear portions **41a** of each of the slits **41** of the common electrode **4** and the bent portions **41b** each are formed into an arcuated shape with the two side edges of the linear portion **41a** and the bent portion **41b** being smoothly continuous. For this reason, the molecular long axis direction of the liquid crystal molecules **3a** in regions along one side edge and the other side edge of one and the other linear portions **41a** changes at the pre-tilt angle set by the aligning treatment, following the tilt direction of the liquid crystal molecules **3a** in regions along one side edge and the other side edge of the bent portions **41b**.

As described above, in the liquid crystal display device of this embodiment, even when the strong lateral electric field E that orients the molecular long axes of the liquid crystal molecules **3a** in regions along edges of one and the other linear portions **41a** of each of the slits **41** of the common electrode **4** in a direction at an angle of almost 45° or an angle

close to it relative to the aligning treatment directions **1a** and **2a** is generated between the common electrode **4** and the pixel electrode **5**, the tilt directions of the liquid crystal molecules **3a** in regions along one side edge and the other side edge of each of the slits **41** of the common electrode **4** are made the same throughout the total length of each slit **41**, as shown in FIGS. 6 and 7. This can obtain good display quality without display irregularity.

In addition, in this liquid crystal display device, the bent end portions **41d** are respectively formed at the ends, of one and the other linear portions **41a** of each of the slits **41** of the common electrode **4**, which are located on the opposite side to their adjacent ends, so as to extend in directions crossing the aligning treatment directions **1a** and **2a** at the angle θ_c smaller than the crossing angle θ_a of the linear portions **41a** with respect to the aligning treatment directions **1a** and **2a**. This also generates, between the pixel electrode **5** and one side edge and the other side edge of the bent end portions **41d**, the lateral electric field **E** in a direction at a larger crossing angle with respect to the aligning treatment directions **1a** and **2a** than the lateral electric field **E** generated between one side edge and the other side of one and the other linear portions **41a** of the slit **41** and the pixel electrode **5**.

For this reason, a change angle ψ_c of the molecular long axis direction of the liquid crystal molecules **3a** in regions along one side edge and the other side edge of the bent end portions **41d** relative to the aligning treatment directions **1a** and **2a** due to the lateral electric field **E** is made smaller than the change angle ψ_a of the molecular long axis direction of the liquid crystal molecules **3a** in regions along one side edge and the other side edge of the linear portions **41a** relative to the aligning treatment directions **1a** and **2a**. This can change the molecular long axis direction of the liquid crystal molecules **3a** in both the regions along one side edge and the other side edge of the bent end portions **41d** in accordance with the pre-tilt angle set by the above aligning treatment.

In this liquid crystal display device, the tilt angle θ_a of one and the other linear portions **41a** of each of the slits **41** of the common electrode **4** with respect to the aligning treatment directions **1a** and **2a** and the tilt angle θ_b of the two bent portions **41b** with respect to the aligning treatment directions **1a** and **2a** are set to

$$70^\circ < \theta_a < 90^\circ$$

$$50^\circ < \theta_b < 70^\circ.$$

This can further stabilize the alignment irregularity of the liquid crystal molecules **3a** due to the lateral electric field **E**.

In addition, in this liquid crystal display device, the length **La** of one and the other linear portions **41a** of each of the slits **41** of the common electrode **4** and the length **Lb** of the two bent portions **41b** are set to

$$La > nLb \text{ (n: 3-5) or}$$

$$10Lb > La > 4Lb.$$

This can further improve the stability of the alignment of the liquid crystal molecules **3a** by the bent portions **41b** of the slits **41** and almost eliminate the influences of the regions corresponding to the bent portions **41b** on display.

In addition, in this liquid crystal display device, the tilt angle θ_c of the bent end portions **41d** formed at the ends, of one and the other linear portions **41a** of each of the slits **41** of the common electrode **4**, which are located on the opposite side to the adjacent ends of the linear portions **41a** with respect to the aligning treatment directions **1a** and **2a** is set to

$$50^\circ < \theta_c < 70^\circ.$$

This can further improve the stability of the alignment of the liquid crystal molecules **3a** when the lateral electric field **E** is applied.

Furthermore, the length **Lc** of the bent end portions **41d** of the slit **41** relative to the length **La** of the linear portions **41a** of the slit **41** is set to a value satisfying:

$$La > nLc \text{ (n: 3-5) or}$$

$$10Lc > La > 4Lc.$$

This can further improve the stability of the alignment of the liquid crystal molecules **3a** by the bent end portions **41d** and almost eliminate the influences of the regions corresponding to the bent end portions **41d** on display.

In this liquid crystal display device, the tilt angle θ_a of one and the other linear portions **41a** of each of the slits **41** of the common electrode **4** with respect to the aligning treatment directions **1a** and **2a** is preferably set to $80^\circ \pm 5^\circ$, more desirably $80^\circ \pm 2^\circ$, and the tilt angles θ_b and θ_c of the bent portions **41b** and bent end portions **41d** with respect to the aligning treatment directions **1a** and **2a** are preferably set to $60^\circ \pm 5^\circ$, more desirably $60^\circ \pm 2^\circ$. This can further improve the stability of the alignment of the liquid crystal molecules **3a** when the lateral electric field **E** is applied.

In this liquid crystal display device, the liquid crystal layer **3** comprises a nematic liquid crystal having a negative dielectric anisotropy (which will be referred to as a liquid crystal whose $\Delta\epsilon$ is negative hereinafter). For this reason, when the lateral electric field **E** is generated between the edges of the slits **41** of the common electrode **4**, each having the above shape, and the pixel electrode **5**, the liquid crystal molecules **3a** are oriented such that the direction of the molecular long axes changes along the edges of the slits **41** of the common electrode **4**, as shown in FIG. 6.

For this reason, even when the strong lateral electric field **E** that orients the molecular long axes of the liquid crystal molecules **3a** in directions at an angle of almost 45° or an angle close to it relative to the aligning treatment directions **1a** and **2a** is generated between the edges of the slits **41** of the common electrode **4** and the pixel electrode **5**, the direction of the lateral electric field **E** is a direction almost perpendicular to the molecular long axes of the liquid crystal molecules **3a**. The lateral electric field **E** therefore acts as a force that aligns the liquid crystal molecules **3a** parallel to the surfaces of the substrates **1** and **2** instead of a force that raises the liquid crystal molecules **3a** upright relative to the surfaces of the substrates **1** and **2**.

That is, this liquid crystal display device uses a liquid crystal whose $\Delta\epsilon$ is negative, and hence the occurrence of disclination along the edges of electrodes due to a lateral electric field is suppressed unlike in a conventional lateral electric field control liquid crystal display device using a liquid crystal whose $\Delta\epsilon$ is positive.

In this liquid crystal display device as well, when the observation surface is pressed with a finger or the like while the lateral electric field **E** is generated, disclination occurs due to the surface pressing. This is because the portion of the observation-side substrate **1** on which the surface pressing force is applied deforms so as to tilt in the inner surface direction from the periphery of the portion toward the center, and the liquid crystal molecules **3a** are oriented so as to rise upright along the tilt direction of the substrate **1**. This oriented state in which the liquid crystal molecules **3a** rise upright is observed as disclination.

In the liquid crystal display device of this embodiment, alignment irregularity due to the above surface pressing occurs. However, disclination due to the above surface press-

ing can be eliminated in a short period of time because the slits **41** of the common electrode **4** each are formed into the continuous shape (to be referred to as a hanger shape hereinafter) constituted by one and the other linear portions **41a** which extend from the middle portion in the lengthwise direction of the slit toward one end and the other end in directions tilting to one side relative to the directions perpendicular to the aligning treatment directions **1a** and **2a** and crossing the aligning treatment directions **1a** and **2a** at the predetermined angle θ_a , the bent portions **41b** which are formed at the adjacent ends of one and the other linear portions **41a** and extend in the directions crossing the aligning treatment directions **1a** and **2a** at the angle θ_b smaller than the crossing angle θ_a of the linear portions **41a** with respect to the aligning treatment directions **1a** and **2a**, the joint portion **41c** between the bent portions **41b**, and the bent end portions **41d** which are respectively formed at the ends, of one and the other linear portions **41a**, which are located on the opposite side to their adjacent ends, so as to extend in the directions crossing the aligning treatment directions **1a** and **2a** at the angle θ_c smaller than the crossing angle θ_a of the linear portions **41a** with respect to the aligning treatment directions **1a** and **2a**.

That is, in this liquid crystal display device, from the viewpoint of the entire pixel **100**, the liquid crystal molecules **3a** are moved by the lateral electric field **E** generated between the edges of one and the other linear portions **41a** of each of the hanger-shaped slits **41** of the common electrode **4** and the pixel electrode **5**, and are oriented such that the molecular long axes are rotated through an angle corresponding to the strength of the lateral electric field **E**.

The middle portion of each of the hanger-shaped slits **41** of the common electrode **4** in the lengthwise direction and the two end portions of the slit, i.e., the two end sides of one and the other linear portions **41a**, are bent at the angle θ_c smaller than the crossing angle θ_a of the linear portions **41a** with respect to the aligning treatment directions **1a** and **2a**. For this reason, when the oriented state of the liquid crystal molecules **3a** is viewed in detail, at the two end sides of the linear portions **41a**, the angle defined by the molecular long axes and the aligning treatment directions **1a** and **2a** is small even in a state in which the lateral electric field **E** is generated.

In this state in which the lateral electric field is generated, therefore, even if alignment irregularity occurs as the liquid crystal molecules **3a** in the corresponding portion rise upright as described above due to the above surface pressing, the liquid crystal molecules **3a** near the bent portions at the middle and two ends of each of the hanger-shaped slits **41** of the common electrode **4** receive the strong anchoring force due to the above aligning treatments. For this reason, when the surface pressing force is released, the liquid crystal molecules **3a** near the bent portions of the slit **41** are restored to the initial alignment state which is almost parallel to the surfaces of the substrates **1** and **2**, and the neighboring liquid crystal molecules **3a** are also attracted by intermolecular force to be restored to the initial alignment state.

As described above, in the above liquid crystal display device, alignment irregularity temporarily occurs due to surface pressing. However, when the surface pressing force is released, the alignment state of the liquid crystal molecules **3a** is restored to the initial alignment state, which is almost parallel to the surfaces of the substrates **1** and **2**, with the liquid crystal molecules **3a** near the bent portions at the middle and two ends of each of the hanger-shaped slits **41** of the common electrode **4** serving as starting points. This can suppress the occurrence of disclination due to the surface pressing and provide display without any display irregularity.

In addition, in this liquid crystal display device, the pixel electrodes **5** provided on the inner surface of the rear substrate **2** are covered with the insulating film **15**, and the common electrode **4** provided with the slits **41** is placed on the insulating film **15**, i.e., on the inner surface side relative to the pixel electrodes **5**. With this structure, the surface of the aligning film **19**, which is formed on the inner surface of the rear substrate **2** so as to cover the common electrode **4**, has high evenness. This provides high alignment stability. Therefore, when the surface pressing force is released, since strong anchoring force acts on the liquid crystal molecules **3a** to restore them to the initial alignment state almost parallel to the surfaces of the substrates **1** and **2**, the alignment irregularity due to the above surface pressing is quickly eliminated, thereby suppressing the occurrence of disclination.

Furthermore, in this liquid crystal display device, since the common electrode **4** is formed to cover the scanning lines **13** and the signal lines **14** extending along the pixels **100**, no strong electric field irrelevant to display is generated between the common electrode **4** and the scanning lines **13** and the signal lines **14**. This can stabilize the alignment of the liquid crystal molecules **3a** in regions other than the pixels **100** and further suppress the occurrence of disclination due to the above surface pressing.

Second Embodiment

FIGS. **8** and **9** show the second embodiment of the present invention. FIG. **8** is a plan view of part of one substrate of a liquid crystal display device. FIG. **9** is an enlarged sectional view of part of one pixel of the liquid crystal display device. Note that the same reference numerals as in the first embodiment denote the same parts in the second embodiment in FIGS. **8** and **9**, and a description will not be repeated.

In the liquid crystal display device of this embodiment, pixel electrodes **5** each are formed from a transparent conductive film (e.g., an ITO film) **50a** which corresponds to a predetermined region for the formation of one pixel and is provided with commonly connected electrode portions **51** formed into a shape conforming to each of the slits **41** of the common electrode **4** described above. Other arrangements are the same as those of the liquid crystal display device of the first embodiment.

In the liquid crystal display device of this embodiment, the electrode portions **51** of the pixel electrode **5** are formed by providing the conductive film **50a** with slits each having a shape almost identical to the shape of each of elongated electrode portions **42** formed from portions between the adjacent slits **41** of the common electrode **4**. The two ends of each of the elongated electrode portions **42** are respectively connected to common connecting portions **52** formed on the two edges of the conductive film **50a**.

According to the liquid crystal display device of this embodiment, since the area of a part-on of the pixel electrode **5** which overlaps the common electrode **4** decreases, the stray capacitance generated between the common electrode **4** and pixel electrode **5** decreases. This reduces the load imposed on the driver for driving the liquid crystal display device.

Other Embodiments

In the first and second embodiments, the bent end portions **41d** are respectively formed at the ends, of one and the other linear portions **41a** of each of the slits **41** of the common electrode **4**, which are located on the opposite side to their

adjacent ends. However, it suffices to form the bent end portion 41d at only one of the ends of one and the other linear portions 41a.

In the above embodiments, the common electrode 4 is placed on the entire region in which the pixel electrodes 5 are arranged in a matrix form. However, the common electrode 4 may be placed for each row or column of the pixel electrodes 5 so as to cover at least the scanning lines 13 or the signal lines 14, and the pixel electrodes of each row or each column may be commonly connected at one end side or the two end sides.

In addition, in the above embodiments, the common electrode 4 and the pixel electrodes 5 are provided on the inner surface of the rear substrate 2. However, the electrodes 4 and 5 may be provided on the inner surface of the observation-side substrate 1.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

What is claimed is:

1. A liquid crystal display device comprising:

a first substrate and a second substrate which have opposed surfaces respectively provided with aligning films and have undergone aligning treatments such that aligning treatment directions are parallel and opposite between the aligning films; and

a liquid crystal layer which comprises a liquid crystal having a negative dielectric anisotropy and is placed between the first substrate and the second substrate such that molecular long axes of the liquid crystal are oriented substantially parallel to surfaces of the substrates,

the first substrate including:

a first conductive layer on which elongated electrode portions obliquely crossing the aligning treatment direction are formed parallel to each other so as to form slit portions between the adjacent electrode portions, and

a second conductive layer which is formed on a layer different from the first conductive layer through an insulating layer so as to overlap the slit portions and overlap at least part of the first conductive layer,

wherein the elongated electrode portions each include a first linear portion and a second linear portion which extend in different directions at angles line-symmetrical with respect to the aligning treatment direction, and

wherein an angle of one of the first linear portion and the second linear portion with respect to the aligning treatment direction is set to an angle of smaller than 90° and larger than 70°.

2. The device according to claim 1, wherein the first conductive layer is formed between the second conductive layer and the aligning film on the first substrate.

3. The device according to claim 1, wherein the electrode portion further includes a third linear portion and a fourth linear portion which extend in different directions at angles line-symmetrical with respect to the aligning treatment direction, and the first linear portion, the third linear portion, the fourth linear portion, and the second linear portion are sequentially connected to each other in the order named.

4. The device according to claim 3, wherein an angle of one of the third linear portion and the fourth linear portion with

respect to the aligning treatment direction is set to an angle of smaller than 70° and larger than 50°.

5. The device according to claim 4, wherein letting La be a length of one of the first linear portion and the second linear portion, and Lb be a length of one of the third linear portion and the fourth linear portion, the lengths are set to satisfy

$$La > 3 \times Lb.$$

6. The device according to claim 4, wherein the electrode portion further includes a fifth linear portion and a sixth linear portion which extend in different directions at angles line-symmetrical with respect to the aligning treatment direction, and the fifth linear portion, the first linear portion, the third linear portion, the fourth linear portion, the second linear portion, and the sixth linear portion are sequentially connected to each other in the order named.

7. The device according to claim 6, wherein an angle of one of the fifth linear portion and the sixth linear portion with respect to the aligning treatment direction is set to an angle of smaller than 70° and larger than 50°.

8. The device according to claim 7, wherein letting La be a length of one of the first linear portion and the second linear portion, and Lc be a length of one of the fifth linear portion and the sixth linear portion, the lengths are set to satisfy

$$La > 3 \times Lc.$$

9. The device according to claim 1, wherein

the first conductive layer is electrically connected among pixel regions, and

the second conductive layer is isolated for each of the pixel regions, and the isolated conductive layers are respectively connected to different thin-film transistors.

10. The device according to claim 1, wherein an area of the second conductive layer is larger than that of the slit portions.

11. A liquid crystal display device comprising:

a first substrate and a second substrate which have opposed surfaces respectively provided with aligning films and have undergone aligning treatments such that aligning treatment directions are parallel and opposite between the aligning films; and

a liquid crystal layer which comprises a liquid crystal having a negative dielectric anisotropy and is placed between the first substrate and the second substrate such that molecular long axes of the liquid crystal are oriented substantially parallel to surfaces of the substrates,

the first substrate including:

a first conductive layer in which elongated slit portions obliquely crossing the aligning treatment direction are formed parallel to each other, and

a second conductive layer which is formed on a layer different from the first conductive layer through an insulating layer so as to overlap the slit portions and overlap at least part of the first conductive layer,

wherein the elongated slit portions each including a first linear portion and a second linear portion which extend in different directions at angles line-symmetrical with respect to the aligning treatment direction, and

wherein an angle of one of the first linear portion and the second linear portion with respect to the aligning treatment direction is set to an angle of smaller than 90° and larger than 70°.

12. The device according to claim 11, wherein the first conductive layer is formed between the second conductive layer and the aligning film on the first substrate.

13. The device according to claim 11, wherein the slit portion further includes a third linear portion and a fourth

17

linear portion which extend in different directions at angles line-symmetrical with respect to the aligning treatment direction, and the first linear portion, the third linear portion, the fourth linear portion, and the second linear portion sequentially communicate with each other in the order named.

14. The device according to claim 13, wherein an angle of one of the third linear portion and the fourth linear portion with respect to the aligning treatment direction is set to an angle of smaller than 70° and larger than 50° .

15. The device according to claim 14, wherein letting L_a be a length of one of the first linear portion and the second linear portion, and L_b be a length of one of the third linear portion and the fourth linear portion, the lengths are set to satisfy

$$L_a > 3 \times L_b.$$

16. The device according to claim 14, wherein the slit portion further includes a fifth linear portion and a sixth linear portion which extend in different directions at angles line-symmetrical with respect to the aligning treatment direction, and the fifth linear portion, the first linear portion, the third linear portion, the fourth linear portion, the second linear

18

portion, and the sixth linear portion are sequentially communicate with each other in the order named.

17. The device according to claim 16, wherein an angle of one of the fifth linear portion and the sixth linear portion with respect to the aligning treatment direction is set to an angle of smaller than 70° and larger than 50° .

18. The device according to claim 17, wherein letting L_a be a length of one of the first linear portion and the second linear portion, and L_c be a length of one of the fifth linear portion and the sixth linear portion, the lengths are set to satisfy

$$L_a > 3 \times L_c.$$

19. The device according to claim 11, wherein the first conductive layer is electrically connected among pixel regions, and

the second conductive layer is isolated for each of the pixel regions, and the isolated conductive layers are respectively connected to different thin-film transistors.

20. The device according to claim 11, wherein an area of the second conductive layer is larger than that of the slit portions.

* * * * *

专利名称(译)	液晶显示装置		
公开(公告)号	US8004643	公开(公告)日	2011-08-23
申请号	US12/400267	申请日	2009-03-09
[标]申请(专利权)人(译)	卡西欧计算机株式会社		
申请(专利权)人(译)	CASIO COMPUTER CO., LTD.		
当前申请(专利权)人(译)	CASIO COMPUTER CO., LTD.		
[标]发明人	KOBAYASHI KUNPEI		
发明人	KOBAYASHI, KUNPEI		
IPC分类号	G02F1/1343 G02F1/1335		
CPC分类号	G02F1/133707		
优先权	2008081256 2008-03-26 JP		
其他公开文献	US20090244464A1		
外部链接	Espacenet USPTO		

摘要(译)

一种液晶显示装置，包括第一和第二基板，所述第一和第二基板具有分别设置有对准膜的相对表面并且经过对准处理使得对准处理方向在所述膜之间平行且相对，并且液晶层由具有负像素的液晶制成电各向异性并置于基板之间，使得液晶的分子长轴平行于基板的表面取向。第一基板包括：第一导电层，其中倾斜地与对准处理方向交叉的细长狭缝彼此平行地形成；以及第二导电层，其通过绝缘层形成在与第一层不同的层上，以与狭缝重叠。重叠至少第一层的一部分。每个狭缝包括以与对准处理方向线对称的角度在不同方向上延伸的第一和第二线性部分。

