



US008345195B2

(12) **United States Patent**
Han et al.

(10) **Patent No.:** **US 8,345,195 B2**
(45) **Date of Patent:** **Jan. 1, 2013**

(54) **LIQUID CRYSTAL DISPLAY**

(75) Inventors: **Kyoung-Tai Han**, Suwon-si (KR);
Eun-Guk Lee, Seoul (KR); **Dong-Yoon Kim**, Seoul (KR); **Hyung-Jun Park**,
Seongnam-si (KR)

(73) Assignee: **Samsung Display Co., Ltd.**, Yongin (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 426 days.

(21) Appl. No.: **12/765,542**

(22) Filed: **Apr. 22, 2010**

(65) **Prior Publication Data**

US 2011/0090443 A1 Apr. 21, 2011

(30) **Foreign Application Priority Data**

Oct. 20, 2009 (KR) 10-2009-0099913

(51) **Int. Cl.**

G02F 1/1337 (2006.01)

G02F 1/1339 (2006.01)

(52) **U.S. Cl.** **349/124; 349/153; 349/123**

(58) **Field of Classification Search** 349/123,
349/124, 153, 154, 155, 156, 157, 158
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,163,357 A * 12/2000 Nakamura 349/155
6,621,548 B2 * 9/2003 Freeman 349/155

6,859,249 B2 * 2/2005 Freeman 349/155
7,528,921 B2 * 5/2009 Ahn et al. 349/153
2005/0286006 A1 * 12/2005 Yanagawa 349/153
2007/0285612 A1 12/2007 Cho et al.
2008/0036956 A1 2/2008 Tung et al.
2008/0158496 A1 * 7/2008 Kim et al. 349/151
2011/0090443 A1 * 4/2011 Han et al. 349/124

FOREIGN PATENT DOCUMENTS

JP 11-142888 5/1999
JP 2007-121687 5/2007
JP 2008-225511 9/2008
JP 2009-003437 1/2009
JP 2009-025803 2/2009
KR 2006-0134504 12/2006
KR 2007-0025430 3/2007
KR 2008-0063016 7/2008

* cited by examiner

Primary Examiner — Brian Healy

(74) *Attorney, Agent, or Firm* — H.C. Park & Associates, PLC

(57) **ABSTRACT**

The present invention relates to a liquid crystal display. The liquid crystal display includes a first substrate and a second substrate facing each other; a liquid crystal layer interposed between the first substrate and the second substrate; a sealant coupling the first substrate and the second substrate and enclosing the liquid crystal layer; a display signal line arranged on the first substrate and including an end portion; and a first spacer disposed between the end portion of the display signal line and the sealant. The liquid crystal layer includes liquid crystal molecules exhibiting a pretilt alignment with respect to the first and second substrates.

19 Claims, 18 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9






FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG.15




FIG.16




FIG.17





FIG.18







FIG. 20



LIQUID CRYSTAL DISPLAY**CROSS REFERENCE TO RELATED APPLICATION**

This application claims priority from and the benefit of Korean Patent Application No. 10-2009-0099913, filed on Oct. 20, 2009, which is hereby incorporated by reference for all purposes as if fully set forth herein.

BACKGROUND OF THE INVENTION**1. Field of the Invention**

Exemplary embodiments of the present invention relates to a liquid crystal display.

2. Discussion of the Background

Liquid crystal displays (LCDs) are now widely used as one type of flat panel display. An LCD has two display panels on which field-generating electrodes such as pixel is electrodes and a common electrode are arranged, and a liquid crystal layer is interposed between the panels. In an LCD, voltages are applied to the field-generating electrodes to generate an electric field through the liquid crystal layer, and the magnitude of an alignment of liquid crystal (LC) molecules of the liquid crystal layer is determined by the electric field strength. Accordingly, the polarization of incident light is controlled via the interaction of the polarized light with the aligned liquid crystal molecules, thereby performing image display.

A vertical alignment (VA) mode LCD aligns the major axes of the liquid crystal molecules perpendicular to the plane of the display panel in the absence of an applied electric field. In a VA mode LCD, a wide viewing angle may be realized by forming cutouts such as minute slits in the field-generating electrodes and by forming protrusions on the field-generating electrodes. Since the electric field established by conductive surfaces with such cutouts and protrusions determines the tilt directions of the liquid crystal molecules, the tilt directions may be spatially distributed into various directions by using various patterns of the cutouts or protrusions such that the reference viewing angle may be enhanced.

In the manufacturing process of an LCD, thin film patterns of a multi-layered structure may be applied on a mother substrate through deposition or photolithographic processes, and a plurality of substrates, i.e., a plurality of cells, may be formed by cutting the mother substrate into unit cells to manufacture the display devices. When voltage is applied to the field-generating electrodes of the individual unit cells in the initial alignment of the liquid crystal molecules, ultraviolet light may be used to irradiate the unit cell to produce alignment of the liquid crystal molecules, which typically requires a lot of time and equipment and causes low LCD production yields.

Also, if the initial alignment of the liquid crystal is not well established, the response speed of the liquid crystal is decreased and the uniformity quality of the liquid crystal display may be deteriorated.

SUMMARY OF THE INVENTION

Exemplary embodiments of the present invention provide an LCD that offers pre-aligned liquid crystal molecules that may be produced in a highly uniform and bulk production process.

Additional features of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention.

An exemplary embodiment of the present invention discloses a liquid crystal display comprising a first substrate and a second substrate facing each other; a liquid crystal layer interposed between the first substrate and the second substrate; a sealant coupling the first substrate and the second substrate and enclosing the liquid crystal layer; a display signal line arranged on the first substrate and comprising an end portion; and a first spacer disposed between the end portion of the display signal line and the sealant.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention, and together with the description serve to explain the principles of the invention.

FIG. 1 is a plan view of an LCD according to an exemplary embodiment of the present invention.

FIG. 2 is an enlarged plan view of portion A of the LCD shown in FIG. 1.

FIG. 3 is a cross-sectional view of the LCD shown in FIG. 2 taken along the line III-III.

FIG. 4 is an enlarged plan view of portion B of the LCD shown in FIG. 1.

FIG. 5 is a cross-sectional view of the LCD shown in FIG. 4 taken along the line V-V.

FIG. 6 is a plan view of an LCD according to another exemplary embodiment of the present invention.

FIG. 7 is a layout view of a display area of an LCD according to an exemplary embodiment of the present invention.

FIG. 8 is a layout view of one pixel of an LCD according to an exemplary embodiment of the present invention.

FIG. 9 and FIG. 10 are cross-sectional views of the LCD of FIG. 8 taken along the line IX-IX, showing different alignment states of several liquid crystal molecules.

FIG. 11 is a layout view of one pixel of an LCD according to another exemplary embodiment of the present invention.

FIG. 12 is a view showing a process of providing a pretit to liquid crystal molecules by using a photopolymerizable prepolymer.

FIG. 13, FIG. 14, FIG. 15, FIG. 16, FIG. 17, and FIG. 18 are views sequentially showing portions of a manufacturing method of an LCD according to an exemplary embodiment of the present invention.

FIG. 19 is a layout view of a lower mother substrate and an upper mother substrate in a manufacturing method of an LCD according to an exemplary embodiment of the present invention.

FIG. 20 is a cross-sectional view of the lower mother substrate and the upper mother substrate shown in FIG. 19 taken along the line XX-XX.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

The invention is described more fully hereinafter with reference to the accompanying drawings, in which embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure is thorough, and will fully convey the scope of the invention to

those skilled in the art. In the drawings, the size and relative sizes of layers and regions may be exaggerated for clarity. Like reference numerals in the drawings denote like elements.

It will be understood that when an element or layer is referred to as being "on" or "connected to" another element or layer, it can be directly on or directly connected to the other element or layer, or intervening elements or layers may be present. In contrast, when an element is referred to as being "directly on" or "directly connected to" another element or layer, there are no intervening elements or layers present.

A liquid crystal display (LCD) according to an exemplary embodiment of the present invention will be described with reference to FIG. 1, FIG. 2, FIG. 3, FIG. 4, FIG. 5, FIG. 6, and FIG. 7.

FIG. 1 is a plan view of an LCD according to an exemplary embodiment of the present invention. FIG. 2 is an enlarged plan view of portion A of the LCD shown in FIG. 1. FIG. 3 is a cross-sectional view of the LCD shown in FIG. 2 taken along the line III-III. FIG. 4 is an enlarged plan view of portion B of the LCD shown in FIG. 1. FIG. 5 is a cross-sectional view of the LCD shown in FIG. 4 taken along the line V-V. FIG. 6 is a plan view of an LCD according to another exemplary embodiment of the present invention. FIG. 7 is a layout view of a display area of an LCD according to an exemplary embodiment of the present invention.

Referring to FIG. 1 and FIG. 7, an LCD includes a display area 10 to display images and a peripheral area 20 surrounding the display area 10. As shown in FIG. 3, the LCD includes a lower panel 100 and an upper panel 200 that face each other and a liquid crystal layer 3 that is interposed between the panels 100 and 200. The upper panel 200 has a smaller area than the lower panel 100.

First, the display area 10 will be described with reference to FIG. 1 and FIG. 7.

The display area 10 includes a plurality of signal lines and a plurality of pixels PX connected thereto and arranged in an approximate matrix format.

The signal lines provided in the lower panel 100 include a plurality of gate lines 121 to transmit gate signals and a plurality of data lines 171 to transmit a data voltage. The gate lines 121 are arranged parallel to each other and extend approximately in a row fashion, and the data lines 171 are arranged parallel to each other and extend approximately in a column fashion.

Each pixel PX includes a switching element (not shown) connected to the gate lines 121 and the data lines 171, a pixel electrode (not shown) connected to the switching element and arranged in the lower panel 100, a common electrode 270 arranged in the upper panel 200, and the liquid crystal layer 3. The pixel electrode receives the data voltage through the switching element. The common electrode 270 may be arranged on the whole surface of the upper panel 200 and receives a common voltage. The liquid crystal layer 3 has a dielectric anisotropy, and the liquid crystal molecules of the liquid crystal layer 3 may be aligned such that their major axes are perpendicular to the surfaces of the two display panels in the absence of an applied electric field.

For color display, each pixel PX uniquely displays one of three primary colors (spatial division), or each pixel PX alternately displays the three primary colors as time passes (temporal division). A desired color is expressed as a spatial or a temporal sum of the primary colors: red, green, and blue. Each pixel PX may include a color filter representing one of the primary colors at the region of the upper panel 200 corresponding to each pixel electrode or on or under the pixel electrode of the lower panel 100.

Next, the peripheral area 20 will be described with reference to FIG. 1, FIG. 2, FIG. 3, FIG. 4, FIG. 5, and FIG. 6.

The peripheral area 20 includes a portion of the gate line 121, an end portion 129 of the gate line 121, a dummy gate conductor 122, a portion of the data line 171, an end portion 179 of the data line 171, a dummy data conductor 172, a sealant 310, and spacer regions 320a, 320b, 330a, and 330b. The portion of peripheral area 20 where the sealant 310 is arranged is covered by the upper panel 200, and the remaining region is exposed since it is not covered by the upper panel 200.

A portion of the gate line 121 and the end portion 129 are arranged on the insulation substrate 110 and may be wide enough for connecting with other layers or a gate driver (not shown). Referring to FIG. 1, the end portion 129 is disposed on the left side of the display area 10 but may be disposed on the right side as well and may be disposed on or under the display area 10 depending on arrangement of the gate lines 121. The dummy gate conductor 122 may be positioned neighboring and parallel to the end portion 129.

A gate insulating layer 140 is arranged on a portion of the gate line 121 and the end portion 129.

A portion of the data line 171 and the end portion 179 are arranged on the gate insulating layer 140. The end portion 179 may also have an area wide enough for connecting with other layers or a data driver 500. Referring to FIG. 1, the end portion 179 may be disposed upward with reference to the display area 10, downward with reference to the display area 10 as shown in FIG. 6, or disposed on the right or left sides of the display area 10 according to the arrangement of the data line 171. The dummy data conductor 172 may be positioned neighboring and parallel to the end portion 179.

A semiconductor layer (not shown) that may be made of amorphous or crystallized silicon may be arranged between the gate insulating layer 140 and a portion of the data line 171 and the end portion 179. A passivation layer 180 is arranged on a portion of the data line 171 and the end portion 179. The passivation layer 180 has a contact hole 182 exposing the end portion 179, and the passivation layer 180 and the gate insulating layer 140 have a contact hole 181 exposing the end portion 129.

Contact assistants 81 and 82 are arranged on the passivation layer 180. The contact assistants 81 and 82 may be made of a transparent conductive material such as indium tin oxide (ITO), indium zinc oxide (IZO), or a metal such as aluminum, silver, chromium, or alloys thereof.

The gate driver (not shown) and the data driver 500 may be directly mounted as at least one integrated circuit chip on the lower panel 100 and connected to the contact assistants 81 and 82. Alternatively, the gate driver and the data driver 500 may be provided on a flexible printed circuit film (not shown) in a tape carrier package (TCP) type and attached to the lower panel 100 to be connected to the contact assistants 81 and 82.

The sealant 310 couples the lower panel 100 to the upper panel 200, encloses the liquid crystal layer 3, and circumferentially surrounds the display area 10.

The upper panel 200 includes an insulation substrate 210, a light-blocking member 220 arranged on the insulation substrate 210, an overcoat 250, and the common electrode 270 arranged on the whole surface of the upper panel 200. The common electrode 270 may be made of a transparent conductor such as ITO or IZO.

The spacer regions 320a, 320b, 330a, and 330b include a first gate spacer region 320a, a second gate spacer region 330a, a first data spacer region 320b, and a second data spacer region 330b.

Referring to FIG. 1, FIG. 2, and FIG. 3, the first gate spacer region **320a** is arranged along the end portions **129** and is disposed between the end portions **129** and the sealant **310**. The first gate spacer region **320a** includes at least one spacer **321a**. The distance L_b between the first gate spacer region **320a** and the sealant **310** may be from 100 μm to 900 μm or may be from 300 μm to 700 μm . The distance L_a between the first gate spacer region **320a** and the end portion **129** or the contact assistants **81** may also be from 100 μm to 900 μm or from 300 μm to 700 μm .

The second gate spacer region **330a** is arranged along the end portions **129** and between the end portions **129** and the edge of the lower panel **100**. The second gate spacer region **330a** includes at least one spacer **331a**. The distance L_c between the second gate spacer region **330a** and the end portion **129** or the contact assistant **81** may also be from 100 μm to 900 μm or from 300 μm to 700 μm .

The first data spacer region **320b** is arranged along the end portions **179** and between the end portions **179** and the sealant **310**. The first data spacer region **320b** includes at least one spacer **321b**. The distance $L_{b'}$ between the first data spacer region **320b** and the sealant **310** may be from 100 μm to 900 μm or from 300 μm to 700 μm . The distance $L_{a'}$ between the first data spacer region **320b** and the end portion **179** or the contact assistants **82** may also be from 100 μm to 900 μm or from 300 μm to 700 μm .

The second data spacer region **330b** is arranged along the end portions **179** and between the end portions **179** and the edge of the lower panel **100**. The second data spacer region **330b** includes at least one spacer **331b**. The distance $L_{c'}$ between the second data spacer region **330b** and the end portion **179** or the contact assistants **82** may also be from 100 μm to 900 μm or from 300 μm to 700 μm .

The spacers **321a**, **321b**, **331a**, and **331b** may be column spacers and may have a uniform interval between them. The spacers **321a**, **321b**, **331a**, and **331b** may be arranged on the lower panel **100** and extend toward the upper panel **200**, and an upper portion of the spacers **321a**, **321b**, **331a**, and **331b** may extend to the upper panel **200**. Referring to FIG. 3 and FIG. 5, although upper panel **200** is not shown as disposed on the spacer regions **320a**, **320b**, **330a**, and **330b**, a portion of the upper panel **200** may be on at least a portion of the spacer regions **320a**, **320b**, **330a**, and **330b**.

The spacers **321a**, **321b**, **331a**, and **331b** maintain the distance between the lower panel **100** and the upper panel **200** such that the contact assistants **81** and **82** and the common electrode **270** do not contact during the manufacturing process of the LCD. The second spacer is regions **330a** and **330b** may be omitted.

Referring to FIG. 6, in the LCD according to another exemplary embodiment of the present invention, the end portion **179**, the first data spacer **320b**, and the second data spacer **330b** are disposed outside of the display area **10**.

Referring to FIG. 8, FIG. 9, and FIG. 10, one pixel PX of an LCD will be described.

FIG. 8 is a layout view of one pixel of an LCD according to an exemplary embodiment of the present invention. FIG. 9 and FIG. 10 are cross-sectional views of the LCD of FIG. 8 taken along the line IX-IX, showing different alignment states of several liquid crystal molecules.

A liquid crystal panel assembly includes a lower panel **100** and an upper panel **200** facing each other and a liquid crystal layer **3** interposed between the display panels **100** and **200**.

First, the lower panel **100** will be described.

A gate line **121** including a gate electrode **124** is arranged on an insulation substrate **110**. A gate insulating layer **140** is arranged on the gate line **121**, and a semiconductor island **154**

made of hydrogenated amorphous silicon (a-Si) or polysilicon is arranged on the gate insulating layer **140**.

Ohmic contact islands **163** and **165** are arranged on the semiconductor island **154**. The ohmic contact islands **163** and **165** may be made of n+hydrogenated a-Si heavily doped with an N-type impurity such as phosphorous or may be made of a silicide.

A data line **171** and a drain electrode **175** are arranged on the ohmic contacts **163** and **165** and the gate insulating layer **140**. The data line **171** includes a source electrode **173** is extending toward the gate electrode **124** and has a U-shape. The drain electrode **175** includes a longitudinal portion facing the source electrode **173** with respect to the gate electrode **124**, a transverse portion **176** intersecting the longitudinal portion and extending parallel to the gate line **121**, and an expansion **177** disposed at one end of the transverse portion **176** and having an area wide enough to accommodate connection with other layers.

A gate electrode **124**, a source electrode **173**, and a drain electrode **175** form a thin film transistor (TFT) along with a semiconductor island **154**, and the channel of the TFT is in the semiconductor island **154** between the source electrode **173** and the drain electrode **175**.

The ohmic contacts **163** and **165** are interposed between the underlying semiconductor islands **154** and the overlying data lines **171** and the drain electrodes **175**, thereby reducing contact resistances.

A passivation layer **180** made of an organic or inorganic insulator is arranged on the data lines **171**, the drain electrodes **175**, and the exposed semiconductor islands **154**. The passivation layer **180** has a contact hole **185** exposing the expansion **177** of the drain electrode **175**.

A plurality of pixel electrodes **191** made of a transparent conductive material such as ITO or IZO or made of a reflective metal such as aluminum, silver, chromium, or an alloy thereof are arranged on the passivation layer **180**.

The overall shape of the pixel electrode **191** is a quadrangle and includes a transverse stem **193**, a longitudinal stem **192** intersecting the transverse stem **193**, a plurality of minute branches **194**, and a lower protrusion **197**. The pixel electrode **191** is divided into four sub-regions by the transverse stem **193** and the longitudinal stem **192**. The minute branches **194** obliquely extend from the transverse stem **193** and the longitudinal stem **192**, and the extension is direction makes an angle of about 45° or 135° with the gate line **121** or the transverse stem **193**. Also, the minute branches **194** of two neighboring sub-regions may be crossed.

The lower protrusion **197** of the pixel electrode **191** is connected to the drain electrode **175** through the contact hole **185**, thereby receiving the data voltage from the drain electrode **175**.

An alignment layer **11** is arranged on the pixel electrode **191**.

Next, the upper panel **200** will be described.

A light-blocking member **220** is arranged on the substrate **210**. The light-blocking member **220** prevents light leakage between neighboring pixels and includes a plurality of openings **225** defining the regions facing the pixel electrodes **191**.

A color filter **230** is arranged on the substrate **210** and the light-blocking member **220**. Most of the color filter **230** is disposed in regions enclosed by the light-blocking members **220**.

An overcoat **250** is arranged on the color filters **230** and the light-blocking member **220**, and a common electrode **270** that may be made of a transparent conductor such as ITO or IZO is arranged on the whole surface of the overcoat **250**.

An alignment layer **21** is arranged on the common electrode **270**. The alignment layers **11** and **21** may be vertical alignment layers.

The liquid crystal layer **3** between the lower panel **100** and the upper panel **200** includes the liquid crystal molecules **31** having a negative dielectric anisotropy. With an applied electric field, the liquid crystal molecules **31** are initially aligned to be pretilted in a direction substantially parallel to the length direction of the minute branches **194**. However when an electric field is not applied across the liquid crystal layer, the liquid crystal molecules **31** is disposed near the surface of the display panels **100** and **200** may be aligned such that their long axes are perpendicular to the surface of the two display panels **100** and **200**.

Next, operation of the LCD will be described with reference to FIG. 8, FIG. 9, and FIG. 10.

FIG. 10 is a cross-sectional view of the LCD of FIG. 8 taken along the line IX-IX showing the liquid crystal layer in the presence of an applied electric field.

When the gate line **121** is applied with a gate signal, the data voltage is applied to the pixel electrode **191** through the data line **171** such that the pixel electrode **191** and the common electrode **270** applied with the common voltage generate an electric field across the liquid crystal layer **3**. Thus, as shown in FIG. 10, the liquid crystal molecules **31** are inclined in a pretilted direction in response to the applied electric field, and the polarization of the incident light through the liquid crystal layer **3** is rotated according to the inclination angles of the liquid crystal molecules. This change of the polarization affects the amount of light transmitted by the polarizer, thereby producing displayed images of the LCD.

Next, one pixel of an LCD according to another exemplary embodiment of the present invention will be described with reference to FIG. 11.

FIG. 11 is a layout view of a pixel of an LCD. The layered structure of the LCD is similar to the layered structure of the LCD shown in FIG. 8 and FIG. 9. A gate line **121** and a storage electrode line **131** are arranged on a substrate (not shown). The gate line **121** includes a first gate electrode **124a** and a second gate electrode **124b**, and the storage electrode line **131** includes right and left longitudinal portions **135** extending downward from the storage electrode line **131** and a storage electrode **133**. The storage electrode **133** is wide enough for overlapping with a pixel electrode **191** (described below).

A gate insulating layer (not shown) is arranged on the gate line **121** and the storage electrode line **131**, and a first semiconductor **154a** and a second semiconductor **154b** are arranged on the gate insulating layer.

Ohmic contacts (not shown) are arranged on the semiconductors **154a** and **154b**, and data lines **171a** and **171b** and drain electrodes **175a** and **175b** are arranged on the ohmic contacts and the gate insulating layer.

A passivation layer (not shown) is arranged on the data lines **171a** and **171b**, the drain electrodes **175a** and **175b**, and the exposed semiconductors **154a** and **154b**. The passivation layer has contact holes **185a** and **185b** exposing the first drain electrode **175a** and the second drain electrode **175b**.

A light-blocking member **220** is arranged on the passivation layer. The light-blocking member **220** prevents light leakage between pixels and may include a portion extending upward and downward on the passivation layer and a quadrangular portion corresponding to the TFT.

A color filter (not shown) is arranged on the passivation layer and the light-blocking member **220**. Most of the color filter is arranged in the region enclosed by the light-blocking member **220** and includes an opening **233** arranged on the

storage electrode **133**. An overcoat (not shown) may be arranged on the color filter and the light-blocking member **220**.

A pixel electrode **191** is arranged on the color filter and the light-blocking member **220** and includes a first subpixel electrode **191a** and a second subpixel electrode **191b** that are separated from each other by a gap **91**.

The second subpixel electrode **191b** includes a connection bridge **195b** enclosing the first subpixel electrode **191a** and extending to the second drain electrode **175b**. The second subpixel electrode **191b** receives the data voltage from the second drain electrode **175b** through the connection bridge **195b**.

Both longitudinal edges of the connection bridge **195b** cover the data lines **171a** and **171b** and prevent crosstalk between the data lines and the first subpixel electrode **191a**.

The first and second subpixel electrodes **191a** and **191b** include longitudinal stems **192a** and **192b**, and transverse stems **193a** and **193b**, and minute branches **194a** and **194b**. The liquid crystal molecules of the liquid crystal layer (not shown) are aligned via an applied electric field and initially pretilted parallel to the length directions of the minute branches **194a** and **194b**.

Next, a method of initially aligning the liquid crystal molecules of a liquid crystal layer to have a pretilted alignment in a manufacturing process of an LCD according to an exemplary embodiment of the present invention will be described with reference to FIG. 8, FIG. 9, FIG. 10, FIG. 11, and FIG. 12.

Generally, a method for providing a pretilt to the liquid crystal that is sustained in the absence of an electric field may improve the response speed of the liquid crystal while realizing wide viewing angle of an LCD. For liquid crystal molecules to have a pretilt in various directions, alignment layers having various alignment directions may be used, or the liquid crystal layer may be applied in the presence of an electric field and a thermal- or light-hardened material added. In the case of light-hardened material being applied, light irradiates the structure to produce alignment of the liquid crystal molecules.

FIG. 12 is a view showing a process providing a pretilt alignment to liquid crystal molecules by using a photopolymerizable prepolymer.

First, a prepolymer **33** such as a monomer that may be polymerized and hardened is through photopolymerization, for example, by ultraviolet irradiation, is injected with the liquid crystal material between the upper display panel **200** and the lower display panel **100**. The prepolymer **33** may be a reactive mesogen.

As shown in FIG. 12, in the absence of an applied electric field, the liquid crystal molecules **31** initially exhibit an alignment perpendicular to the panels **100** and **200**. When the data voltage is applied to the pixel electrode **191** and the common voltage is applied to the common electrode **270**, an electric field is generated across the liquid crystal layer **3**, and the liquid crystal molecules **31** tend to tilt and exhibit an alignment more parallel to the panels **100** and **200**. Near the edges of the minute branches **194a** and **194b**, the electric field has a horizontal component, and the liquid crystal molecules **31** that tend to align in opposite directions tilt parallel to the length direction of the minute branches **194a** and **194b**.

Next, as the electric field is applied across the liquid crystal layer **3**, the prepolymer **33** is irradiated with, for example, ultraviolet light to cause polymerization such that a first polymer **35** and a second polymer **37** are formed as shown in FIG. 12. Upon polymerization, the first polymer **35** is arranged in the liquid crystal layer **3**, and the second polymer **37** is

arranged close to the display panels **100** and **200**. The alignment direction of the liquid crystal molecules **31** have a pretilt in the length direction of the minute branches **194a** and **194b** due to the presence of the first and second polymers **35** and **37**.

Now, a manufacturing method of an LCD including a method of applying a voltage to the lower panel **100** and the upper panel **200** in an initial alignment process of liquid crystal molecules will be described with reference to FIG. **13**, FIG. **14**, FIG. **15**, FIG. **16**, FIG. **17**, FIG. **18**, FIG. **19**, and FIG. **20**.

FIG. **13**, FIG. **14**, FIG. **15**, FIG. **16**, FIG. **17**, and FIG. **18** are views sequentially showing a portion of a manufacturing method of an LCD according to an exemplary embodiment of the present invention. FIG. **19** is a layout view of a lower mother substrate and an upper mother substrate in a manufacturing method of an LCD according to an exemplary embodiment of the present invention, and FIG. **20** is a cross-sectional view of the lower mother substrate and the upper mother substrate shown in FIG. **19** taken along the line XX-XX.

First, referring to FIG. **13**, a lower mother substrate **1** including a plurality of insulation substrates arranged in a matrix format and connected to each other is provided, and display elements and driving elements such as a plurality of gate lines, a plurality of data lines, a plurality of switching elements, and a plurality of pixel electrodes are arranged to complete a plurality of lower panels **100**. Testing pads **128** and **178** to apply a testing signal are arranged on the periphery of the lower panel **100**, and the testing pads **128** and **178** are connected to the gate line and the data line of the lower panel **100** through testing signal lines **126** and **176**.

Also, an upper mother substrate **2** including a plurality of insulation substrates arranged in a matrix format and connected to each other is provided, and thin films such as a common electrode are deposited thereon to complete a plurality of upper panels **200**.

Next, as shown in FIG. **14**, shorting portions **620** and **610** are arranged on the testing pads **128** and **178**. The shorting portions **620** and **610** may be arranged on the upper panel **200**, and in this case, the shorting portions **620** and **610** may be positioned at locations corresponding to the testing pads **128** and **178** of the lower panel **100**.

Also, as shown in FIG. **14**, FIG. **19**, and FIG. **20**, the common electrode **270** of the upper mother substrate **2** is cut along the common electrode cutting line **280**. Accordingly, the common electrode **270** is divided into a first region a and a second region b that are electrically insulated from each other.

Next, referring to FIG. **15** and FIG. **16**, an outer sealant **311** is arranged on one of the lower mother substrate **1** and the upper mother substrate **2**. Then the liquid crystal material is inserted into the region enclosed by the outer sealant **311** to form a liquid crystal layer **3**, and the two mother substrates **1** and **2** are aligned. Then uniform pressure is applied to couple the two mother substrates **1** and **2**. Accordingly, the lower panel **100** and the upper panel **200** comprise a liquid crystal panel assembly **300** along with the liquid crystal layer **3** therebetween. Here, the testing pads **128** and **178** and the shorting portions **620** and **610** are positioned to correspond to the first region a of the upper mother substrate **2**.

Next, as shown in FIG. **17** and FIG. **18**, edge portions L of the lower mother substrate **1** are removed to expose the edge portion of the upper mother substrate **2**, thereby resulting in the relative arrangement of the lower mother substrate **1** and the upper mother substrate **2** as shown in FIG. **18**.

Referring to FIG. **19** and FIG. **20**, each liquid crystal panel assembly **300** includes the display area **10** and the peripheral area **20**. The sealant **310**, the end portion **129**, and the end portion **179** are arranged in the peripheral area **20**. Various characteristics of the exemplary embodiments shown in FIG.

1, FIG. **2**, FIG. **3**, FIG. **4**, FIG. **5**, and FIG. **6** may be applied to the liquid crystal panel assembly **300**.

In FIG. **19**, a voltage application unit **199** is represented as a triangle, and a voltage application unit **299** is represented as a circle. The voltage application units **199** and **299** are positioned in the first region a and the second region b, respectively, of the portion L.

Referring to FIG. **20**, a voltage applied to the voltage application unit **199** biases the common electrode **270** at the first region a, the testing pads **128** and **178**, and the shorting portions **620** and **61**. The voltage may be also applied to the gate line or the data line through the testing signal lines **126** and **176** such that the voltage is applied to the pixel electrode of each pixel PX. Additionally, a voltage applied through the voltage application unit **299** is transmitted to the common electrode **270** at the second region b.

As described above, if the voltage is applied to the voltage application unit **199** and the voltage application unit **299**, an electric field is applied to the liquid crystal layer **3** between the two mother substrates **1** and **2**, and radiation such as ultraviolet light may irradiate a plurality of liquid crystal panel assemblies **300** so that the liquid crystal layers **3** may simultaneously undergo initial alignment, thereby reducing the manufacturing time and cost of the LCD.

Referring to FIG. **1**, FIG. **2**, FIG. **3**, FIG. **4**, FIG. **5**, FIG. **19**, and FIG. **20**, at least one spacer **321a** may be arranged between the sealant **310** of the liquid crystal panel assembly **300** and the end portion **129** or the contact assistant **81**. Also, at least one spacer **331a** may be arranged between the end portion **129** or the contact assistant **81** and the outer sealant **311**. Likewise, at least one spacer **321b** may be arranged between the sealant **310** of the liquid crystal panel assembly **300** and the end portion **179** or the contact assistant **82**, and at least one spacer **331b** may be arranged between the end portion **179** or the contact assistant **82** and the outer sealant **311**. The spacers **321a**, **331a**, **321b**, and **331b** arranged near the end portion **129** or the end portion **179** may be arranged on the lower mother substrate **1** or the upper mother substrate **2** before coupling the two mother substrates **1** and **2**. These spacers **321a**, **331a**, **321b**, and **331b** may maintain the distance between the two mother substrates **1** and **2** such that the common electrode **270** does not contact the end portion **129**, the contact assistant **81**, the end portion **179**, or the contact assistant **82**.

If the common electrode **270** contacts the end portion **129**, the contact assistant **81**, the end portion **179**, or the contact assistant **82**, the voltage difference between the common electrode **270** and the pixel electrode is decreased in the initial alignment step of the liquid crystal layer **3**, and the liquid crystal molecules may not be inclined to the desired angle of alignment.

Accordingly, the spacers **321a**, **331a**, **321b**, and **331b** may be arranged near the end portion **129** or the end portion **179** such that the distance between the mother substrates **1** and **2** may be maintained when initially aligning the liquid crystal layer **3** in a manufacturing process of the LCD. Therefore, a decrease in the voltage difference between the lower panel **100** and the upper panel **200** may be prevented so that a target voltage difference between the pixel electrode and the common electrode **270** may be maintained. Also, the various characteristics of the exemplary embodiments shown in FIG. **1**, FIG. **2**, FIG. **3**, FIG. **4**, and FIG. **5** may be applied to the present exemplary embodiment.

Finally, referring to FIG. **20**, the lower mother substrate **1** and the upper mother substrate **2** are cut according to the cutting line C, thereby resulting in a plurality of liquid crystal panel assemblies **300**. Here, the spacers **331a** and **331b** are included in the liquid crystal panel assembly **300** such that they may remain in the LCD of, for example, FIG. **1**.

According to an exemplary embodiment of the present invention, the liquid crystal layers of a plurality of LCDs may

11

be simultaneously initially aligned such that the manufacturing time and cost of the LCD may be reduced. Further, the spacers may be arranged near the end portion of the display signal line such as the gate line or the data line so that a voltage difference decrease between the upper panel and the lower panel may be prevented when initially aligning the liquid crystal layer.

It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A liquid crystal display, comprising:

a first substrate and a second substrate facing each other;
a liquid crystal layer interposed between the first substrate and the second substrate;

a sealant coupling the first substrate and the second substrate and enclosing the liquid crystal layer;

a display signal line arranged on the first substrate and comprising an end portion; and

a first spacer disposed between the end portion of the display signal line and the sealant, the sealant being disposed between the first spacer and the liquid crystal layer.

2. The liquid crystal display of claim 1, wherein

at least one of a distance between the first spacer and the end portion of the display signal line and a distance between the first spacer and the sealant is in a range of 300 μm to 700 μm .

3. The liquid crystal display of claim 2, wherein the first spacer is disposed along the end portion of the display signal line.

4. The liquid crystal display of claim 3, further comprising: a second spacer disposed opposite the first spacer with respect to the end portion of the display signal line.

5. The liquid crystal display of claim 4, wherein a distance between the second spacer and the end portion of the display signal line is in a range of 300 μm to 700 μm .

6. The liquid crystal display of claim 5, further comprising: a pixel electrode arranged on the first substrate, connected to the display signal line, and comprising branches; and a common electrode arranged on a surface of the second substrate that faces the first substrate.

7. The liquid crystal display of claim 6, further comprising: an alignment layer arranged on the first substrate to align the liquid crystal molecules perpendicular to the first substrate,

wherein the liquid crystal layer comprises:

liquid crystal molecules;

a prepolymer; and

a polymer to align the liquid crystal molecules to be pretilted in a direction parallel to the length of the branches, wherein the prepolymer is irradiated to form the polymer.

8. The liquid crystal display of claim 1, wherein the first spacer is disposed along the end portion of the display signal line.

9. The liquid crystal display of claim 8, further comprising: a second spacer disposed opposite the first spacer with respect to the end portion of the display signal line.

12

10. The liquid crystal display of claim 9, wherein the distance between the second spacer and the end portion of the display signal line is in a range of 300 μm to 700 μm .

11. The liquid crystal display of claim 10, further comprising:

a pixel electrode arranged on the first substrate, connected to the display signal line, and comprising branches; and a common electrode arranged on a surface of the second substrate that faces the first substrate.

12. The liquid crystal display of claim 11, further comprising:

an alignment layer arranged on the first substrate to align the liquid crystal molecules perpendicular to the first substrate,

wherein the liquid crystal layer comprises:

liquid crystal molecules;

a prepolymer; and

a polymer to align the liquid crystal molecules to be pretilted in a direction parallel to the length of the branches, wherein the prepolymer is irradiated to form the polymer.

13. The liquid crystal display of claim 1, further comprising:

a second spacer disposed opposite the first spacer with respect to the end portion of the display signal line.

14. The liquid crystal display of claim 13, wherein the distance between the second spacer and the end portion of the display signal line is in a range of 300 μm to 700 μm .

15. The liquid crystal display of claim 14, further comprising

a pixel electrode arranged on the first substrate, connected to the display signal line, and comprising branches; and a common electrode arranged on a surface of the second substrate that faces the first substrate.

16. The liquid crystal display of claim 15, further comprising:

an alignment layer arranged on the first substrate to align the liquid crystal molecules perpendicular to the first substrate,

wherein the liquid crystal layer comprises:

liquid crystal molecules;

a prepolymer; and

a polymer to align the liquid crystal molecules to be pretilted in a direction parallel to the length of the branches, wherein the prepolymer is irradiated to form the polymer.

17. The liquid crystal display of claim 1, further comprising:

a pixel electrode arranged on the first substrate, connected to the display signal line, and comprising branches; and a common electrode arranged on a surface of the second substrate that faces the first substrate.

18. The liquid crystal display of claim 17, further comprising:

an alignment layer arranged on the first substrate to align the liquid crystal molecules perpendicular to the first substrate,

wherein the liquid crystal layer comprises:

liquid crystal molecules; and

a polymer to align the liquid crystal molecules to be pretilted in a direction parallel to the length of the branches.

19. The liquid crystal display of claim 18, wherein the polymer is arranged by irradiating a prepolymer.

* * * * *

专利名称(译)	液晶显示器		
公开(公告)号	US8345195	公开(公告)日	2013-01-01
申请号	US12/765542	申请日	2010-04-22
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	HAN KYOUNG TAI LEE EUN GUK KIM DONG YOON PARK HYUNG JUN		
发明人	HAN, KYOUNG-TAI LEE, EUN-GUK KIM, DONG-YOON PARK, HYUNG-JUN		
IPC分类号	G02F1/1337 G02F1/1339		
CPC分类号	G02F1/1339 G02F1/133788 G02F1/133703		
审查员(译)	希利, 布瑞恩		
优先权	1020090099913 2009-10-20 KR		
其他公开文献	US20110090443A1		
外部链接	Espacenet USPTO		

摘要(译)

液晶显示器本发明涉及液晶显示器。液晶显示器包括彼此面对的第一基板和第二基板;介于第一基板和第二基板之间的液晶层;密封剂,其耦合第一基板和第二基板并包围液晶层;显示信号线,设置在第一基板上并包括端部;第一间隔物设置在显示信号线的端部和密封剂之间。液晶层包括相对于第一和第二基板呈现预倾斜取向的液晶分子。

