



(12) **Patent Application Publication**
Maeda

(43) **Pub. Date:** **Dec. 2, 2004**

Publication Classification

(52) **U.S. Cl.** 349/114

(57) **ABSTRACT**

The invention provides a liquid crystal display having uniform display and having a wide viewing angle despite the fact that the display includes active elements for switching pixels in the display area, and an electronic device including the same. Specifically, the invention is a transfective liquid crystal display, each dot of which has a reflective display area and a transmissive display area. The liquid crystal display can include an element substrate having a plurality of pixel electrodes, each pixel electrode being provided with a thin film diode (TFD) element, and an opposite substrate facing the element substrate. A reflective layer formed on the opposite substrate extends directly below the TFD element.

(22) Filed: **Apr. 19, 2004**

(30) **Foreign Application Priority Data**

May 1, 2003 (JP) 2003-126579




Fig. 1




Fig. 2




Fig. 3




Fig. 4a




Fig. 4b




Fig. 5





Fig. 6



LIQUID CRYSTAL DISPLAY AND ELECTRONIC DEVICE

BACKGROUND OF THE INVENTION

[0001] 1. Field of Invention

[0002] The present invention relates to a liquid crystal display and an electronic device.

[0003] 2. Description of Related Art

[0004] Transflective liquid crystal displays can include a liquid crystal layer disposed between an upper substrate and a lower substrate. The inner surface of the lower substrate is provided with a reflective film formed of metal, such as aluminum. The reflective film has an opening for transmitting light and functions as a translector. In order to improve brightness and contrast, a transflective liquid crystal display having a structure called multi-gap structure is disclosed. See, for example, Japanese Unexamined Patent Application Publication No. 11-242226. In this structure, the thickness of the liquid crystal layer is different between the reflective display area and the transmissive display area. The reflective display area corresponds to the area in which the reflective film is formed. The transmissive display area corresponds to the opening.

[0005] However, the known transflective liquid crystal device has a problem in that the viewing angle in the transmissive display mode is narrow. This is because the optical design flexibility is restricted. Since the translector is provided on the internal surface of the liquid crystal cell in order not to produce parallax, reflective display needs to be performed with only one polarizer provided at the viewer side. In order to solve this problem, Jisaki et al. disclose a novel transflective liquid crystal display including vertically aligned liquid crystal in "Development of transflective LCD for high contrast and wide viewing angle by using homeotropic alignment", M. Jisaki et al., Asia Display/IDW'01, p. 133-136 (2001). It has the following characteristics:

[0006] (1) A "VA (vertical alignment) mode" is adopted. In the VA mode, molecules of liquid crystal with negative dielectric anisotropy are aligned vertically with respect to the substrate, and then tilted by an applied voltage.

[0007] (2) A "multi-gap structure" is adopted. In the multi-gap structure, the thickness of the liquid crystal layer (cell gap) is different between the transmissive display area and the reflective display area (see, for example, Patent Document 1).

[0008] (3) An "alignment division structure" is adopted. The transmissive display area is a regular octagon in shape. A projection is provided in the center of the transmissive display area on the opposite substrate so that the liquid crystal molecules are tilted in eight directions in the transmissive display area.

SUMMARY OF THE INVENTION

[0009] According to the above article by Jisaki et al., the direction in which the liquid crystal molecules tilt in the transmissive display area is controlled by a projection. However, how to control the direction in which the liquid crystal molecules tilt in the reflective display area is not mentioned at all. If the liquid crystal molecules tilt in random directions, a discontinuous line called disclination

appears at the border between different liquid crystal alignment areas and causes, for example, an afterimage. In addition, since alignment areas of the liquid crystal have different vision properties, non-uniformity will disadvantageously be visible when viewed from an angle.

[0010] Moreover, in an active-matrix liquid crystal display, an electric field is produced in the position and vicinity of the switching element by switching of the element. This electric field may cause alignment disorder of the liquid crystal and reduce contrast. However, the above article does not contain a description concerning the area in which the switching element is formed. It is not considered at all.

[0011] It is an object of the invention to provide a liquid crystal display providing uniform display and having a wide viewing angle despite the fact that it includes active elements for switching pixels in the display area, and an electronic device including the same.

[0012] The invention is a transflective liquid crystal display, each dot of which has a reflective display area and a transmissive display area. The liquid crystal display can include an element substrate having a plurality of pixel electrodes, each pixel electrode being provided with a switching element, an opposite substrate facing the element substrate; and a liquid crystal layer disposed between the two substrates. A reflective layer is provided in the reflective display area of the opposite substrate, and the reflecting layer extends directly below the switching element.

[0013] If alignment disorder of the liquid crystal molecules is caused by an electric field produced in the vicinity of the switching element when the switching element operates, the change of optical property caused by this alignment disorder is not visible to the viewer. Therefore, display defects caused by the alignment disorder are substantially eliminated, and display quality is thereby improved. This is because, in a liquid crystal display having this structure, the reflective layer extends directly below the switching element. The light outputted from the vicinity of the switching element passes through the liquid crystal layer twice. In other words, if the optical property of the light incident on the liquid crystal layer changes due to alignment disorder of the liquid crystal molecules, the change of the optical property is compensated when the light passes through the liquid crystal layer after it is reflected by the reflective layer.

[0014] In the liquid crystal display having this structure, since display defects due to the alignment disorder are substantially eliminated, a black matrix or a light shielding film covering the switching element is unnecessary. The aperture ratio of the liquid crystal display is thereby improved and a bright display is achieved.

[0015] In the liquid crystal display according to the invention, the liquid crystal layer may include liquid crystal with negative dielectric anisotropy. In other words, the liquid crystal display according to the invention may be a liquid crystal display of vertical-alignment mode. By this structure, a high-contrast display with a wide viewing angle is achieved. In addition, a bright display with a high aperture ratio is achieved.

[0016] The liquid crystal display according to the invention may further include electrode layers provided on both sides of the liquid crystal layer, and an alignment controlling device provided in the electrode layers. By this structure, the

direction in which the vertically aligned liquid crystal molecules tilt when the voltage is applied is controlled appropriately, and non-uniformity when viewed from an angle is prevented effectively. This non-uniformity is acknowledged as a problem in display quality for the liquid crystal display of vertical alignment mode. Thus, a high definition display can be provided.

[0017] The liquid crystal display according to the invention preferably further can include a circularly polarized light inputting device that inputs circularly polarized light to the element substrate and the opposite substrate. By this structure, the quality of reflective display and transmissive display is further improved. If circularly polarized light is used, it is not necessary to determine the direction in which the liquid crystal molecules tilt when the voltage is applied. Regardless of the direction, if the liquid crystal molecules tilt by the voltage, a bright display is achieved.

[0018] In the liquid crystal display according to the present invention, the switching element may be a nonlinear diode element. A TFD (thin film diode) element needs comparatively high voltage for switching, therefore intense electric field is produced in the vicinity of the element. However, according to the invention, if the TFD element is used as a switching element, display defects caused by the alignment disorder of the liquid crystal molecules due to the above electric field are substantially eliminated. Therefore, a bright liquid crystal display with a high aperture ratio is provided. Since the TFD element needs only a single metal wiring as compared to other elements such as a TFT element, a bright display with a high aperture ratio is achieved.

[0019] Next, an electronic device according to the present invention includes the liquid crystal display according to the present invention described above. In this way, an electronic device having a bright and high-quality display is provided.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] The invention will be described with reference to the accompanying drawings, wherein like numerals reference like elements, and wherein:

[0021] FIG. 1 is a perspective view partly showing an example, liquid crystal display of a first embodiment;

[0022] FIG. 2 is a plan view showing an exemplary structure of one pixel area;

[0023] FIG. 3 is a sectional view taken along line A-A' of FIG. 2;

[0024] FIG. 4 (a) and FIG. 4 (b) are illustrations of alignment controlling means according to the embodiment;

[0025] FIG. 5 is a plan view showing the structure of one pixel area according to a second embodiment; and

[0026] FIG. 6 is a perspective view showing an example of electronic device.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

[0027] Embodiments of the invention will now be described with reference to the drawings.

[0028] FIG. 1 is a perspective view showing a display area of a liquid crystal display of the first embodiment of the invention. FIG. 2 is a plan view showing the structure of one pixel area. FIG. 3 is a sectional view taken along line A-A' of FIG. 2. The liquid crystal display shown in these figures is an active-matrix color liquid crystal display including TFD (thin film diode) elements (nonlinear diode elements) functioning as switching elements. As shown schematically in FIG. 3, the liquid crystal layer of this embodiment is formed of liquid crystal with negative dielectric anisotropy and the initial alignment state of molecules of the liquid crystal is vertical.

[0029] As shown in FIG. 1, the liquid crystal display of this embodiment is composed mainly of an element substrate 25 and an opposite substrate 10 facing each other. A liquid crystal layer (not shown) is disposed between the substrates 10 and 25. The element substrate 25 has a substrate body 25A formed of transparent material, such as glass, plastic, and quartz. On the inner side (the underside in the figure) of the substrate body 25A, a plurality of data lines 11 are provided in stripes. In addition, a plurality of substantially rectangular pixel electrodes 31 are arranged in a matrix. The pixel electrodes 31 are formed of transparent conductive material such as ITO (indium tin oxide) and are each provided with a TFD element 13. The TFD elements 13 connect the pixel electrodes 31 with the data lines 11.

[0030] On the other hand, the opposite substrate 10 has a substrate body 10A formed of transparent material, such as glass, plastic, and quartz. On the inner side (the upper side in the figure) of the substrate body 10A, a reflective layer 20, a color filter layer 22, and a plurality of scanning lines 9 are formed. The reflective layer 20 is a thin film of metal, such as aluminum and silver. The scanning lines 9 are formed of transparent conductive material such as ITO and extend in the direction crossing the data lines 11 on the element substrate 25. The color filter layer 22 is composed of substantial rectangular color filters 22R, 22G, and 22B arranged periodically, as shown in FIG. 1. The scanning line 9 is formed so as to cover the color filters 22R, 22G; and 22B arranged in the extending direction of the scanning line 9.

[0031] FIG. 2 is a plan view showing the structure of one pixel area of the liquid crystal display shown in FIG. 1. FIG. 2 shows the structure when viewed from the outer side of the element substrate 25 in FIG. 1.

[0032] As shown in FIG. 2, in the liquid crystal display of this embodiment, one pixel consists of three R, G, and B dots. Each dot area is provided with a rectangular frame-like reflective layer 20 having an opening area 20a. The pixel electrodes 31 are disposed in substantially the same positions as the reflective layers 20 when viewed from above. A corner of the pixel electrode 31 is cut off and a TFD element is formed there. The area in which the TFD element 13 is formed is located directly above the area in which the reflective layer 20 is formed.

[0033] Next, refer to the cross-sectional structure shown in FIG. 3. The liquid crystal layer 50 is disposed between the opposite substrate 10 and the element substrate 25. As shown schematically by liquid crystal molecules 51, the liquid crystal layer 50 is formed of liquid crystal with negative dielectric anisotropy and the initial alignment of the liquid crystal molecules is vertical.

[0034] On the substrate body 10A of the opposite substrate 10, a reflective layer 20 is formed partly. The area of the

reflective layer **20** corresponds to the reflective display area R according to this embodiment. The area which is not provided with the reflective layer **20** corresponds to the transmissive display area T. On the reflective layer **20** and on the substrate body **10A** in the transmissive display area T, a color filter layer **22** is provided. In this color filter layer **22**, color filters **22R**, **22G**, and **22B** are disposed in every three adjacent dot areas. The color filters **22R**, **22G**, and **22B** have different colors, that is to say, red (R), green (G), and blue (B), respectively. In order to compensate for differences in chromaticity between reflective display and transmissive display, a pigment layer whose color saturation is different between the reflective display area and the transmissive display area may be provided.

[0035] An insulating film **21** is formed on the color filter layer **22** in the position which corresponds substantially to the reflective display area R. The insulating film **21** is formed of an organic film, such as acrylic resin, which has a thickness of about $2\ \mu\text{m} \pm 1\ \mu\text{m}$. In the vicinity of the border between the reflective display area R and the transmissive display area T, the insulating film **21** has a slope area N so as to vary continuously in thickness. Since the liquid crystal layer **50** in the portion where the insulating film **21** does not exist has a thickness of about 2 to $6\ \mu\text{m}$, the thickness of the liquid crystal layer **50** in the reflective display area R is nearly half of the thickness of the liquid crystal layer **50** in the transmissive display area T. The insulating film **21** functions as an adjusting layer. That is to say, the thickness of the insulating film **21** makes the thickness of the liquid crystal layer **50** different between the reflective display area R and the transmissive display area T. A multi-gap structure is thus realized. By this structure, the liquid crystal display of this embodiment can provide bright and high-contrast display.

[0036] In this embodiment, the edge of the bottom portion of the insulating film **21** substantially corresponds to the edge of the reflective film **20** (reflective display area). Therefore, the slope areas N are substantially included in the reflective display area R. Thus, the area in which the liquid crystal alignment is disordered due to non-uniformity of the liquid crystal layer thickness in the slope area N is disposed outside the transmissive display area T, and thereby superior transmissive display is achieved.

[0037] An electrode **9** is formed on the surface of the opposite substrate **10** including the surface of the insulating film **21**. The electrode **9** can be formed of transparent conductive film, such as ITO (indium tin oxide). An alignment film **23** is formed on the electrode **9**. The alignment film **23** is formed of, for example, polyimide. As shown in FIG. 2, the slit **9a** is formed and extends vertically in the middle of the transmissive display area T. The slit **9a** is formed in the electrode **9** on the opposite substrate **10** as shown in FIG. 3.

[0038] As for the element substrate **25**, a pixel electrode **31** is formed on the substrate body **25A**. An alignment film **33** is formed on the pixel electrode **31**. The pixel electrode **31** is formed of a transparent conductive material such as ITO. The alignment film **33** is formed of, for example, polyimide. Both alignment films **23** and **33** on the opposite substrate **10** and the element substrate **25** are processed for vertical alignment. However, a pre-tilting process, such as rubbing, is not performed.

[0039] As shown in FIG. 3, the pixel electrode **31** has openings in the dot area. In the plan view of FIG. 2, these openings **18** are formed in substantially the same positions as the vertical sides of the opening area **20a** of the rectangular frame-like reflective layer **20**. These openings **18** and the slit **9a** function as an alignment controlling device that controls the direction in which the vertically aligned liquid crystal molecules forming the liquid crystal layer **50** tilt when the voltage is changed.

[0040] On the outer side of the opposite substrate **10**, a retardation film **26** is provided on the substrate body, and a polarizer **27** is provided on the retardation film **26**. On the outer side of the element substrate **25**, a retardation film **36** is provided on the substrate body, and a polarizer **37** is provided on the retardation film **36**. The retardation films **26** and **36** have a phase difference of about $\frac{1}{4}$ wavelength with respect to the wavelength of the visible light. By combinations of the retardation films and the polarizers, circularly polarized light is incident on the liquid crystal layer from both the opposite substrate **10** side and the element substrate **25** side, and linearly polarized light is output. In the outside of the liquid crystal cell corresponding to the outer side of the opposite substrate **10**, a backlight **60** is provided. The backlight **60** has a light source, a reflector, and a light guide substrate.

[0041] In the liquid crystal display of this embodiment having the above structure, as shown in FIG. 2, the TFD element **13** on the element substrate **25** is located directly above the reflective layer **20** on the opposite substrate **10**. The TFD element **13** needs comparatively high voltage for switching. If alignment disorder of the liquid crystal molecules **51** in the vicinity of the TFD element **13** is caused by an electric field, display defects caused by this alignment disorder are not visible to the viewer, and thereby superior display is achieved. The reason is as follows:

[0042] In the reflective display area, the light reaching the viewer passes through the liquid crystal layer **50** twice, that is to say, the light is incident on the liquid crystal layer **50** from the element substrate **25** side, reflected by the reflective layer **20**, and output to the outer side of the element substrate **25**. If the optical property changes due to alignment disorder of the liquid crystal molecules **51** forming the liquid crystal layer **50**, the change of optical property is compensated when the light is reflected by the reflective layer **20** and passes through the liquid crystal layer **50** again.

[0043] It is difficult to control the alignment disorder of liquid crystal caused by an intense electric field in the vicinity of the TFD element **13** by the alignment controlling device, such as an alignment film. Therefore, in the transmissive liquid crystal display including TFD elements, the area in which the TFD element **13** is formed is covered with a black matrix or a light shielding film. In the liquid crystal display of this embodiment, however, for the reasons described above, display defects in the vicinity of the TFD element **13** are substantially eliminated. Therefore, a black matrix or a light shielding film covering the TFD element **13** is unnecessary. Hence, the vicinity of the TFD element **13** can be used as a display area, and the aperture ratio of the liquid crystal display is thereby improved and bright display is achieved.

[0044] In addition, in the liquid crystal display of this embodiment, the direction in which the vertically aligned

liquid crystal molecules **51** tilt when the voltage is applied is controlled appropriately by a slit **9a** formed in the scanning line **9** and by openings **18**, **18** formed in the pixel electrode **31**, as shown in **FIG. 3**.

[0045] **FIG. 4 (a)** is a schematic sectional view illustrating the alignment restriction by the slit **9a** and the openings **18**. As shown in **FIG. 4 (a)**, in the liquid crystal display of this embodiment, when the voltage changes, the liquid crystal molecules **51** tilt toward both sides (across the width) of the openings **18** and the slit **9a**. The openings **18** and the slit **9a** extend substantially perpendicular to the drawing. Therefore, the domain border of the liquid crystal is fixed, and non-uniformity when viewed from an angle is prevented effectively. This non-uniformity is acknowledged as a problem in display quality for the liquid crystal display including a vertically aligned liquid crystal layer. Thus, a superior display with wide viewing angle range is achieved.

[0046] As shown in **FIG. 4 (b)**, ridges **28** extending substantially perpendicular to the drawing may be used as alignment controlling means. These ridges **28** can also control the tilting direction of the liquid crystal molecules **51** favorably, thereby achieving a superior display with a wide viewing angle range.

[0047] In addition, in this embodiment, the openings **18** and the sloping areas **N** are formed in the same positions when viewed from above. By this structure, the portion in which the display defects are caused due to non-uniformity of the liquid crystal layer thickness in the slope area **N** can be located in the same position as the domain border of the liquid crystal formed under the openings **18**. Thus, the aperture ratio of the liquid crystal display is improved and bright display is achieved.

[0048] As described above, the display contrast is improved by adopting a multi-gap structure. In addition, the viewing angle is widened by providing the slit **9a** and the openings **18** for controlling the vertical-alignment liquid crystal. Moreover, the display quality and the aperture ratio are improved by controlling display defects caused by alignment disorder of the liquid crystal molecules **51** in the vicinity of the TFD element **13**. Hence, the liquid crystal display of this embodiment is bright and has high-contrast and a wide viewing angle.

[0049] Next, a second embodiment of the invention will be described with reference to **FIG. 5**. **FIG. 5** is a plan view showing the structure of one pixel area of the liquid crystal display of this embodiment. The liquid crystal display of this embodiment has basically the same structure as the liquid crystal display of the first embodiment; however, the planar shape of the reflective layer **120** is different from the reflective layer **20** shown in **FIG. 2**. In other words, although the opening area **20a** of the reflective layer **20** is formed substantially in the middle of the dot area in the first embodiment, the opening area **120a** forming a transmissive display area has substantially the same width as the pixel electrode **31** on the element substrate **25**.

[0050] In the liquid crystal display of this embodiment having the above structure, the display defects caused by an electric field formed when the TFD element **13** switches are substantially eliminated by disposing the TFD element **13** directly above the reflective layer **120**. Thus, the aperture ratio of the liquid crystal display can be improved and a bright display can be achieved.

[0051] In the first embodiment and second embodiment, the liquid crystal display includes TFD elements functioning as switching elements. However, it should be understood that the invention can be applied to a liquid crystal display, including TFT (thin film transistor) elements functioning as switching elements, and the same advantageous effect as above can be achieved.

[0052] In addition, although the liquid crystal layer **50** is formed of liquid crystal of vertical alignment, the liquid crystal layer **50** may be formed of liquid crystal of parallel alignment or twist alignment.

[0053] **FIG. 6** is a perspective view showing an example of an electronic device according to the invention. A mobile phone **1300** has a display of the present invention as a small-size display **1301**, in addition to a plurality of keys **1302**, an earpiece **1303**, and a mouthpiece **1304**.

[0054] The displays of the above embodiments can be used as and are suitable for a display not only for a mobile phone, but also for an electronic book reader, a personal computer, a digital still camera, a liquid crystal TV, a camcorder with an eyepiece-type viewfinder or a monitor-type viewfinder, a car navigation system, a pager, an electronic organizer, a calculator, a word processor, a workstation, a TV telephone, a point-of-sale terminal, a device with a touch panel, and the like. In any electronic device, bright, high-contrast, and wide viewing angle display can be possible.

[0055] While this invention has been described in conjunction with the specific embodiments thereof, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art. Accordingly, preferred embodiments of the invention as set forth herein are intended to be illustrative, not limiting. There are changes that may be made without departing from the spirit and scope of the invention.

What is claimed is:

1. A transreflective liquid crystal display, each dot of which having a reflective display area and a transmissive display area, the transreflective liquid crystal display comprising:

an element substrate having a plurality of pixel electrodes with each pixel electrode including a switching element;

an opposite substrate facing the element substrate; and

a liquid crystal layer disposed between the two substrates,

a reflective layer being provided in the reflective display area of the opposite substrate; and

the reflective layer extending directly below the switching element.

2. The liquid crystal display according to claim 1, the liquid crystal layer including a liquid crystal with negative dielectric anisotropy.

3. The liquid crystal display according to claim 2, further comprising electrode layers provided on both sides of the liquid crystal layer, and an alignment controlling device provided in the electrode layers.

4. The liquid crystal display according to claim 2, further comprising a circularly polarized light inputting device that inputs circularly polarized light to the element substrate and the opposite substrate.

5. The liquid crystal display according to claim 1, the switching element being a nonlinear diode element.

6. The liquid crystal display according to claim 1, further comprising an adjusting layer that makes a thickness of the liquid crystal layer different between the reflective display

area and the transmissive display area, the adjusting layer being provided at least in the reflective display area.

7. An electronic device including the liquid crystal display according to claim 1.

* * * * *

专利名称(译)	液晶显示器和电子设备		
公开(公告)号	US20040239847A1	公开(公告)日	2004-12-02
申请号	US10/826411	申请日	2004-04-19
[标]申请(专利权)人(译)	精工爱普生株式会社		
申请(专利权)人(译)	SEIKO EPSON CORPORATION		
当前申请(专利权)人(译)	SEIKO EPSON CORPORATION		
[标]发明人	MAEDA TSUYOSHI		
发明人	MAEDA, TSUYOSHI		
IPC分类号	G02F1/1335 G02F1/1333 G02F1/1343 G02F1/1365		
CPC分类号	G02F1/133371 G02F2203/09 G02F2001/133541 G02F1/134309		
优先权	2003126579 2003-05-01 JP		
其他公开文献	US7250995		
外部链接	Espacenet USPTO		

摘要(译)

本发明提供一种具有均匀显示并具有宽视角的液晶显示器，尽管显示器包括用于切换显示区域中的像素的有源元件，以及包括该液晶显示器的电子设备。具体地，本发明是一种半透半反液晶显示器，其每个点具有反射显示区域和透射显示区域。液晶显示器可包括具有多个像素电极的元件基板，每个像素电极设置有薄膜二极管（TFD）元件，以及面对元件基板的相对基板。形成在相对基板上的反射层直接在TFD元件下方延伸。

