



US006680769B1

(12) **United States Patent**
Lee et al.

(10) **Patent No.: US 6,680,769 B1**
(45) **Date of Patent: Jan. 20, 2004**

(54) **MULTI-DOMAIN LIQUID CRYSTAL
DISPLAY DEVICE**

6,356,335 B1 * 3/2002 Kim et al. 349/156

FOREIGN PATENT DOCUMENTS

(75) Inventors: **Yun Bok Lee**, Kunpo-shi (KR); **Doo
Hyun Ko**, Kumi-shi (KR); **Joun Ho
Lee**, Daegu-kwangyokshi (KR)

(73) Assignee: **LG.Philips LCD Co., Ltd.** (KR)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

EP	0 752 611	1/1997
EP	0 814 142	12/1997
EP	0 854 377	7/1998
EP	0 884 626	12/1998
GB	2 296 810	7/1996
GB	2 321 718	8/1998
GB	2 337 843	1/1999
JP	1028622	1/1989
JP	05-297412	11/1993
JP	09-197420	7/1997
JP	09-230387	9/1997
WO	961 0774	4/1996

(21) Appl. No.: **09/497,507**

(22) Filed: **Feb. 4, 2000**

(30) **Foreign Application Priority Data**

Feb. 8, 1999 (KR) 1999-4195
Apr. 22, 1999 (KR) 1999-14492

(51) **Int. Cl.⁷** **G02F 1/1377; G02F 1/1343**
(52) **U.S. Cl.** **349/129; 349/38; 349/143**
(58) **Field of Search** 349/129, 123,
349/38, 42, 43, 84, 110, 143, 139

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,581,608 A	4/1986	Aftergut et al.	340/704
4,728,175 A	3/1988	Baron	350/336
4,937,566 A	6/1990	Clerc	340/784
4,973,135 A	11/1990	Okada et al.	350/334
4,978,203 A	12/1990	Yamazaki et al.	350/339 R
5,249,070 A	9/1993	Takano	359/54
5,479,282 A	12/1995	Toko et al.	359/75
5,574,582 A	11/1996	Takeda et al.	359/59
5,623,354 A	4/1997	Lien et al.	349/124
5,668,650 A	9/1997	Mori et al.	349/42
5,737,051 A	4/1998	Kondo et al.	349/141
5,777,701 A	7/1998	Zhang	349/44

OTHER PUBLICATIONS

A. Lien, R.A. John, Two-Domain TN-LCDs Fabricated by
Parallel Fringe Field Method, SID Digest, 1993, pp.
269-272.

(List continued on next page.)

Primary Examiner—Robert H. Kim


Assistant Examiner—Thoi V. Duong

(74) *Attorney, Agent, or Firm*—McKenna Long & Aldridge
LLP

(57) **ABSTRACT**

A multi-domain liquid crystal display device includes first and second substrates facing each other and a liquid crystal layer between the first and second substrates. A conductive layer distorting electric field is on the first substrate, and a common-auxiliary electrode is on a same layer whereon the conductive layer distorting electric field is formed. A common electrode is on the second substrate, and a storage electrode is in an electric field inducing region that divides the liquid crystal layer into at least two domains.

37 Claims, 29 Drawing Sheets



OTHER PUBLICATIONS

A. Lien, R.A. John, TFT-Addressed Two-Domain TN VGA Displays Fabricated Using the Parallel Fringe Field Method, SID Digest, 1994, pp. 594-597.

N. Koma, Y. Baba, K. Matsuoka, No-Rub Multi-Domain TFT-LCD Using Surrounding-Electrode Method, SID Digest, 1995, pp. 869-872.

H. Murai, M. Suzuki, S. Kaneko, Novel High Contrast Random and Controlled 4-Domain CTN-LCDs with Wide Viewing Angle, Euro Display '96, pp. 159-161.

Y. Koike, S. Kataoka, T. Sasaki, H. Chida, H. Tsuda, A. Takeda and K. Ohmuro, T. Sasabayashi, K. Okamoto, A Vertically Aligned LCD Providing Super-High Image Quality, IDW '97, pp. 159-162.

N. Koma, R. Nishikawa, Development of a High-Quality TFT-LCD for Projection Displays, SID Digest, 1997, pp. 461-464.

K. Ohmuro, S. Kataoka, T. Sasaki, Y. Koike, Development of Super-High Image Quality Vertical Alignment Mode LCD, SID Digest, 1997, pp. 845-848.

* cited by examiner

FIG. 1A
PRIOR ART




FIG. 1B
PRIOR ART




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 2E




FIG. 2F




FIG. 2G




FIG. 2H




FIG. 2I




FIG. 2J





FIG. 2K





FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 3E




FIG. 3F




FIG. 3G




FIG. 3H




FIG. 3I





FIG. 3J





FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4E




FIG. 4F




FIG. 4G




FIG. 4H




FIG. 4I





FIG. 4J





FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 5F





FIG. 5G



MULTI-DOMAIN LIQUID CRYSTAL DISPLAY DEVICE

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a liquid crystal display device (LCD), and more particularly, to a liquid crystal display device having common-auxiliary electrodes surrounding pixel region and storage electrode in the pixel region.

2. Description of the Related Art

Recently, an LCD has been proposed where the liquid crystal is not aligned and the liquid crystal is driven by side electrodes insulated from pixel electrodes. FIGS. 1a and 1b are sectional views of pixel unit of the conventional LCDs.

Regarding conventional LCDs, a plurality of gate bus lines arranged in a first direction on a first substrate and a plurality of data bus lines arranged in a second direction on the first substrate divide the first substrate into a plurality of pixel regions.

A thin film transistor (TFT) applies image signal delivered from the data bus line to a pixel electrode 13 on a passivation layer 37. The TFT is formed on each pixel region and comprises a gate electrode, a gate insulator, a semiconductor layer, a source electrode, and a drain electrode, etc.

Pixel electrode 13 is formed on the gate insulator, thereon passivation layer 37 is formed over the whole first substrate, and side electrode 21 is formed surrounding the pixel electrode 13 and a part of pixel electrode 13 overlaps side electrode 21. (FIG. 1A)

Alternatively, pixel electrode 13 is formed on the gate insulator, and passivation layer 37 is formed over the whole first substrate.

On second substrate, a light shielding layer is formed to shield any light leakage from gate and data bus lines, and the TFT, a color filter layer is formed on the light shielding layer, an over coat layer is formed on the color filter layer, a common electrode 17 is formed to have open area 27 on the over coat layer, and a liquid crystal layer is formed between the first and second substrates.

The common electrode 17 is formed and applies electric field to a liquid crystal layer together with pixel electrode 13. Side electrode 21 and open area (slit) 27 distort the electric field applied to the liquid crystal layer.

Then, in a unit pixel liquid crystal molecules are driven variously. This means that when voltage is applied to the LCD, dielectric energy due to the distorted electric field arranges the liquid crystal directors in needed or desired positions.

In the LCDs, however, open area 27 in common electrode 17 or pixel electrode 13 is necessary, and the liquid crystal molecules could be driven stably when the open area is wider. If the electrodes do not have an open area or the width of the open area is narrow, the electric field distortion needed to divide the pixel region becomes weak. Then, when voltage over a threshold voltage, V_{th} , is applied, the time needed to stabilize the liquid crystal directors increases.

At this time, disclination occurs from the area where the liquid crystal directors are parallel with a transmittance axis of the polarizer, which results in a decrease in brightness. Further, according to the surface state of LCDs, the liquid crystal texture has an irregular structure.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to an LCD that substantially obviates one or more problems due to limitations and disadvantages of the related art.

An object of the present invention is to provide a multi-domain LCD having high response time characteristics and high brightness by stable arrangement of liquid crystal molecules.

Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve the objects and in accordance with the purpose of the invention, as embodied and broadly described herein, a multi-domain liquid crystal display device comprises first and second substrates facing each other; a conductive layer distorting electric field on the first substrate; a common-auxiliary electrode on a same layer whereon the conductive layer distorting-electric field is formed; a common electrode on the second substrate; a liquid crystal layer between the first and second substrates; and a storage electrode in an electric field inducing region that divides the liquid crystal layer into at least two domains.

The liquid crystal layer includes liquid crystal molecules having positive or negative dielectric anisotropy.

The multi-domain liquid crystal display device further comprises a negative uniaxial or negative biaxial film on at least one substrate.

The liquid crystal layer includes chiral dopants.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of the specification, illustrate embodiments of the invention and together with description serve to explain the principles of the invention.

In the drawings:

FIGS. 1A and 1B are sectional views of the liquid crystal display devices in the related art;

FIGS. 2A, 2B, 2C, 2D, 2E, 2F, and 2G are plan views of the multi-domain liquid crystal display device according to the first embodiment of the present invention, and FIGS. 2H, 2I, and 2J, 2K are sectional views taken along the lines I-I' of FIG. 2A;

FIGS. 3A, 3B, 3C, 3D, 3E, 3F, and 3G are plan views of the multi-domain liquid crystal display device according to the second embodiment of the present invention, and FIGS. 3H, and 3I, 3J are sectional views taken along the lines II-II' of FIG. 3A;

FIGS. 4A, 4B, 4C, 4D, 4E, 4F, and 4G are plan views of the multi-domain liquid crystal display devices according to the third embodiment of the present invention, and FIGS. 4H, and 4I, 4J are sectional views taken along the lines III-III' of FIG. 4A;

FIGS. 5A, 5B, 5C, 5D, 5E, 5F, and 5G are plan views of the multi-domain liquid crystal display devices showing various electric field inducing window or dielectric frame according to the embodiments of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Hereinafter, the multi-domain liquid crystal display device of the present invention is explained in detail by accompanying the drawings.

3

FIGS. 2A, 2B, 2C, 2D, 2E, 2F, and 2G are plan views of the multi-domain liquid crystal display device according to the first embodiment of the present invention, FIGS. 2H, 2I are sectional views taken along the lines I-I' of FIG. 2A, and FIGS. 2J, 2K are entire sectional views according to the FIG. 2H.

As shown in the figures, the present invention comprises first and second substrates 31, 33, a plurality of gate bus lines 1 arranged in a first direction on the first substrate and a plurality of data bus lines 3 arranged in a second direction on the first substrate, a TFT, a passivation layer 37, a pixel electrode 13, and a common-auxiliary electrode 15.

Data bus lines 3 and gate bus lines 1 divide the first substrate 31 into a plurality of pixel regions. The common-auxiliary electrode 15 distorts electric field on a same layer whereon the pixel electrode 13 is formed. The TFT is formed on each pixel region and comprises a gate electrode 11, a gate insulator 35, a semiconductor layer, an ohmic contact layer, and source/drain electrodes 7, 9.

Passivation layer 37 is formed on the whole first substrate 31. Pixel electrode 13 is coupled to the drain electrode 9 by a contact hole 39.

On the second substrate 33, a light shielding layer 25 is formed to shield the light leaked from gate and data bus lines 1, 3, and the TFT, a color filter layer 23 is formed on the light shielding layer 25, a common electrode 17 is formed on the color filter layer 23 and electrically connects to the common-auxiliary electrode 15, and a liquid crystal layer is formed between the first and second substrates 31, 33.

The common electrode 17 has dielectric frames 53 thereon, or has electric field inducing window 51 like hole or slit in its inner part.

In the first embodiment of the present invention, a first storage electrode 43 is formed on a same layer whereon the gate bus line is formed (refer to the FIG. 2I), or on a same layer whereon the source/drain electrodes 7, 9 are formed (refer to the FIG. 2H), and then the first storage electrode 43 forms a storage capacitor 41 with the pixel electrode 13. At this time, since the first storage electrode 43 is patterned as shown in the figures, the portions of disclination in the pixel region are covered.

Further, as shown in the FIG. 2C, a third storage electrode 65 is additionally formed to enlarge the capacitance of liquid crystal display device on the gate bus line 1, so that a image flicker or a residual image could be removed.

In the FIGS. 2D, 2E, 2F, and 2G, the first storage electrode 43 are patterned horizontally, vertically, and/or diagonally, or in a shape of "+" or "x", and in these embodiments, the dielectric frame 53 or electric field inducing window 51 on the second substrate is patterned as above.

In the FIGS. 2J and 2K, the common electrode 17 has dielectric frames 53 thereon, and has electric field inducing window 51 like hole or slit therein.

FIGS. 3A, 3B, 3C, 3D, 3E, 3F, and 3G are plan views of the multi-domain liquid crystal display device according to the second embodiment of the present invention, FIG. 3H is sectional view taken along the lines II-II' of FIG. 3A, and FIGS. 3I, 3J are entire sectional views according to the FIG. 3H.

As shown in the figures, the present invention comprises first and second substrates 31, 33, a plurality of gate bus lines 1 arranged in a first direction on the first substrate 31 and a plurality of data bus lines 3 arranged in a second direction on the first substrate 31, a common-auxiliary electrode 15, a first storage electrode 43, a TFT, a passivation layer 37, and a pixel electrode 13.

4

Data bus lines 3 and gate bus lines 1 divide the first substrate 31 into a plurality of pixel regions. The first storage electrode 43 is in the pixel region and on a same layer whereon the gate bus line 1 is formed, and is connected to or independently formed with the common-auxiliary electrode 15 to make a storage capacitor with the pixel electrode 13.

The common-auxiliary electrode 15 surrounds the pixel region and distorts electric field on a same layer whereon the gate bus line is formed.

The TFT is formed on each pixel region and comprises a gate electrode 11, a gate insulator 35, a semiconductor layer, an ohmic contact layer, and source/drain electrodes 7, 9. Passivation layer 37 is formed on the whole first substrate 31. Pixel electrode 13 is coupled to the drain electrode 9 by a contact hole 39.

On the second substrate 33, a light shielding layer 25 is formed to shield the light leaked from gate and data bus lines 1, 3, and the TFT, a color filter layer 23 is formed on the light shielding layer 25, a common electrode 17 is formed on the color filter layer 23 and electrically connects to the common-auxiliary electrode 15, and a liquid crystal layer is formed between the first and second substrates 31, 33.

The common electrode 17 has dielectric frames 53 thereon, or has electric field inducing window 51 like hole or slit in its inner part.

Further, as shown in the FIG. 3B, a third storage electrode 65 is additionally formed to enlarge the capacitance of liquid crystal display device on the gate bus line 1, so that a image flicker or a residual image could be removed.

In the FIG. 3C, all ends of the first storage electrode 43 are connected to the common-auxiliary electrode 15 and the third storage electrode 65 is formed on the common-auxiliary electrode 15 as well as the gate bus line 1, which obtains more enlarged capacitance than that in the embodiment in the FIG. 3B.

In the FIGS. 3D, 3E, 3F, and 3G, the first storage electrode 43 are patterned horizontally, vertically, and/or diagonally, or in a shape of "+" or "x", and in these embodiments, the dielectric frame 53 or electric field inducing window 51 on the second substrate is patterned as above. At this time, since the first storage electrode 43 is patterned as shown in the figures, the portions of disclination in the pixel region are covered.

In the FIGS. 3I and 3J, the common electrode 17 has dielectric frames 53 thereon, and has electric field inducing window 51 like hole or slit therein.

FIGS. 4A, 4B, 4C, 4D, 4E, 4F, and 4G are plan views of the multi-domain liquid crystal display device according to the second embodiment of the present invention, FIG. 4H is sectional view taken along the lines III-III' of FIG. 4A, and FIGS. 4I, 4J are entire sectional views according to the FIG. 4H.

In the third embodiment, a second storage electrode 63 is additionally formed on a same layer whereon the data bus line 3 is formed to the structure in the second embodiment. The second storage electrode 63 is formed at a time when the source/drain electrodes 7, 9 are formed and have a shape like the first storage electrode 43 in the pixel region.

When the second storage electrode 63 is connected to the drain electrode 9, the same voltage with the pixel electrode is applied to the second storage electrode, and then the second storage electrode forms a storage capacitor with the first storage electrode 43 related to the common-auxiliary electrode 15. When the second storage electrode 63 is

5

independently formed, this forms a storage capacitor with the pixel electrode 13 and the first storage electrode 43.

Further, as shown in the FIG. 4B, a third storage electrode 65 is additionally formed to enlarge the capacitance of liquid crystal display device on the gate bus line 1, so that a image flicker or a residual image could be removed.

In the FIG. 4C, all ends of the first storage electrode 43 are connected to the common-auxiliary electrode 15 and the third storage electrode 65 is formed on the common-auxiliary electrode 15 as well as the gate bus line 1, which obtains more enlarged capacitance than that in the embodiment in the FIG. 4B.

In the FIGS. 4D, 4E, 4F, and 4G, the first storage electrode 43 are patterned horizontally, vertically, and/or diagonally, or in a shape of "+" or "x", and in these embodiments, the dielectric frame 53 or electric field inducing window 51 on the second substrate is patterned also as above. At this time, since the first storage electrode 43 is patterned as shown in the figures, the portions of disclination in the pixel region are covered.

In the FIGS. 4I and 4J, the common electrode 17 has dielectric frames 53 thereon, and has electric field inducing window 51 like hole or slit therein.

To manufacture the multi-domain LCD of the present invention, in each pixel region on the first substrate 31, a TFT is formed comprising gate electrode 11, gate insulator 35, semiconductor layer, ohmic contact layer and source/drain electrodes 7, 9. At this time, a plurality of gate bus lines 1 and a plurality of data bus lines 3 are formed to divide the first substrate 31 into a plurality of pixel regions.

Gate electrode 11 and gate bus line 1 are formed by sputtering and patterning a metal such as Al, Mo, Cr, Ta, or Al alloy, etc. Alternatively, it is possible to form the gate electrode and gate bus line as a double layer, the double layer is formed from different materials.

At this time, common-auxiliary electrode 15 is formed surrounding the pixel region. And, the first storage electrode 43 is formed by sputtering and patterning a metal such as ITO, Al, or Cr in the pixel region. The gate insulator 35 is formed by depositing SiN_x , SiO_x , or BCB (BenzoCycloButene), acrylic resin using PECVD thereon.

The semiconductor layer and the ohmic contact layer are formed by depositing with PECVD (Plasma Enhanced Chemical Vapor Deposition), and patterning amorphous silicon (a-Si) and doped amorphous silicon (n^+ a-Si), respectively. Also, gate insulator 35, amorphous silicon (a-Si), and doped amorphous silicon (n^+ a-Si) could be formed by PECVD and patterned simultaneously.

Data bus line 3 and source/drain electrodes 7, 9 are formed by sputtering and patterning a metal such as Al, Mo, Cr, Ta, or Al alloy, etc. Alternatively, it is possible to form the data bus line and source/drain electrodes as a double layer, the double layer is formed from different materials.

At this time, a storage electrode is additionally formed in the pixel region, on the gate bus line 1 and/or common-auxiliary electrode 15 at the same time, the storage electrode makes a storage capacitor with gate bus line 1 and/or common-auxiliary electrode 15.

Subsequently, passivation layer 37 is formed with BCB (BenzoCycloButene), acrylic resin, polyimide based material, SiN_x or SiO_x on the whole first substrate 31. Pixel electrode 13 is formed by sputtering and patterning a metal such as ITO(indium tin oxide). A contact hole 39 is formed to connect the pixel electrode 13 to the drain and storage electrodes by opening and patterning a part of the passivation layer 37 on the drain electrode.

6

When common-auxiliary electrode 15, and gate bus line 1 or pixel electrode 13 are formed with the same material, the common-auxiliary and gate electrodes are simultaneously formed with one mask and connected electrically to common electrode 17, or it is possible to form them with different materials or double layer with additional masks.

On the second substrate 33, a light shielding layer 25 is formed to shield any light leakage from gate and data bus lines 1, 3, the TFT, and common-auxiliary electrode 15. A color filter layer 23 is formed R, G, B (red, green, blue) elements to alternate on the light shielding layer 25.

A common electrode 17 is formed with ITO on the color filter layer 23, and a liquid crystal layer is formed by injecting liquid crystal between the first and second substrates 31, 33. The liquid crystal layer may include liquid crystal molecules having positive or negative dielectric anisotropy. Also, the liquid crystal layer may include chiral dopants.

On the common electrode 17, dielectric frames 53 are formed by depositing photosensitive material and patterning in various shapes using photolithography. The dielectric frame 53 includes material of which dielectric constant is same or smaller than that of the liquid crystal, and the dielectric constant thereof is preferably below 3, for example, photoacrylate or BCB (BenzoCycloButene).

Furthermore, the dielectric frame 53 is formed on at least one substrate between the first and second substrates.

Alternatively, an electric field inducing window 51 is formed on at least one substrate between the first and second substrates 31, 33. At this time, the dielectric frame 53 and electric field inducing window are formed on same substrate together. The electric field inducing window 51 is formed by patterning hole or slit in the common electrode 17 or pixel electrode 13.

To apply voltage (V_{com}) to common-auxiliary electrode 15, Ag-dotting part is formed in each corner of driving area on the first substrate 31, electric field is applied with the second substrate 33, and the liquid crystal molecules are driven by the potential difference. A voltage (V_{com}) is applied to common-auxiliary electrode 15 by connecting the Ag-dotting part to the common-auxiliary electrode 15, which is accomplished simultaneously by forming the common-auxiliary electrode 15.

On at least one substrate, a compensation film 29 is formed with polymer. The compensation film 29 is a negative uniaxial film, which has one optical axis, and compensates the phase difference of the direction according to viewing-angle. Hence, it is possible to compensate effectively the right-left viewing-angle by widening the area without gray inversion, increasing contrast ratio in an inclined direction, and forming one pixel to multi-domain.

In the present multi-domain liquid crystal display device, it is possible to form a negative biaxial film as the compensation film, which has two optical axes and wider viewing-angle characteristics as compared with the negative uniaxial film. The compensation film could be formed on both substrates or on one of them.

After forming the compensation film, polarizer is formed on at least one substrate. At this time, the polarization axis of the polarizer is 45° , 135° against the alignment axis of the liquid crystal molecules, and the compensation film and polarizer are preferably composed as one. Also, it is possible to form that the optic axis of the compensation film and the polarization axis of the polarizer are parallel.

In the multi-domain LCD of the present invention, the aperture ratio is enhanced by an optimum structure design of

a "n-line" thin film transistor (U.S. Pat. No. 5,694,185) so as to reduce power consumption, increase luminance, and lower reflection, thus improving contrast ratio.

Aperture ratio is increased by forming the TFT above the gate line and providing a "n-line" TFT. The parasitic capacitor, occurring between the gate bus line and the drain electrode, can be reduced when a TFT having the same channel length as the symmetrical TFT structure is manufactured due to effect of channel length extension.

FIGS. 5A, 5B, 5C, 5D, 5E, 5F, and 5G are plan views of the multi-domain liquid crystal display devices showing various electric field inducing window or dielectric frame according to the embodiments of the present invention.

The multi-domain LCD of the present invention has a dielectric frame **53** on the pixel electrode **13**, common electrode, and/or color filter layer **23**, or an electric field inducing window **51** like a hole or slit in the pixel electrode **13**, passivation layer **37**, gate insulator **35**, color filter layer **23**, and/or common electrode by patterning, thereby electric field distortion effect and multi-domain are obtained.

That is, from forming electric field inducing window **51** or dielectric frame **53**, the multi-domain is obtained by dividing each pixel into four domains such as in a "+", "x", or "double Y" shape, or dividing each pixel horizontally, vertically, and/or diagonally, and differently alignment-treating or forming alignment directions on each domain and on each substrate.

In multi-domain LCD of the present invention, an alignment layer(not shown in the figure) is formed over the whole first and/or second substrates. The alignment layer includes a material such as polyamide or polyimide based materials, PVA (polyvinylalcohol), polyamic acid or SiO₂. When rubbing is used to determine an alignment direction, it should be possible to apply any material suitable for the rubbing treatment.

Moreover, it is possible to form the alignment layer with a photosensitive material such as PVCN (polyvinylcinnamate), PSCN (polysiloxanecinnamate), and CelCN (cellulosecinnamate) based materials. Any material suitable for the photo-aligning treatment may be used.

Irradiating light once on the alignment layer determines the alignment or pretilt direction and the pretilt angle.

The light used in the photo-alignment is preferably a light in a range of ultraviolet light, and any of unpolarized light, linearly polarized light, and partially polarized light can be used.

In the photo-alignment treatment, it is possible to apply one or both of the first and second substrates, and to apply different aligning-treatment on each substrate.

From the aligning-treatment, a multi-domain LCD is formed with at least two domains, and LC molecules of the LC layer are aligned differently one another on each domain. That is, the multi-domain is obtained by dividing each pixel into four domains such as in a "+" or "x" shape, or dividing each pixel horizontally, vertically, and/or diagonally, and differently alignment-treating or forming alignment directions on each domain and on each substrate.

It is possible to have at least one domain of the divided domains unaligned. It is also possible to have all domains unaligned.

Consequently, since the multi-domain LCD of the present invention forms the common-auxiliary electrode surrounding the pixel region and the storage electrode on a same layer whereon the gate bus line and/or the data bus line in the pixel region, it improves the aperture ratio and storage capacitor, which obtains wide viewing angle and multi-domain effect.

Moreover, when the common-auxiliary electrode is on a same layer with the gate bus line, the short between the pixel and common-auxiliary electrodes is removed, and then the yield is improved.

It will be apparent to those skilled in the art that various modifications can be made in the liquid crystal display device of the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention covers the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A multi-domain liquid crystal display device comprising:

first and second substrates facing each other;

a conductive layer distorting electric field on said first substrate;

a common-auxiliary electrode on a same layer whereon said conductive layer distorting electric field is formed;

a common electrode on said second substrate;

a liquid crystal layer between said first and second substrates; and

a storage electrode in an electric field inducing region that divides said liquid crystal layer into at least two domains.

2. The multi-domain liquid crystal display device according to claim 1, wherein said conductive layer distorting electric field is source and drain electrodes.

3. The multi-domain liquid crystal display device according to claim 2, wherein said source and drain electrodes are formed on a same layer whereon said storage electrode is formed.

4. The multi-domain liquid crystal display device according to claim 1, wherein said storage electrode is a light shielding layer.

5. The multi-domain liquid crystal display device according to claim 1, wherein said electric field inducing region is an electric field inducing window in said common electrode.

6. The multi-domain liquid crystal display device according to claim 1, wherein said electric field inducing region is a dielectric frame on said common electrode.

7. The multi-domain liquid crystal display device according to claim 1, wherein said common-auxiliary electrode includes a material selected from the group consisting of ITO (indium tin oxide), aluminum, molybdenum, chromium, tantalum, titanium, and an alloy thereof.

8. The multi-domain liquid crystal display device according to claim 1, wherein said common electrode includes ITO (indium tin oxide).

9. The multi-domain liquid crystal display device according to claim 1, further comprising:

an alignment layer on at least one substrate between said first and second substrates.

10. The multi-domain liquid crystal display device according to claim 9, wherein said alignment layer is divided into at least two portions, liquid crystal molecules in said liquid crystal layer in each portion being aligned differently from each other.

11. The multi-domain liquid crystal display device according to claim 10, wherein at least one portion of said the alignment layer is alignment-treated.

12. The multi-domain liquid crystal display device according to claim 10, wherein all portions of said the alignment layer are non-alignment-treated.

13. The multi-domain liquid crystal display device according to claim 1, wherein said liquid crystal layer includes liquid crystal molecules having positive dielectric anisotropy.

9

14. The multi-domain liquid crystal display device according to claim 1, wherein said liquid crystal layer includes liquid crystal molecules having negative dielectric anisotropy.

15. The multi-domain liquid crystal display device according to claim 1, further comprising:

a negative uniaxial film on at least one substrate between said first and second substrates.

16. The multi-domain liquid crystal display device according to claim 1, further comprising:

a negative biaxial film on at least one substrate between said first and second substrates.

17. The multi-domain liquid crystal display device according to claim 1, wherein said liquid crystal layer includes chiral dopants.

18. A multi-domain liquid crystal display device comprising:

first and second substrates facing each other;

a pixel electrode on said first substrate;

a common-auxiliary electrode on a same layer whereon said pixel electrode is formed;

a common electrode on said second substrate;

a liquid crystal layer between said first and second substrates; and

a storage electrode in an electric field inducing region that divides said liquid crystal layer into at least two domains.

19. The multi-domain liquid crystal display device according to claim 18, wherein said pixel electrode is on said storage electrode.

20. The multi-domain liquid crystal display device according to claim 18, wherein said storage electrode is a light shielding layer.

21. The multi-domain liquid crystal display device according to claim 18, further comprising:

a supplementary storage electrode in a region other than a region where said pixel electrode is formed.

22. The multi-domain liquid crystal display device according to claim 18, wherein said electric field inducing region is an electric field inducing window in said common electrode.

23. The multi-domain liquid crystal display device according to claim 18, wherein said electric field inducing region is a dielectric frame on said common electrode.

24. The multi-domain liquid crystal display device according to claim 18, wherein said electric field inducing region is an electric field inducing window in said pixel electrode.

10

25. The multi-domain liquid crystal display device according to claim 18, wherein said electric field inducing region is a dielectric frame on said pixel electrode.

26. The multi-domain liquid crystal display device according to claim 18, wherein said common-auxiliary electrode includes a material selected from the group consisting of ITO (indium tin oxide), aluminum, molybdenum, chromium, tantalum, titanium, and an alloy thereof.

27. The multi-domain liquid crystal display device according to claim 18, wherein said pixel electrode includes a material selected from the group consisting of ITO (indium tin oxide), aluminum, and chromium.

28. The multi-domain liquid crystal display device according to claim 18, wherein said common electrode includes ITO (indium tin oxide).

29. The multi-domain liquid crystal display device according to claim 18, further comprising:

an alignment layer on at least one substrate between said first and second substrates.

30. The multi-domain liquid crystal display device according to claim 29, wherein said alignment layer is divided into at least two portions, liquid crystal molecules in said liquid crystal layer in each portion being aligned differently from each other.

31. The multi-domain liquid crystal display device according to claim 30, wherein at least one portion of said the alignment layer is alignment-treated.

32. The multi-domain liquid crystal display device according to claim 30, wherein all portions of said the alignment layer are non-alignment-treated.

33. The multi-domain liquid crystal display device according to claim 18, wherein said liquid crystal layer includes liquid crystal molecules having positive dielectric anisotropy.

34. The multi-domain liquid crystal display device according to claim 18, wherein said liquid crystal layer includes liquid crystal molecules having negative dielectric anisotropy.

35. The multi-domain liquid crystal display device according to claim 18, further comprising:

a negative uniaxial film on at least one substrate between said first and second substrates.

36. The multi-domain liquid crystal display device according to claim 18, further comprising:

a negative biaxial film on at least one substrate between said first and second substrates.

37. The multi-domain liquid crystal display device according to claim 18, wherein said liquid crystal layer includes chiral dopants.

* * * * *

专利名称(译)	多域液晶显示装置		
公开(公告)号	US6680769	公开(公告)日	2004-01-20
申请号	US09/497507	申请日	2000-02-04
[标]申请(专利权)人(译)	乐金显示有限公司		
申请(专利权)人(译)	LG.PHILIPS LCD CO. , LTD.		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	LEE YUN BOK KO DOO HYUN LEE JOUN HO		
发明人	LEE, YUN BOK KO, DOO HYUN LEE, JOUN HO		
IPC分类号	G02F1/1333 G02F1/13 G02F1/139 G02F1/1362 G02F1/136 G02F1/1337 G02F1/1343 G02F1/137		
CPC分类号	G02F1/133707 G02F1/136213 G02F1/1393		
审查员(译)	KIM , 罗伯特H.		
优先权	1019990014492 1999-04-22 KR 1019990004195 1999-02-08 KR		
外部链接	Espacenet USPTO		

摘要(译)

一种多畴液晶显示装置，包括彼此面对的第一和第二基板以及在第一和第二基板之间的液晶层。导电层扭曲电场在第一基板上，并且共辅电极在同一层上，其中形成导电层扭曲电场。公共电极位于第二基板上，并且存储电极位于电场诱导区域中，该区域将液晶层分成至少两个区域。

