



US007995169B2

(12) **United States Patent**
Higa et al.

(10) **Patent No.:** **US 7,995,169 B2**
(45) **Date of Patent:** **Aug. 9, 2011**

(54) **LIQUID CRYSTAL DISPLAY DEVICE AND ELECTRONIC APPARATUS**

(75) Inventors: **Masakatsu Higa**, Chino (JP); **Hayato Kurasawa**, Matsumoto (JP)

(73) Assignee: **Sony Corporation**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1248 days.

(21) Appl. No.: **11/650,998**

(22) Filed: **Jan. 9, 2007**

(65) **Prior Publication Data**
US 2007/0177080 A1 Aug. 2, 2007

(30) **Foreign Application Priority Data**
Feb. 1, 2006 (JP) 2006-024663

(51) **Int. Cl.**
G02F 1/1335 (2006.01)
G02F 1/1343 (2006.01)

(52) **U.S. Cl.** **349/114**; 349/139

(58) **Field of Classification Search** 349/113-114, 349/139
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,119,861 B2	10/2006	Tsuchiya et al.	
7,215,392 B2	5/2007	Nakano et al.	
7,242,448 B2	7/2007	Okumura	
7,245,343 B2	7/2007	Suzuki et al.	
7,307,681 B2	12/2007	Okumura	
7,573,551 B2	8/2009	Koma et al.	
2002/0171791 A1	11/2002	Anno et al.	
2005/0001962 A1 *	1/2005	Maeda	349/114
2005/0036088 A1	2/2005	Okumura	
2005/0083453 A1	4/2005	Nakano et al.	
2005/0184939 A1	8/2005	Ueda et al.	
2006/0077323 A1 *	4/2006	Kurasawa	349/114

2006/0132684 A1 *	6/2006	Tanaka	349/114
2006/0274234 A1 *	12/2006	Takizawa	349/108
2006/0274242 A1	12/2006	Okumura	

FOREIGN PATENT DOCUMENTS

JP	A-3-245122	10/1991
JP	A 2000-047251	2/2000
JP	A 2000-047252	2/2000
JP	A 2000-047253	2/2000
JP	A-2002-287158	10/2002
JP	A-2003-279959	10/2003
JP	A-2004-219528	8/2004
JP	A-2006-11339	1/2006
KR	10-2005-0014737	2/2005
KR	10-2005-0026888	3/2005
KR	10-2005-0069957	7/2005
KR	10-2005-0086349	8/2005

OTHER PUBLICATIONS

Makoto Jisaki et al., "Development of Transflective LCD for High Contrast and Wide Viewing Angle by Using Homeotropic Alignment," Asia Display / IDW, pp. 133-136, 2001. Sang Soo Kim, "Invited Paper: The World's Largest (82-in.) TFT-LCD," Society of Information Display Digest, pp. 1842-1847, 2005.

* cited by examiner

Primary Examiner — Dung T. Nguyen

(74) Attorney, Agent, or Firm — K&L Gates LLP

(57) **ABSTRACT**

A liquid crystal display device includes a first substrate and a second substrate, a liquid crystal layer between the first and second substrates, and an alignment layer between the liquid crystal layer and at least one of the substrates. The liquid crystal layer contains liquid crystal molecules having a negative anisotropy of dielectric constant. The alignment layer aligns the liquid crystal molecules perpendicular to the substrate. The liquid crystal display device further includes pixels. Each pixel includes a plurality of subpixels expressing different colors. Each subpixel includes a stepped layer therein such that the stepped layer is disposed between the liquid crystal layer and at least one of the substrates. The stepped layer defines a first region and a second region in the subpixel. The thickness of the liquid crystal layer is relatively thick in the first region and relatively thin in the second region. The area ratio of the first region depends on a color expressed by the subpixel.

5 Claims, 6 Drawing Sheets





FIG. 1A




FIG. 1B




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5A




FIG. 5B





FIG. 6

LIQUID CRYSTAL DISPLAY DEVICE AND ELECTRONIC APPARATUS

BACKGROUND

1. Technical Field

The present invention relates to liquid crystal display devices and electronic apparatuses.

2. Related Art

As one of display devices used in mobile phones, there is known a liquid crystal display device using liquid crystal molecules aligned perpendicular to a substrate, i.e., homeotropic alignment liquid crystal display device. It is known that the homeotropic alignment liquid crystal display device has excellent viewing angle characteristics by means of multi-domain alignment. As a technique of making multiple domains, there is proposed a continuous pinwheel alignment (CPA) structure in which an opening or protrusion is formed in a transparent electrode and liquid crystal molecules are inclined in all directions, i.e., 360 degrees. The CPA structure is described in "Development of Transflective LCD for High Contrast and Wide Viewing Angle by Using Homeotropic Alignment" (Non-patent Document 1), M. Jisaki et al., Asia Display/IDW'01, pp. 133-136, 2001, and "The World's Largest (82-in.) TFT-LCD" (Non-patent Document 2), S. S. Kim et al., SID 05 DIGEST, pp. 1842-1847.

The above-described homeotropic alignment liquid crystal display devices have a challenge to improve the viewing angle characteristics in gray level. Non-patent Document 2 describes a method of dividing electrodes in each pixel to independently drive the divided electrodes. In this method, however, the load on the display device is large during driving because subpixels for red (R), green (G), and blue (B) are separately driven. In addition, since the optimum driving voltages for the R, G, and B subpixels differ from one another, a change in color depending on voltage is large.

SUMMARY

An advantage of some aspects of the invention is to provide a liquid crystal display device having a small change in color depending on viewing angle characteristics and excellent color reproducibility and an electronic apparatus including the liquid crystal display device.

According to an aspect of the invention, there is provided a liquid crystal display device including a first substrate and a second substrate, a liquid crystal layer between the first and second substrates, and an alignment layer between the liquid crystal layer and at least one of the substrates. The liquid crystal layer contains liquid crystal molecules having a negative anisotropy of dielectric constant. The alignment layer aligns the liquid crystal molecules perpendicular to the substrate. The liquid crystal display device further includes pixels. Each pixel includes a plurality of subpixels expressing different colors. Each subpixel includes a stepped layer therein such that the stepped layer is disposed between the liquid crystal layer and at least one of the substrates. The stepped layer defines a first region and a second region in the subpixel. The thickness of the liquid crystal layer is relatively thick in the first region and relatively thin in the second region. The area ratio of the first region depends on a color expressed by the subpixel.

With this structure, since a plurality of regions having different thicknesses of the liquid crystal layer are arranged in each subpixel, gray levels of the regions are mixed, leading to a gradual change in color as viewed at an angle. In other words, since the gray level characteristics of the first region is

different from that of the second region, the gray level characteristics of these regions are averaged, so that a change in color caused in one region can be compensated for in the other region. In addition, since the area ratio between the regions having different thicknesses of the liquid crystal layer varies from color to color, a shift in γ characteristics can be corrected in each color. Thus, the liquid crystal display device can provide bright display having a small change in color depending on the viewing angle characteristics and excellent color reproducibility.

According to this aspect of the invention, preferably, the area ratio of the first region in the subpixel is larger as the wavelength of the color expressed by the subpixel is longer.

Generally, as the wavelength of a light component is shorter, a change in phase of the light component transmitting through a liquid crystal layer is larger. Regarding the voltage-transmittance characteristics, as the wavelength of a light component is shorter, a smaller voltage causes a change in transmittance. If the stepped layer is formed at the same area ratio of the first region in each of the subpixels of respective colors, a change in transmittance of a light component having a long wavelength may be insufficient. In accordance with this aspect of the invention, as the wavelength of a color light component is longer, the stepped layer is formed such that the area ratio of the first region is larger. Consequently, the change in transmittance does not vary from color to color. Thus, the liquid crystal display device with good color balance can be provided.

In accordance with this aspect of the invention, preferably, the liquid crystal display device further includes a plurality of electrodes on respective surfaces of the first and second substrates close to the liquid crystal layer. The electrodes drive the liquid crystal molecules. Each subpixel includes the electrode on at least one of the substrates. The electrode includes a plurality of island portions and a linking portion electrically connecting the adjacent island portions. The linking portion is two-dimensionally superimposed on a boundary region of the stepped layer.

With this arrangement, since the electrode in each subpixel includes a plurality of island portions, an oblique electric field generated on the end of each island portion upon application of a voltage controls homeotropic alignment of liquid crystal molecules such that the liquid crystal molecules are inclined toward the center of the island portion, thus forming a plurality of liquid crystal domains each having radial alignment of the liquid crystal molecules in a flat area of the corresponding island portion. As described above, a plurality of liquid crystal domains each having planar radial alignment are formed in each subpixel. Consequently, the viewing angle characteristics can be uniformed in all directions in each liquid crystal domain. The border between the liquid crystal domains is fixed to that between the adjacent island portions. Thus, a stain or chrominance non-uniformity is not caused as a display panel is viewed at an angle. Display with good quality can be obtained. In accordance with this aspect of the invention, the boundary region of the stepped layer in each subpixel is two-dimensionally superimposed on the linking portion for electrical connection between the adjacent island portions. Consequently, deterioration of display quality caused by a stepped structure can be effectively prevented. The liquid crystal molecules are aligned along an inclined surface of the stepped layer in the boundary region thereof. If the electrodes are disposed in the boundary region, an oblique electric field is generated upon application of a voltage, so that the alignment of the liquid crystal molecules may be disturbed. In accordance with this aspect of the invention, since the linking portion is disposed in the boundary region of the stepped layer

so that the area of the electrodes is reduced as much as possible, deterioration of display quality caused by the boundary region can be minimized.

According to this aspect of the invention, the liquid crystal display device may further include a light-shielding layer on at least one of the first and second substrates. Preferably, the light-shielding layer is two-dimensionally superimposed on the boundary region of the stepped layer in the subpixel.

With this arrangement, the alignment of the liquid crystal molecules in the boundary region of the stepped layer can be prevented from being disturbed. Thus, the liquid crystal display device can provide display with higher display quality.

According to another aspect of the invention, there is provided a liquid crystal display device including a first substrate and a second substrate, a liquid crystal layer between the first and second substrates, and an alignment layer between the liquid crystal layer and at least one of the substrates. The liquid crystal layer contains liquid crystal molecules having a negative anisotropy of dielectric constant. The alignment layer aligns the liquid crystal molecules perpendicular to the substrate. The liquid crystal display device further includes pixels. Each pixel includes a plurality of subpixels. Each subpixel has a transmissive display area for transmissive display and a reflective display area for reflective display. The subpixel includes a stepped layer therein such that the stepped layer is disposed between the liquid crystal layer and at least one of the substrates. The stepped layer defines a first region and a second region in the transmissive display area of the subpixel. The thickness of the liquid crystal layer is relatively thick in the first region and relatively thin in the second region. The area ratio of the first region depends on a color expressed by the subpixel. The subpixel may further include a thickness adjusting layer therein such that the thickness adjusting layer is disposed between the liquid crystal layer and at least one of the first and second substrates. The thickness adjusting layer makes the thickness of the liquid crystal layer in the reflective display area less than that in the transmissive display area. It is preferred that the stepped layer be disposed in the transmissive display area and the stepped layer and the thickness adjusting layer be made of the same material.

With this arrangement, the liquid crystal display device uses a multi-gap structure in which the thickness of the liquid crystal layer (i.e., the cell gap) in the transmissive display area is different from that in the reflective display area. Consequently, good display characteristics can be obtained in both of transmissive and reflective display modes. In addition, since the stepped layer and the thickness adjusting layer are made of the same material, these layers can be formed by the same process, leading to ease of manufacture.

According to this aspect of the invention, it is preferred that the thickness of the liquid crystal layer in the second region be approximately equal to that in the reflective display area.

With this arrangement, the stepped layer and the thickness adjusting layer can be formed more easily.

According to further another aspect of the invention, there is provided an electronic apparatus including the liquid crystal display device in accordance with any of the above-described aspects of the invention.

With this structure, the electronic apparatus having a small change in color depending on viewing angle characteristics and excellent color reproducibility can be provided.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be described with reference to the accompanying drawings, wherein like numbers reference like elements.

FIGS. 1A and 1B are diagrams showing the entire structure of a liquid crystal display device according to a first embodiment of the invention.

FIG. 2 is a circuit diagram of the liquid crystal display device.

FIG. 3A is a plan view of one pixel of the liquid crystal display device.

FIG. 3B is a cross-sectional view at the line IIIB-IIIB of FIG. 3A.

FIGS. 4A to 4C are schematic plan views showing other stepped structures.

FIG. 5A is a plan view of one pixel of a liquid crystal display device in accordance with a second embodiment of the invention.

FIG. 5B is a cross-sectional view at the line VB-VB of FIG. 5A.

FIG. 6 is a perspective view illustrating an electronic apparatus.

DESCRIPTION OF EXEMPLARY EMBODIMENTS

Embodiments of the invention will be described below with reference to the drawings. The technical scope of the invention is not limited to the following embodiments. In each figure referred to in the following description, respective components are shown on an arbitrary scale changed as appropriate so that the components are easy to see.

In the following description, a side of each component close to a liquid crystal layer in a liquid crystal display device will be called an "inner side" and the opposite side thereof will be called an "outer side". The minimum unit for image display will be called a "subpixel". A group of subpixels having respective color filters will be called a "pixel". A "non-selective voltage application mode" means a mode in which a voltage applied to the liquid crystal layer is close to a threshold voltage of liquid crystal" and a "selective voltage application mode" means a mode in which a voltage applied to the liquid crystal layer is higher than the liquid-crystal threshold voltage. In the following embodiments, in a planar region of each subpixel in a transmissive liquid crystal display device, an area where display can be performed using light coming from a display surface of the liquid crystal display device will be called a "reflective display area" and an area where display can be performed using light coming from a rear surface (the side opposite to the display surface) of the liquid crystal display device will be called a "transmissive display area".

First Embodiment

A liquid crystal display device **100** according to a first embodiment of the invention will now be described with reference to FIGS. 1A to 3. The liquid crystal display device **100** in accordance with the present embodiment is an active matrix type using a thin film transistor (hereinafter, TFT) as each pixel switching element.

FIG. 1A is a plan view of the liquid crystal display device, respective components being viewed from a counter substrate. FIG. 1B is a cross-sectional side view of the device at the line IB-IB of FIG. 1A.

Referring to FIGS. 1A and 1B, in the liquid crystal display device **100** of the present embodiment, a TFT array substrate **10** and a counter substrate **20** are joined by a seal **52**. A space between the substrates **10** and **20** defined by the seal **52** is filled with liquid crystal, thus providing a liquid crystal layer **50**. In a peripheral circuit area outside the seal **52**, a data

signal driving circuit **101** and external circuit connecting terminals **102** are arranged along one side of the TFT array substrate **10**. A scanning signal driving circuit **104** is arranged on each side adjacent to the above-mentioned one side. A plurality of pixel electrodes **9** are arranged on the inner surface of the TFT array substrate **10** and a common electrode **21** is disposed on the inner surface of the counter substrate **20** such that the pixel electrodes **9** face the common electrode **21** with the liquid crystal layer **50** therebetween. In each corner of the counter substrate **20**, an inter-substrate conductive member **106** for conduction between the TFT array substrate **10** and the counter substrate **20** is arranged.

FIG. **2** is an equivalent circuit diagram of the liquid crystal display device **100** using TFTs. In an image display area of the liquid crystal display device **100**, data lines **6a** and scanning lines **3a** are arranged in a lattice. In the vicinity of each intersection of the lines **6a** and **3a**, a subpixel serving as an image display unit is arranged. The pixel electrodes **9** are provided for the respective subpixels arranged in a matrix. A TFT **30**, serving as a switching element for controlling power supply to the corresponding pixel electrode **9**, is arranged in the vicinity of each pixel electrode **9**. The source of each TFT **30** is electrically connected to the data line **6a**. Image signals **S1**, **S2**, . . . , and **Sn** are supplied to the respective data lines **6a**. The gate of each TFT **30** is electrically connected to the scanning line **3a**. Scanning signals **G1**, **G2**, . . . , and **Gm** are supplied as pulse signals to the respective scanning lines **3a** at predetermined timing. The drain of each TFT **30** is electrically connected to the pixel electrode **9**. When the TFTs **30**, serving as the switching elements, are turned on for a predetermined period in response to the scanning signals **G1**, **G2**, . . . , and **Gm** supplied from the respective scanning lines **3a**, the image signals **S1**, **S2**, . . . , and **Sn** supplied from the respective data lines **6a** are written in liquid crystal in the respective subpixels at predetermined timing.

The image signals **S1**, **S2**, . . . , and **Sn**, each having a predetermined level, written in liquid crystal are held by liquid crystal capacitors between the respective pixel electrodes **9** and the common electrode **21**, which will be described later, for a predetermined period of time. To prevent leakage of the held image signals **S1**, **S2**, . . . , and **Sn**, a storage capacitor **70** is arranged between each pixel electrode **9** and the corresponding capacitor line **3b**. The storage capacitor **70** and the associated liquid crystal capacitor are arranged in parallel. As described above, when a voltage signal is applied to liquid crystal, the orientation of liquid crystal molecules changes depending on a level of the applied voltage. Thus, light incident on the liquid crystal is modulated, thus providing grayshade.

FIGS. **3A** and **3B** are diagrams explaining the liquid crystal display device **100** according to the present embodiment. FIG. **3A** is a plan view of a certain pixel in the liquid crystal display device **100**. FIG. **3B** is a cross-sectional view at the line IIIB-IIIIB of FIG. **3A**.

Referring to FIG. **3A**, each pixel of the liquid crystal display device **100** includes three subpixels **SP1** to **SP3** arranged in the Y-axis direction. Each of the flat rectangular subpixels **SP1** to **SP3** includes the pixel electrode **9** and the TFT **30**, serving as a pixel switching element. The data lines **6a** extend in the lateral direction (X-axis direction). The scanning lines **3a** extend in the longitudinal direction (Y-axis direction). Each TFT **30** is arranged in the vicinity of the intersection of the data line **6a** and the scanning line **3a** and is electrically connected to the data line **6a** and the scanning line **3a**.

A color filter (colored layer) **22** having any of three primary colors is arranged for each subpixel. The three subpixels **SP1** to **SP3** constitute one pixel having the three color filters. The

color filters **22R**, **22G**, and **22B** form a stripe pattern such that the respective filters extend in the X-axis direction. In other words, each color filter extends over a plurality of subpixels in the X-axis direction and the color filters of each color are arranged at predetermined intervals in the Y-axis direction. A rectangular frame-shaped black matrix (light-shielding film) **22BM** is arranged around the respective color filters **22** such that the black matrix **22BM** surrounds the subpixels **SP1**.

Referring to FIG. **3A**, the pixel electrode **9** arranged in each of the subpixels **SP1** to **SP3** is divided into two island portions **91** and **92**. The adjacent island portions **91** and **92** are connected through a linking portion **9c**. Each of the island portions **91** and **92** includes a transparent conductive layer made of, for example, indium tin oxide (ITO). A region, where these island portions **91** and **92** are arranged, serves as a transmissive display area. Each linking portion **9c** connecting the island portions **91** and **92** includes a transparent conductive layer made of, for example, ITO. Accordingly, the linking portion **9c** contributes to transmissive display. The island portions **91** and **92** each have a curved shape with rounded corners. Each of the island portions **91** and **92** may have a substantially octagonal shape with chamfered corners. A dielectric protrusion **551** is arranged substantially at the center of each island portion **91**. A dielectric protrusion **552** is arranged substantially at the center of each island portion **92**. The dielectric protrusions **551** and **552** function so as to control the alignment of liquid crystal molecules.

Referring to FIG. **3B**, the liquid crystal display device **100** includes the TFT array substrate **10** and the counter substrate **20** facing the substrate **10**. The liquid crystal layer **50** including liquid crystal having a negative anisotropy of dielectric constant (and having an anisotropy of refractive index Δn of, for example, 0.1) is sandwiched between the substrates **10** and **20**. As shown in FIG. **3B**, the liquid crystal layer **50** has a substantially uniform thickness within an area in which the pixel electrode **9** is arranged. A backlight **90** having a light source, a reflector, a light guide plate constituting an illumination system is arranged on the outer surface of the TFT array substrate **10**, i.e., outside a liquid crystal display cell. Oval bars, shown at **51**, conceptually denote liquid crystal molecules aligned perpendicular to the dielectric protrusions **551** and **552** under the influences of the dielectric protrusions **551** and **552**.

The TFT array substrate **10** includes a base **10A** made of a light-transmissive material, such as quartz or glass. On the inner surface (close to the liquid crystal layer **50**) of the base **10A**, a circuit layer **19** including the TFT **30** is arranged. The pixel electrode **9** is disposed on the circuit layer **19**. A homeotropic alignment layer **15** made of, for example, polyimide is arranged over the pixel electrode **9** and the circuit layer **19**. When a voltage is not applied, the homeotropic alignment layer **15** allows the liquid crystal molecules **51** to be aligned perpendicular to the surface of the substrate **10**. A first retardation film **36** and a first polarizer **14** are laminated on the outer surface of the base **10A**.

The counter substrate **20** includes a base **20A** made of a light-transmissive material, such as quartz or glass. On the inner surface of the base **20A**, the color filter **22** is arranged. The color filters **22** include a plurality of colored layers having different colors. The black matrix **22BM** made of, for example, black resin is arranged between the color filters having different colors.

A stepped layer **34** is selectively arranged on the inner surface of each color filter **22** such that the layer **34** is opposed to a region where the island portion **92** is arranged. The stepped layer **34** arranged partially in each subpixel makes the thickness of the liquid crystal layer **50** in a first region **E1**,

where the island portion **91** is arranged, different from that in a second region **E2** where the island portion **92** is arranged. The stepped layer **34** is made of an organic material, such as acrylic resin. The thickness of the liquid crystal layer **50** in a portion (the second region **E2**), where the stepped layer **34** is arranged, is approximately $\frac{1}{2}$ to $\frac{2}{3}$ of that in a portion (the first region **E1**) where the stepped layer **34** is not disposed. In other words, the stepped layer **34** makes the thickness of the liquid crystal layer **50** in the first region **E1** different from that in the second region **E2** and also provides an intra-pixel stepped structure.

When a plurality of regions having different thicknesses of the liquid crystal layer exist in each transmissive display area, the gray levels of these regions are mixed, resulting in a gradual change in color as viewed at an angle. In other words, since the gray level characteristics of the first region **E1** differs from those of the second region **E2**, the gray level characteristics of these regions are averaged, so that a change in color caused in one region can be compensated for in the other region.

The plane area of the stepped layer **34** depends on a color expressed by each subpixel. As the wavelength of a color expressed by the subpixel is longer, the area ratio of the first region **E1** in the subpixel is larger. In the present embodiment, the subpixels **SP1** to **SP3** express red (R), green (G), and blue (B), respectively. The relationship among the subpixels **SP1** to **SP3** in the area ratio of the first region **E1** is expressed as **SP1** (R)>**SP2** (G)>**SP3** (B).

In the vicinity of the boundary between the first and second regions **E1** and **E2**, an inclined surface where the thickness of the stepped layer **34** gradually varies is arranged. The inclined surface is two-dimensionally substantially superimposed on the edge of the island portion **92** close to the island portion **91** and is also two-dimensionally superimposed on the linking portion **9c**. Alternatively, the linking portion **9c** may be extended so that the edges of the island portions **91** and **92** are slightly separated from a boundary region of the stepped layer **34**. Since the orientation of liquid crystal is disturbed in the vicinity of the inclined surface, the black matrix **22BM** is arranged so as to be two-dimensionally superimposed on the inclined surface, thus preventing leakage of light from a portion corresponding to the inclined surface. When the area of the black matrix **22BM** is larger than that of the inclined surface, the leakage of light can be prevented more effectively. In this case, the intensity of transmitting light is slightly reduced. However, since the linking portion **9c** does not significantly contribute on brightness, display quality is not significantly degraded.

The common electrode **21** is arranged over the color filter **22** and the stepped layer **34** on the inner surface of the base **20A**. The dielectric protrusions **551** and **552** are arranged on the common electrode **21** opposed to the pixel electrode **9** such that the dielectric protrusions **551** and **552** protrude in the liquid crystal layer **50**. Referring to FIG. 3B, each of the dielectric protrusions **551** and **552** has a substantially triangular shape in cross section. The dielectric protrusions **551** and **552** actually each have a gradually curved cross section. In the first region **E1**, the dielectric protrusion **551** is opposed to central part of the island portion **91**. In the second region **E2**, the dielectric protrusion **552** is opposed to central part of the island portion **92**. The dielectric protrusions **551** and **552** are arranged in the X-axis direction along the arrangement of the island portions **91** and **92**. In addition, a homeotropic alignment layer **25** made of, for example, polyimide is arranged over the common electrode **21** and the dielectric protrusions **551** and **552**. The homeotropic alignment layer **25**

allows the liquid crystal molecules **51** to be aligned perpendicular to the surface of the substrate **20** when a voltage is not applied.

A second retardation film **46**, serving as a $\lambda/4$ retardation film, and a second polarizer **24** are laminated on the outer surface of the base **20A**.

In the liquid crystal display device **100** with the above-described structure in accordance with the present embodiment, light radiated from the backlight **90** is converted to circularly polarized light through the first polarizer **14** and the first retardation film **36** and is then incident on the liquid crystal layer **50**. Since the liquid crystal aligned perpendicular to the substrate substantially has no anisotropy of refractive index when a voltage is not applied, the incident light travels in the liquid crystal layer **50** while maintaining a circularly polarized state. The light passing through the second retardation film **46** on the counter substrate **20** is converted to linearly polarized light that is orthogonal to the polarization axis of the second polarizer **24**. The linearly polarized light does not transmit through the second polarizer **24**. Consequently, the liquid crystal display device **100** according to the present embodiment provides black display (normally black mode) when a voltage is not applied.

On the other hand, when a voltage is applied to the liquid crystal layer **50**, the liquid crystal molecules are aligned along the surface of the substrate, so that the liquid crystal has the anisotropy of refractive index. Consequently, the circularly polarized light incident from the backlight **90** on the liquid crystal layer **50** is converted to elliptically polarized light through the liquid crystal layer **50**. When the incident light passes through the second retardation film **46**, the light is not converted to linearly polarized light which is orthogonal to the polarization axis of the second polarizer **24**. The whole or part of the incident light passes through the second polarizer **24**. The liquid crystal display device **100** according to the present embodiment, therefore, provides white display upon application of a voltage. In the above-described structure, a voltage applied to the liquid crystal layer **50** is controlled, thus enabling grayshade. At that time, in the present embodiment, since the strip-shaped dielectric protrusions **551** and **552** extend on the common electrode **21**, the liquid crystal molecules **51** are inclined outwardly from each of the dielectric protrusions **551** and **552** in the Y axis in the vicinity of each of the dielectric protrusions **551** and **552**. As for an area from the periphery of each of the dielectric protrusions **551** and **552** to the edge of the corresponding island portion, the liquid crystal molecules **51** are inclined radially. In the liquid crystal display device **100** in accordance with the present embodiment, therefore, a plurality of liquid crystal domains with different directors of the liquid crystal molecules **51** are provided upon application of a voltage. Thus, display with a remarkably wide viewing angle can be realized.

Further, the boundary between the liquid crystal domains is fixed to the boundary between the adjacent island portions. Consequently, when the liquid crystal display panel is viewed at an angle, a stain or chrominance non-uniformity is not caused. Display with good quality can be provided. In addition, the boundary region of each stepped layer **34** is two-dimensionally superimposed on the linking portion **9c** for electrical connection between the adjacent island portions. Thus, deterioration of display quality caused by the stepped structure can be effectively prevented. When the linking portion **9c** is extended so that the facing ends of the island portions **91** and **92** are slightly separated from the boundary region of the stepped layer **34**, the above-described deterioration can be more effectively prevented. The reason is as follows. The liquid crystal molecules **51** are aligned along the

inclined surface of the stepped layer **34**. If the electrodes are arranged in the boundary region of the stepped layer **34**, an oblique electric field occurs upon application of a voltage. The alignment of liquid crystal molecules may be disturbed. In the present embodiment, since the area of the electrodes is reduced as much as possible in the boundary region of the stepped layer **34**. Thus, deterioration of display quality in the boundary region of each stepped layer **34** can be effectively prevented.

Since the regions **E1** and **E2** having different thicknesses of the liquid crystal layer is arranged in each subpixel, the gray levels of the regions **E1** and **E2** with different gray-level display performances are mixed, thus reducing a change in gray level depending on a viewing angle. Particularly, in the present embodiment, the area ratio between the regions **E1** and **E2** having different thicknesses of the liquid crystal layer varies from color to color. Accordingly, a shift in γ characteristics can be corrected in each color. Thus, bright display having a small change in color depending on the viewing angle characteristics and excellent color reproducibility can be realized. As the wavelength of a light component is shorter, a change in phase of the light component transmitting through the liquid crystal layer is larger. Regarding the voltage-transmittance characteristics, as the wavelength of a light component is shorter, a change in transmittance is caused upon application of a smaller voltage. If the stepped layers are formed at the same area ratio of the first region **E1** in the respective R, G, and B subpixels **SP1** to **SP3**, a change in transmittance with respect to a light component R having a long wavelength may be insufficient. In the present embodiment, as the wavelength of a color light component is longer, the stepped layer **34** is formed such that the area ratio of the first region **E1** in the corresponding subpixel is larger. Consequently, the change in transmittance does not vary from color to color. Thus, the liquid crystal display device with good color balance can be provided.

In the present embodiment, the R, G, and B subpixels have different area ratios of the first region **E1**. So long as at least two color subpixels have different area ratios, the viewing angle characteristics in gray level can be improved. FIGS. **4A** to **4C** are diagrams of other examples of the stepped layers **34**. The present embodiment uses the arrangement of FIG. **4A**. The arrangement of FIG. **4B** or **4C** may be used. Referring to FIG. **4B**, the area of the stepped layer **34** in the subpixel **SP2** is different from that in the subpixel **SP3**. Those areas can be equalized. In FIG. **4A**, similarly, the area of the stepped layer **34** in the subpixel **SP1** can be equal to that in the subpixel **SP2**. Alternatively, the area of the stepped layer **34** in the subpixel **SP2** can be equal to that in the subpixel **SP3**.

In the present embodiment, the dielectric protrusions on the common electrode are used as alignment controllers. As another alignment controller, a slit (opening) may be used. Each opening is formed in the common electrode by partially cutting the common electrode. In this case, although the action of the opening is different from that of the dielectric protrusion, the effect of controlling the orientation of liquid crystal molecules upon application of an electric field can be obtained. Alternatively, the opening and the dielectric protrusion may be arranged together in each subpixel. Assuming that the plane area of the opening is equal to that of the dielectric protrusion, generally, alignment controlling force caused by the dielectric protrusion is stronger than that caused by the opening. Accordingly, it is preferred that the opening be arranged in each of the reflective display area and the second region **E2**, where the liquid crystal layer is thin, of the transmissive display area and the dielectric protrusion be arranged in the first region **E1**, where the liquid crystal layer

is thick, of the transmissive display area. Further, a dielectric protrusion may be arranged within the opening.

Second Embodiment

A second embodiment of the invention will now be described.

FIG. **5A** is a plan view of each pixel of a liquid crystal display device **200** in accordance with the present embodiment. FIG. **5B** is a cross-sectional view at the line VB-VB of FIG. **5A**. The same components and portions as those in the first embodiment are designated by the same reference numerals and a detailed description thereof is omitted.

Referring to FIG. **5A**, the liquid crystal display device **200** of the present embodiment is an active matrix transmissive liquid crystal display in which a reflecting electrode **393** is partially arranged in each of subpixels **SP1** to **SP3** and a TFT **30** is arranged as a switching element in each subpixel.

A pixel electrode **39** is arranged in each subpixel. The pixel electrode **39** includes three island portions **391**, **392**, and **393** which are electrically connected through linking portions **39c**. The island portions **391**, **392**, and **393** are arranged in this order in the lengthwise direction of each pixel electrode **39**. The two island portions **391** and **392** from the left of each pixel electrode **39** in FIG. **5A** serve as transparent electrodes each including a transparent conductive layer made of, for example, ITO. The island portion **393** on the right of each pixel electrode **39** serves as a reflecting electrode including a reflective metal layer made of, for example, aluminum or silver.

The island portion **393**, including the reflective metal layer of aluminum or silver, functions as a reflecting layer in each subpixel. A region where the island portion **393** is arranged serves as a reflective display area. An insulating layer **16** is selectively arranged in each reflective display area on a circuit layer **19**. The island portion **393** is arranged on the insulating layer **16** in each reflective display area. The insulating layer **16** has an uneven surface. The island portion **393** has an uneven surface along the uneven surface of the insulating layer **16**. Reflected light is scattered by the uneven surface, thus providing display with excellent visibility.

A region, where the island portions **391** and **392** functioning as the transparent electrodes are arranged, serves as a transmissive display area. In the liquid crystal display device **200** in accordance with the present embodiment, approximately $\frac{1}{3}$ of the displayable area of each subpixel contributes to reflective display and the remaining $\frac{2}{3}$ thereof contributes to transmissive display. The linking portions **39c** connecting the island portions **391**, **392**, and **393** each include a transparent conductive layer made of, for example, ITO. The linking portions **39c**, therefore, contribute to transmissive display. Dielectric protrusions **561**, **562**, and **563**, each serving as an alignment controller for controlling the alignment of liquid crystal molecules, are arranged in substantially central parts of the island portions **391**, **392**, and **393**, respectively. In the present embodiment, the island portions **391**, **392**, and **393** each have a curved shape with rounded corners. Each island portion may have a substantially octagonal shape with chamfered corners.

Referring to FIG. **5B**, the liquid crystal display device **200** includes a TFT array substrate **10** and a counter substrate **20** facing the substrate **10**. A liquid crystal layer **50** contains liquid crystal having a negative anisotropy of dielectric constant. The liquid crystal layer **50** is sandwiched between the substrates **10** and **20**. A backlight **90** is arranged on the outer surface of the TFT array substrate **10**, i.e., outside a liquid crystal display cell.

The TFT array substrate **10** includes a base **10A**. The circuit layer **19** similar to that of the first embodiment is arranged on the inner surface (close to the liquid crystal layer **50**) of the base **10A**. The pixel electrode **39**, including the island portions **391** and **392** (the transparent electrodes) and the island portion **393** (the reflecting electrode), is disposed on the circuit layer **19**. The insulating layer **16** is arranged between the circuit layer **19** and the island portion **393**. The surface of the insulating layer **16** is partially uneven. The island portion **393** is arranged in a region with the uneven surface. The pixel electrode **39** and the circuit layer **19** are covered with a homeotropic alignment layer **15** made of, for example, polyimide. When a voltage is not applied, the homeotropic alignment layer **15** allows liquid crystal molecules **51** to be aligned perpendicular to the surface of the substrate **10**. A first retardation film **36**, serving as a $\lambda/4$ retardation film, and a first polarizer **14** are laminated on the outer surface of the base **10A**.

The counter substrate **20** includes a base **20A**. On the inner surface of the base **20A**, a color filter **22** is arranged over the reflective display area and the transmissive display area in each subpixel. The color filters **22** include a plurality of colored layers having different colors. A black matrix **22BM** made of, for example, black resin is arranged between the colored filters having different colors.

On the inner surface of each color filter **22**, a stepped layer **34** is arranged in a region where the island portion **391** is formed in the transmissive display area (where the island portions **391** and **392** are arranged). In addition, on the inner surface of the color filter **22**, a thickness adjusting layer **35** for thickness adjustment of the liquid crystal layer is arranged so as to correspond to the reflective display area (where the island portion **393** is disposed). In each of the subpixels SP1 to SP3, a second region E2 where the stepped layer **34** is arranged, a first region E1 where the stepped layer **34** is not arranged, and the reflective display area where the thickness adjusting layer **35** is disposed are arranged in this order in the lengthwise direction of the subpixel. In other words, the stepped layer **34** and the thickness adjusting layer **35** are arranged on both ends of each subpixel, thus providing a stepped structure. Consequently, the thickness of the liquid crystal layer **50** is made different between the reflective display area and the first region E1 by the thickness adjusting layer **35** selectively arranged in each subpixel and is also made different between the first region E1 and the second region E2 by the stepped layer **34** selectively arranged.

The thickness adjusting layer **35** is made of an organic material, such as acrylic resin. The thickness of the layer **35** is set to about $2\pm 1\ \mu\text{m}$. The thickness of the liquid crystal layer **50** in the transmissive display area segment E1, where neither the thickness adjusting layer **35** nor the stepped layer **34** are arranged, is about $2\ \mu\text{m}$ to about $6\ \mu\text{m}$. The thickness of the liquid crystal layer **50** in the reflective display area is about half of that in the transmissive display area segment E1. In other words, the thickness adjusting layer **35** makes the thickness of the liquid crystal layer **50** in the reflective display area different from that in the transmissive display area segment E1 and also provides a multi-gap structure.

The stepped layer **34** is made of the same material as that of the thickness adjusting layer **35**. In other words, the stepped layer **34** is formed by the same process as that for the thickness adjusting layer **35**. The stepped layer **34** made of the same organic material, such as acrylic resin, as that of the thickness adjusting layer **35** is arranged in the second region E2 in the transmissive display area. The stepped layer **34** makes the thickness of the liquid crystal layer **50** in the first region E1 different from that in the second region E2.

The plane area of the stepped layer **34** depends on a color expressed by each subpixel. As the wavelength of a color expressed by the subpixel is longer, the area ratio of the first region E1 is larger in the subpixel. In the present embodiment, the subpixels SP1 to SP3 express red (R), green (G), and blue (B), respectively. The relationship among the subpixels SP1 to SP3 in the area ratio of the first region E1 is expressed as $\text{SP1 (R)} > \text{SP2 (G)} > \text{SP3 (B)}$.

The stepped layer **34** and the thickness adjusting layer **35** can be formed by applying, for example, a photosensitive resin to the whole surface of the substrate **20** and removing the resin in each first region E1 using development and exposure. Referring to FIG. 5B, the thickness of the stepped layer **34** is approximately equal to that (i.e., about $2\pm 1\ \mu\text{m}$) of the thickness adjusting layer **35**. In other words, the thickness of the liquid crystal layer **50** in the second region E2 of the transmissive display area is approximately equal to that in the reflective display area. In this case, it is unnecessary to perform an additional process of adjusting the thickness of the liquid crystal layer **50** in the transmissive display area, leading to ease of manufacture. The stepped layer **34** and the thickness adjusting layer **35** may be made different from each other in thickness by controlling the amount of exposure.

The liquid crystal display device **200** with the above-described structure in accordance with the present embodiment can provide bright and high-contrast display. In addition, the liquid crystal display device **200** has excellent viewing angle characteristics in gray level in a transmissive display mode. In the vicinity of the boundary between the reflective display area and the first region E1 in each subpixel, an inclined surface where the thickness of the thickness adjusting layer **35** gradually changes is arranged. The inclined surface is two-dimensionally substantially superimposed on the end of the reflecting electrode **393** close to the transparent electrode **392** and is also two-dimensionally superimposed on the linking portion **39c**. Alternatively, the linking portion **39c** may be extended such that the edges of the island portions **392** and **393** are slightly separated from a boundary region of the thickness adjusting layer **35**. In the inclined surface, an oblique electric field occurs upon application of a voltage, so that the alignment of the liquid crystal molecules may be disturbed. In the present embodiment, the narrow linking portion **39c** serves as the pixel electrode corresponding to the inclined surface. The area of the electrodes is reduced as much as possible in the boundary region of the thickness adjusting layer **35**. Thus, deterioration of display quality can be minimized.

Further, a common electrode **21** is arranged on the inner surface of the base **20A** such that the color filter **22**, the stepped layer **34**, and the thickness adjusting layer **35** of each subpixel are covered with the common electrode **21**. The dielectric protrusions **561** to **563** are arranged on the common electrode **21** such that the dielectric protrusions face each pixel electrode **39** and protrude in the liquid crystal layer **50**. Referring to FIG. 5B, each of the dielectric protrusions **561** to **563** has a substantially triangular shape in cross section. Actually, the dielectric protrusions **561** to **563** each have a gradually curved cross section. In the transmissive display area, the dielectric protrusions **561** and **562** are opposed to central parts of the transparent electrodes **391** and **392**, respectively. In the reflective display area, the dielectric protrusion **563** is opposed to central part of the reflecting electrode **393**. The dielectric protrusions **561**, **562**, and **563** are arranged in the X-axis direction along the arrangement of the transparent electrodes **391** and **392** and the reflecting electrode **393**. In addition, the dielectric protrusions **561** to **563** and the common electrode **21** are covered with a homeotropic

alignment layer **25** made of, for example, polyimide. The homeotropic alignment layer **25** allows the liquid crystal molecules **51** to be aligned perpendicular to the surface of the substrate **20** when a voltage is not applied. A second retardation film **46**, serving as a $\lambda/4$ retardation film, and a second polarizer **24** are laminated on the outer surface of the base **20A**.

In the liquid crystal display device **200** with the above-described structure in accordance with the present embodiment, the display operation in a transmissive mode is the same as that in the first embodiment. In other words, the liquid crystal molecules **51** are inclined outwardly from each of the dielectric protrusions **561** and **562** in the Y axis in the vicinity of each of the dielectric protrusions **561** and **562**. As for an area from the periphery of each of the dielectric protrusions **561** and **562** to the edge of the corresponding island portion, the liquid crystal molecules **51** are inclined radially. Therefore, a plurality of liquid crystal domains with different directors of the liquid crystal molecules **51** are provided upon application of a voltage. Thus, display with a remarkably wide viewing angle can be realized. In addition, since the regions E1 and E2 having different thicknesses of the liquid crystal layer are arranged in each subpixel, the gray levels of the regions E1 and E2 with different gray-level display performances are mixed, thus reducing a change in the gray level depending on a viewing angle. Particularly, since the area ratio between the regions E1 and E2 having different thicknesses of the liquid crystal layer varies from color to color in the present embodiment, a shift in γ characteristics can be corrected in each color. Thus, bright display having a small change in color depending on the viewing angle characteristics and excellent color reproducibility can be realized.

In a reflective mode, external light radiated from the outside of the counter substrate **20** is converted to circularly polarized light through the second polarizer **24** and the second retardation film **46** and is then incident on the liquid crystal layer **50**. Since the liquid crystal aligned perpendicular to the substrate substantially has no anisotropy of refractive index when a voltage is not applied, the incident light travels in the liquid crystal layer **50** while maintaining a circularly polarized state and then reaches the reflecting electrode **393**. The light is reflected by the reflecting electrode **393** and is then returned to the liquid crystal layer **50**. The reflected light is again incident on the second retardation film **46**. At that time, the direction of rotation of the circularly polarized light reflected through the reflecting electrode **393** is reversed. Accordingly, the light is converted through the second retardation film **46** to linearly polarized light that is orthogonal to the polarization axis of the second polarizer **24**. The linearly polarized light does not transmit through the second polarizer **24**. Consequently, the liquid crystal display device **200** in accordance with the present embodiment provides black display (normally black mode) when a voltage is not applied.

On the other hand, when a voltage is applied to the liquid crystal layer **50**, the liquid crystal molecules are aligned along the surface of the substrate, so that the liquid crystal has the anisotropy of refractive index. Consequently, the circularly polarized light, which is radiated from the outside of the counter substrate **20** and is incident on the liquid crystal layer **50**, is converted to linearly polarized light through the liquid crystal layer **50**. The linearly polarized light reaches the reflecting electrode **393**. After the light is reflected by the reflecting electrode **393**, the reflected light passes through the liquid crystal layer **50** and enters the second retardation film **46**. Since the reflected light is circularly polarized light in the same direction of rotation as that of the foregoing incident light, the reflected light is converted through the second retardation film **46** to linearly polarized light that is parallel to the polarization axis of the second polarizer **24**. The linearly polarized light passes through the second polarizer **24**. The liquid crystal display device **200** of the present embodiment, therefore, provides white display upon application of a voltage.

With the above-described structure, a voltage applied to the liquid crystal layer **50** is controlled, thus performing gray-shade. In this instance, since the dielectric protrusion **563** is opposed to the central part of the reflecting electrode **393** in the present embodiment, the liquid crystal molecules **51** are aligned perpendicular to the border of the reflecting electrode **393**. In the vicinity of the dielectric protrusion **563**, the liquid crystal molecules **51** are aligned outwardly from the dielectric protrusion **563** upon application of a voltage. As viewed two-dimensionally, the liquid crystal molecules **51** are aligned radially around the vicinity of the dielectric protrusion **563**. In the liquid crystal display device **200** of the present embodiment, therefore, the directors of the liquid crystal molecules **51** are oriented in all directions, thus providing display with a remarkably wide viewing angle.

In the present embodiment, the stepped layer **34** is arranged in the transmissive display area in each subpixel to improve the viewing angle characteristics in gray level in the transmission display mode. The stepped layer **34** may be arranged in the reflective display area. Alternatively, the stepped layer **34** may be arranged in each of the transmissive and reflective display areas.

In the present embodiment, the stepped layer **34** is arranged in the transmissive display area in each subpixel to improve the viewing angle characteristics in gray level in the transmission display mode. The stepped layer **34** may be arranged in the reflective display area. Alternatively, the stepped layer **34** may be arranged in each of the transmissive and reflective display areas.

Electronic Apparatus

FIG. **6** is a perspective view illustrating an electronic apparatus according to the invention. Referring to FIG. **6**, a mobile phone **1300** includes a small-sized display unit **1301** to which the liquid crystal display device according to the invention is applied, a plurality of operation buttons **1302**, an earpiece **1303**, and a mouthpiece **1304**.

The electronic apparatus according to the invention is not limited to the above-described mobile phone. The display device in accordance with each of the embodiments of the invention may be suitably used as an image display unit of an electronic apparatus, e.g., a personal computer, a digital still camera, a liquid crystal television, a view-finder type or monitor-direct-view type video tape recorder, a car navigation system, a pager, an electronic organizer, an electronic calculator, a word processor, a workstation, a videophone, a POS terminal, or an apparatus having a touch panel. The display device can provide bright display in any of the electronic apparatuses.

Having described the preferred embodiments of the invention referring to the accompanying drawings, it should be understood that the invention is not limited to those embodiments and various changes and modifications of the combination, arrangement, and shapes of parts in the above-described embodiments may be made on the basis of design requirements without departing from the spirit or scope of the invention.

The entire disclosure of Japanese Patent Application No. 2006-024663, filed Feb. 1, 2006 is expressly incorporated by reference herein.

What is claimed is:

1. A liquid crystal display device comprising:
 - a first substrate and a second substrate;
 - a liquid crystal layer between the first and second substrates, the liquid crystal layer containing liquid crystal molecules having a negative anisotropy of dielectric constant; and

15

an alignment layer between the liquid crystal layer and at least one of the substrates, the alignment layer controlling the liquid crystal molecules to be aligned perpendicular to the substrate,

a dielectric protrusion that protrudes in the liquid crystal layer, wherein the alignment layer covers the dielectric protrusion,

the liquid crystal display device further including pixels, each pixel including a plurality of subpixels, each subpixel having a transmissive display area for transmissive display and a reflective display area for reflective display,

the subpixel including a stepped layer therein such that the stepped layer is disposed between the liquid crystal layer and at least one of the substrates,

the stepped layer defining a first region and a second region in the transmissive display area of the subpixel, the thickness of the liquid crystal layer being relatively thick in the first region and relatively thin in the second region, the area ratio of the first region depending on a color expressed by the subpixel, wherein the area ratio of the first region in the transmissive display area of the subpixel is larger as the wavelength of the color expressed by the subpixel is longer.

2. The device according to claim 1, wherein

the subpixel includes a thickness adjusting layer therein such that the thickness adjusting layer is disposed between the liquid crystal layer and at least one of the substrates, the thickness adjusting layer making the

16

thickness of the liquid crystal layer in the reflective display area less than that in the transmissive display area,

the stepped layer is disposed in the transmissive display area, and

the stepped layer and the thickness adjusting layer are made of the same material.

3. The device according to claim 1, further comprising:

a plurality of electrodes on respective surfaces of the first and second substrates close to the liquid crystal layer, the electrodes driving the liquid crystal molecules, wherein each subpixel includes the electrode on at least one of the substrates,

the electrode includes a plurality of island portions and linking portions each electrically connecting the adjacent island portions, and

the linking portion is two-dimensionally superimposed on a boundary region of the stepped layer.

4. The device according to claim 1, further comprising:

a light-shielding layer on at least one of the first and second substrates, wherein

the light-shielding layer is two-dimensionally superimposed on the boundary region of the stepped layer in the subpixel.

5. The device according to claim 1, wherein the thickness of the liquid crystal layer in the second region is approximately equal to that in the reflective display area.

* * * * *

专利名称(译)	液晶显示装置和电子设备		
公开(公告)号	US7995169	公开(公告)日	2011-08-09
申请号	US11/650998	申请日	2007-01-09
申请(专利权)人(译)	三洋爱普生影像设备CORP.		
当前申请(专利权)人(译)	索尼公司		
[标]发明人	HIGA MASAKATSU KURASAWA HAYATO		
发明人	HIGA, MASAKATSU KURASAWA, HAYATO		
IPC分类号	G02F1/1335 G02F1/1343		
CPC分类号	G02F1/133371 G02F1/133555		
审查员(译)	NGUYEN , 龚便T.		
优先权	2006024663 2006-02-01 JP		
其他公开文献	US20070177080A1		
外部链接	Espacenet USPTO		

摘要(译)

一种液晶显示装置，包括第一基板和第二基板，位于第一和第二基板之间的液晶层，以及位于液晶层和至少一个基板之间的取向层。液晶层包含具有负的介电常数各向异性的液晶分子。取向层使液晶分子垂直于基板取向。液晶显示装置还包括像素。每个像素包括表示不同颜色的多个子像素。每个子像素在其中包括台阶层，使得台阶层设置在液晶层和至少一个基板之间。阶梯层限定子像素中的第一区域和第二区域。液晶层的厚度在第一区域中相对较厚而在第二区域中相对较薄。第一区域的面积比取决于由子像素表示的颜色。

