



US 20070279556A1

(19) **United States**(12) **Patent Application Publication****Wang et al.**(10) **Pub. No.: US 2007/0279556 A1**(43) **Pub. Date: Dec. 6, 2007**(54) **CONTROLLING POLARIZATION FOR
LIQUID CRYSTAL DISPLAYS**


application No. 11/298,755, filed on Dec. 9, 2005,
which is a continuation-in-part of application No.
11/135,609, filed on May 23, 2005.

(76) Inventors: **Ran-Hong Raymond Wang**, Irvine, CA
(US); **Min-Shinc Chow Wang**, Irvine,
CA (US)

Correspondence Address:
KNOBBE MARTENS OLSON & BEAR LLP
2040 MAIN STREET
FOURTEENTH FLOOR
IRVINE, CA 92614 (US)

Publication Classification(51) **Int. Cl.**
G02F 1/1335 (2006.01)(52) **U.S. Cl.** **349/102; 349/96**(57) **ABSTRACT**(21) Appl. No.: **11/842,017**(22) Filed: **Aug. 20, 2007****Related U.S. Application Data**(63) Continuation of application No. 11/438,905, filed on
May 23, 2006, which is a continuation-in-part of

Certain embodiments of liquid crystal display protection
panels and liquid crystal display protection panel integrals
have low reflection for outdoor applications. Various
embodiments also have the advantage of being able to
provide increased contrast and brightness for certain con-
venient viewing directions for outdoor viewers wearing
polarized sunglasses.






FIG. 1




FIG. 2

Range of Wave Plate Retardation and Dispersion Effect




FIG. 3





FIG. 4










FIG. 5

FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6

FIG. 7A




FIG. 7B




FIG. 7




FIG. 8




FIG. 9




FIG. 10

FIG. 11A




FIG. 11B




FIG. 11




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 13




FIG. 14A

$\theta_2 = 45^\circ$
left handed
1410

FIG. 14B




FIG. 14C

FIG. 14




FIG. 15A




FIG. 15B




FIG. 15C

FIG. 16A





FIG. 16C




FIG. 16D




FIG. 16B

CONTROLLING POLARIZATION FOR LIQUID CRYSTAL DISPLAYS

PRIORITY APPLICATION

[0001] This application is a continuation of patent application of Ser. No. 11/438,905 entitled "Controlling Polarization for Liquid Crystal Displays" filed May 23, 2006, which is a continuation-in-part of U.S. patent application Ser. No. 11/298,755 entitled "Controlling Polarization for Liquid Crystal Displays" filed Dec. 9, 2005, which is a continuation-in-part of U.S. patent application Ser. No. 11/135,609 entitled "Controlling Polarization For Liquid Crystal Displays" filed May 23, 2005, each of which is incorporated herein by reference in their entirety.

FIELD OF INVENTION

[0002] The present invention relates to liquid crystal displays and polarization.

DESCRIPTION OF RELATED TECHNOLOGY

[0003] Many features of liquid crystal displays (LCDs), such as light weight, compact dimensions, low power consumption and high resolution, make LCDs popular choices in various outdoor electronic applications, including for PDAs, navigation systems, rugged notebooks, and information terminals. To avoid direct exposure to the outdoor environment, many LCDs in these applications are overlaid with an outer transparent protection panel, which introduces extra air-surface interfaces and generates a significant amount of back-reflection that reduces the readability of these displays. Often this outer transparent protection panel is a touch interface, such as a resistive touch panel, a capacitive touch panel, a SAW touch panel, a near field touch panel, or a IR touch panel. Some of the devices may also include other functional parts, such as EMI shield, IR block, and screen heater. However, these highly reflective functional parts also generate large amount of back reflection and further interfere with the readability of the system. Thus, providing a sunlight readable display system integrated with a protection panel or a touch panel, EMI, IR block, and screen heater becomes highly challenging.

[0004] In addition, a common optical property of a conventional liquid crystal display and a polarized touch panel is that they both selectively pass linearly polarized light from the LCD at a transmission direction with respect to the horizontal and vertical axes defined by the display or touch panel that is normally other than a vertical direction. Viewers of outdoor display systems may often wear vertically polarized sunglasses in order to block out horizontally polarized sunlight, especially in some working environments, such as on the sea or in the air, where the horizontally polarized sunlight is particularly strong. A conventional liquid crystal display or a liquid crystal display with a polarized touch screen that emits linearly polarized light would thus appear to be black for viewers wearing polarized sunglasses for common viewing directions, which is inconvenient for outdoor applications.

SUMMARY

[0005] Certain embodiments of liquid crystal displays, liquid crystal display protection panels and liquid crystal display protection panel integrals have low reflection for

outdoor applications and also have the advantage of being able to provide increased contrast and brightness for certain convenient viewing directions for outdoor viewers wearing polarized sunglasses.

[0006] One embodiment, for example, comprises a liquid crystal display comprising: a liquid crystal cell configured to modulate light; a linear polarizer layer forward said liquid crystal cell; a retarder layer comprising one or more retarders; and a display front surface through which said modulated light exits, wherein said one or more retarders and said linear polarizer layer are oriented such that said modulated light that exits said display front surface has an elliptical or circular polarization.

[0007] Another embodiment comprises a functional part integrated display comprising: a liquid crystal cell configured to modulate light defining vertical and horizontal axes, said liquid crystal cell comprising a liquid crystal layer sandwiched between two sheets of transparent electrodes; a first linear polarizer forward said liquid crystal cell, said first linear polarizer having a first linear polarization axis; a first retarder layer forward said first linear polarizer, said first retarder layer has a retardance of about $(2n+1)\lambda/4$ and a first slow axis which forms an angle θ_1 with respect to said first linear polarization axis, where n is an integer and λ between about 400 to 700 nanometers (nm); a functional element forward of said first retarder layer, said functional element comprising at least one of an EMI shield, an infrared filter, and an LCD heater; a second retarder layer forward of said functional element, said second retarder layer having a second slow axis and a retardance of about $(2m+1)\lambda/4$, where m is an integer and λ is between about 400 nm to 700 nm; a second linear polarizer forward said second retarder layer, said second linear polarizer having a second polarization axis, which forms an angle θ_2 with respect to said second slow axis; and a display front surface through which said modulated light exits.

[0008] Another embodiment comprises a touch panel integrated display comprising a liquid crystal cell configured to modulate light defining vertical and horizontal axes, said liquid crystal cell comprising a liquid crystal layer sandwiched between two sheets of substantially optically transmissive electrodes; a first linear polarizer forward said liquid crystal cell, said first linear polarizer having a first linear polarization axis; a first retarder layer forward said first linear polarizer, said first retarder layer having a retardance of about $(2n+1)\lambda/4$ and a first slow axis which forms an angle θ_1 to said first linear polarization axis, where n is an integer and λ is between about 400 nm to 700 nm; a resistive touch panel forward of said first retarder layer; a second retarder layer forward of said resistive touch panel, said second retarder layer has a second slow axis and a retardance of about $(2m+1)\lambda/4$, where m is an integer and λ is between about 400 nm to 700 nm; a second linear polarizer forward said second retarder layer, said second linear polarizer having a second polarization axis, which forms an angle θ_2 to said second slow axis of said second retarder layer; and a display front surface through which said modulated light exits, wherein said resistive touch panel is isotropic and $(m+n)$ is not zero.

[0009] Another embodiment comprise a touch panel integrated liquid crystal display comprising: a liquid crystal cell configured to modulate light defining vertical and horizontal

axes, said liquid crystal cell comprising a liquid crystal layer sandwiched between two sheets of transparent electrodes; a first linear polarizer forward said liquid crystal cell, said first linear polarizer having a first linear polarization axis; a first quarter wave retarder forward said first linear polarizer, said quarter wave retarder having a first slow axis; a resistive touch panel forward said first quarter wave retarder; a second quarter wave retarder forward said resistive touch panel, said quarter wave retarder having a second slow axis and a rear surface through which incident light passes; a second linear polarizer forward said second quarter wave retarder, said second linear polarizer oriented relative to said second quarter wave retarder such that said incident light which passes said rear surface of said second quarter wave retarder has a substantially circular polarization; and a display front surface through which said modulated light exits, wherein said second slow axis of said second quarter wave retarder is oriented at an angle other than about 0° or 90° with respect to said horizontal axis and other than at about 90° with respect to said first slow axis of said first quarter wave retarder.

[0010] Another embodiment of the invention comprises a polarized touch panel comprising: a resistive touch panel module defining the vertical and horizontal axes; a first quarter wave retarder forward said touch panel module, said first quarter wave retarder having a first slow axis; a second quarter wave retarder rearward said resistive touch panel module, said second quarter wave retarder having a second slow axis which is oriented at about 0° or 90° with respect to said horizontal axis; a linear polarizer forward said first quarter wave retarder, said linear polarizer having a linear polarization axis; and a display front surface through which modulated light of a display exits, wherein said first slow axis of said first quarter wave retarder is oriented at an angle other than about 90° with respect to said horizontal axis and other than about 90° relative to said second slow axis of said second quarter wave retarder.

[0011] Another embodiment of the invention comprises a polarized touch panel comprising: a resistive touch panel module defining the vertical and horizontal axes; a first retarder layer forward said touch panel module, said first retarder layer having a retardance of about $(2n+1)\lambda/4$ and a first slow axis, where n is an integer and λ is 400 nm to 700 nm; a linear polarizer forward said first retarder layer, said linear polarizer having a linear polarization axis; a second retarder layer forward said linear polarizer; and a display front surface through which modulated light of a display exits, wherein said slow axis of said first retarder layer is set at an angle of about $\pm 45^\circ$ relative to said linear polarization axis of said linear polarizer.

[0012] Another embodiment of the invention comprises a reflective functional part integrated display comprising: a liquid crystal cell configured to modulate light defining vertical and horizontal axes, said liquid crystal cell comprising a liquid crystal layer sandwiched between two sheets; a partial reflector rearward said liquid crystal layer; a first linear polarizer forward said liquid crystal cell, said first linear polarizer having a front surface and a first linear polarization axis; a first retarder layer forward said first linear polarizer, said first retarder layer having a front surface, a rear surface, a retardance of about $(2n+1)\lambda/4$, and a first slow axis which forms an angle θ_1 to said first linear polarization axis, where n is an integer and λ is between

about 400 nm to 700 nm; a reflective functional part forward of said first retarder layer, said reflective functional part having a rear surface and comprising at least one of a resistive touch panel, an EMI shield, an infrared filter, and an LCD heater; a second retarder layer forward of said reflective functional part, said second retarder layer having a second slow axis and a retardance of about $(2m+1)\lambda/4$, where m is an integer and λ is between about 400 nm to 700 nm; a second linear polarizer forward said second retarder layer, said second linear polarizer having a second polarization axis, which forms an angle θ_2 to said second slow axis of said second retarder layer; and a display front surface through which said modulated light exits.

[0013] Another embodiment of the invention comprises a reflective functional part integrated display comprising: a liquid crystal cell configured to modulate light defining vertical and horizontal axes, said liquid crystal cell having a front surface and comprising a liquid crystal layer sandwiched between two sheets; a partial reflector rearward said liquid crystal cell; said partial reflector comprising a reflective polarizer having a first linear polarizing axis; a first retarder layer forward said liquid crystal cell, said first retarder layer having a front surface, a rear surface, a retardance of about $(2n+1)\lambda/4$, and a first slow axis which forms an angle θ_1 to said first linear polarization axis, where n is an integer and λ is between about 400 nm to 700 nm; a reflective functional part forward of said first retarder layer, said reflective functional part having a rear surface and comprising at least one of a resistive touch panel, an EMI shield, an infrared filter and an LCD heater; a second retarder layer forward of said reflective functional part, said second retarder layer having a second slow axis and a retardance of about $(2m+1)\lambda/4$, where m is an integer and λ is between about 400 nm to 700 nm; a second linear polarizer forward said second retarder layer, said second linear polarizer having a second polarization axis, which forms an angle θ_2 to said second slow axis of said second retarder layer; and a display front surface through which said modulated light exits.

[0014] Another embodiment of the invention comprises a reflective functional part integrated transreflective display comprising: a liquid crystal cell configured to modulate light defining vertical and horizontal axes, said liquid crystal cell having a front surface and comprising a liquid crystal layer sandwiched between two sheets; a first linear polarizer rearward said liquid crystal cell, said first linear polarizer having a rear surface and a first linear polarization axis; a partial reflector rearward said first linear polarizer; a first retarder layer forward said liquid crystal cell, said first retarder layer having a front surface, a rear surface, a retardance of about $(2n+1)\lambda/4$, and a first slow axis which forms an angle θ_1 to said first linear polarization axis, where n is an integer and λ is between about 400 nm to 700 nm; a reflective functional part forward of said first retarder layer, said reflective functional part having a rear surface and comprising at least one of a resistive touch panel, an EMI shield, an infrared filter, and an LCD heater; a second retarder layer forward of said reflective functional part, said second retarder layer having a second slow axis and a retardance of about $(2m+1)\lambda/4$, where m is an integer and λ is between about 400 nm to 700 nm; a second linear polarizer forward said second retarder layer, said second linear polarizer having a second polarization axis, which

forms an angle θ_2 to said second slow axis of said second retarder layer; and a display front surface through which said modulated light exits.

[0015] Another embodiment of the invention comprises a reflective functional part integrated transmissive display comprising: a transmissive liquid crystal display module having a module front surface that selectively outputs linearly polarized light oriented along a first linear polarization axis, said liquid crystal display module comprising a liquid crystal cell, a partial reflector, and a backlight module; a first retarder layer forward said liquid crystal display module, said first retarder layer having a front surface, a rear surface, a retardance of about $(2n+1)\lambda/4$, and a first slow axis, which forms an angle θ_1 to said first linear polarization axis, where n is an integer and λ is between about 400 nm to 700 nm; a reflective functional part forward said first retarder layer, said reflective functional part having a rear surface; a second retarder layer forward said reflective functional part, said second retarder layer having a second slow axis and a retardance of about $(2m+1)\lambda/4$, where m is an integer and λ is between about 400 nm to 700 nm; a second linear polarizer forward said second retarder layer, said second linear polarizer having a second polarization axis, which forms an angle θ_2 to said second slow axis of said second retarder layer; and a display front surface through which light from said backlight module exits. In some embodiment, said reflective functional part comprises at least one of a resistive touch panel, an EMI shield, an infrared filter, and an LCD heater.

[0016] Another embodiment of the invention comprises a reflective functional part integrated transmissive display comprising: a liquid crystal display module having a module front surface, said liquid crystal display module comprising, from front to rear, a liquid crystal cell, a partial reflector comprising a reflective polarizer having a first linear polarization axis, and a light module; a first retarder layer forward said liquid crystal display module, said first retarder layer having a front surface, a rear surface, a retardance of about $(2n+1)\lambda/4$, and a first slow axis, which forms an angle θ_1 to said first linear polarization axis, where n is an integer and λ is between about 400 nm to 700 nm; a reflective functional part forward said first retarder layer, said reflective functional part having a rear surface; a second retarder layer forward said reflective functional part, said second retarder layer having a second slow axis and a retardance of about $(2m+1)\lambda/4$, where m is an integer and λ is between about 400 nm to 700 nm; a second linear polarizer forward said second retarder layer, said second linear polarizer having a second polarization axis, which forms an angle θ_2 to said second slow axis of said second retarder layer; and a display front surface through which light from the light module exits. In some embodiment, said reflective functional part comprises at least one of a resistive touch panel, an EMI shield, an infrared filter, and an LCD heater.

[0017] Another embodiment of the invention comprises a reflective functional part integrated display comprising: a liquid crystal display module having a module front surface that selectively outputs linearly polarized light oriented along a first linear polarization axis, said liquid crystal display module comprising, from front to rear, a liquid crystal cell, and a light module; a reflective functional part forward said liquid crystal display module, said reflective functional part having a rear surface; a second retarder layer

forward said reflective functional part, said second retarder layer having a second slow axis and a retardance of about $(2m+1)\lambda/4$, where m is an integer and λ is between about 400 nm to 700 nm; a second linear polarizer forward said second retarder layer, said second linear polarizer having a second polarization axis, which forms an angle θ_2 to said second slow axis of said second retarder layer; and a display front surface through which light from said light module exits, wherein said liquid crystal display module front surface includes at least one of an anti-reflection treatment and a diffusing structure. In certain embodiments anti-reflection treatment comprises a multi-layer AR coating or a laminated sheet member with AR coating. In some embodiment, said reflective functional part comprises at least one of a resistive touch panel, an EMI shield, an infrared filter, and an LCD heater.

[0018] Another embodiment of the invention comprises a reflective functional part integrated display comprising: a liquid crystal display module having a module front surface that selectively outputs linearly polarized light oriented along a first linear polarization axis, said liquid crystal display module comprising, from front to rear, a liquid crystal cell and a light module; a first retarder layer forward said liquid crystal display module, said first retarder layer having a front surface, a retardance of about $(2n+1)\lambda/4$, and a first slow axis which forms an angle θ_1 to said first linear polarization axis, where n is an integer and λ is between about 400 nm to 700 nm; a reflective functional part forward said first retarder layer, said reflective functional part having a rear surface; a second retarder layer forward of said reflective functional part, said second retarder layer having a second slow axis and a retardance of about $(2m+1)\lambda/4$, where m is an integer and λ is between about 400 nm to 700 nm; a second linear polarizer forward said second retarder layer, said second linear polarizer having a second polarization axis, which forms an angle θ_2 to said second slow axis of said second retarder layer; and a display front surface through which light exits, wherein at least one of said first retarder layer front surface and said reflective functional part rear surface includes at least one of an anti-reflection treatment and a diffusing structure. In certain embodiments the anti-reflection treatment comprising a multi-layer AR coating or a laminated sheet member with AR coating. In some embodiment, said reflective functional part comprises at least one of a resistive touch panel, an EMI shield, an infrared filter, and an LCD heater.

[0019] Another embodiment of the invention comprises a polarizing liquid crystal display protection panel having a protection panel rear surface and a protection panel front surface through which light from a display module may pass and exit to a viewer, said protection panel comprising: a retarder layer RB having a front surface, a rear surface, a slow axis RBX, and a retardance of about $(2m+1)\lambda/4$, where m is an integer and λ is between about 400 nm to 700 nm; a linear polarizer PB forward said retarder layer RB and closer to the viewer, said linear polarizer PB having a linear polarization axis PBX that forms an angle θ_2 of about 45° or -45° to said slow axis RBX of said retarder layer RB; and a transparent supportive panel, said transparent supportive panel comprises a sheet of glass substrate, a sheet of plastic substrate, or a touch input device, wherein at least one of said panel front and rear surfaces comprises an anti-reflection treatment.

[0020] Another embodiment of the invention comprises a polarizing protection panel liquid crystal display integral comprising: a liquid crystal display module having a module front surface that selectively outputs linearly polarized light oriented along a linear polarization axis PAX, said liquid crystal display module comprising a backlight module and a liquid crystal cell having a liquid crystal layer sandwiched between two transparent substrates; a polarizing protection panel forward said liquid crystal display module, said polarizing protection panel has a protection panel rear surface and a protection panel front surface and comprises a transparent supportive panel and a linear polarizer PB with a linear polarization axis PBX that is positioned either forward or rearward said transparent supportive panel; and a display front surface through which light from said backlight module exits, wherein said transparent supportive panel of said protection panel comprises a sheet of glass substrate, a sheet of plastic substrate, or a touch input device and at least one of said display front surface, said protection panel rear surface, and said module front surface comprises an anti-reflection treatment.

[0021] Another embodiment of the invention comprises a polarizing protection panel transmissive liquid crystal display integral comprising: a transmissive liquid crystal display module having a module front surface that selectively outputs linearly polarized light oriented along a linear polarization axis PAX, said transmissive liquid crystal display module comprising a liquid crystal cell having a liquid crystal layer sandwiched between two transparent substrates, a partial reflector comprising a reflective electrode or reflective sheet member, and a backlight module; a retarder layer RA forward said transmissive liquid crystal display module, said retarder layer RA having a front surface, a rear surface, a retardance of about $(2n+1)\lambda/4$, and a first slow axis, which forms an angle θ_1 to said linear polarization axis PAX, where n is an integer and λ is between about 400 nm to 700 nm; a polarizing protection panel forward said liquid crystal display module, said protection panel having a protection panel rear surface and a protection panel front surface and comprising a transparent supportive panel, a retarder layer RB having a slow axis RBX with a retardance of about $(2m+1)\lambda/4$, where m is an integer and λ is between about 400 nm to 700 nm, and a linear polarizer PB having a linear polarization axis PBX, which forms an angle θ_2 to said slow axis RBX; and a display front surface through which light from said backlight module exits, wherein said linear polarizer PB of said protection panel is disposed at the front side of said retarder layer RB of said protection panel and said transparent supportive panel of said protection panel comprises a sheet of glass substrate, a sheet of plastic substrate, or a touch input device and is positioned forward said linear polarizer PB, rearward said retarder layer RB, or between said linear polarizer PB and said retarder layer RB.

[0022] Another embodiment of the invention comprises a polarizing protection panel transmissive liquid crystal display integral comprising: a transmissive liquid crystal display module having a module front surface, said transmissive liquid crystal display module comprising, from front to rear, a linear polarizer PA having a linear polarization axis PAX, a liquid crystal cell having a liquid crystal layer sandwiched between two transparent substrates, a partial reflector comprising reflective electrode or reflective sheet members, and a backlight module; a retarder layer RA forward said transmissive liquid crystal display module, said

retarder layer RA having a front surface, a rear surface, a retardance of about $(2n+1)\lambda/4$, and a first slow axis, which forms an angle θ_1 to said linear polarization axis PAX, where n is an integer and λ is between about 400 nm to 700 nm; a polarizing protection panel forward said liquid crystal display module, said protection panel having a protection panel rear surface and a protection panel front surface and comprising a transparent supportive panel, a retarder layer RB having a slow axis RBX with a retardance of about $(2m+1)\lambda/4$, where m is an integer and λ is between about 400 nm to 700 nm, and a linear polarizer PB having a linear polarization axis PBX, which forms an angle θ_2 to said slow axis RBX; and a display front surface through which light from said backlight module exits, wherein said linear polarizer PB of said protection panel is at the front side of said retarder layer RB of said protection panel and said transparent supportive panel of said protection panel comprises a sheet of glass substrate, a sheet of plastic substrate, or a type of touch input device and is positioned forward said linear polarizer PB, rearward said retarder layer RB, or between said linear polarizer PB and said retarder layer RB.

BRIEF DESCRIPTION OF THE DRAWINGS

[0023] FIGS. 1A and 1B are schematic diagrams used in the discussion of retarders and polarization conversion.

[0024] FIGS. 1C-1H are schematic diagrams illustrating conversion of a linearly polarized light wave into circular polarization using a retarder layer comprising various retardation plates.

[0025] FIG. 2 is a schematic cross-sectional view of a liquid crystal display having non-linearly polarized output.

[0026] FIG. 3 is a plot on axes of retardance in waves (R/A) versus wavelength showing the dispersion effect and the range of wave plate retardation.

[0027] FIGS. 4A and 4B are front and cross-sectional views of LCD display configurations comprising a first retarder layer and a first linear polarizer that produce left-handed and right-handed circularly polarized light, respectively.

[0028] FIGS. 5A-5D are schematic diagrams illustrating the effect of viewing direction on the apparent brightness of a conventional LCD or a conventionally polarized touch screen to a viewer wearing polarized sunglasses.

[0029] FIGS. 6A-6C are schematic diagrams showing the effect of viewing direction on the apparent brightness of an NLP-LCD to a viewer wearing polarized sunglasses.

[0030] FIG. 7A is a schematic diagram of the apparent brightness of various viewing zones for a conventional LCD or an LCD integrated together with a polarized touch screen that produces linearly polarized light.

[0031] FIG. 7B is a schematic diagram showing the apparent brightness of various viewing zones for the NLP-LCD 200 which outputs circularly polarized light to viewers wearing polarized sunglasses.

[0032] FIG. 8 is a schematic cross-sectional diagram of an NLP-LCD shell structure comprising first and second circularly polarizers that produces linearly polarized light, e.g., having a polarization direction of 90°.

[0033] FIGS. 9A-9C are schematic diagrams of light propagating between two linear polarizers with various retarder layers disposed therebetween.

[0034] FIG. 9D is a schematic diagram that shows how reflection of incident light from surfaces in the display is reduced or minimized by using circularly polarized light.

[0035] FIGS. 10A-10D are schematic diagrams of circularly polarized light generated by various orientations of the second circularly polarizing retarder.

[0036] FIGS. 11A and 11B are schematic diagrams illustrating the apparent brightness of the different viewing zones of a display system with 90° polarization axis direction as seen by a viewer wearing polarized sunglasses.

[0037] FIGS. 12A-12C are schematic illustrations showing a polarizing transparent protection panel integrated together with a liquid crystal display with or without incorporation of other functional parts.

[0038] FIG. 13 is a schematic diagram illustrating the polarization change of a circular polarized light upon reflection.

[0039] FIGS. 14A-14C are schematic illustrations showing how reflections from functional parts are reduced by the second circularly polarizing retarder.

[0040] FIGS. 15A-15C are schematic diagrams showing a polarizing transparent protection panel integrated together with an alternative liquid crystal display with or without incorporation of other functional parts.

[0041] FIG. 16A is a schematic cross-sectional view of a LCD display 1500 configuration of FIG. 15A showing a first circularly polarizing plate formed from a first retarder layer, a liquid crystal cell, and a first linear polarizer.

[0042] FIG. 16B is a perspective view of the LCD display 1600 configuration of FIG. 16A showing a first circularly polarizing plate formed from a first retarder layer, a liquid crystal cell, and a first linear polarizer.

[0043] FIG. 16C is a front view of the LCD display 1600 configuration of FIG. 16B showing the first retarder layer, the liquid crystal cell, and the first linear polarizer arranged to produce left-handed circularly polarized light.

[0044] FIG. 16D is a front view of the LCD display 1600 configuration of FIG. 16B showing the first retarder layer, the liquid crystal cell, and the first linear polarizer arranged to produce right-handed circularly polarized light.

DETAILED DESCRIPTION OF CERTAIN EMBODIMENTS

[0045] A retardation plate is a birefringent optical element, in which light propagating longitudinally in a z-axis direction travels with different velocities for different polarizations oriented along orthogonal x and y axes. Thus, the light wave may have orthogonal polarization components, one of which is retarded relative to the other, by an amount that may be expressed as a retardance, R. The retardance R is determined by $d(N_s - N_f)$, wherein N_s is the refractive index of the slow axis of the retardation plate, N_f is the fast axis of the retardation plate, and d is the physical thickness of the plate. A retardation plate with retardance, R, will cause a phase difference of $2\pi R/\lambda$ between the orthogonal polariza-

tions of a light wave that passes therethrough. Thus, when the angle between the linear polarization axis of the incident light beam and the slow axis of a quarter wave plate (where $R=\lambda/4$) is at about 45 degrees, a phase difference of $2\pi R/\lambda=90^\circ$ between the orthogonal polarizations of the incident light beam results. Hence, the linearly polarized light wave is converted into a circularly polarized light wave with rotation directions either clockwise or counterclockwise. If the retardance is other than $(2n+1)\lambda/4$, where n is an integer, or the slow axis of a quarter wave plate and the linear polarization axis of the incident light beam are at angles other than 45 degrees, elliptically polarized light is produced. An integer is defined herein as including the values . . . -2, -1, 0, 1, 2 . . .

[0046] A linearly polarized light wave can be transformed into circularly polarized light by using various retarder layers comprising one or more retarder plates in proper arrangement. To facilitate the discussion below, quarter wave plates, half wave plates, and full wave plates will be used as examples. In FIG. 1A, a quarter wave plate 102 is shown with a slow axis indicated as a dotted line. FIG. 1A also shows a half wave plate 103 and a full wave plate 104 with a slow axis indicated as a dotted line. A linear polarizer 105 is shown with a polarization axis indicated as the double-headed arrow. Linearly polarized light 106 is shown with the polarization also indicated as the double-headed arrow. Right-handed circularly polarized light 107 is shown as a circle with an arrow going clockwise. Left-handed circularly polarized light 108 is shown as a circle with an arrow going counterclockwise.

[0047] Although the term plate is used in describing retarders herein, retarders may comprise a thin or thick film, a layer, a sheet, or a plate, having varying degrees of thickness, rigidity, and other optical and non-optical properties. Reference to a retarder plate is thus not limiting as the retarder may likewise comprise a film, layer, sheet or other medium that introduces retardance. Similarly, the film, layer, sheet, or plate may comprise multiple portions itself. Accordingly, layers are described as comprising plates but may otherwise comprise sublayers comprising films, sheets, etc.

[0048] As illustrated in FIG. 1B, a retarder layer comprising quarter wave plates, half wave plates, or full wave plates with various orientations of slow axes will result in different "effective retardances". For example, retarder layer 110, comprising two quarter wave plates with perpendicular slow axes as shown, has an effective retardance equivalent to 0. Retarder layer 120 comprising a full wave plate and two quarter wave plates having perpendicular slow axes as shown, has an effective retardance equivalent to a full wave plate. Additionally, retarder layer 130, comprising a full wave plate and a half wave plate as shown, has an effective equivalent to a half wave plate with slow axis being horizontal.

[0049] FIGS. 1C-1H show a plurality of retarder arrangements 140, 150, 160, 170, 180, and 190 comprising combinations of retardation plates having their relative orientations varied as indicated. The polarization axis of the linearly polarized light 106 incident on the slow axis of retardation plate 102 is at about 45°. Each of the retarder layers shown contains an odd number of equivalent quarter wave plates with slow axis as shown in each arrangement.

For example, the arrangement **140** in FIG. 1C is equivalent to a single quarter plate having a slow axis in the vertical direction. For example, the arrangement **150** in FIG. 1D is equivalent to a three quarter plates having a slow axis in the vertical direction, etc. Though having different effective retardances, each arrangement invariably circularly polarizes the linear polarization **106** producing either clockwise or counterclockwise circularly polarized light.

[0050] Although not shown, there are many other combinations of retarder layers having an effective retardance of $(2n+1)\lambda/4$, where n is an integer (e.g., $\dots -2, -1, 0, 1, 2, \dots$) and $\lambda/4$ is between about 400 nm-700 nm, which produce either clockwise (right-handed), or counterclockwise (left-handed) circularly polarized light. In some embodiments, the retardation plates comprising the retarder layer can be loosely stacked or laminated. As described above, these layers may comprise sublayers comprising different layers of film. It is also applicable to manufacture a single thick sheet retarder, which has $(2n+1)\lambda/4$ equivalent retardance and which circularly polarizes a linearly polarized light like a single quarter wave plate. A thick film may also be deposited. Thus, "a retarder layer" having $(2n+1)\lambda/4$ retardance, comprised of a single sheet retarder or a thick film, or a stack of laminated or loose sheets or other sublayers comprising quarter wave plates, half wave plates, or full wave plates, would have a "collective" slow axis and a "collective" fast axis that functions similarly to the slow and fast axes of a single quarter wave plate. Such a retarder layer will be termed as "quarter wave retarder." As discussed above, an incident angle other than 45° or -45° (and 0° and 90°) between the polarization axis of linearly polarized light and the slow axis of a quarter wave retarder will result in elliptically polarized light. Passing light through a retarder layer with retardance other than about $(2n+1)\lambda/4$ also results in elliptically polarized light.

[0051] Referring now to FIG. 2, a liquid crystal display having non-linearly polarized light output, abbreviated as NLP-LCD hereafter, is shown. The NLP-LCD **200** includes, with viewer's side as the front side, a liquid crystal cell **210**, comprised of a liquid crystal layer **201** sandwiched between a front transparent substrate **202** and a rear transparent substrate **203** containing electrodes. The front substrate **202** can be a thin glass sheet containing transparent electrodes, such as in a transmissive or transreflective type of TFT liquid crystal display. The front substrate **202** can also be a thin glass sheet with a stack of transparent retardation compensator plates or layers having a surface coated with transparent electrodes, such as in a reflective, transreflective or transmissive type of TN/STN liquid crystal display. The NLP-LCD **200** can also include a rear polarizer **204** and a backlight module **208** in the rear side of liquid crystal cell **210**. The backlight module **208** can be a high efficiency transmissive backlight cell assembly comprising sheets of brightness enhancement films and other polymeric films for enhancing light transmission and optical performances. The backlight module **208** can also be a transreflective or reflective type of lighting device. The reflective function can be implemented by reflective electrodes (not shown) deposited on the front surface of the rear substrate **203**, or a sheet member with transreflective or reflective property (not shown) placed on the rear side of the rear substrate **203**. For example, a combination of a diffusing element and a reflective polarizer (not shown) will provide substantially optimized optical performances under the sun, which will be

discussed further below. However, embodiments may include any conventional backlight cell or high brightness backlight cell, e.g., with edge or backside lamps.

[0052] The NLP-LCD **200** also includes a first linear polarizer **206** bonded to the front surface of the liquid crystal cell **210**. The NLP-LCD **200** further comprises a first retarder layer **205**, for example, a quarter wave retarder having a retardance of about $(2n+1)\lambda/4$ where n is an integer and λ is between about 400 nm-700 nm, forward of the first linear polarizer **206**. The first retarder layer **205** has a front surface **207**, e.g., with a haze value less than about 30%. The low haze value of the surface is useful for reducing the specular reflections for clear outdoor visibility. The front surface **207** can be a highly efficient multilayer anti-reflection coating, for example, having reflection less than about 1.5%, to reduce the surface reflection **230** and to maximize the entry of light beam **140** for reflective illumination **250**. The front surface **207** can further be a separate transmissive substrate or layer comprising, e.g., glass or plastic, such as PET, PEN, TAC, PC, ARTON, etc., having its low haze front surface coated with the high efficient multilayer anti-reflection coating, for example, having reflection less than about 1.5%, and with its rear surface being laminated to or coated on the front surface of the first retarder layer **205** with index matching pressure sensitive adhesive (PSA). In other embodiments, the front surface **207** may comprise a retarder or a thin film coating or multilayer disposed thereon. Still other configurations are possible (for example, the anti-reflective coating may be located elsewhere).

[0053] The first retarder layer **205** may be a single sheet retarder or a stack of laminated or loose sheets or may be a film or multiple films. This first retarder layer may comprise various combinations of retarder plates or layers or sublayers, e.g., quarter wave plates, half wave plates, or full wave plates as previously discussed. A quarter wave plate with $R/\lambda=0.25$, where λ is the wavelength in the visible light region, would be a particularly suitable retardation plate for the application. However, a perfect quarter wave plate with $R/\lambda=0.25$ is difficult to make due to the dispersion effect, as shown in FIG. 3. Thus, quarter wave plates with R/λ values in the range between curves **301** and **302**, as shown in FIG. 3, can be used. For example, a quarter wave plate having a R/λ value between about 0.216 and 0.315 at wavelength about 520 nm can be used. Similarly, embodiments may include half wave plates with R/λ values in the range between curves **303** and **304**, as shown in FIG. 3. For example, a half wave plate having an R/λ value between about 0.432 and 0.630 at a wavelength of about 520 nm may be employed. Embodiments may include a full wave plate have an R/λ value in the range between curves **305** and **306**, as shown in FIG. 3. A full wave plate having, for example, an R/λ value between about 0.864 and 1.260 at wavelength about 520 nm may be used. Values outside these ranges are also possible. The rear surface of the first retarder layer **205** can be laminated to the front surface of the first linear polarizer **206** with an index-matched pressure sensitive adhesive (PSA) to form a first circularly polarizing retarder **260** as a part of the display.

[0054] FIGS. 4A and 4B show diagrams of configurations **410** and **420** comprising the first retarder layer **205** and the first linear polarizer **206** that produce left-handed and right-handed circularly polarized light, respectively. As discussed above with reference to FIG. 1, the first retarder layer **205**

has an optical slow axis **401** and an optical fast axis **402** and operates as a single quarter wave plate. The first linear polarizer **206** has a polarization axis **403**. Viewed from the front side of the retarder layer looking towards the LCD light source **208**, the configuration of the first retarder layer **205** and the first linear polarizer **206** can be defined by the angle, θ_1 , between the slow axis **401** of the first retarder layer **205** and the polarization axis **403** of the first linear polarizer **206**. As generally defined, angle θ_1 has a positive value, if it increases from the slow axis **401** of the first retarder layer counterclockwise to the polarization axis **403** of the first linear polarizer **206**. On the other hand, θ_1 has a negative value, if it increases from the slow axis **401** of the first retarder layer clockwise to the polarization axis **403** of the first linear polarizer **206**.

[0055] Projections of two different configurations **410** and **420** between the first retarder layer **205** and the first linear polarizer **206** are shown in FIGS. 4A and 4B, respectively. In configuration **410** in FIG. 4A, in which θ_1 is substantially 45° , light **220** emitted by the LCD is transformed into a counterclockwise circularly polarized light wave **404**, which is a left-handed circular polarization by definition. The circularly polarizing retarder **260**, comprising the first retarder layer **205** and the first linear polarizer **206**, is thus said to have a left-handed circular polarization configuration. Likewise, as shown in configuration **420** in FIG. 2B, in which θ_1 is substantially -45° , light **220** emitted by the LCD is transformed into a clockwise circularly polarized light wave **405**, which is a right-handed circular polarization by definition. The circularly polarizing retarder **260** is said to have a right-handed circular polarization configuration. Angles other than -45° or 45° (and 0° and 90°) cause the emitted light to have elliptical polarization.

[0056] Referring now back to FIG. 2, by suitably disposing the first retarder layer **205** in relation to the linear polarizer **206**, the NLP-LCD **200** emits a non-linearly polarized light **220**—for example, an elliptical or a circularly polarized light depending on how the first retarder **205** and the first linear polarizer **206** are oriented. Though being elliptically or circularly polarized, the illumination intensity of the NLP-LCD **200** is substantially maintained and the optical performance of the NLP-LCD performs at least as well as a conventional linearly polarized light emitting LCD. The advantage of having a circularly polarized illumination, for example, in enhancing displays performance for wearer's of polarized sunglasses is discussed in further detail below.

[0057] FIGS. 5A-5D are diagrams schematically illustrating the effect of viewing direction on the apparent brightness of a conventional LCD or a conventional polarized touch screen to a viewer wearing polarized sunglasses. Usually, the light polarization direction of a liquid crystal display is determined by the orientation of the polarization axis of the linear polarizer disposed forward of the liquid crystal cell, which is described with respect to display modulator. Directions of 0° (horizontal) and 90° (vertical) in a landscape and a portrait view of a display module (or a touch panel module) are shown in **510** and **520** in FIG. 5A. The polarization direction of a conventional TFT LCD or a polarized touch panel is typically 45° or 135° , and substantially 0° in some larger size LCDs. Polarized sunglasses usually have a vertical transmission in order to block out the strong horizontally polarized scattered/reflected sunlight.

Depending on the viewing position of a viewer **501** wearing polarized sunglasses, the polarization direction **502** light from the LCD or touch panel, e.g. 45° in FIGS. 5B-5C, forms an angle θ with the transmission direction **503** of the polarized sunglasses, which is always vertical to viewer's eyes. Hence the apparent brightness of the LCD to the viewer will bear a factor of $\cos \theta$ to the actual brightness of LCD. Thus, when the viewer is in the most common straight front viewing position shown in **530** in FIG. 5B, θ is in about 45° , and approximately half of the LCD brightness will be seen by viewer. When the viewer moves to his or her left side, as shown in **540** in FIG. 5C, θ is about 0° and $\cos 0^\circ$ equals to 1, so most light from the LCD will be seen. When the viewer moves to his or her right side, as shown in **550**, θ is about 90° and since $\cos 90^\circ$ equals to 0, little of the LCD light is seen from this viewing position.

[0058] FIGS. 6A-6C show the effect of viewing direction on the apparent brightness of the NLP-LCD **200** to a viewer wearing polarized sunglasses. The light from the NLP-LCD **200** is circularly polarized to be either left-handed or right-handed. The viewer is indicated by **501** and the transmission direction of the polarized sunglasses is indicated as **503**. The circularly polarized LCD light is indicated as **602**, which is right-handed in this illustration. When the viewer **501** is in the front position **610**, the relationship of the circularly polarized light **602** to the transmission direction of polarized sunglasses **503** is shown in **640**. About one half of the circularly polarized light is selectively passed by the polarized sunglasses. When the viewer **501** moves to the left **620** as shown in FIG. 6B, the relationship of the circularly polarized light **602** to the transmission direction of polarized sunglasses **503** is shown in **650**. Again, about one half of the circularly polarized light is selectively passed by the polarized sunglasses. When viewer moves to the right **630** as shown in FIG. 6C, the relationship of the circularly polarized light **602** to the transmission direction of polarized sunglasses **503** is shown in **660**. About one half of the circularly polarized light is again selectively passed by the polarized sunglasses. Thus, in substantially all viewing positions of the NLP-LCD **200**, about one half of the LCD brightness is visible to a viewer wearing polarized sunglasses.

[0059] FIG. 7A shows a diagram of the apparent brightness of various viewing zones for a conventional LCD or an LCD integrated together with a polarized touch screen that produces linearly polarized light. As discussed below with reference to FIGS. 5A-5C, a conventional LCD or a regular polarized touch panel integrated LCD with linearly polarized light appears black to viewers wearing polarized sunglasses either in zones **701**, zones **702**, or zones **703** depending on whether the light transmission direction is 135° , 45° , or 0° , respectively.

[0060] FIG. 7B shows the apparent brightness of various viewing zones for the NLP-LCD **200** which outputs circularly polarized light to viewers wearing polarized sunglasses. Discussions in connection with FIGS. 6A-6C demonstrate that the NLP-LCD **200** with circularly polarized light has a superior optical property for outdoor applications, as it can deliver consistent brightness in viewing zones all around NLP-LCD to viewers wearing polarized glasses regardless viewer's viewing positions. Thus, NLP-LCD **200** has advantage of a conventional LCD yet it offers substantially consistent brightness in all viewing directions to

viewer wearing polarized sunglasses. A more convenient and comfortable visual experiences is provided compared to a conventional LCD. Although a circular polarization output by the NLP-LCD 200 is given as an example to illustrate the advantage of providing a liquid crystal display having a non-linearly polarized light over the conventional liquid crystal display with linearly polarized light, it is possible to have a liquid crystal display with elliptically polarized light and still provide improvement by mitigating the effect of the dark zones for viewers wearing polarized sunglasses.

[0061] In various embodiment, convenient viewing zones of a display are achieved by converting the light polarization direction output by the display to 90 degrees. The advantages of such an arrangement is discussed more fully below.

[0062] Referring now to FIG. 8, a diagram of an exemplary NLP-LCD shell structure 800 is shown. The NLP-LCD structure 800 comprises, a front side facing the viewer, an NLP-LCD 200 (see FIG. 2) with a transmissive sheet 801, a second retarder layer 805 having a rear surface 806 forward of the first retarder layer 205, and a second linear polarizer 807 forward of the second retarder layer 805. In certain preferred embodiments, the second retarder layer 805 is a quarter wave retarder having a retardance of about $(2m+1)\lambda/4$, where m is an integer and λ is between about 400 nm-700 nm. This second retarder layer 805 can be, e.g., a single sheet retarder or a stack of laminated or loose sheets or a film or multiple films. Combinations of quarter wave plates, half wave plates, or full wave plates may be used. Quarter wave plates with R/λ value in the range, e.g., between curves 301 and 302, as shown in FIG. 3, can be used. For example, a quarter wave plate of R/λ value between about 0.216 and 0.315 at wavelength 520 nm may be employed. Half wave plates with R/λ value in the range, e.g., between curves 303 and 304 as shown in FIG. 3 can be used. For example, a half wave plate of R/λ value between about 0.432 and 0.630 at wavelength about 520 nm may be used. And, full wave plates with R/λ value in the range, e.g., between curves 305 and 306 as shown in FIG. 3 can be used. For example, a full wave plate of R/λ value between about 0.864 and 1.260 at wavelength about 520 nm may be employed.

[0063] The rear surface of the second linear polarizer 807 can be laminated to or formed on the front surface of the second retarder layer 805. The polarization axis of the second linear polarizer 807 may be set substantially at an angle in the range of about $\pm(25^\circ-65^\circ)$ to the slow axis of the second retarder layer 805, for example, at about $\pm 45^\circ$ to form the second circularly polarizing plate 840. However, as discussed below, the polarization axis of the second linear polarizer 807 can be conveniently set at an orientation anywhere from 0 to 360° regardless of the orientation of polarization axis of the first linear polarizer 205.

[0064] In FIG. 8, a gap is shown between the first and second circularly polarizing retarders 260 and 840. An element such as a touch screen panel, an EMI shield, an IR blocker, or a heater may be disposed in this gap. As discussed more fully below, such elements can introduce substantial backreflections. The second circularly polarizing retarder 840 reduces the reflection from these elements and the first circularly polarizing retarder 260 increases the transmission of LCD light through the second circularly polarizing retarder 840, thereby enhancing the brightness

and contrast of the display. How the second circularly polarizing retarder 840 reduces this back reflection and how the first circularly polarizing retarder 260 increases the transmission of LCD light through the second circularly polarizing retarder 840 are discussed more fully below.

[0065] To better understand the operation of the first and second circularly polarizing retarders 260 and 840 in the NLP-LCD shell structure, propagation of a light wave through retardation plates between two linear polarizers is discussed with reference to FIGS. 9A-9C. In particular, FIGS. 9A-9C are schematic diagrams of light propagating between two linear polarizers with various retarder layers disposed therebetween. The emitted light beam is marked as 901 and the light propagation direction is indicated as 930.

[0066] In arrangement 900 in FIG. 9A, there is only one quarter wave plate 205, with the slow axis indicated with a dotted line, between the two linear polarizers 206 and 807. The first linear polarizer 206 has a polarization axis, which selectively passes incident light 901 as the linearly polarized light wave 902. When light 902 passes the retardation plate 205, it is transformed into circularly polarized light 904, of which about 40~50% is selectively passed by the second linear polarizer 807. Accordingly, arrangements with odd number $(2p+1)$ of quarter wave plates, where p is an integer, between the two linear polarizers 206 and 807 similarly allow at most 40~50% of the incident light 901 to be transmitted through the second linear polarizer 807 as arrangement 900, which is an example of such arrangements with $p=0$.

[0067] In arrangement 910 in FIG. 9B, two retardation plates are placed between linear polarizers 206 and 807. The first retardation plate 205 and the first linear polarizer 206 together form a circularly polarizing retarder 260 having a left-handed configuration. Light 901 is selectively passed by the first linear polarizer 206 and emerges from the first retardation plate 205 as left-handed circularly polarized light 904. The circularly polarized light 904 continues to propagate and pass through the second retardation plate 805, with the slow axis indicated by the dotted line. The light 904 is thereby converted into linearly polarized light 906 with the polarization perpendicular to the linearly polarized light 902. In order to pass the linearly polarized light 906, the polarization axis 911 of the second linear polarizer 807 is perpendicular to the polarization axis of the linear polarizer 206 as shown in arrangement 910. Such an arrangement makes the configuration of the second circularly polarizing plate 840 left-handed, which is the same configuration as the first circularly polarizing retarder 260 comprising the first linear polarizer 206 and first retardation plate 205.

[0068] FIG. 9C shows an arrangement 920 comprising four quarter-wave plates 205, 921, 922, and 805 between linear polarizers 206 and 807. Similarly, light wave 901 is circularly polarized after it passes through the first retardation plate 205 and emerges as circularly polarized light 904. The light wave 904 propagates through quarter wave plates 921, 922, and 805, which have their slow axes indicated by the dotted lines, and is converted into linearly polarized light 908. The linearly polarized light 908 has the same polarization as linearly polarized light 902. In order to pass linearly polarized light 908, the second linear polarizer 807 has the polarization axis 923 as shown. This configuration of the second circularly polarizing retarder 840, comprising the

second retardation plate **805** and the second linear polarizer **807**, is right-handed, which is reverse to the configuration of the first circularly polarizing retarder **260** comprising the first linear polarizer **206** and first retardation plate **205**. Although not shown, when there are six quarter wave plates between the two linear polarizers **206** and **807**, the configurations of the second and first circularly retarders **260**, **840** should be the same (e.g., both left-handed) in order to pass substantial amount of **901**.

[0069] It can be generalized that in order to have substantial transmission of light wave **901** from the first linear polarizer **206** through the second linear polarizer **807**, an even number of quarter wave plates are arranged between two linear polarizers **206** and **807**, producing a retardance of about $2p\lambda/4$, where p is a positive integer. In the arrangements shown, the slow axes of the retarder plates are parallel. In certain embodiments, the slow axes of the retarder plates may be arranged with other orientations and result in an effective retardance of $2p\lambda/4$, and still allow the efficient transmission of light **901** through **807**. A retarder layer having effective retardance other than $2p\lambda/4$, however, will allow transmission of **901** through **807** with less efficiency.

[0070] In addition to efficient transmission of light **901**, it is also desirable to have a setup that can effectively prevent reflection of incident light from components in the display system. Illustration **960** in FIG. 9D shows how reflected light is reduced or minimized. As discussed below, if incident light **940** is circularly polarized light **980** when it reaches the reflective surface **950**, the back reflection can be blocked. Thus, the retarder layer **990** forward of the reflective surface **950** may comprise an odd number of quarter wave plates, as discussed in FIG. 1, to produce circularly polarized light from linear polarized light. Likewise, if an even number of quarter wave plates is to be used between the linear polarizers **206** and **807** in the system, these quarter wave plates may be divided into sections forward and rearward of the reflective surface. The arrangement **910** in FIG. 9B shows two retarder layers with odd number of quarter wave plates in each layer, such as $(2m+1)\lambda/4$ and $(2n+1)\lambda/4$, where m and n are integers. The arrangement **910** contains two quarter wave plates, which are divided into two retarder layers, **205**, **805** with $m=0$ and $n=0$, respectively. Each retarder layer **205**, **805** forms with the respective first and second linear polarizers **206**, **807**, a circularly polarizing retarder **260** and **840** with left-handed configuration. Similarly, in FIG. 9C, arrangement **920** contains four quarter wave plates, which can be divided into two retarder layers using two different approaches, with $m=1$ and $n=0$, or with $m=0$ and $n=1$. In either case, the resultant circularly polarizing retarders **260** and **840** have reverse configurations. Accordingly, It can be generalized that when $(m+n)$ is 0 or an even integer, the configurations of the circularly polarizing retarders **260** and **840** are same with each other; and when $(n+m)$ is an odd integer, the configurations of the circularly polarizing retarders **260** and **840** are reverse to each other.

[0071] Referring back to FIG. 8, the NLP-LCD shell structure **800** has two quarter wave plates **205**, **805** between the first and second linear polarizers **206** and **807**. The propagation of light **820** through the structure **800**, therefore, is equivalent to the propagation of **901** in arrangement **910** of FIG. 9B. Accordingly, the configurations of the first and

second circularly polarizing retarders **260** and **840** are the same (e.g., both left-handed or both right-handed) in certain preferred embodiments. For example, if the first circularly polarizing retarder **260** is right-handed, the polarization axis of the second linear polarizer **807** is set substantially at -45° to the slow axis of the second retarder layer **805**, which makes the second circularly polarizing plate **840** right-handed. And if the first circularly polarizing plate **260** is left handed, the polarization axis of the second linear polarizer **807** is set substantially at 45° to the slow axis of the second retarder layer **805**, which makes the second polarizing plate **840** left-handed. In such an arrangement, transmissive illumination **820** and reflective illumination **850** will propagate similarly to the light wave **901** of arrangement **910** in FIG. 9B, and can be efficiently delivered to viewer's eyes.

[0072] In certain embodiments, the orientation of the second linear polarizer **807** can be set freely at any angle from 0 to 360 degrees as discussed more fully below. This free rotation of the second linear polarizer can result in a display, e.g., a functional part integrated display, with convenient viewing zones for viewers wearing polarized sunglasses. As shown in FIG. 9B, the second circular retarder **840** can be rotated freely with respect to the first circular retarder **260**. The second circular retarder **840** will in each case convert the circularly polarized light wave **904** into linearly polarized light **906**. Accordingly, the second polarizer **807** can be oriented at any angle from 0 to 360 degrees.

[0073] The result is shown in FIGS. 10A-10D, which are schematic diagrams of the circular polarization generated by various orientations of the second circularly polarizing retarder **840** having a defined configuration of the second retardation plate **805** and the second linear polarizer **807**. The NLP-LCD light output, for example, is a left-handed circularly polarized light **1011** in the illustrations. Viewed from the front side of the second linear polarizer looking towards LCD light source, the angle between the polarization axis **1001** of the second linear polarizer **807** to the slow axis **1002** of the second retardation plate **805** is defined as θ_2 . If θ_2 increases from the polarization axis **1001** counter-clockwise to the slow axis **1002**, the angle is positive. On the other hand, if θ_2 increases from the polarization axis **1001** clockwise to the slow axis **1002**, the angle is negative. The second circularly polarizing retarder **840** has a left-handed configuration in the case where the transmission **1001** of the second linear polarizer **807** is about 45° with respect to the slow axis **1002** of the second retarder layer **805**. The various orientations of the circularly polarizing plate **840** are illustrated as **1003**, **1005**, **1007** and **1009** in FIGS. 10A-10D, respectively. The circularly polarized light output **1004**, **1006**, **1008** and **1010** from the NLP-LCD in the illustrated embodiments having the corresponding orientations **1003**, **1005**, **1007**, **1009** are each left-handed. Although not all shown, any rotation of the circularly polarizer **840**, in the range of 0° to 360° , would invariably circularly polarize incident light thereby producing left-handed circularly polarized light as long as the configuration of the second linear polarizer **807** and the second retarder layer **805** is substantially maintained. Moreover, the light emitted with left-handed configuration from the rear side of second retarder plate **805** is transmitted by the second linear polarizer **807**.

[0074] Accordingly embodiments such as shown in FIG. 8 may have the polarization axis of the second linear polarizer

807 set at any orientation from 0 to 360 degree with respect to the polarization axis of the first linear polarizer **206** without compromising transmission efficiency of LCD light. Out of the possible orientations for the polarization axis of the second linear polarizer **807**, an orientation of about 90 degree is used in certain preferred embodiments. The advantage of setting the polarization axis at 90° can be understood from the following discussions.

[0075] FIGS. 11A and 11B schematically illustrate the apparent brightness as seen by a viewer wearing polarized sunglasses for different viewing zones of a display system that outputs linearly polarized light oriented at about 90° with respect to the horizontal. As shown in FIG. 11A, the display system **1100** has a 90° transmission direction **1101**. The transmission direction **1101** forms various angles θ with the polarization axis **503** of viewer's polarized sunglasses depending to viewer's location. When the viewer **501** is in the most common straight front viewing position **1102**, θ is about 0°, as shown in **1120** where most of LCD brightness will be seen. This area is marked as the bright area G1 in **1110** in FIG. 11B. For the same reason, area G2 is also a full brightness area. However, when viewer **501** moves to his or her left, as shown in **1103** in FIG. 11A, θ is about 45°, and the LCD will appear about one half as bright, as shown in **1130**. This area is marked as the shaded area H1 in **1110** in FIG. 11B. For the same reason, areas H2, H3, and H4, the LCD also would appear to be about half as bright. Only when viewer **501** is at either side of the LCD, such as position **1104** in FIG. 11A, θ would be about 90° as shown in **1140**, and little of the light from the LCD will be seen by the viewer. This area is marked as the dark area I1 in **1110** in FIG. 11B. For the same reason, area I2 would also appear dark. Thus, although with the edge viewing areas **11** and **12** being dark, the display system **1110** with a 90° transmission direction offers much more convenient viewing zones for outdoor viewers wearing polarized sunglasses when it is compared to a conventional display or polarized touch panel that has a light transmission direction of about 45°, 135°, or 0° as shown in FIG. 7.

[0076] Accordingly, it is advantageous to set the polarization axis of the second linear polarizer **807** (see FIG. 8) at about 90° for outdoor applications, especially for viewers wearing polarized sunglasses. In some embodiments, depending on the properties of the first and second retardation members **205** and **805** used, color distortion may sometime be observed due to the optical characteristics, such as inhomogeneity in retardation properties, of the retarders. Color correction, however, can be achieved by offsetting either angle θ_1 between the first retarder layer **205** and the first linear polarizer **206** or angle θ_2 between the second linear polarizer **807** and the second retarder layer **805**. In various preferred embodiments, for example, the angle θ_1 between the first retarder layer **205** and the first linear polarizer **206** is offset from $\pm 45^\circ$. The amount of angle adjustment can be up to about $\pm 20^\circ$ with respect to $\pm 45^\circ$. Similarly the angle θ_2 between the second retarder layer **805** and the second linear polarizer **807** is offset from $\pm 45^\circ$. The amount of angle adjustment can be up to about $\pm 20^\circ$ with respect to $\pm 45^\circ$. Alternatively, an even number of quarter wave plates can be introduced between the first and second retarder layers **205** and **805** as color correcting sheets. Other configurations are also possible.

[0077] As discussed above, many outdoor electronic applications also might entail the addition of a transparent protection panel or other functional parts comprising highly reflective films, such as EMI shield (EMI), IR block (IR), LCD screen heater (heater), and resistive touch panel (RTP). The following discussions will demonstrate such protection panel and functional parts can readily be incorporated into the shell structure of NLP-LCD **800** (e.g., shown in FIG. 8) and preserve and not introduce significant reflections.

[0078] FIG. 12A shows a polarizing transparent protection panel integrated together with a liquid crystal display with or without incorporation of other functional parts. The polarizing transparent supportive panel display integral **1200** (e.g. PT-TRIOLCD, from Advanced Link Photonics, Inc., Tustin, Calif.) comprises, with viewers side as the front side, a liquid crystal cell **210**, comprised of a liquid crystal layer **201** sandwiched between a front substrate **202** and an electrode containing rear substrate **203**. The front substrate **202** may comprise a thin glass sheet comprising transparent electrodes, such as in a transmissive or transreflective type of TFT liquid crystal display. The front substrate **202** may also comprise a thin glass sheet with a stack of transparent retardation compensator plates having a surface coated with transparent electrodes, such as in a reflective, transreflective, or transmissive type of TN/STN liquid crystal display. The display integral **1200** (e.g., PT-TRIOLCD) can also include a rear polarizer **204** and a backlight module **208** at the rear side of liquid crystal cell **210**. The backlight module **208** may comprise a high efficiency transmissive backlight cell assembly comprising sheets of brightness enhancement films and other polymeric films for enhancing light transmission and optical performances. However, any conventional backlight cell or high brightness backlight cell with edge or backside lamps can be used. Other backlight cells are also possible. The backlight module **208** can also be a transreflective or reflective type of light device with a transreflector or a reflector. The transreflector or the reflector can be the reflective electrodes (not shown) deposited on the front surface of the rear substrate **203**, or a sheet member **1201** with transreflective or reflective properties positioned on the rear side of the liquid crystal layer **201**.

[0079] In one embodiment, the sheet member **1201** can simply comprise a reflective polarizer. In other embodiments, the sheet member **1201** is comprised of a diffusing element or structure **1234** and a reflective polarizer **1235**. The reflective polarizer **1235** may absorb less than about 10% of incident the light energy. The reflective polarizer **1235** may also have an extinction coefficient, defined as the transmission of the p state polarization over the transmission of the s state polarization, ranging from about 1.5 to 9, for example. In addition, the polarization axis of the reflective polarizer **1235** may be parallel to or within about (+/-) 60 degrees in relation to the polarization axis of the rear polarizer **204** in some embodiments. The rear polarizer **204** and the reflective polarizer **1235** can be formed as an integral by being laminated with a layer of adhesive. It is also possible that in some embodiments the reflective polarizer is used as the rear polarizer **204**.

[0080] The reflective polarizer **1235** can be formed with multiple sheets of a selective reflective polarizer with optimized polarization axes. The reflective polarizer **1235** can also be a diffuser laminated selective reflective polarizer. The diffusing element or structure **1234** may be a corrugated

surface with haze in the range of about 10% to 85% in some embodiments. The corrugated surface can be a roughened surface on the rear surface of the rear polarizer **204** or on a separate transmissive polymeric substrate, such as PET, PC, PEN, TAC, or ARTON etc. The corrugated surface can also be a dielectric or other material, and may comprise, e.g., TiO_2 , Ta_2O_5 , SiO_2 , SiN, ITO, ZnS, Al_2O_3 , LaF_3 , MgF_2 , Ge, or Si, deposited on the rear surface of the rear polarizer **204**, or on a separate sheet of transmissive substrate. The corrugated surface may comprise small metal particles, ranging in size from about 10 nm to 10000 nm, deposited on the rear surface of the rear polarizer **204** or on a separate sheet transmissive substrate. The choice of the metal includes, for example, silver, gold, aluminum, copper, titanium, tantalum, chromium, nickel or an alloy thereof. One or more sheets of loose-packed or optically bonded transmissive substrates with the corrugated surface can make up the diffusing element **1234**. In addition, diffusing element **1234** can be optically bonded to the rear surface of the rear polarizer **204** or/and to the front surface of the reflective polarizer **1235**. The diffusing element can also be a layer of adhesive material, which bonds the rear polarizer **204** and the reflective polarizer **1235** and comprises dispersed particles such that the haze value of the layer is in the range of about 10% to 85% in some embodiments. In other embodiments such as described herein where a diffuser is utilized, an adhesive material comprising diffusing particles may be used. This adhesive material comprising diffusing particles can diffuse the light. In certain embodiments, the diffusing adhesive has a haze value in the range of about 10% to 85% as described above. Values outside these ranges as well as different configurations both well known as well as those yet devised are possible. Other types of diffusing structures may also be used and may be located elsewhere.

[0081] With continued reference to FIG. 12A, the display integral **1200** (e.g. PT-TRIOLCD, from Advanced Link Photonics, Inc., Tustin, Calif.) can also include a first linear polarizer **206**, which has a linear polarization axis and selectively passes the module light in one transmission direction. The linear polarizer **206** can be bonded to the front surface of the liquid crystal cell **210** to form an integrated display module. The display integral **1200** (e.g. PT-TRIOLCD) can further include a first retarder layer **205** to the front side of the first linear polarizer **206**. The first retarder layer **205** may comprise a quarter wave retarder having a retardance of about $(2m+1)\lambda/4$, where m is an integer and λ is between about 400 nm-700 nm. The first retarder layer **205** may comprise a single sheet retarder or a stack of laminated or loose sheets or a film or multiple films. The first retarder layer **205** may comprise quarter wave plates, half wave plates, or full wave plates. The rear surface of the first retarder layer **205** can be laminated to the front surface of the first linear polarizer **206** with an index-matched pressure sensitive adhesive (PSA) to form a first circularly polarizing retarder **260** as a part of display. Quarter wave plates with R/λ values in the range between curves **301** and **302**, as shown in FIG. 3, can be used. For example, a quarter wave plate having an R/λ value between about 0.216 and 0.315 at a wavelength of about 520 nm may be employed. Half wave plates with R/λ values in the range between curves **303** and **304** as shown in FIG. 3 can be used. For example, a half wave plate of R/λ value between about 0.432 and 0.630 at a wavelength of about 520 nm may be employed. And full wave plates with R/λ values in the range between curves **305**

and **306** as shown in FIG. 3 can be used. For example, a full wave plate having R/λ values between about 0.864 and 1.260 at a wavelength of about 520 nm may be employed.

[0082] The slow axis of the first retarder layer **205** may be set at an angle θ_1 in the range of about 25° to 65° or $-(25^\circ$ to $65^\circ)$, for example at about 45° or -45° , with respect to the polarization axis of the first linear polarizer **206**. While viewed from the front side of the retardation plate **205** looking towards the LCD light source, as shown in FIG. 4, if the angle θ_1 is substantially 45° , the configuration of the first circularly polarizing plate **260** is left-handed. If the angle θ_1 is substantially -45° , the configuration of the first circularly polarizing plate **260** is right-handed. Other values outside these ranges may be used.

[0083] Further referring to FIG. 12A, the display integral **1200** (e.g. PT-TRIOLCD, from Advanced Link Photonics, Inc., Tustin, Calif.) also includes a transparent protection panel **1210** that circularly polarizes the incident sunlight **140**. The protection panel **1210** has a front surface **1211** and a rear surface **1212**. Practically, the transparent protection panel **1210** can be the integral of the linear polarizer **807** and the retarder layer **805**. It is also possible that a separate transparent supportive substrate **1220** is added to form the transparent protection panel **1210**. The transparent supportive substrate **1220** can be a sheet of glass or plastic. In some embodiments, the supportive substrate **1220** can also be a type of touch input device, such as a resistive touch panel, a capacitive touch panel, a SAW touch panel, a near field image touch panel, or an IR touch panel. The separate transparent supportive substrate **1220** can be at the rear side of the retarder layer **805** as shown in FIG. 12A. The supportive substrate **1220** can also be between the linear polarizer **807** and the retarder layer **805** as shown in FIG. 12B. The supportive substrate can further be at the front side of the linear polarizer **807** as shown in FIG. 12C. These sheet members of the protection panel **1210**, regardless the positioning of the supportive substrate **1220**, can be laminated to form an integral panel. An isotropic transparent substrate can be used to construct the supportive transparent substrate **1220**. It is also possible to use non-isotropic material and the retardance of the supportive transparent substrate **1220** may be taken into consideration. Or in some embodiments, the non-isotropic substrate **1220** can be positioned forward the linear polarizer **807** as shown in FIG. 12C to avoid interferences may be generated by non-isotropic substrate. This polarizing protection panel **1210** can effectively prevent the back reflections that would be generated by rearward reflective surfaces of parts such as an EMI shielding, an IR blocking and a screen heater. Details will be further discussed in the following sections. Thus, other functional parts comprising conductive films, such as an EMI shield, an IR block and a screen heater can be integrated by introducing the parts on separate substrates to the rear side of the protection panel (not shown). Or these functional parts can be easily incorporated into the display integral **1200** using the front surface **207** of the first retarder layer **205** and the rear surface **1212** of the transparent protection panel **1210** as the surfaces for conductive film coating to form the above mentioned functional parts. Practically, EMI shielding and IR blocking (EMI/IR) can be integrated in a single sheet of transparent substrate coated with conductive film. To provide EMI shielding, the conductive film may be grounded. Screen heating and IR blocking functions (IR/heater) can also be achieved on a single sheet of transparent substrate

coated with conductive film. The conductive film may also be electroded to provide current flow for resistive heating. In one embodiment, the IR blocker can also be a hot mirror coating comprising dielectric material and may comprise all dielectric material. Thus, to incorporate either EMI/IR or/and IR/heater, a conductive film can be deposited on either (or both) surfaces **207** and **1212**. The conductive film may comprise, for example, ITO, ZnO, Ni, Cr, Au, ZrO₂, TiO₂, SiO₂, or SnO₂ having a conductivity in the range, e.g., of about 1 ohm to 1000 ohm per square, a transmission of about 50% to 95% in the visible range of about 400 nm to 700 nm, and a reflectance of about 20% to 90% for wavelengths about 700 nm and greater. Values outside these ranges are possible. The EMI/IR or IR/heater may be provided with proper electrodes or grounding setups as discussed above. Various combinations are possible or alternatively only one functional part may be included. Integration of functional parts by introducing a separate conductive film coated substrate is also possible as mentioned above.

[0084] Still referring to FIG. 12A, the second retarder layer **805** may comprise a quarter wave retarder having a retardance of about $(2n+1)\lambda/4$, where n is an integer and λ is between about 400 nm-700 nm. The second retarder layer may comprise a single sheet retarder or a stack of laminated or loose sheets or a film or multiple films. The second retarder layer may comprise quarter wave plates, half wave plates, or full wave plates. Quarter wave plates with R/λ values in the range between curves **301** and **302**, as shown in FIG. 3, can be used. For example, a quarter wave plate having an R/λ value between about 0.216 and 0.315 at a wavelength of about 520 nm may be employed. Half wave plates with R/λ values in the range between curves **303** and **304** as shown in FIG. 3 can be used. For example, a half wave plate having an R/λ value between about 0.432 and 0.630 at a wavelength of about 520 nm may be employed. And full wave plates with R/λ values in the range between curves **305** and **306** as shown in FIG. 3 can be used. For example, a full wave plate having an R/λ value between about 0.864 and 1.260 at a wavelength of about 520 nm can be employed.

[0085] The polarization axis of the second linear polarizer **807** may be set at an angle θ_2 in the range of about $\pm(25^\circ-65^\circ)$, for example at about $\pm 45^\circ$, to the slow axis of the second retarder layer **805** forming the second circular polarizer **1240**. This second circular retarder effectively reduces or prevents the reflections from the reflective surfaces, such as **1212** and **207** or other highly reflective functional parts (not shown). However, as previously disclosed, the polarization axis of the second linear polarizer **807** can be conveniently set at an angle in the range of 0 to 360° regardless the orientation of the polarization axis of the first linear polarizer **205**.

[0086] The following examples illustrate that in such an arrangement, the reflections generated by the air-surface interfaces or the conductive film coated surfaces **1212** and **207** are effectively reduced by the second circularly polarizing plate **1240** comprised by the linear polarizing plate **807** and the retarder layer **805** in FIGS. 12A, 12B, and 12C. Nevertheless, the LCD transmissive and transreflective illuminations are effectively transmitted as discussed above.

[0087] FIG. 13 is a schematic diagram illustrating the polarization change of circular polarized light upon reflection.

Circularly polarized light is reflected with reversed polarization. Left-handed circularly polarized light **1321** is reflected by a reflective surface **1320**, which operates as a mirror, and converted into the right-handed circularly polarized light **1322**. Right-handed circularly polarized light **1323** is reflected by the reflective surface **1320** and converted into left-handed circularly polarized light **1324** upon reflection.

[0088] FIG. 14A is an enlarged projection view around the second linear polarizer **807** of FIGS. 12A, 12B, and 12C. In some embodiments, the supportive substrate is made of isotropic material with reduced or minimum retardation properties. The configuration of the polarizing transparent protection panel can be determined by considering the polarization of the linear polarizer **807** and the retardation of the retarder **805**. As shown, the second linear polarizer **807** has a polarization axis **1001** and the second retarder layer **805** has a slow axis **1002**. A front view is depicted in FIG. 14B. As seen from the perspective of the viewer, θ_2 is about 45° . The incident sunlight **140** is linearly polarized by the second linear polarizer **807** and has a polarization parallel to the polarization axis **1001**. The orientation of this linear polarization is about 45° with respect to the slow axis **1002** of the second retarder layer **805**. The linear polarized light therefore emerges from the second retarder layer **805** as left-handed circularly polarized light **140_{circ}**. The circularly polarized light **140_{circ}** is reflected from the reflective conductive film coated surfaces (such as **1212** and **207** in FIG. 12A), which is collectively indicated as surface **1420**. As shown in FIG. 14C, the right-handed polarized beams that are reflected are indicated as **1430_{circ}**. This right-handed polarized light **1430_{circ}** travels back to the second retarder layer **805** where the right-handed circularly polarized light is converted into a linearly polarized light with a polarization axis indicated by an arrow **1403**. As shown, the polarization axis **1403** is perpendicular to the polarization axis **1001** of the second linear polarizer **807**, and is thus not transmitted through the second linear polarizer **807**. Thus, the reflected light beams **1403_{circ}** can be effectively blocked from viewer's eyes regardless of the number of conductive films in the system.

[0089] As briefly discussed with reference to FIG. 9, the relative configurations of the second and first circular retarders **840** and **260** may be determined by retardance of the two retarder layers, $(2m+1)\lambda/4$ for **205** and $(2n+1)\lambda/4$ for **807**, where n and m are integers and λ is about 400 nm-700 nm. When $(n+m)$ is 0 or an even integer, the configuration of the first and second circular retarders **260** and **840** are the same (e.g. both left-handed or both right-handed). If $(n+m)$ is an odd integer, the configurations of the second and first circularly polarizers **840** and **260** are to be reverse to each other. Other values outside these ranges may also be used.

[0090] With reference back to FIGS. 12A, 12B, and 12C, to determine the corresponding configurations of the first and second circular retarders **260** and **1240** in the display integral **1200** (e.g. PT-TRILCD), the retardance of the supportive substrate **1220** and functional part(s) may be taken into consideration. In certain embodiments, the supportive substrate and the functional parts are made of thin glass sheets or isotropic plastic sheets, such as PET, PEN, TAC, PC, ARTON, etc., with minimum retardation properties, for example with retardance less than about 80 nm. In such embodiments with $(n+m)$ being 0 or an even integer, the propagation of LCD illumination **1221** is substantially

equivalent to the propagation of the light **901** in the arrangement **910** of FIG. 9. Accordingly, the configurations of the first and second circular polarizers **260** and **1240** can be determined to be the same as each other (e.g., both right-handed or both left-handed). That is to say, if the first circular retarder **260** is right-handed with θ_1 being substantially -45° as shown in **420** of FIG. 4B, the polarization axis of the second linear polarizer **807** is set such that the angle from the polarization axis of the second linear polarizer to the slow axis of the second retarder layer **805** is substantially at -45° , which makes the second circular retarder **1240** right-handed. And if the first circular retarder **260** is left-handed with θ_1 being substantially 45° as shown in **410** of FIG. 4A, the polarization axis of the second linear polarizer **807** is set such that the angle from the polarization axis of the second linear polarizer to the slow axis of the second retarder layer **805** is substantially at 45° to the slow axis of the second retarder layer **805**, which makes the second circular retarder left-handed.

[0091] On the other hand, if $(n+m)$ is an odd integer and the retardance of the functional parts is not significant, the configurations of the first and second circular polarizers **260** and **1240** can be determined to be opposite as each other (e.g., one right-handed and one left-handed, like in FIG. 9C). That is to say, if the first circular retarder **260** is left-handed with θ_1 being substantially 45° as shown in **410** of FIG. 4A, the polarization axis of the second linear polarizer **807** is set such that the angle from the polarization axis of the second linear polarizer to the slow axis of the second retarder layer **805** is substantially at -45° , which makes the second circular retarder **1240** right-handed. And if the first circular retarder **260** is right-handed with θ_1 being substantially -45° as shown in **420** of FIG. 4B, the polarization axis of the second linear polarizer **807** is set such that the angle from the polarization axis of the second linear polarizer to the slow axis of the second retarder layer **805** is substantially at 45° to the slow axis of the second retarder layer **805**, which makes the second circular retarder left-handed.

[0092] In some other embodiments, the functional parts may contain significant retardance. The retardance of the functional parts may be integrated as a part of the first retarder layer retardance, which may be adjusted to obtain an effective retardance of about $(2m+1)\lambda/4$. The configurations of the first and second circular retarders **260** and **1240** may be determined accordingly. Thus, efficient delivery of both reflective illumination **1250** and transmissive illumination **1221** to viewer's eyes can be achieved.

[0093] In various preferred embodiments, an air gap between components creates two air-material interfaces, which cause reflections due to index mismatch. These reflections may interfere and compromise the optical performances of the integral. The air-material interfaces can be eliminated by laminating the separate parts together and removing the air gap therebetween. However, adequately applying anti-reflection treatment or incorporating diffusing property on surfaces can also conveniently reduce undesirable backreflections and the resultant interference and enhance the optical properties of the integral. For example, the rear surface of the first retarder layer **205** can be laminated to the front surface of the first linear polarizer **206** to form an integrated display module as described in FIG. 2. In such an arrangement, a diffusing element or structure or an anti-reflection treatment (not shown) can be included on

the front surface of the first retarder layer **205**, the front or rear surface of the reflective parts (not shown), or the rear surface **1212** of the protection panel **1210** to curtail or prevent interference of the reflections and enhance the optical properties. The diffusing structure (not shown) can be a roughened surface or may comprise particles (as discussed above) deposited on the front surface of the first retarder layer **205**. In certain embodiments, the diffusing structure may comprise a laminated sheet member (not shown) with diffusing property of Haze value greater than zero. In other arrangements, the front surface of the first retarder layer **205** is laminated to the rear surface of the reflective parts (not shown) or the front surface **1212** of the protection panel **1210**. In such arrangements, an anti-reflection treatment (not shown) or diffusing structure may be disposed on at least one of the rear surface of the first retarder layer **205** and on the front surface of the first linear polarizer **206** to achieve the equivalent optical performances. Different types of diffusing structures may be used and other configurations are possible (for example, the diffusing structure and/or anti-reflective coating may be located elsewhere).

[0094] In some arrangements, depending on the properties of the first and second retarder layers **205** and **805** used, color distortion may sometime be observed. Color correction can be achieved by offsetting either angle θ_1 between the first retarder layer **205** and the first linear polarizer **206**, or angle θ_2 between the second linear polarizer **807** and the second retarder layer **805**. For example, angle θ_1 may be offset. The amount of angle adjustment can be within about $\pm 20^\circ$ off the $\pm 45^\circ$. In other embodiments, $2n$ equivalent quarter wave plates, n being an integer, can be introduced between the first retarder layer **205** and the protection panel **1210** as color correcting sheets (not shown). With proper arrangement of the optical axes among the plates, satisfactory color corrections can be obtained. In one embodiment, depending on the equivalent retardance of the plates introduced for the color correction, configurations of the first and second circular polarizers **260** and **1240** may need to be adjusted according to the discussion presented above in connection with FIG. 9.

[0095] With continued reference to FIGS. 12A, 12B, and 12C, as discussed above, the polarization axis of the second linear polarizer **807** can be conveniently set at any orientation in the range of 0 to 360 degrees, e.g., at 90 degrees to the horizontal, regardless the orientation of the polarization axis of the first linear polarizer **206**. At least two advantages result. First, setting the polarization axis at 90 degrees provides a cost saving in production. A linear polarizer is a relatively expensive raw material. A regular polarized touch screen is usually made with 45° or 135° light in order to match up with the light transmission direction of a regular LCD, in which case the sheet of linear polarizer will need to be cut diagonally. In one embodiment, there is no need to restrict the orientation of the polarization axis of the second linear polarizer **807**, and the polarizer sheet can be cut in any way, whichever is cost beneficial. Second, a 90° transmission direction can provide convenient viewing zones for viewers wearing sunglasses as discussed in connection with FIG. 11.

[0096] Still referring to FIG. 12A, the advantage of being able to deliver convenient viewing zones for viewers wearing polarized sunglasses can also be achieved by further

disposing a third retarder layer **1203** to the front side of the protection panel **1210** as described above. The third retarder layer **1203** may comprise a quarter wave retarder having a retardance of about $(2k+1)\lambda/4$, where k an integer and λ is about 400 nm-700 nm. The third retarder layer **1203** may comprise a single sheet retarder or a stack of laminated or loose sheets or a film or multiple films. The third retarder layer **1203** may comprise quarter wave plates, half wave plates, or full wave plates. The third retarder layer **1203** converts the otherwise linearly polarized transmission **1221** to a circularly polarized transmission. The advantage of the effect can be similarly understood with reference to discussions of FIGS. 6 and 7. The front surface **1211** of the protection panel **1210** or the front surface **1204** of the third retarder layer **1203** may comprise a highly efficient multi-layer anti-reflection coating, for example, having reflection less than about 1.5% to reduce or prevent the surface reflection **1230** and to increase or maximize the entry of light beam **140** for reflective illumination **1250**. In some embodiments, the front surface **1211** of the transparent protection panel **1210** or the front surface **1204** of the third retarder layer **1203** can also comprise a separate transmissive substrate, e.g., glass or plastic, such as PET, PEN, TAC, PC, ARTON, with its front surface being coated with the high efficient multi-layer anti-reflection coating, for example, providing reflection less than about 1.5%. The rear surface of the separate transmissive substrate can be bonded to the front surface **1211** of the protection panel or the front surface of the third retarder layer **1203** with index matching pressure sensitive adhesive (PSA). Combination of reduction or minimization of reflections, **1230** and **1231**, and increase or maximization of LCD illuminations, **1221** and **1250**, in this embodiment, is sufficient to make the display integral **1200** (e.g. PT-TRIOLCD) direct sunlight readable. Values outside the ranges provided above and other configurations may be employed (for example, the anti-reflective coating may be located elsewhere).

[0097] FIG. 15A shows a polarizing transparent protection panel integrated together with an alternative liquid crystal display with or without incorporation of functional parts. The polarizing transparent protection panel display integral **1500** (e.g. PT-TRIOLCD, Advanced Link Photonics, Inc., Tustin, Calif.) comprises, with viewer's side as the front side, a liquid crystal cell **210**, comprised of a liquid crystal layer **201** sandwiched between a front substrate **202** and an electrode containing rear substrate **203**. The front substrate **202** may comprise a thin glass sheet comprising transparent electrodes, such as in a transmissive or transreflective type of TFT liquid crystal display. The front substrate **202** may also comprise a thin glass sheet with a stack of transparent retardation compensator plates having a surface coated with transparent electrodes, such as in a reflective, transreflective, or transmissive type of TN/STN liquid crystal display. The display integral **1500** (e.g., PT-TRIOLCD) can also include a backlight module **208** at the rear side of liquid crystal cell **210**. The backlight module **208** may comprise a high efficiency transmissive backlight cell assembly comprising sheets of brightness enhancement films and other polymeric films for enhancing light transmission and optical performances. However, any conventional backlight cell or high brightness backlight cell which may have edge or backside lamps can be used. Other backlight cells are also possible. The backlight module **208** can also be a transreflective or reflective type of light device with a transflector or a

reflector. The transflector or the reflector can be the reflective electrodes (not shown) deposited on the front surface of the rear substrate **203**, or a sheet member **1501** with transreflective or reflective properties positioned on the rear side of the liquid crystal layer **201**. The display integral **1500** (e.g. PT-TRIOLCD) can also include a first linear polarizer **206** which has a linear polarization axis and selectively polarizes the emitted light from the backlight module **208** to one direction. The linear polarizer **206** can be bonded to the rear surface of the liquid crystal cell **210**.

[0098] In one embodiment, the sheet member **1501** can simply comprise a reflective polarizer, which can be laminated to the rear surface of the linear polarizer **206** to form an integral. In other embodiments, the sheet member **1501** is comprised of a diffusing element or structure **1534** and a reflective polarizer **1535**. The reflective polarizer **1535** may absorb less than about 10% of the incident light energy in some embodiments. The reflective polarizer **1535** may also have an extinction coefficient, defined as the transmission of the p state polarization over the transmission of the s state polarization, ranging from about 1.5 to 9, for example. In addition, the polarization axis of the reflective polarizer **1535** may be parallel to or within about (+/-) 60 degrees in relation to the polarization axis of the first linear polarizer **206** in some embodiments. The first linear polarizer **206** and the reflective polarizer **1535** can be formed as an integral by being laminated with a layer of adhesive. It is also possible that in some embodiments, the reflective polarizer **1535** is used as the first linear polarizer **206**.

[0099] The reflective polarizer **1535** can be formed with multiple sheets of a selective reflective polarizer with optimized polarization axes. The reflective polarizer **1535** can also be a reflective polarizer that comprises a diffuser laminated thereto. The diffusing element or structure **1534** may be a corrugated surface with haze in the range of about 10% to 85% in some embodiments. The corrugated surface can be a roughened surface on the rear surface of the first linear polarizer **206** or on a separate transmissive polymeric substrate, such as PET, PC, PEN, TAC, or ARTON etc. The corrugated surface can also be a dielectric or other material, and may comprise, e.g., TiO_2 , Ta_2O_5 , SiO_2 , SiN , ITO , ZnS , Al_2O_3 , LaF_3 , MgF_2 , Ge , or Si , deposited on the rear surface of the first linear polarizer **206**, or on a separate sheet of transmissive substrate. The corrugated surface may comprise small metal particles, ranging in size from about 10 nm to 10000 nm, deposited on the rear surface of the first linear polarizer **206** or on a separate sheet transmissive substrate. The choice of the metal includes, for example, silver, gold, aluminum, copper, titanium, tantalum, chromium, nickel or an alloy thereof. One or more sheets of loose-packed or optically bonded transmissive substrates at least one of which has a corrugated surface can make up the diffusing element **1534**. In addition, diffusing element **1534** can be optically bonded to the rear surface of the first linear polarizer **206** or/and to the front surface of the reflective polarizer **1535**. The diffusing element can also be a layer of adhesive material, which bonds the first linear polarizer **206** and the reflective polarizer **1535** and comprises dispersed particles such that the haze value of the layer is in the range of about 10% to 85% in some embodiments. In other embodiments such as described herein where a diffuser is utilized, an adhesive material comprising diffusing particles may be used. This adhesive material comprising diffusing particles can diffuse the light. In certain embodiments, the

diffusing adhesive has a haze value in the range of about 10% to 85% as described above. Values outside these ranges as well as different configurations both well known as well as those yet devised are possible. Other types of diffusing structures may also be used and may be located elsewhere.

[0100] With continued reference to FIG. 15A, the display integral 1500 (e.g., PT-TRIOLCD) can further include a first retarder layer 205 to the front side of the liquid crystal cell 210. The first retarder layer 205 may comprise a quarter wave retarder having a retardance of about $(2m+1)\lambda/4$, where m is an integer and λ is between about 400 nm-700 nm. The first retarder layer 205 may comprise a single sheet retarder or a stack of laminated or loose sheets or a film or multiple films. The first retarder layer 205 may comprise quarter wave plates, half wave plates, or full wave plates. The rear surface of the first retarder layer 205 can be laminated to the front surface of the liquid crystal cell 210 with an index-matched pressure sensitive adhesive (PSA). Quarter wave plates with R/λ values in the range between curves 301 and 302, as shown in FIG. 3, can be used. For example, a quarter wave plate having an R/λ value between about 0.216 and 0.315 at a wavelength of about 520 nm may be employed. Half wave plates with R/λ values in the range between curves 303 and 304 as shown in FIG. 3 can be used. For example, a half wave plate of R/λ value between about 0.432 and 0.630 at a wavelength of about 520 nm may be employed. And full wave plates with R/λ values in the range between curves 305 and 306 as shown in FIG. 3 can be used. For example, a full wave plate having R/λ values between about 0.864 and 1.260 at a wavelength of about 520 nm may be employed.

[0101] The light polarization and configuration of the first circularly polarizing plate 1560 in arrangement of 1500 can be understood by the light polarization and configuration of the first circularly polarizing plate 1560 illustrated in FIGS. 16A, 16B, 16C and 16D. As indicated in the arrangements 1580 and 1590 of FIGS. 16C and 16D, respectively, the slow axis 1553 of the first retarder layer 205 may be set at an angle θ_0 in the range of about $-(25^\circ \text{ to } 65^\circ)$ or $25^\circ \text{ to } 65^\circ$, for example at about -45° or 45° , with respect to the polarization axis 1551 of the first linear polarizer 206 (as measured from the slow axis 1553 to the polarization axis 1551). It is common that a liquid crystal cell introduces a change of polarization state of the passing linearly polarized light due to the optical properties of twisted numerical liquid crystal layer sandwiched within. A most common polarization change introduced by the liquid crystal layer is 90 degree, which will be used as an example for the determination of configurations of the first circularly polarizing plate in this embodiment. Thus, as shown in the arrangement 1570 of FIG. 16B (see also FIG. 16A), the emitted light 1521 in display integral 1500 from the backlight module 208, passing through the first linear polarizer 206 with the direction of polarization of 1551, is altered by 90 degree to the polarization direction indicated by 1552 before entering the first retarder layer 205. Thus, the first linear polarizer 206, the liquid crystal cell 210, and the first retarder layer 205 constitute the first circularly polarizing plate 1560 with an effective configuration that is determined by the display module light transmission direction 1552 and the slow axis 1553. While viewed from the front side of the retardation plate 205 looking towards the LCD light source, as shown in arrangement 1580 of FIG. 16C, with angle θ_0 being substantially -45° , the angle θ_1 of the slow axis 1553 to the

display module light transmission polarization 1552 is substantially 45° . The configuration of the first circularly polarizing plate 1560 is thus effectively determined by the slow axis 1553 to the polarization direction 1552 to be a left-handed as previously defined (reference also FIG. 4A). Similarly as shown in arrangement 1590 of FIG. 16D, with angle θ_0 being substantially 45° , the configuration of the first polarizing plate 1560 is determined by the angle θ_1 , -45° , of the slow axis 1553 to the display module light transmission polarization 1552 to be right-handed (also reference FIG. 4B). Other values outside these ranges may be used.

[0102] Referring back to FIG. 15A, the display integral 1500 (e.g., PT-TRIOLCD) also includes a transparent protection panel 1510 that circularly polarizes incident sunlight 140. The protection panel has a front surface 1511 and a rear surface 1512. Practically, the transparent protection panel 1510 can be the integral of the linear polarizer 807 and the retarder layer 805. It is also possible that a separate transparent supportive substrate 1520 is added to form the transparent protection panel 1510. The transparent supportive substrate 1520 can be a sheet of glass or plastics. In some embodiments, the supportive substrate 1520 can also be a type of touch input device, such as a resistive touch panel, a capacitive touch panel, a SAW touch panel, a near field image touch panel, or an IR touch panel. The separate transparent supportive substrate 1520 can be at the rear side of the retarder layer 805 as shown in FIG. 15A. The supportive substrate 1520 can also be between the linear polarizer 807 and the retarder layer 805 as shown in FIG. 15B. The supportive substrate can further be at the front side of the linear polarizer 807 as shown in FIG. 15C. These sheet members of the protection panel 1510, regardless the positioning of the supportive substrate 1520, can be laminated to form an integrated panel. An isotropic transparent substrate can be used to construct the supportive transparent substrate 1520. It is also possible to use non-isotropic material and the retardance of the supportive transparent substrate 1520 may be taken into consideration. Or in some embodiments, the non-isotropic substrate 1520 can be positioned forward the linear polarizer 807 as shown in FIG. 15C to avoid interferences that may be generated by non-isotropic substrate. This circularly polarizing protection panel 1510 can effectively prevent the back reflections that would be generated by reflective surfaces or parts, such as an EMI shield, an IR block and a screen heater as discussed above. Thus, other functional parts comprising conductive films, such as an EMI shield, an IR block and a screen heater, can be integrated by introducing the parts on separate substrates to the rear side of the protection panel (not shown). Or these functional parts can be easily incorporated into the display integral 1500 using the front surface 207 of the first retarder layer 205 and the rear surface 1512 of the transparent protection panel 1510 as the surfaces for conductive film coating to from the above mentioned functional parts. Practically, EMI shielding and IR blocking (EMI/IR) can be integrated in a single sheet of transparent substrate coated with conductive film. To provide EMI shielding, the conductive film may be grounded. Screen heating and IR blocking functions (IR/heater) can also be achieved on a single sheet of transparent substrate coated with conductive film. The conductive film may also be electroded to provide current flow for resistive heating. In one embodiment, the IR blocker can also be a hot mirror coating comprising dielectric material and may comprise all dielectric material. Thus,

to incorporate either EMI/IR or/and IR/heater, a conductive film can be deposited on either (or both) surfaces **207** and **1512**. The conductive film may be deposited on the surface and may comprise, for example, ITO, ZnO, Ni, Cr, Au, ZrO_2 , TiO_2 , SiO_2 , or SnO_2 having a conductivity in the range, e.g., of about 1 ohm to 1000 ohm per square, a transmission of about 50% to 95% in the visible range of about 400 nm to 700 nm, and a reflectance of about 20% to 90% for wavelengths about 700 nm and greater. Values outside these ranges are possible. The EMI/IR or IR/heater may be provided with proper electrodes or grounding setups as discussed above. Various combinations are possible or alternatively only one functional part may be included. Integration of functional parts by introducing a separate conductive film coated substrate is also possible as mentioned above.

[0103] Still referring to FIG. 15A, the second retarder layer **805** may comprise a quarter wave retarder having a retardance of about $(2n+1)\lambda/4$, where n is an integer and λ is between about 400 nm-700 nm. The second retarder layer may comprise a single sheet retarder or a stack of laminated or loose sheets or a film or multiple films. The second retarder layer may comprise quarter wave plates, half wave plates, or full wave plates. Quarter wave plates with R/λ values in the range between curves **301** and **302**, as shown in FIG. 3, can be used. For example, a quarter wave plate having an R/λ value between about 0.216 and 0.315 at a wavelength of about 520 nm may be employed. Half wave plates with R/λ values in the range between curves **303** and **304** as shown in FIG. 3 can be used. For example, a half wave plate having an R/λ value between about 0.432 and 0.630 at a wavelength of about 520 nm may be employed. And full wave plates with R/λ values in the range between curves **305** and **306** as shown in FIG. 3 can be used. For example, a full wave plate having an R/λ value between about 0.864 and 1.260 at a wavelength of about 520 nm can be employed.

[0104] The polarization axis of the second linear polarizer **807** may be set at an angle θ_2 in the range of about $\pm(25^\circ-65^\circ)$, for example at about $\pm 45^\circ$, to the slow axis of the second retarder layer **805** forming the second circular polarizer **1540**. This second circular retarder effectively reduces or prevents the reflections from the reflective surfaces **1512**, the front surface **207** of **205**, or other highly reflective functional parts (not shown). However, as previously disclosed, the polarization axis of the second linear polarizer **807** can be conveniently set at an angle in the range of 0 to 360° regardless the orientation of the polarization axis of the first linear polarizer **205**.

[0105] As discussed with reference to FIG. 9, the design or configurations of the second and first circular retarders **840** and **860** may be determined by retardance of the two retarder layers, $(2m+1)\lambda/4$ for **205** and $(2n+1)\lambda/4$ for **807**, where n and m are integers and λ is about 400 nm-700 nm. When $(n+m)$ is 0 or an even integer, the configuration of the first and second circular retarders **860** and **840** are the same (e.g. both left-handed or both right-handed); see FIG. 9B. If $(n+m)$ is an odd integer, the configurations of the second and first circularly polarizers **840** and **860** are to be reverse to each other; see FIG. 9C. Other values outside these ranges may also be used.

[0106] As described above, however, the liquid crystal cell **210** may introduce a 90 degree rotation of a linearly polar-

ized light in some embodiments. The design of the structure **1500** may be adjusted to accommodate this 90° polarization change. In particular, the orientation of the polarizers and/or retarders may be altered in the first or second circular retarders, or both, in certain preferred embodiments.

[0107] With reference back to FIG. 15A, to determine the corresponding configurations of the first and second circular polarizers **1560** and **1540** in the display integral **1500** (e.g. PT-TRIO LCD), the retardance of the supportive substrate and functional part(s) may also be taken into consideration. In certain embodiments, the supportive substrate and functional parts are made of thin glass sheets or isotropic plastic sheets, such as PET, PEN, TAC, PC, ARTON, etc., with minimum retardation properties, for example with retardance less than about 80 nm. In such embodiments, with $(n+m)$ being 0 or an even integer, the propagation of LCD illumination **1521** is substantially equivalent to the propagation of the light **901** in the arrangement **910** of FIG. 9B. Accordingly, the configurations of the first and second circular retarders **1560** and **1540** can be determined to be the same as each other (e.g., both right-handed or both left-handed, like in FIG. 9B). That is to say, if the first circular retarder **1560** (which includes the effects of the 90° polarization rotation introduced by the liquid crystal cell **210**) is left-handed as shown in **1580** of FIG. 16C, the second circular retarder **1540** is also left-handed. For example, if the first circular retarder **1560** has an angle θ_1 that is substantially 45° as shown in **1580** of FIG. 16C, the polarization axis of the second linear polarizer **807** is set such that the angle from the polarization axis to the slow axis of the second retarder layer **805** is substantially at 45° , which makes the second circular retarder **1540** left-handed. And if the first circular retarder **1560** (which includes the effects of the 90° polarization rotation introduced by the liquid crystal cell **210**) is right-handed with θ_1 being substantially -45° as shown in **1590** of FIG. 16D, the polarization axis of the second linear polarizer **807** is set such that the angle from the polarization axis to the slow axis of the second retarder layer **805** is substantially at -45° , which makes the second circular retarder **1540** right-handed.

[0108] On the other hand, if $(n+m)$ is an odd integer and the retardance of the functional parts is not significant, the configurations of the first and second circular retarders **1560** and **1540** can be determined to be opposite as each other (e.g., one right-handed and one left-handed, like in FIG. 9C). That is to say, if the first circular retarder **1560** is left-handed as shown in **1580** of FIG. 16C (which includes the effects of the 90° polarization rotation introduced by the liquid crystal cell **210**), then the second circular retarder **1540** is right-handed. For example, if the first circular retarder **1560** has an orientation θ_1 that is substantially 45° as shown in the left-handed configuration **1580** of FIG. 16C, the polarization axis of the second linear polarizer **807** is set such that the angle from the polarization axis to the slow axis of the second retarder layer **805** is substantially at -45° , which makes the second circular retarder **1540** right-handed. And if the first circular retarder **1560** is right-handed with θ_1 being substantially -45° as shown in **1590** of FIG. 16D (which includes the effects of the 90° polarization rotation introduced by the liquid crystal cell **210**), the polarization axis of the second linear polarizer **807** is set such that the angle from the polarization axis to the slow axis of the second retarder layer **805** is substantially at 45° , which makes the second circular retarder **1540** left-handed.

[0109] In some other embodiments, the functional parts may contain significant retardance. The retardance of the functional parts may be integrated as a part of the first retarder layer retardance, which may be adjusted to obtain an effective retardance of about $(2m+1)\lambda/4$. The configurations of the first and second circular retarders 1560 and 1540 may be determined accordingly. Thus, efficient delivery of both reflective illumination 1550 and transmissive illumination 1521 to viewer's eyes can be achieved. Other configurations are also possible.

[0110] In various preferred embodiments, an air gap between components creates two air-material interfaces, which cause reflections due to index mismatch. These reflections may interfere and compromise the optical performances of the integral. The air-material interfaces can be eliminated by laminating the separate parts together and removing the air gap therebetween. However, adequately applying anti-reflection treatment or incorporating a diffusing property onto surfaces can also conveniently reduce undesirable backreflections and the resultant interference and enhance the optical properties of the integral. In some embodiments, the rear surface of the first retarder layer 205 can be laminated to the front surface of the liquid crystal cell 210 to form an integrated display module as described in FIG. 2. In such arrangements, a diffusing element or structure or an anti-reflection treatment (not shown) can be disposed on the front surface of the first retarder layer 205, the front or rear surface of the reflective parts (not shown), or the rear surface 1512 of the protection panel 1510 to curtail or prevent interference of the reflections and enhance the optical properties. The diffusing structure (not shown) can be a roughened surface or may comprise particles (as discussed in previous section) deposited on the front surface of the first retarder layer 205. In certain embodiments, the diffusing structure may comprise a laminated sheet member (not shown) with diffusing property of Haze value greater than zero. In other arrangements, the front surface of the first retarder layer 205 is laminated to the rear surface 1512 of the protection panel 1510. In such arrangements, an anti-reflection treatment (not shown) or diffusing structure may be disposed on at least one of the rear surface of the first retarder layer 205 and on the front surface of the liquid crystal cell 210 to achieve the equivalent optical performances. Different types of diffusing structures may be used and other configurations are possible (for example, the diffusing structure and/or anti-reflective coating may be located elsewhere).

[0111] In such arrangements, the color tone and contrast of the display may be substantially maintained by reducing or minimizing the optical path of light 1521. Color tone can also be maintained by setting the transmission direction of the second linear polarizer 807 at 90 degree with respect to the polarization axis of the first linear polarizer 206 or the reflective polarizer 1535.

[0112] With continued reference to FIG. 15A, as discussed above, in other embodiments, the polarization axis of the second linear polarizer 807 can be conveniently set at any orientation in the range of 0 to 360 degrees, e.g., at 90 degrees to the horizontal, regardless the orientation of the polarization axis of the first linear polarizer 206. At least two advantages result. First, setting the polarization axis at 90 degrees provides a cost saving in production. A linear polarizer is a relatively expensive raw material. A regular

polarized touch screen is usually made with 45° or 135° light in order to match up with the light transmission direction of a regular LCD, in which case the sheet of linear polarizer will need to be cut diagonally. In one embodiment, there is no need to restrict the orientation of the polarization axis of the second linear polarizer 807, and the polarizer sheet can be cut in any way, whichever is cost beneficial. Second, a 90° transmission direction can provide convenient viewing zones for viewers wearing sunglasses as discussed in connection with FIG. 11.

[0113] With further reference to FIG. 15A, the advantage of being able to deliver convenient viewing zones for viewers wearing polarized sunglasses can be achieved by further disposing a third retarder layer 1203 to the front side of the second linear polarizer 807 as described above. The third retarder layer 1203 may comprise a quarter wave retarder having a retardance of about $(2k+1)\lambda/4$, where k is an integer and λ is about 400 nm-700 nm. The third retarder layer 1203 may comprise a single sheet retarder or a stack of laminated or loose sheets or a film or multiple films. The third retarder layer 1203 may comprise quarter wave plates, half wave plates, or full wave plates. The third retarder layer 1203 converts the otherwise linearly polarized transmission 1521 to a circularly polarized transmission. The advantage of the effect can be similarly understood with reference to discussions of FIGS. 6 and 7. The front surface 1511 of the protection panel 1510 or the front surface 1204 of the third retarder layer 1203 may comprise a highly efficient multi-layer anti-reflection coating, for example, having reflection less than about 1.5% to reduce or prevent the surface reflection 1530 and to increase or maximize the entry of light beam 140 for reflective illumination 1550. In some embodiments, the front surface 1511 of the protection panel 1510 or the front surface 1204 of the third retarder layer 1203 can also comprise a separate transmissive substrate, e.g., glass or plastic, such as PET, PEN, TAC, PC, ARTON, with its front surface being coated with the highly efficient multi-layer anti-reflection coating, for example, providing reflection less than about 1.5%. The rear surface of the separate transmissive substrate can be bonded to the front surface of the second linear polarizer 807 or the front surface of the third retarder layer 1203 with index matching pressure sensitive adhesive (PSA). The combination of reduction or minimization of reflections, 1530 and 1531, and increase or maximization of LCD illumination, 1521 and 1550, in this embodiment, is sufficient to make the display integral 1500 (e.g. PT-TRIOLCD) direct sunlight readable. Values outside the ranges provided above and other configurations may be employed (for example, the anti-reflective coating may be located elsewhere).

[0114] Several examples are presented below; however these examples are not limiting.

EXAMPLE 1

[0115] A 10.4" NLP-LCD with right-handed circular polarization output was tested and demonstrates no dark viewing zones for viewers wearing polarized sunglasses.

[0116] In comparison, an 10.4" LCD with 45 degree linear polarization output with 200 nits measured brightness, shows dark viewing zones in directions of about 1:00 and 7:00 o'clock when viewed with polarized sunglasses on. This LCD was converted to an NLP-LCD with right-handed

circular polarization output by laminating a quarter wave retardation film, 65 μm in thickness, with its slow axis oriented at an angle of -45° with respect to the linear polarization of the LCD. The brightness of the converted LCD was measured as 185 nits and showed no dark viewing zones when viewed with polarized sunglasses on.

EXAMPLE 2

[0117] A 10.4" NLP-LCD integrated with a polarized resistive touch panel shows no limitation on the orientation of the second circularly polarizing plate on the touch panel. The second right-handed circularly polarizing plates were prepared by laminating together a quarter wave plate retarder described in Example 1 and a linear polarizer having a thickness of 100 μm , a transmission $\sim 43\%$, and a polarization coefficient $\sim 96\%$. The second right-handed circular polarizer was laminated in various orientations on a 5-wired 10.4" resistive touch panel (82% transmission) to generate low reflection polarized touch panels. The low reflection polarized touch panel with various orientation of the second linear polarization axis was then disposed on the NLP-LCD generated as described in Example 1. Brightness of light output was measured. The brightness measured and the various orientations of the polarization axis are summarized below:

Orientation of the second linear polarization axis (degrees)	Brightness (nits) of the light output from the touch panel integrated NLP-LCD
0	146
15	146
45	148
75	145
90	146
105	145
135	143
165	145
180	146

[0118] As it can be seen from the measurements, the brightness is generally constant and was not affected by the orientation of the second linear polarization axis of the polarized touch panel. The orientation of 90° showed almost full brightness when it was viewed at 6:00 o'clock of direction and showed dark viewing zones in viewing directions of 3:00 and 9:00 o'clock when viewed through polarized sunglasses. Overall, an arrangement with the second linear polarization axis being at 90° provides more convenient viewing experiences for viewers wearing polarized sunglasses.

[0119] In various embodiments describe herein, commercial TFT LCDs, protective panels, resistive touch panel, and conductive films for EMI shield, IR block, screen heater of various sizes and structures can be readily be modified and integrated to generate multi-function display structures that are viewable under direct sunlight and also providing convenient viewing zones for viewers wearing polarized sunglasses. Other advantages are also possible.

[0120] Other configurations may also be used. Additional components may be added, components may be removed, or the order of the components may be altered. Values other than those specifically recited above may be used. Other

variations, both those well known in the area as well as those yet to be devised are also possible.

What is claimed is:

1. A polarizing liquid crystal display protection panel having a protection panel rear surface and a protection panel front surface through which light from a display module may pass and exit to a viewer, said protection panel comprising:

a retarder layer RB having a front surface, a rear surface, a slow axis RBX, and a retardance of about $(2m+1)\lambda/4$, where m is an integer and λ is between about 400 nm to 700 nm;

a linear polarizer PB forward said retarder layer RB and closer to the viewer, said linear polarizer PB having a linear polarization axis PBX that forms an angle θ_2 of about 45° or -45° to said slow axis RBX of said retarder layer RB; and

a transparent supportive panel, said transparent supportive panel comprises a sheet of glass substrate, a sheet of plastic substrate, or a touch input device,

wherein at least one of said panel front and rear surfaces comprises an anti-reflection treatment.

2. The protection panel of claim 1, wherein said transparent supportive panel is positioned forward said linear polarizer PB.

3. The protection panel of claim 1, wherein said transparent supportive panel is positioned between said linear polarizer PB and said retarder layer RB.

4. The protection panel of claim 1, wherein said transparent supportive panel is positioned rearward said retarder layer RB.

5. The protection panel of claim 1 further comprising a retarder layer RC, said retarder layer RC comprising one or more retarders oriented such that display module light exits as elliptical or circular polarized light.

6. A polarizing protection panel liquid crystal display integral comprising:

a liquid crystal display module having a module front surface that selectively outputs linearly polarized light oriented along a linear polarization axis PAX, said liquid crystal display module comprising a backlight module and a liquid crystal cell having a liquid crystal layer sandwiched between two transparent substrates;

a polarizing protection panel forward said liquid crystal display module, said polarizing protection panel has a protection panel rear surface and a protection panel front surface and comprises a transparent supportive panel and a linear polarizer PB with a linear polarization axis PBX that is positioned either forward or rearward said transparent supportive panel; and

a display front surface through which light from said backlight module exits,

wherein said transparent supportive panel of said protection panel comprises a sheet of glass substrate, a sheet of plastic substrate, or a touch input device and at least one of said display front surface, said protection panel rear surface, and said module front surface comprises an anti-reflection treatment.

7. The display integral of claim 6, wherein said transparent supportive panel comprises a linear polarizer forward said liquid crystal cell.

8. The display integral of claim 6, wherein said protection panel further comprising a retarder layer RB having a front surface, a rear surface, and a slow axis RBX with a retardance of about $(2m+1)\lambda/4$, where m is an integer and λ is between about 400 nm to 700 nm, said retarder RB being positioned at the rear side of said linear polarizer PB such that said linear polarization axis PBX forms an angle θ_2 of about $\pm 45^\circ$ to said slow axis RBX and said transparent supportive panel being in one of the following positions: forward said linear polarizer PB, rearward said retarder layer RB, or between said linear polarizer PB and retarder layer RB.

9. The display integral of claim 8, further comprising a reflective functional part rearward said retarder layer RB, said reflective functional part having a rear surface and comprising at least one of an EMI shield, an infrared filter, and an LCD heater which is formed by conductive film coating on the rear surface of said retarder RB or by conductive film coating on a separate substrate.

10. The display integral of claim 8 further comprising a retarder layer RA rearward said protection panel and forward said display module, said retarder layer RA having a front surface, a rear surface, a retardance of about $(2n+1)\lambda/4$, and a slow axis RAX, which forms an angle θ_1 to said linear polarization axis PAX, where n is an integer and λ is between about 400 nm to 700 nm.

11. The display integral of claim 10, where in said θ_1 is between about $+25^\circ$ to about $+65^\circ$ and θ_2 is about $+45^\circ$, or θ_1 is between about -25° to about -65° and θ_2 is about -45° when $(m+n)$ is zero or an even integer.

12. The display of claim 10, wherein θ_1 is between about $+25^\circ$ to about $+65^\circ$ and θ_2 is about -45° , or θ_1 is between about -25° to about -65° and θ_2 is about $+45^\circ$ when $(m+n)$ is an odd integer.

13. The display integral of claim 10, further comprising a reflective functional part rearward the retarder layer RB, said reflective functional part having a front surface and a rear surface and comprising at least one of an EMI shield, an infrared filter, and an LCD heater which comprises a conductive film coating on said retarder RB rear surface or said retarder RA front surface or a conductive film coating on a separate substrate.

14. The display integral of claim 10, wherein at least one of said display front surface, said protection panel rear surface, said RA retarder layer front and rear surfaces, and said module front surface comprises an anti-reflection treatment.

15. A polarizing protection panel transfective liquid crystal display integral comprising:

a transfective liquid crystal display module having a module front surface that selectively outputs linearly polarized light oriented along a linear polarization axis PAX, said transfective liquid crystal display module comprising a liquid crystal cell having a liquid crystal layer sandwiched between two transparent substrates, a partial reflector comprising a reflective electrode or reflective sheet member, and a backlight module;

a retarder layer RA forward said transfective liquid crystal display module, said retarder layer RA having a front surface, a rear surface, a retardance of about

$(2n+1)\lambda/4$, and a first slow axis, which forms an angle θ_1 to said linear polarization axis PAX, where n is an integer and λ is between about 400 nm to 700 nm;

a polarizing protection panel forward said liquid crystal display module, said protection panel having a protection panel rear surface and a protection panel front surface and comprising a transparent supportive panel, a retarder layer RB having a slow axis RBX with a retardance of about $(2m+1)\lambda/4$, where m is an integer and λ is between about 400 nm to 700 nm, and a linear polarizer PB having a linear polarization axis PBX, which forms an angle θ_2 to said slow axis RBX; and

a display front surface through which light from said backlight module exits,

wherein said linear polarizer PB of said protection panel is disposed at the front side of said retarder layer RB of said protection panel and said transparent supportive panel of said protection panel comprises a sheet of glass substrate, a sheet of plastic substrate, or a touch input device and is positioned forward said linear polarizer PB, rearward said retarder layer RB, or between said linear polarizer PB and said retarder layer RB.

16. The display integral of claim 15, wherein said partial reflector comprises a reflective polarizer and a diffusing element, said diffusing element being a layer of adhesive or a corrugated diffusing surface.

17. The display integral of claim 15, further comprising a reflective functional part rearward said retarder layer RB, said reflective functional part having a rear surface and comprising at least one of an EMI shield, an infrared filter, and an LCD heater which is formed by a conductive film coated on the rear surface of said retarder RB or by a conductive film coated on a separate substrate.

18. The display integral of claim 15, wherein at least one of said display front surface, said protection panel front and rear surfaces, said RA retarder layer front and rear surfaces, and said module front surface comprises an anti-reflection treatment.

19. The display integral of claim 17, wherein at least one of said display front surface, said protection panel front and rear surfaces, said RA retarder layer front and rear surfaces, and said module front surface comprises an anti-reflection treatment.

20. A polarizing protection panel transfective liquid crystal display integral comprising:

a transfective liquid crystal display module having a module front surface, said transfective liquid crystal display module comprising, from front to rear, a linear polarizer PA having a linear polarization axis PAX, a liquid crystal cell having a liquid crystal layer sandwiched between two transparent substrates, a partial reflector comprising reflective electrode or reflective sheet members, and a backlight module;

a retarder layer RA forward said transfective liquid crystal display module, said retarder layer RA having a front surface, a rear surface, a retardance of about $(2n+1)\lambda/4$, and a first slow axis, which forms an angle θ_1 to said linear polarization axis PAX, where n is an integer and λ is between about 400 nm to 700 nm;

a polarizing protection panel forward said liquid crystal display module, said protection panel having a protec-

tion panel rear surface and a protection panel front surface and comprising a transparent supportive panel, a retarder layer RB having a slow axis RBX with a retardance of about $(2m+1)\lambda/4$, where m is an integer and λ is between about 400 nm to 700 nm, and a linear polarizer PB having a linear polarization axis PBX, which forms an angle θ_2 to said slow axis RBX; and a display front surface through which light from said backlight module exits,

wherein said linear polarizer PB of said protection panel is at the front side of said retarder layer RB of said protection panel and said transparent supportive panel of said protection panel comprises a sheet of glass substrate, a sheet of plastic substrate, or a type of touch input device and is positioned forward said linear polarizer PB, rearward said retarder layer RB, or between said linear polarizer PB and said retarder layer RB.

21. The display integral of claim 20, wherein said partial reflector comprises a reflective polarizer and a diffusing

element, said diffusing element being a layer of adhesive or a corrugated diffusing surface.

22. The display integral of claim 20, further comprising a reflective functional part rearward said retarder layer RB, said reflective functional part having a rear surface and comprising at least one of an EMI shield, an infrared filter, and an LCD heater which is formed by a conductive film coating on the rear surface of said retarder RB or by conductive film coating on a separate substrate.

23. The display integral of claim 20, wherein at least one of said display front surface, said protection panel front and rear surfaces, said RA retarder layer front and rear surfaces, and said module front surface comprises an anti-reflection treatment.

24. The display integral of claim 22, wherein at least one of said display front surface, said protection panel front and rear surfaces, said RA retarder layer front and rear surfaces, and said module front surface comprises an anti-reflection treatment.

* * * * *

专利名称(译)	控制液晶显示器的偏振		
公开(公告)号	US20070279556A1	公开(公告)日	2007-12-06
申请号	US11/842017	申请日	2007-08-20
[标]申请(专利权)人(译)	王冉红 - [R 王敏SHINCÇ		
申请(专利权)人(译)	王然，洪ř 王民SHINCÇ		
当前申请(专利权)人(译)	王然，洪ř 王民SHINCÇ		
[标]发明人	WANG RAN HONG RAYMOND WANG MIN SHINC CHOW		
发明人	WANG, RAN-HONG RAYMOND WANG, MIN-SHINC CHOW		
IPC分类号	G02F1/1335		
CPC分类号	G02F1/133502 G02F1/133528 G02F1/13363 G02F2001/133531 G02F2413/07 G02F2001/133638 G02F2201/50 G02F2413/03 G02F2001/133541		
外部链接	Espacenet USPTO		

摘要(译)

液晶显示器保护板和液晶显示器保护板积分的某些实施例对于户外应用具有低反射。各种实施例还具有能够为佩戴偏振太阳镜的户外观众的某些方便观看方向提供增强的对比度和亮度的优点。

