



US007130006B2

(12) **United States Patent**
Chu et al.

(10) **Patent No.:** **US 7,130,006 B2**
(45) **Date of Patent:** **Oct. 31, 2006**

(54) **LIQUID CRYSTAL DISPLAY DEVICE AND
FABRICATING METHOD THEREOF**

(75) Inventors: **Hung-Jen Chu**, Nantou County (TW);
Chien-Kuo He, Taipei County (TW);
Meng-Feng Hung, Changhua County
(TW)

(73) Assignee: **Chunghwa Picture Tubes, Ltd.**, Taipei
(TW)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 118 days.

(21) Appl. No.: **10/707,085**

(22) Filed: **Nov. 20, 2003**

(65) **Prior Publication Data**

US 2005/0062910 A1 Mar. 24, 2005

(30) **Foreign Application Priority Data**

Sep. 24, 2003 (TW) 92126303 A

(51) **Int. Cl.**
G02F 1/1333 (2006.01)

(52) **U.S. Cl.** **349/110; 349/111; 349/44**

(58) **Field of Classification Search** **349/110-111,**
349/44

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,081,305 A *	6/2000	Sato et al.	349/5
6,097,457 A *	8/2000	Kim et al.	349/110
6,580,486 B1 *	6/2003	Sekine	349/139
2003/0076459 A1 *	4/2003	Murade	349/111

* cited by examiner


Primary Examiner—James A. Dudek

(74) *Attorney, Agent, or Firm*—Jianq Chyun IP Office

(57) **ABSTRACT**

A liquid crystal display device comprising a first substrate, a second substrate, a liquid crystal layer and a shading film is provided. The first substrate includes a display region and a non-display region. The liquid crystal layer is sandwiched between the first substrate and the second substrate. The shading film is located between the first substrate and the liquid crystal layer covering the non-display region. With the shading film covering the entire non-display region, the problem of light leakage from the edge of the display device is resolved.

7 Claims, 6 Drawing Sheets






FIG. 1 (PRIOR ART)




FIG. 2




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 6




FIG. 7




FIG. 8

LIQUID CRYSTAL DISPLAY DEVICE AND FABRICATING METHOD THEREOF

BACKGROUND OF INVENTION

1. Field of the Invention

The present invention relates to a display device and fabricating method thereof. More particularly, the present invention relates to a liquid crystal display device and fabricating method thereof.

2. Description of the Related Art

With big advance in electronic technologies, digital video products or imaging devices has become one of the most common electronic gadgets in our daily life. Among various video products and imaging devices, display devices inarguably occupy a central position because a user must extract information from a display device, or in the case of performing a real-time control, receive real-time data from a display device.

To fit the lifestyle of modern day people, the size and weight of video and imaging products must be reduced as much as possible. Although cathode ray tubes (CRT) still has some advantages, bulkiness and volume are the two major setbacks that reduce its popularity in the future. With breakthroughs in photo-electronic and semiconductor fabrication technologies, panel type displays such as the liquid crystal displays are starting to replace the conventional CRT because of its low operating voltage, radiation free operation and light-weight and streamline body. In fact, researches in liquid crystal display and other flat panel displays such as plasma display panel and electro-luminance displays have dominated the field in recent years due to its potential as a mainstream product in the market.

In general, a thin film transistor (TFT) liquid crystal display comprises a thin film transistor array substrate, a color filter substrate and a liquid crystal layer. FIG. 1 is a schematic cross-sectional view of a conventional liquid crystal display panel. The liquid crystal display panel in FIG. 1 comprises a color filter substrate **100**, a thin film transistor array substrate **102**, a sealant **104** and a liquid crystal layer **106**. The liquid crystal layer **106** is enclosed within the space bounded by the color filter substrate **100**, the thin film transistor array substrate **102** and the sealant **104**. The color filter substrate **100** further comprises a color filter **113** and a black matrix **114**. Furthermore, the thin film transistor array substrate **102** comprises a display region **108** and a non-display region **110**. The non-display region **110** has a plurality of lead lines **112** serving as drivers for operating the display device.

To form the liquid crystal layer **106**, the sealant **104** is placed between the substrates **100** and **102** to form an enclosed space. Thereafter, a small quantity of liquid crystal is gradually filled into the space between the color filter substrate **100** and the thin film transistor array substrate **102** under a capillary effect due to the presence of an external atmospheric pressure. Because the injection speed of liquid crystal under capillary effect is slow, other injection techniques such as the one-drop fill (ODF) process is deployed. In the one-drop fill process, a layer of UV sealant is coated on the thin film transistor array substrate **102** (or the color substrate **100**) to form a sealant **104**. Each drop of liquid crystal is dropped inside the area enclosed by the sealant **104**. Thereafter, the color filter substrate **100** (or the thin film transistor array substrate **102**) is placed over the sealant **104**.

The sealant **104** is illuminated with UV light so that the sealant **104** hardens so that the sealant **104** bonds the color filter substrate **100** and the thin film transistor array substrate **102** together.

Using the ODF technique, time for injecting liquid crystal into a liquid crystal display panel is reduced considerably. For example, only 2 hours are required to fill a 30 inches panel using the ODF technique. If the same display panel is filled using the capillary injection technique, roughly five days are required. Hence, production time is shortened considerably. Furthermore, ODF technique requires only 40% of the liquid crystal needed in a capillary injection process. However, care must be executed to prevent any contamination of the liquid crystal by the sealant that may lead to liquid crystal display problems. In general, the black matrix (BM) **114** on the color filter substrate **100** has to move a definite distance toward the central area of the panel. With the black matrix (BM) **114** moved from the edges, a strip of area **116** adjacent to the edge is no longer covered with any barrier. Since the gap between lead lines **112** in the non-display region **110** has no barrier, light can easily leak from the edge of the display panel.

SUMMARY OF INVENTION

Accordingly, one objective of the present invention is to provide a liquid crystal display device capable of minimizing the amount of light leakage from the edges of the display device.

Another objective of the present invention is to provide a method of fabricating a liquid crystal display device capable of minimizing the amount of light leakage from the edges of the display device without increasing the number of processing steps.

To achieve these and other advantages and in accordance with the purpose of the invention, as embodied and broadly described herein, the present invention provides a liquid crystal display device. The display device comprises a first substrate, a second substrate, a liquid crystal layer and a first shading film. The first substrate includes a display region and a non-display region positioned around the periphery of the first substrate. The liquid crystal layer is sandwiched between the first substrate and the second substrate. The first shading film is set between the first substrate and the liquid crystal layer within the non-display region. Furthermore, the first substrate further includes at least a thin film transistor with at least a gate and a source/drain.

The present invention also provides a method of fabricating a liquid crystal device. First, a first substrate is provided. The first substrate has a display region and a non-display region positioned around the periphery of the display region. Thereafter, at least a thin film transistor is formed within the display region. The method of forming the thin film transistor includes forming a gate over the first substrate, forming an insulating layer over the first substrate to cover the gate, forming a channel layer over the insulating layer above the gate and forming a source source/drain region over the channel layer. The process of fabricating the thin film transistor further includes forming a first shading film within the non-display region. The first shading film is formed together with either the gate or the source/drain. Thereafter, a second substrate is provided. A sealant is formed on the first substrate or the second substrate. A liquid crystal layer is formed on the substrate surface with the sealant. The first substrate and the second substrate are bonded together and then the sealant is illuminated.

3

In the aforementioned liquid crystal display device and fabricating method, the first shading film is set over the non-display region in such a way that the entire non-display region is covered.

The aforementioned liquid crystal display device and fabricating method thereof further includes forming a plurality of lead lines within the non-display region. The lead lines and the gate are fabricated together or the lead lines and the source/drain are fabricated together. When the lead lines and the gate are fabricated together, the first shading film and the source/drain are formed at the same time in a position above the gap between neighboring lead lines within the non-display region. Alternatively, an additional second shading film is set up within the non-display region. The second shading film and the gate are formed together and positioned between neighboring lead lines. Furthermore, the second shading film is electrically isolated from its neighboring lead lines. The first shading film is set over the gap between the second shading film and an adjacent lead line.

When the lead lines and the source/drain are formed at the same time, the first shading film and the gate are fabricated together and positioned underneath the gap between neighboring lead lines within the non-display region. Alternatively, an additional second shading film is set within the non-display region. The second shading film and the source/drain are formed together and positioned between neighboring lead lines. Furthermore, the second shading film is electrically isolated from its neighboring lead lines. The first shading film is set underneath the gap between the second shading film and an adjacent lead line.

In the present invention, an additional shading film is set between the liquid crystal layer and the first substrate of the liquid crystal display device. The shading film essentially blocks out any light trying to escape through the non-display region near the edge of the display device.

In the process of fabricating the liquid crystal display device, the first shading film is formed within the non-display region close to the edge of the substrate together with the source/drain (or the gate). Hence, there is no need to introduce extra processing steps just to prevent any light leakage from the edge of the display device.

It is to be understood that both the foregoing general description and the following detailed description are exemplary, and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF DRAWINGS

The accompanying drawings are included to provide a further understanding of the invention, and are incorporated in and constitute a part of this specification. The drawings illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention.

FIG. 1 is a schematic cross-sectional view of a conventional liquid crystal display panel.

FIG. 2 is a schematic cross-sectional view of a liquid crystal display device according to a first preferred embodiment of this invention.

FIG. 3 is a schematic cross-sectional view of a liquid crystal display device according to a second preferred embodiment of this invention.

FIG. 4 is a schematic cross-sectional view of a liquid crystal display device according to a third preferred embodiment of this invention.

4

FIGS. 5A through 5D are schematic cross-sectional views showing the steps for fabricating a liquid crystal display device according to one preferred embodiment of this invention.

FIG. 6 is a schematic cross-sectional view of a liquid crystal display device according to a fourth preferred embodiment of this invention.

FIG. 7 is a schematic cross-sectional view of a liquid crystal display device according to a fifth preferred embodiment of this invention.

FIG. 8 is a schematic cross-sectional view of a liquid crystal display device according to a sixth preferred embodiment of this invention.

DETAILED DESCRIPTION

Reference will now be made in detail to the present preferred embodiments of the invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers are used in the drawings and the description to refer to the same or like parts.

FIG. 2 is a schematic cross-sectional view of a liquid crystal display device according to a first preferred embodiment of this invention. The liquid crystal display device comprises a first substrate **200**, a second substrate **202**, a liquid crystal layer **204** and a first shading film **222**. The first substrate **200** is a color filter substrate with a color filter **208** thereon, for example. The color filter **208** further comprises a plurality of red (R) filter films **210**, green (G) filter films **210** or blue (B) filter films **210**. The color filter **208** are organized into a mosaic, a delta or a stripe pattern. In addition, a net-like black matrix **212** is also formed in the space between the color filter **208**. A plurality of other film layers (not shown) may also be formed over the color filter **208** such as a passivation film **226**, a metal electrode film and an alignment film. The passivation film **226** can protect the color filter **208**, and make it planar. Furthermore, the electrode film may be fabricated using indium-tin-oxide (ITO) or equivalent materials. The alignment film serves as a guide to orient any liquid crystal molecules on the film to a pre-defined direction (alignment) so that the liquid crystal molecules are pre-tilted. The other surface of the first substrate **200** may include a polarizing plate (not shown) that provides a display function.

The second substrate **202** is thin film transistor array substrate, for example. The second substrate **202** comprises a display region **214** and a non-display region **216**. The display region **214** includes at least a thin film transistor **217** (having a gate **302**, a source **306a** and a drain **306b**). The non-display region **216** includes a plurality of lead lines **218** thereon. Furthermore, an insulation layer **220** that joins with the gate insulation layer of the thin film transistor **217** is also formed over the lead lines **218**.

The first shading film **222** is set between the second substrate **202** and the liquid crystal layer **204** within the non-display region **216**. The first shading film **222** is formed using a substance selected from a group of conductive and non-transparent materials, for example.

It is to be noted that the first shading film **222** and the source **304a**/drain **304b** (**306a**/**306b**) in this embodiment are fabricated using the same film material. In other words, the first shading film **222** and the source **306a**/drain **306b** are formed together in the same step. Similarly, the lead lines **218** and the gate **302** are fabricated using the same film material. In an alternative embodiment, the first shading film **222** and the gate **302** are fabricated using the same film material. In other words, the first shading film **222** and the

gate 302 are formed together in the same step. In this case, the lead lines 218 and the source 306a/drain 306b are also fabricated using the same film material.

The first shading film 222 is set on the non-display region 216 so that the first shading film 222 covers the non-display region 216 completely (as shown in FIG. 2) or lies underneath the non-display region 216 (as shown in FIG. 6).

In another embodiment of this invention, the first shading film 222 is set over (or underneath) the gaps between neighboring lead lines 218 within the non-display region 216 (as shown in FIG. 3 and FIG. 7). With this structural setup, the first shading film 222 is prevented from forming a short circuit with neighboring lead lines 218 and the first shading film 222 due to some imperfection in the process of fabricating the first shading film 222.

In another embodiment, a second shading film 224 is formed within the non-display region 216. The second shading film 224 is set between neighboring lead lines 218 and electrically isolated from them. Furthermore, the first shading film 222 is positioned over (or underneath) the gap between the second shading film 224 and the lead line 218 (as shown in FIG. 4 and FIG. 8). With this structural setup, the first shading film 222 is prevented from forming a short circuit with neighboring lead lines 218 and the first shading film 222 due to some imperfection in the process of fabricating the first shading film 222.

In addition, the sealant 206 is set between the first substrate 200 and the second substrate 202 to form an interior space for holding the liquid crystal molecules. The sealant 206 is fabricated from a UV photosensitive material, for example.

Obviously, other film layers may also be formed over the second substrate 202. For example, a passivation film 226, an electrode film (not shown) and an alignment film (not shown) are sequentially formed over the second substrate 202. Furthermore, a polarizing plate (not shown) may also be formed on the other surface of the second substrate 202.

Accordingly, an additional shading film is formed between the liquid crystal layer and the second substrate 202. The shading film is set in such a way that the non-display region is completely covered by the shading film or the shading film is set over the gap between neighboring lead lines. Alternatively, a shading film is first set in the gap between neighboring lead lines and then another shading film is set over the gap between the first shading film and the lead lines. Hence, this invention provides an effective means of preventing light leakage from the edge of the display device (the non-display region).

FIGS. 5A through 5D are schematic cross-sectional views showing the steps for fabricating a liquid crystal display device according to one preferred embodiment of this invention. In particular, FIGS. 5A through 5C illustrates the process of fabricating a substrate 202. As shown in FIG. 5A, a substrate 300 is provided. The substrate 300 includes a display region 214 and a non-display region 216 positioned around the periphery of the substrate 300. The substrate 300 is a glass substrate or a transparent plastic substrate, for example. Thereafter, a metallic layer having a thickness of several thousand angstroms is formed over the substrate 300 and then patterned to form at least a gate 302 within the display region 214 and a plurality of lead lines 218 within the non-display region 216. The metallic layer is formed, for example, by performing a sputtering. The lead lines 218 subsequently serve as driving lines for the device. Next, an insulation layer 220 is formed over the substrate 300 globally to cover the gate 302 and the lead lines 218. The

insulation layer 220 is, for example, a silicon nitride layer or a silicon oxide layer formed by performing a plasma chemical vapor deposition.

As shown in FIG. 5B, a channel material layer (not shown) is formed over the insulation layer 220 and then patterned to form a channel layer 304. The channel layer 304 is positioned over the insulation layer 220 above the gate 302 and is fabricated using amorphous silicon, for example.

As shown in FIG. 5C, another metallic layer (not shown) is formed over the substrate 300 and then patterned to form a source 306a/drain 306b and a first shading film 222. The first shading film 222 is fabricated using a substance selected from a group of conductive and non-transparent materials. The gate 302, the channel layer 304 and the source 306a/306b together form a thin film transistor 217. It is to be noted that in one embodiment of this invention, the first shading film 222 covers the entire non-display region 216 (as shown in FIG. 2 and FIG. 5C). In another embodiment, the first shading film 222 is formed over the gap between neighboring lead lines 218 (as shown in FIG. 3) so that a short circuit between the first shading film 222 and the lead lines 218 due to manufacturing defect is prevented.

In another embodiment, in the process of forming the lead lines 218, a second shading film 224 is also patterned out in the gap between neighboring lead lines 218. The second shading film 224 is electrically isolated from neighboring lead lines 218 (as shown in FIG. 4) and is fabricated using a substance selected from a group of conductive and non-transparent materials. Thereafter, in the process of patterning out the source 306a/drain 306b, the first shading film 222 is also simultaneously patterned so that the patterned first shading film 222 is located above the gap between the second shading film 224 and neighboring lead lines 218. Consequently, the probability of having a short circuit between the first shading film 222 and the lead lines 218 due to an imperfection in the manufacturing process is minimized.

Obviously, other film layers may also be formed over the substrate 300. For example, a passivation film 226, an electrode film (not shown) and an alignment film (not shown) are sequentially formed over the substrate 202. Furthermore, a polarizing plate (not shown) may also be formed on the other surface of the substrate 300.

As shown in FIG. 5D, a color filter substrate 200 is provided. The color filter substrate 200 has at least a black matrix 212 and a color filter 210 thereon. A sealant 206 is coated on the substrate 300 or on the color filter substrate 200 just outside the black matrix 212 to form an enclosed area. Thereafter, liquid crystal 204 is dropped into the area enclosed by the UV sealant 206 and then the thin film transistor substrate 300 and the color filter substrate 200 are pressed together. Finally, ultraviolet light 308 is shone to harden the sealant 206 and bind the two substrates (200 and 300) together.

In the aforementioned embodiment, the first shading film 222 and the source 306a/drain 306b are formed together in the same step. However, if the lead lines 218 and the source 306a/drain 306b are formed together in the same step, the first shading film 222 and the gate 302 can be formed together in the same step. When the first shading film 222 and the gate 302 are formed together in the same step, the first shading film 222 may lie underneath the non-display region 216 (as shown in FIG. 6) in one embodiment. Alternatively, the first shading film 222 may lie underneath the gap between neighboring lead lines 218 (as shown in FIG. 7).

7

In another embodiment, the second shading film **224** is formed in the gap between neighboring lead lines **218** and are formed together in the same step. However, the second shading film **224** is electrically isolated from neighboring lead lines **218** (as shown in FIG. **8**). The first shading film **222** is formed underneath the gap between the second shading film **224** and the lead lines **218**. With this setup, a short circuit between the first shading film **222** and the lead lines **218** can be prevented.

According to the method of fabricating liquid crystal display device in this invention, a shading film is formed within the non-display region of a substrate near the edge of the substrate in the process of fabricating the source/drain (or gate). Alternatively, a second shading film the gate (or source/drain) are formed in the same step. Hence, there is no need to introduce an extra step in the fabricating process just to prevent the leakage of light from the edges of the display device.

It will be apparent to those skilled in the art that various modifications and variations can be made to the structure of the present invention without departing from the scope or spirit of the invention. In view of the foregoing, it is intended that the present invention cover modifications and variations of this invention provided they fall within the scope of the following claims and their equivalents.

The invention claimed is:

1. A liquid crystal display device, comprising:

- a first substrate having a display region and a non-display region around the periphery of the display region;
- a second substrate;
- a liquid crystal layer sandwiched between the first substrate and the second substrate;
- a first shading film disposed between the first substrate and the liquid crystal layer within the non-display region of the first substrate;

8

a plurality of lead lines disposed over the non-display region of the first substrate; and

a second shading film disposed over the gap between neighboring lead lines within the non-display region, wherein the second shading film is electrically isolated from the neighboring lead lines, and the first shading film is disposed over the gap between the second shading film and neighboring lead lines, such that the first shading film, the second shading film and the lead lines are located at different height levels and electrically isolated from one another.

2. The liquid crystal display device of claim **1**, wherein the first shading film covers over the non-display region.

3. The liquid crystal display device of claim **1**, wherein the first shading film is positioned over the gap between neighboring lead lines within the non-display region and the first shading film and the lead lines are electrically isolated from each other and located at different height levels.

4. The liquid crystal display device of claim **1**, wherein the first substrate includes at least a thin film transistor with a gate, a source and a drain.

5. The liquid crystal display device of claim **4**, wherein the first shading film and the source/drain are fabricated using the same film material.

6. The liquid crystal display device of claim **1**, further comprising a black matrix layer set between the second substrate and the liquid crystal layer.

7. The liquid crystal display device of claim **4**, wherein the first shading film and the gate are fabricated using the same film material.

* * * * *

专利名称(译)	液晶显示装置及其制造方法		
公开(公告)号	US7130006	公开(公告)日	2006-10-31
申请号	US10/707085	申请日	2003-11-20
[标]申请(专利权)人(译)	储宏仁 何CHIEN KUO 洪猛冯		
申请(专利权)人(译)	主鸿仁 何建KUO 洪猛，冯		
当前申请(专利权)人(译)	中华映管股份有限公司.		
[标]发明人	CHU HUNG JEN HE CHIEN KUO HUNG MENG FENG		
发明人	CHU, HUNG-JEN HE, CHIEN-KUO HUNG, MENG-FENG		
IPC分类号	G02F1/1333 G02F1/1335 G02F1/1345		
CPC分类号	G02F1/133512 G02F1/1345 G02F2001/133388		
优先权	092126303 2003-09-24 TW		
其他公开文献	US20050062910A1		
外部链接	Espacenet USPTO		

摘要(译)

提供一种液晶显示装置，包括第一基板，第二基板，液晶层和遮光膜。第一基板包括显示区域和非显示区域。液晶层夹在第一基板和第二基板之间。遮光膜位于第一基板和覆盖非显示区域的液晶层之间。在遮光膜覆盖整个非显示区域的情况下，解决了从显示装置的边缘漏光的问题。

