



US007327416B2

(12) **United States Patent**
Lee et al.

(10) **Patent No.:** **US 7,327,416 B2**
(45) **Date of Patent:** **Feb. 5, 2008**

(54) **BACK LIGHT ASSEMBLY AND LIQUID CRYSTAL DISPLAY DEVICE HAVING THE SAME**

(52) **U.S. Cl.** 349/65; 349/58
(58) **Field of Classification Search** 349/65, 349/58; 362/615
See application file for complete search history.

(75) Inventors: **Jeong-Hwan Lee**, Suwon-si (KR); **Keun-Woo Lee**, Gyeonggi-do (KR); **Jong-Dae Park**, Seoul (KR); **Jae-Ho Jung**, Yongin-si (KR); **Tae-Jin Lee**, Gyeonggi-do (KR); **Chang-Young Bang**, Suwon-si (KR)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,046,826 A	9/1991	Iwamoto et al.	
5,394,255 A	2/1995	Yokota et al.	
6,111,699 A	8/2000	Iwata et al.	
6,407,781 B2*	6/2002	Kitada	349/58
6,636,282 B2*	10/2003	Ogawa et al.	349/58
6,958,789 B2*	10/2005	Cueff et al.	349/61
7,178,963 B2*	2/2007	Ueda et al.	362/615
2002/0012085 A1	1/2002	Honda et al.	
2002/0113924 A1*	8/2002	Saito et al.	349/112

(73) Assignee: **Samsung Electronics Co., Ltd.** (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 121 days.

* cited by examiner

(21) Appl. No.: **10/519,599**

Primary Examiner—David Nelms
Assistant Examiner—David Chung

(22) PCT Filed: **Jun. 24, 2003**

(74) *Attorney, Agent, or Firm*—Don C. Lawrence; MacPherson Kwok Chen & Heid LLP

(86) PCT No.: **PCT/KR03/01231**

§ 371 (c)(1),
(2), (4) Date: **Dec. 22, 2004**

(57) **ABSTRACT**

(87) PCT Pub. No.: **WO2004/003637**

PCT Pub. Date: **Jan. 8, 2004**

Disclosed are a back light assembly for preventing discoloration and deformation caused by heat generated from a lamp, and a liquid crystal display device for displaying an enhanced image. The back light assembly includes a receiving container, a lamp, a glass substrate and a diffuser. The receiving container has a receiving space. The lamp for generating the light is disposed in the receiving space. The glass substrate is interposed between the liquid crystal display panel and the lamp. The diffuser diffuses the light generated by the lamp so as to unify a luminance distribution of the liquid crystal display panel. The liquid crystal display device includes the back light assembly.

(65) **Prior Publication Data**

US 2005/0206805 A1 Sep. 22, 2005

(30) **Foreign Application Priority Data**

Jun. 28, 2002 (KR) 2002-37087

(51) **Int. Cl.**

G02F 1/1335 (2006.01)
G02F 1/1333 (2006.01)

22 Claims, 9 Drawing Sheets




FIG. 1




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12





FIG. 13



**BACK LIGHT ASSEMBLY AND LIQUID
CRYSTAL DISPLAY DEVICE HAVING THE
SAME**

TECHNICAL FIELD

The present invention relates to a back light assembly, and a liquid crystal display device having the back light assembly, and more particularly to a back light assembly for preventing discoloration and deformation caused by heat generated from a lamp, and a liquid crystal display device displaying an enhanced image.

BACKGROUND ART

A liquid crystal display device displays an image processed by the information-processing device, so that a user can perceive the image.

The liquid crystal display device, one of display devices, uses a liquid crystal, of which transmissivity is modulated according to electric fields so as to display an image.

The liquid crystal modulates the light transmissivity only. Therefore, the liquid crystal display device needs light passing through the liquid crystal so as to display an image.

A lamp generates the light. A Cold Cathode Fluorescent Lamp (CCFL) may be used as the lamp of the liquid crystal display device.

The cold cathode fluorescent lamp has many merits. For example, the cold cathode fluorescent lamp may be formed in a cylindrical shape having a very small diameter. The cold cathode fluorescent lamp generates white light that is similar to sunlight. The cold cathode fluorescent lamp has a long life span and generates a little amount of heat in comparison with incandescent lamp.

The cold cathode fluorescent lamp may be arranged variously according to a size of a liquid crystal display panel.

In a small sized or a middle sized liquid crystal display device, one or two cold cathode fluorescent lamps are sufficient to get enough luminance for displaying an image. In the small sized or the middle sized liquid crystal display device, a volume and a weight are important. The cold cathode fluorescent lamp is attached to a side of an optical distribution-regulating device called as a light-guide plate (LGP).

This liquid crystal display device is referred to as an edge-illumination type liquid crystal display device.

Comparatively, in a large sized liquid crystal display device, one or two cold cathode fluorescent lamps is not enough to generate sufficient luminance, because the area of effective display region is large.

Therefore, more than three cold cathode fluorescent lamps are needed to get sufficient luminance for displaying an image. In this case, the cold cathode fluorescent lamps are arranged in parallel with each other under the liquid crystal display panel for applying light to the liquid crystal display panel.

This liquid crystal display device is referred to as a direct-illumination type liquid crystal display device.

The direct-illumination type liquid crystal display device may have sufficient luminance to display an image. However, the direct-type liquid crystal display device has a variation of the luminance according to a region of the liquid crystal display panel.

A region of the liquid crystal display panel, disposed over the lamp, has a high luminance. A region of the liquid crystal display panel, disposed over a region between the lamps, has a low luminance.

Therefore, a diffusion plate is interposed between the liquid crystal display panel and the lamp so as to reduce the variation of the luminance.

In general, the diffusion plate comprises acryl resin. The diffusion plate comprising the acryl resin is light and may be easily manufactured.

However, when a display time becomes longer, specific characters of the diffusion plate comprising acryl resin becomes bad, so that display quality may be deteriorated.

Firstly, the diffusion plate comprising acryl resin gets curved or sags easily due to the heat generated by the lamp.

Secondly, the diffusion plate comprising acryl resin discolored easily due to the heat generated by the lamp. When the diffusion plate is discolored, the white light generated by the cold cathode fluorescent lamp is filtered into a different color, so that display quality becomes bad.

DISCLOSURE OF THE INVENTION

The present invention provides a back light assembly preventing discoloration and deformation caused by heat generated from a lamp, and generating light having uniform luminance.

The present invention also provides a liquid crystal display device having back light assembly preventing discoloration and deformation caused by heat generated from a lamp, and displaying an enhanced image.

The back light assembly includes a receiving container, a lamp, a glass substrate and a diffuser. The receiving container has a receiving space. The lamp for generating the light is disposed in the receiving space. The glass substrate is interposed between the liquid crystal display panel and the lamp. The diffuser diffuses the light generated by the lamp so as to make the luminance distribution of the liquid crystal display panel uniform.

The liquid crystal display device includes a receiving container, a lamp, a glass substrate, a diffusion plate and liquid crystal display panel assembly. The receiving container includes a bottom face and a sidewall. The bottom face and the sidewall form a receiving space. The lamp for generating a first light is disposed on the bottom face. The glass substrate is disposed in the receiving space. The diffusion plate includes a diffuser for diffusing the first light. When the first light is diffused, the first light is transformed into a second light. The luminance of the second light is more uniform than the luminance of the first light. The liquid crystal display panel assembly displays an image by using the second light.

The back light assembly and the liquid crystal display device according to the present invention prevent deformation and discoloration and diffuse light effectively, so that an image quality is enhanced.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other advantages of the present invention will become readily apparent by reference to the following detailed description when considered in conjunction with the accompanying drawings wherein:

FIG. 1 is a top view showing a back light assembly according to an exemplary first embodiment of the present invention;

FIG. 2 is a partially cut perspective view showing a back light assembly of FIG. 1;

FIG. 3 is an enlarged view showing a portion "A" of FIG. 2;

FIG. 4 is a cross-sectional view showing a portion of a glass substrate according to an exemplary second embodiment of the present invention;

FIG. 5 is a cross-sectional view showing a portion of a glass substrate according to a modified second embodiment of the present invention;

FIG. 6 is a cross-sectional view showing a portion of a glass substrate according to an exemplary third embodiment of the present invention;

FIG. 7 is a cross-sectional view showing a portion of a glass substrate according to a modified third embodiment of the present invention;

FIG. 8 is a partially cut perspective view showing a back light assembly according to an exemplary fourth embodiment of the present invention;

FIG. 9 is an enlarged view showing "C" of FIG. 8;

FIG. 10 is a cross-sectional view showing a first glass plate and a second glass plate according to a modified fourth embodiment of the present invention;

FIG. 11 is a cross-sectional view showing a glass substrate according to an exemplary fifth embodiment of the present invention;

FIG. 12 is a cross-sectional view showing a glass substrate according to a modified fifth embodiment of the present invention; and

FIG. 13 is a partially cut perspective view showing a back light assembly according to an exemplary embodiment of the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

Embodiment 1

FIG. 1 is a top view showing a back light assembly according to an exemplary first embodiment of the present invention and FIG. 2 is a partially cut perspective view showing a back light assembly of FIG. 1.

Referring to FIGS. 1 and 2, a back light assembly 100 includes a receiving container 110, a lamp 120, a glass substrate 130 and a diffusion sheet 140.

The receiving container 110 has a receiving space for receiving the lamp 120, the glass substrate 130 and the diffusion sheet 140.

Referring to FIG. 2, the receiving container 110 includes a first receiving frame 114 and a bottom chassis 117. The first receiving frame 114 and the bottom chassis 117 form the receiving space.

The first receiving frame 114 includes a first plate 111, a second plate 112 and a third receiving plate 113.

The second plate 112 has a rectangular frame shape having an opening inside the rectangular frame. The glass substrate 130 and the diffusion sheet 140 are disposed on the second plate 112.

A top portion of the first plate 111 is connected with an inner portion of the second plate 112 and the first plate 111 is inclined inward. The first plate 111 has a lamp fixing portion (not shown) to fix the lamp 120 thereto.

A top portion of the third plate 113 is connected with an outer portion of the second plate 112. A hook 113a is formed at a lower portion of the third plate 113 and is combined with a bottom chassis 117.

The bottom chassis 117 includes a bottom face 115 and a sidewall 116 protruding upward from the outer portion of the bottom face 115. A hook hole 116a corresponding to the hook 113a is formed on the sidewall 116 of the bottom chassis 117.

The lamp 120 is supported by the first plate 111 of the first receiving frame 114 and is supplied with electric power to generate first light 121.

Preferably, a cold cathode fluorescent lamp may be used as the lamp 120. A plurality of the lamps 120 is arranged to be parallel with each other on the bottom face 115 of the bottom chassis 117.

A reflecting plate 119 is interposed between the lamp 120 and the bottom face 115. The reflecting plate 119 reflects a portion of the first light generated by the lamp 120 toward the glass substrate 130.

The lamps 120 generating linear light are disposed in parallel with each other, so that a luminance distribution of the first light 121 is non-uniform.

The luminance difference between a first region disposed over the lamp 120 and a second region deviated from the lamps 120 is a maximum.

When the luminance distribution is non-uniform, brightness of image displayed on a liquid crystal display panel is also non-uniform. Therefore, a display quality is lowered.

In order to prevent a deterioration of the display quality, members (not shown) for making the luminance distribution uniform are disposed over the lamp 120. Hereinafter, the members for making the luminance distribution of the first light 121 uniform are explained in detail.

FIG. 3 is an enlarged view showing a portion "A" of FIG. 2.

Referring to FIG. 3, the glass substrate 130 and the diffusion sheet 140 are disposed on the second plate 112 of the first receiving frame 115.

The glass substrate 130 seldom gets curved or sags due to the heat generated by the lamp, when the lamp 120 generates the first light 112.

Further, the glass substrate 130 seldom is discolored, even though the glass substrate 130 is exposed for a long time to the first light 121 generated the lamp 120.

However the glass substrate 130 is fragile. Therefore, an impact-proof glass or a tempered glass may be used as the glass substrate 130. The tempered glass has a low thermal expansion coefficient and is impervious to an external impact.

The thicker the glass substrate 130 is, the more impervious is the liquid crystal display device to the external impact. However, the thicker the glass substrate 130 is, the heavier is the liquid crystal display device. Therefore, the thickness of the glass substrate is determined in consideration of the strength and the weight. Preferably, the thickness of the glass substrate 130 is about 2 mm.

Referring to FIG. 2, an impact-absorbing member 118 may be interposed between the second plate 112 and the glass substrate 130.

The impact-absorbing member 118 absorbs an external impact so that the external impact force may not be transferred to the glass substrate 130.

The glass substrate 130 includes a first face 132 and a second face 134. The first light 121 generated by the lamp 120 is incident onto the first face 132 and exits from the second face 134.

The glass substrate 130 seldom gets curved and is discolored. However, the glass substrate 130 is transparent, so that the variation of the luminance occurs due to discretely

disposed lamps 120. Therefore, the diffusion sheet 140 is disposed over the glass substrate 130 so as to reduce the variation of the luminance.

Referring to FIG. 3, the diffusion sheet 140 includes a diffusion sheet body 142 and a light diffusion bead 144. The light diffusion beads 144 are mixed with a binder 143. The binder 143 is transparent, and the binder 143 has adhesive property. The light diffusion beads 144 mixed with the binder 143 are disposed on both side of the diffusion sheet body 142.

An amount of the light diffusion bead 144 is modulated, such that the Haze value is higher than about 90%.

The Haze value is a barometer indicating the transmittance and a ratio of diffusion of the first light 121 that is incident from the diffusion sheet 140. The Haze value is defined as follows.

$$\text{Haze value} = (\text{an amount of transmitted and diffused light} / \text{total amount of transmitted light}) \times 100 \quad \text{<Expression 1>}$$

“The amount of transmitted and diffused light” is referred to as an amount of light that passes through the diffusion sheet 140 and is diffused. “The total amount of light” is referred to as total amount of light that pass through the diffusion sheet 140.

The diffusion sheet 140 is disposed on the second face 134 of the glass substrate 130 such that the Haze value is higher than about 90%.

Referring to FIG. 2, when the glass substrate 130 is large, the glass substrate 130 may sag due to the weight thereof. Therefore, a substrate-supporting member 150 is formed on the bottom face 115 of the bottom chassis 117 so as to prevent the sag of the glass substrate 130. The substrate-supporting member 150 has a cone-shape. However, the substrate-supporting member 150 may have a cylindrical shape, a triangular pillar shape or a polygonal pillar shape.

The first light 121 passes through the glass substrate 130 and passes through the diffusion sheet 140 so that the first light is transformed into a second light 122 that is diffused by the diffusion sheet 140.

Embodiment 2

FIG. 4 is a cross-sectional view showing a portion of a glass substrate according to an exemplary second embodiment of the present invention, and FIG. 5 is a cross-sectional view showing a portion of a glass substrate according to a modified second embodiment of the present invention.

Referring to FIGS. 2, 4 and 5, the glass substrate 130 is disposed on the second plate 112 of the first receiving frame 114. The diffusion sheet 146 is disposed on the glass substrate 130. The glass substrate 130 includes a first face 132 and a second face 134. Light generated by the lamp 120 is incident onto a first face 132 of the glass substrate 130. The first face 132 faces a second face 134 of the glass substrate 130.

Referring to FIG. 4, a light diffusion layer 146 is formed on the first face 132 of the glass substrate 130.

The light diffusion layer 146 includes a binder 146a and a light diffusion bead 146b. The binder 146a is transparent and adhesive. The light diffusion bead 146b has a grain-shape. The light diffusion bead 146b diffuses light.

The light binder 146a mixed with a pre-determined amount of the diffusion bead 146b is coated on the first face 132 of the glass substrate 130 by a predetermined thickness.

The light diffusion layer 146 diffuses the first light 121 generated by the lamp 120, so that the first light 121 is transformed into a second light 122. The second light 122 is

incident onto the first face 132 of the glass substrate 130, and the second light 122 exits from the second face 134 of the glass substrate 130.

In FIG. 5, the light diffusion layer 146 is formed on the second face 134 of the glass substrate 130.

The light diffusion layer 146 formed on the second face 134 of the glass substrate 130 includes a binder 146a and a light diffusion bead 146b. The binder 146a is transparent and adhesive. The light diffusion bead 146b has a grain-shape. The light diffusion bead 146b diffuses light.

The binder 146a is mixed with a predetermined amount of the diffusion bead 146b and coated on the second face 134 of the glass substrate 130 by predetermined thickness.

The light diffusion layer 146 diffuses the first light 121 generated by the lamp 120, so that the first light 121 is transformed into the second light 122.

Preferably, the light diffusion layer 146 formed on the first face 132 or on the second face 134 has the Haze value that is higher than about 90%.

Embodiment 3

FIG. 6 is a cross-sectional view showing a portion of a glass substrate according to an exemplary third embodiment of the present invention, and FIG. 7 is a cross-sectional view showing a portion of a glass substrate according to a modified third embodiment of the present invention.

A light diffusion portion 135 is formed on a glass substrate 130. For example, an impact-proof glass or a tempered glass may be used as the glass substrate 130. The tempered glass has a low thermal expansion coefficient. The tempered glass is impervious to external impact.

A first light 121 generated by the lamp 120 is incident onto a first face 132 of the glass substrate 130. The first face 132 faces a second face 134.

Referring to FIGS. 6 and 7, the light diffusion portion 135 is formed on the first face 132 or on the second face 134.

The light diffusion portion 135 may be formed via various manufacturing methods. For example, the light diffusion portion 135 may be formed via the sand blaster process on the first face 132 or on the second face 134 of the glass substrate 130 having plate-shape, or a roller may roll on the face of the glass substrate 130 to make an embossing pattern on the face of the glass substrate 130, when the glass substrate is not completely hardened.

The light diffusion portion 135 diffuses the first light 121 generated by the lamp 120 so as to make a luminance of light uniform.

Preferably, the light diffusion portion 135 formed on the first face 132 or on the second face 134 has the Haze value that is higher than about 90%.

Embodiment 4

FIG. 8 is a partially cut perspective view showing a back light assembly according to an exemplary fourth embodiment of the present invention and FIG. 9 is an enlarged view showing “C” of FIG. 8.

In FIG. 8, the same reference numerals denote the same elements in FIG. 2, and thus the detailed descriptions of the same elements will be omitted.

Referring to FIG. 8, a glass substrate includes a first glass plate 137 and a second glass plate 138. A structure of the glass substrate having the two plates seldom is deformed or sags. The first glass plate 137 and the second glass plate 138 are disposed on the second plate 112 of the first receiving

frame **114**. A diffusion sheet **145** is interposed between the first glass plate **137** and the second glass plate **138**.

Referring to FIG. **9**, a diffusion sheet **145** includes a diffusion sheet body **145a** and a light diffusion bead **145b**. The light diffusion bead **145b** is mixed with binder **145c** and coated on the diffusion sheet body **145a**.

An amount of the light diffusion bead **145b** is modulated, such that the Haze value is higher than about 90%.

For example, a thickness of the glass substrate including the first glass plate **137**, the diffusion sheet **145** and the second glass plate **138** is about 2 mm. Therefore, the thickness and the weight of the liquid crystal display device are reduced.

FIG. **10** is a cross-sectional view showing a first glass plate and a second glass plate according to a modified fourth embodiment of the present invention.

Referring to FIG. **10**, a glass substrate includes a first glass plate **137** and a second glass plate **138**. This structure of the glass substrate having the two plates seldom is deformed or sags. A light diffusion layer **146** is interposed between the first glass plate **137** and the second glass plate **138**. The light diffusion layer **146** transforms a first light **121** generated by the lamp **120** into a second light **122**.

The light diffusion layer **146** includes a light diffusion bead **146b** and a binder **146a**. The binder **146a** mixed with the light diffusion bead **146b** is coated on the first glass plate **137** or on the second glass plate **138**.

FIG. **11** is a cross-sectional view showing a glass substrate according to an exemplary fifth embodiment of the present invention, and FIG. **12** is a cross-sectional view showing a glass substrate according to a modified fifth embodiment of the present invention.

Referring to FIG. **11**, a glass substrate includes a first glass plate **137a** and a second glass plate **138**. A lower face of the first glass plate **137a** has an embossing pattern. The lower face of the first glass plate **137a** faces the second plate **138**.

Referring to FIG. **12**, a glass substrate includes a first glass plate **137** and a second glass plate **138a**. An upper face of the second glass plate **138a** has an embossing pattern. The upper face of the second glass plate **138a** faces the first plate **137**.

Both of a face of the first plate and a face of the second plate may have the embossing pattern.

Hereinafter, a liquid crystal display device having the back light assembly described above is disclosed in detail.

FIG. **13** is a partially cut perspective view showing a back light assembly according to an exemplary embodiment of the present invention.

A liquid crystal display device **600** includes a first receiving frame **110**, a back light assembly **100**, a liquid crystal display panel assembly **200**, a second receiving frame **300**, a top chassis **400** and a back cover **500**. The back light assembly **100** includes a lamp **120** for generating first light **121**, a glass substrate **130** and a diffusion plate. The diffusion plate includes a diffusion sheet **140** for transforming the first light **121** into a second light **122**, a light diffusion layer or a light diffusion portion.

The back light assembly **100** may be one of the embodiments disclosed above.

The second receiving frame **300** is in contact with an edge portion of the glass substrate **130** disposed on a second plate **112** of the first receiving frame **110** so as to fix the glass substrate **130**.

The second receiving frame **300** has a rectangular shape. A liquid crystal display panel guide **310** is formed on the second receiving frame **300** so as to guide the liquid crystal display panel assembly **200**.

An impact-absorbing member **118** may be interposed between the second receiving frame **300** and the glass substrate **130** so as to absorb an external impact transferred to the glass substrate **130**, and so as to support the glass substrate **130**.

The liquid crystal display panel assembly **200** is disposed on the second receiving frame **300**. The second receiving frame **300** supports the liquid crystal display panel assembly **200**. A liquid crystal display panel guide **310** fixes the liquid crystal display panel assembly **200**.

The liquid crystal display panel assembly **200** includes a liquid crystal display panel **210**, a tape carrier package (not shown) and a printed circuit board **220**.

The liquid crystal display panel **210** includes a thin film transistor substrate **216**, a liquid crystal **214** and a color filter substrate **212**.

A first end of the tape carrier package is connected to the thin film transistor substrate **216** and a second end of the tape carrier package is connected to the printed circuit board **220**.

The printed circuit board **220** is bent in accordance with a bottom chassis **117** of the back light assembly **100** to be disposed under the bottom face **115** of the bottom chassis **117**. A back cover **500** fixes the printed circuit board **220** disposed under the bottom face **115**.

The top chassis **400** presses an edge portion of the liquid crystal display panel **210** to fix the liquid crystal display panel **210** and protects the liquid crystal display panel **210** and the glass substrate **130**.

Hereinafter, a process of displaying an image is explained.

The lamp **120** generates the first light **121**. The first light **121** is incident onto the glass substrate **130** and passes through the glass substrate **130**. Then the first light **121** is incident onto the light diffusion sheet, the light diffusion layer or the light diffusion portion described above. The light diffusion sheet, the light diffusion layer or the light diffusion portion diffuses the first light **121**, so that the first light **121** is transformed into the second light **122** having uniform luminance.

In order to transform the first light **121** into the second light **122**, the diffusion sheet having the light diffusion bead may be disposed on the glass substrate.

In order to transform the first light **121** into the second light **122**, the light diffusion layer may be formed on the glass substrate **130**.

In order to transform the first light **121** into the second light **122**, the glass substrate may have the light diffusion portion which is an embossing pattern formed on a face of the glass substrate **130**.

The first light **121** passes through the diffusion sheet, the light diffusion layer or the light diffusion portion to be transformed into the second light **122**. The second light **122** may be diffused additionally. The second light **122** is applied to the liquid crystal display panel **210**.

The liquid crystal display panel **210** transforms the second light **122** into an image light **123** having image information. When the image light **123** arrives at eyes of user, the user perceives an image of the image information.

INDUSTRIAL APPLICABILITY

The back light assembly according to embodiments of the present invention reduces the variation of the luminance distribution and prevents concentration of light. The back light assembly also prevents discoloration. Therefore, the back light assembly enhances the display quality.

Although the exemplary embodiments of the present invention have been described, it is understood that the

present invention should not be limited to these exemplary embodiments but various changes and modifications can be made by one ordinary skilled in the art within the spirit and scope of the present invention as hereinafter claimed.

The invention claimed is:

1. A back light assembly for applying light to a liquid crystal display panel, comprising:

a receiving container having a receiving space and a plate defining first and second ledges extending at least partially about an upper periphery thereof,

the second ledge being disposed above the first ledge and having an inner edge generally coincident with or disposed outside of an outer edge of the first ledge such that the first and second ledges do not overlap;

a lamp disposed in the receiving space, for generating the light; and,

a diffuser for diffusing the light generated by the lamp so as to make uniform a luminance distribution of the liquid crystal display panel.

2. The backlight assembly of claim 1, further comprising a glass substrate interposed between the liquid crystal display panel and the lamp and having an outer periphery supported on the first ledge of the receiving container plate.

3. The back light assembly of claim 2, wherein the diffuser is a first diffusion sheet disposed on a first face of the glass substrate, the first face facing the liquid crystal display panel.

4. The back light assembly of claim 3, wherein the first diffusion sheet comprises a first diffusion sheet body having an upper face and a lower face, and a light diffusion bead disposed on the upper face and the lower face.

5. The back light assembly of claim 2, wherein a bottom face of the receiving container includes a substrate-supporting member for supporting the glass substrate.

6. The back light assembly of claim 2, wherein the glass substrate comprises a first glass plate, a second glass plate and a second diffusion sheet interposed between the first glass plate and the second glass plate.

7. The back light assembly of claim 6, wherein the second diffusion sheet comprises a second diffusion body and a light diffusion bead disposed on both faces of the second diffusion body.

8. The back light assembly of claim 2, wherein the diffuser comprises a binder and a light diffusion bead mixed with the binder, the binder being disposed on a first face of the glass substrate, the first face facing the lamp.

9. The back light assembly of claim 2, wherein the diffuser comprises a binder and a light diffusion bead mixed with the binder, the binder being disposed on a second face of the glass substrate, the second face facing the liquid crystal display panel.

10. The back light assembly of claim 2, wherein the diffuser is an embossing pattern formed on a first face of the glass substrate, the first face facing the lamp.

11. The back light assembly of claim 2, wherein the diffuser is an embossing pattern formed on a second face of the glass substrate, the second face facing the liquid crystal display panel.

12. The back light assembly of claim 2, wherein the diffuser has a Haze value higher than about 90%.

13. The back light assembly of claim 2, wherein the glass substrate comprises two glass plates, and the diffuser is an

embossing pattern formed on at least one face of the two glass plates, the face being disposed between the two glass plates.

14. The back light assembly of claim 2, wherein the glass substrate comprises a first glass plate, a second glass plate, a bead and a binder; the bead being mixed with the binder and interposed between the first glass plate and the second glass plate.

15. A liquid crystal display device, comprising:

a receiving container including a bottom face, a sidewall

and a plate defining first and second ledges extending at least partially about an upper periphery thereof, the bottom face and the sidewall forming a receiving space, and the second ledge being disposed above the first ledge and having an inner edge generally coincident with or disposed outside of an outer edge of the first ledge such that the first and second ledges do not overlap;

a lamp disposed on the bottom face, for generating a first light;

a diffusion plate including a diffuser for diffusing the first light so as to transform the first light into a second light having a more uniform luminance than the first light; and,

a liquid crystal display panel assembly having an outer periphery supported on the second ledge of the receiving container plate for displaying an image by using the second light.

16. The liquid crystal display device of claim 15, further comprising a glass substrate disposed in the receiving space and having an outer periphery supported on the first ledge of the receiving container plate, the first light advancing toward the glass substrate.

17. The liquid crystal display device of claim 16, wherein the diffuser is an embossing pattern formed on a first face of the glass substrate, the first face facing the lamp.

18. The liquid crystal display device of claim 16, wherein the diffuser is an embossing pattern formed on a second face of the glass substrate, the second face facing the liquid crystal display panel.

19. The liquid crystal display device of claim 16, wherein the diffuser is a diffusion sheet disposed on a second face of the glass substrate, the second face facing the liquid crystal display panel.

20. The liquid crystal display device of claim 19, wherein the diffusion sheet comprises a diffusion sheet body and a light diffusion bead for diffusing the first light, the light diffusion bead being mixed with a binder and disposed on both face of the diffusion sheet body.

21. The liquid crystal display device of claim 16, wherein the glass substrate comprises a first glass plate, a second glass plate, a bead and a binder; the bead being mixed with the binder and interposed between the first glass plate and the second glass plate.

22. The liquid crystal display device of claim 16, wherein the glass substrate comprises two glass plates, and the diffuser is an embossing pattern formed on at least one face of the two glass plates, the face being disposed between the two glass plates.

专利名称(译)	背光组件和具有该背光组件的液晶显示装置		
公开(公告)号	US7327416	公开(公告)日	2008-02-05
申请号	US10/519599	申请日	2003-06-24
[标]申请(专利权)人(译)	李贞焕 李根雨 朴钟DAE 郑在HO 李泰金 BANG张师弟		
申请(专利权)人(译)	李贞焕 李槿WOO 朴钟DAE 郑在HO 李泰金 BANG CHANG-YOUNG		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	LEE JEONG HWAN LEE KEUN WOO PARK JONG DAE JUNG JAE HO LEE TAE JIN BANG CHANG YOUNG		
发明人	LEE, JEONG-HWAN LEE, KEUN-WOO PARK, JONG-DAE JUNG, JAE-HO LEE, TAE-JIN BANG, CHANG-YOUNG		
IPC分类号	G02F1/1335 G02F1/1333 F21V8/00 G02F1/13357		
CPC分类号	G02F1/133604 G02F1/133606		
审查员(译)	内尔姆斯, DAVID		
助理审查员(译)	CHUNG, DAVID		
优先权	1020020037087 2002-06-28 KR		
其他公开文献	US20050206805A1		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种用于防止由灯产生的热量引起的变色和变形的背光组件，以及用于显示增强图像的液晶显示装置。背光组件包括接收容器，灯，玻璃基板和漫射器。接收容器具有容纳空间。用于产生光的灯设置在容纳空间中。玻璃基板介于液晶显示板和灯之间。漫射器漫射由灯产生的光，以统一液晶显示板的亮度分布。液晶显示装置包括背光组件。

