



US008009255B2

(12) **United States Patent**
Onishi et al.

(10) **Patent No.:** **US 8,009,255 B2**
(45) **Date of Patent:** **Aug. 30, 2011**

(54) **DISPLAY PANEL COMPRISING A MARK LOCATED OUTSIDE OF A SEALANT AND A FLATTENING FILM INCLUDING A SEALING EXPOSING PORTION**

(75) Inventors: **Noriaki Onishi**, Nara (JP); **Yohsuke Fujikawa**, Tokyo (JP); **Hiroaki Tomioka**, Matsusaka (JP); **Hiroaki Kojima**, Kashiba (JP); **Yasunobu Tagusa**, Ikoma (JP)

(73) Assignee: **Sharp Kabushiki Kaisha**, Osaka (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **12/753,130**

(22) Filed: **Apr. 2, 2010**

(65) **Prior Publication Data**

US 2010/0188631 A1 Jul. 29, 2010

Related U.S. Application Data

(62) Division of application No. 12/064,114, filed as application No. PCT/JP2006/318166 on Sep. 13, 2006, now Pat. No. 7,907,246.

(30) **Foreign Application Priority Data**

Sep. 15, 2005 (JP) 2005-268899

(51) **Int. Cl.**

G02F 1/1333 (2006.01)

G02F 1/1339 (2006.01)

(52) **U.S. Cl.** **349/138; 349/153**

(58) **Field of Classification Search** 349/153, 349/138, 43; 361/679.01

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,936,695 A *	8/1999	Hida et al.	349/153
6,078,367 A	6/2000	Satou	
6,229,586 B1	5/2001	Date et al.	
6,750,938 B2	6/2004	Koyama	
2001/0012079 A1	8/2001	Yamamoto et al.	
2005/0146666 A1	7/2005	Hatta	
2009/0046235 A1 *	2/2009	Onishi et al.	349/153

FOREIGN PATENT DOCUMENTS

JP	63-180932 A	7/1988
JP	4-60517 A	2/1992
JP	09-258670 A	10/1997
JP	11-142825 A	5/1999

(Continued)

OTHER PUBLICATIONS

Official communication issued in the International Application No. PCT/JP2006/318166, mailed on Dec. 12, 2006.

Onishi et al. "Display Panel", U.S. Appl. No. 12/064,114, filed on Feb. 19, 2008.

Official communication issued in counterpart Japanese Application No. 2007-535512, mailed on Sep. 24, 2008.

(Continued)


Primary Examiner — Thoi Duong

(74) *Attorney, Agent, or Firm* — Keating & Bennett, LLP

(57) **ABSTRACT**

A liquid crystal display panel includes an active matrix substrate, a counter substrate, a liquid crystal layer, and a sealant. The counter electrode is opposed to the active matrix substrate. The liquid crystal layer is provided between the active matrix substrate and the counter substrate. The sealant, which surrounds the liquid crystal layer between the active matrix substrate and the counter substrate, joins the active matrix substrate and the counter substrate and seals the liquid crystal layer. A portion of the surface on the liquid crystal layer side of the active matrix substrate which is located at the periphery of the liquid crystal display panel is flat.

14 Claims, 11 Drawing Sheets



FOREIGN PATENT DOCUMENTS

JP	2000-231086 A	8/2000
JP	2001-337334 A	12/2001
JP	2002-043703 A	2/2002
JP	2002-174819 A	6/2002
JP	2002-182185 A	6/2002
JP	2002-297048 A	10/2002
JP	2003-222904 A	8/2003
JP	2004-212690 A	7/2004
JP	2005-283885 A	10/2005

OTHER PUBLICATIONS

Onishi et al. "Display Panel", U.S. Appl. No. 12/064,114, filed on Oct. 25, 2010.

Onishi et al. "Display Panel", U.S. Appl. No. 12/911,164, filed on Oct. 25, 2010.

Onishi et al. "Display Panel", U.S. Appl. No. 12/911,169, filed on Oct. 25, 2010.

* cited by examiner

FIG. 1




FIG. 2




FIG. 3




FIG. 4A





FIG. 4B






FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16





FIG. 17



DISPLAY PANEL COMPRISING A MARK LOCATED OUTSIDE OF A SEALANT AND A FLATTENING FILM INCLUDING A SEALING EXPOSING PORTION

BACKGROUND OF THE INVENTION

1. Summary of the Invention

The present invention relates to a display panel.

2. Description of the Related Art

A flat display panel typified by a liquid crystal display panel includes a pair of substrates of which peripheral portions are joined to each other by means of a sealant and a display medium layer (for example, a liquid crystal layer) introduced in a cell formed by the pair of substrates and the sealant. For manufacturing such a flat display panel, especially, for manufacturing a flat display panel comparatively small in size, a method is employed, with a view to achieving high production efficiency, in which a plurality of cells (constitutional units) are formed on a large-size mother glass substrate; scribe lines for individually dividing the plurality of cells thus formed are formed; then the cells (constitutional units) are divided individually along the scribe lines (see Japanese Unexamined Patent Application Publication No. 2003-222904 and Japanese Unexamined Patent Application Publication No. 2004-212690, for example).

In the conventional scribing method as disclosed in Japanese Unexamined Patent Application Publication No. 2003-222904 and Japanese Unexamined Patent Application Publication No. 2004-212690, however, chips and cracks may be formed in the glass substrate which lowers the efficiency percentage. In other words, the conventional flat display panel involves insufficient manufacturing efficiency (efficiency percentage). Particularly, recent progress in thinning the flat display panel accompanies thinning of the glass substrates used, and therefore, a flat display panel using such thin glass substrates (glass substrates having a thickness of 0.5 mm or smaller or 0.4 mm or smaller, for example) makes the above problem more significant.

SUMMARY OF THE INVENTION

In order to overcome the problems described above, preferred embodiments of the present invention provide a display panel that is capable of being manufactured with high production efficiency.

A display panel in accordance with a preferred embodiment of the present invention includes: a first substrate; a second substrate opposed to the first substrate; a display medium layer provided between the first substrate and the second substrate; and a sealant surrounding the display medium layer between the first substrate and the second substrate to join the first substrate and the second substrate and sealing the display medium layer. In the display panel in accordance with the present preferred embodiment of the present invention, a portion of a surface on a display medium layer side of the first substrate which is located at a periphery of the display panel is flat. It is preferable that each portion of the surfaces (the surface on the display medium layer side and the surface on the opposite side of the display medium layer side) of the first substrate which is located at the periphery of the display panel is flat. More preferably, these surfaces are flat and smooth.

The first substrate may include a first substrate body and a flattening film covering at least an entirety of the portion of the surface on the display medium layer side of the first substrate body which is located at the periphery of the display

panel. The flattening film may be a resin film. In the present specification, the term "resin film" means a film containing organic resin or silicon resin. Further, the term "display medium layer" means a layer of which light transmittance or light reflectance is modified by potential difference between electrodes opposed to each other or a layer spontaneously emitting light by current flowing between the electrodes opposed to each other. Specifically, the display medium layer includes, for example, liquid crystal layers, inorganic or organic electroluminescent layers, light emitting gas layers, electrophoretic layers, electrochromic layers, and the like. Accordingly, the display panel in accordance with the present preferred embodiment of the present invention may be a liquid crystal display panel, an inorganic or organic electroluminescent display panel, or the like.

Moreover, the term "flat" in the present specification means flat to such an extent that the micro variation amount of a surface is about 0.3 μm or smaller, for example. The micro variation amount of a surface can be measured by a probe type surface profiling device, P-15 manufactured by KLA-Tencor Corporation.

The first substrate may be an active matrix substrate. Specifically, the first substrate further may include: a plurality of thin film transistors formed on the first substrate body; an interlayer insulating film which is formed on the plurality of thin film transistors and in which a plurality of through holes open to the plurality of thin film transistors are formed; and a plurality of pixel electrodes which are formed on the interlayer insulating film and which are electrically connected to the thin film transistors through the plurality of through holes. In this case, the interlayer insulating film is preferably formed as the flattening film on the entirety of the portion of the first substrate body which is located at the periphery of the display panel.

In the display panel in accordance with a preferred embodiment of the present invention, preferably, a portion of a surface on a display medium layer side of the second substrate which is located at the periphery of the display panel is flat. Preferably, each portion of both the surfaces (the surface on the display medium layer side and the surface on the opposite side of the display medium layer side) of the second substrate which is located at the periphery of the display panel is flat. More preferably, these surfaces are flat and smooth.

A display panel in accordance with another preferred embodiment of the present invention includes: a first substrate in which a plurality of conductive members are provided; a second substrate opposed to the first substrate; a display medium layer provided between the first substrate and the second substrate; and a sealant surrounding the display medium layer between the first substrate and the second substrate to join the first substrate and the second substrate and sealing the display medium layer. In the second display panel in accordance with the present preferred embodiment of the present invention, at least one scribe mark is formed on a portion of the first substrate which is located at a periphery of the display panel, the scribe mark being formed of the same film as a film forming the thinnest conductive member of all the plurality of conductive members. In the present specification, the term "conductive member" means a member presenting a conductivity of about 10^6 S/m or larger in the steady state. The conductivity may be measured by a four-terminal method or the like.

In the display panel in accordance with the present preferred embodiment of the present invention, the first substrate may be an active matrix substrate. Specifically, the first substrate may include: a plurality of gate lines extending in parallel to each other; a plurality of source lines extending in

parallel to each other with an angle formed relative to a direction that the plurality of gate lines extend; switching elements connected to both the gate lines and the source lines; an interlayer insulating film which is formed on the switching elements and in which a plurality of through holes open to the switching elements are formed; and a plurality of pixel electrodes electrically connected to the switching elements through the plurality of interlayer insulating films. In this case, the plurality of conductive members include the plurality of gate lines, the plurality of source lines, and the plurality of pixel electrodes. One or more scribe marks may be formed of the same film as a film forming the thinnest conductive member out of the plurality of gate lines, the plurality of source lines, and the plurality of pixel electrodes.

The plurality of pixel electrodes may be substantially made of conductive oxide while the at least one scribe mark may preferably be formed of the same film as a film forming the plurality of pixel electrodes. The conductive oxide includes indium thin oxide (ITO), indium zinc oxide (IZO), tin oxide (SnO), and the like, for example.

The at least one scribe mark may be substantially made of metal. For example, the at least one scribe mark may be formed of the same film as a film forming the electrode line.

Preferably, the at least one scribe mark may be separated from an edge of the first substrate.

The at least one scribe mark may be in a polygonal form in plan view having a side agreeing with an edge of the first substrate in plan view. In this case, preferably, the at least one scribe mark includes at least one edge in perpendicular contact with an edge of the first substrate in plan view.

The at least one scribe mark may be substantially made of conductive oxide.

These and other features, elements, steps, advantages, and characteristics of the present invention will be apparent from the following description of preferred embodiments with reference to the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a liquid crystal display panel in accordance with a preferred embodiment of the present invention.

FIG. 2 is a schematic sectional view of a portion taken along the line II-II in FIG. 1.

FIG. 3 is a partial sectional view of the liquid crystal display panel.

FIGS. 4A and 4B are enlarged views showing a portion encircled in IV in FIG. 1, and specifically, FIG. 4A is an enlarged plan view showing the portion encircled in IV in FIG. 1 and FIG. 4B is an enlarged perspective view thereof.

FIG. 5 is a plan view showing a step of manufacturing the liquid crystal display panel 1 in accordance with a preferred embodiment of the present invention.

FIG. 6 is an enlarged plan view showing an arrangement in a portion encircled in VI in FIG. 5.

FIG. 7 is a plan view showing a step of manufacturing the liquid crystal display panel in accordance with a preferred embodiment of the present invention.

FIG. 8 is a partial plan view of a conventional substrate structure.

FIG. 9 is a schematic sectional view of a portion taken along the line IX-IX in FIG. 8.

FIG. 10 is a schematic sectional view of a portion taken along the line X-X in FIG. 6.

FIG. 11 is a schematic sectional view for explaining a scribing step in the case where a thick scribe mark is formed.

FIG. 12 is a schematic sectional view of a portion taken along the line XII-XII in FIG. 6 for showing a scribing step in a preferred embodiment of the present invention.

FIG. 13 is a partial plan view of a liquid crystal display panel in accordance with Modified Example 1.

FIG. 14 is a schematic plan view showing in an enlarged scale a portion of a liquid crystal display panel in accordance with Modified Example 2.

FIG. 15 is a plan view showing a step of manufacturing the liquid crystal display panel in accordance with Modified Example 2.

FIG. 16 is a schematic plan view showing an arrangement in a liquid crystal display panel in accordance with a preferred embodiment of the present invention.

FIG. 17 is a plan view showing a step of manufacturing the liquid crystal display panel in accordance with a preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the present invention will be described below in detail with reference to the accompanying drawings.

First Preferred Embodiment

FIG. 1 to FIG. 4 show a liquid crystal display panel 1 in accordance with the present preferred embodiment.

The liquid crystal display panel 1 in accordance with the present preferred embodiment preferably includes: an active matrix substrate 10 as a first substrate; a counter substrate 30 as a second substrate; and a liquid crystal layer 20 as a display medium layer provided between the active matrix substrate 10 and the counter substrate 30. The counter electrode 30 is not shown in FIG. 4B for the sake of explanation.

Between the active matrix substrate 10 and the counter substrate 30, a sealant 40 is provided so as to surround the liquid crystal layer 20. The sealant 40 joins the active matrix substrate 10 and the counter substrate 30 and seals the liquid crystal layer 20.

As shown in FIG. 3, the active matrix substrate 10 includes: a first substrate body 11 made of glass, for example; a plurality of gate lines 12 extending in parallel to each other; a plurality of source lines 13 extending in parallel to each other; a plurality of thin film transistor elements (hereinafter, they may be referred to as "TFT elements") 14; an interlayer insulating film 15; a plurality of pixel electrodes 16 substantially made of transparent conductive oxide (indium tin oxide, indium zinc oxide, or the like, for example); scribe marks 50 in a trapezoidal form in plan view formed in the peripheral portion of the first substrate body 11 separately from the edges of the first substrate body 11; a first rubbing film (an alignment film) 17; and a first polarizing plate 18 provided on the surface opposite to the surface on the liquid crystal layer 20 side of the first substrate body 11.

The plurality of gate lines 12 are formed on the first substrate body 11. The plurality of source lines 13 are formed across the gate lines 12 so as to extend in parallel to each other in a direction intersecting with the gate lines 12 (typically, intersecting at a right angle). The gate lines 12 and the source lines 13 are preferably made of metal, such as tungsten (W), tantalum (Ta), or the like. An insulating film (a silicon oxide film, a silicon nitride film, or the like, for example) is formed between the gate lines 12 and the source lines 13 for insulating them from each other.

The TFT elements **14** as switching elements, which are electrically connected to both the gate lines **12** and the source lines **13**, are provided in the vicinity of the intersections of the plurality of gate lines **12** and the plurality of source lines **13**. The interlayer insulating film **15**, which is preferably made of organic resin (resin of which main component is epoxy acrylate resin, urethane acrylate resin, o-diazonaphthoquinone novolac based resin, or the like), is formed on the plurality of TFT elements **14**. The resin used for the interlayer insulating film **15** preferably has high light transmittance, low dielectric constant, large resistivity, and high mechanical strength.

The plurality of pixel electrodes **16** arranged in a predetermined pattern (typically, arranged in matrix) and the scribe marks **50** are formed on the interlayer insulating film **15**. Through holes **15a** open to the TFT elements **14** are formed in the interlayer insulating film **15** so that the pixel electrodes **16** and the TFT elements **14** are connected electrically to each other through the through holes **15a**. The scribe marks **50** in the present specification are alignment marks for aiding precise division.

In the liquid crystal display panel **1** in accordance with the present preferred embodiment, the film of the pixel electrodes **16** is the thinnest of all the conductive members of the electrode lines of the gate lines **12** and the source lines **13**, the pixel electrodes **16**, and the like. The scribe marks **50** are formed of the same film as a conductive oxide film, for example, an ITO film forming the pixel electrodes **16**, which are the thinnest of all the conductive members.

As shown in FIG. 4, the interlayer insulating film **15** separating and insulating the TFT elements **14** and the pixel electrodes **16** covers the entire surface of a portion on the liquid crystal layer **20** side of the first substrate body **11** which is located at the periphery of the liquid crystal display panel **1** with a portion of the first substrate body **11** exposed which is overlapped with a portion (a corner part, for example) of the sealant **40**. The interlayer insulating film **15** functions also as a generally-called flattening film for flattening a portion of the surface on the liquid crystal layer **20** side of the first substrate body **11** which is located at the periphery of the liquid crystal display panel **1**. Each portion of both the surfaces of the first substrate body **11** including the surface on the liquid crystal layer **20** side which is located at the periphery of the liquid crystal display panel **1** is formed so as to be flat and smooth.

The reason why a portion (a portion overlapped with a corner of the sealant **40**, for example) of the first substrate body **11** is allowed to be exposed through the interlayer insulating film **15** is to increase the adhesiveness of the sealant **40**, which is made of a material generally exhibiting excellent adhesiveness to inorganic materials, for example, a material of which main component is epoxy-based thermosetting resin, ultraviolet curing resin, or the like, to the active matrix substrate **40**.

The counter substrate **30** includes: a second substrate body **31** made of glass, for example; a color filter layer **32**; an upper common electrode **33**; a second rubbing film (an alignment film) **34**; and a second polarizing plate **35** provided on the surface on the opposite side of the liquid crystal layer **20** side of the second substrate body **31**. The color filter layer **32** is formed on the second substrate body **31** and is composed of a plurality of types of filter layers different from each other in color tone for transmitting light and a black matrix layer dividing the filter layers. The upper common electrode **33** is formed on the color filter layer **32**, and the second rubbing film **34** in contact with the liquid crystal layer **20** is formed on the upper common electrode **33**. Each portion of the surfaces, including the surface on the liquid crystal layer **20** side, of the

counter substrate **30** which is located at the periphery of the liquid crystal display panel **1** is formed so as to be flat and smooth.

A process for manufacturing the liquid crystal display panel **1** will be described next with reference to FIG. 5 to FIG. 12.

First, as shown in FIG. 5, a first mother glass **60** as a base material of the active matrix substrate **10** is prepared. The first mother glass **60** is a large-size glass substrate from which a plurality of active matrix substrates **10** can be cut out (for example, about 120 active matrix substrates **10** arranged in matrix of 12 rows by 10 columns). On the first mother glass substrate **60**, the gate lines **12**, the source lines **13**, the TFT elements **14**, the pixel electrodes **16**, the scribe marks **50**, and the like are formed sequentially to form plural constitutional units of the active matrix substrates **10** connected to each other in series on the first mother glass **60** as the first substrate body **11**.

In this active matrix substrate forming step, the scribe marks **50** are preferably formed with the use of the same film as the film forming the pixel electrodes **16** simultaneously with the formation of the pixel electrodes **16**.

In parallel to the above step, a second mother glass **70** as a base material of the counter substrate **30** is prepared. The second mother glass **70** is a middle-size glass substrate smaller than the first mother glass substrate **60**, from which a plurality of counter substrates **30** can be cut out (for example, about 10 counter substrates **30** arranged in one direction). On the second mother glass substrate **70**, the color filter layer **32**, the upper common electrode **33**, the second rubbing film **34**, and the like are formed sequentially to form plural constitutional units of the counter substrates **30** arranged in one direction simultaneously.

Thereafter, a plurality of annular sealants **40** each having an opening (a liquid crystal injection port) are formed on the first mother glass **60** by, for example, screen printing. Then, the second mother glass substrate **70** is arranged on and joined to the sealants **40** to thus manufacture a substrate structure (joined substrate) **80** in which plural constitutional units are formed in a predetermined pattern (typically in matrix), as shown in FIG. 5.

Next, the substrate structure **80** is cut to form a strip-shaped substrate structure **81** in which a plurality of constitutional units are arranged in one direction (hereinafter this step may be referred to as a "first dividing step"). Specifically, first scribe lines (linear cracks) **61a** are formed in each of the active matrix substrate **10** and the counter substrate **30** preferably by a cutter wheel with the use of the pairs of scribe marks **50** opposed to each other as guides so as to pass through the centers of the slits between pairs of scribe marks **50**, as shown in FIG. 5 and FIG. 6. Then, the substrate is divided along the first scribe lines **61a** to form the strip-shaped substrate structure **81**.

In general, in order to simplify the manufacturing process, the liquid crystal layers **20** are formed by injecting liquid crystal to a plurality of vacant cells arranged in a strip. After formation of the liquid crystal layers **20**, the plural constitutional units arranged in a strip are divided individually to complete a plurality of liquid crystal display panels **1** (hereinafter this step may be referred to as a "second dividing step"). Specifically, second scribe lines **61b** for dividing the plural constitutional units arranged in a strip are formed in each of the active matrix substrate **10** and the counter substrate **30** so as to pass through the centers of the slits between the pairs of scribe marks **50** opposed to each other. Hereinafter, the first scribe lines **61a** and the second scribe lines **61b** may be called scribe lines **61** collectively. Then, the substrates

are divided along the second scribe lines **61b** to thus complete the liquid crystal display panels **1**. Conventionally, breakage and chipping occur in the active matrix substrate **10** and the counter substrate **30** with high frequency in the first and second dividing steps.

As described above, the sealant **40** exhibits high adhesiveness to inorganic members when compared with that to organic members, and accordingly, the active matrix substrate **10** and the counter substrate **30** adhere to each other strongly. On this basis, it is preferable to expose a portion of the first substrate body **11** to a portion (a corner, for example) of the sealant **40** without forming the interlayer insulating film **15** in the vicinity of the corners of the liquid crystal display panel, as shown in FIG. **8**. If so, there are formed in the scribe lines **61** a portion where the interlayer insulating film **15** is formed and a portion where the interlayer insulating film **15** is not formed. Accordingly, as shown in FIG. **9**, a step **15b** is formed at the boundary between the portion where the interlayer insulating film **15** is formed and the portion where the interlayer insulating film **15** is not formed.

The scribe lines **61** are formed across the step **15b**, which causes comparatively large stress at the step **15b**, thereby increasing the possibility of forming undesirable cracks and chips in the vicinity of the step **15b** which may cause breakage and chipping of the active matrix substrate **10** and the counter substrate **30**. For this reason, it is difficult to manufacture a liquid crystal display panel from the conventional substrate structure **80** at high production efficiency.

In contrast, in the present preferred embodiment, no step is formed in the scribe lines **61** and the scribe lines **61** are flat to lower the possibility of causing breakage and chipping of the active matrix substrate **10** and the counter substrate **30**.

In the present preferred embodiment, as shown in FIG. **6**, a portion of the first substrate body **11** (a portion overlapped with the corner of the sealant **40**, for example) is exposed to the sealant **40** through the interlayer insulating film **15**, and the interlayer insulating film **15** covers a region where the scribe lines **61** is to be formed. Accordingly, as shown in FIG. **10**, the vicinity of the scribe lines **60** on the surface on the liquid crystal layer **20** side of the first mother glass substrate **60** is flat. In detail, the interlayer insulating film **15** covers the periphery of the surface on the liquid crystal layer **20** side of the first substrate body **11** of the divided liquid crystal display panel **1**, and therefore, the periphery of the surface on the liquid crystal layer **20** side of the first substrate body **11** is flat. Hence, in the present preferred embodiment, undesirable cracks are effectively prevented from being formed in the surface on the liquid crystal layer **20** side of the active matrix substrate **10** in forming the scribe lines **61** in the first mother glass substrate **60** in the first and second dividing steps. This enables the liquid crystal display panel **1** to be manufactured with high production efficiency.

Preferably, the flattening film for flattening the vicinity of the scribe lines **60** in the surface on the liquid crystal layer **20** side of the first mother glass substrate **60** is made of resin (more preferably, organic resin) as in the present preferred embodiment. By covering the scribe lines **61** with resin, undesirable cracks are prevented effectively from being formed in the scribing step.

In the present preferred embodiment, a portion of the surface on the liquid crystal layer **20** side of the counter substrate **30** which is located at the periphery of the divided liquid crystal display panel **1** is flat, as well. Specifically, the vicinity of the scribe lines **61** in the surface on the liquid crystal layer **20** side of the second mother glass substrate **70** is flat. Accordingly, in the present preferred embodiment, undesirable cracks are effectively prevented from being formed in the

surface on the liquid crystal layer **20** side of the counter substrate **30** in forming the scribe lines **61** in the second mother glass substrate **70** in the first and second dividing steps. This enables the liquid crystal display panel **1** to be manufactured with high production efficiency.

The scribe marks **50** in the present preferred embodiment will be described further in detail.

In the present preferred embodiment, the scribe marks **50** are not formed across the scribe lines **61** but are formed so as to be opposed to each other with the scribe lines **61** interposed. In other words, the scribe marks **50** are formed apart from the edge of the active matrix substrate **10** of the divided liquid crystal display panel **1**. For example, in the case where the scribe marks **50** are formed across the scribe lines **61**, undesirable cracks might be formed in the scribing step in the vicinity of portions where scribe marks **50** are formed, which is due to the difference in material characteristics (hardness and the like, for example) between the scribe marks **50** and the first mother glass substrate **60**. In contrast, in the present preferred embodiment, the scribe marks **50** are not formed across the scribe lines **61** to suppress formation of undesirable cracks. Hence, the liquid crystal display panel **1** can be manufactured with high production efficiency.

Further, in the present preferred embodiment, the scribe marks **50** are preferably formed of the same film as the film of the pixel electrodes **16** which is the thinnest of all the conductive members of the electrode lines (the gate lines **12**, the source lines **13**, and the like), the pixel electrodes **16**, and the like. In other words, the scribe marks **50** are formed comparatively thinly in the present preferred embodiment. This effectively suppresses breakage and chipping of the counter substrate **30**.

For forming the scribe marks **50** in the counter substrate **30**, the cutter wheel **80** presses and scans the counter substrate **30**. The counter substrate **30**, which is comparatively thinner than the active matrix substrate **10**, is deformed convexly toward the active matrix substrate **10** by the pressure from the cutter wheel **80**. In the case where the opposed scribe marks **50** interposing the scribe lines **61** are comparatively thick, the thus deformed counter substrate **30** may be in contact with the scribe marks **50**, as shown in FIG. **11**. When the counter substrate **30** is in contact with the scribe marks **50**, the counter substrate **30** is pressed by three members of the pair of scribe marks **50** and the cutter wheel **80**, thereby increasing the possibility of causing breakage and chipping of the counter substrate **30**. This might lower the production efficiency.

In contrast, in the present preferred embodiment, the scribe marks **50** is formed comparatively thinly to suppress contact of the counter substrate **30** to the scribe marks **50**, as shown in FIG. **12**. Accordingly, formation of undesirable cracks and the like in the counter substrate **30** is suppressed, thereby enabling manufacture of the liquid crystal display panel **1** with high production efficiency. In view of this, it is preferable that the scribe marks **50** on the active matrix substrate **10** are thin enough not to be in contact with the counter substrate **30** in the scribing step.

Though the scribe marks **50** are preferably formed of the same film as the conductive oxide film forming the pixel electrodes **16** in the present preferred embodiment, the present invention is not limited thereto and the scribe marks **50** may be substantially formed of a metal material, for example. To do so, the scribe marks **50** may be formed of the same film as a film forming the electrode lines of the gate lines **12** or the source lines **13**, for example. The scribe marks **50**

made of a metal material is excellent in visibility, and therefore, more precise division can be achieved.

Modified Example 1

Modified Example of the First Preferred Embodiment

FIG. 13 shows a liquid crystal display panel in accordance with Modified Example 1.

As shown in FIG. 13, the surface on the liquid crystal layer 20 side of the second substrate body may be flattened in such a manner that a black matrix layer 32a included in the color filter layer 32 is formed so as to cover a portion of the surface on the liquid crystal layer 20 side thereof which is located at the periphery of the liquid crystal display panel. In other words, the black matrix layer 32a may cover a portion of the second mother glass substrate 70 where the scribe lines 61 are formed.

Modified Example 2

Modified Example of First Preferred Embodiment

FIG. 14 shows a liquid crystal display panel in accordance with Modified Example 2. FIG. 15 shows a manufacturing step thereof.

As shown in FIG. 14 and FIG. 15, each scribe mark 50 may be a set of marks having a substantially triangular shape (e.g., equilateral triangle) in plan view.

Second Preferred Embodiment

FIG. 16 shows a liquid crystal display panel 2 in accordance with a second preferred embodiment. FIG. 17 shows a manufacturing step thereof.

The liquid crystal display panel 2 in accordance with the second preferred embodiment preferably has the same features as the liquid crystal display panel 1 in accordance with the first preferred embodiment except for the arrangement of the scribe marks 50. Hereinafter, only the arrangement of the scribe marks 50 in the second preferred embodiment will be described in detail. In the description of the second preferred embodiment, the reference numerals common to those of the first preferred embodiment are assigned to elements having substantially the same functions for omitting detailed description.

In the liquid crystal display panel 2 in accordance with the second preferred embodiment, the scribe marks 50 are preferably formed to have a substantially rectangular shape in plan view of which one of the sides thereof is aligned with an edge of the active matrix substrate 10 in plan view. In other words, as shown in FIG. 17, the scribe marks 50 having a substantially rectangular shape in plan view are formed across the scribe lines 61. In this case, the scribe marks 50 may be made of a metal material but preferably is made of conductive oxide (the same film as the film of the pixel electrodes 16, for example). Scribing of the scribe marks 50 made of a metal material, which is largely different in material characteristics from the glass-made first substrate body 11, readily forms undesirable cracks or the like in the vicinity of the scribe marks 50. In contrast, the scribe mark made of conductive oxide comparatively similar in material characteristics to glass, such as indium tin oxide, indium zinc oxide, or the like effectively suppresses formation of cracks and the like in the vicinity of the scribe marks 50. Hence, the liquid

crystal display panel 2 capable of being manufactured with high production efficiency can be attained.

In the second preferred embodiment, sides 50a of the scribe marks 50 are intersected at a right angle with the edge of the active matrix substrate 10 (scribe lines 61). This effectively suppresses formation of cracks and the like in the vicinity of the scribe marks 50 when compared with the case, for example, where the sides 50a of the scribe marks 50 are inclined with respect to the scribe lines 61.

It is noted that the scribe marks 50 referred to in the first and second preferred embodiments and Modified Examples 1 and 2 are mere examples and are not limiting of the present invention in any respect.

Hereinbefore, the preferred embodiments of the display panel in accordance with the present invention have been described by referring to the active matrix liquid crystal display panels in first and second preferred embodiments and Modified Examples 1 and 2, but the display panel in accordance with the present invention is not limited to the active matrix display panels. For example, the display panel may be a passive matrix display panel or a segment display panel. Further, the flattening film is not limited to the interlayer insulating film 15 and may be another film. For example, a metal reflective film (see, Japanese Unexamined Patent Application Publication No. 11-242215 and the like, for example) or a color filter flattening film (see, Japanese Unexamined Patent Application Publication No. 4-60517 and the like, for example) may be used in the case of a passive matrix display panel.

Moreover, the display panel in accordance with the present invention is not limited to the liquid crystal display panel and may be any kind of display panels, such as an inorganic electroluminescent display panel, an organic electroluminescent display panel, a field emission display panel, a plasma display panel, and the like. In addition, the present invention is applicable to various kinds of general electronic components.

As described above, the display panel in accordance with various preferred embodiments of the present invention can be manufactured with high production efficiency and is, therefore, useful for mobile appliances, such as mobile phones, PDAs, and the like, televisions, electronic books, monitors, electronic posters, watches, electronic shelf labels, emergency signs, and the like.

While preferred embodiments of the present invention have been described above, it is to be understood that variations and modifications will be apparent to those skilled in the art without departing the scope and spirit of the present invention. The scope of the present invention, therefore, is to be determined solely by the following claims.

What is claimed is:

1. A display panel comprising:

a first substrate;

a second substrate opposed to the first substrate;

a display medium layer provided between the first substrate and the second substrate;

a sealant surrounding the display medium layer between the first substrate and the second substrate so as to join the first substrate and the second substrate and sealing the display medium layer; wherein

the first substrate includes a mark located at a periphery of the display panel outside of the sealant and arranged on a side of the display medium layer, and a flattening film which is arranged on the side of the display medium layer to cover a surface of the first substrate;

11

the flattening film includes a sealing exposing portion arranged around the display panel so as to expose the sealant to an outside; and

the mark is arranged on a portion between the sealing exposed opening and an edge side of the flattening film. 5

2. The display panel of claim 1, wherein the first substrate further includes a plurality of thin film transistors located on the first substrate, an interlayer insulating film which is located on the plurality of thin film transistors and in which a plurality of through holes open to the plurality of thin film transistors are formed, and a plurality of pixel electrodes which are located on the interlayer insulating film and which are electrically connected to the thin film transistors through the plurality of through holes, and the interlayer insulating film defines the flattening film on the entirety of the portion of the first substrate which is located at the periphery of the display panel. 10

3. The display panel of claim 1, wherein the flattening film is a resin film. 15

4. The display panel of claim 1, wherein the display medium layer is a liquid crystal layer. 20

5. The display panel of claim 1, wherein the first substrate includes a plurality of conductive members; and

the mark is defined by a thinnest one of the plurality of conductive members. 25

6. The display panel of claim 5, wherein the first substrate includes a plurality of gate lines extending in parallel or substantially in parallel to one another, a plurality of source lines extending in parallel or substantially in parallel to one another to define angles with respect to a direction in which the plurality of gate lines extend, a plurality of switching elements each connected to both a corresponding one of the plurality of gate lines and a corresponding one of the plurality of source lines, an interlayer insulating film provided on the switching 30

12

elements and including a plurality of through holes that are each open to a corresponding one of the switching elements, and a plurality of pixel electrodes that are each electrically connected to a corresponding one of the switching elements through the interlayer insulating film; and

the plurality of conductive members include the plurality of gate lines, the plurality of source lines, and the plurality of pixel electrodes.

7. The display panel of claim 6, wherein the mark is substantially made of a transparent conductive oxide.

8. The display panel of claim 7, wherein the plurality of pixel electrodes are substantially made of the transparent conductive oxide; and the mark is made of a same material as that of the plurality of pixel electrodes.

9. The display panel of claim 1, wherein the mark is substantially made of a metal material.

10. The display panel of claim 9, wherein the first substrate includes electrode lines substantially made of a metal material; and the mark is made of a same material as that of the electrode lines.

11. The display panel of claim 1, wherein the mark is spaced from an edge of the first substrate.

12. The display panel of claim 1, wherein the mark has a polygonal shape in plan view including a side corresponding to an edge of the first substrate in plan view.

13. The display panel of claim 12, wherein the mark includes at least one edge in perpendicular or substantially perpendicular contact with an edge of the first substrate in plan view.

14. The display panel of claim 1, wherein the mark is a scribe mark.

* * * * *

专利名称(译)	显示面板包括位于密封剂外部的标记和包括密封暴露部分的平坦化膜		
公开(公告)号	US8009255	公开(公告)日	2011-08-30
申请号	US12/753130	申请日	2010-04-02
[标]申请(专利权)人(译)	夏普株式会社		
申请(专利权)人(译)	夏普株式会社		
当前申请(专利权)人(译)	夏普株式会社		
[标]发明人	ONISHI NORIAKI FUJIKAWA YOHSUKE TOMIOKA HIROAKI KOJIMA HIROAKI TAGUSA YASUNOBU		
发明人	ONISHI, NORIAKI FUJIKAWA, YOHSUKE TOMIOKA, HIROAKI KOJIMA, HIROAKI TAGUSA, YASUNOBU		
IPC分类号	G02F1/1333 G02F1/1339		
CPC分类号	G02F1/133351 G02F1/133345 G02F2001/133354 G02F1/1362		
优先权	2005268899 2005-09-15 JP PCT/JP2006/318166 2006-09-13 WO		
其他公开文献	US20100188631A1		
外部链接	Espacenet USPTO		

摘要(译)

液晶显示面板包括有源矩阵基板，对置基板，液晶层和密封剂。对电极与有源矩阵衬底相对。液晶层设置在有源矩阵基板和対置基板之间。围绕有源矩阵衬底和对衬底之间的液晶层的密封剂连接有源矩阵衬底和对衬底并密封液晶层。位于液晶显示板周边的有源矩阵基板的液晶层侧的表面的一部分是平坦的。

