



US008496988B2

(12) **United States Patent**
Geum(10) **Patent No.:** **US 8,496,988 B2**
(45) **Date of Patent:** **Jul. 30, 2013**(54) **DISPENSER FOR FABRICATING LIQUID CRYSTAL DISPLAY PANEL AND METHOD FOR CONTROLLING GAP BETWEEN NOZZLE AND SUBSTRATE BY USING THE SAME**(75) Inventor: **Chang-Seok Geum**, Kyongsangbuk-do (KR)(73) Assignee: **LG Display Co., Ltd.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

4,775,225 A	10/1988	Tsuboyama et al.
5,247,377 A	9/1993	Omeis et al.
5,263,888 A	11/1993	Ishihara et al.
5,379,139 A	1/1995	Sato et al.
5,406,989 A	4/1995	Abe
5,409,545 A *	4/1995	Levey et al. 134/22.18
5,431,771 A *	7/1995	Vinouze et al. 216/23
5,499,128 A	3/1996	Hasegawa et al.
5,507,323 A	4/1996	Abe
5,511,591 A	4/1996	Abe
5,539,545 A	7/1996	Shimizu et al.
5,548,429 A	8/1996	Tsujita
5,642,214 A	6/1997	Ishii et al.
5,680,189 A	10/1997	Shimizu et al.
5,742,370 A	4/1998	Kim et al.
5,757,451 A	5/1998	Miyazaki et al.
5,852,484 A	12/1998	Inoue et al.

(Continued)

(21) Appl. No.: **10/660,655**(22) Filed: **Sep. 12, 2003**(65) **Prior Publication Data**

US 2004/0090590 A1 May 13, 2004

(30) **Foreign Application Priority Data**

Nov. 11, 2002 (KR) 10-2002-0069768

(51) **Int. Cl.**
G02F 1/13 (2006.01)(52) **U.S. Cl.**
USPC **427/58**; 349/187(58) **Field of Classification Search**
USPC 427/8, 58, 64, 256
See application file for complete search history.(56) **References Cited**

U.S. PATENT DOCUMENTS

3,978,580 A	9/1976	Leupp et al.
4,094,058 A	6/1978	Yasutake et al.
4,653,864 A	3/1987	Baron et al.
4,691,995 A	9/1987	Yamazaki et al.


FOREIGN PATENT DOCUMENTS

EP	1 003 066	5/2000
EP	1 240 913 A2	9/2002

(Continued)

Primary Examiner — Michael Cleveland*Assistant Examiner* — Tabassom Tadayyon Eslami(74) *Attorney, Agent, or Firm* — McKenna, Long & Aldridge, LLP(57) **ABSTRACT**

A dispenser for fabricating a liquid crystal display panel and a method for controlling a gap between a nozzle and a substrate by using the same are disclosed in the present invention. The dispenser for fabricating a liquid crystal display panel includes a syringe having a nozzle at one end and separated from a substrate, a vertical driving motor driving the syringe in a vertical direction, a contact type switch switching on/off the vertical driving motor depending on whether the nozzle and the substrate are in contact with each other, and a first sensor detecting an initial value between the nozzle and the substrate by switching on and off the contact type switch.

5 Claims, 8 Drawing Sheets

US 8,496,988 B2

Page 2

U.S. PATENT DOCUMENTS

5,854,664	A	12/1998	Inoue et al.	JP	10-123537	5/1998
5,861,932	A	1/1999	Inata et al.	JP	10-123538	5/1998
5,875,922	A	3/1999	Chastine et al.	JP	10-142616	5/1998
5,952,676	A	9/1999	Sato et al.	JP	10-177178	6/1998
5,956,112	A	9/1999	Fujimori et al.	JP	10-221700	8/1998
6,001,203	A *	12/1999	Yamada et al. 156/106	JP	10-282512	10/1998
6,011,609	A	1/2000	Kato et al.	JP	10-333157	12/1998
6,016,178	A	1/2000	Kataoka et al.	JP	10-333159	12/1998
6,016,181	A	1/2000	Shimada	JP	11-14953	1/1999
6,055,035	A	4/2000	von Gutfeld et al.	JP	11-38424	2/1999
6,139,639	A *	10/2000	Kitamura et al. 118/680	JP	11-64811	3/1999
6,144,438	A *	11/2000	Izumi 349/155	JP	11-109388	4/1999
6,163,357	A	12/2000	Nakamura	JP	11-133438	5/1999
6,219,126	B1	4/2001	Von Gutfeld	JP	11-142864	5/1999
6,222,603	B1	4/2001	Sakai et al.	JP	11-174477	7/1999
6,226,067	B1	5/2001	Nishiguchi et al.	JP	11-212045	8/1999
6,236,445	B1	5/2001	Foschaar et al.	JP	11-248930	9/1999
6,284,073	B1 *	9/2001	Nemoto et al. 156/64	JP	11-326922	11/1999
6,304,306	B1	10/2001	Shiomi et al.	JP	11-344714	12/1999
6,304,311	B1	10/2001	Egami et al.	JP	2000-2879	1/2000
6,337,730	B1	1/2002	Ozaki et al.	JP	2000-29035	1/2000
6,391,378	B1 *	5/2002	Carr et al. 427/8	JP	2000-56311	2/2000
6,414,733	B1	7/2002	Ishikawa et al.	JP	2000-66165	3/2000
6,455,099	B1 *	9/2002	Enchi et al. 427/96.2	JP	2000-137235	5/2000
6,595,819	B1 *	7/2003	Kitahara et al. 445/24	JP	2000-147528	5/2000
2001/0021000	A1	9/2001	Egami	JP	2000-193988	7/2000
				JP	2000-241824	9/2000
				JP	2000-284295	10/2000
				JP	2000-292799	10/2000
				JP	2000-310759	11/2000
				JP	2000-310784	11/2000
				JP	2000-338501	12/2000
				JP	2001-5401	1/2001
				JP	2001-5405	1/2001
				JP	2001-13506	1/2001
				JP	2001-33793	2/2001
				JP	2001-42341	2/2001
				JP	2001-51284	2/2001
				JP	2001-66615	3/2001
				JP	2001-91727	4/2001
				JP	2001-117105	4/2001
				JP	2001-117109	4/2001
				JP	2001-133745	5/2001
				JP	2001-133794	5/2001
				JP	2001-133799	5/2001
				JP	2001-142074	5/2001
				JP	2001-147437	5/2001
				JP	2001-154211	6/2001
				JP	2001-166272	6/2001
				JP	2001-166310	6/2001
				JP	2001-183683	7/2001
				JP	2001-201750	7/2001
				JP	2001-209052	8/2001
				JP	2001-209060	8/2001
				JP	2001-215459	8/2001
				JP	2001-222017	8/2001
				JP	2001-235758	8/2001
				JP	2001-255542	9/2001
				JP	2001-264782	9/2001
				JP	2001-272640	10/2001
				JP	2001-281675	10/2001
				JP	2001-281678	10/2001
				JP	2001-282126	10/2001
				JP	2001-305563	10/2001
				JP	2001-330837	11/2001
				JP	2001-330840	11/2001
				JP	2001-356353	12/2001
				JP	2001-356354	12/2001
				JP	2002-14360	1/2002
				JP	2002-23176	1/2002
				JP	2002-49045	2/2002
				JP	2002-82340	3/2002
				JP	2002-90759	3/2002
				JP	2002-90760	3/2002
				JP	2002-107740	4/2002
				JP	2002-122872	4/2002
				JP	2002-122873	4/2002
				JP	2002-139734	5/2002
				JP	2002-202512	7/2002

FOREIGN PATENT DOCUMENTS

JP	51-65656	6/1976	JP	2000-310759	11/2000
JP	57-38414	3/1982	JP	2000-310784	11/2000
JP	57-88428	6/1982	JP	2000-338501	12/2000
JP	58-27126	2/1983	JP	2001-5401	1/2001
JP	59-57221	4/1984	JP	2001-5405	1/2001
JP	59-195222	11/1984	JP	2001-13506	1/2001
JP	60-111221	6/1985	JP	2001-33793	2/2001
JP	60-164723	8/1985	JP	2001-42341	2/2001
JP	60-217343	10/1985	JP	2001-51284	2/2001
JP	61-7822	1/1986	JP	2001-66615	3/2001
JP	61-55625	3/1986	JP	2001-91727	4/2001
JP	62-89025	4/1987	JP	2001-117105	4/2001
JP	62-90622	4/1987	JP	2001-117109	4/2001
JP	62-205319	9/1987	JP	2001-133745	5/2001
JP	63-109413	5/1988	JP	2001-133794	5/2001
JP	63-110425	5/1988	JP	2001-133799	5/2001
JP	63-128315	5/1988	JP	2001-142074	5/2001
JP	63-311233	12/1988	JP	2001-147437	5/2001
JP	05-127179	5/1993	JP	2001-154211	6/2001
JP	5-154923	6/1993	JP	2001-166272	6/2001
JP	5-265011	10/1993	JP	2001-166310	6/2001
JP	5-281557	10/1993	JP	2001-183683	7/2001
JP	5-281562	10/1993	JP	2001-201750	7/2001
JP	05-323332	12/1993	JP	2001-209052	8/2001
JP	6-51256	2/1994	JP	2001-209060	8/2001
JP	06-114315	* 4/1994	JP	2001-215459	8/2001
JP	6-148657	5/1994	JP	2001-222017	8/2001
JP	6-160871	6/1994	JP	2001-235758	8/2001
JP	6-235925	8/1994	JP	2001-255542	9/2001
JP	6-265915	9/1994	JP	2001-264782	9/2001
JP	6-313870	11/1994	JP	2001-272640	10/2001
JP	7-84268	3/1995	JP	2001-281675	10/2001
JP	7-128674	5/1995	JP	2001-281678	10/2001
JP	7-181507	7/1995	JP	2001-282126	10/2001
JP	8-95066	4/1996	JP	2001-305563	10/2001
JP	8-101395	4/1996	JP	2001-330837	11/2001
JP	8-106101	4/1996	JP	2001-330840	11/2001
JP	8-171094	7/1996	JP	2001-356353	12/2001
JP	8-190099	7/1996	JP	2001-356354	12/2001
JP	8-240807	9/1996	JP	2002-14360	1/2002
JP	09-005762	1/1997	JP	2002-23176	1/2002
JP	9-26578	1/1997	JP	2002-49045	2/2002
JP	9-61829	3/1997	JP	2002-82340	3/2002
JP	9-73075	3/1997	JP	2002-90759	3/2002
JP	9-73096	3/1997	JP	2002-90760	3/2002
JP	9-127528	5/1997	JP	2002-107740	4/2002
JP	9-230357	9/1997	JP	2002-122872	4/2002
JP	9-281511	10/1997	JP	2002-122873	4/2002
JP	9-311340	12/1997	JP	2002-139734	5/2002
			JP	2002-202512	7/2002

US 8,496,988 B2

Page 3

JP	2002-202514	7/2002
JP	2002-214626	7/2002
KR	2000-0002415	2/2000
KR	2000-0035302	6/2000

WO	WO00/11710	* 3/2000
WO	WO/0011710	* 3/2000

* cited by examiner

FIG. 1
RELATED ART




FIG. 2A
RELATED ART




FIG. 2B
RELATED ART




FIG. 3
RELATED ART




FIG. 4
RELATED ART




FIG. 5
RELATED ART




FIG. 6




FIG. 7





FIG. 8



1

DISPENSER FOR FABRICATING LIQUID CRYSTAL DISPLAY PANEL AND METHOD FOR CONTROLLING GAP BETWEEN NOZZLE AND SUBSTRATE BY USING THE SAME

This application claims the benefit of the Korean Application No. P2002-069768 filed on Nov. 11, 2002, which is hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a liquid crystal display panel, and more particularly, to a dispenser for fabricating a liquid crystal display panel and a method for controlling a gap between a nozzle and a substrate by using the same.

2. Discussion of the Related Art

In general, a liquid crystal display panel is a display device where data signals including picture information are individually supplied to liquid crystal cells arranged in a matrix form, and the light transmittance of the liquid crystal cells is controlled to display a desired picture. Thus, the liquid crystal display device includes a liquid crystal display panel, and a driver integrated circuit (IC) for driving the liquid crystal cells. The liquid crystal cells are arranged in a unit pixel in a matrix form.

The liquid crystal display panel includes a color filter substrate and a thin film transistor array substrate facing into each other. The liquid crystal display panel further includes a liquid crystal layer between the color filter substrate and the thin film transistor array substrate.

Data lines and gate lines are formed on the thin film transistor array substrate of the liquid crystal display panel, and intersect one another at right angles, so that liquid crystal cells are defined at each intersection. The data lines transmit a data signal supplied from the data driver integrated circuit to the liquid crystal cells, and the gate lines transmit a scan signal supplied from the gate driver integrated circuit to the liquid crystal cells. At one portion of the data lines and the gate lines, a data pad and a gate pad are provided in which data signals and scan signals are applied from the data driver integrated circuit and the gate driver integrated circuit.

The gate driver integrated circuit sequentially supplies the scan signal to the gate lines so that the liquid crystal cells arranged in a matrix form can be sequentially selected line by line, and the data signal is supplied to the selected one line of the liquid crystal cells from the data driver integrated circuit.

A common electrode and a pixel electrode are formed at the inner side of the color filter substrate and the thin film transistor array substrate, and apply an electric field to the liquid crystal layer. The pixel electrode is formed at each liquid crystal cell on the thin film transistor array substrate, while the common electrode is integrally formed at the entire surface of the color filter substrate. Therefore, by controlling a voltage applied to the pixel electrode in a state where a voltage is applied to the common electrode, the light transmittance of the liquid crystal cells can be individually controlled.

In order to control the voltage applied to the pixel electrode by liquid crystal cells, a thin film transistor used as a switching device is formed at each liquid crystal cell.

Elements of the liquid crystal display device will now be described.

FIG. 1 is a plane view of a unit liquid crystal display panel having a thin film transistor array substrate and a color filter substrate according to the related art.

2

In FIG. 1, a liquid crystal display panel 100 includes an image display part 113 where liquid crystal cells are arranged in a matrix form, a gate pad part 114 connected to the gate lines of the image display part 113, and a data pad part 115 connected to the data lines of the image display part 113. The gate pad part 114 and the data pad part 115 are formed along the edge region of the thin film transistor array substrate 101 that does not overlap the color filter substrate 102. The gate pad part 114 supplies a scan signal from the gate driver integrated circuit to the gate lines of the image display part 113, and the data pad part 115 supplies image information from the data driver integrated circuit to the data lines of the image display part 113.

The data lines to which image information is applied and the gate lines to which a scan signal is applied intersect one another. A thin film transistor for switching the liquid crystal cells, a pixel electrode for driving the liquid crystal cells by connecting the thin film transistor, and a passivation layer formed at the entire surface to protect the electrodes and the thin film transistor are provided at the intersections.

Color filters formed at the cell regions separated by the black matrix and a common transparent electrode formed at the thin film transistor array substrate 101 are provided at the color filter substrate 102 of the image display part 113. A cell gap is formed by a spacer between the thin film transistor array substrate 101 and the color filter substrate 102, and the thin film transistor array substrate 101 and the color filter substrate 102 are attached to each other by a seal pattern 116 formed along the outer edge of the image display part 113, thereby forming a unit liquid crystal display panel.

In fabricating a unit liquid crystal display panel, a plurality of unit liquid crystal display panels are simultaneously formed on a large-scale mother substrate. Thus, it requires a process for separating the unit liquid crystal display panels from the large-scale mother substrate by cutting and processing the mother substrate with the plurality of liquid crystal display panels formed thereon.

As for the unit liquid crystal display panel separated from the large-scale mother substrate, liquid crystal is injected through a liquid crystal injection hole to form a liquid crystal layer at the cell gap that separates the thin film transistor array substrate 101 and the color filter substrate 102, and then the liquid crystal injection hole is sealed.

As mentioned above, in order to fabricate a unit liquid crystal display panel, the following processes are generally required. The thin film transistor array substrate 101 and the color filter substrate 102 are separately fabricated and attached to each other, so that a uniform cell gap is maintained therebetween. And, the attached substrates are cut into unit liquid crystal display panels, then a liquid crystal is injected into the cell gap of the unit liquid crystal display device panel.

Especially, the process of forming the seal pattern 116 along the outer edge of the image display part 113 is required to attach the thin film transistor array substrate 101 and the color filter substrate 102. A method of a seal pattern according to the related art will now be described as follows.

FIGS. 2A and 2B illustrate a screen printing process to form a seal pattern according to the related art.

As shown in FIGS. 2A and 2B, a patterned screen mask 206 is provided so that a seal pattern forming region is selectively exposed. A rubber squeegee 208 is provided for selectively supplying a sealant 203 to a substrate 200 through the screen mask 206 to form a seal pattern 216.

The seal pattern 216 formed on the substrate 200 is to be used for a cell gap to which liquid crystal is injected, and prevents leakage of the injected liquid crystal. Thus, the seal pattern 216 is formed along the outer edge of the image

display part **213** of the substrate **200**, and a liquid crystal injection hole is formed at one side of the seal pattern **216**.

The screen printing method includes applying the sealant **203** on the screen mask **206** with a seal pattern forming region patterned thereon, forming the seal pattern **216** on the substrate **200** through printing with the rubber squeegee **208**, evaporating a solvent contained in the seal pattern **216**, and leveling the seal pattern **216**.

The screen printing method is widely used due to an advantage in convenience in the process. However, it is disadvantageous in that the sealant **203** is much consumed as the sealant **203** is applied at the entire surface of the screen mask **206** and printed with the rubber squeegee **208** to form the seal pattern **216**.

In addition, the screen printing method has a problem that the rubbing process of an alignment layer (not shown) formed on the substrate **200** is defective as the screen mask **206** and the substrate **200** are in contact with each other, thereby degrading a picture quality of the liquid crystal display device.

Therefore, in order to complement the shortcomings of the screen printing method, a seal dispensing method has been proposed.

FIG. **3** is a schematic view illustrating a dispensing method for forming a seal pattern according to the related art.

As shown in FIG. **3**, a table **310** with a substrate **300** loaded thereon is moved in forward/backward and left/right directions. At the same time, a seal pattern **316** is formed along the outer edge of an image display part **313** of the substrate **300** by applying a pressure to a syringe **301** filled with a sealant.

In the seal dispensing method, as a sealant is selectively supplied to the region where the seal pattern **316** is to be formed, a sealant consumption can be reduced. In addition, since the syringe **301** is not in contact with an alignment layer (not shown) of the image display part **313** of the substrate **300**, the rubbed alignment layer would not be damaged, and thus a picture quality of the liquid crystal display device can be improved.

In case of forming the seal pattern **316** on the substrate **300** loaded on the table **310** by using the syringe **301**, a gap between the substrate **300** and the syringe **301** must be precisely controlled.

In other words, if the substrate **300** and the syringe **301** are too close to each other, the seal pattern **316** formed on the substrate **300** becomes widened and has a short height. If, however, the substrate **300** and the syringe **301** are separated too far apart from each other, the seal pattern **316** formed on the substrate **300** becomes narrow and a broken part may exist, thereby causing a defect in the liquid crystal display device.

In addition, if the sealant filled in the syringe **301** is completely used up, a broken part may exist in the seal pattern **316**, or the seal pattern **316** is not formed at all. In this case, the syringe **301** should be replaced with another syringe **301** filled with a sealant before it is completely used up. At this time, however, the gap between the substrate **300** and the syringe **301** varies with how the syringe **301** is combined with the dispenser, and thus, the gap between the substrate **300** and the syringe **301** should be newly set whenever the syringe **301** is replaced with a new one.

The syringe **301** is frequently replaced in manufacturing products. Therefore, there is a demand for a method for setting the gap between the substrate **300** and the syringe **301** within a short time.

In the related art, in order to control the gap between the substrate **300** and the syringe **301**, a manual operation method has been adopted, which will now be described in detail.

FIG. **4** is a schematic view showing a seal dispenser for fabricating a liquid crystal display panel according to the related art.

As shown in FIG. **4**, a seal dispenser includes a syringe **403** having a nozzle **402** at one end thereof and supplying a sealant onto a substrate **401** loaded on a table **400**, a vertical driving motor **405** for driving a body **404** in the vertical direction, a micrometer **406** for driving the vertical driving motor **405** by a manual operation, a first sensor **407** for detecting a contact between the substrate **401** and the nozzle **402**, and a second sensor **408** for detecting a gap between the substrate **401** and the nozzle **402**.

FIG. **5** is a flow chart illustrating the method for controlling a gap between the nozzle and the substrate by using the seal dispenser of FIG. **4**.

As shown in FIG. **5**, the method for controlling a gap between the nozzle and the substrate by using the seal dispenser of the liquid crystal display panel includes lowering the nozzle **402** by manually manipulating the micrometer **406**, detecting whether the nozzle **402** and the substrate **401** are in contact with each other, lifting up the nozzle **402** by manually manipulating the micrometer **406**, and stopping the nozzle and constantly maintaining a desirable gap between the nozzle **402** and the substrate **401**.

The related art seal dispenser for fabricating the liquid crystal display panel and the method for controlling a gap between the nozzle and the substrate by using the dispenser will now be described.

First, when the substrate **401** is loaded on the table **400**, a user drives the vertical driving motor **405** by manually manipulating the micrometer **406**, thereby lowering the syringe **403** mounted in the body **404**. At this time, the user detects whether the nozzle **402** provided at one end portion of the syringe **403** and the substrate **401** loaded on the table **400** are in contact with each other through a process of monitoring a value measured by the first sensor **407**.

When the substrate **401** and the nozzle **402** are detected to be in contact with each other by the first sensor **407**, the user drives the vertical driving motor **405** by manually manipulating the micrometer **406**, thereby lifting up the syringe **403** mounted in the body **404**. At this time, the user detects whether the gap between the substrate **401** and the nozzle **402** reaches a pre-set value through a process of monitoring a value measured by the second sensor **408** and stops manipulating the micrometer **406**.

However, the related art seal dispenser for fabricating the liquid crystal display panel and the method for controlling a gap between the nozzle and the substrate have the following problems.

Since the user controls the gap between the substrate **401** and the nozzle **402** by manually manipulating the micrometer **406**, reliability is much degraded, and yield in fabricating liquid crystals display panel is decreased.

In addition, much time is required for setting the gap between the substrate **401** and the nozzle **402** precisely even by a skilled user, resulting in degrading productivity.

Furthermore, since the gap is set by the user's manual operation, an equipment manipulation is inconvenient in the related art process.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to a dispenser for fabricating a liquid crystal display panel and a method for controlling a gap between a nozzle and a substrate

5

by using the same that substantially obviate one or more of problems due to limitations and disadvantages of the related art.

Another object of the present invention is to provide a dispenser for fabricating a liquid crystal display panel and a method for controlling a gap between a nozzle and a substrate by using the same that are capable of automatically controlling the gap between the nozzle provided at the dispenser and the substrate.

Additional features and advantages of the invention will be set forth in the description which follows and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described, a dispenser for fabricating a liquid crystal display panel includes a syringe having a nozzle at one end separated from a substrate, a vertical driving motor driving the syringe in a vertical direction, a contact type switch switching on/off the vertical driving motor depending on whether the nozzle and the substrate are in contact with each other, and a first sensor detecting an initial value between the nozzle and the substrate by switching on and off the contact type switch.

In another aspect of the present invention, a method for controlling a gap between a nozzle and a substrate by using a dispenser for fabricating a liquid crystal display panel includes lowering a body supporting a syringe having a nozzle at one end until the nozzle contacts a substrate, determining an initial value between the nozzle and the substrate by turning on or turning off a contact type switch by lifting up the body when the nozzle contacts the substrate, lifting up the body, so that the nozzle is isolated from the substrate, and lowering the body, so that the nozzle reaches a desirable height from the initial value.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this application, illustrate embodiments of the invention and together with the description serve to explain the principle of the invention.

In the drawings:

FIG. 1 is a plane view of a unit liquid crystal panel formed by a thin film transistor array substrate and a color filter substrate according to the related art;

FIGS. 2A and 2B illustrate a screen printing method to form a seal pattern according to the related art;

FIG. 3 is a schematic view illustrating a dispensing method for forming a seal pattern according to the related art;

FIG. 4 a schematic view showing a seal dispenser for fabricating a liquid crystal display panel according to the related art;

FIG. 5 is a flow chart illustrating the method for controlling a gap between a nozzle and a substrate by using the seal dispenser of FIG. 4;

FIG. 6 illustrates a dispenser for fabricating a liquid crystal display panel according to the present invention;

6

FIG. 7 is a flow chart illustrating a method for controlling a gap between a nozzle and a substrate by using the dispenser of FIG. 6; and

FIG. 8 is a schematic cross-sectional view illustrating a structure of one edge of the liquid crystal display panel.

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

Reference will now be made in detail to the illustrated embodiments of the present invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

FIG. 6 illustrates a dispenser for fabricating a liquid crystal display panel according to the present invention.

As shown in FIG. 6, a dispenser according to the present invention includes a syringe 503 with a nozzle 502 provided at one end portion thereof and supplying a sealant onto a substrate 501 loaded on a table 500, a body 504 in which the syringe 503 is installed, a contact type switch 509 for switching from opening to closing, and vice versa, depending on whether the nozzle 502 of the syringe 503 and the substrate 501 are in contact with each other, a first sensor 507 for detecting an initial value with which the nozzle 502 of the syringe 503 and the substrate 501 are in contact with each other according to the contact type switch 509, and a vertical driving motor 505 for driving the body 504 in the vertical direction.

FIG. 7 is a flow chart illustrating a method for controlling a gap between a nozzle and a substrate by using the dispenser of FIG. 6.

As shown in FIG. 7, a method for controlling a gap between a nozzle and a substrate by using the dispenser includes lowering the body 504 with the syringe 503 installed therein, stopping the lowering the body 504 when the switch 509 is opened, and the nozzle 502 of the syringe 503 and the substrate 501 are in contact with each other due to the lowering the body 504, detecting an initial value with which the nozzle 502 and the substrate 501 are in contact with each other by opening or closing the contact type switch 509 by lifting up the body 504, lifting up the body 504 so that the nozzle 502 can be isolated from the substrate 501, and lowering the body 504 so that the nozzle 502 can reach a desired height from the initial value.

The dispenser for fabricating a liquid crystal display panel and the method for controlling a gap between the nozzle and the substrate by using the dispenser will now be described in detail.

First, when the substrate 501 is loaded on the table 500, the vertical driving motor 505 is driven to lower the position of the body 504 with the syringe 503 installed therein.

When the nozzle 502 provided at one end portion of the syringe 503 is in contact with the substrate 501 due to the lowered body 504, the contact type switch 509 is opened, and at this time, the vertical driving motor 505 stops lowering the body 504 and lifts up the body 504 at a speed slower than that of the lowering the body 504.

When the body 504 is lifted up by the vertical driving motor 505, the nozzle 502 is isolated from the substrate 501 and an opening or closing state of the contact type switch 509 is switched. At this time, an initial value is detected and stored by the first sensor 507. Thus, the initial value signifies the height information on the nozzle 502 when the nozzle 502 is in contact with the substrate 501.

For example, a laser displacement sensor may be adopted as the first sensor 507, which can measure $\pm 200 \mu\text{m}$ (micrometer)

The vertical driving motor 505 lifts up the body 504 so as to be separated from the substrate 501 with a distance and then lowers the body 504. When the nozzle 502 reaches a desired height from the initial value, the vertical driving motor 505 stops lowering the body 504. Thus, when the nozzle 502 reaches a height of, for example, about $40 \mu\text{m}$ (micrometer) from the initial value, the lowering of the body 504 is stopped and a gap between the nozzle 502 and the substrate 501 is controlled to be maintained at about $40 \mu\text{m}$ (micrometer).

After the gap between the substrate 501 and the nozzle 502 is controlled to be maintained at a certain interval, either the table 500 on which the substrate 501 has been loaded or the body 504 with the syringe 503 installed therein is horizontally moved, so that a relative position is changed, while the sealant is discharged to form a seal pattern on the substrate 501.

In case that the body 504 with the syringe 503 installed therein is moved, an undesirable material may be generated by the horizontal driving of the dispenser and adsorbed onto the substrate 501. Thus, the table 500 with the loaded substrate 501 may be horizontally moved in forward/backward and left/right directions in forming a seal pattern.

As mentioned above, in the dispenser for fabricating a liquid crystal display panel and the method for controlling a gap between the nozzle and the substrate by using the dispenser in the present invention, driving conditions are inputted by a user through an input unit such as a touch panel or a keyboard. The vertical driving motor 505 automatically lowers, stops, lifts up, and lowers again the body 504. Thus, the process to control the gap between the nozzle 502 provided at the syringe 503 and the substrate 501 loaded on the table 500 can be simple and precise.

Thus, the reliability is improved compared to the manual operation of the related art and a product failure can be reduced.

In addition, even for an unskilled user, he/she can precisely control the gap between the substrate 501 and the nozzle 502 within a short time, so that a productivity can be considerably improved.

In the present invention as described above, the seal pattern is formed on the substrate 501 through the syringe 503 filled with the sealant. Further, in fabricating the liquid crystal display panel, the preferred embodiment of the present invention can be also adopted for forming a liquid crystal layer.

The method for forming a liquid crystal layer can be divided into a vacuum injection method and a dropping method, which will now be described in detail.

The vacuum injection method is that a liquid crystal injection hole of a unit liquid crystal display panel separated from a large-scale mother substrate is dipped in a container filled with liquid crystal in a chamber under a vacuum condition, and then the liquid crystal is injected into the liquid crystal display panel, which is caused by a pressure difference between the inner side and the outer side of the liquid crystal display panel by varying a vacuum condition. After the liquid crystal is filled in the liquid crystal display panel, the liquid crystal injection hole is sealed, thereby forming the liquid crystal layer of the liquid crystal display panel.

However, the vacuum injection method as described above has the following problems.

Most of all, it takes too much time for filling the liquid crystal in the liquid crystal display panel. In general, the attached liquid crystal display panel with an area of several hundreds cm^2 (square centimeter) has only a gap of a few μm

(micrometer). Thus, even with the vacuum injection method utilizing a pressure difference, an injected amount of the liquid crystal by unit time is quite small.

For instance, in case of fabricating a liquid crystal display panel of about 15 inches, about 8 hours are required to fill the gap with the liquid crystal. Thus, the productivity is much reduced due to such a long period of time for fabricating a liquid crystal display panel.

In addition, as the liquid crystal display panel becomes large in size, it takes more time required to fill the liquid crystal and a deficiency in filling the liquid crystal may occur. Therefore, the liquid crystal cannot be properly filled by using the vacuum injection method in the large-scale liquid crystal display panel.

Other problem is that too much of the liquid crystal is consumed in the vacuum injection method. In general, an actually injected amount of the liquid crystal is very small compared to the amount of the liquid crystal filled in the container, and when the liquid crystal is exposed to the air or a specific gas, it reacts with the gas and becomes degraded. Thus, even if the liquid crystal stored in the container is to fill a plurality of the liquid crystal display panels, a large amount of the liquid crystal still remains after the filling process and the leftover will be discarded. Thus, a unit price of the liquid crystal display will be increased and lose the competitive edge in price.

In order to overcome such problems in the vacuum injection method, recently, a dropping or dispensing method is applied.

A dropping method is that liquid crystal is dropped and dispensed on a plurality of thin film transistor array substrates fabricated on one large-scale mother substrate or on a plurality of color filter substrates fabricated on another large-scale mother substrate by using a dispenser in accordance with the present invention, and then the two mother substrates are attached to each other so that the liquid crystal is uniformly distributed at the entire image display regions by the attaching pressure, thereby forming a liquid crystal layer between the substrates.

Accordingly, through the dropping method, liquid crystal can be dropped in a short time compared to the vacuum injection method. Thus, even if the liquid crystal display panel is large in size, the liquid crystal layer can be formed quickly.

In addition, since only a required amount of liquid crystal is dropped on the substrate, the dropping method prevents waste of liquid crystal, so that the unit price can be maintained with a good competitive price.

Unlike the vacuum injection method, the dropping method necessarily proceeds with separating unit liquid crystal display panels from the large-scale mother substrate after the liquid crystal layer is formed. Thus, in case of dropping liquid crystal on the substrate through the dropping method, the dispenser of the liquid crystal display panel according to the present invention can be used.

As stated above, with the dispenser for the liquid crystal display panel according to the present invention, the sealant is filled in the syringe 503, the gap between the nozzle 502 provided at one end portion of the syringe 503 and the substrate 501 is precisely controlled in forming a seal pattern at the outer edge of the image display part of the substrate 501. In this respect, in case of applying the liquid crystal, the syringe 503 is filled with the liquid crystal, the gap between the nozzle 502 and the substrate 501 is precisely controlled, and the liquid crystal is dropped to a desired position of the

substrate **501**. In this manner, the present invention can be applied to form a liquid crystal layer by using the dropping method.

In addition, the dispenser for fabricating a liquid crystal display panel and the method of controlling a gap between a nozzle and a substrate can be also applied to a formation of a silver (Ag) dot in fabricating a liquid crystal display panel.

The formation of the silver (Ag) dot will now be described with reference to the accompanying drawings.

FIG. **8** is a schematic cross-sectional view illustrating a structure of one edge of a liquid crystal display panel.

As shown in FIG. **8**, a liquid crystal display panel is formed such that a thin film transistor array substrate **601** and a color filter substrate **602** are attached to each other with a cell gap maintained by a spacer **603** and a seal pattern **604**, and a liquid crystal layer **605** is formed in the cell gap between the thin film transistor array substrate **601** and the color filter substrate **602**.

The thin film transistor array substrate **601** is formed to be protruded from the edge of the color filter substrate **602**, and at the protruded portion, a gate pad part connected to gate lines of the thin film transistor array substrate **601** and a data pad part connected to data lines are formed.

At the image display part of the thin film transistor array substrate **601**, gate lines to which a scan signal is applied from the gate pad part and data lines to which image information is applied through the data pad part are arranged to intersect one another, and a thin film transistor for switching liquid crystal cells and a pixel electrode connected to the thin film transistor are formed at each intersection.

At the image display part of the color filter substrate **602**, color filters are separately formed at cell regions by a black matrix and a common electrode **606** for driving liquid crystal layer with the pixel electrode formed on the thin film transistor array substrate **601**.

A common voltage line **607** for applying a common voltage to the common electrode **606** formed on the color filter substrate **602** is formed on the thin film transistor array substrate **601**.

Thus, a silver (Ag) dot **608** may be formed either on the thin film transistor array substrate **601** or the color filter substrate **602** to electrically connect the common voltage line **607** and the common electrode **606**, so that the common voltage applied to the common voltage line **607** can be applied to the common electrode **606** by way of the silver (Ag) dot **608**.

One or more silver (Ag) dots **608** are formed at each unit liquid crystal display panel fabricated on the large-scale mother substrate, which can be also formed by using the dispenser for a liquid crystal display panel according to the present invention.

As stated above, in the dispenser for fabricating the liquid crystal display panel and the method for controlling a gap between the nozzle and the substrate according to the present invention, a sealant is filled in the syringe **503**, the gap between the nozzle **502** provided at one end portion of the syringe **503** and the substrate **501** can be precisely controlled in forming a seal pattern at the outer edge of the image display part of the substrate **501**. In this respect, in case of adopting a silver (Ag) dot, the syringe **503** is filled with silver (Ag), a gap between the nozzle **502** and the substrate **501** is precisely controlled, and a silver (Ag) droplet is dropped to a desirable position of the substrate **501**. In this manner, the present invention may be applied to form the silver (Ag) dot **608**.

As so far described, the dispenser for fabricating a liquid crystal display panel and the method for controlling a gap between the nozzle and the substrate by using the dispenser have the following advantages.

When driving data are inputted by a user through an input unit such as a touch panel or a keyboard, the vertical driving motor is automatically lowered, stopped, lifted up, and lowered again the body, thereby precisely controlling the gap between the nozzle and the substrate. Thus, the reliability in operation is improved compared to the manual operation.

Since the seal pattern can be formed to have height and width, a product failure of the liquid crystal display panel can be reduced.

In addition, even for an unskilled user, he/she can precisely control the gap between the nozzle and the substrate within a short time, so that the productivity can be improved.

Furthermore, the syringe can be filled with liquid crystal or silver (Ag) as well as a sealant. Thus, dropping liquid crystal or forming a silver (Ag) dot can be readily performed in the present invention.

It will be apparent to those skilled in the art that various modifications and variations can be made in the dispenser for the liquid crystal display panel and the method for controlling the gap between the nozzle and the substrate by using the same of the present invention without departing from the spirit or scope of the inventions. Thus, it is intended that the present invention covers the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A method for dropping material for fabricating a liquid crystal display panel, comprising:

loading a substrate on a table;

lowering a body supporting a syringe having a nozzle at one end towards the substrate using a vertical driving motor, wherein the vertical driving motor drives the syringe according to driving data input from a user through an input unit which comprises one of a touch panel and a keyboard, wherein the lowering is performed at a first speed;

stopping the lowering of the body when the nozzle contacts the substrate, wherein a contact type switch is opened, and lifting up the body at a second speed is slower than the first speed of the lowering the body, lifting up the nozzle to be isolated from the substrate when the body is lifted up, and a state of the contact type switch is switched; detecting and storing an initial value between the nozzle and the substrate when the body is lifted up, wherein the initial value is height information of the nozzle when the nozzle is in contact with the substrate, and wherein the detecting the initial value is performed by a laser displacement sensor; lifting up the body to be separated from the substrate with a distance; lowering the body; and stopping the lowering of the body when the nozzle reaches a desired height from the initial value so that a gap between the nozzle and the substrate is controlled to be maintained at the desired height; and horizontally moving the table with the loaded substrate in forward/backward and left/right directions while the dropping material within the syringe is being dropped through the nozzle onto the substrate.

2. The method of claim **1**, wherein a sealant is stored in the syringe.

3. The method of claim **1**, wherein a liquid crystal is stored in the syringe.

4. The method of claim **1**, wherein a liquid silver is stored in the syringe.

5. A method for dropping dropping material for fabricating liquid crystal display panel, comprising:
loading a substrate on a table;
lowering a body supporting a syringe having a nozzle at one end towards the substrate; 5
stopping the lowering of the body when the nozzle contacts the substrate, wherein a contact type switch is opened
lifting up the nozzle to be isolated from the substrate when the body is lifted up, and a state of the contact type switch is switched; 10
detecting and storing an initial value between the nozzle and the substrate when the body is lifted up, and wherein the detecting the initial value is performed by a laser displacement sensor, wherein the initial value is height information of the nozzle when the nozzle is in contact 15 with the substrate;
lifting up the body to be separated from the substrate with a distance, and lowering the body;
stopping the lowering of the body when the nozzle reaches a desired height from the initial value so that a gap 20 between the nozzle and the substrate is controlled to be maintained at the desired height; and
horizontally moving the table with the loaded substrate in forward/backward and left/right directions while a seal- 25 ant is being dropped through the nozzle onto the substrate to form a seal pattern.

* * * * *

专利名称(译)	用于制造液晶显示板的分配器和使用该分配器控制喷嘴和基板之间的间隙的方法		
公开(公告)号	US8496988	公开(公告)日	2013-07-30
申请号	US10/660655	申请日	2003-09-12
[标]申请(专利权)人(译)	乐金显示有限公司		
申请(专利权)人(译)	LG.PHILLIPS液晶CO. , LTD.		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	GEUM CHANG SEOK		
发明人	GEUM, CHANG-SEOK		
IPC分类号	G02F1/13 G02F1/1341		
CPC分类号	G02F1/1341 G02F2001/13415		
优先权	1020020069768 2002-11-11 KR		
其他公开文献	US20040090590A1		
外部链接	Espacenet USPTO		

摘要(译)

在本发明中公开了一种用于制造液晶显示板的分配器和一种通过使用该分配器来控制喷嘴和基板之间的间隙的方法。用于制造液晶显示板的分配器包括：注射器，其一端具有喷嘴并与基板分离；垂直驱动电机，其在垂直方向上驱动注射器；接触式开关，根据所述垂直驱动电机接通/断开垂直驱动电机。喷嘴和基板是否彼此接触，第一传感器通过接通和断开接触型开关来检测喷嘴和基板之间的初始值。

