



US007525629B2

(12) **United States Patent**
Konuma et al.

(10) **Patent No.:** **US 7,525,629 B2**
(45) **Date of Patent:** **Apr. 28, 2009**

(54) **LIQUID CRYSTAL DISPLAY DEVICE
COMPRISING DRIVE CIRCUITS THAT
INCLUDE THIN FILM TRANSISTORS
FORMED ON BOTH SUBSTRATES**

(75) Inventors: **Toshimitsu Konuma**, Atsugi (JP);
Takahiro Tsuji, Isehara (JP); **Kouji
Moriya**, Atsugi (JP)

(73) Assignee: **Semiconductor Energy Laboratory
Co., Ltd.**, Kanagawa-ken (JP)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/148,275**

(22) Filed: **Jun. 9, 2005**

(65) **Prior Publication Data**

US 2005/0270438 A1 Dec. 8, 2005

Related U.S. Application Data

(60) Division of application No. 08/698,204, filed on Aug.
14, 1996, now Pat. No. 6,980,275, which is a continuation
of application No. 08/301,774, filed on Sep. 7,
1994, now abandoned.

(30) **Foreign Application Priority Data**

Sep. 20, 1993 (JP) 5-256571

(51) **Int. Cl.**

G02F 1/1345 (2006.01)

G02F 1/1339 (2006.01)

(52) **U.S. Cl.** **349/151; 349/153; 349/154;
349/155**

(58) **Field of Classification Search** **349/153-154,
349/189**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,600,061 A 8/1971 Heilmeier et al.
4,308,533 A * 12/1981 Schmidt 349/153
4,362,771 A 12/1982 Umeda et al.
4,394,067 A 7/1983 Spruijt et al.

(Continued)

FOREIGN PATENT DOCUMENTS

JP 55-064212 5/1980

(Continued)

OTHER PUBLICATIONS

Mitsuru Ikezaki, Seminar Textbook, "Super High Definition Tech-
nique in LCD," pp. 1-6, Jul. 3, 2001.

(Continued)

Primary Examiner—David Nelms


Assistant Examiner—W. Patty Chen

(74) *Attorney, Agent, or Firm*—Eric J. Robinson; Robinson
Intellectual Property Law Office, P.C.

(57) **ABSTRACT**

A highly reliable liquid crystal display device in which the
drive circuit region is protected, which comprises a first substrate
having thereon a display region and a drive circuit region comprising
a drive circuit for controlling the display in
said display region and a second substrate opposed to said
first substrate, provided that said regions are partitioned by a
sealing agent and that a liquid crystal material is incorporated
between said first substrate and said second substrate opposed
to the first one, wherein, said second substrate opposed to the
first is extended to oppose both of said display region and said
drive circuit region provided on the first substrate.

20 Claims, 6 Drawing Sheets



U.S. PATENT DOCUMENTS

4,600,273 A	7/1986	Ohno	JP	64-049022	2/1989	
4,688,074 A	8/1987	Iinuma	JP	01-068725	3/1989	
4,768,863 A *	9/1988	Fertig et al.	349/143	JP	02068524 A *	3/1990
4,807,973 A *	2/1989	Kawasaki	349/192	JP	03-029923	2/1991
4,826,297 A	5/1989	Kubo et al.		JP	03-035528	4/1991
5,076,667 A	12/1991	Stewart et al.		JP	03-246522	11/1991
5,130,832 A	7/1992	Kawaguchi et al.		JP	04-034409	2/1992
5,130,833 A	7/1992	Mase		JP	04-042215	2/1992
5,148,301 A	9/1992	Sawatsubashi et al.		JP	04-078819	3/1992
5,200,847 A	4/1993	Mawatari et al.		JP	04-083227	3/1992
5,202,778 A *	4/1993	Niki	349/54	JP	04-093925	3/1992
5,247,375 A	9/1993	Mochizuki et al.		JP	04-116623	4/1992
5,278,682 A	1/1994	Niki		JP	04-133029	5/1992
5,278,685 A	1/1994	Iwamoto et al.		JP	04-260023	9/1992
5,311,342 A	5/1994	Watanabe		JP	04-120934	10/1992
5,387,445 A *	2/1995	Horiuchi et al.	428/1.54	JP	04-355433	12/1992
5,436,744 A	7/1995	Arledge et al.		JP	05-005884	1/1993
5,442,470 A	8/1995	Hashimoto		JP	05-061054	3/1993
5,460,983 A	10/1995	Hodges et al.		JP	05-066413	3/1993
5,517,344 A	5/1996	Hu et al.		JP	05-188379	7/1993
5,548,428 A	8/1996	Masaki et al.		JP	05-203977	8/1993
5,710,612 A	1/1998	Mase		JP	06-186579	7/1994
6,023,075 A	2/2000	Yamazaki		JP	06-186580	7/1994
6,175,395 B1	1/2001	Yamazaki et al.		JP	07-092475	4/1995
6,236,444 B1	5/2001	Konuma et al.		JP	07-281141	10/1995
6,404,476 B1	6/2002	Mase		JP	08-271873	10/1996

OTHER PUBLICATIONS

Chapter 3, Panel Assembling Technique Scriber/Cell Breaking Device: JKL-454F, 93 Latest Liquid Crystal Process Techniques, *Semiconductor World*, Oct. 1, 1992, p. 272 (full Eng. Translation). IBM Technical Disclosure Bulletin, "Sealing Structure for Liquid Crystal Display," vol. 32, No. 5a, Oct. 1989, pp. 223-224. English Translation of Japanese Patent Office Communication dated Nov. 16, 1999 for Application No. 05-256571, 2 pages.

* cited by examiner

FOREIGN PATENT DOCUMENTS

JP	56-111831	9/1981
JP	61-056322	3/1986
JP	62-109026	5/1987
JP	62-240934	10/1987
JP	62-251723	11/1987
JP	01-049022	2/1989



FIG. 1A
PRIOR ART**FIG. 1B**
PRIOR ART



FIG. 2A**FIG. 2B**

FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6A




FIG. 6B





FIG. 6C



**LIQUID CRYSTAL DISPLAY DEVICE
COMPRISING DRIVE CIRCUITS THAT
INCLUDE THIN FILM TRANSISTORS
FORMED ON BOTH SUBSTRATES**

BACKGROUND OF THE INVENTION

1. Industrial Field of the Invention

The present invention relates to a liquid crystal display device comprising both a display region and a drive circuit region for a drive circuit which controls the display formed on a single substrate. The liquid crystal display device according to the present invention comprises another substrate opposed to the portion of the drive circuit in order to prevent failure from occurring on the drive circuit due to external pressure or shock.

2. Prior Art

Conventionally known liquid crystal display devices include active matrix-addressed (active matrix) liquid crystal display device comprising active elements such as a thin film transistor (referred to simply hereinafter as a "TFT") on each of the pixels. Among them, there is also known an active matrix display device of a monolithic structure comprising drive circuits, which controls the signal applied to each of the pixels, provided integrated to the substrate having thereon the active elements connected to each of the pixels. The drive circuit is formed simultaneously with the fabrication of an amorphous silicon TFT for the display portion constituting the matrix, and then crystallized by selectively irradiating laser and the like to the drive circuit portion alone. In this manner, the TFTs in the drive circuit were converted into crystalline silicon TFTs.

Referring to FIGS. 1A and 1B which schematically show a device of the type described above, it can be seen a substrate 2 opposing to a substrate 1 having thereon the drive circuit is extended to cover only a display region 5 comprising a liquid crystal material 3, and no measure is taken for the drive circuit portion 6 except for covering with a resin 7 or a like material.

However, in the construction of a liquid crystal display device of a conventional type, an external force toward the drive circuit portion may easily cause damage on the drive circuit.

SUMMARY OF THE INVENTION

In the light of the aforementioned circumstances, the present invention provides a highly reliable liquid crystal electro-optical display device comprising both a display region and a drive circuit region on a single substrate, in which the drive circuit region is protected against external forces and the like.

According to one embodiment of the present invention, there is provided a liquid crystal electro-optical display device comprising a first substrate having thereon a display region and a drive circuit region comprising a drive circuit for controlling the display in said display region and a second substrate opposed to said first substrate, provided that said regions are partitioned by a sealing agent and that a liquid crystal material is incorporated between said first substrate and said second substrate opposed to the first one, wherein, said second substrate opposed to the first is extended to oppose both of said display region and said drive circuit region provided on the first substrate.

According to another embodiment of the present invention, there is provided a liquid crystal electro-optical display device comprising a first substrate having thereon a display region and a drive circuit region comprising a drive circuit for

controlling the display in said display region and a second substrate opposed to said first substrate, provided that said regions are partitioned by a sealing agent and that a liquid crystal material is incorporated between said first substrate and said second substrate opposed to the first one, wherein, said second substrate opposed to the first is extended to oppose both of said display region and said drive circuit region provided on the first substrate, and at least a part of the periphery of said drive circuit region has thereon a sealing agent.

According to a still other embodiment of the present invention, there is provided a liquid crystal electro-optical display device comprising a first substrate having thereon a display region and a drive circuit region comprising a drive circuit for controlling the display in said display region and a second substrate opposed to said first substrate, provided that said regions are partitioned by a sealing agent and that a liquid crystal material is incorporated between said first substrate and said second substrate opposed to the first one, wherein, said second substrate opposed to the first is extended to oppose both of said display region and said drive circuit region provided on the first substrate, and a resin material is charged at least between said second substrate and said drive circuit region.

According to a yet other embodiment of the present invention, there is provided a liquid crystal electro-optical display device comprising a first substrate having thereon a display region and a drive circuit region comprising a drive circuit for controlling the display in said display region and a second substrate opposed to said first substrate, provided that said regions are partitioned by a sealing agent and that a liquid crystal material is incorporated between said first substrate and said second substrate opposed to the first one, wherein, said second substrate opposed to the first is extended to oppose both of said display region and said drive circuit region provided on the first substrate, at least a part of the periphery of said drive circuit region has thereon a sealing agent, and a resin material is charged at least between said second substrate and said drive circuit region.

According to further other embodiments of the present invention, there are provided liquid crystal display devices having the constitution enumerated above, wherein, a drive circuit is formed on the second substrate at a region opposed to the drive circuit region.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1(A) and 1(B) show a schematic view of a prior art liquid crystal display device;

FIGS. 2(A) and 2(B) show a schematic view of a liquid crystal display device according to an embodiment of the present invention;

FIGS. 3(A) and 3(B) show a schematic view of a liquid crystal display device according to another embodiment of the present invention;

FIGS. 4(A), 4(B) and 4(C) show a schematic view of a liquid crystal display device according to a still other embodiment of the present invention;

FIGS. 5(A), 5(B) and 5(C) show a schematic view of a liquid crystal display device according to a yet other embodiment of the present invention; and

FIGS. 6(A), 6(B) and 6(C) show a schematic view of a liquid crystal display device according to a further other embodiment of the present invention.

DETAILED DESCRIPTION OF THE PRESENT INVENTION

As described in the foregoing, the present invention provides a liquid crystal display device comprising both a display region and a drive circuit region for a drive circuit which controls the display on a single substrate, provided that a substrate is opposed to the portion of the drive circuit in order to protect the drive circuit from external pressure and shock.

Furthermore, a resin material is charged between at least the drive circuit region and the substrate opposed thereto, thereby preventing the intrusion of moisture and the like. In this manner, a liquid crystal display device with further improved reliability can be realized.

Another drive circuit and the like can be further provided on the region of the second substrate opposed to the drive circuit region. In this manner, a multilayer-structured device having a large drive circuit region can be implemented without increasing the substrate area.

The present invention is described in further detail below referring to the preferred embodiments according to the present invention. It should be understood, however, that the present invention is not to be construed as being limited to the examples below.

EXAMPLE 1

Referring to FIG. 2(A), an amorphous silicon TFT was fabricated on a display region 12 of a Corning 7059 glass substrate 10. A crystalline silicon TFT was fabricated on a drive circuit region 13 by irradiating a laser beam to an amorphous silicon TFT for its crystallization. If necessary, the crystalline silicon TFT is covered with a passivation film made of, for example, SiN, SiO₂, PSG (phosphosilicate glass), BSG (borosilicate glass), or polyimide to construct a drive circuit. A pixel electrode and the like were formed thereafter on the display region 12 to implement a 640×480-matrix.

A sealing agent 14, more specifically, an ultraviolet-curable (referred to simply hereinafter as "UV-curable") resin in this case, was applied to a second substrate to be opposed to the first substrate above. This second substrate is capable of covering the drive circuit region of the facing first substrate, and comprises an ITO (indium tin oxide) facing electrode either on the display region alone or on the entire surface thereof. Referring to FIG. 2(B), the sealing agent 14 was applied by screen printing in such a manner that each of the display region 12 and the drive circuit region 13 may be surrounded separately. An inlet 15 for injecting the liquid crystal material must be formed to the sealing agent provided for covering the display region. The entire periphery of drive circuit region need not be surrounded by the sealing agent. Otherwise, the display region alone can be surrounded by the sealing agent while leaving the drive circuit region uncovered by the sealing agent. Furthermore, the sealing agent may contain spacers.

Thus, the first substrate 10 and the second substrate 11 opposed to the first substrate were laminated after scattering spacers on the display region of the substrate 10, and an ultraviolet radiation was irradiated thereto for curing.

A liquid crystal material 16 was injected into inside of the display region after reducing the pressure of the laminated substrates, and sealed.

FIGS. 3(A) and 3(B) illustrate a liquid crystal display device formed in such manner described above. The liquid crystal display device according to the present embodiment of the present invention was found to have far improved strength against external pressure as compared to a prior art device comprising both the display region and the drive circuit region on a single substrate but having its drive circuit covered by a resin and the like instead of providing a glass substrate opposed thereto. Thus, the drive circuit of the liquid crystal display device according to the present invention was found sufficiently protected against external force and therefore free from breakage. Moreover, the liquid crystal display device according to the present invention can be fabricated by an extremely simple process.

EXAMPLE 2

Referring to FIG. 4(A), a first substrate 10 having thereon a display region and a drive circuit region as well as a second substrate 11 having thereon a facing electrode were fabricated in the same manner as in Example 1. Then, a sealing agent 14, more specifically, a UV-curable resin in this case, was applied by screen printing to the second substrate 11 to cover the display region 12. The sealing agent may contain spacers. An inlet 15 for injecting a liquid crystal material must be provided in this step.

A resin material 17, such as a UV-curable resin or an epoxy resin, is provided to the portion to be opposed to the drive circuit region 13 by either screen printing or potting, so that the resin material can be charged sufficiently on at least the drive circuit region upon laminating the first substrate 10 and the second substrate 11 opposed thereto. The resin material may be the same as that for the sealing agent. The sealing agent and the resin may be applied not on the second substrate side, but on the first substrate side having thereon the display region and the drive circuit region.

After scattering spacers on the display region of the first substrate 10, the first substrate 10 was laminated with the second substrate 11. The sealing agent and the resin on the drive circuit region were cured thereafter.

The thus laminated substrates were placed under vacuum, and a liquid crystal material 16 was injected inside the display region and sealed.

Thus was implemented a liquid crystal display device as illustrated in FIG. 4(B). Similar to the case in Example 1, the drive circuit in this liquid crystal display device was again found protected against external force, and the device itself had excellent resistance against intrusion of moisture. Accordingly, a highly reliable liquid crystal display device was implemented by a process according to an embodiment of the present invention.

EXAMPLE 3

Referring to FIG. 5(A), a first substrate 10 having thereon a display region and a drive circuit region as well as a second substrate 11 having thereon a facing electrode were fabricated in the same manner as in Example 1. Then, a sealing agent 14, more specifically, a UV-curable resin in this case, was applied by screen printing to the second substrate 11 to cover the display region 12. The sealing agent may contain spacers. An inlet 15 for injecting a liquid crystal material must be provided in this step.

After scattering spacers on the display region of the first substrate 10, the first substrate 10 was laminated with the second substrate 11. The sealing agent was cured thereafter.

The thus laminated substrates were placed under vacuum, and a liquid crystal material **16** was injected inside the display region and sealed.

Then, a resin material (a UV-curable resin in this case) was charged in the portion between the substrates under a reduced pressure of from about 0.01 to 10 Torr, and the entire structure was placed under normal pressure or under a pressurized state. The resin material was found to intrude into the periphery of the sealing agent, and the space between the substrates corresponding to the drive circuit region **13** was charged with a resin material **17**. The resin was cured thereafter by irradiating an ultraviolet radiation.

In case two substrates of the same size are used, the resin can be mounted on both sides of the substrates. This further facilitates the fabrication process. The liquid crystal material can be injected after charging and curing the resin.

Similar to Example 2, thus was implemented a highly reliable liquid crystal display device having sufficiently high resistance against moisture. The resulting device is illustrated in FIG. 5(B).

EXAMPLE 4

Referring to FIG. 6(A), a first substrate **10** having thereon a display region and a drive circuit region as well as a second substrate **11** having thereon a facing electrode were fabricated in the same manner as in Example 1. Then, a sealing agent **14**, more specifically, a UV-curable resin in this case, was applied by screen printing to the second substrate **11** to form an inlet **15** for injecting a liquid crystal material and an inlet **18** for injecting a resin. The sealing agent may contain spacers.

After scattering spacers on the display region of the first substrate **10**, the first substrate **10** was laminated with the second substrate **11**. The sealing agent was cured thereafter.

The entire laminated substrates were placed under a reduced pressure of from about 0.01 to 10 Torr, and a liquid crystal material **16** and a resin material **17** (a UV-curable resin in this case) were injected from the inlets **15** and **18**, respectively. In this manner, the display region and the region surrounding the drive circuit can be charged with the liquid crystal material **16** and the resin material **17**, respectively. The injection can be effected simultaneously; otherwise, it can be effected separately to prevent mixing of the resin material and the liquid crystal from occurring due to evaporation during the injection.

The resulting structure was then placed under a normal pressure or a pressurized state. The resin material **17** was found to intrude into the region covered by the sealing agent to fill the space between the substrates corresponding to the drive circuit region. An ultraviolet radiation was irradiated thereafter to cure the resin.

Similar to Examples 2 and 3, thus was implemented by an extremely simple process, a highly reliable liquid crystal display device having sufficiently high resistance against moisture. The resulting device is illustrated in FIG. 6(B).

In the aforementioned embodiments, the drive circuit need not to be provided on only one substrate, but it may be fabricated on both of the substrates. The electrical connection between the drive circuits in such a case can be established by using, for example, a silver paste or an electrically conductive spacer. The liquid crystal material may be of any type, inclusive of nematic and smectic liquid crystal materials. In the attached drawings, the first and the second substrates **10** and **11** are drawn in the same size. However, the size of the substrates can be changed as desired as long as a substrate is

opposed to the drive circuit provided on the other substrate. Electrodes can be more easily connected by increasing the size of the substrate **10**.

In the examples above, special reference was made to active matrix-addressed devices using thin film transistors for the display region. However, the present invention is also applicable to device using non-linear devices such as MIM diodes as well as to simple matrix-addressed devices using simple matrix electrodes.

As described in the foregoing, the present invention provides a liquid crystal display device comprising both a display region and a drive circuit region on a single substrate, in which the drive circuit region is protected against external forces and the like. Furthermore, in case of chamfering a plurality of liquid crystal display panels from a large area substrate by applying a scribe to the laminated substrates, the drive circuit could be protected against the impact and the like which is caused by the operation of a scribe. Thus, the present invention enables production of liquid crystal display panels with high production yield.

Furthermore, in the liquid crystal display device according to the present invention, a resin material was charged between the drive circuit region and the substrate opposed thereto. In this manner, a highly reliable device was implemented by preventing the intrusion of moisture.

In the liquid crystal display device according to the present invention, another drive circuit and the like can be further provided on the region of the second substrate opposed to the drive circuit region. In this manner, a multilayer-structured device having a large drive circuit area can be implemented without increasing the substrate area.

While the invention has been described in detail and with reference to specific embodiments thereof, it will be apparent to one skilled in the art that various changes and modifications can be made therein without departing from the spirit and scope thereof.

What is claimed is:

1. A liquid crystal display device comprising:
a first substrate and a second substrate;
a display region and a first drive circuit comprising a first thin film transistor formed over the first substrate;
a second drive circuit comprising a second thin film transistor over the second substrate;
a conductive spacer electrically connecting the first and second drive circuits;
a liquid crystal material interposed between the first substrate and the second substrate;
a sealing agent formed between the first substrate and the second substrate; and
an inlet for injecting the liquid crystal material,
wherein the sealing agent surrounds the first and second drive circuits and the display region except for a portion where the inlet is provided, and

wherein the portion where the inlet is provided is located at an opposite side of the first and second drive circuits with the display region interposed therebetween.

2. A liquid crystal display device according to claim 1, wherein the first and second drive circuits and the display region are separated by the sealing agent.

3. A liquid crystal display device according to claim 1, wherein the first drive circuit is covered with a resin material.

4. A liquid crystal display device according to claim 3, wherein the resin material comprises one of an epoxy resin and an ultraviolet curable resin.

5. A liquid crystal display device according to claim 1, wherein the display region comprises an amorphous silicon transistor, and the thin film transistor is a crystalline silicon transistor.

6. A liquid crystal display device comprising:
a first substrate and a second substrate;
a display region and a first drive circuit comprising a first thin film transistor formed over the first substrate;
a second drive circuit comprising a second thin film transistor over the second substrate;
a conductive spacer electrically connecting the first and second drive circuits;
a liquid crystal material interposed between the first substrate and the second substrate;
a sealing agent formed between the first substrate and the second substrate, wherein the sealing agent comprises an ultraviolet-curable resin; and
an inlet for injecting the liquid crystal material,
wherein the sealing agent surrounds the first and second drive circuits and the display region except for a portion where the inlet is provided, and
wherein the portion where the inlet is provided is located at an opposite side of the first and second drive circuits with the display region interposed therebetween.

7. A liquid crystal display device according to claim 6, wherein the first and second drive circuits and the display region are separated by the sealing agent.

8. A liquid crystal display device according to claim 6, wherein the first drive circuit is covered with a resin material.

9. A liquid crystal display device according to claim 8, wherein the resin material comprises one of an epoxy resin and an ultraviolet curable resin.

10. A liquid crystal display device according to claim 6, wherein the display region comprises an amorphous silicon transistor, and the thin film transistor is a crystalline silicon transistor.

11. A liquid crystal display device comprising:
a first substrate and a second substrate;
a display region and a first drive circuit comprising a first thin film transistor formed over the first substrate;
a second drive circuit comprising a second thin film transistor over the second substrate;
a conductive spacer electrically connecting the first and second drive circuits;
a liquid crystal material interposed between the first substrate and the second substrate;
a sealing agent formed between the first substrate and the second substrate; and
an inlet for injecting the liquid crystal material,

5 wherein the sealing agent surrounds the first and second drive circuits and the display region except for a portion where the inlet is provided, and

wherein the display region is provided between the portion where the inlet is provided and the first and second drive circuits.

12. A liquid crystal display device according to claim 11, wherein the first and second drive circuits and the display region are separated by the sealing agent.

13. A liquid crystal display device according to claim 11, wherein the first drive circuit is covered with a resin material.

14. A liquid crystal display device according to claim 13, wherein the resin material comprises one of an epoxy resin and an ultraviolet curable resin.

15. A liquid crystal display device according to claim 11, wherein the display region comprises an amorphous silicon transistor, and the thin film transistor is a crystalline silicon transistor.

16. A liquid crystal display device comprising:
a first substrate and a second substrate;
a display region and a first drive circuit comprising a first thin film transistor formed over the first substrate;
a second drive circuit comprising a second thin film transistor over the second substrate;
a conductive spacer electrically connecting the first and second drive circuits;
a liquid crystal material interposed between the first substrate and the second substrate;
a sealing agent formed between the first substrate and the second substrate, wherein the sealing agent comprises an ultraviolet-curable resin; and
an inlet for injecting the liquid crystal material,
wherein the sealing agent surrounds the first and second drive circuits and the display region except for a portion where the inlet is provided, and
wherein the display region is provided between the portion where the inlet is provided and the first and second drive circuits.

17. A liquid crystal display device according to claim 16, wherein the first and second drive circuits and the display region are separated by the sealing agent.

18. A liquid crystal display device according to claim 16, wherein the first drive circuit is covered with a resin material.

19. A liquid crystal display device according to claim 18, wherein the resin material comprises one of an epoxy resin and an ultraviolet curable resin.

20. A liquid crystal display device according to claim 16, wherein the display region comprises an amorphous silicon transistor, and the thin film transistor is a crystalline silicon transistor.

* * * * *

专利名称(译)	液晶显示装置包括驱动电路，该驱动电路包括在两个基板上形成的薄膜晶体管		
公开(公告)号	US7525629	公开(公告)日	2009-04-28
申请号	US11/148275	申请日	2005-06-09
[标]申请(专利权)人(译)	株式会社半导体能源研究所		
申请(专利权)人(译)	半导体能源研究所有限公司.		
当前申请(专利权)人(译)	半导体能源研究所有限公司.		
[标]发明人	KONUMA TOSHIMITSU TSUJI TAKAHIRO MORIYA KOUJI		
发明人	KONUMA, TOSHIMITSU TSUJI, TAKAHIRO MORIYA, KOUJI		
IPC分类号	G02F1/1345 G02F1/1339 G02F1/1362		
CPC分类号	G02F1/1339 G02F1/13452 G02F2201/50 G02F2202/023		
审查员(译)	内尔姆斯，DAVID		
优先权	1993256571 1993-09-20 JP		
其他公开文献	US20050270438A1		
外部链接	Espacenet USPTO		

摘要(译)

一种高可靠的液晶显示装置，其中驱动电路区域受到保护，其包括其上具有显示区域的第一基板和驱动电路区域，驱动电路区域包括用于控制所述显示区域中的显示的驱动电路和与所述显示区域相对的第二基板第一基板，条件是所述区域由密封剂分隔，并且液晶材料结合在所述第一基板和与第一基板相对的所述第二基板之间，其中，与第一基板相对的所述第二基板延伸以与两者相对所述显示区域和所述驱动电路区域设置在第一基板上。

