



US 2004/0110317A1

(19) **United States**(12) **Patent Application Publication****Choo et al.**(10) **Pub. No.: US 2004/0110317 A1**(43) **Pub. Date: Jun. 10, 2004**(54) **MANUFACTURING METHOD OF LIQUID CRYSTAL DISPLAY****Publication Classification**(75) Inventors: **Dae-Ho Choo**, Yongin-city (KR); **Suk Ki**, Seoul (KR)(51) **Int. Cl.⁷** **H01L 21/00**; G02F 1/1343(52) **U.S. Cl.** **438/30**; 427/372.2; 349/153; 349/144

Correspondence Address:

McGuireWoods LLP**Tysons Corner****Suite 1800****1750 Tysons Boulevard****McLean, VA 22102-4215 (US)**

(57)

ABSTRACT(73) Assignee: **Samsung Electronics Co., Ltd.**(21) Appl. No.: **10/726,677**(22) Filed: **Dec. 4, 2003**(30) **Foreign Application Priority Data**

Dec. 4, 2002 (KR) 2002-76607

A method of manufacturing a liquid crystal display is provided, which includes: forming a sealant on a first panel; dropping liquid crystal on the first panel to form a plurality of liquid crystal dots; assembling a second panel with the first panel, wherein the first and the second panels have a striped array of pixel areas, each stripe extending in a first direction, and a first distance in the first direction between the liquid crystal dots is equal to or smaller than a second distance in a second direction perpendicular to the first direction between the liquid crystal dots.




FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 9A





FIG. 9B



MANUFACTURING METHOD OF LIQUID CRYSTAL DISPLAY

BACKGROUND OF THE INVENTION

[0001] (a) Field of the Invention

[0002] The present invention relates to a method of manufacturing a liquid crystal display.

[0003] (b) Description of the Related Art

[0004] Generally, a liquid crystal display (LCD) includes upper and lower panels provided with field-generating electrodes and a liquid crystal (LC) layer interposed therebetween. The upper and the lower panels are combined with a sealant printed along periphery thereof and enclosing the LC layer and they are spaced apart with a gap supported by a plurality of spacers.

[0005] The LCD applies voltages to the field-generating electrodes to generate an electric field in the LC layer having a dielectric anisotropy and controls the magnitude of the voltages applied to the electrodes to control the strength of the electric field, thereby controlling the transmittance of light passing through the LC layer to display images.

[0006] One of the techniques of filling the liquid crystal in the gap between the two panels is so called drop filling. The drip filling defines a filling area enclosed by a sealant having a closed-loop shape on one of the two panels and drops the liquid crystal in the filling area. The two panels are assembled in a vacuum state and the sealant is hardened. An important issue is to make the thickness of the liquid crystal kept constant without any void in the filling area of the panel for obtaining a uniform cell gap.

[0007] The uniformity of the cell gap is determined by the uniformity and the amount of a liquid crystal coated in the filling area on the panel. In order to improve the uniformity of the cell gap and to remove the voids in the liquid crystal layer as well as to match the process time in a manufacturing line, it is preferable to shorten the tact time by using one drop filling that has an advantage of filling accurate amount of the liquid crystal. It is because although each drop causes a minute deviation, the accumulation of the minute deviations for several drops causes significant errors.

[0008] However, the one drop filling has a disadvantage of the prevention of voids. The voids are mainly formed by different diffusion distances when diffusing the dropped liquid crystal. In particular, the voids are more probable to be generated near the corners of the panels. The difference in the diffusion distances is resulted from several causes such as the rectangular shapes of the panels, the difference in the materials of the diffusion surfaces, the evenness of the diffusion surfaces, existence of the sealant, and so on.

[0009] The probability of the generation of the voids depends on the characteristics of the liquid crystal and the modes of the LCD. For example, a twisted nematic (TN) mode LCD, an in-plane-switching (IPS) mode LCD, and an optically compensated birefringent (OCB) mode LCD, which employ homogeneous (or horizontal) liquid crystal alignment, has less probability of the void generation than a vertically aligned (VA) mode LCD employing homeotropic (or vertical) liquid crystal alignment. The voids generated in the display area is called AUA (active unfilled area), while the voids generated near the sealant is called SUA (surface unfilled area).

SUMMARY OF THE INVENTION

[0010] A motivation of the present invention is to reduce voids in a liquid crystal layer.

[0011] A method of manufacturing a liquid crystal display is provided, which includes: forming a sealant on a first panel; dropping liquid crystal on the first panel to form a plurality of liquid crystal dots; assembling a second panel with the first panel, wherein the first and the second panels have a striped array of pixel areas, each stripe extending in a first direction, and a first distance in the first direction between the liquid crystal dots is equal to or smaller than a second distance in a second direction perpendicular to the first direction between the liquid crystal dots.

[0012] Preferably, the first and the second distances are in a range of about 5-40 mm and an amount of one drop of the liquid crystal is in a range of about 1-15 mg.

[0013] The liquid crystal dots preferably include a plurality of first dots arranged along a plurality of straight lines, which preferably extend in the second direction such that the first dots form a plurality of dot rows.

[0014] The first dots in adjacent two of the dot rows may be arranged along a straight line extending in the first direction.

[0015] Alternatively, the first dots in adjacent two of the dot rows may be arranged offset in the first direction. Each of the first dots in one of the dot rows preferably has four equidistant nearest neighbors of the first dots in adjacent rows.

[0016] A third distance between the sealant and one of the first dots closest to the sealant may be equal to or smaller than the first distance. In this case, the liquid crystal, which preferably includes nematic liquid crystal, is preferably aligned such that long axes of molecules of the liquid crystal are substantially parallel to a surface of the first and the second panels.

[0017] Alternatively, a third distance between the sealant and one of the first dots closest to the sealant is equal to or larger than the second distance. In this case, the liquid crystal is aligned such that long axes of molecules of the liquid crystal are substantially perpendicular to a surface of the first and the second panels. The liquid crystal may include smectic liquid crystal.

[0018] According to an embodiment of the present invention, the liquid crystal dots further include a plurality of second dots disposed near a corner of the sealant.

[0019] According to another embodiment of the present invention, the liquid crystal dots further include a plurality of second dots disposed around an edge of the first panel, which are preferably smaller than the first dots. Preferably, a third distance in the second direction between one of the second dots and one of the first dots closest to the one of the second dots is equal to or larger than the second distance and equal to or smaller than a fourth distance in the first direction between one of the second dots and one of the first dots closest to the one of the second dots.

[0020] The method may further include: curing the sealant after assembling the first and the second panels. The curing of the sealant may include: light curing the sealant; and heat curing the sealant.

BRIEF DESCRIPTION OF THE DRAWINGS

[0021] FIGS. 1, 2 and 5 are sectional views of an LCD in intermediate steps of manufacturing method thereof according to an embodiment of the present invention;

[0022] FIG. 3 is a schematic plan view of an LCD according to an embodiment of the present invention; and

[0023] FIGS. 4A and 4B, 6A and 6B, 7A and 7B, 8A and 8B, and 9A and 9B show patterns of LC dots according to embodiments of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0024] The present invention now will be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. The present invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein.

[0025] In the drawings, the thickness of layers, films and regions are exaggerated for clarity. Like numerals refer to like elements throughout. It will be understood that when an element such as a layer, film, region or substrate is referred to as being "on" another element, it can be directly on the other element or intervening elements may also be present. In contrast, when an element is referred to as being "directly on" another element, there are no intervening elements present.

[0026] Now, liquid crystal displays and manufacturing methods thereof according to embodiments of the present invention will be described with reference to the accompanying drawings.

[0027] A manufacturing method of an LCD according to an embodiment of the present invention is described in detail with reference FIGS. 1-3.

[0028] FIGS. 1, 2 and 5 are sectional views of an LCD in intermediate steps of manufacturing method thereof according to an embodiment of the present invention, and FIG. 3 is a schematic plan view of an LCD according to an embodiment of the present invention.

[0029] Referring to FIG. 1, a sealant 310 is formed on a first panel 100 including a plurality of thin film transistors (TFTs), which is usually called a TFT array panel. The sealant 310 adheres a second panel 200 called a color filter (CF) array panel to the TFT array panel 100 and confines a liquid crystal therein. The sealant 310 corresponds to a periphery of the color filter array panel 200. An area enclosed by the sealant 310 is defined as an active area P.

[0030] Referring to FIG. 2, a liquid crystal is dropped in the active area P on the TFT array panel 100 to form a plurality of LC dots 330.

[0031] FIG. 3 is a schematic plan view of an LCD according to an embodiment of the present invention.

[0032] Referring to FIG. 3, a plurality of red (R), green (G) and blue (B) pixel areas 231, 232 and 233 are formed on the color filter array panel 200 of the LCD. Each of the pixel areas 231, 232 and 233 are located substantially in an area defined by a black matrix 220 and the pixel areas 231, 232 and 233 are arranged in a matrix.

[0033] Each row indicated by an X direction includes a plurality of R, G and B pixel areas 231, 232 and 233 arranged in turn. As shown in FIG. 3, a branch of the black matrix 220 is located right to an R pixel area 231 and a G pixel area 232 is disposed right to the branch of the black matrix 220. Likewise, another branch of the black matrix 220 is located right to the G pixel area 232 and a B pixel area 233 is disposed right to the another branch of the black matrix 220. Similarly, another branch of the black matrix 220 is located right to the B pixel area 233 and a R pixel area 231 is disposed right to the branch of the black matrix 220.

[0034] The pixel areas 231, 232 and 233 in each column indicated by a Y direction represent the same color, i.e., one of red, green and blue. As shown in FIG. 3, a first column includes only R pixel areas 231 interposing branches of the black matrix 220, a second column includes only G pixel areas 232, and a third column includes B pixel areas 233.

[0035] FIGS. 4A and 4B show patterns of LC dots formed in a sealant 310 according to embodiments of the present invention.

[0036] As shown in FIGS. 4A and 4B, a plurality of rows of LC dots 330a are formed on a TFT array panel 100. The distance A between adjacent LC dots 330a in each row is constant and the distance B between adjacent rows of the LC dots 330a is also constant. The distances A and B or the concentration of the LC dots 330a may be determined depending on the types of LCDs. For example, the concentration of the LC dots 330a for a homogeneously aligned liquid crystal is preferably lower than that for a homeotropically aligned liquid crystal, and the concentration of the LC dots 330a for a nematic liquid crystal, is preferably lower than that for a smectic liquid crystal, which has lower diffusivity than the nematic liquid crystal.

[0037] The distances A and B satisfy a relation $A \leq B$ since the diffusion of the LC dot 330a in X direction experiences different diffusion surfaces between R, G and B pixel areas and several protrusions and depressions such that the diffusion distance in the row direction becomes short, while the diffusion in Y direction does not. That is, the distance between the LC dots 330a in X direction where the diffusion distance is relatively short is smaller than that in Y direction where the diffusion distance is relatively long such that the diffusion of the liquid crystal is sufficient for preventing the generation of voids.

[0038] The distances A and B are preferably in a range of about 5-40 mm and they are preferably determined in consideration of the diffusion distances in X and Y directions. A distance between the LC dots 330a lower than 5 mm may not meet the process speed of an in-line LCD manufacturing equipment, and a distance larger than 40 mm may make the AUA (active unfilled area) control difficult.

[0039] Furthermore, amount of one drop for forming an LC dot is preferably in a range of about 1-15 mg. The amount of one drop less than one milligram requires increased number of the LC dots to increase the tact time. On the contrary, the amount of one drop larger than 15 milligrams increases the deviation of the LC drop amount to increase the probability of the generation of the AUA and the SUA, thereby making the cell gap control difficult.

[0040] The above-described conditions are applicable to any of a twisted nematic (TN) mode LCD, an in-plane

switching (IPS) mode LCD, and an optical compensated bend (OCB) mode LCD, as well as to a vertically-aligned (VA) mode LCD.

[0041] The LC dots **330a** shown in **FIG. 4A** form a regular matrix. Each LC dot **330a** in a row has two nearest neighbors and four next nearest neighbors in upper and lower rows.

[0042] The LC dots **133a** in adjacent rows shown in **FIG. 4B** are offset in Y direction. Preferably, the LC dots **133a** are arranged such that each LC dot **330a** in a row has four nearest neighbors in upper and lower rows. This arrangement effectively removes voids probable to be generated between the next nearest neighbors shown in **FIG. 4A**. For example, if the distance B in the arrangement shown in **FIG. 4A** is determined to be twice the diffusion distance in Y direction, the liquid crystal may not reach a place on a midpoint of a line segment connecting the next nearest neighbors such that a void may be generated there. If the distance B in the arrangement shown in **FIG. 4A** is determined to have a magnitude much larger than twice the diffusion distance in Y direction such that the above-described place on the line segment is filled with the liquid crystal, the number of the LC dots **133a** is larger than that effectively required. In particular, although the distance B is determined much larger than twice the diffusion distance in Y direction, the probability of generation of voids is increased when the diffusion surface gives higher surface tension than is expected to reduce the diffusion distance. However, the arrangement shown in **FIG. 4B**, which gives four nearest neighbors in adjacent row spaced apart by equal distances, effectively removes local voids.

[0043] Referring to **FIG. 5**, the color filter array panel **200** is attached to the TFT array panel **100** with the LC dots **133a** and the sealant **310** is UV cured to be hardened.

[0044] Furthermore, the sealant **310** may be additionally cured by heat. If the liquid crystal is in smectic phase, the smectic LC is transphased into a nematic LC having increased diffusivity by the heat. The heat curing is preferably performed at a temperature of about 120° C. for about 50 minutes.

[0045] **FIGS. 6A and 6B** show patterns of LC dots according to other embodiments of the present invention.

[0046] As shown in **FIGS. 6A and 6B**, a plurality of rows of LC dots **330a** are formed on a TFT array panel **100** such that a distance A between adjacent LC dots **330a** in a row, a distance B between adjacent rows, and a distance C between a sealant **310** and the LC dots closest thereto satisfy $C \leq A \leq B$. In other words, the concentration of the LC dots **330a** near the sealant **310** is higher than that at the other positions. The high concentration of the LC dots **330a** near the sealant **310** may remove the voids probable to be generated near the sealant **310**.

[0047] The above-described condition is determined since the LC diffusivity near the sealant **310** is reduced. This condition is preferably applicable to the LCDs having homogeneous liquid crystal alignment such as the TN mode LCD, the IPS mode LCD, and the OCB mode LCD. In this case, the concentration of the LC dots **330a** near the sealant **310** is preferably high in consideration of the affinity of the liquid crystal and the sealant **310**.

[0048] **FIGS. 7A and 7B** show patterns of LC dots according to other embodiments of the present invention.

[0049] As shown in **FIGS. 7A and 7B**, a plurality of rows of LC dots **330a** are formed on a TFT array panel **100** such that a distance A between adjacent LC dots **330a** in a row, a distance B between adjacent rows, and a distance C between a sealant **310** and the LC dots **330a** closest thereto satisfy $A \leq B \leq C$.

[0050] This condition is preferably applied to the VA mode LCD having homeotropic LC alignment or smectic liquid crystal. The homeotropically aligned liquid crystal has lower diffusivity than the homogeneously aligned liquid crystal as described above. In this case, if the concentration of the LC dots **330a** near the sealant **310** is high, the pressure applied to the sealant **310** located between the TFT array panel **100** and the color filter array panel **200** for combining the two panels **100** and **200** is required to be increased, but high pressure exerted on the sealant **310** may break the sealant **310**. Accordingly, it is preferable to reduce the concentration of the LC dots **330a** for the VA mode LCD.

[0051] **FIGS. 8A and 8B** show patterns of LC dots according to other embodiments of the present invention.

[0052] As shown in **FIGS. 8A and 8B**, a plurality of rows of inner LC dots **330a** are formed on most of an active area P of a TFT array panel **100** enclosed by a sealant **310** and a plurality of corner LC dots **330b** are formed near corners of the active area P. The corner LC dots **330b** may be larger or smaller than the inner LC dots **330a**, or may have the same size as the inner LC dots **330a**. The corner LC dots **330b** prevents the generation of voids near the corners of the active area P and around the periphery of the active area P, and, in particular, they are important for a VA mode LCD having relatively low liquid crystal diffusivity.

[0053] **FIGS. 9A and 9B** show patterns of LC dots according to other embodiments of the present invention.

[0054] As shown in **FIGS. 9A and 9B**, a plurality of rows of inner LC dots **330a** are formed on most of an active area P of a TFT array panel **100** enclosed by a sealant **310** and a plurality of edge LC dots **330c** are formed around edges of the active area P. It is preferable that the edge LC dots **330c** are larger than the inner LC dots **330a**.

[0055] The LCD dots **330a** and **330b** are arranged such that a distance A between adjacent LC dots **330a** in a row, a distance B between adjacent rows, a distance D in X direction between the leftmost edge LC dots **330c** and the leftmost inner LC dots **330a** or between the rightmost edge LC dots **330c** and the rightmost inner LC dots **330a**, and a distance E between the lowermost edge LC dots **330c** and the lowermost inner LC dots **330a** or between the uppermost edge LC dots **330c** and the uppermost inner LC dots **330a** satisfy $A \leq B \leq D \leq E$. The above-described conditions $A \leq D$ and $B \leq E$ is chosen for facilitating to press the TFT array panel **100** and a color filter array panel **200** without loss of the sealant **310** and for preventing the SUA. In addition, the above-described condition $D \leq E$ is chosen for the above-described reason for $A \leq B$, that is, since the diffusion distance in Y direction is longer than that in X direction.

[0056] The manufacturing methods according to the embodiments of the present invention reduce the probable

voids by suitable adjusting the patterns and the amounts of the LC dots, thereby obtaining uniform cell gap.

[0057] While the present invention has been described in detail with reference to the embodiments, those skilled in the art will appreciate that various modifications and substitutions can be made thereto without departing from the spirit and scope of the present invention as set forth in the appended claims.

what is claimed is:

1. A method of manufacturing a liquid crystal display, the method comprising:

forming a sealant on a first panel;

dropping liquid crystal on the first panel to form a plurality of liquid crystal dots;

assembling a second panel with the first panel,

wherein the first and the second panels have a striped array of pixel areas, each stripe extending in a first direction, and a first distance in the first direction between the liquid crystal dots is equal to or smaller than a second distance in a second direction perpendicular to the first direction between the liquid crystal dots.

2. The method of claim 1, wherein the first and the second distances are in a range of about 5-40 mm.

3. The method of claim 2, wherein an amount of one drop of the liquid crystal is in a range of about 1-15 mg.

4. The method of claim 3, wherein the liquid crystal dots comprise a plurality of first dots arranged along a plurality of straight lines.

5. The method of claim 3, wherein the straight lines extend in the second direction such that the first dots form a plurality of dot rows.

6. The method of claim 5, wherein the first dots in adjacent two of the dot rows are arranged along a straight line extending in the first direction.

7. The method of claim 5, wherein the first dots in adjacent two of the dot rows are arranged offset in the first direction.

8. The method of claim 7, wherein each of the first dots in one of the dot rows has four equidistant nearest neighbors of the first dots in adjacent rows.

9. The method of claim 5, wherein a third distance between the sealant and one of the first dots closest to the sealant is equal to or smaller than the first distance.

10. The method of claim 9, wherein the liquid crystal is aligned such that long axes of molecules of the liquid crystal are substantially parallel to a surface of the first and the second panels.

11. The method of claim 9, wherein the liquid crystal comprises nematic liquid crystal.

12. The method of claim 5, wherein a third distance between the sealant and one of the first dots closest to the sealant is equal to or larger than the second distance.

13. The method of claim 12, wherein the liquid crystal is aligned such that long axes of molecules of the liquid crystal are substantially perpendicular to a surface of the first and the second panels.

14. The method of claim 12, wherein the liquid crystal comprises smectic liquid crystal.

15. The method of claim 12, wherein the liquid crystal dots further comprises a plurality of second dots disposed near a corner of the sealant.

16. The method of claim 12, wherein the liquid crystal dots further comprises a plurality of second dots disposed around an edge of the first panel.

17. The method of claim 16, wherein the second dots are smaller than the first dots.

18. The method of claim 17, wherein a third distance in the second direction between one of the second dots and one of the first dots closest to the one of the second dots is equal to or larger than the second distance and equal to or smaller than a fourth distance in the first direction between one of the second dots and one of the first dots closest to the one of the second dots.

19. The method of claim 5, further comprising:

curing the sealant after assembling the first and the second panels.

20. The method of claim 19, wherein the curing of the sealant comprises:

light curing the sealant; and

heat curing the sealant.

* * * * *

专利名称(译)	液晶显示器的制造方法		
公开(公告)号	US20040110317A1	公开(公告)日	2004-06-10
申请号	US10/726677	申请日	2003-12-04
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	CHOO DAE HO KI SUK		
发明人	CHOO, DAE-HO KI, SUK		
IPC分类号	G02F1/13 G02F1/1341 H01L21/00 G02F1/1343		
CPC分类号	G02F2001/13415 G02F1/1341		
优先权	1020020076607 2002-12-04 KR		
其他公开文献	US7379150		
外部链接	Espacenet USPTO		

摘要(译)

提供一种制造液晶显示器的方法，包括：在第一面板上形成密封剂；将液晶滴在第一面板上以形成多个液晶点；将第二面板与第一面板组装在一起，其中第一和第二面板具有条纹阵列的像素区域，每个条带沿第一方向延伸，并且液晶点之间沿第一方向的第一距离等于或小于在液晶点之间垂直于第一方向的第二方向上的第二距离。

