





US 20070024792A1

(19) **United States**(12) **Patent Application Publication**
Chang et al.(10) **Pub. No.: US 2007/0024792 A1**(43) **Pub. Date: Feb. 1, 2007**(54) **IN-PLANE SWITCHING LIQUID CRYSTAL
DISPLAY HAVING SIMPLE STRUCTURE**(75) Inventors: **Jun Won Chang**, Yuseong-gu (KR);
Byoung Kun Jeon, Yuseong-gu (KR);
Soo Jin Jang, Seoul (KR)Correspondence Address:
MCKENNA LONG & ALDRIDGE LLP
1900 K STREET, NW
WASHINGTON, DC 20006 (US)(73) Assignee: **LG CHEM, LTD.**, Youngdeungpo-gu
(KR)(21) Appl. No.: **11/493,025**(22) Filed: **Jul. 26, 2006**(30) **Foreign Application Priority Data**

Jul. 29, 2005 (KR) 10-2005-69278

Publication Classification(51) **Int. Cl.**
G02F 1/1343 (2006.01)(52) **U.S. Cl.** **349/141**(57) **ABSTRACT**

An IPS-LCD, in which the direction of an optical axis and retardation values are adjusted according to the disposition of a phase retardation film replacing one protective film, obtains a contrast ratio similar to that of an IPS-LCD having upper and lower protective films, and has a small thickness. The IPS-LCD includes first and second polarizing plates (1, 2), an IPS panel (3), and a first protective film. Absorption axes (4, 5) of the first and second polarizing plates (1, 2) are orthogonal to each other, and an optical axis of a liquid crystal in the IPS panel (3) and the absorption axis (4) are parallel with each other. A second phase retardation film, obtained by coating a biaxial film (17) with a uniaxial C film (11), is disposed between the second polarizing plate (2) and the IPS panel (3) and is used as a second protective film.

first polarizing
plate(1)




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23

IN-PLANE SWITCHING LIQUID CRYSTAL DISPLAY HAVING SIMPLE STRUCTURE

TECHNICAL FIELD

[0001] The present invention relates to a liquid crystal display, and more particularly to an in-plane switching liquid crystal display (hereinafter, referred to as an "IPS-LCD"), which is filled with a liquid crystal having positive dielectric constant anisotropy ($\Delta\epsilon > 0$).

BACKGROUND ART

[0002] In general, LCDs are divided into an in-plane switching (IPS)-LCD, a super in-plane switching (super IPS)-LCD, and a fringe field switching (FFS)-LCD according to modes of an active matrix driving electrode including pairs of electrodes. In the present invention, IPS-LCDs include the super IPS-LDS and the FFS-LCD.

[0003] FIG. 1 illustrates the basic structure of a conventional IPS-LCD. The IPS-LCD comprises a first polarizing plate 1, a second polarizing plate 2, and an IPS panel 3. An absorption axis 4 of the first polarizing plate 1 is orthogonal to an absorption axis 5 of the second polarizing plate 2, and is parallel with an optical axis 6 of a liquid crystal in the IPS panel 3.

[0004] Polarizing films in the first and second polarizing plates 1 and 2 are very thin and stretched films, thus being easily damaged by external physical and mechanical force. Accordingly, in order to protect the polarizing films of the first and second polarizing plates 1 and 2, a protective film is essentially formed on the internal surfaces of the first and second polarizing plates 1 and 2, on which the liquid crystal is formed.

[0005] In order to compensate for the light polarization of a polarizing plate to improve visibility and increase clearness of a screen, various phase retardation films are used. That is, in order to prevent light leakage and improve a contrast ratio, various phase retardation films or optical compensating films are used.

[0006] Accordingly, the polarizing plate includes various film layers, such as a polarizing film, a protective film for protecting the polarizing film, and a phase retardation film for improving optical characteristics of the polarizing plate. These various film layers increase the thickness of the polarizing plate.

[0007] This thick polarizing plate goes against the thin profile trend of the IPS-LCD. Thus, the improvement of the thick polarizing plate has been required.

[0008] In order to satisfy the above requirement, several techniques are proposed. According to one technique, the protective film is removed from the polarizing plate and the phase retardation film serves to protect the polarizing plate.

[0009] However, when the protective film is removed from the polarizing plate and the phase retardation film serves to protect the polarizing plate, the contrast ratio of the IPS-LCD is lowered. That is, the contrast ratio refers to a ratio of the luminance of the brightest portion to the luminance of the darkest portion. The higher a difference of luminances between the brightest portion and the darkest portion is, the higher the contrast ratio is. Accordingly, in order to assure the contrast ratio, it is necessary to prevent

the light leakage at the darkest portion. When a phase retardation between the polarizing film and the phase retardation film is not properly controlled, the light leakage is severe according to viewable angles, thus causing a difficulty in assuring the contrast ratio.

[0010] Accordingly, an IPS-LCD comprising a polarizing plate, in which a phase retardation between a phase retardation film and a polarizing film is properly controlled, is required.

[0011] Particularly, the IPS-LCD has the worst contrast characteristic at a tilt angle of 75° . The improvement of the contrast characteristic of the IPS-LCD at a tilt angle of 75° means the improvement of the contrast characteristics of the IPS-LCD at all viewable angles. Thus, it is necessary to set the contrast characteristic of the IPS-LCD at tilt angle of 75° to more than a sufficient value.

[0012] For the above reason, a protective film is provided on the inner surfaces of the first and second polarizing plates of the IPS-LCD. In this case, the contrast ratio of the IPS-LCD is 10:1~45:1. Consequently, it is preferable that an LCD having a contrast ratio similar to the above range and a simple structure is developed.

DISCLOSURE

[Technical Problem]

[0013] Therefore, the present invention has been made in view of the above problems, and it is an object of the present invention to provide an IPS-LCD, in which the direction of an optical axis and retardation values are adjusted according to the disposition order of a phase retardation film even when a protective film is removed from an internal surface of one polarizing plate, thus obtaining a contrast ratio similar to that of an IPS-LCD having upper and lower protective films, and having a small thickness.

[Technical Solution]

[0014] In accordance with an aspect of the present invention, the above and other objects can be accomplished by the provision of an in-plane switching liquid crystal display (IPS-LCD) comprising a first polarizing plate, a second polarizing plate, an horizontally oriented IPS panel disposed between the first and second polarizing plates and filled with a liquid crystal having positive dielectric constant anisotropy ($\Delta\epsilon > 0$), and a first protective film disposed between the first polarizing plate and the IPS panel, in which an absorption axis of the first polarizing plate and an absorption axis of the second polarizing plate are orthogonal to each other, and an optical axis of the liquid crystal in the IPS panel and the absorption axis of the first polarizing plate are parallel with each other, wherein a second phase retardation film, obtained by coating a biaxial film with a uniaxial C film, is disposed between the second polarizing plate and the IPS panel and is used as a second protective film between the IPS panel and the second polarizing plate.

[0015] Thereby, the second phase retardation film plays an original role of increasing a viewable angle, and further serves as the protective film of the second polarizing plate. That is, it is possible to omit one protective film, thus reducing the thickness of the IPS-LCD, simplifying the structure of the IPS-LCD, and reducing the production costs of the IPS-LCD.

[0016] The IPS-LCD may further comprise a first phase retardation film including a uniaxial A film and disposed between the IPS panel and the first polarizing film.

[0017] Preferably, the first phase retardation film including the uniaxial A film has an in-plane retardation value (R_{in}) of 30~450 nm, the biaxial film of the second phase retardation film has an in-plane retardation value (R_{in}) of 50~150 nm and a thickness retardation value (R_{th}) of ~50~150 nm, and the uniaxial C film of the second phase retardation film has a thickness retardation value (R_{th}) of 50~170 nm. Here, the above retardation values denote retardation values at a wavelength of 550 nm.

[0018] In accordance with another aspect of the present invention, there is provided an in-plane switching liquid crystal display (IPS-LCD) comprising a first polarizing plate, a second polarizing plate, horizontally oriented IPS panel disposed between the first and second polarizing plates and filled with a liquid crystal having positive dielectric constant anisotropy ($\Delta\epsilon > 0$), and a first protective film disposed between the first polarizing plate and the IPS panel, in which an absorption axis of the first polarizing plate and an absorption axis of the second polarizing plate are orthogonal to each other, and an optical axis of the liquid crystal in the IPS panel and the absorption axis of the first polarizing plate are parallel with each other, wherein a second phase retardation film, obtained by coating a uniaxial A film with a uniaxial C film, is disposed between the second polarizing plate and the IPS panel and is used as a second protective film between the IPS panel and the second polarizing plate, and a first phase retardation film including a uniaxial A film is disposed between the IPS panel and the first polarizing film.

[0019] Thereby, the second phase retardation film plays an original role of increasing a viewable angle, and further serves as the protective film of the second polarizing plate. That is, it is possible to omit one protective film, thus reducing the thickness of the IPS-LCD, simplifying the structure of the IPS-LCD, and reducing the production costs of the IPS-LCD.

[0020] Preferably, the first phase retardation film including the uniaxial A film has an in-plane retardation value (R_{in}) of 30~450 nm, the uniaxial A film of the second phase retardation film has an in-plane retardation value (R_{in}) of 80~150 nm, and the uniaxial C film of the second phase retardation film has a thickness retardation value (R_{th}) of 50~170 nm. Here, the above retardation values denote retardation values at a wavelength of 550 nm.

[0021] Further, preferably, an optical axis of the first phase retardation film in the direction of the X axis is parallel with the absorption axis of the first polarizing plate.

[0022] The first protective film is preferably one film selected from the group consisting of a non-stretched zero COP film, a non-stretched zero TAC film, and a TAC film having a thickness of 50 μm and having a thickness retardation value, and more preferably a non-stretched zero TAC film. The thickness retardation value of the TAC film is 30~40 nm.

[0023] Preferably, the uniaxial A film is made of lengthwise stretched polymer, the biaxial film is made of crosswise stretched polymer, and the uniaxial C film is obtained by coating an orientation film with a liquid crystal and hardening the liquid crystal coated on the orientation film. However, the uniaxial C film may be made of a non-orientation film.

[Advantageous Effects]

[0024] The present invention provides an in-plane switching liquid crystal display (IPS-LCD), which uses a second phase retardation film exhibiting a broad viewable angle property as a protective film of one polarizing plate. The IPS-LCD of the present invention has a thin profile and a simple structure, and causes the reduction of the production costs thereof.

[0025] The conventional IPS-LCD having upper and lower protective films exhibits a contrast ratio of 10:1~45:1. On the other hand, the IPS-LCD of the present invention exhibits a contrast ratio of 25:1~55:1. Accordingly, the IPS-LCD of the present invention has a simple structure and exhibits a reasonably high contrast ratio.

DESCRIPTION OF DRAWINGS

[0026] The above and other objects, features and other advantages of the present invention will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

[0027] FIG. 1 is a schematic view illustrating the basic structure of a conventional IPS-LCD;

[0028] FIG. 2 is a view illustrating the disposition of absorption axes of two polarizing plates and an optical axis of an IPS panel of the IPS-LCD of FIG. 1;

[0029] FIG. 3 is a view illustrating the refractivities of a phase retardation film of the IPS-LCD;

[0030] FIGS. 4 to 8 are schematic views illustrating structures of IPS-LCDs, each of which has a second phase retardation film, obtained by coating a biaxial film with a uniaxial C film, between a second polarizing plate and an IPS panel, in accordance with embodiments of the present invention;

[0031] FIGS. 9 to 12 are schematic views illustrating structures of IPS-LCDs, each of which has a second phase retardation film, obtained by coating a uniaxial A film with a uniaxial C film, between a second polarizing plate and an IPS panel, in accordance with other embodiments of the present invention;

[0032] FIGS. 13A and 13B are views illustrating viewable angle characteristics of the IPS-LCDs in accordance with the first and second embodiments, as shown in FIGS. 4 and 5;

[0033] FIGS. 14A and 14B are views illustrating viewable angle characteristics of the IPS-LCDs in accordance with the third and fourth embodiments, as shown in FIGS. 6 and 7;

[0034] FIGS. 15A and 15B are views illustrating viewable angle characteristics of the IPS-LCDs in accordance with the fifth and sixth embodiments, as shown in FIGS. 8 and 9;

[0035] FIGS. 16A to 16C are views illustrating viewable angle characteristics of the IPS-LCDs in accordance with the seventh to ninth embodiments, as shown in FIGS. 10 to 12;

[0036] FIG. 17 is a view illustrating a structure of an IPS-LCD, which uses a zero COP film or a zero TAC film as an internal protective film of a first polarizing plate, and has a second phase retardation film, obtained by coating a biaxial film with a uniaxial C film, in accordance with a tenth embodiment of the present invention;

[0037] FIG. 18 is a view illustrating a structure of an IPS-LCD, which has the same structure as that of the IPS-LCD of FIG. 17 and uses a TAC film having a thickness

retardation value of $-30\sim-40$ nm as an internal protective film of a first polarizing plate, in accordance with an eleventh embodiment of the present invention;

[0038] FIG. 19 is a view illustrating a structure of an IPS-LSCD, which has the same structure as that of the IPS-LCD of FIG. 17 and uses a general TAC film having a thickness retardation value of $-55\sim-65$ nm as an internal protective film of a first polarizing plate, in accordance with a twelfth embodiment of the present invention;

[0039] FIG. 20 is a view illustrating a structure of an IPS-LSCD, which has the same structure as that of the IPS-LCD of FIG. 17 except that an optical axis of a second internal protective film and an absorption axis of a second polarizing plate are parallel with each other, in accordance with a thirteenth embodiment of the present invention;

[0040] FIG. 21 is a view illustrating a structure of an IPS-LSCD, which has the same structure as that of the IPS-LCD of FIG. 17 except that retardation values of a biaxial film and a C film of a second internal protective film deviate from the range regulated by the present invention, in accordance with a fourteenth embodiment of the present invention;

[0041] FIG. 22 is a view illustrating a structure of an IPS-LSCD, which has a uniaxial A film, interposed between an internal protective film of a first polarizing plate and an IPS panel, and a second internal protective film including a uniaxial A film and a uniaxial C film, which are sequentially stacked, in accordance with a fifth embodiment of the present invention; and

[0042] FIGS. 23A to 23F are views illustrating distributions of contrast ratios of the IPS-LCDs, as shown in FIGS. 17 to 22.

MODE FOR INVENTION

[0043] Now, preferred embodiments of the present invention will be described in detail with reference to the annexed drawings.

[0044] FIG. 2 illustrates an absorption axis 6 of a liquid crystal in an IPS panel 3 and absorption axes 4 and 5 two polarizing plates 1 and 2. The absorption axis 4 of the first polarizing plate 1 is orthogonal to the absorption axis 5 of the second polarizing plate 2, and is parallel with the optical axis 6 of the liquid crystal in the IPS panel 6.

[0045] With reference to FIGS. 1 and 2, the FPS panel 3 interposed between two polarizing plates 1 and 2, the absorption axes 4 and 5 of which are orthogonal to each other, comprises liquid molecules 7, which are disposed in parallel with first and second substrates 20 and 21 and arranged in the direction of rubbing (a method for treating the surface of the panel for arranging the liquid crystal modules in one direction). When the absorption axis of the polarizing plate adjacent to a backlighting and the rubbing direction are parallel with each other, the IPS-LCD is referred to as an "O-mode IPS-LCD", and when the absorption axis of the polarizing plate adjacent to the backlighting and the rubbing direction are orthogonal to each other, the IPS-LCD is referred to as an "E-mode IPS-LCD".

[0046] FIG. 3 is a view illustrating the refractivities of a phase retardation film for compensating for the viewable angle of the IPS-LCD. n_x represents the refractivity 8 of the phase retardation film in the direction of the X-axis, n_y represents the refractivity 9 of the phase retardation film in the direction of the Y-axis, and n_z represents the refractivity

10 of the phase retardation film in the direction of the Z-axis. The characteristics of the phase retardation film are determined by the degrees of the refractivities. A phase retardation film, in which the refractivities in the directions of the two axes are different, is referred to as a uniaxial phase retardation film, and a phase retardation film, in which the refractivities in the directions of the three axes are different, is referred to as a biaxial phase retardation film.

[0047] The uniaxial phase retardation film and the biaxial phase retardation film are defined as below equations.

[0048] (1) When a phase retardation film satisfies the expression of $n_x > n_y = n_z$, the phase retardation film is referred to as a uniaxial A film, and an in-plane retardation value is defined using a difference ($n_x - n_y$) between two refractivities located on a plane and a thickness (d) of the film by the below equation 1.

$$Rin = d \times (n_x - n_y) \quad [\text{Equation 1}]$$

[0049] (2) When a phase retardation film satisfies the expression of $n_x = n_y < n_z$, the phase retardation film is referred to as a uniaxial C film, and a thickness retardation value is defined using a difference ($n_z - n_y$) between the refractivity located on a plane and the refractivity in the thickness direction and a thickness (d) of the film by the below equation 2.

$$Rth = d \times (n_z - n_y) \quad [\text{Equation 2}]$$

[0050] (3) When a phase retardation film satisfies the expression of $n_x > n_y > n_z$, the phase retardation film is referred to as a negative biaxial phase retardation film (hereinafter, referred to as a "biaxial phase retardation film"). Since the refractivities in the directions of the three axes are different, the biaxial phase retardation film has an in-plane retardation value and a thickness retardation value, which are defined by the above equations 1 and 2, respectively.

[0051] The retardation values are affected by the wavelength of light to be used. The wavelength of light is 550 nm except being specially defined.

[0052] FIGS. 4 to 8 illustrate structures of IPS-LCDs, each of which has a second phase retardation film, obtained by coating a biaxial film 17 with a uniaxial C film 11, between a second polarizing plate 2 and an IPS-panel 3, in accordance with embodiments of the present invention. Further, FIGS. 9 to 12 illustrate structures of IPS-LCDs, each of which has a second phase retardation film, obtained by coating a uniaxial A film 14 with a uniaxial C film 11, between a second polarizing plate 2 and an IPS-panel 3, in accordance with other embodiments of the present invention.

[0053] Each of the IPS-LCDs, shown in FIGS. 4 to 12, comprises a protective film, for protecting a polarizing device made of stretched polyvinyl alcohol, on the internal surface of a first polarizing plate 1. The protective film is made of TAC (triacetate cellulose) of a thickness of 50 μ m having a thickness retardation value, biaxial COP (cycloolefin) simultaneously having an in-plane retardation value and a thickness retardation value, TAC without a thickness retardation value (hereinafter, referred to as "zero TAC"), or COP without a thickness retardation value (hereinafter, referred to as "zero COP").

[0054] Preferably, the uniaxial A films 12 and 14 are made of lengthwise stretched polymer, the biaxial film 17 is made of crosswise stretched polymer, and the uniaxial C film 11 is obtained by coating an orientation film with a liquid crystal and hardening the liquid crystal coated on the orientation film.

[0055] Here, the stacking structures of the IPS-LCDs of FIGS. 4 and 5 and the structures of the IPS-LCDs of FIGS. 6 and 7 are the same except that the positions of an observer and a backlighting 19 are reversed. As described above, when the absorption axis of the polarizing plate adjacent to the backlighting 19 and the rubbing direction are parallel with each other, the IPS-LCD is referred to as an "O-mode IPS-LCD", and when the absorption axis of the polarizing plate adjacent to the backlighting 19 and the rubbing direction are orthogonal to each other, the IPS-LCD is referred to as an "E-mode IPS-LCD". The IPS-LCDs, as shown in FIGS. 4, 6, 8, 9, and 11, are O-mode IPS-LCDs, and the IPS-LCDs, as shown in FIGS. 5, 7, 10, and 12 are E-mode IPS-LCDs. The IPS-LCDs of FIGS. 4 and 5, the IPS-LCDs of FIGS. 6 and 7, the IPS-LCDs of FIGS. 9 and 10, and the IPS-LCDs of FIGS. 11 and 12 have the same structure except that one IPS-LCD is an O-mode IPS-LCD and the other IPS-LCD is an E-mode IPS-LCD, and will be thus described simultaneously.

[0056] FIGS. 4 and 5 illustrate structures of IPS-LCDs, each of which has a phase retardation film, in accordance with first and second embodiments of the present invention. Here, the optical axis 18 of the biaxial film 17 is orthogonal to the absorption axis 5 of the second polarizing plate 2, and is located at a position adjacent to the second polarizing plate 2. Further, the uniaxial C film 11 is located at a position adjacent to the IPS-panel 3.

[0057] FIGS. 6 and 7 illustrate structures of IPS-LCDs, each of which has a phase retardation film, in accordance with third and fourth embodiments of the present invention. Here, the optical axis 18 of the biaxial film 17 is parallel with the absorption axis 5 of the second polarizing plate 2, and is located at a position adjacent to the IPS-panel 3. Further, the uniaxial C film 11 is located at a position adjacent to the second polarizing plate 2.

[0058] FIG. 8 illustrates a structure of an IPS-LCD, which has a phase retardation film, in accordance with a fifth embodiment of the present invention. Here, the optical axis 18 of the biaxial film 17 and the optical axis 13 of the uniaxial A film 12 are orthogonal to the absorption axis 5 of the second polarizing plate 2. The uniaxial C film 11 is located at a position adjacent to the second polarizing plate 2, and the biaxial film 17 is located at a position adjacent to the IPS-panel 3. Further, the uniaxial A film 12 is located between the first polarizing plate 1 and the IPS-panel 3.

[0059] FIGS. 9 and 10 illustrate structures of IPS-LCDs, each of which has a phase retardation film, in accordance with sixth and seventh embodiments of the present invention. Here, the optical axis 13 of one uniaxial A film 12 adjacent to the first polarizing plate 1 is orthogonal to the absorption axis 5 of the second polarizing plate 2, and the optical axis 15 of the other uniaxial A film 14 is parallel with the absorption axis 5 of the second polarizing plate 2. The uniaxial C film 11 is located at a position adjacent to the second polarizing plate 2, and the uniaxial A film 14 is

located at position adjacent to the IPS-panel 3. Further, the uniaxial A film 12 is located between the first polarizing plate 1 and the IPS-panel 3.

[0060] FIGS. 11 and 12 illustrate structures of IPS-LCDs, each of which has a phase retardation film, in accordance with eighth and ninth embodiments of the present invention. Here, the optical axis 13 of one uniaxial A film 12 adjacent to the first polarizing plate 1 and the optical axis 15 of the other uniaxial A film 14 adjacent to the second polarizing plate 2 are orthogonal to the absorption axis 5 of the second polarizing plate 2. The uniaxial A film 14 is located at position adjacent to the second polarizing plate 2, and the uniaxial C film 11 is located at a position adjacent to the IPS-panel 3. Further, the uniaxial A film 12 is located between the first polarizing plate 1 and the IPS-panel 3.

Embodiments

[0061] Each of the IPS-LCDs in accordance with all the below embodiments of the present invention comprises an IPS panel including liquid crystal cells, which have a cell interval of 3.3 μm and are filled with a liquid crystal having a pretilt angle of 1.4°, dielectric constant anisotropy ($\Delta\epsilon=+7$), and birefringence ($\Delta n=0.1$) at a wavelength of 550 nm.

[0062] First, in order to determine whether or not the IPS-LCDs have a proper contrast ratio when an internal protective film is replaced with a phase retardation film, polarizing plates were manufactured by methods stated in the first to ninth embodiments of the present invention, and results were obtained by simulation.

First Embodiment

[0063] In the IPS-LCD of the first embodiment, as shown in FIG. 4, the internal protective film of the first polarizing plate 1 was made of zero COP or zero TAC. The internal protective film of the second polarizing plate 2 was replaced with a phase retardation film obtained by coating the upper surface of the biaxial film 17, which has a thickness of 80 μm , an in-plane retardation value (R_{in}) of 90 nm, and a thickness retardation value (R_{th}) of -75 nm, with the C film 11, which has a thickness retardation value (R_{th}) of 140 nm. When the above obtained phase retardation film and the polarizing plates 1 and 2 were applied to an IPS-LCD, the simulated minimum contrast ratios of a tilt angle of 75° to all azimuthal angles in the IPS-LCD were 45:1.

[0064] FIG. 13A illustrates contrast characteristics of tilt angles of 0~80° to all azimuthal angles under the above conditions. Here, the center of a circle represents contrast characteristics at a tilt angle of 0°, and the circumference of the circle represents contrast characteristics at a tilt angle of 80°. The larger the radius of the circle is, the larger the tilt angle is. Values 0~330, which are written along the circumference of the circle, denote azimuthal angles.

[0065] Below Table 1 states simulated results showing viewable angle characteristics at a tilt angle of 75° according to retardation values of the internal protective film and the phase retardation film in the structure of the IPS-LCD of the first embodiment.

TABLE 1

Internal protective film of 1 st polarizing plate	IPS-LCD	Retardation value of C film	Retardation value of B film	Internal protective film of 2 nd polarizing plate	Minimum contrast ratio
Zero COP or zero TAC film	330 nm	Rth = 50 nm Rth = 60 nm Rth = 80 nm Rth = 100 nm Rth = 126 nm Rth = 50 nm Rth = 80 nm Rth = 110 nm Rth = 132 nm Rth = 35 nm Rth = 60 nm Rth = 100 nm Rth = 140 nm	Rin = 90 nm, Rth = -50 nm Rin = 90 nm, Rth = -70 nm Rin = 90 nm, Rth = -100 nm Rin = 90 nm, Rth = -120 nm Rin = 90 nm, Rth = -150 nm Rin = 70 nm, Rth = -50 nm Rin = 70 nm, Rth = -90 nm Rin = 70 nm, Rth = -120 nm Rin = 70 nm, Rth = -150 nm Rin = 110 nm, Rth = -50 nm Rin = 110 nm, Rth = -80 nm Rin = 110 nm, Rth = -130 nm Rin = 90 nm, Rth = -75 nm	B film + C film	45:1

Second Embodiment

[0066] In the IPS-LCD of the second embodiment, as shown in FIG. 5, the internal protective film of the first polarizing plate 1 and the internal protective film of the second polarizing plate 2 were the same as those of the first embodiment, but have retardation values different from those of the first embodiment. That is, in the IPS-LCD of the second embodiment, as shown in FIG. 5, the internal protective film of the first polarizing plate 1 was made of zero COP or zero TAC. The internal protective film of the second polarizing plate 2 was replaced with a phase retardation film obtained by coating the upper surface of the biaxial film 17, which has a thickness of 100 μm , an in-plane retardation value (Rin) of 90 nm, and a thickness retardation value (Rth) of -100 nm, with the C film 11, which has a thickness retardation value (Rth) of 115 nm. When this phase retardation film and the polarizing plates 1 and 2 were applied to an IPS-LCD, the simulated minimum contrast ratios of a tilt angle of 75° to all azimuthal angles in the IPS-LCD were 40:1.

[0067] FIG. 13B illustrates contrast characteristics of tilt angles of 0-80° to all azimuthal angles under the above conditions.

[0068] Below Table 2 states simulated results showing viewable angle characteristics at a tilt angle of 75° according to retardation values of the internal protective film and the phase retardation film in the structure of the IPS-LCD of the second embodiment.

Third Embodiment

[0069] In the IPS-LCD of the third embodiment, as shown in FIG. 6, the internal protective film of the first polarizing plate 1 was a zero COP film or a zero TAC film. The internal protective film of the second polarizing plate 2 was replaced with a phase retardation film obtained by coating the upper surface of the biaxial film 17, which has a thickness of 80 μm , an in-plane retardation value (Rin) of 90 nm, and a thickness retardation value (Rth) of -75 nm, with the C film 11, which has a thickness retardation value (Rth) of 130 nm. When the above obtained phase retardation film and the polarizing plates 1 and 2 were applied to an IPS-LCD, the simulated minimum contrast ratios of a tilt angle of 75° to all azimuthal angles in the IPS-LCD were 35:1-45:1. After the upper surface of the biaxial phase retardation film 17 is coated with the C film 11, a film made of zero TAC without a retardation value may be additionally stacked thereon. The IPS-LCD of this embodiment differs from the conventional IPS-LCD using TAC having a retardation value in that the EPS-LCD of this embodiment uses zero TAC without a retardation value. The contrast ratio of the IPS-LCD having the phase retardation film of the second polarizing plate, which includes the film made of zero TAC, is the same as the IPS-LCD having the phase retardation film of the second polarizing plate, which does not include the film made of zero TAC (The film made of zero TAC is applied to third to seventh embodiments).

TABLE 2

Internal protective film of 1 st polarizing plate	IPS-LCD	Retardation value of C film	Retardation value of B film	Internal protective film of 2 nd polarizing plate	Minimum contrast ratio
Zero COP or zero TAC film	330 nm	Rth = 115 nm Rth = 130 nm Rth = 160 nm Rth = 130 nm Rth = 160 nm Rth = 140 nm	Rin = 90 nm, Rth = -100 nm Rin = 90 nm, Rth = -120 nm Rin = 90 nm, Rth = -150 nm Rin = 70 nm, Rth = -120 nm Rin = 70 nm, Rth = -150 nm Rin = 110 nm, Rth = -130 nm	B film + C film	40:1

[0070] FIG. 14A illustrates contrast characteristics of tilt angles of 0~80° to all azimuthal angles under the above conditions.

[0071] Below Table 3 states simulated results showing viewable angle characteristics at a tilt angle of 75° according to retardation values of the internal protective film and the phase retardation film in the structure of the IPS-LCD of the third embodiment.

second polarizing plate 2 was replaced with a phase retardation film obtained by coating the upper surface of the biaxial film 17, which has a thickness of 100 μm, an in-plane retardation value (Rin) of 90 nm, and a thickness retardation value (Rth) of -150 nm, with the C film 11, which has a thickness retardation value (Rth) of 150 nm. When this phase retardation film and the polarizing plates 1 and 2 were applied to an IPS-LCD, the simulated minimum contrast

TABLE 3

Internal protective film of 1 st polarizing plate	IPS-LCD	Retardation value of B film	Retardation value of C film	Internal protective film of 2 nd polarizing plate	Minimum contrast ratio
TAC film having thickness of 50 μm	330 nm	Rin = 70 nm, Rth = -90 nm Rin = 70 nm, Rth = -120 nm Rin = 90 nm, Rth = -100 nm Rin = 90 nm, Rth = -120 nm Rin = 90 nm, Rth = -150 nm Rin = 110 nm, Rth = -80 nm Rin = 110 nm, Rth = -120 nm Rin = 110 nm, Rth = -150 nm	Rth = 66 nm Rth = 90 nm Rth = 70 nm Rth = 80 nm Rth = 110 nm Rth = 45 nm Rth = 70 nm Rth = 100 nm	B film + C film (+zero TAC film)	35:1
Zero COP or zero TAC film		Rin = 110 nm, Rth = -150 nm Rin = 110 nm, Rth = -120 nm Rin = 110 nm, Rth = -80 nm Rin = 90 nm, Rth = -150 nm Rin = 90 nm, Rth = -120 nm Rin = 90 nm, Rth = -50 nm Rin = 70 nm, Rth = -90 nm Rin = 90 nm, Rth = -75 nm	Rth = 125 nm Rth = 100 nm Rth = 70 nm Rth = 132 nm Rth = 110 nm Rth = 55 nm Rth = 90 nm Rth = 130 nm		45:1

Fourth Embodiment

[0072] In the IPS-LCD of the fourth embodiment, as shown in FIG. 7, the internal protective film of the first polarizing plate 1 and the internal protective film of the second polarizing plate 2 were the same as those of the third embodiment, but have retardation values different from those of the third embodiment. That is, in the IPS-LCD of the fourth embodiment, as shown in FIG. 7, the internal protective film of the first polarizing plate 1 was a zero COP film or a zero TAC film. The internal protective film of the

ratios of a tilt angle of 75° to all azimuthal angles in the IPS-LCD were 25:1~30:1.

[0073] FIG. 14B illustrates contrast characteristics of tilt angles of 0~80° to all azimuthal angles under the above conditions.

[0074] Below Table 4 states simulated results showing viewable angle characteristics at a tilt angle of 75° according to retardation values of the internal protective film and the phase retardation film in the structure of the IPS-LCD of the fourth embodiment.

TABLE 4

Internal protective film of 1 st polarizing plate	IPS-LCD	Retardation value of B film	Retardation value of C film	Internal protective film of 2 nd polarizing plate	Minimum contrast ratio
TAC film having thickness of 50 μm	330 nm	Rin = 90 nm, Rth = -150 nm Rin = 110 nm, Rth = -150 nm	Rth = 150 nm Rth = 100 nm	B film + C film (+zero TAC film)	25:1
Zero COP or zero TAC film		Rin = 110 nm, Rth = -150 nm Rin = 110 nm, Rth = -120 nm Rin = 90 nm, Rth = -150 nm Rin = 90 nm, Rth = -150 nm	Rth = 140 nm Rth = 120 nm Rth = 140 nm Rth = 150 nm		30:1

Fifth Embodiment

[0075] In the IPS-LCD of the fifth embodiment, as shown in FIG. 8, the biaxial film 17 was made of stretched COP, which has an in-plane retardation value (Rin) of 90 nm and a thickness retardation value (Rth(550 nm)) of -75 nm. The internal protective film of the first polarizing plate 1 was a zero COP film or a zero TAC film. An A film 13, which has a thickness of 100 μ m and in-plane retardation value(Rin) of 70 nm, is inserted between the first polarizing plate 1 and IPS panel 3. The internal protective film of the second polarizing plate 2 was replaced with a phase retardation film obtained by coating the upper surface the biaxial film 17 with the C film 11, which has a thickness retardation value (Rth) of 110 nm. When the above obtained phase retardation film and the polarizing plates 1 and 2 were applied to an IPS-LCD, the simulated minimum contrast ratios of a tilt angle of 75° to all azimuthal angles in the IPS-LCD were 48:1~52:1. After the upper surface of the biaxial film 17 is coated with the C film 11, a film made of zero TAC without a retardation value may be additionally stacked thereon.

[0076] FIG. 15A illustrates contrast characteristics of tilt angles of 0~80° to all azimuthal angles under the above conditions.

[0077] Below Table 5 states simulated results showing viewable angle characteristics at a tilt angle of 75° according to retardation values of the internal protective film and the phase retardation film in the structure of the IPS-LCD of the fifth embodiment.

Sixth Embodiment

[0078] In the EPS-LCD of the sixth embodiment, as shown in FIG. 9, the uniaxial A film 12 adjacent to the first polarizing plate 1 was made of stretched COP, which has an in-plane retardation value (Rin) of 160 nm, and the uniaxial A film 14 adjacent to the second polarizing plate 2 was made of stretched COP, which has an in-plane retardation value (Rin) of 130 nm. The internal protective film of the first polarizing plate 1 was a TAC film, which has a thickness of 50 μ m and a thickness retardation value (Rth) of -32 nm. The internal protective film of the second polarizing plate 2 was replaced with a phase retardation film obtained by coating the upper surface of the uniaxial A film 14 with the C film 11, which has a thickness retardation value (Rth) of 110 nm. When the above phase retardation film and the polarizing plates 1 and 2 were applied to an IPS-LCD, the simulated minimum contrast ratios of a tilt angle of 75° to all azimuthal angles in the IPS-LCD were 45:1~55:1. A film made of zero TAC without a retardation value may be additionally stacked on the second polarizing plate 2.

[0079] FIG. 15B illustrates contrast characteristics of tilt angles of 0~80° to all azimuthal angles under the above conditions.

[0080] Below Table 6 states simulated results showing viewable angle characteristics at a tilt angle of 75° according to retardation values of the internal protective film and the phase retardation film in the structure of the IPS-LCD of the sixth embodiment.

TABLE 5

Internal protective film of 1 st polarizing plate	Retardation value of A film (1 st polarizing plate side)		IPS-LCD	Retardation value of B film	Retardation value of C film	Internal protective film of 2 nd polarizing plate	Minimum contrast ratio
	Rin	Rth					
TAC film having thickness of 50 μ m	Rin = 100 nm	Rth = -75 nm	330 nm	Rin = 70 nm, Rth = -90 nm	Rth = 80 nm	B film + C film (+zero TAC film)	48:1
	Rin = 90 nm	Rth = -120 nm		Rin = 70 nm, Rth = -120 nm	Rth = 100 nm		
	Rin = 120 nm	Rth = -100 nm		Rin = 90 nm, Rth = -100 nm	Rth = 50 nm		
	Rin = 100 nm	Rth = -120 nm		Rin = 90 nm, Rth = -120 nm	Rth = 90 nm		
	Rin = 70 nm	Rth = -150 nm		Rin = 90 nm, Rth = -150 nm	Rth = 110 nm		
	Rin = 150 nm	Rth = -80 nm		Rin = 110 nm, Rth = -80 nm	Rth = 55 nm		
	Rin = 100 nm	Rth = -120 nm		Rin = 110 nm, Rth = -120 nm	Rth = 70 nm		
	Rin = 230 nm	Rth = -150 nm		Rin = 110 nm, Rth = -150 nm	Rth = 130 nm		
Zero COP or zero TAC film	Rin = 90 nm	Rth = -150 nm		Rin = 110 nm, Rth = -150 nm	Rth = 125 nm		52:1
	Rin = 70 nm	Rth = -120 nm		Rin = 110 nm, Rth = -120 nm	Rth = 100 nm		
	Rin = 80 nm	Rth = -80 nm		Rin = 110 nm, Rth = -80 nm	Rth = 70 nm		
	Rin = 50 nm	Rth = -150 nm		Rin = 90 nm, Rth = -150 nm	Rth = 132 nm		
	Rin = 50 nm	Rth = -120 nm		Rin = 90 nm, Rth = -120 nm	Rth = 110 nm		
	Rin = 40 nm	Rth = -90 nm		Rin = 70 nm, Rth = -90 nm	Rth = 90 nm		
	Rin = 70 nm	Rth = -75 nm		Rin = 90 nm, Rth = -75 nm	Rth = 110 nm		

TABLE 6

	Retardation			Internal			
Internal	value of A					Internal	
protective	film					protective	
film of 1 st	(1 st					film of 2 nd	Minimum
polarizing	polarizing		Retardation	Retardation		polarizing	contrast
plate	plate side)	IPS-LCD	value of A film	value of C film		plate	ratio
TAC film	Rin = 100 nm	330 nm	Rin = 110 nm	Rth = 66 nm	A film + C	film (+zero TAC film)	45:1
having	Rin = 80 nm		Rin = 120 nm	Rth = 55 nm			
thickness of	Rin = 160 nm		Rin = 130 nm	Rth = 100 nm			
50 μm	Rin = 180 nm		Rin = 140 nm	Rth = 88 nm			
	Rin = 100 nm		Rin = 90 nm	Rth = 77 nm			
	Rin = 160 nm		Rin = 130 nm	Rth = 110 nm			
Zero COP or	Rin = 50 nm		Rin = 110 nm	Rth = 88 nm			55:1
zero TAC	Rin = 100 nm		Rin = 130 nm	Rth = 100 nm			
film	Rin = 200 nm		Rin = 150 nm	Rth = 100 nm			

Seventh Embodiment

[0081] In the IPS-LCD of the seventh embodiment, as shown in FIG. 10, the uniaxial A film 12 adjacent to the first polarizing plate 1 was made of stretched COP, which has an in-plane retardation value (Rin) of 160 nm, and the uniaxial A film 14 adjacent to the second polarizing plate 2 was made of stretched COP, which has an in-plane retardation value (Rin(550 nm)) of 130 nm. The internal protective film of the first polarizing plate 1 was a TAC film, which has a thickness of 50 μ m and a thickness retardation value (Rth) of -32 nm. The internal protective film of the second polarizing plate 2 was replaced with a phase retardation film obtained by coating the upper surface of the uniaxial A film 14 with the C film 11, which has a thickness retardation value (Rth) of 110 nm. When the above obtained phase retardation film and

the polarizing plates 1 and 2 were applied to an IPS-LCD, the simulated minimum contrast ratios of a tilt angle of 75° to all azimuthal angles in the IPS-LCD were 40:1~48:1. A film made of zero TAC without a retardation value may be additionally stacked on the second polarizing plate 2.

[0082] FIG. 16A illustrates contrast characteristics of tilt angles of 0~80° to all azimuthal angles under the above conditions.

[0083] Below Table 7 states simulated results showing viewable angle characteristics at a tilt angle of 75° according to retardation values of the internal protective film and the phase retardation film in the structure of the IPS-LCD of the seventh embodiment.

TABLE 7

	Retardation					
Internal	value of A				Internal	
protective	film				protective	
film of 1 st	(1 st				film of 2 nd	Minimum
polarizing	polarizing		Retardation	Retardation	polarizing	contrast
plate	plate side)	IPS-LCD	value of A film	value of C film	plate	ratio
TAC film	Rin = 240 nm	300 nm	Rin = 140 nm	Rth = 110 nm	A film + C	40:1
having	Rin = 240 nm		Rin = 130 nm	Rth = 120 nm	film (+zero	
thickness of	Rin = 220 nm		Rin = 120 nm	Rth = 100 nm	TAC film)	
50 μm	Rin = 200 nm		Rin = 110 nm	Rth = 100 nm		
	Rin = 180 nm		Rin = 90 nm	Rth = 100 nm		
	Rin = 160 nm		Rin = 130 nm	Rth = 110 nm		
Zero COP	Rin = 30 nm		Rin = 110 nm	Rth = 90 nm		48:1
or zero TAC	Rin = 30 nm		Rin = 130 nm	Rth = 110 nm		
film						

Eighth Embodiment

[0084] In the IPS-LCD of the eighth embodiment, as shown in FIG. 11, the uniaxial A film 12 adjacent to the first polarizing plate 1 was made of stretched COP, which has an in-plane retardation value (Rin(550 nm)) of 150 nm, and the uniaxial A film 14 adjacent to the second polarizing plate 2 was made of stretched COP, which has an in-plane retardation value (Rin(550 nm)) of 150 nm. The internal protective film of the first polarizing plate 1 was a zero COP film or a zero TAC film. The internal protective film of the second polarizing plate 2 was replaced with a phase retardation film obtained by coating the uniaxial A film 14 with the C film 11 having thickness retardation value of 110 nm. When the above obtained phase retardation film and the polarizing plates 1 and 2 were applied to an IPS-LCD, the simulated minimum contrast ratios of a tilt angle of 75° to all azimuthal angles in the IPS-LCD were 32:1~38:1.

[0085] FIG. 16B illustrates contrast characteristics of tilt angles of 0~80° to all azimuthal angles under the above conditions.

[0086] Below Table 8 states simulated results showing viewable angle characteristics at a tilt angle of 75° according to retardation values of the internal protective film and the phase retardation film in the structure of the IPS-LCD of the eighth embodiment.

TABLE 8

Internal protective film of 1 st polarizing plate	Retardation value of A film (1 st polarizing plate side)	IPS-LCD	Retardation value of C film	Retardation value of A film	Internal protective film of 2 nd polarizing plate	Minimum contrast ratio
Zero COP or zero TAC film	Rin = 160 nm Rin = 150 nm	330 nm	Rth = 90 nm Rth = 110 nm	Rin = 150 nm Rin = 150 nm	A film + C film (+zero TAC)	38:1
TAC film having thickness of 50 μm	Rin = 150 nm		Rth = 100 nm	Rin = 120 nm		32:1

Ninth Embodiment

[0087] In the IPS-LCD of the ninth embodiment, as shown in FIG. 12, the uniaxial A film 12 adjacent to the first polarizing plate 1 was made of stretched COP, which has an in-plane retardation value (Rin(550 nm)) of 140 nm, and the uniaxial A film 14 adjacent to the second polarizing plate 2 was made of stretched COP, which has an in-plane retardation value (Rin(550 nm)) of 110 nm. The internal protective film of the first polarizing plate 1 was a TAC film, which has a thickness of 50 μm and a thickness retardation value (Rth) of -32 nm. The internal protective film of the second polarizing plate 2 was replaced with a phase retardation film obtained by coating the uniaxial A film 14 with the C film 11 having thickness retardation value of 100 nm. When the above obtained phase retardation film and the polarizing plates 1 and 2 were applied to an IPS-LCD, the simulated minimum contrast ratios of a tilt angle of 75° to all azimuthal angles in the IPS-LCD were 25:1~30:1.

[0088] FIG. 16C illustrates contrast characteristics of tilt angles of 0~80° to all azimuthal angles under the above conditions.

[0089] Below Table 9 states simulated results showing viewable angle characteristics at a tilt angle of 75° according to retardation values of the internal protective film and the phase retardation film in the structure of the IPS-LCD of the ninth embodiment.

TABLE 9

Internal protective film of 1 st polarizing plate	Retardation value of A film (1 st polarizing plate side)	IPS-LCD	Retardation value of C film	Retardation value of A film	Internal protective film of 2 nd polarizing plate	Minimum contrast ratio
Zero COP or zero TAC having thickness of 50 μm	Rin = 350 nm Rin = 120 nm Rin = 180 nm Rin = 130 nm Rin = 110 nm Rin = 80 nm Rin = 140 nm	330 nm	Rth = 115 nm Rth = 130 nm Rth = 160 nm Rth = 130 nm Rth = 160 nm Rth = 140 nm Rth = 100 nm	Rin = 140 nm Rin = 150 nm Rin = 150 nm Rin = 130 nm Rin = 110 nm Rin = 90 nm Rin = 110 nm	A film + C film	30:1 25:1

[0090] As described above, all the IPS-LCDs, in which the protective film of a polarizing plate is replaced with a phase retardation film, had a high contrast ratio of more than 25:1. Particularly, the IPS-LCD, which uses a zero TAC film, had a higher contrast ratio than that of the IPS-LCD, which does not use the zero TAC film. In order to confirm the above fact, polarizing plates were manufactured, and contrast characteristics of IPS-LCDs were measured and compared with each other under the conditions in accordance with below embodiments.

[0091] First, IPS-LCDs in accordance with tenth to fourteenth embodiments of the present invention, which use a phase retardation film, obtained by coating a negative biaxial film with a uniaxial C film as the internal protective film of the second polarizing plate, were analyzed.

Tenth Embodiment

[0092] The IPS-LCD of the tenth embodiment, as shown in FIG. 17, was manufactured, and contrast characteristics of the IPS-LCD were measured. In the IPS-LCD of the tenth embodiment, the internal protective film of the first polarizing plate 1 was made of zero COP or zero TAC. The internal protective film of the second polarizing plate 2 was replaced with a phase retardation film obtained by coating the biaxial film 17, which has a thickness of 80 μm , an in-plane retardation value (Rin) of 90 nm, and a thickness retardation value (Rth) of -75 nm, with the C film 11, which has a thickness retardation value (Rth) of 140 nm.

Eleventh Embodiment

[0093] The IPS-LCD of the eleventh embodiment, as shown in FIG. 18, was manufactured, and contrast characteristics of the IPS-LCD were measured. In the IPS-LCD of the eleventh embodiment, the internal protective film of the first polarizing plate 1 was a thin TAC film, which has a thickness retardation value (Rth) of -30 nm. The internal protective film of the second polarizing plate 2 was replaced with a phase retardation film obtained by coating the biaxial film 17, which has a thickness of 80 μm , an in-plane retardation value (Rin) of 90 nm, and a thickness retardation value (Rth) of -75 nm, with the C film 11, which has a thickness retardation value (Rth) of 140 nm.

Twelfth Embodiment

[0094] The IPS-LCD of the twelfth embodiment, as shown in FIG. 19, was manufactured, and contrast characteristics of the IPS-LCD were measured. In the IPS-LCD of the twelfth embodiment, the internal protective film of the first polarizing plate 1 was a general TAC film, which has a thickness retardation value (Rth) of -60 nm. The internal protective film of the second polarizing plate 2 was replaced with a phase retardation film obtained by coating the biaxial film 17, which has a thickness of 80 μm , an in-plane retardation value (Rin) of 90 nm, and a thickness retardation value (Rth) of -75 nm, with the C film 11, which has a thickness retardation value (Rth) of 140 nm.

Thirteenth Embodiment

[0095] The IPS-LCD of the thirteenth embodiment, as shown in FIG. 20, was manufactured, and contrast characteristics of the IPS-LCD were measured. In the IPS-LCD of the thirteenth embodiment, the internal protective film of the

first polarizing plate 1 was a zero TAC film, which does not have a retardation value. The internal protective film of the second polarizing plate 2 was replaced with a phase retardation film obtained by coating the biaxial film 17, which is provided with an optical axis parallel with the absorption axis of the second polarizing plate 2 and has a thickness of 80 μm , an in-plane retardation value (Rin) of 90 nm, and a thickness retardation value (Rth) of -75 nm, with the C film 11, which has a thickness retardation value (Rth) of 140 nm.

Fourteenth Embodiment

[0096] The IPS-LCD of the fourteenth embodiment, as shown in FIG. 21, was manufactured, and contrast characteristics of the IPS-LCD were measured. In the IPS-LCD of the fourteenth embodiment, the internal protective film of the first polarizing plate 1 was a zero TAC film, which does not have a retardation value. The internal protective film of the second polarizing plate 2 was replaced with a phase retardation film obtained by coating the upper surface of the biaxial film 17, which has a thickness of 80 μm , an in-plane retardation value (Rin) of 60 nm, and a thickness retardation value (Rth) of -170 nm, with the C film 11, which has a thickness retardation value (Rth) of 220 nm.

Fifteenth Embodiment

[0097] The IPS-LCD of the fifteenth embodiment, as shown in FIG. 22, was manufactured, and contrast characteristics of the IPS-LCD were measured. In the IPS-LCD of the fifteenth embodiment, the internal protective film of the first polarizing plate 1 was a zero TAC film, which does not have a retardation value, and the A film 12, which has a thickness of 110 μm and an in-plane retardation value (Rin) of 100 nm, was located between the internal protective film of the first polarizing plate 1 and the IPS-panel 3. The internal protective film of the second polarizing plate 2 was replaced with a phase retardation film obtained by coating the upper surface of the uniaxial A film 14, which has a thickness of 100 μm and an in-plane retardation value (Rin) of 130 nm, with the C film 11, which has a thickness retardation value (Rth) of 100 nm.

[0098] In all the above embodiments, the C film has a thickness of 1~2 μm .

[0099] FIGS. 23A to 23F illustrate measured results of contrast ratios of the IPS-LCDs, in accordance with the tenth to fifteenth embodiments. The measured values were similar to the above simulated results, and had the tendency similar as the simulated results, although a small difference between the measured values and the simulated results exists.

[0100] FIG. 23A illustrates the measured results of the contrast ratios of the IPS-LCD of the tenth embodiment, which uses the zero TAC film as the protective film of the first polarizing plate. In the IPS-LCD, the region having the highest contrast ratio is distributed throughout the Poincare sphere. Accordingly, the IPS-LCD exhibited high contrast ratios at all viewable angles.

[0101] FIG. 23B illustrates the measured results of the contrast ratios of the IPS-LCD of the eleventh embodiment, which uses the same polarizing plates as those of the IPS-LCD of the tenth embodiment except for the thin TAC film having a thickness retardation value (Rth) of -30 nm used as the protective film of the first polarizing plate. The

IPS-LCD generally exhibited high contrast ratios, but low contrast ratios of less than 20:1 in some regions at azimuthal angles of 240° and 340°. Accordingly, the IPS-LCD of the eleventh embodiment exhibited comparatively high contrast ratios, although the contrast ratios of the IPS-LCD of the eleventh embodiment are not satisfactory compared to the IPS-LCD of the tenth embodiment.

[0102] FIG. 23C illustrates the measured results of the contrast ratios of the IPS-LCD of the twelfth embodiment, which uses the same polarizing plates as those of the IPS-LCD of the tenth embodiment except for the general TAC film having a thickness retardation value (R_{th}) of -60 nm used as the protective film of the first polarizing plate. The IPS-LCD had the region exhibiting low contrast ratios, which is broader than that of the IPS-LCD of the eleventh embodiment.

[0103] FIG. 23D illustrates the measured results of the contrast ratios of the IPS-LCD of the thirteenth embodiment, which uses the same conditions as those of the IPS-LCD of the tenth embodiment except that the optical axis of the biaxial film is parallel with the absorption axis of the second polarizing plate. The IPS-LCD of the thirteenth embodiment exhibited low contrast ratios, compared to the IPS-LCDs of other embodiments. Accordingly, it was confirmed that the dispositional direction of each of the films is an important factor for determining the contrast ratio.

[0104] FIG. 23E illustrates the measured results of the contrast ratios of the IPS-LCD of the fourteenth embodiment, which uses the zero TAC film as the protective film of the first polarizing plate, identically with the IPS-LCD of the tenth embodiment, but uses the biaxial film of the phase retardation film having a thickness retardation value being lower than the value regulated by the present invention, as the internal protective film of the second polarizing plate. The IPS-LCD of the fourteenth embodiment exhibited contrast ratios, which are higher than those of the IPS-LCD of the twelfth embodiment using the general TAC, but are lower than those of the IPS-LCDs of the tenth and eleventh embodiments, which have the most preferable condition. Accordingly, it was confirmed that the control of the retardation values of each of film layers of the phase retardation film is another important factor for determining the contrast ratio.

[0105] FIG. 23F illustrates the measured results of the contrast ratios of the IPS-LCD of the fifteenth embodiment, which uses the A film and the C film as the internal protective film of the second polarizing plate. As shown in FIG. 23F, the IPS-LCD of the fifteen embodiment exhibited high contrast ratios, similarly to the IPS-LCD of the tenth embodiment.

INDUSTRIAL APPLICABILITY

[0106] As apparent from the above description, the present invention provides an in-plane switching liquid crystal display (IPS-LCD), which uses a second phase retardation film exhibiting a broad viewable angle property as a protective film of one polarizing plate. The IPS-LCD of the present invention has a thin profile and a simple structure, and causes the reduction of the production costs thereof.

[0107] The conventional IPS-LCD having upper and lower protective films exhibits a contrast ratio of 10:1~45:1.

On the other hand, the IPS-LCD of the present invention exhibits a contrast ratio of 25:1~55:1. Accordingly, the IPS-LCD of the present invention has a simple structure and exhibits a reasonably high contrast ratio.

[0108] Although the preferred embodiments of the present invention have been disclosed for illustrative purposes, those skilled in the art will appreciate that various modifications, additions and substitutions are possible, without departing from the scope and spirit of the invention as disclosed in the accompanying claims.

1. An in-plane switching liquid crystal display (IPS-LCD) comprising a first polarizing plate, a second polarizing plate, an horizontally oriented IPS panel disposed between the first and second polarizing plates and filled with a liquid crystal having positive dielectric constant anisotropy ($\Delta\epsilon > 0$), and a first protective film disposed between the first polarizing plate and the IPS panel, in which an absorption axis of the first polarizing plate and an absorption axis of the second polarizing plate are orthogonal to each other, and an optical axis of the liquid crystal in the IPS panel and the absorption axis of the first polarizing plate are parallel with each other,

wherein a second phase retardation film, obtained by coating a biaxial film with a uniaxial C film, is disposed between the second polarizing plate and the IPS panel and is used as a second protective film between the IPS panel and the second polarizing plate.

2. The IPS-LCD according to claim 1, further comprising a first phase retardation film including a uniaxial A film and disposed between the IPS panel and the first polarizing film.

3. The IPS-LCD according to claim 2, wherein the first phase retardation film including the uniaxial A film has an in-plane retardation value (R_{in}) of 30~450 nm, the biaxial film of the second phase retardation film has an in-plane retardation value (R_{in}) of 50~150 nm and a thickness retardation value (R_{th}) of -50~-150 nm, and the uniaxial C film of the second phase retardation film has a thickness retardation value (R_{th}) of 50~170 nm, said retardation values denoting retardation values at a wavelength of 550 nm.

4. An in-plane switching liquid crystal display (IPS-LCD) comprising a first polarizing plate, a second polarizing plate, horizontally oriented IPS panel disposed between the first and second polarizing plates and filled with a liquid crystal having positive dielectric constant anisotropy ($\Delta\epsilon > 0$), and a first protective film disposed between the first polarizing plate and the IPS panel, in which an absorption axis of the first polarizing plate and an absorption axis of the second polarizing plate are orthogonal to each other, and an optical axis of the liquid crystal in the IPS panel and the absorption axis of the first polarizing plate are parallel with each other,

wherein a second phase retardation film, obtained by coating a uniaxial A film with a uniaxial C film, is disposed between the second polarizing plate and the IPS panel and is used as a second protective film between the IPS panel and the second polarizing plate, and a first phase retardation film including a uniaxial A film is disposed between the IPS panel and the first polarizing film.

5. The IPS-LCD according to claim 4, wherein the first phase retardation film including the uniaxial A film has an in-plane retardation value (R_{in}) of 30~450 nm, the uniaxial A film of the second phase retardation film has an in-plane

retardation value (R_{in}) of 80~150 nm, and the uniaxial C film of the second phase retardation film has a thickness retardation value (R_{th}) of 50~170 nm, said retardation values denoting retardation values at a wavelength of 550 nm.

6. The IPS-LCD according to claim 2 or 4, wherein an optical axis of the first phase retardation film in the direction of the X axis is parallel with the absorption axis of the first polarizing plate.

7. The IPS-LCD according to claim 1 or 4, wherein the first protective film is one film selected from the group consisting of a non-stretched zero COP film, a non-stretched

zero TAC film, and a TAC film having a thickness of 50 μm and a thickness retardation value.

8. The IPS-LCD according to claim 7, wherein the first protective film is a non-stretched zero TAC film.

9. The IPS-LCD according to claim 2 or 4, wherein the uniaxial A film is made of lengthwise stretched polymer, the biaxial film is made of crosswise stretched polymer, and the uniaxial C film is obtained by coating an orientation film with a liquid crystal and hardening the liquid crystal coated on the orientation film.

* * * * *

专利名称(译)	面内切换液晶显示器结构简单		
公开(公告)号	US20070024792A1	公开(公告)日	2007-02-01
申请号	US11/493025	申请日	2006-07-26
[标]申请(专利权)人(译)	乐金化学股份有限公司		
申请(专利权)人(译)	LG化学有限公司.		
当前申请(专利权)人(译)	LG化学有限公司.		
[标]发明人	CHANG JUN WON JEON BYOUNG KUN JANG SOO JIN		
发明人	CHANG, JUN WON JEON, BYOUNG KUN JANG, SOO JIN		
IPC分类号	G02F1/1343		
CPC分类号	G02F1/13363 G02F2413/03 G02F2001/133635 G02F1/134363		
优先权	1020050069278 2005-07-29 KR		
其他公开文献	US7511792		
外部链接	Espacenet USPTO		

摘要(译)

IPS-LCD，其中根据替换一个保护膜相位延迟膜的布置来调整光轴的方向和延迟值，获得与具有上保护膜和下保护膜的IPS-LCD类似的对比度，并且厚度很小。IPS-LCD包括第一和第二偏振板（1,2），IPS面板（3）和第一保护膜。第一和第二偏振板（1,2）的吸收轴（4,5）彼此正交，并且IPS板（3）和吸收轴（4）中的液晶的光轴平行于彼此。通过用双轴C膜（11）涂覆双轴膜（17）获得的第二相位延迟膜设置在第二偏振板（2）和IPS板（3）之间，并用作第二保护膜。

