



US007619708B2

(12) **United States Patent**
Ogishima et al.

(10) **Patent No.:** **US 7,619,708 B2**
(45) **Date of Patent:** **Nov. 17, 2009**

(54) **MULTI-DOMAIN LIQUID CRYSTAL DISPLAY DEVICE**

6,384,889 B1 5/2002 Miyachi et al.

(75) Inventors: **Kiyoshi Ogishima**, Soraku-gun (JP);
Masumi Kubo, Ikoma (JP)

(Continued)

(73) Assignee: **Sharp Kabushiki Kaisha**, Osaka (JP)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

EP 0 884 626 A2 12/1998

(Continued)

(21) Appl. No.: **12/068,902**

OTHER PUBLICATIONS

(22) Filed: **Feb. 13, 2008**

U.S. Appl. No. 10/648,340, filed Aug. 27, 2003.

(65) **Prior Publication Data**

(Continued)

US 2008/0143898 A1 Jun. 19, 2008

Related U.S. Application Data

Primary Examiner—David Nelms
Assistant Examiner—W. Patty Chen
(74) *Attorney, Agent, or Firm*—Nixon & Vanderhye P.C.

(63) Continuation of application No. 10/648,340, filed on Aug. 27, 2003, now Pat. No. 7,355,664.

(57) **ABSTRACT**

(30) **Foreign Application Priority Data**

Aug. 30, 2002 (JP) 2002-254114

The liquid crystal display device of this invention includes a first substrate, a second substrate, and a vertical alignment type liquid crystal layer including liquid crystal molecules having negative dielectric anisotropy disposed between the two substrates. In each of a plurality of picture-element regions, the liquid crystal layer has a plurality of liquid crystal regions different in the direction in which liquid crystal molecules tilt upon application of a voltage. At least one of the first and second substrates has a light-shield layer overlapping at least part of boundary region defined as regions separating the plurality of liquid crystal regions from each other. The part of the boundary region overlapping the light-shield layer is a region permitting liquid crystal molecules surrounding the region to tilt so that the ends of the liquid crystal molecules closer to the substrate having the light-shield layer go away from the region upon application of a voltage.

(51) **Int. Cl.**

G02F 1/1337 (2006.01)
G02F 1/1333 (2006.01)

(52) **U.S. Cl.** **349/129; 349/110**


(58) **Field of Classification Search** 349/129
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 5,309,264 A 5/1994 Lien et al.
- 5,648,828 A 7/1997 Sakamoto et al.
- 5,652,634 A 7/1997 Hirata et al.
- 5,666,179 A 9/1997 Koma
- 5,781,262 A 7/1998 Suzuki et al.
- 5,995,176 A 11/1999 Sibahara

7 Claims, 13 Drawing Sheets



US 7,619,708 B2

Page 2

U.S. PATENT DOCUMENTS

6,400,440 B1 6/2002 Colgan et al.
6,446,293 B2 9/2002 Lindquist et al.
6,476,896 B1 11/2002 Liu
6,567,139 B2 5/2003 Huang
6,567,144 B1 5/2003 Kim et al.
6,583,836 B2 6/2003 Kim et al.
6,710,837 B1 3/2004 Song et al.
6,741,314 B2 5/2004 Song
6,788,375 B2 9/2004 Ogishima et al.
6,950,160 B2 9/2005 Kubo et al.
6,950,161 B2 9/2005 Ogishima et al.
7,084,943 B2 8/2006 Kubo et al.
7,355,664 B2 4/2008 Ogishima et al.
2001/0019388 A1 9/2001 Kim et al.
2002/0036740 A1 3/2002 Kubo et al.

2002/0063834 A1 5/2002 Sawasaki et al.
2002/0075436 A1 6/2002 Kubo et al.
2003/0107695 A1 6/2003 Kubo et al.

FOREIGN PATENT DOCUMENTS

EP 1 006 394 6/2000
EP 1 103 840 A2 5/2001
EP 1 111 441 A2 6/2001
EP 1 113 311 A2 7/2001
EP 1 113 312 A2 7/2001
JP 08-313896 11/1996

OTHER PUBLICATIONS

Korean Office Action mailed Sep. 27, 2005 (w/English translation thereof).





FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7A




FIG. 7B




FIG. 8A




FIG. 8B




FIG. 9A




FIG. 9B




FIG. 10A




FIG. 10B




FIG. 11A





FIG. 11B






FIG. 12B




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17





FIG. 18



MULTI-DOMAIN LIQUID CRYSTAL DISPLAY DEVICE

This application is a Continuation of application Ser. No. 10/648,340, filed Aug. 27, 2003 now U.S. Pat. No. 7,355,664, the entire content of which is hereby incorporated herein by reference in this application.

BACKGROUND OF THE INVENTION

The present invention relates to a liquid crystal display device, and more particularly, to a liquid crystal display device having a wide viewing angle characteristic and providing high quality display.

The liquid crystal display device is a flat display device having excellent features of being thin, light in weight and low in power consumption. However, the liquid crystal display device has a shortcoming of being large in "viewing angle dependence" in which the display state changes with the direction in which the display device is observed. A main cause for the large viewing angle dependence of the liquid crystal display device is that liquid crystal molecules having uniaxial optical anisotropy are oriented uniformly in the display plane.

To improve the viewing angle characteristic of the liquid crystal display device, an orientation division method is effective, in which a plurality of regions different in orientation states are formed in each picture-element region. Various techniques have been proposed to implement this method. Among these, a technique disclosed in Japanese Laid-Open Patent Publication No. 6-301036 and No. 2000-47217 and a technique called MVA disclosed in Japanese Laid-Open Patent Publication No. 11-242225 are considered as typical techniques for implementing the orientation division on vertical alignment mode liquid crystal display devices.

In the technique disclosed in Japanese Laid-Open Patent Publication No. 6-301036 and No. 2000-47217, an inclined electric field is generated by forming slits (openings) for an electrode, to control the orientation direction of liquid crystal molecules with the generated inclined electric field.

In the MVA technique disclosed in Japanese Laid-Open Patent Publication No. 11-242225, a pair of substrates (for example, a TFT substrate and a color filter substrate) opposed to each other via a liquid crystal layer have protrusions, depressions or slits (openings of an electrode) formed on their surfaces facing the liquid crystal layer, to thereby realize the orientation division.

As the type of the orientation division of each picture-element region, there are comparatively simple types, such as two-division type in which liquid crystal molecules in each picture-element region are oriented in two directions and four-division type in which they are oriented in four directions, and comparatively complicate types, such as infinite-division type in which liquid crystal molecules are oriented in all directions and the type in which liquid crystal molecules are twisted in a liquid crystal layer.

From the standpoint of achieving equal display characteristics in all directions, liquid crystal molecules are preferably oriented in as many directions as possible in each picture-element region. In general, orientation in four or more directions is considered providing sufficient display quality.

However, as a result of examinations by the present inventors, it was found that the techniques disclosed in Japanese Laid-Open Patent Publication No. 6-301036, No. 2000-47217 and No. 11-258606 had the following problem. Although the azimuthal angle dependence of the display characteristics can be improved by these techniques, the dis-

play characteristics obtained when the display device is observed from the front is greatly different from that obtained when it is observed obliquely. Therefore, the gray-scale characteristic greatly varies with the angle at which the observer views the display plane, and this makes the observer feel unnatural.

SUMMARY OF THE INVENTION

The present invention was devised to overcome the aforementioned disadvantages, and an object of the present invention is providing a liquid crystal display device with high display quality that has a wide viewing angle characteristic and can provide display free from unnaturalness.

The liquid crystal display device of the present invention includes a first substrate, a second substrate, and a vertical alignment type liquid crystal layer including liquid crystal molecules having negative dielectric anisotropy disposed between the first substrate and the second substrate, the device having a plurality of picture-element regions each defined by a first electrode placed in the first substrate on the side facing the liquid crystal layer and a second electrode placed in the second substrate to oppose to the first electrode via the liquid crystal layer, in each of the plurality of picture-element regions, the liquid crystal layer having a plurality of liquid crystal regions different in the direction in which liquid crystal molecules tilt when a voltage is applied between the first electrode and the second electrode, wherein at least one of the first substrate and the second substrate has a light-shield layer overlapping (lying above or below) at least part of boundary region defined as regions separating the plurality of liquid crystal regions from each other, and the at least part of boundary region overlapping (lying above or below) the light-shield layer is a region permitting liquid crystal molecules surrounding the region to tilt so that ends of the liquid crystal molecules closer to the substrate having the light-shield layer go away from the region when a voltage is applied between the first electrode and the second electrode.

Preferably, the light-shield layer is placed with a predetermined spacing from the liquid crystal layer.

Alternatively, the liquid crystal display device of the present invention includes a first substrate, a second substrate, and a vertical alignment type liquid crystal layer including liquid crystal molecules having negative dielectric anisotropy disposed between the first substrate and the second substrate, the device having a plurality of picture-element regions each defined by a first electrode placed in the first substrate on the side facing the liquid crystal layer and a second electrode placed in the second substrate to oppose to the first electrode via the liquid crystal layer, in each of the plurality of picture-element regions, the liquid crystal layer having a plurality of liquid crystal regions different in the direction in which liquid crystal molecules tilt when a voltage is applied between the first electrode and the second electrode, the plurality of liquid crystal regions of the liquid crystal layer including a first liquid crystal region of which the retardation value for light incident on the liquid crystal layer obliquely from the normal to the liquid crystal layer increases with rise of an applied voltage and a second liquid crystal region of which the retardation value first decreases and then increases, wherein the device includes a light-shield layer selectively shading the first liquid crystal region when the device is observed in a direction oblique from the normal to the display plane.

The liquid crystal display device described above may further include a pair of polarizing plates placed opposing to each other via the liquid crystal layer so that their polarization axes are substantially perpendicular to each other, wherein in

each of the plurality of picture-element regions, at least one of the first substrate and the second substrate may have an additional light-shield layer overlapping (lying above or below) at least part of regions in which liquid crystal molecules tilt in directions substantially parallel to the polarization axes of the pair of polarizing plates when a voltage is applied between the first electrode and the second electrode.

Alternatively, the liquid crystal display device of the present invention includes a first substrate, a second substrate, a vertical alignment type liquid crystal layer including liquid crystal molecules having negative dielectric anisotropy disposed between the first substrate and the second substrate, and a pair of polarizing plates placed opposing to each other via the liquid crystal layer so that their polarization axes are substantially perpendicular to each other, the device having a plurality of picture-element regions each defined by a first electrode placed in the first substrate on the side facing the liquid crystal layer and a second electrode placed in the second substrate to oppose to the first electrode via the liquid crystal layer, in each of the plurality of picture-element regions, the liquid crystal layer having a plurality of liquid crystal regions different in the direction in which the liquid crystal molecules tilt when a voltage is applied between the first electrode and the second electrode, wherein in each of the plurality of picture-element regions, at least one of the first substrate and the second substrate has a light-shield layer overlapping (lying above or below) at least part of regions in which liquid crystal molecules tilt in directions substantially parallel to the polarization axes of the pair of polarizing plates when a voltage is applied between the first electrode and the second electrode.

Preferably, the light-shield layer is placed substantially right on the liquid crystal layer.

At least one of the first substrate and the second substrate may have at least one protrusion having a slant side formed on the surface facing the liquid crystal layer, and the direction in which liquid crystal molecules tilt in each of the plurality of liquid crystal regions may be defined by orientation-regulating force of the at least one protrusion.

Otherwise, at least one of the first electrode and the second electrode may have at least one opening, and the direction in which liquid crystal molecules tilt in each of the plurality of liquid crystal regions may be defined by an inclined electric field generated at an edge portion of the at least one opening when a voltage is applied between the first electrode and the second electrode.

Otherwise, at least one of the first substrate and the second substrate may have at least one protrusion having a slant side formed on the surface facing the liquid crystal layer, at least one of the first electrode and the second electrode may have at least one opening, and the direction in which liquid crystal molecules tilt in each of the plurality of liquid crystal regions may be defined by orientation-regulating force of the at least one protrusion and an inclined electric field generated at an edge portion of the at least one opening when a voltage is applied between the first electrode and the second electrode.

In a preferred embodiment, the first substrate further includes switching elements respectively placed to correspond to the plurality of picture-element regions, and the first electrode includes a plurality of picture-element electrodes respectively placed for the plurality of picture-element regions and switched with the switching elements, and the

second electrode includes at least one counter electrode opposed to the plurality of picture-element electrodes.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1A and 1B diagrammatically show a liquid crystal display device **100** of Embodiment 1 of the present invention, where FIG. 1A is a top view and FIG. 1B is a cross-sectional view taken along line 1B-1B' in FIG. 1A.

FIGS. 2A and 2B diagrammatically show a conventional liquid crystal display device **1000** having no light-shield layer, where FIG. 2A is a top view and FIG. 2B is a cross-sectional view taken along line 2B-2B' in FIG. 2A.

FIG. 3 is a graph showing the voltage-transmittance characteristics obtained when the liquid crystal display device **1000** is observed in a normal direction D1 and in an oblique direction D2.

FIG. 4 is a graph showing the voltage-transmittance characteristics obtained when a liquid crystal region **31** in which liquid crystal molecules **30a** tilt to fall toward the observer is observed in an oblique direction and when a liquid crystal region **31** in which liquid crystal molecules **30a** tilt to fall toward the opposite to the observer is observed in an oblique direction.

FIG. 5 is a graph showing the voltage-transmittance characteristics obtained when the liquid crystal display device **100** of Embodiment 1 is observed in the normal direction D1 and in the oblique direction D2.

FIG. 6 is a diagrammatic cross-sectional view of the liquid crystal display device **100** of Embodiment 1.

FIGS. 7A and 7B diagrammatically show another liquid crystal display device **100A** of Embodiment 1 of the present invention, where FIG. 7A is a top view and FIG. 7B is a cross-sectional view taken along line 7B-7B' in FIG. 7A.

FIGS. 8A and 8B diagrammatically show yet another liquid crystal display device **100B** of Embodiment 1 of the present invention, where FIG. 8A is a top view and FIG. 8B is a cross-sectional view taken along line 8B-8B' in FIG. 8A.

FIGS. 9A and 9B diagrammatically show a liquid crystal display device **200** of Embodiment 2 of the present invention, where FIG. 9A is a top view and FIG. 9B is a cross-sectional view taken along line 9B-9B' in FIG. 9A.

FIGS. 10A and 10B diagrammatically show another liquid crystal display device **200A** of Embodiment 2 of the present invention, where FIG. 10A is a top view and FIG. 10B is a cross-sectional view taken along line 10B-10B' in FIG. 10A.

FIGS. 11A and 11B diagrammatically show yet another liquid crystal display device **200B** of Embodiment 2 of the present invention, where FIG. 11A is a top view and FIG. 11B is a cross-sectional view taken along line 11B-11B' in FIG. 11A.

FIGS. 12A and 12B diagrammatically show a liquid crystal display device **300** of Embodiment 3 of the present invention, where FIG. 12A is a top view and FIG. 12B is a cross-sectional view taken along line 12B-12B' in FIG. 12A.

FIG. 13 is a diagrammatic top view of the liquid crystal display device **300** of Embodiment 3.

FIG. 14 is a graph showing the voltage-transmittance characteristic of a region in which liquid crystal molecules **30a** tilt along a polarization axis PA1 obtained when the liquid crystal display device **1000** is observed in an oblique direction along a polarization axis PA2.

FIG. 15 is a graph showing the voltage-transmittance characteristics obtained when the liquid crystal display device **300** of Embodiment 3 is observed in the normal direction and in an oblique direction.

FIG. 16 is a graph showing the voltage-transmittance characteristics obtained when the liquid crystal display device 100 is observed in the normal direction and in an oblique direction, and the voltage-transmittance characteristic obtained when a liquid crystal display device having an additional light-shield layer is observed in an oblique direction.

FIG. 17 is a diagrammatic top view of a liquid crystal display device 400 of Embodiment 4 of the present invention.

FIG. 18 is a diagrammatic top view of another liquid crystal display device 400A of Embodiment 4 of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Hereinafter, preferred embodiments of the present invention will be described with reference to the accompanying drawings. Since excellent display characteristics can be obtained according to the present invention, the present invention is suitably applied to active matrix liquid crystal display devices. Herein, as embodiments of the present invention, active matrix liquid crystal display devices having thin film transistors (TFTs) as the switching elements for switching picture-element electrodes will be described. The present invention can also be applied to MIM type active matrix liquid crystal display devices and simple active matrix liquid crystal display devices.

As used herein, a region of a liquid crystal display device corresponding to one "picture element" as the minimum unit of display is called a "picture-element region". In a color liquid crystal display device, R, G and B "picture elements" constitute one "pixel". In an active matrix liquid crystal display device, a picture-element electrode and a portion of a counter electrode opposed to the picture-element electrode define a picture-element region. In a simple matrix liquid crystal display device, each of the crossings of stripe-shaped column electrodes and stripe-shaped row electrodes running perpendicular to each other defines a picture-element region. If a black matrix is placed, the picture-element region is strictly defined as a portion of a region across which a voltage is applied according to the state to be displayed that corresponds to each opening of the black matrix.

Embodiment 1

The structure of a liquid crystal display device 100 of Embodiment 1 of the present invention will be described with reference to FIGS. 1A and 1B. Note that in the following description, color filters and a black matrix are ignored for simplification. Throughout the drawings, components having the same functions are denoted by the same reference numerals and are not described repeatedly. FIG. 1A is a top view of the liquid crystal display device 100 as viewed in the direction normal to the substrate plane, and FIG. 1B is a cross-sectional view taken along line 1B-1B' in FIG. 1A. FIGS. 1A and 1B show the state under application of a voltage across the liquid crystal layer.

The liquid crystal display device 100 includes an active matrix substrate (hereinafter, called a "TFT substrate") 10a, a counter substrate (also called a "color filter substrate") 10b, and a vertical alignment type liquid crystal layer 30 disposed between the TFT substrate 10a and the counter substrate 100b.

Liquid crystal molecules 30a in the liquid crystal layer 30, which have negative dielectric anisotropy, are aligned vertically to the surfaces of vertical alignment films (not shown) formed on the surfaces of the TFT substrate 100a and the counter substrate 100b facing the liquid crystal layer 30 when

no voltage is applied across the liquid crystal layer 30. That is, the liquid crystal layer 30 is in a vertically aligned state during non-voltage application. Note however that the liquid crystal molecules 30a in the liquid crystal layer 30 in the vertically aligned state may somewhat be tilted from the normal to the surfaces of the vertical alignment films (surfaces of the substrates) depending on the kind of the vertical alignment films and the kind of the liquid crystal material. In general, when the axes (also called the "axial directions") of liquid crystal molecules are at about 85° or more with respect to the surfaces of the vertical alignment films, this state is called the vertically aligned state.

The TFT substrate 10a of the liquid crystal display device 100 includes a transparent plate (glass plate, for example) 11 and picture-element electrodes 14 formed on the surface of the transparent plate 11. The counter substrate 100b includes a transparent plate (glass plate, for example) 21 and a counter electrode 24 formed on the surface of the transparent plate 21. The orientation state of the liquid crystal layer 30 in each picture-element region changes with the voltage applied between the corresponding picture-element electrode 14 and the counter electrode 24 opposed to each other via the liquid crystal layer 30. As the orientation state of the liquid crystal layer 30 changes, the polarized state and amount of light passing through the liquid crystal layer 30 change, and using this phenomenon, display is achieved. In this embodiment, a pair of polarizing plates (not shown) are opposed to each other via the TFT substrate 10a and the counter substrate 100b so that their polarization axes (transmission axes) PA1 and PA2 are orthogonal to each other.

In the liquid crystal display device 100, each picture-element region is divided in terms of the orientation to improve the viewing angle characteristic, in which the liquid crystal layer 30 includes a plurality of liquid crystal regions 31 different in the direction in which the liquid crystal molecules 30a tilt (the orientation of the major axes of the tilting liquid crystal molecules 30a orthogonally projected on the substrate surface: azimuthal direction). Arrows 36 in FIG. 1A indicate the directions in which the liquid crystal molecules 30a in the liquid crystal regions 31 tilt, and in this case, indicate the directions in which the ends of the liquid crystal molecules 30a closer to the counter substrate 100b fall upon application of a voltage.

The direction in which the liquid crystal molecules 30a tilt is defined by an orientation-regulating structure placed on the side of the TFT substrate 100a and an orientation-regulating structure placed on the side of the counter substrate 10b. Hereinafter, this will be described in detail.

The picture-element electrode 14 of the TFT substrate 10a has a plurality of openings 14a. In this embodiment, the openings 14a, having a shape of a slit (a shape having a width (side orthogonal to the length) extremely small with respect to the length), extend in parallel with each other. Each opening 14a has a side extending at an angle of 45° with respect to the longitudinal and lateral sides of the picture-element electrode 14. The direction in which the side of the opening 14a extends changes by 90° every predetermined pitch, forming a zigzag (or dogleg) shape. In this embodiment, the openings 14a of the picture-element electrode 14 are formed to have a width of 10 μm and a pitch of 60 μm.

When a voltage is applied between the picture-element electrode 14 and the counter electrode 24, an inclined electric field represented by an inclined equipotential line is formed in a region of the liquid crystal layer 30 located above an edge portion of each opening 14a of the picture-element electrode 14 (a portion around the inside of each opening 14a including the boundary (fringe) of the opening 14a). Therefore, when a

voltage is applied, the liquid crystal molecules **30a** having negative dielectric anisotropy, which are in the vertically aligned state during non-voltage application, tilt along the inclination of the inclined electric field generated in the edge portion of the opening **14a**.

The counter substrate **100b** has protrusions **26** on the surface thereof facing the liquid crystal layer **30**. Each protrusion **26** has slant sides **26s** and extends in a zigzag (or dogleg) shape as viewed in the direction normal to the substrate surface, as in the case of the openings **14a**. The direction in which the slant sides **26s** extend corresponds with the direction in which the sides of the openings **14a** extend, and the protrusion **26** is placed roughly in the middle between the two adjacent openings **14**. In this embodiment, the protrusions **16** are formed to have a width of 10 μm and a pitch of 60 μm .

The surface of the protrusion **26** has a vertical alignment property (typically, a vertical alignment film (not shown) is formed to cover the protrusion **26**). Therefore, liquid crystal molecules **30a** on the slant sides **26s** are aligned substantially vertically to the slant sides **26s** due to the anchoring effect of the slant sides **26s**.

When a voltage is applied across the liquid crystal layer **30** in the state described above, other liquid crystal molecules **30a** in the vicinity of the protrusion **26** tilt to conform to the inclined orientation on the slant sides **26s** of the protrusion **26** caused due to the anchoring effect of the slant sides **26s**.

As described above, the direction of the tilt of the liquid crystal molecules **30a** located above the edge portion of the opening **14a** of the picture-element electrode **14** upon application of a voltage is defined by the orientation-regulating structure of the TFT substrate **100a**, that is, the picture-element electrode **14** having the opening **14a**. Also, the direction of the tilt of the liquid crystal molecules **30a** located in the vicinity of the protrusion **26** upon application of a voltage is defined by the orientation-regulating structure of the counter substrate **100b**, that is, the protrusion **26** having the slant sides **26s**. Therefore, upon application of a voltage, the remaining liquid crystal molecules **30a** tilt to conform to the tilt of these liquid crystal molecules **30a** located in the portions described above. As a result, the direction of the tilt of the liquid crystal molecules **30a** in each liquid crystal region **31** is defined by the inclined electric field generated in the edge portion of the opening **14a** of the picture-element electrode **14** and the orientation-regulating force of the protrusion **26** on the counter substrate **100b**.

As shown in FIG. 1A, the picture-element region of the liquid crystal display device **100** includes a plurality of liquid crystal regions **31** different in the direction of the tilt of the liquid crystal molecules **30a**. In the illustrated example, the picture-element region is divided to provide four directions apart by angles of integral multiples of 90° from one another, and these four directions are at an angle of about 45° with respect to the polarization axes PA1 and PA2 of polarizing plates.

In the liquid crystal display device **100** according to the present invention, the TFT substrate **10a** further includes light-shield layers **40**. As shown in FIG. 1B, each light-shield layer **40** is formed to overlap (lie below) at least part of boundary region **33** defined as region separating the plurality of liquid crystal regions **31** from one another.

More specifically, in this embodiment, the light-shield layer **40** has the same width of 10 μm as the protrusion **26**, so as to be the same in shape as viewed in the direction normal to the substrate as the protrusion **26** and extend below the protrusion **26**. Note that in FIG. 1B, the width of the light-shield layer **40** is exaggerated for the purpose of easy understanding of description to follow. In the illustrated example, a trans-

parent insulating layer **12** is formed covering the light-shield layer **40** formed on the transparent plate **11**, so that a predetermined spacing is provided between the light-shield layer **40** and the liquid crystal layer **30**.

As shown in FIG. 1B, the boundary region **33** overlapping (lying above) the light-shield layer **40** corresponds to a region permitting liquid crystal molecules **30a** surrounding the region to tilt so that ends **30a1** of the liquid crystal molecules **30a** closer to the TFT substrate **100a**, that is, the substrate having the light-shield layer **40** go away from this region when a voltage is applied between the picture-element electrode **14** and the counter electrode **24**.

The liquid crystal display device **100**, having the light-shield layers **40** placed as described above, is small in the difference of the display characteristics between observation from the front and observation in an oblique direction, and thus can provide display free from unnaturalness. This will be described in detail as follows.

First, referring to FIGS. 2A and 2B, why a conventional liquid crystal display device **1000** having no light-shield layer makes the viewer feel unnatural will be described.

The conventional liquid crystal display device **1000** of FIGS. 2A and 2B has substantially the same structure as the liquid crystal display device **100** except that the former has no light-shield layer overlapping at least part of the boundary region **33**.

In the liquid crystal display device **1000**, the azimuthal angle dependence of the display characteristics is improved because each picture-element region is divided into a plurality of liquid crystal regions **31**. However, a great difference arises in display characteristics between observation from the front and observation in an oblique direction.

FIG. 3 is a graph showing the normalized voltage-transmittance characteristic obtained when the liquid crystal display device **1000** is observed in the normal direction (direction indicated by arrow D1 in FIG. 2B) and the normalized voltage-transmittance characteristic obtained when it is observed in an oblique direction (direction indicated by arrow D2 in FIG. 2B) at a visual angle tilted along the polarization axis PA1. In FIG. 3, the axis of abscissas represents the applied voltage (V) across the liquid crystal layer **30** and the axis of ordinates represents the normalized transmittance.

As shown in FIG. 3, a voltage-transmittance curve L2 obtained during observation in an oblique direction is sharper than a voltage-transmittance curve L1 obtained during observation in the normal direction. In the state of application of a gray-scale voltage, the transmittance obtained during observation in an oblique direction (normalized transmittance) is higher than the transmittance obtained during observation in the normal direction.

The increase of the transmittance in an oblique direction during application of a gray-scale voltage is caused by the behavior of liquid crystal molecules **30a** in a specific liquid crystal region **31** among the plurality of liquid crystal regions **31** of each picture-element region. Specifically, it is caused by the behavior of the liquid crystal molecules **30a** tilting in the direction opposite to the observer who observes obliquely (that is, tilting so that the ends of the liquid crystal molecules **30a** closer to the counter substrate **100b** go away from the observer).

The above discussion will be made in more detail focusing on the two liquid crystal regions **31** shown in FIG. 2B. The liquid crystal molecules **30a** in both liquid crystal regions **31** tilt at an angle of 45° with respect to the polarization axes PA1 and PA2 as shown in FIG. 2A. However, when the two liquid crystal regions **31** are observed in an oblique direction (direction indicated by arrow D2 in FIG. 2B) at a visual angle tilted

along the polarization axis PA1, for example, the liquid crystal molecules 30a in the liquid crystal region 31 on the left as viewed from FIG. 2B tilt to fall toward the observer, while those in the liquid crystal region 31 on the right tilt to fall toward the opposite to the observer.

FIG. 4 is a graph showing the voltage-transmittance characteristic obtained when the two liquid crystal regions 31 shown in FIG. 2B are observed in an oblique direction, in which a voltage-transmittance curve L3 is for the liquid crystal region 31 in which the liquid crystal molecules 30a tilt to fall toward the observer (liquid crystal region on the left in FIG. 2B), and a voltage-transmittance curve L4 is for the liquid crystal region 31 in which the liquid crystal molecules 30a tilt to fall toward the opposite to the observer (liquid crystal region on the right in FIG. 2B).

As shown in FIG. 4, in the liquid crystal region 31 in which the liquid crystal molecules 30a fall toward the observer, the transmittance first drops and then rises with rise of the voltage. In the liquid crystal region 31 in which the liquid crystal molecules 30a fall toward the opposite to the observer, the transmittance rises roughly monotonously with rise of the voltage. The reason is that, while the retardation value of the liquid crystal layer 30 for light incident obliquely to the liquid crystal layer 30 (in a direction oblique from the normal to the liquid crystal layer 30) first decreases and then increases with rise of the voltage in the liquid crystal region 31 in which the liquid crystal molecules 30a fall toward the observer, it increases monotonously with rise of the voltage in the liquid crystal region 31 in which the liquid crystal molecules 30a fall toward the opposite to the observer.

The voltage-transmittance characteristic obtained during observation in an oblique direction shown in FIG. 3 represents the sum of the voltage-transmittance characteristics of the respective liquid crystal regions 31 as those shown in FIG. 4. It is therefore considered that the increase of the transmittance in an oblique direction during application of a gray-scale voltage is caused by the liquid crystal molecules 30a falling toward the opposite to the observer.

In the liquid crystal display device 100 according to the present invention, the light-shield layer 40 is formed to overlap (lie below) at least part of the boundary region 33 defined as region separating the plurality of liquid crystal regions 31 from one another. The at least part of the boundary region 33 that is overlapping (lying above) the light-shield layer 40 is a region permitting the liquid crystal molecules 30a surrounding the region to tilt so that the ends of the liquid crystal molecules 30a closer to the TFT substrate 10a, that is, the substrate having the light-shield layer 40 go away from this region when a voltage is applied.

The thus-provided light-shield layer 40 selectively shades the liquid crystal region 31 in which the liquid crystal molecules 30a tilt toward the opposite to the observer, that is, the liquid crystal region 31 of which the retardation value for light incident obliquely increases roughly monotonously with rise of the voltage, among the two liquid crystal regions 31 adjacent to each other via the boundary region 33.

In FIG. 1B, W1 denotes the width of a region shaded by the light-shield layer 40 during observation in the normal direction D1, and W2 denotes the width of a region shaded by the light-shield layer 40 during observation in the oblique direction D2. As shown in FIG. 1B, during observation in the normal direction, the light-shield layer 40 shades the region of the liquid crystal layer 30 right above the light-shield layer 40, and thus will not change the proportion of contribution to the front-view display between the two liquid crystal regions 31. However, during observation in an oblique direction, in which parallax occurs, the light-shield layer 40 selectively

shades the liquid crystal region 31 in which the liquid crystal molecules 30a fall toward the opposite to the observer. FIG. 1B also shows the width W3 of a region shaded by the light-shield layer 40 during observation in an oblique direction D3 opposite to the oblique direction D2. As is found from FIG. 1B, during observation in the oblique direction D3, also, the light-shield layer 40 selectively shades the liquid crystal region 31 in which the liquid crystal molecules 30a fall toward the opposite to the observer.

Therefore, the liquid crystal region 31 in which the liquid crystal molecules 30a fall toward the opposite to the observer partly fails to contribute to the display observed in an oblique direction. This suppresses the increase of the transmittance in the oblique direction during application of a gray-scale voltage, and thus brings the voltage-transmittance characteristic during observation in the oblique direction close to the voltage-transmittance characteristic during observation in the normal direction. As a result, the oblique-direction display characteristics and the normal-direction display characteristics can be made close to each other, and hence display free from unnaturalness can be realized.

FIG. 5 shows a voltage-transmittance curve L3 obtained when the liquid crystal display device 100 of this embodiment is observed in the normal direction D1 and voltage-transmittance curves L4 and L5 obtained when it is observed in the oblique direction D2. The voltage-transmittance curves L4 and L5 show the cases when the depth of the light-shield layer 40, which is defined as the spacing between the bottom surface of the light-shield layer 40 (surface farther from the liquid crystal layer 30) and the liquid crystal layer 30, is 3 μm and 5 μm , respectively. The thickness of the liquid crystal layer 30 is 4 μm . FIG. 5 also shows the voltage-transmittance curve L2 obtained when the conventional liquid crystal display device 1000 is observed in the oblique direction D2 for comparison.

As shown in FIG. 5, the voltage-transmittance curves L4 and L5 of the liquid crystal display device 100 obtained during observation in an oblique direction are closer in shape to the voltage-transmittance curve L3 obtained during observation in the normal direction than the voltage-transmittance curve L2 of the display device having no light-shield layer is. Therefore, natural display in which the normal-direction display characteristics and the oblique-direction display characteristics are close to each other is obtained.

The depth, width, shape and the like of the light-shield layer 40 are not limited to those described in this embodiment, but may be appropriately set depending on the specifications of the liquid crystal display device and desired transmittance, display characteristics and the like.

The depth of the light-shield layer 40 may be set depending on the thickness of the liquid crystal layer 30, the size of the liquid crystal regions 31 and the like so that the liquid crystal region 31 can be effectively shaded. To effectively shade a specific liquid crystal region 31 by use of occurrence of parallax, the light-shield layer 40 should preferably be placed with a predetermined spacing from the liquid crystal layer 30, and the spacing between the light-shield layer 40 and the liquid crystal layer 30, that is, the depth of the light-shield layer 40 should preferably be large to some extent. The parallax is larger when the light-shield layer 40 is placed with a predetermined spacing from the liquid crystal layer 30 than when it is placed immediately under the liquid crystal layer 30. In the former case, the liquid crystal region 31 can be sufficiently shaded even if the visual angle (the tilt angle from the normal to the display plane) is comparatively small. As is found from FIG. 5, in this embodiment, the oblique-direction voltage-transmittance characteristic can be brought closer to

the normal-direction voltage-transmittance characteristic when the depth of the light-shield layer 40 is 5 μm than when it is 3 μm .

A preferred depth of the light-shield layer 40 will be described with reference to FIG. 6. In this embodiment, the liquid crystal region 31 can be effectively shaded by setting the depth D of the light-shield layer 40 to satisfy the relationship, $D+T_3/2=\sqrt{3}\times P/2$ where D is the depth of the light-shield layer (=thickness T_1 of the light-shield layer 40+thickness T_2 of the transparent insulating layer 12 existing on the light-shield layer 40, in this case), T_3 is the thickness of the liquid crystal layer 30, and P is the pitch of arrangement of the protrusions 26 and the openings 14a. By setting the depth D of the light-shield layer 40 in this way, the center of the light-shield layer 40 will shade roughly the middle of the region between the protrusion 26 and the opening 14a adjacent to each other, that is, the center portion of the liquid crystal region 31, when the liquid crystal display device is observed at a visual angle of 60° (assuming that the average refractive index of the components of the liquid crystal display device is 1.6 and the observation is made in the air having the refractive index of 1.0).

In this embodiment, the width W of the light-shield layer 40 was made substantially equal to the width of the protrusion 26. The width of the light-shield layer 40 is not limited to this, but is preferably wider from the standpoint of further improving the display characteristics by shading a larger portion of the liquid crystal region 31 in which the liquid crystal molecules 30a fall toward the opposite to the observer. In this case, the light-shield layer 40 may overlap part of the liquid crystal region 31, not only the boundary region 33. A wider light-shield layer 40 may however decrease the transmittance during observation from the front. Therefore, from the standpoint of suppressing decrease of the transmittance in the normal direction, the narrow light-shield layer 40 is preferred. A side face of the light-shield layer 40 also functions to shade the liquid crystal region 31 due to occurrence of parallax. Therefore, the light-shield layer 40 may be made thick to increase the region of the side face and thereby enable shading of a larger portion of the liquid crystal region 31. Thus, even when the width of the light-shield layer 40 is set comparative small, the liquid crystal region 31 can be sufficiently shaded while preventing decrease of the transmittance in the normal direction by increasing the thickness of the light-shield layer 40.

The shape of the light-shield layer 40 is not limited to that described above. In the case that the light-shield layer 40 is opposed to the protrusion 26 as in this embodiment (or opposed to the opening 14a of the picture-element electrode as will be described later), loss in transmittance in the normal direction can be minimized by providing the light-shield layer 40 of the same shape as the protrusion 26 (or opening 14a). The reason is that the liquid crystal molecules 30a in the boundary region 31 facing the protrusion 26 (or opening 14a) are aligned roughly vertically even during application of a voltage, to maintain the conformity of the alignment with the surrounding liquid crystal molecules 30a. Therefore, the region of the liquid crystal layer 30 facing the protrusion 26 (or opening 14a) is inherently low in the proportion of contribution to the transmittance.

The light-shield layer 40 was placed only on the side of the TFT substrate 100a in the above description. Alternatively, a light-shield layer 40 may be placed additionally or only on the side of the counter substrate 100b.

FIGS. 7A and 7B show another liquid crystal display device 100A of this embodiment, which includes light-shield

layers 40' placed on the side of the counter substrate 100b in addition to the light-shield layers 40 placed on the side of the TFT substrate 100a.

Each light-shield layer 40' of the counter substrate 100b is formed to overlap (lie above) at least part of the boundary region 33. As shown in FIG. 7B, the at least part of the boundary region 33 that overlaps (lies below) the light-shield layer 40' is a region permitting liquid crystal molecules 30a surrounding the region to tilt so that ends 30a2 of the liquid crystal molecules 30a closer to the counter substrate 100b, that is, the substrate having the light-shield layer 40' go away from this region when a voltage is applied. A transparent insulating film 22 is formed covering the light-shield layers 40' formed on the transparent plate 21, and thus the light-shield layers 40' are placed with a predetermined spacing from the liquid crystal layer 30.

Each light-shield layer 40' of the counter substrate 100b selectively shades the liquid crystal region 31 in which the liquid crystal molecules 30a fall toward the opposite to the observer, that is, the liquid crystal region 31 of which the retardation value for light incident obliquely increases monotonously with rise of the voltage, among the liquid crystal regions 31 adjacent to each other via the boundary region 33.

In FIG. 7B, W4 denotes the width of a region shaded by the light-shield layer 40' during observation in the normal direction D4, and W5 denotes the width of a region shaded by the light-shield layer 40' during observation in an oblique direction D5. As shown in FIG. 7B, during observation in the normal direction, the light-shield layer 40' shades the region of the liquid crystal layer 30 right under the light-shield layer 40'. However, during observation in an oblique direction, the light-shield layer 40' selectively shades the liquid crystal region 31 in which the liquid crystal molecules 30a tilt toward the opposite to the observer due to occurrence of parallax.

Thus, in the liquid crystal display device 100A, not only the light-shield layers 40 on the side of the TFT substrate 100a but also the light-shield layers 40' on the side of the counter substrate 100b selectively shade the liquid crystal regions 31 in which the liquid crystal molecules 30a tilt toward the opposite to the observer. Accordingly, the oblique-direction display characteristics can be made close to the normal-direction display characteristics, and thus display free from unnaturalness can be realized.

In the liquid crystal display device 100A shown in FIGS. 7A and 7B, the width of the light-shield layers 40 and 40' is preferably equal to or larger than the width of the protrusions 26 and the openings 14a, and is preferably smaller than the pitch of arrangement of the protrusions 26 and the openings 14a (P in FIG. 6). If the width of the light-shield layers 40 and 40' is equal to or larger than the pitch of arrangement of the protrusions 26 and the openings 14a, the transmittance in the normal direction will be almost zero.

As described above, in the liquid crystal display devices 100 and 100A, the light-shield layers 40 (40') are placed on the side of the TFT substrate 10a and/or on the side of the counter substrate 100b, to enable selective shading of the liquid crystal regions 31 in which the liquid crystal molecules 30a tilt toward the opposite to the observer.

On the side of which substrate the light-shield layer should be placed for a certain boundary region 33 may be determined in the following manner. The liquid crystal molecules 30a surrounding a boundary region 33 tilt so that the ends of the liquid crystal molecules 30a closer to either one of the substrates go away from the boundary region 33. On the side of this substrate, the light-shield layer for the boundary region 33 is placed. In other words, the light-shield layer should be

placed so that the liquid crystal molecules **30a** surrounding the region overlapping (lying above or below) the light-shield layer tilt so that the ends thereof closer to the substrate having the light-shield layer go away from the region upon application of a voltage.

Specifically, when the surrounding liquid crystal molecules **30a** tilt so that the ends thereof closer to the TFT substrate **100a** go away from the boundary region (for example, when the light-shield layer is placed to correspond to the boundary region **33** facing the protrusion **26** shown in FIGS. 1B and 7B), the light-shield layer may be placed on the side of the TFT substrate **100a**. Likewise, when the surrounding liquid crystal molecules **30a** tilt so that the ends thereof closer to the counter substrate **100b** go away from the boundary region (for example, when the light-shield layer is placed to correspond to the boundary region **33** facing the opening **14a** shown in FIGS. 1B and 7B), the light-shield layer may be placed in the counter substrate **100b**.

In the liquid crystal display device according to the present invention, the light-shield layer is selectively placed on the side of either one of the substrates determined by paying attention to the behavior of the liquid crystal molecules **30a** surrounding each boundary region **33** during application of a voltage. Therefore, the liquid crystal regions **31** in which the liquid crystal molecules **30a** tilt toward the opposite to the observer are selectively shaded in whichever oblique direction the observer views the liquid crystal display device, and thus natural display free from unnaturalness can be realized. Since the boundary regions shaded by the light-shield layers during observation in the normal direction are typically regions that hardly contribute to the display inherently (even without the light-shield layers), it is unlikely to decrease the transmittance due to the placement of the light-shield layers.

The light-shield layers are made of a light-shield material such as metal including aluminum and resin, and may be formed at an arbitrary stage in the process of fabrication of the TFT substrate **100a** and the counter substrate **100b** so that a predetermined spacing is provided between the light-shield layers and the liquid crystal layer **30**. If the light-shield layers are formed of a film commonly used for scanning lines and signal lines formed on the transparent plate **11** of the TFT substrate **100a**, no new step is required for formation of the light-shield layers. The light-shield layers may shade substantially the entire incident light incident thereon, or may be a translucent film allowing passing of part of incident light.

In this embodiment, the TFT substrate **100a** includes the picture-element electrodes **14** having the openings (slits) **14a** as the orientation-regulating structure, and the counter substrate **100b** includes the protrusions **26** having the slant sides **26s** as the orientation-regulating structure. The present invention is not limited to this, but may be suitably applied to other liquid crystal display devices having a structure permitting orientation division of the picture-element regions. For example, a liquid crystal display device **100B** shown in FIGS. 8A and 8B may be adopted, in which the TFT substrate **100a** has protrusions **16** having slant sides **16s** and the counter substrate **100b** has a counter electrode **24** having openings **24a**. Only one substrate may have an orientation-regulating structure (for example, electrodes having openings and protrusions). However, from the standpoint of stability of alignment, both substrates preferably have respective orientation-regulating structures.

Embodiment 2

FIGS. 9A and 9B show a liquid crystal display device **200** of Embodiment 2 according to the present invention, where

FIG. 9A is a top view of the liquid crystal display device **200** as viewed in the direction normal to the substrate, and FIG. 9B is a cross-sectional view taken along line 9B-9B' in FIG. 9A. FIGS. 9A and 9B show the state under application of a voltage across the liquid crystal layer.

In the liquid crystal display device **100** of Embodiment 1, each picture-element region was divided into four in terms of the orientation so that the liquid crystal molecules are oriented in four directions. In the liquid crystal display device **200** of Embodiment 2, each picture-element region is divided into an infinite number in terms of the orientation so that the liquid crystal molecules are oriented in all directions.

A TFT substrate **200a** of the liquid crystal display device **200** includes picture-element electrodes **14** having openings **14a** as an orientation-regulating structure. The openings **14a** are slits formed in a square grid pattern.

A counter substrate **200b** opposed to the TFT substrate **200a** has protrusions **26** on the surface thereof facing the liquid crystal layer **30** as an orientation-regulating structure. Each protrusion **26** has a shape of a square truncated pyramid having slant sides **26s** and a top face **26t**, and is roughly in the center of each square surrounded by the grid-shaped openings **14a**.

In this embodiment, the openings **14a** of the picture-element electrode **14**, having a line width of 10 μm , surround a square having a size of 40 μm \times 40 μm . The protrusion **26** has a bottom size of 20 μm \times 20 μm .

In the liquid crystal display device **200** having the orientation-regulating structures described above, when a voltage is applied between the picture-element electrode **14** and the counter electrode **24**, liquid crystal molecules **30a** in a liquid crystal layer **30** are oriented axially symmetrically with respect to the protrusion **26** as the center as shown in FIGS. 9A and 9B. Although the change in the orientation direction of the liquid crystal molecules **30a** is shown simply in FIG. 9A, the orientation direction of the liquid crystal molecules **30a** actually changes sequentially with change of the azimuthal direction. A liquid crystal molecule **30a** existing at a position in a certain azimuthal direction with respect to the protrusion **26** is oriented in a direction substantially parallel to this azimuthal direction.

As described above, the liquid crystal layer **30**, which is in the state of axially-symmetric orientation with respect to the protrusions **26** as the center, has a plurality of (a myriad of) liquid crystal regions **31** different in orientation direction, and thus the liquid crystal molecules **30a** in each picture-element region are oriented in all directions. In other words, each picture-element region of the liquid crystal display device **200** is divided into an infinite number in terms of the orientation so that the liquid crystal molecules are oriented in all directions. In this embodiment, one liquid crystal domain, which is axially symmetrically oriented with respect to the protrusion **26** as the center, is formed in correspondence with one square surrounded with the grid-shaped openings **14a** when a voltage is applied. The "liquid crystal domain" as used herein refers to a region in which the continuity of orientation of the liquid crystal molecules **30a** is maintained.

The TFT substrate **200a** of the liquid crystal display device **200** has light-shield layers **40**. As shown in FIG. 9B, each light-shield layer **40** is formed to overlap (lie below) part of boundary region **33** defined as region separating the plurality of liquid crystal regions **31** from one another. More specifically, the light-shield layer **40** is formed near the center of the liquid crystal domain, to oppose to the protrusion **26** of the counter substrate **200b**. In this embodiment, the light-shield layer **40** is formed to be the same in shape as viewed in the direction normal to the substrate as the protrusion **26** and

overlap the protrusion 26, that is, formed in a shape of a square having a side of 20 μm .

As shown in FIG. 9B, the region of the boundary region 33 that overlaps (lies above) the light-shield layer 40 is a region permitting the liquid crystal molecules 30a surrounding the region to tilt so that the ends of the liquid crystal molecules 30a closer to the TFT substrate 100a, that is, the substrate having the light-shield layer 40 go away from this region when a voltage is applied between the picture-element electrode 14 and the counter electrode 24.

The light-shield layer 40 formed as described above selectively shades the liquid crystal region 31 in which the liquid crystal molecules 30a fall toward the opposite to the observer, that is, the liquid crystal region 31 of which the retardation value for light incident obliquely monotonously increases with rise of the voltage, among the liquid crystal regions 31 adjacent to each other via the boundary region 33.

In FIG. 9B, W6 denotes the width of a region shaded by the light-shield layer 40 during observation in the normal direction D6, and W7 denotes the width of a region shaded by the light-shield layer 40 during observation in an oblique direction D7. As shown in FIG. 9B, during observation in the normal direction, the light-shield layer 40 shades the region of the liquid crystal layer 30 located right above the light-shield layer 40. However, during observation in an oblique direction, the light-shield layer 40 selectively shades the liquid crystal region 31 in which the liquid crystal molecules 30a fall toward the opposite to the observer due to occurrence of parallax. FIG. 9B also shows the width W8 of a region shaded by the light-shield layer 40 during observation in an oblique direction D8 opposite to the oblique direction D7. As is found from FIG. 9B, during observation in the oblique direction D8, also, the light-shield layer 40 selectively shades the liquid crystal region 31 in which the liquid crystal molecules 30a fall toward the opposite to the observer.

As described above, the light-shield layer 40 selectively shades the liquid crystal region 31 in which the liquid crystal molecules 30a tilt toward the opposite to the observer in whichever oblique direction the observer observes the display device. Therefore, part of the liquid crystal region 31 in which the liquid crystal molecules 30a fall toward the opposite to the observer fails to contribute to the display during observation in an oblique direction. This suppresses the increase of the transmittance in the oblique direction during application of a gray-scale voltage, and thus brings the voltage-transmittance characteristic obtained during observation in the oblique direction close to the voltage-transmittance characteristic obtained during observation in the normal direction. As a result, the oblique-direction display characteristics and the normal-direction display characteristics can be made close to each other, and hence display free from unnaturalness can be realized.

In this embodiment, the light-shield layer 40 was placed to overlap (lie below) the region among the boundary regions 33 that corresponds to the center of the liquid crystal domain. Alternatively, the light-shield layer 40 may be placed to oppose to the region corresponding to a boundary between the adjacent liquid crystal domains. FIGS. 10A and 10B show a liquid crystal display device 200A having light-shield layers 40' overlapping (lying above) the boundaries between the adjacent liquid crystal domains.

A counter substrate 200b of the liquid crystal display device 200A has the light-shield layers 40' formed to overlap (lie above) regions among the boundary regions 33 that correspond to the boundaries between the adjacent liquid crystal domains. That is, each light-shield layer 40' is formed to overlap (lie above) the opening 14a of the picture-element

electrode 14. In other words, the region among the boundary regions 33 that overlaps (lies below) the light-shield layer 40' is a region permitting the liquid crystal molecules 30a surrounding the region to tilt so that the ends of the liquid crystal molecules 30a closer to the counter substrate 200b, that is, the substrate having the light-shield layer 40' go away from this region when a voltage is applied between the picture-element electrode 14 and the counter electrode 24.

The light-shield layer 40' of the counter substrate 200b selectively shades the liquid crystal region 31 in which the liquid crystal molecules 30a fall toward the opposite to the observer, that is, the liquid crystal region 31 of which the retardation value for light incident obliquely monotonously increases with rise of the voltage, among the liquid crystal regions 31 adjacent to each other via the boundary region 33, as in the case of the light-shield layer 40' of the counter substrate 100b of the liquid crystal display device 100A shown in FIGS. 7A and 7B. In this way, in the liquid crystal display device 200A, also, display free from unnaturalness can be realized.

The light-shield layers may be provided to correspond to both the center of the liquid crystal domain and the boundaries between the liquid crystal domains. FIGS. 11A and 11B shows a liquid crystal display device 200B having the light-shield layers 40 and 40' provided for both the center of the liquid crystal domain and the boundaries between the liquid crystal domains.

In the liquid crystal display device 200B, the TFT substrate 200a has the light-shield layer 40 formed at the same position as that of the light-shield layer 40 of the TFT substrate 200a of the liquid crystal display device 200, and the counter substrate 200b has the light-shield layer 40' formed at the same position as that of the light-shield layer 40' of the counter substrate 200b of the liquid crystal display device 200A.

In the liquid crystal display device 200B, also, in which the light-shield layers 40 and 40' selectively shade the liquid crystal region 31 in which the liquid crystal molecules 30a fall toward the opposite to the observer, display free from unnaturalness is realized.

Embodiment 3

The structure of a liquid crystal display device 300 of Embodiment 3 according to the present invention will be described with reference to FIGS. 12A and 12B. FIG. 12A is a top view of the liquid crystal display device 300 as viewed in the direction normal to the substrate, and FIG. 12B is a cross-sectional view taken along line 12B-12B' in FIG. 12A. FIGS. 12A and 12B show the state under application of a voltage across the liquid crystal layer.

The liquid crystal display device 300 of Embodiment 3 is the same in construction as the liquid crystal display device 100 of Embodiment 1 except for the position of the light-shield layers.

A counter substrate 300b of the liquid crystal display device 300 has a light-shield layer 41 in each of a plurality of picture-element regions. The light-shield layer 41 is formed to overlap (lie above) a specific region of the liquid crystal layer 30 as will be described later.

In the liquid crystal display device 300 in which each picture-element region is divided into four in terms of the orientation, the liquid crystal molecules 30a in each liquid crystal region 31 tilt at an angle of about 45° with respect to the polarization axes PA1 and PA2 of the polarizing plates as shown in FIG. 12A. However, as shown in FIG. 13, in a region (oval-encircled region) 35, among the regions separating the adjacent liquid crystal regions 31 from each other, which is

located between a bend **14a'** of the opening **14a** and a bend **26'** of the protrusion **26**, the liquid crystal molecules **30a** tilt in a direction substantially parallel to the polarization axis PA1 of the polarizing plate in an attempt of maintaining the continuity of the orientation.

In the liquid crystal display device **300**, the light-shield layer **41** is formed to overlap (lie above) the region **35** in which the liquid crystal molecules **30a** tilt in a direction substantially parallel to the polarization axis PA1 of the polarizing plate. In this embodiment, the light-shield layer **41** is formed right on the counter electrode **24**. The counter electrode **24** of the counter substrate **300b** has a thickness of 100 nm (1000 Å), for example, and the light-shield layer **41** is placed substantially right on the liquid crystal layer **30** via the counter electrode **24**.

In Embodiments 1 and 2, described was the liquid crystal display device capable of suppressing unnaturalness that would otherwise be felt by the observer due to the liquid crystal molecules tilting toward the opposite to the observer. The liquid crystal display device **300** of Embodiment 3 can suppress unnaturalness that may otherwise be felt by the observer due to the liquid crystal molecules tilting in a direction substantially parallel to a polarization axis. This will be described in detail as follows.

The conventional liquid crystal display device **1000** having no light-shield layer shown in FIGS. 2A and 2B makes the observer feel unnatural due to the liquid crystal molecules **30a** tilting in a direction substantially parallel to a polarization axis for the following reason.

When the liquid crystal display device **1000** is observed in an oblique direction along the polarization axis PA2, liquid crystal molecules **30a** tilting along the polarization axis PA2 (assuming that such liquid crystal molecules **30a** exist although actually they hardly exist in the liquid crystal display device **1000**) hardly cause a phase difference for light incident obliquely to the liquid crystal layer **30**, and thus do not affect the display characteristics. However, liquid crystal molecules **30a** tilting along the polarization axis PA1 (corresponding to the liquid crystal molecules **30a** in the regions **35** shown in FIG. 13), which tilt to block the observation direction, cause a phase difference for light incident obliquely to the liquid crystal layer **30**. Moreover, such regions in which liquid crystal molecules **30a** tilt in this direction exhibit a voltage-transmittance characteristic having the peak transmittance at a gray-scale voltage.

FIG. 14 shows a voltage-transmittance curve L6 of the region in which the liquid crystal molecules **30a** tilt along the polarization axis PA1 obtained when the liquid crystal display device **1000** is observed in an oblique direction along the polarization axis PA2. For comparison, FIG. 14 also shows the voltage-transmittance curves L3 and L4 (shown in FIG. 4) of the region in which the liquid crystal molecules **30a** tilt toward the observer at an angle of 45° with respect to the polarization axes PA1 and PA2 and the region in which the liquid crystal molecules **30a** tilt in the direction opposite to the observer at an angle of 45° with respect to the polarization axes PA1 and PA2, respectively.

As is found from FIG. 14, in the region in which the liquid crystal molecules **30a** tilt along the polarization axis PA1, the transmittance reaches the peak at a gray-scale voltage, causing inversion of the gradation of brightness. Therefore, if the proportion of existence of such liquid crystal molecules **30a** in the picture-element region is high, breaking or inversion of the gradation becomes evident in the voltage-transmittance characteristic obtained during observation in an oblique direction. This increases the difference between the normal-

direction display characteristics and the oblique-direction display characteristics, and the resultant display makes the observer feel unnatural.

In the liquid crystal display device **300** of this embodiment, the light-shield layer **41** is placed to overlap (lie above) the region **35** in which the liquid crystal molecules **30a** tilt in a direction substantially parallel to the polarization axis PA1, to prevent this region **35** from contributing to the display. This suppresses excessive increase of the transmittance at a gray-scale voltage, and thus can bring the oblique-direction voltage-transmittance characteristic close to the normal-direction voltage-transmittance characteristic. As a result, since the oblique-direction display characteristics and the normal-direction display characteristics can be brought close to each other, display free from unnaturalness can be realized.

FIG. 15 shows a voltage-transmittance curve L7 obtained when the liquid crystal display device **300** of this embodiment is observed in the normal direction and a voltage-transmittance curve L8 obtained when it is observed in an oblique direction (direction at a visual angle falling along the polarization axis PA2). For comparison, FIG. 15 also shows a voltage-transmittance curve L9 obtained when the conventional liquid crystal display device **1000** is observed in the oblique direction. Note that the voltage-transmittance curves shown in FIG. 15 are those obtained when the regions **35** in which the liquid crystal molecules **30a** tilt roughly in parallel with the polarization axis PA1 occupy about 25% of each picture-element region.

As shown in FIG. 15, the voltage-transmittance curve L8 obtained when the liquid crystal display device **300** is observed in an oblique direction is closer in shape to the voltage-transmittance curve L7 obtained when it is observed in the normal direction than the voltage-transmittance curve L9 of the display device having no light-shield layer is. Therefore, natural display in which the normal-direction display characteristics and the oblique-direction display characteristics are close to each other is obtained.

The region in which the liquid crystal molecules **30a** tilt in a direction substantially parallel to the polarization axis does not contribute to the transmittance obtained during observation in the normal direction. Therefore, there is little loss in transmittance in the normal direction by providing the light-shield layer shading only such a region. To effectively shade only such a region, the light-shield layer should preferably be formed at a position that can prevent occurrence of parallax. In view of this, the light-shield layer is preferably formed substantially right on the liquid crystal layer so that the spacing of the light-shield layer from the liquid crystal layer is as small as possible. The effect of improving the display characteristics may be obtained when the light-shield layers are placed to cover only part of the regions in which the liquid crystal molecules **30a** tilt in a direction substantially parallel to the polarization axis. However, from the standpoint of further improving the display quality, the light-shield layers are preferably placed to cover a largest possible portion of such regions, more preferably placed to cover substantially all of such regions.

The effect of improving the display quality, obtained by placing the light-shield layers to overlap (lie above or below) the regions in which the liquid crystal molecules tilt in a direction substantially parallel to the polarization axis, is significant in a liquid crystal display device having such regions in a comparatively high proportion.

For example, in the liquid crystal display device **1000** shown in FIGS. 2A and 2B, if the pitch of bends of each opening **14a** and protrusion **26** (corresponding to P' in FIG. 13) is small, the proportion of the regions in which the liquid

crystal molecules tilt in a direction substantially parallel to the polarization axis PA of the polarizing plate in each picture-element region is high. This will increase the difference between the normal-direction display characteristics and the oblique-direction display characteristics, and as a result, make unnaturalness of the display evident.

In view of the above, in a liquid crystal display device having such regions in a comparatively high proportion, a light-shield layer shading the regions in which the liquid crystal molecules **30a** tilt in a direction substantially parallel to the polarization axis, like the light-shield layer **41** in the liquid crystal display device **300** of this embodiment, may be placed in addition to a light-shield layer selectively shading the liquid crystal regions in which the liquid crystal molecules tilt toward the opposite to the observer (the light-shield layers **40** and **40'** in the liquid crystal display devices **100** and **200** of Embodiments 1 and 2). By this placement, the display quality can be further improved.

Light-shield layers shading the regions in which the liquid crystal molecules **30a** tilt in a direction substantially parallel to the polarization axis (light-shield layers roughly the same as the light-shield layers **41** in the liquid crystal display device **300** of Embodiment 3) were additionally placed in the liquid crystal display device **100** of Embodiment 1, and the effect of improving the display quality by this additional placement was examined.

FIG. **16** shows a voltage-transmittance curve **L10** obtained when the liquid crystal display device **100** is observed in the normal direction, a voltage-transmittance curve **L11** obtained when it is observed in an oblique direction (direction at a visual angle falling along the polarization axis PA2), and a voltage-transmittance curve **L12** obtained when a liquid crystal display device having the additional light-shield layers described above is observed in an oblique direction. The voltage-transmittance curves shown in FIG. **16** are those obtained when the proportion of the regions in which the liquid crystal molecules **30a** tilt in a direction substantially parallel to the polarization axis PA1 is about 25%.

As shown in FIG. **16**, the voltage-transmittance curve **L12** obtained by placing the additional light-shield layers is closer in shape to the normal-direction voltage-transmittance curve **L10** than the voltage-transmittance curve **L11** obtained without the additional light-shield layer is. Therefore, by placing the additional light-shield layers, the oblique-direction display characteristics become closer to the normal-direction display characteristics, and thus the display quality can further be improved.

Embodiment 4

FIG. **17** shows a liquid crystal display device **400** of Embodiment 4 according to the present invention. The liquid crystal display device **400** shown in FIG. **17** has the same construction as the liquid crystal display device **200** of Embodiment 2 except for the position of the light-shield layers.

The counter substrate (not shown) of the liquid crystal display device **400** has a light-shield layer **41** in each of the plurality of picture-element regions. The light-shield layer **41** is formed to overlap (lie above) regions in which the liquid crystal molecules **30a** tilt in directions substantially parallel to the polarization axes PA1 and PA2 of the polarizing plates. In the example shown in FIG. **17**, the polarization axes PA1 and PA2 of the polarizing plates are arranged in parallel with the two directions in which the openings **14a** of the picture-element electrodes **14** extend, and the light-shield layer **41**

has a shape of a cross composed of two sides extending parallel to the polarization axes PA1 and PA2.

In the liquid crystal display device **400**, the light-shield layer **41** is placed to overlap (lie above) regions in which the liquid crystal molecules **30a** tilt in directions substantially parallel to the polarization axes PA1 and PA2 of the polarizing plates. Therefore, as in the liquid crystal display device **300** of Embodiment 3, natural display free from unnaturalness can be realized.

In the liquid crystal display device **300** of Embodiment 3, the light-shield layer **41** was placed to overlap (lie above) only the regions in which the liquid crystal molecules **30a** tilt in a direction substantially parallel to the polarization axis PA1 considering the fact that there hardly exist liquid crystal molecules **30a** tilting in a direction substantially parallel to the polarization axis PA2. In the liquid crystal display device **400** of this embodiment, there exist liquid crystal molecules **30a** tilting along the polarization axis PA2 as well as those tilting along the polarization axis PA1. Therefore, the light-shield layer **41** is placed to cover the regions including such liquid crystal molecules **30a**.

The light-shield layer **41** may be placed to overlap (lie above) only either the regions in which the liquid crystal molecules **30a** tilt along the polarization axis PA1 or the regions in which the liquid crystal molecules **30a** tilt along the polarization axis PA2. However, more natural display can be realized by placing the light-shield layer **41** to cover both regions.

If the polarization axes of the polarizing plates are arranged differently for liquid crystal cells having roughly the same construction, the regions in which liquid crystal molecules tilt in directions substantially parallel to the polarization axes are different between these liquid crystal cells. Therefore, for different arrangements of the polarization axes, it should be ensured that the light-shield layer is placed so as to cover regions including such liquid crystal molecules. FIG. **18** shows a liquid crystal display device **400A** in which the arrangement of the polarization axes PA1 and PA2 of the polarizing plates is different from that in the liquid crystal display device **400**.

In the liquid crystal display device **400A** shown in FIG. **18**, the polarization axes PA1 and PA2 are arranged to form an angle of 45° with the two directions of extension of the openings **14a** of the picture-element electrodes **14**. Therefore, the light-shield layer **41** of the liquid crystal display device **400A** has a shape obtained by rotating the light-shield layer **41** of the liquid crystal display device **400** by 45° in the plane parallel to the substrate plane.

In the liquid crystal display device **400A**, also, the light-shield layer **41** is placed to cover regions in which the liquid crystal molecules **30a** tilt in directions substantially parallel to the polarization axes PA1 and PA2 of the polarizing plates. Therefore, as in the liquid crystal display device **400**, natural display free from unnaturalness can be realized.

Thus, according to the present invention, a liquid crystal display device with high display quality that has a wide viewing angle characteristic and can provide display free from unnaturalness is provided.

While the present invention has been described in preferred embodiments, it will be apparent to those skilled in the art that the disclosed invention may be modified in numerous ways and may assume many embodiments other than that specifically set out and described above. Accordingly, it is intended by the appended claims to cover all modifications of the invention that fall within the true spirit and scope of the invention.

What is claimed is:

1. A liquid crystal display device comprising:

a first substrate, a second substrate, and a substantially vertical alignment type liquid crystal layer including liquid crystal molecules having negative dielectric anisotropy disposed between the first substrate and the second substrate;

the device having a plurality of picture-element regions each defined by a first electrode placed on the first substrate on the side facing the liquid crystal layer and a second electrode placed on the second substrate to oppose to the first electrode via the liquid crystal layer; in each of the plurality of picture-element regions, the liquid crystal layer having a plurality of liquid crystal regions different in the direction in which liquid crystal molecules tilt when a voltage is applied between the first electrode and the second electrode;

wherein at least one of the first substrate and the second substrate comprises a light-shield layer overlapping at least part of boundary region defined as regions separating the plurality of liquid crystal regions from each other;

the at least part of boundary region overlapping the light-shield layer is a region permitting liquid crystal molecules surrounding the region to tilt so that ends of the liquid crystal molecules closer to the substrate having the light-shield layer go away from the region when a voltage is applied between the first electrode and the second electrode, and

the light-shield layer is located so that a vertical distance, in a direction normal to the substrates, between the light-shield layer and a closest portion of the liquid crystal layer to the light-shield layer, is 3 μm or more.

2. The liquid crystal display device of claim 1, wherein a spacing between the light-shield layer and the liquid crystal layer is 5 μm or more.

3. The liquid crystal display device of claim 1, further comprising:

a pair of polarizing plates placed opposing to each other via the liquid crystal layer so that their polarization axes are substantially perpendicular to each other;

wherein in each of the plurality of picture-element regions, at least one of the first substrate and the second substrate

has an additional light-shield layer overlapping at least part of regions in which liquid crystal molecules tilt in directions substantially parallel to the polarization axes of the pair of polarizing plates when a voltage is applied between the first electrode and the second electrode.

4. The liquid crystal display device of claim 1, wherein at least one of the first substrate and the second substrate has at least one protrusion having a slant side formed on the surface facing the liquid crystal layer, and the direction in which liquid crystal molecules tilt in each of the plurality of liquid crystal regions is defined by orientation-regulating force of the at least one protrusion.

5. The liquid crystal display of claim 1, wherein at least one of the first electrode and the second electrode has at least one opening, and the direction in which liquid crystal molecules tilt in each of the plurality of liquid crystal regions is defined by an inclined electric field generated at an edge portion of the at least one opening when a voltage is applied between the first electrode and the second electrode.

6. The liquid crystal display device of claim 1, wherein at least one of the first substrate and the second substrate has at least one protrusion having a slant side formed on the surface facing the liquid crystal layer;

at least one of the first electrode and the second electrode has at least one opening; and

the direction in which liquid crystal molecules tilt in each of the plurality of liquid crystal regions is defined by orientation-regulating force of the at least one protrusion and an inclined electric field generated at an edge portion of the at least one opening when a voltage is applied between the first electrode and the second electrode.

7. The liquid crystal display device of claim 1, wherein the first substrate further includes switching elements respectively placed to correspond to the plurality of picture-element regions, and

the first electrode comprises a plurality of picture-element electrodes respectively placed for the plurality of picture-element regions and switched with the switching elements, and the second electrode comprises at least one counter electrode opposed to the plurality of picture-element electrodes.

* * * * *

专利名称(译)	多域液晶显示装置		
公开(公告)号	US7619708	公开(公告)日	2009-11-17
申请号	US12/068902	申请日	2008-02-13
[标]申请(专利权)人(译)	夏普株式会社		
申请(专利权)人(译)	夏普株式会社		
当前申请(专利权)人(译)	夏普株式会社		
[标]发明人	OGISHIMA KIYOSHI KUBO MASUMI		
发明人	OGISHIMA, KIYOSHI KUBO, MASUMI		
IPC分类号	G02F1/1337 G02F1/1333 G02F1/133 G02F1/1335 G02F1/1343 G02F1/139		
CPC分类号	G02F1/133512 G02F1/133707 G02F1/1393		
审查员(译)	内尔姆斯, DAVID		
优先权	2002254114 2002-08-30 JP		
其他公开文献	US20080143898A1		
外部链接	Espacenet USPTO		

摘要(译)

本发明的液晶显示装置包括第一基板，第二基板和垂直取向型液晶层，该液晶层包括设置在两个基板之间的具有负介电各向异性的液晶分子。在多个像素区域的每一个中，液晶层具有在施加电压时液晶分子倾斜的方向不同的多个液晶区域。第一和第二基板中的至少一个具有遮光层，该遮光层与边界区域的至少一部分重叠，该边界区域被限定为将多个液晶区域彼此分开的区域。与遮光层重叠的边界区域的部分是允许围绕该区域的液晶分子倾斜的区域，使得靠近具有遮光层的基板的液晶分子的端部在施加时远离该区域。一个电压。

