



US 20050243573A1

(19) **United States**

(12) **Patent Application Publication**

**Kim et al.**

(10) **Pub. No.: US 2005/0243573 A1**

(43) **Pub. Date: Nov. 3, 2005**

(54) **BACKLIGHT UNIT AND LIQUID CRYSTAL DISPLAY DEVICE USING THE SAME**

(30) **Foreign Application Priority Data**

Apr. 30, 2004 (KR)..... 2004-0030588

(76) Inventors: **Dong Soo Kim**, Daegu (KR); **Jin-Seob Lim**, Gyeongsangbukdo (KR)

**Publication Classification**

(51) **Int. Cl.<sup>7</sup>** ..... **G02F 1/1335**

(52) **U.S. Cl.** ..... **362/600**

Correspondence Address:

**MCKENNA LONG & ALDRIDGE LLP**

**1900 K STREET, NW**

**WASHINGTON, DC 20006 (US)**

(57) **ABSTRACT**

A backlight unit for a liquid crystal display device includes: a lamp; a light guide plate adjacent to the lamp; a reflector under the light guide plate; a lamp housing covering the lamp, the lamp housing being combined with edges of the light guide plate and the reflector; and a housing pad under the lamp housing, the housing pad overlapping an edge of the lamp housing.

(21) Appl. No.: **11/117,288**

(22) Filed: **Apr. 29, 2005**




FIG. 1  
RELATED ART





FIG. 2



## BACKLIGHT UNIT AND LIQUID CRYSTAL DISPLAY DEVICE USING THE SAME

[0001] The present invention claims the benefit of Korean Patent Application No. 2004-30588, filed in Korea on Apr. 30, 2004, which is hereby incorporated by reference for all purposes as if fully set forth herein.

### BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The present invention relates to a display device, and more particularly, to a backlight unit and a liquid crystal display device using a backlight unit.

### DISCUSSION OF THE RELATED ART

[0004] As the information age progresses, flat panel display (FPD) devices having light weight, thin profile, and low power consumption characteristics are being developed and commonly used as a substitute for cathode ray tube (CRT) devices. Generally, display devices may be classified according to their ability for self-emission, and may include emissive display devices and non-emissive display devices. The emissive display devices display images by taking advantage of their ability to self-emit light, and the non-emissive display devices require a light source since they do not emit light by themselves. For example, plasma display panel (PDP) devices, field emission display (FED) devices, and electroluminescent display (ELD) devices are commonly used as emissive display devices. Liquid crystal display (LCD) devices, which may be categorized as non-emissive display devices, are commonly used in notebook and desktop computers because of their high resolution, capability of displaying color images, and high quality image display.

[0005] A LCD module of the LCD device includes an LCD panel for displaying images to an exterior and a backlight unit for supplying light to the LCD panel. The LCD panel includes two substrates facing and spaced apart from each other, and a liquid crystal material interposed therebetween. Liquid crystal molecules of the liquid crystal material have a dielectric constant and refractive index anisotropic characteristics due to their long, thin shape. In addition, two electric field generating electrodes are formed on the two substrates, respectively. Accordingly, an orientation alignment of the liquid crystal molecules can be controlled by supplying a voltage to the two electrodes, wherein transmittance of the LCD panel is changed based on polarization properties of the liquid crystal material. However, since the LCD panel is a non-emissive-type display device, an additional light source is required. Thus, a backlight unit is disposed under the LCD panel, wherein the LCD device displays images using light produced by the backlight unit. In general, backlight units may be classified into two types according to a disposition of the light source, such as side-type and direct-type. As display areas of the LCD devices become increasingly larger, direct-type backlight units including a plurality of light sources have become commonly used to provide high brightness.

[0006] FIG. 1 is a schematic cross sectional view illustrating a backlight unit of an LCD module according to the related art.

[0007] In FIG. 1, an LCD module 1 includes a main support 14 supporting a LCD panel 2 of the LCD module 1,

a top case 10 covering the main support 14 and an edge of the LCD panel 2, and a backlight unit 30 under the LCD panel 2. The backlight unit 30 includes an optical element 31 and a light guide plate 24.

[0008] Upper and lower polarizers 42 and 40 are disposed on upper and lower surfaces of the LCD panel 2, respectively. Although not shown, the LCD panel 2 includes an upper substrate, a lower substrate facing the upper substrate, and a liquid crystal layer interposed between the upper and lower substrates, wherein the lower substrate includes a plurality of gate lines and a plurality of data lines having a matrix type, and a plurality of thin film transistors connected to each of the plurality of gate lines and plurality of data lines.

[0009] More specifically, the top case 10 is bent to cover sides of the main support 14 and the edge of the LCD panel 2, and the main support 14 and the top case 10 are combined by a screw (not shown). Although the main support 14 generally is formed as a mold type, it may further include a metallic material having a characteristic of protection against heat, such as aluminum (Al), with respect to a high brightness television or monitor. A backlight unit 30 is disposed under the main support 14 and includes a backlight lamp 20 as a light source, a lamp housing 16 covering the backlight lamp 20, a light guide plate 24 converting incident light from the lamp 20 into plane light, a reflector 26 on an backside of the light guide plate 24, and the optical element 31 over the light guide plate 24. The optical element 31 has a diffusion sheet 32, an upper prism sheet 36 and a lower prism sheet 34 sequentially laminated over the light guide plate 24. The LCD panel 2 is disposed over the optical element 31, wherein the LCD panel 2 is substantially disposed over the optical element 31 through a protrusion 14a of the support main 14.

[0010] The backlight lamp 20 includes, for example, a cold cathode fluorescent lamp (CCFL) and light emitting from the lamp 20 enters the light guide plate 24 through an incident surface defined as a side portion of the light guide plate 24.

[0011] The lamp housing 16 reflects light emitting from the backlight lamp 20 toward the incident surface of the light guide plate 24 because the lamp housing 16 includes a reflecting portion on an inner surface thereof. In addition, the light guide plate 24 is manufactured to have a sloped backside and a horizontal front side. The reflector 26 has a role of reducing light loss by reflecting light toward the light guide plate 24 such that incident light reflects through the backside of the light guide plate 24. As a result, when the light emitting from the backlight lamp 20 enters the light guide plate 24, the light is reflected with a predetermined angle on the sloped backside, thereby uniformly progressing with respect to an entire surface of the light guide plate 24. At this time, the light emitted to the lower and side surfaces of the light guide plate 24 enters toward the entire surface by reflecting to the reflector 26. In other words, the light emitting from the light guide plate 24 is diffused on an entire area by the diffusion sheet 32.

[0012] In addition, when the incident light is perpendicularly disposed with the LCD panel 2, light efficiency increases. Therefore, the upper and lower prism sheets 36 and 34, may be laminated as two pieces to be perpendicularly disposed with the angle of the light emitting from the

light guide plate **24** for the LCD panel **2** in order to increase light efficiency. The light through the diffusion sheet **32** may enter the LCD panel **2** through the upper and lower prism sheets **36** and **34**.

[0013] However, there is a gap A in an assembly structure of the mentioned backlight unit **30**, an interval between the optical element **31** and the LCD panel **2** forms the gap A.

[0014] As a result, the gap A leads to a bright line in a portion of the light guide plate **24** where light enters due to the sloped side of the optical element **31**. That is, the bright line is shown in the LCD panel **2** adjacent to the lamp **20**, wherein the bright line leads to problems such that brightness uniformity of the whole LCD panel **2** is reduced and the whole brightness is decreased. More particularly, in the case that the light guide plate **24** includes a prism pattern, the bright line phenomenon is exacerbated.

#### SUMMARY OF THE INVENTION

[0015] Accordingly, the present invention is directed to a backlight unit and a liquid crystal display device using a backlight unit that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

[0016] An object of the present invention is to provide a backlight unit that can be solved a bright line problem.

[0017] An advantage of the present invention is to provide a backlight unit having a high image quality.

[0018] Another advantage of the present invention is to provide an LCD having a backlight unit that can be used to solve a bright line problem.

[0019] Another advantage of the present invention is to provide an LCD using a backlight unit having a high image quality.

[0020] Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. These and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

[0021] To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described, a backlight unit for a liquid crystal display device includes: a lamp; a light guide plate adjacent to the lamp; a reflector under the light guide plate; a lamp housing covering the lamp, the lamp housing being combined with edges of the light guide plate and the reflector; and a housing pad under the lamp housing, the housing pad overlapping an edge of the lamp housing.

[0022] In another aspect, a liquid crystal display device using a backlight unit includes: a backlight unit including: a lamp; a light guide plate adjacent to the lamp; a reflector under the light guide plate; a lamp housing covering the lamp, the lamp housing being combined with edges of the light guide plate and the reflector; and a housing pad under the lamp housing, the housing pad overlapping an edge of the lamp housing; and a liquid crystal display panel over the backlight unit, the liquid crystal display panel including a first substrate, a second substrate facing the first substrate

and a liquid crystal layer interposed between the first substrate and the second substrate.

[0023] It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0024] The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention. In the drawings:

[0025] FIG. 1 is a schematic cross sectional view showing a backlight unit of an LCD module according to the related art.

[0026] FIG. 2 is a schematic cross sectional view showing a backlight unit of an LCD module according to the present invention.

#### DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

[0027] Reference will now be made in detail to embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

[0028] FIG. 2 is a schematic cross sectional view showing a backlight unit of an LCD module according to the present invention.

[0029] In FIG. 2, a backlight unit **130** includes a backlight lamp **120** as a light source, a light guide plate **124** converting the light emitting from the backlight lamp **120** into a plane light and disposed adjacent to an edge of the backlight lamp **120**, a reflector **126** reflecting the light from the light guide plate **124** to upper portion and disposed under the light guide plate **124**, and a lamp housing **116** covering the backlight lamp **120**, wherein edges of the light guide plate **124** and the reflector **126** are inserted in edges of the lamp housing **116** to attach with each other.

[0030] At least one optical element **131** is disposed over the light guide plate **124** and an LCD panel **102** attached over the optical element **131**. Upper and lower polarizers **142** and **140** are also over the optical element **131**. The optical element **131** may include a diffusion sheet **132**, an upper prism sheet **136** and a lower prism sheet **134**. An edge of the LCD panel **102** is disposed in a main support **114** over the lamp housing **116** and another edge of the LCD panel **102** is covered by a top case **110**.

[0031] It is noted that the backlight unit **130** further includes a housing pad **160** between the lamp housing and a bottom case **150**, wherein the housing pad **160** pushes up the lamp housing **116** corresponding to a portion of the light guide plate **124** in which light enters. The housing pad **160** can reduce a gap B between the LCD panel **102** and the optical element **131**. For example, the housing pad **160** may include a tape that is attached to the lamp housing **116** and may have a plate shape.

[0032] In other words, the housing pad **160** may be utilized to remove the gap B between the LCD panel **102** and

the optical element **131** by being inserted between the lamp housing **116** and the bottom case **150**. Therefore, a bright line due to the gap **B** between the LCD panel **102** and the optical element **131** can be effectively reduced.

[0033] For example, the housing pad **160** may include a polyethylene terephthalate (PET) material and a thickness of the housing pad **160** is about 0.1 millimeter. Further, the housing pad **160** may be manufactured in various sizes and shapes and inserted between the bottom case **150** and the lamp housing **116**. More specifically, the housing pad **160** may be inserted between the bottom case **150** and a backside edge of the lamp housing **116**.

[0034] The LCD panel **2**, the backlight unit **130**, the top case **110** and the bottom case **150** form a LCD module **100** which may be referred as an LCD device.

[0035] According to the present invention, a backlight unit **130** and an LCD using a backlight unit does not experience the bright line phenomenon when a housing pad is added between the lamp housing **116** and the bottom case **150**.

[0036] Although not shown, the LCD panel includes a first substrate, a second substrate facing the first substrate, and a liquid crystal layer interposed between the first and second substrates.

[0037] Additionally, a simple process of the backlight unit and a LCD using the same is accomplished without modifying the driving method and the structure thereof, thereby improving productivity in accordance with reduction of a defect rate.

[0038] It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A backlight unit for a liquid crystal display device, comprising:

- a lamp;
- a light guide plate adjacent to the lamp;
- a reflector under the light guide plate;
- a lamp housing covering the lamp, the lamp housing being combined with edges of the light guide plate and the reflector; and
- a housing pad under the lamp housing, the housing pad overlapping an edge of the lamp housing.

2. The backlight unit according to claim 1, wherein the housing pad includes a polyethylene terephthalate material.

3. The backlight unit according to claim 1, wherein the housing pad includes a tape attached to the lamp housing.

4. The backlight unit according to claim 1, wherein a thickness of the housing pad is greater than about 0.1 millimeter.

5. The backlight unit according to claim 1, wherein the housing pad has a plate shape.

6. The backlight unit according to claim 1, further comprising:

- at least one optical sheet over the light guide plate;
- a main support over the lamp housing;
- a bottom case covering the lamp housing; and
- a top case over the main support, wherein the top case is combined with the bottom case over the main support.

7. The backlight unit according to claim 6, wherein the housing pad is disposed between the lamp housing and the bottom case.

8. A liquid crystal display device using a backlight unit, comprising:

- a backlight unit including:
  - a lamp;
  - a light guide plate adjacent to the lamp;
  - a reflector under the light guide plate;
  - a lamp housing covering the lamp, the lamp housing being combined with edges of the light guide plate and the reflector; and
  - a housing pad under the lamp housing, the housing pad overlapping an edge of the lamp housing; and
  - a liquid crystal display panel over the backlight unit, the liquid crystal display panel including a first substrate, a second substrate facing the first substrate and a liquid crystal layer interposed between the first substrate and the second substrate.

9. The device according to claim 8, wherein the housing pad includes a polyethylene terephthalate material.

10. The device according to claim 8, wherein the housing pad includes a tape attached to the lamp housing.

11. The device according to claim 8, wherein a thickness of the housing pad is greater than about 0.1 millimeter.

12. The device according to claim 8, wherein the housing pad has a plate shape.

13. The device according to claim 8, further comprising at least one optical sheet over the light guide plate, a main support over the lamp housing, a top case covering the main support and an edge of the liquid crystal panel, and a bottom case being combined with the top case and covering the lamp housing.

14. The device according to claim 13, wherein the housing pad is disposed between the lamp housing and the bottom case.

\* \* \* \* \*

专利名称(译)	背光单元和使用其的液晶显示装置		
公开(公告)号	<a href="#">US20050243573A1</a>	公开(公告)日	2005-11-03
申请号	US11/117288	申请日	2005-04-29
[标]申请(专利权)人(译)	金东小号 LIM JIN SEOB		
申请(专利权)人(译)	金东小号 LIM JIN-SEOB		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	KIM DONG SOO LIM JIN SEOB		
发明人	KIM, DONG SOO LIM, JIN-SEOB		
IPC分类号	G02F1/13357 F21V8/00 G02B6/00 G02F1/13 G02F1/1335		
CPC分类号	G02B6/0031 G02B6/0086 G02F2201/54 G02F1/133308 G02F1/1336 G02B6/0088		
优先权	1020040030588 2004-04-30 KR		
其他公开文献	US7585099		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

一种用于液晶显示装置的背光单元，包括：灯；与灯相邻的导光板；导光板下方的反射器；灯壳覆盖灯，灯壳与导光板和反射器的边缘结合；并且灯壳下方的壳体垫，壳体垫与灯壳的边缘重叠。

