



US008228459B2

(12) **United States Patent**
Hong

(10) **Patent No.:** **US 8,228,459 B2**
(45) **Date of Patent:** **Jul. 24, 2012**

(54) **BACKLIGHT UNIT AND LIQUID CRYSTAL DISPLAY DEVICE HAVING THE SAME**

(75) Inventor: **Bongtaek Hong**, Cheongju-si (KR)

(73) Assignee: **LG Electronics Inc.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 337 days.

(21) Appl. No.: **12/599,119**

(22) PCT Filed: **Dec. 27, 2007**

(86) PCT No.: **PCT/KR2007/006876**

§ 371 (c)(1),

(2), (4) Date: **Nov. 6, 2009**

(87) PCT Pub. No.: **WO2008/150057**

PCT Pub. Date: **Dec. 11, 2008**

(65) **Prior Publication Data**

US 2010/0220256 A1 Sep. 2, 2010

(30) **Foreign Application Priority Data**

Jun. 4, 2007 (KR) 10-2007-0054545

(51) **Int. Cl.**

G02F 1/1333 (2006.01)

F21V 7/04 (2006.01)

(52) **U.S. Cl.** **349/58**; 349/56; 349/61; 362/608; 362/97.1

(58) **Field of Classification Search** 349/56, 349/61, 62, 65, 57, 58, 59, 60, 64, 112; 362/97.1, 362/97.2, 97.3, 97.4, 608

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,241,358	B1	6/2001	Higuchi et al.	
6,469,755	B1	10/2002	Adachi et al.	
7,581,845	B2 *	9/2009	Lee	362/97.2
2002/0021563	A1	2/2002	Ohsumi	
2002/0197051	A1	12/2002	Tamura et al.	
2003/0137821	A1	7/2003	Gotoh et al.	
2003/0179566	A1	9/2003	Ito	
2003/0179580	A1	9/2003	Ito et al.	
2006/0044779	A1 *	3/2006	Lee	362/29
2006/0061705	A1	3/2006	Onishi	
2006/0103774	A1 *	5/2006	Han et al.	349/58
2006/0291065	A1 *	12/2006	Hasei et al.	359/619
2010/0220256	A1 *	9/2010	Hong	349/58

(Continued)

FOREIGN PATENT DOCUMENTS

JP 7-333442 12/1995

(Continued)

OTHER PUBLICATIONS

Taiwanese Office Action dated Nov. 23, 2011 issued in Application No. 97102283 (with English translation).

(Continued)


Primary Examiner — Brian Healy

(74) *Attorney, Agent, or Firm* — KED & Associates LLP

(57) **ABSTRACT**

A backlight unit and liquid crystal display device comprising the backlight unit is disclosed. A backlight unit comprises a light source, an optical sheet where light from the light source is incident, a frame surrounding an edge portion of the optical sheet; and at least one sheet holder disposed at a bottom part of the frame facing the optical sheet.

20 Claims, 7 Drawing Sheets



US 8,228,459 B2

Page 2

U.S. PATENT DOCUMENTS

2010/0283937 A1 * 11/2010 Takeba 349/61
2010/0290211 A1 * 11/2010 Takeba 362/97.1

FOREIGN PATENT DOCUMENTS

JP 2004-38108 2/2004
JP 2006-024429 1/2006
JP 2006-278251 10/2006
JP 2007-123086 5/2007
KR 1998-064332 11/1998
KR 10-2004-00376 06 5/2004


KR 2005-0030397 3/2005
KR 10-2005-0065116 6/2005
TW 200408882 A 6/2004
TW I230238 B 4/2005

OTHER PUBLICATIONS


International Search Report dated Mar. 24, 2008.
Korean Office Action dated Feb. 29, 2008.
Korean Notice of Allowance dated Nov. 26, 2008.

* cited by examiner


[FIG. 1]




[FIG. 2]




[FIG. 3]




[FIG. 4]




[FIG. 5]




[FIG. 6]




[FIG. 7]




[FIG. 8]




[FIG. 9]




[FIG. 10]




[FIG. 11]



[FIG. 12]



[FIG. 13]



BACKLIGHT UNIT AND LIQUID CRYSTAL DISPLAY DEVICE HAVING THE SAME

TECHNICAL FIELD

This document relates to a backlight unit and a liquid crystal display device having the same.

BACKGROUND ART

Liquid crystal display device, which is a passive display device, comprises a backlight unit installed under a liquid crystal panel.

Backlight unit comprises a light source, an optical sheet, a frame, a bottom cover, etc. in a single module form and can provide light to a liquid crystal panel.

In the backlight unit, the light source receives a voltage from an external driving power source and emits light, however, can emit a heat incidentally. The heat emitted from the light source causes a thermal expansion of the optical sheet adjacent to the light source.

In consideration of the thermal expansion of the optical sheet, a frame surrounding an edge portion of the optical sheet can be spaced a predetermined distance apart from the optical sheet.

DISCLOSURE OF INVENTION

Technical Problem

The optical sheet may be partially subjected to non-uniform thermal expansion because a heat emitted from the light source may be non-uniform at each part of the optical sheet.

This leads to occurrence of a deformation of the optical sheet caused by a heat emitted from the light source. For example, wrinkles may occur.

Technical Solution

An aspect of this document is to provide a backlight unit and liquid crystal display device comprising the backlight unit capable of preventing a deformation of optical sheet and capable of improving the quality

In an aspect, a backlight unit comprises a light source, an optical sheet where light from the light source is incident, a frame surrounding an edge portion of the optical sheet, and at least one sheet holder disposed at a bottom part of the frame facing the optical sheet.

In another aspect, a liquid crystal display device, comprises a light source, an optical sheet where light emitted from the light source is incident, a frame surrounding an edge portion of the optical sheet, at least one sheet holder disposed at a bottom part of the frame facing the optical sheet and a liquid crystal display panel disposed on the frame.

Advantageous Effects

This document is to provide a backlight unit and liquid crystal display device comprising the backlight unit capable of preventing a deformation of optical sheet and capable of improving the quality

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an exploded perspective view illustrating a construction of a backlight unit in accordance with an exemplary embodiment of the present invention.

FIG. 2 is a cross section taken along line II-II' of FIG. 1;

FIGS. 3 to 9 are views illustrating a sheet holder in detail in accordance with an exemplary embodiment of the present invention;

FIG. 10 is an exploded perspective view illustrating a construction of a backlight unit in accordance with an exemplary embodiment of the present invention;

FIG. 11 is a cross section taken along line VIII-VIII' of FIG. 10;

FIG. 12 is an exploded perspective view illustrating a construction of a liquid crystal display device in accordance with an exemplary embodiment of the present invention; and

FIG. 13 is a cross section taken along line X-X' of FIG. 12.

BEST MODE FOR CARRYING OUT THE INVENTION

FIG. 1 is an exploded perspective view illustrating a construction of a backlight unit in accordance with an exemplary embodiment of the present invention. FIG. 2 is a cross section taken along line II-II' of FIG. 1.

FIGS. 1 and 2 show an edge type backlight unit. However, this is to describe a backlight unit according to an exemplary embodiment of the present invention and hence, is not intended to limit the scope of the present invention.

Referring to FIGS. 1 and 2, the backlight unit 110 can be comprised in a liquid crystal display device. The backlight unit 110 can provide light to a liquid crystal panel comprised in the liquid crystal display device.

The backlight unit 110 can comprise a light source 120, an optical sheet 130, a frame 140, and a sheet holder 150a. The backlight unit 110 can further comprise a bottom cover 160, a reflector plate 170, and a light guide plate 180.

The light source 120 can receive a voltage applied from an external driving power source, generating and emitting light.

The light source 120 can be formed one or more at one side of the light guide plate 180 along an X-axis direction that is a long-axis direction of the light guide plate 180, or can be formed one or more at each of both sides of the light guide plate 180 along the X-axis direction. Light emitted from the light source 120 can be directly incident inside the light guide plate 180, or can be incident inside the light guide plate 180 after being reflected from a light source housing 122.

The light source 120 can be at least one of, but not limited to, Cold Cathode Fluorescent Lamp (CCFL), Hot Cathode Fluorescent Lamp (HCFL), External Electrode Fluorescent Lamp (EEFL), and Light Emitting Diode (LED)

The optical sheet 130 is disposed over the light guide plate 180, and can improve optical characteristics of the light, for example, a luminance and a viewing angle, by diffusing and concentrating light emitted from the light source 120.

For example, the optical sheet 130 can be configured to have a structure where a diffuser sheet 132, a first prism sheet 134, and a second prism sheet 136 are laminated in regular sequence. However, this is not intended to limit the scope of the present invention since the number of the optical sheet 130 can be different depending on a specification of the backlight unit 110. For example, a protector sheet or a reflective polarization film can be additionally disposed over the second prism sheet 136. The optical sheet 130 can be configured with one or more sheets. A laminated sequence of the optical sheet 130 is not also limited to the above.

The frame 140 is formed in an approximately square shape, and can be disposed in the outermost of constituent elements of the backlight unit 110 to surround an edge portion of the optical sheet 130. The frame 140 can be combined with the bottom cover 160 in a top down manner.

The frame **140** can be formed of, for example, polycarbonate through injection molding, but this is not intended to limit the scope of the present invention. For example, the frame **140** can be at least one of epoxy, polyurethane, and polyacrylate.

The sheet holder **150a** can be disposed at a bottom part of the frame **140** facing the optical sheet **130**. The sheet holder **150a** is formed along a long-axis or short-axis edge portion of the frame **140**, and can be formed one or more. The sheet holder **150a** can hold the optical sheet **130** by pressing the optical sheet **130** in Z-axis direction. Specifically, the sheet holder **150a** can hold the second prism sheet **136** disposed in the uppermost of the optical sheet **130**. Of the optical sheet **130**, the diffuser sheet **132** and the first prism sheet **134** disposed under the second prism sheet **136** are not in direct contact with the sheet holder **150a**, but can be held as the sheet holder **150a** presses the second prism sheet **136**.

The sheet holder **150a** can hold the optical sheet **130**, preventing a deformation of the optical sheet **130** caused by a heat radiated from the light source **120**. For example, wrinkles, etc. can be prevented.

The sheet holder **150a** will be described in more detail with reference to FIGS. 3 and 9.

FIG. 3 is a view illustrating a sheet holder in detail in accordance with an exemplary embodiment of the present invention. FIG. 3 shows an example in which the sheet holder is formed along a long-axis edge portion of the optical sheet. The sheet holder can be formed along a long-axis or short-axis edge portion of the optical sheet. A case where the sheet holder is formed along the short-axis edge portion of the optical sheet is similar with a case where the sheet holder is formed along the long-axis edge portion of the optical sheet. Hence, a detailed description of the case where the sheet holder is formed along the short-axis edge portion of the optical sheet will be omitted. FIGS. 3 and 4 show only the second prism sheet disposed in the uppermost of the optical sheet for description convenience.

Referring to FIGS. 3 and 4, the sheet holder **150a** can be formed integrally with the frame **140**. The sheet holder **150a** can be additionally formed of the same material of the frame **140** at the time of injection molding of the frame **140** because the frame **140** can be formed through injection molding.

The backlight unit can have the sheet holder **150a** of a dot type, but this is not intended to limit the scope of the present invention. In detail, the backlight unit can also have a different type of sheet holder including a bar type sheet holder **150b**. The bar type sheet holder **150b** and the dot type sheet holder **150a** all are to prevent a deformation of the optical sheet, and are merely different in shape only. Thus, only the dot type sheet holder will be described below. This description is identically applicable also to the optical sheet with the bar type sheet holder.

The sheet holder **150a** can be formed one or more at a bottom part of the frame **140** facing an edge portion of the second prism sheet **136** along an X-axis direction that is a long-axis direction of the second prism sheet **136**.

The sheet holder **150a** can get in contact with a long-axis edge portion of the second prism sheet **136** discontinuously or continuously. For example, the sheet holder **150a** can get in contact with the long-axis edge portion of the second prism sheet **136** by point contact or line contact.

A shape of the sheet holder **150a** can be at least one of a semisphere, a semiellipsoid, and a polyhedron, but this is not intended to limit the scope of the present invention.

A height (H) of the sheet holder **150a** can be within a range of about 100 μm to 800 μm , in more detail, 150 μm to 400 μm . In a case where the height (H) of the sheet holder **150a** is 100 μm or more, a foreign substance can be prevented to the

maximum from being introduced between the frame **140** and the second prism sheet **136** through between the sheet holder **150a** within limits in which a deformation of the second prism sheet **136** caused by a heat can be prevented. Also, in a case where the height (H) of the sheet holder **150a** is 800 μm or less, a deformation of the second prism sheet **136** can be suppressed to the maximum within limits in which a foreign substance can be prevented from being introduced between the frame **140** and the second prism sheet **136** through between the sheet holder **150a**.

The height (H) of the sheet holder **150a** can be constant along the long-axis edge portion of the second prism sheet **136** within the above range.

An interval (Ls) between the sheet holders **150a** can be about 0.01 to 0.1 times, in more detail, 0.02 to 0.05 times of a long-axis length (Lx) of the frame **140**. This is to effectively prevent a deformation of the second prism sheet **136** by getting the interval (Ls) between the sheet holders **150a** to be within the above range, because the sheet holder **150a** does not get in continuous contact with the second prism sheet **136**.

The interval (Ls) between the sheet holders **150a** can be constant along the long-axis edge portion of the second prism sheet **136** within the above range.

As described above, the sheet holder **150a** is disposed between the frame **140** and the optical sheet **130** such that it can hold the optical sheet **130** by pressing the second prism sheet **136** disposed in the uppermost of the optical sheet **130**. This leads to preventing a deformation of the optical sheet **130** caused by a heat, improving a display quality of the backlight unit **110** and the liquid crystal display device comprising the backlight unit **110**.

FIGS. 5 and 6 are views illustrating a sheet holder in detail according to an exemplary embodiment of the present invention. FIGS. 5 and 6 show an example in which the sheet holder is formed along a long-axis edge portion of a frame. The sheet holder can be formed along a long-axis or short-axis edge portion of the frame. A case where the sheet holder is formed along the short-axis edge portion of the frame is similar with a case where the sheet holder is formed along the long-axis edge portion of the frame. Hence, a detailed description of the case where the sheet holder is formed along the short-axis edge portion of the frame will be omitted. The sheet holder shown in FIGS. 5 and 6 is identical with the sheet holder shown in FIGS. 3 and 4 excepting that its height is variable depending on position. Thus, a repeated description will be omitted, and its feature only will be described. FIGS. 5 and 6 show only a second prism sheet disposed in the uppermost of an optical sheet for description convenience.

Referring to FIGS. 5 and 6, a height (H) of the sheet holder **150a** according to an exemplary embodiment of the present invention can be within a range of about 100 μm to 800 μm , in detail, 150 μm to 400 μm .

The height (H) of the sheet holder **150a** is variable depending on a long-axis edge portion of the prism within the above range. For example, the height (H) of the sheet holder **150a** can become greater within the above range as the sheet holder goes from terminal end of the frame's edge portions toward the center part thereof, but this is not intended to limit the scope of the present invention.

By varying the height (H) of the sheet holder **150a** as above, a deformation of the optical sheet can be effectively prevented when the optical sheet is partially subjected to non-uniform thermal expansion.

FIGS. 7 and 8 are views illustrating a sheet holder in detail according to an exemplary embodiment of the present invention. FIGS. 7 and 8 show an example in which the sheet holder is formed along a long-axis edge portion of a frame. The sheet

holder can be formed along a long-axis or short-axis edge portion of the frame. A case where the sheet holder is formed along the short-axis edge portion of the frame is similar with a case where the sheet holder is formed along the long-axis edge portion of the frame. Hence, a detailed description of the case where the sheet holder is formed along the short-axis edge portion of the frame will be omitted. The sheet holder shown in FIGS. 7 and 8 is identical with the sheet holder shown in FIGS. 3 and 4 excepting that an interval between the sheet holders is variable depending on position. Thus, a repeated description will be omitted, and its feature only will be described. FIGS. 7 and 8 show only a second prism sheet disposed in the uppermost of an optical sheet for description convenience.

Referring to FIGS. 7 and 8, an interval (Ls) between the sheet holders 150a can be about 0.01 to 0.1 times, in more detail, 0.02 to 0.05 times of a long-axis length (Lx) of the frame 140.

The interval (Ls) between the sheet holders 150a is variable along a long-axis edge portion of the frame within the above range. For example, the length (Ls) between the sheet holders 150a can become greater within the above range as the sheet holder goes from terminal end of the frame's edge portion toward the center part thereof, but this is not intended to limit the scope of the present invention.

By varying the length (Ls) between the sheet holders 150a as above, a deformation of the optical sheet can be effectively prevented when the optical sheet is partially subjected to non-uniform thermal expansion.

FIG. 9 is a view illustrating a sheet holder in detail according to an exemplary embodiment of the present invention. FIG. 9 shows a case where the sheet holder is formed along a long-axis edge portion of a frame. The sheet holder can be formed along a long-axis or short-axis edge portion of the frame. A case where the sheet holder is formed along the short-axis edge portion of the frame is similar with a case where the sheet holder is formed along the long-axis edge portion of the frame. Hence, a detailed description of the case where the sheet holder is formed along the short-axis edge portion of the frame will be omitted. The sheet holder shown in FIG. 9 is identical with the above description excepting that the sheet holder is attached to the frame by an adhesive member. Thus, a repeated description will be omitted, and its feature only will be described. FIG. 9 shows only a second prism sheet disposed in the uppermost of an optical sheet for description convenience.

Referring to FIG. 9, the sheet holder 150c according to an exemplary embodiment of the present invention can be attached to the frame 140 by the adhesive member 152, for example, an adhesive and a both-sided adhesive tape. A substance of the sheet holder 150c can be identical or different from a substance of the frame 140. In detail, the substance of the sheet holder 150c can be at least one of epoxy, polyurethane, polycarbonate, and polyacrylate.

The height (H) of the sheet holder 150c can be within a range of about 100 μ m to 800 μ m, in more detail, 150 μ m to 400 μ m. The height (H) of the sheet holder 150c is constant or variable depending on the long-axis edge portion of the prism within the above range.

The interval (Ls) between the sheet holders 150c can be about 0.01 to 0.1 times, in more detail, 0.02 to 0.05 times of the long-axis length (Lx) of the frame 140. The interval (Ls) between the sheet holders 150c is constant or variable along the long-axis edge portion of the frame within the above range.

Referring again to 1 and 2, the bottom cover 160 can comprise a bottom part 162 and a side part 164 formed to

extend from the bottom part 162, providing a housing space. The housing space can house the light source 120 and the optical sheet 130. Also, the bottom cover 160 can house the reflector plate 170 and the light guide plate 180 in the housing space. The reflector plate 170 is disposed under the light guide plate 180 and can upwardly reflect light emitted downwardly via the light guide plate 180 among light emitted from the light source 120.

The light guide plate 180 is disposed to face the light source 120 and can guide light incident from the light source 120 such that the light can be emitted upwardly.

FIG. 10 is an exploded perspective view illustrating a construction of a backlight unit in accordance with an exemplary embodiment of the present invention. FIG. 11 is a cross section taken along line VIII-VIII' of FIG. 10.

FIGS. 10 and 11 show a direct type backlight unit. However, this is to describe a backlight unit according to an exemplary embodiment of the present invention, hence, is not intended to limit the scope of the present invention. The backlight unit shown in FIGS. 10 and 11 is similar with the backlight unit shown in FIGS. 1 and 2 excepting that a disposition of the light source is different. Thus, a repeated description will be omitted, and its feature only will be described.

Referring to FIGS. 10 and 11, the backlight unit 210 according to an exemplary embodiment of the present invention can be comprised in a liquid crystal display device. The backlight unit 210 can provide light to a liquid crystal panel comprised in the liquid crystal display device.

The backlight unit 210 can comprise a light source 220, an optical sheet 230, a frame 240, and a sheet holder 250a. The backlight unit 210 can further comprise a bottom cover 260, a reflector plate 270, and a diffuser plate 280.

The light source 220 can receive a voltage applied from an external driving power source, generating and emitting light. The light source 220 can be formed one or more under the diffuser plate 280. Light emitted from the light source 220 can be directly incident on the diffuser plate 280.

The optical sheet 230 is disposed over the diffuser plate 280, and can improve optical characteristics of the light, for example, a luminance and a viewing angle by diffusing and concentrating light emitted from the light source 220.

For example, the optical sheet 230 can be configured to have a structure where three sheets, i.e., a diffuser sheet 232, a first prism sheet 234, and a protective sheet 236 are laminated in regular sequence. However, this is not intended to limit the number and a laminated sequence of the optical sheet 230. And 236 can be not the protective sheet, but a brightness enhancement sheet.

The frame 240 is formed in an approximately square shape, and can be disposed in the outermost of constituent elements of the backlight unit 210 to surround an edge portion of the optical sheet 230.

The sheet holder 250a can be disposed at a bottom part of the frame 240 facing the optical sheet 230. The sheet holder 250a is formed along a long-axis or short-axis edge portion of the frame 240, and can be formed one or more. The sheet holder 250a can hold the optical sheet 230, specifically, the second prism sheet 236 disposed in the uppermost of the optical sheet 230 by pressing the optical sheet 230 in Z-axis direction.

The sheet holder 250a can prevent a deformation of the optical sheet 230 caused by a heat radiated from the light source 220 as holding the optical sheet 230. For example, wrinkles, etc. can be prevented. As a result, a display quality of the backlight unit 210 and the liquid crystal display device comprising the backlight unit 210 can be improved.

The diffuser plate **280** is disposed between the light source **220** and the optical sheet **230** and can upwardly diffuse light incident from the light source **220**.

FIG. **12** is an exploded perspective view illustrating a construction of a liquid crystal display device in accordance with an exemplary embodiment of the present invention. FIG. **13** is a cross section taken along line XX' of FIG. **12**.

FIGS. **12** and **13** show the backlight unit shown in FIGS. **1** and **2** as a backlight unit of the liquid crystal display device. However, this is to describe the liquid crystal display device comprising the backlight unit according to an exemplary embodiment of the present invention and hence, is not intended to limit the scope of the present invention. Thus, the liquid crystal display device comprising the backlight unit shown in FIGS. **10** and **11** makes no difference. The backlight unit shown in FIGS. **12** and **13** is the same as described above. Hence, a repeated description will be omitted and its feature only will be described.

Referring to FIGS. **12** and **13**, the liquid crystal display device **300** displays an image using electro optic characteristics of liquid crystal.

The liquid crystal display device **300** can comprise a backlight unit **110** and a liquid crystal panel **310**.

The backlight unit **110** can be installed under a liquid crystal panel **310** and can provide light to the liquid crystal panel **310**.

The backlight unit **110** can comprise a light source **120**, an optical sheet **130**, a frame **140**, and a sheet holder **150a**. The backlight unit **110** can further comprise a bottom cover **160**, a reflector plate **170**, and a light guide plate **180**.

The liquid crystal panel **310** is disposed over the frame **140** and can be fixed by a top cover **320** combined with a bottom cover **160** in a top down manner.

The liquid crystal panel **310** can display an image using light radiated from the light source **120** of the backlight unit **110**.

The liquid crystal panel **310** can comprise a color filter substrate **312** and a thin film transistor substrate **314** that face each other, interposing a liquid crystal.

The color filter substrate **312** can realize a color of an image displayed through the liquid crystal panel **310**.

The color filter substrate **312** can comprise a color filter array formed as a thin film on a transparent substrate, for example, red/green/blue color filters. An upper polarization plate can be disposed over the color filter substrate **312**.

The thin film transistor substrate **314** can electrically connect with a printed circuit board **318** where a plurality of circuit parts are mounted through a driving film **316**. The thin film transistor substrate **314** applies a driving voltage from the printed circuit board **318** to a liquid crystal in response to a driving signal from the printed circuit board **318**.

The thin film transistor substrate **314** can comprise a thin film transistor and a pixel electrode formed as a thin film on a different substrate of a transparent material such as glass or plastic.

A lower polarization plate can be attached to a bottom part of the thin film transistor substrate **314**.

The invention claimed is

1. A backlight unit, comprising:

a light source;
an optical sheet to pass light from the light source;
a frame surrounding an edge portion of the optical sheet;
and
at least one sheet holder coupled to the frame and in contact with a top surface of the optical sheet.

2. The backlight unit of claim 1, wherein the sheet holder is either a bar type or a dot type.

3. The backlight unit of claim 1, wherein the sheet holder extends from a portion of the frame that at least partially overlaps the optical sheet, the sheet holder extending in a direction toward the top surface of the optical sheet to contact the top surface of the optical sheet.

4. The backlight unit of claim 1, wherein the sheet holder is made at least one of epoxy, polyurethane, polycarbonate, or polyacrylate.

5. The backlight unit of claim 2, wherein a shape of the sheet holder of the dot type is at least one of a semisphere, a semiellipsoid, or a polyhedron.

6. A backlight unit of comprising:

a light source;
an optical sheet to pass light from the light source;
a frame surrounding an edge portion of the optical sheet;
and
at least one sheet holder coupled to the frame, wherein a height of the sheet holder is substantially 100 to 800 μm .

7. The backlight unit of claim 1, wherein a height of the sheet holder is substantially constant.

8. The backlight unit of claim 7, wherein a height of the sheet holder changes over a length of the frame.

9. A backlight unit comprising:

a light source;
an optical sheet to pass light from the light source;
a frame surrounding an edge portion of the optical sheet;
and
a plurality of sheet holders coupled to the frame and facing the optical sheet,
wherein an interval between the sheet holders is substantially 0.01 to 0.1 times a length of the frame.

10. The backlight unit of claim 1, further comprising:

a plurality of sheet holders coupled to the frame,
wherein an interval between the sheet holders is substantially constant.

11. A backlight unit comprising:

a light source;
an optical sheet to pass light from the light source;
a frame surrounding an edge portion of the optical sheet;
and
a plurality of sheet holders coupled to the frame, wherein intervals between adjacent ones of the sheet holders change over a length of the frame.

12. A liquid crystal display device, comprising:

an optical sheet to pass light from the light source;
a frame surrounding an edge portion of the optical sheet;
at least one sheet holder coupled to the frame and in contact with a top surface of the optical sheet; and
a liquid crystal display panel coupled to the frame.

13. The liquid crystal display device of claim 12, wherein the sheet holder is either a bar type or a dot type.

14. The liquid crystal display device of claim 12, wherein the sheet holder extends from a portion of the frame that at least partially overlaps the optical sheet, the sheet holder extending in a direction toward the top surface of the optical sheet to contact the top surface of the optical sheet.

15. The liquid crystal display device of claim 12, wherein the sheet holder is made at least one of epoxy, polyurethane, polycarbonate, or polyacrylate and is attached at the frame.

16. The liquid crystal display device of claim 13, wherein a shape of the sheet holder of the dot type is at least one of a semisphere, a semiellipsoid, or a polyhedron.

17. A liquid crystal display device comprising:

an optical sheet to pass light from the light source;
a frame surrounding an edge portion of the optical sheet;
at least one sheet holder coupled to the frame and facing the optical sheet and

9

a liquid crystal display panel coupled to the frame, wherein a height of the sheet holder is substantially 100 to 800 μm .

18. The liquid crystal display device of claim **12**, wherein a height of the sheet holders is substantially constant.

19. A liquid crystal display device comprising:
an optical sheet to pass light from the light source;
a frame surrounding an edge portion of the optical sheet;
a plurality of sheet holders coupled to the frame; and

10

a liquid crystal display panel coupled to the frame, wherein intervals between adjacent ones of the sheet holders is substantially 0.01 to 0.1 times a length of the frame.

20. The liquid crystal display device of claim **12**, further comprising:

a plurality of sheet holders,
wherein an interval between the sheet holders is substantially constant.

* * * * *

专利名称(译)	背光单元和具有该背光单元的液晶显示装置		
公开(公告)号	US8228459	公开(公告)日	2012-07-24
申请号	US12/599119	申请日	2007-12-27
[标]申请(专利权)人(译)	HONG BONGTAEK		
申请(专利权)人(译)	HONG BONGTAEK		
当前申请(专利权)人(译)	LG电子株式会社.		
[标]发明人	HONG BONGTAEK		
发明人	HONG, BONGTAEK		
IPC分类号	G02F1/1333 F21V7/04		
CPC分类号	G02B6/0088 G02F1/1336 G02B6/005 G02F1/133608 G02F2001/133317		
审查员(译)	希利, 布瑞恩		
优先权	1020070054545 2007-06-04 KR		
其他公开文献	US20100220256A1		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种背光单元和包括该背光单元的液晶显示装置。背光单元包括光源, 来自光源的光入射的光学片, 围绕光学片的边缘部分的框架;至少一个纸张支架设置在框架的面向光学片的底部。

