

(43) **Pub. Date:** **Jan. 11, 2007**




FIG. 1
(PRIOR ART)




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7B




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32





FIG. 33



LIQUID CRYSTAL DISPLAY APPARATUS

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application is a divisional application of U.S. patent application Ser. No. 10/114,639, filed on Apr. 2, 2002, the disclosure of which is herein incorporated by reference in its entirety.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The present invention relates to a liquid crystal display apparatus, and more particularly to a liquid crystal display apparatus in which a liquid crystal display module is tightly combined with cases, which is available for a notebook computer.

[0004] 2. Description of the Related Art

[0005] Recently, information processors have been rapidly developed in a trend with various architectures, functions and faster information processing speed. Such information processors need display devices such as a liquid crystal display apparatus for displaying processed information to a user.

[0006] When a voltage is applied to a liquid crystal cell, a molecular arrangement of the liquid crystal is changed. The liquid crystal display device converts variations in optical characteristics such as a birefringence, a rotatory polarization, a dichroism and a light scattering according to the molecular arrangements of the liquid crystal into variations in visual characteristics, thereby displaying an image.

[0007] A size of the liquid crystal display apparatus gradually increases according to a demand of the user, and a liquid crystal display module and cases for receiving the liquid crystal display module also have dimensions that gradually increase in response to the size of the liquid crystal display apparatus. Thus, research concerning not only an assembled structure between the liquid crystal display module and cases but also a layout for parts of the liquid crystal display apparatus is performed so as to meet an augmentation of the dimension of the liquid crystal display apparatus and reductions of a weight, a size and a thickness of the liquid crystal display apparatus in these days.

[0008] In particular, a combining space according to a combination of the liquid crystal display module and cases becomes more important as for an installation structure between the liquid crystal display module and cases.

[0009] FIG. 1 is an exploded perspective view schematically showing a conventional liquid crystal display apparatus.

[0010] Referring to FIG. 1, a liquid crystal display apparatus 60 has a liquid crystal display module 30, for displaying an image, and cases including a front case (not shown) and a rear case 40 in order to receive the liquid crystal display module 30.

[0011] The liquid crystal display module 30 includes a display unit for displaying the image, a back light assembly for supplying a light to the display unit, a mold frame for receiving the display unit and the back light assembly, and a top chassis combining with the mold frame to fix the

display unit and the back light assembly to the mold frame. When the back light assembly and the display unit are successively received in the mold frame, the top chassis combines with the mold frame.

[0012] A top installation method is utilized for mounting the liquid crystal display module 30 in the rear case 40. Particularly, first, second, third, and fourth mounting portions 11, 12, 13 and 14 having predetermined heights are formed on four corners of the top chassis 10 of the liquid crystal display module 30. First, second, third and fourth screwed combining holes 11a, 12a, 13a and 14a are formed through the first, second, third and fourth mounting portions 11, 12, 13 and 14, respectively. First, second, third and fourth burrings 41, 42, 43 and 44 corresponding to the first, second, third and fourth screwed combining holes 11a, 12a, 13a and 14a are formed on four corners of the rear case 40 corresponding to the first, second, third and fourth mounting portions 11, 12, 13 and 14.

[0013] When the first, second, third and fourth screwed combining holes 11a, 12a, 13a and 14a of the top chassis 10 correspond to the first, second, third and fourth burrings 41, 42, 43 and 44 of the rear case 40, respectively, first, second, third and fourth screws 11b, 12b, 13b and 14b engage with the first, second, third and fourth screwed combining holes 11a, 12a, 13a and 14a and the first, second, third and fourth burrings 41, 42, 43 and 44, thereby fixing the liquid crystal display module 30 to the rear case 40.

[0014] The top installation method, however, has some disadvantages as follows.

[0015] First, the number of assembling steps for fabrication of the liquid crystal display apparatus 60 increases since the liquid crystal display module 30 is combined with the cases using the screws. Hence, productivity as well as operation efficiency decreases in fabricating the liquid crystal display apparatus 60.

[0016] Also, manufacturing costs and time for the liquid crystal display apparatus 60 increase because additional parts such as the screws are demanded for combining the liquid crystal display module 30 with those cases.

[0017] Furthermore, an overall size of the liquid crystal display apparatus 60 increases because the first, second, third and fourth mounting portions 11, 12, 13, and 14 are protruded from side walls of the top chassis toward outside.

SUMMARY OF THE INVENTION

[0018] The present invention provides a liquid crystal display apparatus in which a liquid crystal display module is tightly combined with cases.

[0019] The present invention further provides a liquid crystal display apparatus enhancing productivity by reducing the number of parts demanded for a fabrication of the liquid crystal display apparatus.

[0020] In one aspect, there is provided a liquid crystal display apparatus comprising a liquid crystal display module having at least one first protruding portion, a rear case for receiving the liquid crystal display module, wherein the rear case has at least one first fixing portion for guiding and fixing the at least one first protruding portion, and a front case combined with the rear case wherein the front case has at least one second protruding portion for fixing the liquid crystal display module.

[0021] The liquid crystal display module includes a back light assembly for generating a light, a display unit for receiving the light to display an image, a mold frame for receiving the back light assembly and the display unit, and a top chassis for fixing the display unit and the back light assembly to the mold frame by combining with the mold frame, which has a first side wall and a second side wall opposed each other wherein the at least one first protruding portion having a predetermined height is formed on the first and the second side walls, respectively.

[0022] The at least one first fixing portion is respectively formed on third and fourth side walls of the rear case corresponding to the first and second side walls of the top chassis. The at least one first fixing portion includes at least one first fixing groove extended from upper faces of the third and the fourth side walls of the rear case toward a bottom face of the rear case, and a second fixing groove extended from a lower portion of the first fixing groove toward a fifth side wall disposed between the third and the fourth side walls of the rear case.

[0023] The liquid crystal display module slides toward the second fixing groove of the rear case to be combined with the rear case when the at least one first protruding portion of the top chassis is received in the first fixing groove of the rear case.

[0024] The at least one second protruding portion is protruded from first and second upper faces of the front case corresponding to the third and the fourth side walls of the rear case, and the at least one second protruding portion is received in the at least one first fixing groove of the rear case. A bottom face of the at least one second protruding portion of the front case directly contacts a bottom face of the at least one first fixing groove of the rear case.

[0025] Also, a third protruding portion protruded toward the bottom face of the rear case is formed on a third upper face of the front case positioned on a sixth side wall of the rear case corresponding to the fifth side wall of the rear case. The third protruding portion of the front case is received in an isolation space formed between the sixth side wall of the rear case and the liquid crystal display module, and a bottom face of the third protruding portion directly contacts the bottom face of the rear case.

[0026] Also, a fourth protruding portion protruded toward the fifth side wall of the rear case is formed on a seventh side wall of the top chassis corresponding to the fifth side wall of the rear case. The at least one second fixing portion is formed on the fifth side wall of the rear case wherein the at least one second fixing portion has a third fixing groove formed from the liquid crystal display module received in the rear case toward the fifth side wall of the rear case. Hence, the liquid crystal display module is fixed as the fourth protruding portion of the top chassis is received in the third fixing groove formed on the second fixing portion of the rear case when the liquid crystal display module slides toward the fifth side wall of the rear case.

[0027] In addition, the at least one first fixing portion comprises a fourth fixing groove extended from upper faces of the third and the fourth side walls of the rear case toward the bottom face of the rear case. The at least one second protruding portion is protruded by a predetermined height from the first and second upper faces of the front case

corresponding to the third and fourth side walls of the rear case. The liquid crystal display module combines the rear case by the first protruding portion of the top chassis received in a lower portion of the fourth fixing groove, and the second protruding portion of the front case received in an upper portion of the fourth fixing groove so as to press the first protruding portion. A height of the fourth fixing groove is substantially identical to a sum of heights of the first protruding portion of the top chassis and the second protruding portion of the front case.

[0028] In another aspect, there is provided a liquid crystal display apparatus comprising a liquid crystal display module having a first protruding portion and a second protruding portion, and a rear case for receiving the liquid crystal display module wherein the rear case has a fixing groove for guiding and receiving the first protruding portion and a fixing protuberance for fixing the liquid crystal display module.

[0029] The liquid crystal display module includes a back light assembly for generating a light, a display unit for receiving the light and displaying an image, a mold frame for receiving the back light assembly and the display unit, and a top chassis combined with the mold frame for fixing the display unit and the back light assembly, which has a first side wall and a second side wall opposed each other wherein first and second protruding portions protruding by a predetermined height from the first and second side walls.

[0030] The fixing groove is formed on third and fourth side walls of the rear case corresponding to the first and second side walls of the top chassis. The fixing groove includes a first fixing groove formed from upper faces of the third and fourth side walls of the rear case toward a bottom face of the rear case, and a second fixing groove extended from a lower portion of the first fixing groove toward a fifth side wall of the rear case.

[0031] The liquid crystal display module slides toward the second fixing groove of the rear case to be combined with the rear case after the first protruding portion of the top chassis is received in the first groove of the rear case.

[0032] The fixing protuberances are formed on the third and said fourth side walls of the rear case corresponding to the second protruding portion formed on the first and second side walls of the top chassis. Also, each fixing protuberance has a supporting portion having a predetermined height toward an opposing side wall, a body extended from an end of the supporting portion toward the fifth side wall and separated by a predetermined interval from the third and the fourth side walls, and a suspending portion protruding from the body and engaging with the second protruding portion of the top chassis, preventing the liquid crystal display module from being moved. The suspending portion has a slope shape gradually wider toward said fifth side wall of the rear case.

[0033] According to the liquid crystal display apparatus of the present invention, the liquid crystal display module is fixed in the rear case as protuberances formed on the top chassis are combined with fixing portions formed on the rear case, and also the liquid crystal display module is firmly fixed by fixing protuberances formed on the front case. Therefore, the combining strength between the liquid crystal module and those cases can increase, and productivity of the

liquid crystal display apparatus can be improved by reducing the number of parts demanded in fabricating the liquid crystal module and cases.

BRIEF DESCRIPTION OF THE DRAWINGS

[0034] The above and other advantages of the present invention will become apparent by describing exemplary embodiment with reference to the attached drawings in which:

[0035] FIG. 1 is an exploded perspective view schematically showing a conventional liquid crystal display apparatus;

[0036] FIG. 2 is an exploded perspective illustrating a liquid crystal display apparatus according to one embodiment of the present invention;

[0037] FIG. 3 is a plan view showing a structure of a top chassis shown in FIG. 2;

[0038] FIG. 4 is a plan view showing a structure of a rear case shown in FIG. 2;

[0039] FIG. 5 is a plan view showing a structure of a front case shown in FIG. 2;

[0040] FIG. 6 is partially cut perspective view illustrating the front case shown in FIG. 5;

[0041] FIG. 7A is a plan view showing an assembled structure between the top chassis and the rear case;

[0042] FIG. 7B is a cross-sectional view taken along the line of C₁-C₂ for illustrating the assembled structure between the top chassis and the rear case shown in FIG. 7A;

[0043] FIG. 8 is a plan view showing an assembled structure among the front case, the top chassis and the rear case shown in FIG. 7A;

[0044] FIGS. 9 to 11 are partially cut perspective views illustrating a method for combining the top chassis with the rear case;

[0045] FIGS. 12 and 13 are cross-sectional views illustrating the method for combining the top chassis with the rear case;

[0046] FIG. 14 is a cross-sectional view taken along the line of A₁-A₂ for illustrating the assembled structure of the top chassis and the rear case shown in FIG. 7A;

[0047] FIG. 15 is a cross-sectional view taken along the line of B₁-B₂ for illustrating the assembled structure of the liquid crystal display device shown in FIG. 8;

[0048] FIG. 16 is a plan view showing a front case according to another embodiment of the present invention;

[0049] FIGS. 17 and 18 are cross-sectional views illustrating a combination of the front case and the rear case;

[0050] FIG. 19 is an exploded perspective view showing a liquid crystal display apparatus according to another embodiment of the present invention;

[0051] FIG. 20 is a plan view showing a structure of a rear case shown in FIG. 19;

[0052] FIG. 21 is a plan view showing a structure of a front case shown in FIG. 19;

[0053] FIGS. 22 and 23 are partially cut perspective views illustrating a method for combining the top chassis with the rear case shown in FIG. 19;

[0054] FIG. 24 is a cross-sectional view showing an assembled structure of the top chassis, the rear case and the front case;

[0055] FIG. 25 is an exploded perspective view showing a liquid crystal display device according to still another embodiment of the present invention;

[0056] FIG. 26 is a plan view showing a structure of a top chassis shown in FIG. 25;

[0057] FIG. 27 is a partial perspective view showing a structure of the top chassis shown in FIG. 25;

[0058] FIGS. 28 and 29 are side views illustrating the top chassis shown in FIG. 25;

[0059] FIG. 30 is a partially cut perspective view showing the rear case shown in FIG. 25;

[0060] FIG. 31 is a plan view showing the top chassis and the rear case shown in FIG. 25 before the top chassis combines with the rear case;

[0061] FIG. 32 is an enlarged plan view showing 'B' shown in FIG. 31; and

[0062] FIG. 33 is a plan view illustrating an assembled structure of the top chassis and the rear case shown in FIG. 25.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0063] Hereinafter, a liquid crystal display device according to various embodiments of the present invention will be described in detail with reference to the drawings.

[0064] FIG. 2 is an exploded perspective view showing a liquid crystal display device according to one embodiment of the present invention, FIG. 3 is a plan view illustrating a structure of a top chassis in FIG. 2, FIG. 4 is a plan view showing a structure of a rear case in FIG. 2, FIG. 5 is a plan view showing a structure of a front case in FIG. 2, and FIG. 6 is a partially cut perspective view showing the front case in FIG. 5.

[0065] Referring to FIG. 2, a liquid crystal display apparatus 600 has a liquid crystal display module 300 for displaying an image, and cases for receiving the liquid crystal display module 300. Those cases include a front case 500 and a rear case 400.

[0066] The liquid crystal display module 300 includes a display unit 310 for displaying the image, and a back light assembly 360 disposed under the display unit 310 for supplying a light to the display unit 310 (see FIG. 7B). The display unit 310 and the back light assembly 360 are received in a mold frame 200. Also, a top chassis 100 is provided for fixing the display unit 310 and the back light assembly 360 to the mold frame 200.

[0067] In particular, when the back light assembly 360 and the display unit 310 are subsequently received in the mold frame 200, the top chassis 100 is provided on the display unit 310. The top chassis 100 has a rectangular clamp shape. The top chassis 100 covers an upper portion of the display unit

310 except for an effective display area of the display unit **310**. The top chassis **100** is combined with the mold frame **200** so that inner surfaces of four side walls of the top chassis **100** correspond to outer surfaces of side walls of the mold frame **200**.

[0068] As shown in FIGS. 2 and 3, the top chassis **100** has a first side wall **110**, a second side wall **120**, a third side wall **130** and a fourth side wall **140**. First to third protuberances **111**, **112** and **113** respectively having a predetermined height are formed on the first side wall **110** of the top chassis **100**, and fourth to sixth protuberances **121**, **122** and **123** respectively having a predetermined height are formed on the second side wall **120** of the top chassis **100**. The second side wall **120** is opposed to the first side wall **110**. In addition, seventh and eighth protuberances **131** and **132** are formed on the third side wall **130**, which locates between the first side wall **110** and the second side wall **120**. The first to eighth protuberances **111**, **112**, **113**, **121**, **122**, **123**, **131** and **132** can be formed by partially cutting predetermined portions of the first to third side walls **110**, **120** and **130** of the top chassis **100** and extending the portions toward outside. The first to eighth protuberances **111**, **112**, **113**, **121**, **122**, **123**, **131** and **132** may have various shapes such as hemi-circular shapes, trapezoidal shapes or rectangular shapes when the first to eighth protuberances **111**, **112**, **113**, **121**, **122**, **123**, **131** and **132** are observed from the direction of the cases **500** and **400**. Preferably, the first to eighth protuberances **111**, **112**, **113**, **121**, **122**, **123**, **131** and **132** have trapezoidal shapes, respectively.

[0069] Referring to FIGS. 2 and 4, the rear case **400** includes fifth to eighth side walls **410**, **420**, **430** and **440**, and a bottom face **450** enclosed by the fifth to eighth side walls **410**, **420**, **430** and **440**. An upper face of the rear case **400** corresponding to the bottom face **450** is opened. First to third protruding portions **411**, **412** and **413** having a predetermined height are formed on the fifth side wall **410** of the rear case **400**, which corresponds to and is combined with the first side wall **110** of the top chassis **100**. Also, fourth to sixth protruding portions **421**, **422** and **423** having a predetermined height are formed on the sixth side wall **420** of the rear case **400**, which corresponds to and is combined with the second side wall **120** of the top chassis **100**. Furthermore, seventh and eighth protruding portions **431** and **432** having a predetermined height are formed on the seventh side wall **430** of the rear case **400**, which corresponds to and is combined with the third side wall **130** of the top chassis **100**.

[0070] First to sixth fixing grooves **411a**, **412a**, **413a**, **421a**, **422a** and **423a** are respectively formed on the first to sixth protruding portions **411**, **412**, **413**, **421**, **422** and **423** so as to be combined with the first to sixth protuberances **111**, **112**, **113**, **121**, **122** and **123** formed on the first and second side walls **110** and **120** of the top chassis **100**. In addition, seventh to twelfth fixing grooves **411b**, **412b**, **413b**, **421b**, **422b** and **423b** are formed on the first to sixth protruding portions **411**, **412**, **413**, **421**, **422** and **423**. The first to sixth fixing grooves **411a**, **412a**, **413a**, **421a**, **422a** and **423a** are respectively formed from upper ends of the fifth and sixth side walls **410** and **420** of the rear case **400** toward the bottom face **450** of the rear case **400**. The seventh to twelfth fixing grooves **411b**, **412b**, **413b**, **421b**, **422b** and **423b** are respectively extended from lower portions of the first and sixth fixing grooves **411a**, **412a**, **413a**, **421a**, **422a** and **423a** toward the seventh side wall **430** of the rear case **400**. Thus,

each corresponding pair of the first to sixth fixing grooves **411a**, **412a**, **413a**, **421a**, **422a** and **423a** and the seventh to twelfth fixing grooves **411b**, **412b**, **413b**, **421b**, **422b** and **423b** may form a shape of "L".

[0071] Thirteenth and fourteenth fixing grooves **431a** and **432a** are formed on the seventh and eighth protruding portions **431** and **432** positioned on the seventh side wall **430** of the rear case **400** so that the thirteenth and fourteenth fixing grooves **431a** and **432a** are combined with the seventh and eighth protuberances **131** and **132** formed on the third side wall **130** of the top chassis **100**.

[0072] The rear case **400** includes first and second suspending protuberances **441** and **442** respectively extended from the bottom face **450** and the eighth side wall **440**. The first and second suspending protuberances **441** and **442** will be described in detail with reference to FIGS. 7A and 7B.

[0073] Referring to FIGS. 5 and 6, and further FIG. 16, the front case **500** has four side walls, and first to fourth top faces **510**, **520**, **530** and **540**. The four side walls of the front case **500** are combined with the fifth to eighth side walls **410**, **420**, **430**, and **440** of the rear case **400**, and the first to fourth top faces **510**, **520**, **530** and **540** cover a non-effective display area of the liquid display module **300**. Also, a lower face of the front case **500** corresponding to an effective display area of the liquid display module **300** is opened.

[0074] Ninth and tenth protuberances **511** and **512** are formed on the first top face **510** of the front case **500** positioned over the eighth side wall **440** of the rear case **400**. Each of the ninth and tenth protuberances **511** and **512** has a substantially same height as a height of the eighth side wall **440** of the rear case **400** as shown in FIG. 6. The ninth and tenth protuberances **511** and **512** will be described more detail with reference to cross-sectional views.

[0075] FIG. 7A is a plan view showing an assembled structure between the top chassis and the rear case, FIG. 7B is a cross-sectional view taken along the line of C₁-C₂ for illustrating the assembled structure between the top chassis and the rear case, and FIG. 8 is a plan view showing an assembled structure among the front case, the top chassis and the rear case.

[0076] When the liquid crystal display module **300** including the display unit **310** is received in the rear case **400** as shown in FIG. 7B, the first to third protuberances **111**, **112** and **113** formed on the first side wall **110** of the top chassis **100** are respectively combined with the first to third fixing grooves **411a**, **412a** and **413a** formed on the fifth side wall **410** of the rear case **400**. Also, the fourth to sixth protuberances **121**, **122** and **123** formed on the second side wall **120** of the top chassis **100** are respectively combined with the fourth to sixth fixing grooves **421a**, **422a** and **423a** formed on the sixth side wall **420** of the rear case **400**, as shown in FIG. 7A.

[0077] Then, the first to sixth protuberances **111**, **112**, **113**, **121**, **122** and **123** move toward the seventh side wall **430** of the rear case **400**, so the first to sixth protuberances **111**, **112**, **113**, **121**, **122** and **123** are received in the seventh to twelfth fixing grooves **411b**, **412b**, **413b**, **421b**, **422b** and **423b**, respectively. In this way, the rear case **400** is combined with the top chassis **100**, which is illustrated in FIGS. 9-11. The seventh and eighth protuberances **131** and **132** formed on the third side wall **130** of the top chassis **100** are respectively

combined with the thirteenth and fourteenth fixing grooves **431a** and **432a** formed on the seventh side wall **430** of the rear case **400**.

[0078] When the liquid crystal display module **300** moves toward the seventh side wall **430** of the rear case **400** to be combined with the rear case **400**, an isolation space A is formed between the eighth side wall **440** of the rear case **400** and the fourth side wall **140** of the top chassis **100**.

[0079] Referring to FIG. 7B, the first and second suspending protuberances **441** and **442** are protruded from the eighth side wall **440** of the rear case **400** toward the liquid crystal display module **300** along the bottom face **450** of the rear case **400**. The first and second suspending protuberances **441** and **442** have terraced shapes gradually lowered from the eighth side wall **440** to the liquid crystal display module **300**. The widths of the first and second suspending protuberances **441** and **442** are identical to a width W1 of the isolation space A between the liquid crystal module **300** and the eighth side wall **440** of the rear case **400**. Hence, an end of the liquid crystal display module **300** moves along the first and second suspending protuberances **441** and **442** of the rear case **400** when the liquid crystal display module **300** moves toward the seventh side wall **430** after the liquid crystal display module **300** is received in the rear case **400**. A predetermined portion of the fourth side wall **140** of the top chassis **100** corresponds to terraced portions of the first and second suspending protuberances **441** and **442** when the liquid crystal display module **300** completely moves, thereby preventing the liquid crystal display module **300** from being moved toward the eighth side wall **440** of the rear case **400**.

[0080] The front case **500** is combined with the rear case **400** while the liquid crystal display module **300** is received in the rear case **400**. The ninth and tenth protuberances **511** and **512** are inserted into the isolation space A between the rear case **400** and the top chassis **100**. Widths of the ninth and tenth protuberances **511** and **512** are substantially identical to the width W1 of the isolation space A so that the ninth and tenth protuberances **511** and **512** are tightly inserted into the isolation space A. Thus, the liquid crystal display module **300** does not move in the isolation space A by the ninth and tenth protuberances **511** and **512**, as shown in FIGS. 8 and 15.

[0081] FIGS. 9 to 11 are partially cut perspective views illustrating a method for combining the top chassis with the rear case, and FIGS. 12 and 13 are cross-sectional views illustrating the method for combining the top chassis with the rear case.

[0082] Referring to FIGS. 9 to 13, the fifth protuberance **422** formed on the sixth side wall **420** of the rear case **400** includes the fifth fixing groove **422a** formed from the upper face of the sixth side wall **420** toward the bottom face **450** of the rear case **400**, and the eleventh fixing groove **422b** extended from the lower portion of the fifth fixing groove **422a** toward the seventh side wall **430** of the rear case **400**. The fifth fixing groove **422a** is higher than the eleventh fixing groove **422b**. That is, an upper face of the eleventh fixing groove **422b** is not exposed to the upper face of the sixth side wall **420**.

[0083] The fifth protuberance **122** protruding toward the sixth side wall **420** of the rear case **400** by a predetermined

height is formed on the second side wall **120** of the top chassis **100** corresponding to the sixth side wall **420** of the rear case **400**. A portion of the second side wall **120** of the top chassis **100** is partially cut in the direction parallel with the bottom face **450** of the rear case **400**, and the cut portion of the second side wall **120** of the top chassis **100** is extended toward the sixth side wall **420** of the rear case **400**. The fifth protuberance **122** protrudes toward the sixth side wall **420** of the rear case **400**.

[0084] When the top chassis **100** is received in the rear case **400**, the fifth protuberance **122** of the top chassis **100** is inserted into the fifth fixing groove **422a** of the rear case **400**. The liquid crystal display module **300** moves toward the seventh side wall **430** of the rear case **400** when the fifth protuberance **122** makes contact with a bottom face of the fifth fixing groove **422a**. The fifth protuberance **122** is combined with the eleventh fixing groove **422b** so that the liquid crystal display module **300** is fixed in the rear case **400**. Namely, the fifth protuberance **122** is fixed by an upper end of the fifth protruding portion **422** adjacent the eleventh fixing groove **422b**, thereby preventing the liquid crystal display module **300** from being moved through the opened upper face of the rear case **400**. Therefore, the liquid crystal display module **300** received in the rear case **400** cannot move through the opened upper face of the rear case **400**.

[0085] FIG. 14 is a cross-sectional view taken along the line of A₁-A₂ for illustrating the assembled structure of the top chassis and the rear case shown in FIG. 7A, and FIG. 15 is a cross-sectional view taken along the line of B₁-B₂ for illustrating the assembled structure of the liquid crystal display device shown in FIG. 8.

[0086] Referring to FIG. 14, the back light assembly **360** is received in the mold frame **200**. In particular, a reflection plate **340** is received in a bottom face of the mold frame **200**, and then a light guiding plate **330** is mounted thereon. Optical sheets **350** are mounted on the light guiding plate **330** so that the back light assembly **360** is received in the mold frame **200**. The display unit **310** is mounted on the back light assembly **360**.

[0087] When the back light assembly **360** and the display unit **310** are received in the mold frame **200**, the top chassis **100** is provided for fixing the back light assembly **360** and the display unit **310** in the mold frame **200**. The top chassis **100** is combined with the mold frame **200**, thereby completing the liquid crystal display module **300**.

[0088] The completed liquid crystal display module **300** is received in the rear case **400**. The sixth protuberance **123** formed on the second side wall **120** of the top chassis **100** is combined with the sixth and twelfth fixing grooves **423a** and **423b** formed on the sixth side wall **420** of the rear case **400**. That is, the sixth protuberance **123** of the top chassis **100** moves along the sixth fixing groove **423a** toward the twelfth fixing groove **423b** to be combined therewith. Hence, the liquid crystal display module **300** is fixed in the rear case **400** so that the liquid crystal display module **300** is not separated from the rear case **400** through the opened upper face of the rear case **400**.

[0089] Referring to FIG. 15, the front case **500** is combined with the rear case **400** after the liquid crystal display module **300** is received in the rear case **400**. The ninth protuberance **511** is formed on the first upper face **510** of the

front case 500. The ninth protuberance 511 protrudes from the first upper face 510 toward the rear case 400 and has a width substantially identical to the width W1 of the isolation space A formed between the liquid crystal display module 300 and the rear case 400. Also, a height of the ninth protuberance 511 is identical to a height of the eighth side wall 440.

[0090] When the liquid crystal display module 300 is received in the rear case 400, the liquid crystal display module 300 moves toward the seventh side wall 430 of the rear case 400 to be combined therewith. The isolation space A is formed between the eighth side wall 440 of the rear case 400 and the fourth side wall 140 of the top chassis 100. The ninth protuberance 511 formed on the first upper face 510 of the front case 500 is inserted into the isolation space A. Therefore, the liquid crystal display module 300 does not move toward the eighth side wall 440 of the rear case 400.

[0091] FIG. 16 is a plan view showing a front case according to another embodiment of the present invention, and FIGS. 17 and 18 are cross-sectional views illustrating a combination of the front case and the rear case shown in FIG. 16.

[0092] Referring to FIG. 16, eleventh to sixteenth protuberances 531, 532, 533, 541, 542 and 543 toward the bottom face 450 of the rear case 400 are respectively formed on the third and fourth upper faces 530 and 540 of the front case 500 except the first and second upper faces 510 and 520 of the front case 500. The eleventh to sixteenth protuberances 531, 532, 533, 541, 542 and 543 correspond to the first to sixth fixing grooves 411a, 412a, 413a, 421a, 422a and 423a of the rear case 400, respectively. In addition, the eleventh to sixteenth protuberances 531, 532, 533, 541, 542 and 543 are spaced from the side walls of the front case 500 by a length identical to a width of each of the fifth and sixth side walls 410 and 420 of the rear case 400.

[0093] As shown in FIGS. 17 and 18, after the liquid crystal display module 300 is received in the rear case 400, the eleventh to thirteenth protuberances 531, 532 and 533 are respectively inserted into the first to third fixing grooves 411a, 412a and 413a when the front case 500 is combined with the rear case 400. Heights of the eleventh to thirteenth protuberances 531, 532 and 533 are substantially the same as those of the first to third fixing grooves 411a, 412a and 413a. As a result, a wall of each of the eleventh to thirteenth protuberances 531, 532 and 533 close an inlet of each of the seventh to ninth fixing grooves 411b, 412b and 413b when the eleventh to thirteenth protuberances 531, 532 and 533 are received in the first to third fixing grooves 411a, 412a and 413a. Therefore, the liquid crystal display module 300 cannot move toward the eighth side wall 440 of the rear case 400.

[0094] Hereinafter, it will be described an assembled structure of a liquid crystal display module and cases of a liquid crystal display apparatus according to another embodiment of the present invention with reference to FIGS. 19 to 24.

[0095] FIG. 19 is an exploded perspective view showing a liquid crystal display apparatus according to another embodiment of the present invention, FIG. 20 is a plan view showing a structure of a rear case shown in FIG. 19, and FIG. 21 is a plan view showing a structure of a front case

shown in FIG. 19. In FIG. 19, elements identical to those in FIG. 2 have the same reference numerals and the description concerning their functions will be omitted.

[0096] Referring to FIG. 19, a liquid crystal display apparatus 900 has a liquid crystal display module 300 for displaying an image, and cases for receiving the liquid crystal display module 300. Those cases include a front case 800 and a rear case 700.

[0097] When a back light assembly 360 and a display unit 310 are successively received in a mold frame 200, a top chassis 100 is mounted on the display unit 310. The top chassis 100 covers an upper portion of the display unit 310 besides an effective display area of the display unit 310, and insides of four side walls of the top chassis 100 are combined with outsides of side walls of the mold frame 200, respectively.

[0098] First to third protuberances 111, 112 and 113 are formed on a first side wall 110 of the top chassis 100, and fourth to sixth protuberances 121, 122 and 123 are formed on a second side wall 120 facing the first side wall 110 of the top chassis 100.

[0099] As shown in FIG. 20, the rear case 700 includes a bottom face 750 and ninth to twelfth side walls 710, 720, 730 and 740. Ninth to eleventh protruding portions 711, 712 and 713 having a predetermined height are formed on the ninth side wall 710 of the rear case 700 combined with the first side wall 110 of the top chassis 100. Also, twelfth to fourteenth protruding portions 721, 722 and 723 having a predetermined height are formed on the tenth side wall 720 of the rear case 700 combined with the second side wall 120 of the top chassis 100.

[0100] Fifteenth to seventeenth fixing grooves 711a, 712a and 713a are respectively formed on the ninth to eleventh protruding portions 711, 712 and 713 from an upper end of the ninth side wall 710 toward the bottom face 750 of the rear case 700. Eighteenth to twentieth fixing grooves 721a, 722a and 723a are respectively formed on the twelfth to fourteenth protruding portions 721, 722 and 723 from an upper end of the tenth side wall 720 of the rear case 700 toward the bottom face 750 of the rear case 700.

[0101] Referring to FIG. 21, the front case 800 is combined with the rear case 700 after the liquid crystal display module 300 is received in the rear case 700. Seventeenth to nineteenth protuberances 811, 812 and 813 having a predetermined height are formed on a fifth upper face 810 of the front case 800 adjacent to the ninth side wall 710 of the rear case 700. The seventeenth to nineteenth protuberances 811, 812 and 813 are formed toward the bottom face 750 of the rear case 700. In addition, twentieth to twenty-second protuberances 821, 822 and 823 having a predetermined height toward 15 the bottom face 750 of the rear case 700 are formed on a sixth upper face 820 of the front case 800 adjacent to the tenth side wall 720 of the rear case 700. The seventeenth to twenty-second protuberances 811, 812, 813, 821, 822 and 823 are formed spaced from side walls of the front case 800 by a distance identical to each of the thickness of the ninth and tenth side walls 710 and 720.

[0102] FIGS. 22 and 23 are partially cut perspective views illustrating a method for combining the top chassis with the rear case in FIG. 19, and FIG. 24 is a cross-sectional view

showing an assembled structure of the top chassis, the rear case and the front case shown in FIG. 19.

[0103] Referring to FIGS. 22 and 23, the tenth protruding portion 712 formed on the ninth side wall 710 of the rear case 700 includes the sixteenth fixing groove 712a formed from an upper end of the ninth side wall 710 toward the bottom face 750 of the rear case 700.

[0104] A second protuberance 112 having a predetermined height toward the ninth side wall 710 of the rear case 700 is formed on the first side wall 110 of the top chassis 100 corresponding to the ninth side wall 710 of the rear case 700. The first side wall 110 of the top chassis 100 is partially cut in parallel with the bottom face 750 of the rear case 700 and toward the ninth side wall 710 of the rear case 700, and the second protuberance 112 is protruded toward a cut portion of the first side wall 110 of the top chassis 100. When the top chassis 100 is received in the rear case 700, the second protuberance 112 of the top chassis 100 is inserted into the sixteenth fixing groove 712a of the rear case 700.

[0105] Referring to FIG. 24, when the liquid crystal display module 300 is received in the rear case 700, the front case 800 is mounted thereon. The seventeenth to nineteenth protuberances 811, 812 and 813 protruded from the fifth upper face 810 of the front case 800 are inserted into the fifteenth to seventeenth fixing grooves 711a, 712a and 713a, respectively. That is, each of the fifteenth to seventeenth fixing grooves 711a, 712a and 713a has a depth identical to a sum of heights of the first to third protuberances 111, 112 and 113 of the top chassis 100 and heights of the seventeenth to nineteenth protuberances 811, 812 and 813 of the front case 800. The seventeenth to nineteenth protuberances 811, 812 and 813 of the front case 800 pressurize the first to third protuberances 111, 112 and 113, thereby preventing the liquid crystal display module 300 from being deviated from the rear case 700.

[0106] Hereinafter, it will be described an assembled structure of a liquid crystal display module and cases of a liquid crystal display apparatus according to still another embodiment of the present invention with reference to FIGS. 25 to 33.

[0107] FIG. 25 is an exploded perspective view showing a liquid crystal display apparatus according to still another embodiment of the present invention, FIG. 26 is a plan view showing a structure of a top chassis shown in FIG. 25, FIG. 27 is a partial perspective view showing a structure of the top chassis shown in FIG. 25, and FIGS. 28 and 29 are side views illustrating the top chassis shown in FIG. 25.

[0108] Referring to FIG. 25, a liquid crystal display apparatus 1600 has a liquid crystal display module 1300 for displaying an image, and cases for receiving the liquid crystal display module 1300. Those cases include a front case 1500 and a rear case 1400.

[0109] When a back light assembly and a display unit are successively received in a mold frame 1200, a top chassis 1100 is mounted on the display unit. The top chassis 1100 has a rectangular cramp shape. The top chassis 1100 covers an upper portion of the display unit except for an effective display area of the display unit, and insides of four side walls of the top chassis 1100 are combined with outsides of side walls of the mold frame 1200, respectively.

[0110] As shown in FIGS. 26 to 29, the top chassis 1100 has thirteenth to sixteenth side walls 1110, 1120, 1130 and 1140. Twenty-third to twenty-fifth protuberances 1111, 1112 and 1113 each having a predetermined height are formed on the thirteenth side wall 1110 of the top chassis 1100, and twenty-sixth to twenty-eighth protuberances 1121, 1122 and 1123 each having a predetermined height are formed on the fourteenth side wall 1120 corresponding to the thirteenth side wall 1110. Also, twenty-ninth and thirtieth protuberances 1131 and 1132 each having a predetermined height are formed on the fifteenth side wall 1130 of the top chassis 1100. The twenty-third to thirtieth protuberances 1111, 1112, 1113, 1121, 1122, 1123, 1131 and 1132 are formed by cutting predetermined portions of the thirteenth to fifteenth side walls 1110, 1120 and 1130 of the top chassis 1100. The twenty-fourth, twenty-fifth, twenty-seventh and twenty-eighth protuberances 1112, 1113, 1122 and 1123 are extended parallel with a bottom face 1450 of the rear case 1400, with various shapes. The twenty-fourth, twenty-fifth, twenty-seventh and twenty-eighth protuberances 1112, 1113, 1122 and 1123 respectively have semicircular shapes, trapezoidal shapes or rectangular shapes when observed from the front and rear cases 1500 and 1400. Among them, trapezoidal shapes are preferable. In the meantime, the twenty-third and twenty-sixth protuberances 1111 and 1121 are extended perpendicular to the bottom face 1450 of the rear case 1400. The twenty-third and twenty-sixth protuberances 1111 and 1121 have trapezoidal shapes when observed from the nineteenth side wall 1430 of the rear case 1400.

[0111] FIG. 30 is a partially cut perspective view showing the rear case shown in FIG. 25.

[0112] Referring to FIGS. 25 and 30, the rear case 1400 has seventeenth to twentieth side walls 1410, 1420, 1430 and 1440, and the bottom face 1450 enclosed by the seventeenth to twentieth side walls 1410, 1420, 1430 and 1440. An upper face of the rear case 1400 corresponding to the bottom face 1450 is opened. Fifteenth and sixteenth protruding portions 1412 and 1413 each having a predetermined height are formed on the seventeenth side wall 1410 of the rear case 1400 combined with the thirteenth side wall 1110 of the top chassis 1100. Seventeenth and eighteenth protruding portions 1422 and 1423 each having a predetermined height are formed on the eighteenth side wall 1420 of the rear case 1400 combined with the fourteenth side wall 1120 of the top chassis 1100.

[0113] Twenty-first to twenty-fourth fixing grooves 1412a, 1413a, 1422a and 1423a are formed on the fifteenth to eighteenth protruding portions 1412, 1413, 1422 and 1423. The twenty-first to twenty-fourth fixing grooves 1412a, 1413a, 1422a and 1423a are formed from upper ends of the seventeenth and eighteenth side walls 1410 and 1420 of the rear case 1400 toward the bottom face 1450 of the rear case 1400. Also, twenty-fifth to twenty-eighth fixing grooves 1412b, 1413b, 1422b and 1423b are formed on the fifteenth to eighteenth protruding portions 1412, 1413, 1422 and 1423. The twenty-fifth to twenty-eighth fixing grooves 1412b, 1413b, 1422b and 1423b are parallel with the bottom face 1450 of the rear case 1400 and protrude toward the nineteenth side wall 1430.

[0114] First and second fixing protuberances 1411 and 1412 are respectively formed on the seventeenth and eighteenth side walls 1410 and 1420 of the rear case 1400, and

the first and second fixing protuberances **1411** and **1412** are combined with the twenty-third and twenty-sixth protuberances **1111** and **1121**, respectively. The first and second fixing protuberances **1411** and **1412** respectively have supporting portions **1411a** and **1421a**, and bodies **1411b** and **1421b**. Supporting portions **1411a** and **1421a** protrude toward opposite side walls by a predetermined height, and bodies **1411b** and **1421b** are extended from ends of supporting portions **1411a** and **1421a** toward the nineteenth side wall **1430**. Suspending portions **1411c** and **1421c** are formed on sides of the bodies **1411b** and **1421b**, and the suspending portions **1411c** and **1421c** are protruded from the bodies **1411b** and **1421b**. The suspending portions **1411c** and **1421c** are engaged with the twenty-third and the twenty-sixth protuberances **1111** and **1121**.

[0115] The bodies **1411b** and **1421b** are separated from the seventeenth and the eighteenth side walls **1410** and **1420** by a predetermined interval, and the suspending portions **1411c** and **1421c** have a slope shape that is gradually wider toward the nineteenth side wall **1430** of the rear case **1400**.

[0116] Twenty-ninth and thirtieth fixing grooves **1431a** and **1432a** are formed on the nineteenth and twentieth protruding portions **1431** and **1432** which are formed on the nineteenth side wall **1430** of the rear case **1400** and protrude toward the twentieth side wall **1440** by a predetermined height. The twenty-ninth and thirtieth fixing grooves **1431a** and **1432a** are combined with the twenty-ninth and thirtieth protuberances **1131** and **1132** formed on the fifteenth side wall **1130** of the top chassis **1100**, respectively.

[0117] FIG. 31 is a plan view showing the top chassis and the rear case shown in FIG. 25 before the top chassis is completely combined with the rear case, FIG. 32 is an enlarged plan view showing 'B' shown in FIG. 31, and FIG. 33 is a plan view illustrating an assembled structure of the top chassis and the rear case shown in FIG. 25.

[0118] Referring to FIG. 31, when the liquid crystal display module **1300** is received in the rear case **1400**, the twenty-fourth and twenty-fifth protuberances **1112** and **1113** formed on the thirteenth side wall **1110** of the top chassis **1100** are respectively combined with the twenty-first and twenty-second fixing grooves **1412a** and **1413a** formed on the seventeenth side wall **1410** of the rear case **1400**. Also, the twenty-seventh and twenty-eighth protuberances **1122** and **1123** of the top chassis **1100** are respectively combined with the twenty-third and twenty-fourth fixing grooves **1422a** and **1423a** of the rear case **1400**.

[0119] The twenty-third and twenty-sixth protuberances **1111** and **1121** make contact with portions of bodies **1411a** and **1421b** positioned between the supporting portions **1411a** and **1421a** and the suspending portions **1411c** and **1421c** of the first and second fixing protuberances **1411** and **1421**.

[0120] When the liquid crystal display module **1300** moves toward the nineteenth side wall **1430** of the rear case **1400**, the twenty-fourth and twenty-fifth protuberances **1112** and **1113** formed on the thirteenth side wall **1110** of the top chassis **1100** are respectively combined with the twenty-fifth and twenty-sixth fixing grooves **1412b** and **1413b** formed on the seventeenth side wall **1410** of the rear case **1400**. In addition, the twenty-seventh and twenty-eighth protuberances **1122** and **1123** formed on the fourteenth side wall

1120 of the top chassis **1100** are respectively combined with the twenty-seventh and twenty-eighth fixing grooves **1422a** and **1423b** formed on the eighteenth side wall **1420** of the rear case **1400**.

[0121] Referring to FIG. 32, the twenty-third and twenty-sixth protuberances **1111** and **1121** are inclined to the seventeenth and eighteenth side walls **1410** and **1420** of the rear case **1400** and move toward the nineteenth side wall **1430** of the rear case **1400** through the suspending portions **1411c** and **1421c** having slope shapes as those bodies **1411b** and **1421b** are inclined toward the seventeenth and eighteenth side walls **1410** and **1420** of the rear case by elastic forces of bodies **1411b** and **1421b**.

[0122] As shown in FIG. 33, the twenty-third and twenty-sixth protuberances **1111** and **1121** are engaged with bodies **1411b** and **1421b** at ends of the suspending portions **1411c** and **1421c**, and the bodies **1411b** and **1421b** support the twenty-third and the twenty-sixth protuberances **1111** and **1121** by restoring force of the bodies **1411b** and **1421b**. The twenty-third and twenty-sixth protuberances **1111** and **1121** are hung by the suspending portions **1411c** and **1421c**, thereby preventing the liquid crystal display module **300** from being moved toward the twentieth side wall **1440** corresponding to the nineteenth side wall **1430** of the rear case **1400**.

[0123] Also, the twenty-ninth and thirtieth protuberances **1131** and **1132** formed on the fifteenth side wall **1130** of the top chassis **1100** are respectively combined with the twenty-ninth and thirtieth fixing grooves **1431a** and **1432a** formed on the nineteenth side wall **1430** of the rear case **1400** when the liquid crystal display module **1300** moves toward the nineteenth side wall **1430** of the rear case **1400**. Therefore, the liquid crystal module **1300** is not separated from the rear case **1400** through the open upper face of the rear case **1400**.

[0124] An isolation space A is formed between the liquid crystal display module **1300** and the twentieth side wall **1440** of the rear case **1400** as shown in FIG. 33. Also, at least one protuberance inserted into the isolation space A may be formed on an upper face of the front case **1500** corresponding to the twentieth side wall **1440** of the rear case **1400** so as to more effectively prevent the liquid crystal display module **1300** from being moved toward the isolation space A.

[0125] As described above, according to the liquid crystal display apparatus of the present invention, protuberances are formed on the top chassis, and fixing portions to be combined with the protuberances are formed on the rear case facing the top chassis. Also, fixing protuberances are formed on predetermined portions of the front case, and the fixing protuberances are inserted into between the liquid crystal display module and the rear case.

[0126] Therefore, the liquid crystal display module is fixed in the rear case as the protuberances formed on the top chassis are combined with the fixing portions formed on the rear case, and also the liquid crystal display module is tightly fixed therein by the fixing protuberances formed on the front case.

[0127] In addition, the combining strength between the liquid crystal module and the cases can increase, and productivity of the liquid crystal display apparatus can be

improved by reducing the number of parts demanded in order to assemble the liquid crystal module and cases.

[0128] Although the preferred embodiments of the present invention have been described, it is understood that the present invention should not be limited to these preferred embodiments but various changes and modifications can be made by one skilled in the art within the spirit and scope of the present invention as hereinafter claimed.

1-16. (canceled)

17. A liquid crystal display apparatus comprising:

a liquid crystal display module having a first protruding portion and a second protruding portion; and

a rear case for receiving said liquid crystal display module, said rear case having a fixing groove for guiding and receiving said first protruding portion and a fixing protuberance combined with said second protruding portion, for fixing said liquid crystal display module to said rear case.

18. The liquid crystal display apparatus of claim 17, wherein said liquid crystal display module comprises:

a back light assembly for generating a light;

a display unit for receiving the light to display an image;

a mold frame for receiving said back light assembly and said display unit; and

a top chassis combined with said mold frame, for fixing said display unit and said back light assembly to said mold frame, said top chassis having opposing first and second side walls wherein each of said first and second side walls comprise first and second protruding portions.

19. The liquid crystal display apparatus of claim 18, wherein said rear case comprises third and fourth side walls corresponding to said first and second side walls of said top chassis, and each of said third and fourth side walls comprises said fixing groove corresponding to said first protruding portion formed on said first and second sidewalls of said top chassis.

20. The liquid crystal display apparatus of claim 19, wherein said fixing groove comprises:

a first fixing groove extended from upper faces of said third and fourth side walls of said rear case toward a bottom face of said rear case; and

a second fixing groove extended from a lower portion of said first fixing groove toward a fifth side wall of said rear case disposed between said third and fourth side walls.

21. The liquid crystal display apparatus of claim 20, wherein said liquid crystal display module slides toward said second fixing groove of said rear case to be combined with said rear case when said first protruding portion of said top chassis is received in said first fixing groove of said rear case.

22. The liquid crystal display apparatus of claim 18, wherein said rear case comprises third and fourth side walls corresponding to said first and second side walls of said top chassis, and each of said third and fourth side walls comprises said fixing protuberance corresponding to said second protruding portion formed on said first and second side walls of said top chassis.

23. The liquid crystal display apparatus of claim 22, wherein said fixing protuberance comprises:

a supporting portion extending a predetermined height toward an opposing side wall;

a body extended from an end of said supporting portion toward a fifth side wall disposed between said third and fourth side walls and separated by a predetermined interval from said third side wall or said fourth side wall; and

a suspending portion extending from said body and engaging with said second protruding portion of said top chassis, preventing said liquid crystal display module from being moved.

24. The liquid crystal display apparatus of claim 23, wherein said suspending portion has a cross-section which gradually widens toward said fifth side wall of said rear case.

25. The liquid crystal display apparatus of claim 17, further comprising a front case combined with said rear case, said front case having first and second upper faces corresponding to third and fourth side walls of said rear case wherein each of said first and second upper faces comprises a third protruding portion having a predetermined height toward a bottom face of said rear case.

26. The liquid crystal display apparatus of claim 25, wherein said third protruding portion of said front case is received in said fixing groove, and a bottom face of said third protruding portion directly contacts a bottom face of said fixing groove of said rear case.

* * * * *

专利名称(译)	液晶显示装置		
公开(公告)号	US20070008452A1	公开(公告)日	2007-01-11
申请号	US11/519626	申请日	2006-09-12
[标]申请(专利权)人(译)	金东CHEOL 褚杨BEE KANG TAE GIL LEE YOUNG JAE 金正KI 崔在常 OH JEONG SEOK KWAK YONG SEOK		
申请(专利权)人(译)	金东哲 褚YOUNG-BEE KANG TAE-GIL 李英宰 金正KI 崔在常 OH JEONG-SEOK KWAK永硕		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	KIM DONG CHEOL CHU YOUNG BEE KANG TAE GIL LEE YOUNG JAE KIM JUNG KI CHOI JAE CHANG OH JEONG SEOK KWAK YONG SEOK		
发明人	KIM, DONG-CHEOL CHU, YOUNG-BEE KANG, TAE-GIL LEE, YOUNG-JAE KIM, JUNG-KI CHOI, JAE-CHANG OH, JEONG-SEOK KWAK, YONG-SEOK		
IPC分类号	G02F1/1333 G02F1/13 G02F1/13357 G09F9/00 G09F9/35		
CPC分类号	G02F1/133308 G02F2001/133314 G02F2201/503 G02F2201/465 G02F2001/133322		
优先权	1020010060156 2001-09-27 KR		
其他公开文献	US7304693		
外部链接	Espacenet USPTO		
摘要(译)			

公开了一种液晶显示装置，其中液晶显示模块和壳体紧密结合。形成在液晶显示模块的顶部框架上的至少一个突起将至少一个固定部分组合在一起，该固定部分形成在对应于至少一个突起的后壳体的一部分上。而且，形成在前壳的一部分上的固定突起插入液晶显示模块和后壳之间，从而防止液晶显示模块移动。因此，液晶显示模块和壳体紧密结合，并且通过减少制造液晶显示模块和壳体所需的部件数量，可以提高液晶显示装置的生产率。

