



(43) **Pub. Date:** **Feb. 18, 2010**

Publication Classification

(52) U.S. Cl. 349/58

(57) **ABSTRACT**

An LCD device capable of preventing damage of an LC panel by an impact damping member or through a design modification of a functional member when a functional plate such as a touch panel or the functional member is attached onto the LC panel. The LCD device comprises an LC panel, a backlight unit disposed below the LC panel for providing light, a functional member disposed on the LC panel within a size range of the LC panel, and an impact damping member disposed to be spacing from one or more sides of the functional member for absorbing an impact of the functional member when the LC panel moves.

(22) Filed: **Dec. 30, 2008**

Aug. 13, 2008 (KR) 10-2008-0079641




FIG. 1
RELATED ART




FIG. 2





FIG. 5



LIQUID CRYSTAL DISPLAY DEVICE

RELATED APPLICATION

[0001] The present disclosure relates to subject matter contained in priority Korean Application 10-2008-0079641, filed on Aug. 13, 2008, which is herein expressly incorporated by reference in its entirety.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The present invention relates to a liquid crystal display (LCD) device, and particularly, to an LCD device capable of preventing damage of an LC panel by an impact damping member or through a design modification of a functional member when a functional plate such as a touch panel or the functional member is attached onto the LC panel.

[0004] 2. Background of the Invention

[0005] Generally, one of display devices, a cathode ray tube (CRT) is being widely used to a monitor of a meter, an information terminal device, etc., as well as a TV. However, an electronic device mounted with the CRT therein is not implemented in a small size and a light weight due to a large size and a heavy weight of the CRT.

[0006] In order to replace the CRT, has been proposed an LCD device having a small size, a light weight, and low power consumption. Recently, are being increased demands for a flat type display device such as a notebook computer, a desk top computer, an outdoor monitor having a large size of 30-inch or more, and a wall-mounted TV.

[0007] In order to effectively use each kind of electronic device, being widely used a touch panel for inputting a signal onto a display of a display device without requiring a remote controller or an additional input device. More concretely, a flat type display device such as a liquid crystal display (LCD) device, a plasma display panel (PDP), and an electroluminescence (EL) is provided with a functional plate such as a touch panel onto a display thereof, thereby allowing a user to select his or her desired information with watching the image display device.

[0008] FIG. 1 is a sectional view of a touch panel integral type LCD device in accordance with the conventional art.

[0009] As shown in FIG. 1, the conventional touch panel integral type LCD device comprises an LC panel 50 for representing an image, a backlight unit disposed below the LC panel 50 and providing light, and a touch panel 60 attached onto the LC panel 50. The LC panel 50 may be provided with polarizing films 51 and 52 disposed on both side surfaces thereof.

[0010] The backlight unit includes a lamp 22 disposed on one or more sides of a lower cover 10 and providing light, a lamp housing 21 for coupling the lamp 22 thereto and protecting the lamp 22 from an external impact, a reflection plate 12 for reflecting light from the lamp 22 to the upper or front LC panel 50 without optical loss, a light guide plate 24 disposed at one side of the lamp 22 for

[0011] Here, the optical sheet 49 includes a diffusion plate 49a for obtaining a uniform brightness according to a viewing angle so as to enhance characteristics of light having passed through the light guide plate 24, a prism sheet 49b disposed on the diffusion plate 49a for enhancing a frontal brightness of light having passed through the diffusion plate 49a, and a protection sheet 49c for protecting the prism sheet 49b from scratch, and so on.

[0012] The LC panel 50 includes a TFT array substrate having a TFT at each unit pixel, a color filter substrate having color filters for representing colors, and an LC injected between the TFT array substrate and the color filter substrate. Here, the TFT array substrate is formed to have a larger area than the color filter substrate, thereby exposing out gate and data pad portions to which an external signal is input.

[0013] On the LC panel 50 having the polarizing films 51 and 52 attached thereto, disposed is a functional plate such as the touch panel 60, or a functional member. Here, the functional plate or the functional member has a size equal to or smaller than a size of the color filter substrate of the LC panel 50 without depending on a specific design reference.

[0014] However, when the functional member such as the touch panel 60 is attached onto the LC panel 50, the LC panel 50 become more susceptible to an external impact or vibration. This causes an edge region of the LC panel, especially, an edge region of the TFT array substrate to be damaged.

SUMMARY OF THE INVENTION

[0015] Therefore, an object of the present invention is to provide an LCD device capable of preventing damage of an LC panel by an impact damping member or through a design modification of a functional member when the functional member such as a touch panel is attached onto the LC panel.

[0016] To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described herein, there is provided a liquid crystal display (LCD) device, comprising: an LC panel; a backlight unit disposed below the LC panel for providing light; and a functional member disposed on the LC panel for preventing damage of the LC panel due to an impact when the LC panel moves.

[0017] According to another embodiment of the present invention, there is provided an LCD device, comprising: an LC panel; a backlight unit disposed below the LC panel for providing light; a functional member disposed on the LC panel within a size range of the LC panel; and an impact damping member disposed to be spacing from one or more sides of the functional member, for absorbing an impact of the functional member when the LC panel moves.

[0018] In the present invention, when the functional member for an additional function such as a touch panel is provided on the LC panel, can be prevented damage of the LC panel due to an external impact or vibration.

[0019] The foregoing and other objects, features, aspects and advantages of the present invention will become more apparent from the following detailed description of the present invention when taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0020] The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention. In the drawings:

[0021] FIG. 1 is a sectional view of a touch panel integral type LCD device in accordance with the conventional art;

[0022] FIG. 2 is an exploded perspective view of an LCD device according to a first embodiment of the present invention;

[0023] FIG. 3 is a sectional view showing a coupled state of the LCD device of FIG. 2;

[0024] FIG. 4 is a sectional view of an LCD device according to a second embodiment of the present invention; and

[0025] FIG. 5 is a sectional view showing a modification example of the LCD device of FIG. 4.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0026] Hereinafter, an LCD device of the present invention will be explained in more detail with reference to the attached drawings.

[0027] FIG. 2 is an exploded perspective view of an LCD device according to a first embodiment of the present invention, and FIG. 3 is a sectional view showing a coupled state of the LCD device of FIG. 2.

[0028] As shown in FIGS. 2 and 3, the LCD device according to a first embodiment of the present invention comprises a backlight unit (not shown) for receiving a voltage from outside and providing light, an LC panel 150 disposed above the backlight unit for displaying an image, and a functional member 160 disposed on the LC panel 150 for preventing damage of the LC panel 150 due to an impact when the LC panel 150 moves.

[0029] Here, the functional member 160 may include a tempered substrate 160a serving as a protection member for protecting the LC panel 150 from an external impact, and an anti-reflect layer 160b disposed on the tempered substrate 160a for reducing reflectivity of light incident from outside. Moreover, the functional member 160 may further include an adhesion layer 160c formed of the same refractivity as the tempered substrate 160a of the functional member 160, for adhering the functional member 160 onto the LC panel 150.

[0030] On both side walls of a lower cover 100 formed of iron or Electro Galvanized Steel (EGI) plate, vertically formed are balance PCBs (Printed circuit boards) for driving a plurality of lamps 120 by receiving an AC high voltage from external first and second inverters.

[0031] More concretely, the balance PCBs 101 and 103 respectively comprise connectors 101a and 103a for receiving an AC high voltage from the first and second inverters, ballast capacitors 101b and 103b formed in patterns for outputting a stable current from the AC high voltage, and lamp sockets 101c and 103c formed to have conductivity such that a ballast current is stably introduced into the lamps 120, and formed in an angle of 90° such that a plurality of lamps 120 are easily coupled thereto.

[0032] A reflection plate 105 is attached onto the lower cover 100 at a middle region of the balance PCBs 101 and 103 vertically disposed at both sides of the lower cover 100. As the reflection plate 105, may be used a white polyester film, or a film coated with metallic material such as Ag or Al. Visible rays on the reflection plate 105 has reflectivity about 90~97%. The thicker the coated film is, the higher the reflectivity is.

[0033] The plurality of lamps 120 are coupled to the lamp sockets 101c and 103c fixed onto the balance PCBs 101 and 103 and formed to be upwardly bent. Here, a distance between the lamps 120 coupled to the lamp sockets 101c and 103c, and the reflection plate 105 disposed at a rear side of the lamps 120 may be constant within the range of about 5 mm. For instance, when the distance between the lamps 120 and the reflection plate 105 is more than 5 mm, an optical sheet (not shown) to be coupled onto the lamps 120 may be influenced. This may cause a wrinkle phenomenon due to heat.

[0034] In order to control a distance between the reflection plate 105 and the lamps 120, the height of the balance PCBs 101 and 103 vertically disposed at both sides of the lower cover 100 may be controlled. Alternatively, the angle of the lamp sockets 101c and 103c may be controlled.

[0035] Here, will be explained a method for controlling a distance between the lamps 120 and the reflection plate 105 by controlling the angle of the lamp sockets 101c and 103c. The lamp sockets 101c and 103c may be bent freely enough for the lamps 120 to be coupled thereto. For instance, the lamp sockets 101c and 103c may be formed to have an 'L' shape. One end portions of the lamp sockets 101c and 103c are fixed on the balance PCBs 101 and 103, while another end portions thereof serve as holders for coupling the lamps 120.

[0036] The plurality of lamps 120 are coupled to the 'L'-shaped lamp sockets 101c and 103c fixed onto the balance PCBs 101 and 103, with a constant gap therebetween. Generally, an LCD TV of 32-inch is provided with about 16 lamps for high brightness, whereas an LCD TV of 40-inch is provided with about 18~20 lamps. However, the number of the lamps may be variable according to a model type of the LCD device. As the lamps 120, may be used one type of lamps among cold cathode fluorescent lamps (CCFL), external electrode fluorescent lamps (EEFL), and hot cathode fluorescent lamps (HCFL).

[0037] On the balance PCBs 101 and 103 including the lamp sockets 101c and 103c, disposed are fixing members for protecting the balance PCBs 101 and 103 from outside, i.e., side supports 130. Frames of the side support 130 formed by a pressing method include an inclined frame 130b formed to have a certain inclination angle and having semi-circular lamp fixing portions 130b1 for fixing the lamps 120 to the lower cover 100, a vertical frame 130a vertically formed and spacing from the inclined frame 130b, and an upper frame 130c extending from an upper side of the inclined frame 130b and the vertical frame 130a to be horizontally formed.

[0038] In the present invention, the vertical frames 130b of the side supports 130 are disposed at an outer periphery of both side walls of the lower cover 100. In order to outwardly protrude the connector 101a to which an AC high voltage is applied from the first and second inverters, holes are preferably formed at a part of the vertical frame 130a.

[0039] An optical member 140 is disposed in a state that both sides thereof are supported by the side supports 130. The optical member 140 includes a diffusion plate (not shown) for uniformly distributing light directly emitted from the plurality of lamps 120, and light reflected by the reflection plate 105 to all surfaces of the LC panel 150, and an optical sheet (not shown) such as a prism sheet and a protection sheet to allow light having passed through the diffusion plate to have an additional optical characteristic.

[0040] A main support 145 formed of molded synthetic resin or SUS steel is coupled to an upper side of the backlight unit. Here, the main support 145 is formed to have a stepped portion between inner and outer surfaces thereof with consideration that the LC panel 150 is disposed on a front surface (or upper surface) thereof. The main support 145 serves to maintain a balance of an entire force applied to the LCD device in the occurrence of an external impact, by being provided with the backlight unit therebelow.

[0041] The LC panel 150 disposed on the main support 145 undergoes a plurality of unit processes. More concretely, the LC panel 150 includes a TFT array substrate having a TFT at each unit pixel as a switching device, a color filter substrate

having color filters for representing colors, and an LC injected between the TFT array substrate and the color filter substrate.

[0042] Polarizers **151** and **152** are attached to both side surfaces of the LC panel **150**. The polarizers **151** and **152** serve to transmit only light vibrating in the same direction as polarizing axes, among light emitted from the backlight unit, but to absorb or reflect light vibrating in other directions by using a suitable medium, to implement light vibrating in a specific direction.

[0043] On the LC panel **150**, disposed is the function member **160** for protecting the LC panel **150** from an external impact and reducing reflectivity of light incident from outside.

[0044] The functional member **160** includes a tempered substrate **160a** for protecting the LC panel **150** from an external impact; an anti-reflect layer **160b** disposed on the tempered substrate **160a** to be exposed out, and contacting external light, and an adhesion layer **160c** formed below the tempered substrate **160a** and contacting the LC panel **150** or the polarizer **151** on the LC panel **150**.

[0045] Here, the tempered substrate **160a** may be implemented as tempered glass having a thickness of about 3 mm such that the LC panel **150** disposed therein is protected from an external impact. The tempered glass is formed by heating molded plate glass at a temperature of 500~600° C. close to a softening temperature, and is drastically cooled by compressed cool air. Then, the surface of the molded plate glass is deformed in compression, and the inside of the molded plate glass is deformed in tension. The tempered substrate has a bending intensity corresponding to 3~5 times of a general glass, an impact endurance corresponding to 3~8 times of a general glass, and an excellent heat endurance. Since the tempered substrate maintains a balance of an entire force therein, even if one side of the tempered substrate is cut off, the entire part is cracked into pieces. Accordingly, it is required to form the tempered substrate in a shape suitable for the purpose before performing a tempered process.

[0046] The anti-reflect layer **160b** formed on an upper side surface of the tempered substrate **160a** and exposed to external light has a surface processed by an anti-reflect sputtering. That is, the anti-reflect layer **160b** is formed as two materials having different refractivity are alternately formed on the tempered substrate **160a** in 5 or 6 layers. For instance, a first layer firstly exposed to sunlight or an external lamp is formed of a material having a low refractivity, a second layer is formed of a material having a high refractivity, and a third layer is again formed of a material having a low refractivity. Under this configuration, light incident from outside gradually disappears while passing through each layer, thereby reducing a reflectivity. However, the anti-reflect layer **160a** does not necessarily undergo a surface processing using an anti-reflect sputtering. Rather, various surface-processing methods such as an anti-reflect coating, or anti-contamination processing or an anti-fingerprint processing may be applied to the anti-reflect layer **160a**.

[0047] The adhesive layer **160c** formed on a lower side surface of the tempered substrate **160a** and contacting the LC panel **150** is formed of a paste, etc. having a similar refractivity to the upper tempered substrate **160a**, or the lower polarizer **151** in a UV or thermal hardening manner. Light incident to the anti-reflect layer **160b** and passing through the tempered substrate **160a** is made to be continuously absorbed into (or to pass through) the adhesive layer **160c** and the

polarizer **151** having a similar refractivity to the tempered substrate **160a**. Accordingly, a total reflectivity to outside of the LC panel **150** is reduced to the maximum.

[0048] For example, if light passing through the anti-reflect layer **160b** contacts air disposed at an air gap between the functional member **160** including the anti-reflect layer **160b** and the LC panel **150**, the light is outwardly reflected from a boundary between the functional member **160** and the air gap, due to different refractivity between the tempered substrate **160a** and the air. As a result, a total reflectivity to outside of the LC panel **150** increases.

[0049] To cope with this problem, the adhesive layer **160c** on the functional member **160** is formed of a material having a similar refractivity to the tempered substrate **160a**, and is formed of a material having a similar refractivity to the lower LC panel **150** or the polarizer **151** on the LC panel **150**.

[0050] As the paste having a similar refractivity of 1.4~1.6 to the tempered substrate **160a** or the polarizer **151**, an optical elastic resin, SVR (super view resin) containing an acryl-based ultraviolet hardening type resin as a main component and made from Sony Corporation of Japan may be used.

[0051] Here, the paste may additionally include at least one of a solvent, a plasticizer, and/or an interface activator. The paste enhances a bonding force between the tempered substrate **160a** and the polarizer **151** on the LC panel **150**. An amount of the paste may be varied to accelerate a UV or thermal hardening process.

[0052] The paste is disposed on a lower side surface of the tempered substrate **160a** in the form of liquid, and the tempered substrate **160a** having the paste thereunder is attached onto the polarizer **151** formed on one side surface of the LC panel **150**. Then, the paste is hardened by undergoing UV irradiation from an upper side of the tempered substrate **160a**, or heat supply from a lower side of the LC panel **150**. As a result, the protection member **160** coupled to the LC panel **150** is formed.

[0053] Rather than the method that a paste formed on a lower side surface of the tempered substrate **160a** is adhered onto the LC panel **150**, other methods may be used. That is, a paste may be formed on the polarizer **151** on the LC panel **150**, or may be directly formed on the LC panel **150** when the polarizer **151** is not implemented. Then, the tempered substrate **160a** is attached onto the paste. Then, the paste may undergo UV irradiation from an upper side of the tempered substrate **160a**, or heat supply from a lower side of the LC panel **150**, thereby being hardened. Accordingly, the functional member **160** coupled to the LC panel **150** may be formed.

[0054] When the functional member **160** is attached onto the LC panel **150**, a moving width of the LC panel **150** is increased by a heavy weight of the functional member **160** in the occurrence of an external vibration or impact applied to the LCD device. This may cause the LC panel **150** to have damages at edge regions thereof when the LCD device collides with the main support **145**.

[0055] In the present invention, the functional member **160** is formed to have a length (L') larger than a length (L) of the LC panel **150** with spacing from one or more sides of the LC panel **150**. Here, the functional member **160** is formed within a range of a stepped inner portion (A) of an upper frame of the main support **145**. Preferably, a tolerance between the functional member **160** and the main support **145** is less than a tolerance between the LC panel **150** and the main support **145**.

[0056] For instance, at edge portions of the TFT-array substrate of the LC panel 150, a gate pad portion or/and a data pad portion may be exposed out such that gate and data signals are input thereto. Here, the TFT-array substrate where the gate or data pad portion is exposed out may be more susceptible to an external impact or vibration than in any other portions. Accordingly, the functional member 160 having higher impact resistance than the TFT-array substrate formed of glass, etc. is formed to have a length longer than that of the TFT-array substrate where the gate or data pad portion is exposed out. This causes the functional member 160 having high impact resistance to firstly come in contact with the main support 145 even when the LC panel 150 is moved by an external impact or vibration. As a result, the TFT-array substrate is prevented from being damaged.

[0057] An upper cover 170 is coupled to the main support 145 and/or the lower cover 100, with covering four edges of the functional member 160 disposed on the LC panel 150, and with covering side surfaces of the main support 145.

[0058] FIG. 4 is a sectional view of an LCD device according to a second embodiment of the present invention.

[0059] Referring to FIG. 4, the LCD device according to a second embodiment of the present invention comprises an LC panel 250, a backlight unit disposed below the LC panel 250 for providing light, a functional member 260 disposed on the LC panel 250 within a size range of the LC panel 250, and an impact damping member 247 disposed to be spacing from one or more sides of the functional member 260 for absorbing an impact of the functional member 260 when the LC panel 250 moves. Here, the impact damping member 247 is provided on the main support 245.

[0060] In the LCD device according to the second embodiment of the present invention, the length (L') of one or more sides of the functional member 260 disposed on the LC panel 250 is formed to be shorter than the length (L) of the LC panel 250. Here, the impact damping member 247 is disposed at the stepped inner portion (A) of an upper frame of the main support 245, more concretely, between the main support 245 and the functional member 260.

[0061] Under this configuration, when the LC panel 250 is moved, may be indirectly prevented damage of the LC panel 250 due to an impact between the main support 245 and the LC panel 250. More concretely, even when the LC panel 250 is moved in the occurrence of an external impact or vibration, damage of the LC panel 250 occurring as the LC panel 250 comes in contact with the main support 245 is prevented. The reason is because the functional member 260 and the impact damping member 247 firstly come in contact with each other.

[0062] To this end, a gap (l') between the functional member 260 having the length (L') and the main support 245 is formed to be narrower than a gap (t) between the LC panel 250 having the length (L) and the main support 245.

[0063] The impact damping member 247 is provided at the inner side portion (A) of the main support 245 through a strong adhesive or various coupling manners. The impact damping member 247 may be formed of the same material as the main support 245, i.e., synthetic resin or SUS steel, or may be formed of a different material.

[0064] When it is assumed that the impact damping member 247 is formed of the same material as the main support 245, the impact damping member 247 may be integrally formed with the main support 245. That is, when the main support 245 is injection molded, the impact damping member

247 may be simultaneously injection molded. Accordingly, the shape of the impact damping member 247 is not limited in the present invention.

[0065] The LCD device according to the second embodiment is similar to the LCD device according to the first embodiment except for the impact damping member 247, and their detailed explanations will be omitted.

[0066] FIG. 5 is a sectional view showing a modification example of the LCD device of FIG. 4.

[0067] Referring to FIG. 5, the LCD device according to a third embodiment of the present invention comprises an LC panel 350, a backlight unit disposed below the LC panel 350 for providing light, a functional member 360 disposed on the LC panel 350 within a size range of the LC panel 350, an upper cover 370 coupled to an upper edge region of the functional member 360, and an impact damping member 347 disposed to be spacing from one or more sides of the functional member 360 for absorbing an impact of the functional member 360 when the LC panel 350 moves. Here, the impact damping member 347 is attached or coupled onto the upper cover 370.

[0068] In the same manner as the second embodiment, in the LCD device according to the third embodiment of the present invention, the length (L') of one or more sides of the functional member 360 disposed on the LC panel 350 is formed to be shorter than the length (L) of the LC panel 350. Here, the impact damping member 347 is disposed at the stepped inner portion (A) of an upper frame of the main support 345, more concretely, at the inner side portion (A) between the main support 245 and the functional member 260.

[0069] The impact damping member 247 may be formed of the same material as the main support 345, i.e., synthetic resin or SUS steel, or may be formed of a different material. The impact damping member 347 is attached or coupled onto the upper cover 370 through a strong adhesive or various coupling manners, and then is provided at the inner side portion (A) of the main support 345. Here, a gap (l') between the functional member 360 having the length (L') and the main support 345 is formed to be narrower than a gap (t) between the LC panel 350 having the length (L) and the main support 345.

[0070] Under this configuration, even if the LC panel 350 is moved by an external impact or vibration, damage of the LC panel 350 due to contact with the main support 345 is prevented. The reason is because the impact damping member 347 and the functional member 360 firstly come in contact with each other.

[0071] The LCD device according to the third embodiment is similar to the LCD device according to the first embodiment except for the impact damping member 347, and their detailed explanations will be omitted.

[0072] The foregoing embodiments and advantages are merely exemplary and are not to be construed as limiting the present disclosure. The present teachings can be readily applied to other types of apparatuses. This description is intended to be illustrative, and not to limit the scope of the claims. Many alternatives, modifications, and variations will be apparent to those skilled in the art. The features, structures, methods, and other characteristics of the exemplary embodiments described herein may be combined in various ways to obtain additional and/or alternative exemplary embodiments.

[0073] As the present features may be embodied in several forms without departing from the characteristics thereof, it

should also be understood that the above-described embodiments are not limited by any of the details of the foregoing description, unless otherwise specified, but rather should be construed broadly within its scope as defined in the appended claims, and therefore all changes and modifications that fall within the metes and bounds of the claims, or equivalents of such metes and bounds are therefore intended to be embraced by the appended claims.

What is claimed is:

1. A liquid crystal display (LCD) device, comprising:
an LC panel;
a main support provided with a square-shaped frame work having an opened center portion, for supporting the LC panel thereon;
a backlight unit disposed below the LC panel for providing light; and
a functional member disposed on the LC panel, and having one or more sides larger than the LC panel, for preventing damage of the LC panel occurring when the LC panel moves, by firstly coming in contact with the main support.
2. The LCD device of claim 1, wherein the functional member is implemented as one of a tempered substrate and a touch panel.
3. The LCD device of claim 1, wherein a tolerance between the functional member and the main support is less than a tolerance between the LC panel and the main support.

4. A liquid crystal display (LCD) device, comprising:
an LC panel;
a backlight unit disposed below the LC panel for providing light;
a functional member disposed on the LC panel within a size range of the LC panel; and
an impact damping member disposed to be spacing from one or more sides of the functional member for absorbing an impact of the functional member when the LC panel moves.

5. The LCD device of claim 4, further comprising a main support provided at edge regions of the LC panel and the functional member.

6. The LCD device of claim 4, wherein a distance (L) between the main support and the LC panel is longer than a distance (L') between the functional member and the impact damping member.

7. The LCD device of claim 4, wherein the impact damping member is coupled to the main support.

8. The LCD device of claim 4, further comprising an upper cover provided at upper edge regions of the LC panel and the functional member.

9. The LCD device of claim 4, wherein the impact damping member is coupled onto the upper cover.

* * * * *

专利名称(译)	液晶显示装置		
公开(公告)号	US20100039578A1	公开(公告)日	2010-02-18
申请号	US12/318532	申请日	2008-12-30
[标]申请(专利权)人(译)	乐金显示有限公司		
申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	ROH SU DONG BAIK IN SU		
发明人	ROH, SU-DONG BAIK, IN-SU		
IPC分类号	G02F1/1333		
CPC分类号	G02F2201/503 G02F1/133604		
优先权	1020080079641 2008-08-13 KR		
其他公开文献	US8405791		
外部链接	Espacenet USPTO		

摘要(译)

一种LCD装置，当诸如触摸板或功能构件的功能板附接到LC面板上时，能够防止冲击阻尼构件对LC面板的损坏或通过功能构件的设计修改。LCD装置包括LC面板，设置在LC面板下方用于提供光的背光单元，设置在LC面板的LC面板的尺寸范围内的功能构件，以及设置成与一个或多个间隔开的冲击阻尼构件当LC面板移动时，功能构件的侧面用于吸收功能构件的冲击。

