



US007126651B2

(12) **United States Patent**
Kim et al.

(10) **Patent No.:** **US 7,126,651 B2**
(45) **Date of Patent:** **Oct. 24, 2006**

(54) **LIQUID CRYSTAL DISPLAY APPARATUS
HAVING PARTICULAR PROTRUDING
PORTIONS AND FIXING GROOVES**

(75) Inventors: **Dong-Cheol Kim**, Suwon-si (KR);
Young-Bee Chu, Suwon-si (KR);
Tae-Gil Kang, Suwon-si (KR);
Young-Jae Lee, Seongnam-si (KR);
Jung-Ki Kim, Seoul (KR); **Jae-Chang**
Choi, Yongin-si (KR); **Jeong-Seok Oh**,
Seoul (KR); **Yong-Seok Kwak**, Seoul
(KR)

(73) Assignee: **Samsung Electronics Co., Ltd.** (KR)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **11/103,720**

(22) Filed: **Apr. 12, 2005**

(65) **Prior Publication Data**

US 2005/0179832 A1 Aug. 18, 2005

Related U.S. Application Data

(62) Division of application No. 10/114,639, filed on Apr.
2, 2002, now Pat. No. 6,919,937.

(30) **Foreign Application Priority Data**

Sep. 27, 2001 (KR) 2001-60156

(51) **Int. Cl.**

G02F 1/1333 (2006.01)
G02F 1/1335 (2006.01)
H05K 7/00 (2006.01)

(52) **U.S. Cl.** **349/58; 349/64; 349/65;**
361/681

(58) **Field of Classification Search** 349/58,
349/61, 65; 361/600, 681, 679; 174/50
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,626,550 B1* 9/2003 Choi 362/632
2001/0003471 A1* 6/2001 Lee et al. 349/58
2001/0036057 A1* 11/2001 Fukuyoshi 361/681
2001/0038523 A1* 11/2001 Bang 361/681

* cited by examiner

Primary Examiner—Andrew Schechter

Assistant Examiner—Mike Qi

(74) *Attorney, Agent, or Firm*—Cantor Colburn LLP

(57) **ABSTRACT**

Disclosed is a liquid crystal display apparatus in which a liquid crystal display module and cases are tightly combined. At least one protuberance formed on a top chassis of the liquid crystal display module combines at least one fixing portion formed on a portion of a rear case corresponding to the at least one protuberance. Also, a fixing protuberance formed on a portion of a front case is inserted into between the liquid crystal display module and the rear case, thereby preventing the liquid crystal display module from being moved. Therefore, the liquid crystal display module and the cases are tightly combined, and productivity of the liquid crystal display apparatus can increase by reducing the number of parts demanded for fabrication of the liquid crystal display module and the cases.

4 Claims, 34 Drawing Sheets




FIG. 1
(PRIOR ART)




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7B




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32





FIG. 33



LIQUID CRYSTAL DISPLAY APPARATUS HAVING PARTICULAR PROTRUDING PORTIONS AND FIXING GROOVES

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a divisional application of U.S. patent application Ser. No. 10/114,639, filed on Apr. 2, 2002 now U.S. Pat. No. 6,919,937, the disclosure of which is herein incorporated by reference in its entirety.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a liquid crystal display apparatus, and more particularly to a liquid crystal display apparatus in which a liquid crystal display module is tightly combined with cases, which is available for a notebook computer.

2. Description of the Related Art

Recently, information processors have been rapidly developed in a trend with various architectures, functions and faster information processing speed. Such information processors need display devices such as a liquid crystal display apparatus for displaying processed information to a user.

When a voltage is applied to a liquid crystal cell, a molecular arrangement of the liquid crystal is changed. The liquid crystal display device converts variations in optical characteristics such as a birefringence, a rotatory polarization, a dichroism and a light scattering according to the molecular arrangements of the liquid crystal into variations in visual characteristics, thereby displaying an image.

A size of the liquid crystal display apparatus gradually increases according to a demand of the user, and a liquid crystal display module and cases for receiving the liquid crystal display module also have dimensions that gradually increase in response to the size of the liquid crystal display apparatus. Thus, research concerning not only an assembled structure between the liquid crystal display module and cases but also a layout for parts of the liquid crystal display apparatus is performed so as to meet an augmentation of the dimension of the liquid crystal display apparatus and reductions of a weight, a size and a thickness of the liquid crystal display apparatus in these days.

In particular, a combining space according to a combination of the liquid crystal display module and cases becomes more important as for an installation structure between the liquid crystal display module and cases.

FIG. 1 is an exploded perspective view schematically showing a conventional liquid crystal display apparatus.

Referring to FIG. 1, a liquid crystal display apparatus 60 has a liquid crystal display module 30, for displaying an image, and cases including a front case (not shown) and a rear case 40 in order to receive the liquid crystal display module 30.

The liquid crystal display module 30 includes a display unit for displaying the image, a back light assembly for supplying a light to the display unit, a mold frame for receiving the display unit and the back light assembly, and a top chassis combining with the mold frame to fix the display unit and the back light assembly to the mold frame. When the back light assembly and the display unit are successively received in the mold frame, the top chassis combines with the mold frame.

A top installation method is utilized for mounting the liquid crystal display module 30 in the rear case 40. Par-

ticularly, first, second, third, and fourth mounting portions 11, 12, 13 and 14 having predetermined heights are formed on four corners of the top chassis 10 of the liquid crystal display module 30. First, second, third and fourth screwed combining holes 11a, 12a, 13a and 14a are formed through the first, second, third and fourth mounting portions 11, 12, 13 and 14, respectively. First, second, third and fourth burrings 41, 42, 43 and 44 corresponding to the first, second, third and fourth screwed combining holes 11a, 12a, 13a and 14a are formed on four corners of the rear case 40 corresponding to the first, second, third and fourth mounting portions 11, 12, 13 and 14.

When the first, second, third and fourth screwed combining holes 11a, 12a, 13a and 14a of the top chassis 10 correspond to the first, second, third and fourth burrings 41, 42, 43 and 44 of the rear case 40, respectively, first, second, third and fourth screws 11b, 12b, 13b and 14b engage with the first, second, third and fourth screwed combining holes 11a, 12a, 13a and 14a and the first, second, third and fourth burrings 41, 42, 43 and 44, thereby fixing the liquid crystal display module 30 to the rear case 40.

The top installation method, however, has some disadvantages as follows.

First, the number of assembling steps for fabrication of the liquid crystal display apparatus 60 increases since the liquid crystal display module 30 is combined with the cases using the screws. Hence, productivity as well as operation efficiency decreases in fabricating the liquid crystal display apparatus 60.

Also, manufacturing costs and time for the liquid crystal display apparatus 60 increase because additional parts such as the screws are demanded for combining the liquid crystal display module 30 with those cases.

Furthermore, an overall size of the liquid crystal display apparatus 60 increases because the first, second, third and fourth mounting portions 11, 12, 13, and 14 are protruded from side walls of the top chassis toward outside.

SUMMARY OF THE INVENTION

The present invention provides a liquid crystal display apparatus in which a liquid crystal display module is tightly combined with cases.

The present invention further provides a liquid crystal display apparatus enhancing productivity by reducing the number of parts demanded for a fabrication of the liquid crystal display apparatus.

In one aspect, there is provided a liquid crystal display apparatus comprising a liquid crystal display module having at least one first protruding portion, a rear case for receiving the liquid crystal display module, wherein the rear case has at least one first fixing portion for guiding and fixing the at least one first protruding portion, and a front case combined with the rear case wherein the front case has at least one second protruding portion for fixing the liquid crystal display module.

The liquid crystal display module includes a back light assembly for generating a light, a display unit for receiving the light to display an image, a mold frame for receiving the back light assembly and the display unit, and a top chassis for fixing the display unit and the back light assembly to the mold frame by combining with the mold frame, which has a first side wall and a second side wall opposed each other wherein the at least one first protruding portion having a predetermined height is formed on the first and the second side walls, respectively.

The at least one first fixing portion is respectively formed on third and fourth side walls of the rear case corresponding to the first and second side walls of the top chassis. The at least one first fixing portion includes at least one first fixing groove extended from upper faces of the third and the fourth side walls of the rear case toward a bottom face of the rear case, and a second fixing groove extended from a lower portion of the first fixing groove toward a fifth side wall disposed between the third and the fourth side walls of the rear case.

The liquid crystal display module slides toward the second fixing groove of the rear case to be combined with the rear case when the at least one first protruding portion of the top chassis is received in the first fixing groove of the rear case.

The at least one second protruding portion is protruded from first and second upper faces of the front case corresponding to the third and the fourth side walls of the rear case, and the at least one second protruding portion is received in the at least one first fixing groove of the rear case. A bottom face of the at least one second protruding portion of the front case directly contacts a bottom face of the at least one first fixing groove of the rear case.

Also, a third protruding portion protruded toward the bottom face of the rear case is formed on a third upper face of the front case positioned on a sixth side wall of the rear case corresponding to the fifth side wall of the rear case. The third protruding portion of the front case is received in an isolation space formed between the sixth side wall of the rear case and the liquid crystal display module, and a bottom face of the third protruding portion directly contacts the bottom face of the rear case.

Also, a fourth protruding portion protruded toward the fifth side wall of the rear case is formed on a seventh side wall of the top chassis corresponding to the fifth side wall of the rear case. The at least one second fixing portion is formed on the fifth side wall of the rear case wherein the at least one second fixing portion has a third fixing groove formed from the liquid crystal display module received in the rear case toward the fifth side wall of the rear case. Hence, the liquid crystal display module is fixed as the fourth protruding portion of the top chassis is received in the third fixing groove formed on the second fixing portion of the rear case when the liquid crystal display module slides toward the fifth side wall of the rear case.

In addition, the at least one first fixing portion comprises a fourth fixing groove extended from upper faces of the third and the fourth side walls of the rear case toward the bottom face of the rear case. The at least one second protruding portion is protruded by a predetermined height from the first and second upper faces of the front case corresponding to the third and fourth side walls of the rear case. The liquid crystal display module combines the rear case by the first protruding portion of the top chassis received in a lower portion of the fourth fixing groove, and the second protruding portion of the front case received in an upper portion of the fourth fixing groove so as to press the first protruding portion. A height of the fourth fixing groove is substantially identical to a sum of heights of the first protruding portion of the top chassis and the second protruding portion of the front case.

In another aspect, there is provided a liquid crystal display apparatus comprising a liquid crystal display module having a first protruding portion and a second protruding portion, and a rear case for receiving the liquid crystal display module wherein the rear case has a fixing groove for guiding and receiving the first protruding portion and a fixing protuberance for fixing the liquid crystal display module.

The liquid crystal display module includes a back light assembly for generating a light, a display unit for receiving the light and displaying an image, a mold frame for receiving the back light assembly and the display unit, and a top chassis combined with the mold frame for fixing the display unit and the back light assembly, which has a first side wall and a second side wall opposed each other wherein first and second protruding portions protruding by a predetermined height from the first and second side walls.

The fixing groove is formed on third and fourth side walls of the rear case corresponding to the first and second side walls of the top chassis. The fixing groove includes a first fixing groove formed from upper faces of the third and fourth side walls of the rear case toward a bottom face of the rear case, and a second fixing groove extended from a lower portion of the first fixing groove toward a fifth side wall of the rear case.

The liquid crystal display module slides toward the second fixing groove of the rear case to be combined with the rear case after the first protruding portion of the top chassis is received in the first groove of the rear case.

The fixing protuberances are formed on the third and said fourth side walls of the rear case corresponding to the second protruding portion formed on the first and second side walls of the top chassis. Also, each fixing protuberance has a supporting portion having a predetermined height toward an opposing side wall, a body extended from an end of the supporting portion toward the fifth side wall and separated by a predetermined interval from the third and the fourth side walls, and a suspending portion protruding from the body and engaging with the second protruding portion of the top chassis, preventing the liquid crystal display module from being moved. The suspending portion has a slope shape gradually wider toward said fifth side wall of the rear case.

According to the liquid crystal display apparatus of the present invention, the liquid crystal display module is fixed in the rear case as protuberances formed on the top chassis are combined with fixing portions formed on the rear case, and also the liquid crystal display module is firmly fixed by fixing protuberances formed on the front case. Therefore, the combining strength between the liquid crystal module and those cases can increase, and productivity of the liquid crystal display apparatus can be improved by reducing the number of parts demanded in fabricating the liquid crystal module and cases.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other advantages of the present invention will become apparent by describing exemplary embodiment with reference to the attached drawings in which:

FIG. 1 is an exploded perspective view schematically showing a conventional liquid crystal display apparatus;

FIG. 2 is an exploded perspective illustrating a liquid crystal display apparatus according to one embodiment of the present invention;

FIG. 3 is a plan view showing a structure of a top chassis shown in FIG. 2;

FIG. 4 is a plan view showing a structure of a rear case shown in FIG. 2;

FIG. 5 is a plan view showing a structure of a front case shown in FIG. 2;

FIG. 6 is partially cut perspective view illustrating the front case shown in FIG. 5;

FIG. 7A is a plan view showing an assembled structure between the top chassis and the rear case;

FIG. 7B is a cross-sectional view taken along the line of C_1-C_2 for illustrating the assembled structure between the top chassis and the rear case shown in FIG. 7A;

FIG. 8 is a plan view showing an assembled structure among the front case, the top chassis and the rear case shown in FIG. 7A;

FIGS. 9 to 11 are partially cut perspective views illustrating a method for combining the top chassis with the rear case;

FIGS. 12 and 13 are cross-sectional views illustrating the method for combining the top chassis with the rear case;

FIG. 14 is a cross-sectional view taken along the line of A_1-A_2 for illustrating the assembled structure of the top chassis and the rear case shown in FIG. 7A;

FIG. 15 is a cross-sectional view taken along the line of B_1-B_2 for illustrating the assembled structure of the liquid crystal display device shown in FIG. 8;

FIG. 16 is a plan view showing a front case according to another embodiment of the present invention;

FIGS. 17 and 18 are cross-sectional views illustrating a combination of the front case and the rear case;

FIG. 19 is an exploded perspective view showing a liquid crystal display apparatus according to another embodiment of the present invention;

FIG. 20 is a plan view showing a structure of a rear case shown in FIG. 19;

FIG. 21 is a plan view showing a structure of a front case shown in FIG. 19;

FIGS. 22 and 23 are partially cut perspective views illustrating a method for combining the top chassis with the rear case shown in FIG. 19;

FIG. 24 is a cross-sectional view showing an assembled structure of the top chassis, the rear case and the front case;

FIG. 25 is an exploded perspective view showing a liquid crystal display device according to still another embodiment of the present invention;

FIG. 26 is a plan view showing a structure of a top chassis shown in FIG. 25;

FIG. 27 is a partial perspective view showing a structure of the top chassis shown in FIG. 25;

FIGS. 28 and 29 are side views illustrating the top chassis shown in FIG. 25;

FIG. 30 is a partially cut perspective view showing the rear case shown in FIG. 25;

FIG. 31 is a plan view showing the top chassis and the rear case shown in FIG. 25 before the top chassis combines with the rear case;

FIG. 32 is an enlarged plan view showing 'B' shown in FIG. 31; and

FIG. 33 is a plan view illustrating an assembled structure of the top chassis and the rear case shown in FIG. 25.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Hereinafter, a liquid crystal display device according to various embodiments of the present invention will be described in detail with reference to the drawings.

FIG. 2 is an exploded perspective view showing a liquid crystal display device according to one embodiment of the present invention, FIG. 3 is a plan view illustrating a structure of a top chassis in FIG. 2, FIG. 4 is a plan view showing a structure of a rear case in FIG. 2, FIG. 5 is a plan view showing a structure of a front case in FIG. 2, and FIG. 6 is a partially cut perspective view showing the front case in FIG. 5.

Referring to FIG. 2, a liquid crystal display apparatus 600 has a liquid crystal display module 300 for displaying an image, and cases for receiving the liquid crystal display module 300. Those cases include a front case 500 and a rear case 400.

The liquid crystal display module 300 includes a display unit 310 for displaying the image, and a back light assembly 360 disposed under the display unit 310 for supplying a light to the display unit 310 (see FIG. 7B). The display unit 310 and the back light assembly 360 are received in a mold frame 200. Also, a top chassis 100 is provided for fixing the display unit 310 and the back light assembly 360 to the mold frame 200.

In particular, when the back light assembly 360 and the display unit 310 are subsequently received in the mold frame 200, the top chassis 100 is provided on the display unit 310. The top chassis 100 has a rectangular clamp shape. The top chassis 100 covers an upper portion of the display unit 310 except for an effective display area of the display unit 310. The top chassis 100 is combined with the mold frame 200 so that inner surfaces of four side walls of the top chassis 100 correspond to outer surfaces of side walls of the mold frame 200.

As shown in FIGS. 2 and 3, the top chassis 100 has a first side wall 110, a second side wall 120, a third side wall 130 and a fourth side wall 140. First to third protuberances 111, 112 and 113 respectively having a predetermined height are formed on the first side wall 110 of the top chassis 100, and fourth to sixth protuberances 121, 122 and 123 respectively having a predetermined height are formed on the second side wall 120 of the top chassis 100. The second side wall 120 is opposed to the first side wall 110. In addition, seventh and eighth protuberances 131 and 132 are formed on the third side wall 130, which locates between the first side wall 110 and the second side wall 120. The first to eighth protuberances 111, 112, 113, 121, 122, 123, 131 and 132 can be formed by partially cutting predetermined portions of the first to third side walls 110, 120 and 130 of the top chassis 100 and extending the portions toward outside. The first to eighth protuberances 111, 112, 113, 121, 122, 123, 131 and 132 may have various shapes such as hemi-circular shapes, trapezoidal shapes or rectangular shapes when the first to eighth protuberances 111, 112, 113, 121, 122, 123, 131 and 132 are observed from the direction of the cases 500 and 400. Preferably, the first to eighth protuberances 111, 112, 113, 121, 122, 123, 131 and 132 have trapezoidal shapes, respectively.

Referring to FIGS. 2 and 4, the rear case 400 includes fifth to eighth side walls 410, 420, 430 and 440, and a bottom face 450 enclosed by the fifth to eighth side walls 410, 420, 430 and 440. An upper face of the rear case 400 corresponding to the bottom face 450 is opened. First to third protruding portions 411, 412 and 413 having a predetermined height are formed on the fifth side wall 410 of the rear case 400, which corresponds to and is combined with the first side wall 110 of the top chassis 100. Also, fourth to sixth protruding portions 421, 422 and 423 having a predetermined height are formed on the sixth side wall 420 of the rear case 400, which corresponds to and is combined with the second side wall 120 of the top chassis 100. Furthermore, seventh and eighth protruding portions 431 and 432 having a predetermined height are formed on the seventh side wall 430 of the rear case 400, which corresponds to and is combined with the third side wall 130 of the top chassis 100.

First to sixth fixing grooves 411a, 412a, 413a, 421a, 422a and 423a are respectively formed on the first to sixth protruding portions 411, 412, 413, 421, 422 and 423 so as to

be combined with the first to sixth protuberances 111, 112, 113, 121, 122 and 123 formed on the first and second side walls 110 and 120 of the top chassis 100. In addition, seventh to twelfth fixing grooves 411b, 412b, 413b, 421b, 422b and 423b are formed on the first to sixth protruding portions 411, 412, 413, 421, 422 and 423. The first to sixth fixing grooves 411a, 412a, 413a, 421a, 422a and 423a are respectively formed from upper ends of the fifth and sixth side walls 410 and 420 of the rear case 400 toward the bottom face 450 of the rear case 400. The seventh to twelfth fixing grooves 411b, 412b, 413b, 421b, 422b and 423b are respectively extended from lower portions of the first and sixth fixing grooves 411a, 412a, 413a, 421a, 422a and 423a toward the seventh side wall 430 of the rear case 400. Thus, each corresponding pair of the first to sixth fixing grooves 411a, 412a, 413a, 421a, 422a and 423a and the seventh to twelfth fixing grooves 411b, 412b, 413b, 421b, 422b and 423b may form a shape of "L".

Thirteenth and fourteenth fixing grooves 431a and 432a are formed on the seventh and eighth protruding portions 431 and 432 positioned on the seventh side wall 430 of the rear case 400 so that the thirteenth and fourteenth fixing grooves 431a and 432a are combined with the seventh and eighth protuberances 131 and 132 formed on the third side wall 130 of the top chassis 100.

The rear case 400 includes first and second suspending protuberances 441 and 442 respectively extended from the bottom face 450 and the eighth side wall 440. The first and second suspending protuberances 441 and 442 will be described in detail with reference to FIGS. 7A and 7B.

Referring to FIGS. 5 and 6, and further FIG. 16, the front case 500 has four side walls, and first to fourth top faces 510, 520, 530 and 540. The four side walls of the front case 500 are combined with the fifth to eighth side walls 410, 420, 430, and 440 of the rear case 400, and the first to fourth top faces 510, 520, 530 and 540 cover a non-effective display area of the liquid display module 300. Also, a lower face of the front case 500 corresponding to an effective display area of the liquid display module 300 is opened.

Ninth and tenth protuberances 511 and 512 are formed on the first top face 510 of the front case 500 positioned over the eighth side wall 440 of the rear case 400. Each of the ninth and tenth protuberances 511 and 512 has a substantially same height as a height of the eighth side wall 440 of the rear case 400 as shown in FIG. 6. The ninth and tenth protuberances 511 and 512 will be described more detail with reference to cross-sectional views.

FIG. 7A is a plan view showing an assembled structure between the top chassis and the rear case, FIG. 7B is a cross-sectional view taken along the line of C₁-C₂ for illustrating the assembled structure between the top chassis and the rear case, and FIG. 8 is a plan view showing an assembled structure among the front case, the top chassis and the rear case.

When the liquid crystal display module 300 including the display unit 310 is received in the rear case 400 as shown in FIG. 7B, the first to third protuberances 111, 112 and 113 formed on the first side wall 110 of the top chassis 100 are respectively combined with the first to third fixing grooves 411a, 412a and 413a formed on the fifth side wall 410 of the rear case 400. Also, the fourth to sixth protuberances 121, 122 and 123 formed on the second side wall 120 of the top chassis 100 are respectively combined with the fourth to sixth fixing grooves 421a, 422a and 423a formed on the sixth side wall 420 of the rear case 400, as shown in FIG. 7A.

Then, the first to sixth protuberances 111, 112, 113, 121, 122 and 123 move toward the seventh side wall 430 of the rear case 400, so the first to sixth protuberances 111, 112, 113, 121, 122 and 123 are received in the seventh to twelfth fixing grooves 411b, 412b, 413b, 421b, 422b and 423b, respectively. In this way, the rear case 400 is combined with the top chassis 100, which is illustrated in FIGS. 9-11. The seventh and eighth protuberances 131 and 132 formed on the third side wall 130 of the top chassis 100 are respectively combined with the thirteenth and fourteenth fixing grooves 431a and 432a formed on the seventh side wall 430 of the rear case 400.

When the liquid crystal display module 300 moves toward the seventh side wall 430 of the rear case 400 to be combined with the rear case 400, an isolation space A is formed between the eighth side wall 440 of the rear case 400 and the fourth side wall 140 of the top chassis 100.

Referring to FIG. 7B, the first and second suspending protuberances 441 and 442 are protruded from the eighth side wall 440 of the rear case 400 toward the liquid crystal display module 300 along the bottom face 450 of the rear case 400. The first and second suspending protuberances 441 and 442 have terraced shapes gradually lowered from the eighth side wall 440 to the liquid crystal display module 300. The widths of the first and second suspending protuberances 441 and 442 are identical to a width W1 of the isolation space A between the liquid crystal module 300 and the eighth side wall 440 of the rear case 400. Hence, an end of the liquid crystal display module 300 moves along the first and second suspending protuberances 441 and 442 of the rear case 400 when the liquid crystal display module 300 moves toward the seventh side wall 430 after the liquid crystal display module 300 is received in the rear case 400. A predetermined portion of the fourth side wall 140 of the top chassis 100 corresponds to terraced portions of the first and second suspending protuberances 441 and 442 when the liquid crystal display module 300 completely moves, thereby preventing the liquid crystal display module 300 from being moved toward the eighth side wall 440 of the rear case 400.

The front case 500 is combined with the rear case 400 while the liquid crystal display module 300 is received in the rear case 400. The ninth and tenth protuberances 511 and 512 are inserted into the isolation space A between the rear case 400 and the top chassis 100. Widths of the ninth and tenth protuberances 511 and 512 are substantially identical to the width W1 of the isolation space A so that the ninth and tenth protuberances 511 and 512 are tightly inserted into the isolation space A. Thus, the liquid crystal display module 300 does not move in the isolation space A by the ninth and tenth protuberances 511 and 512, as shown in FIGS. 8 and 15.

FIGS. 9 to 11 are partially cut perspective views illustrating a method for combining the top chassis with the rear case, and FIGS. 12 and 13 are cross-sectional views illustrating the method for combining the top chassis with the rear case.

Referring to FIGS. 9 to 13, the fifth protuberance 422 formed on the sixth side wall 420 of the rear case 400 includes the fifth fixing groove 422a formed from the upper face of the sixth side wall 420 toward the bottom face 450 of the rear case 400, and the eleventh fixing groove 422b extended from the lower portion of the fifth fixing groove 422a toward the seventh side wall 430 of the rear case 400. The fifth fixing groove 422a is higher than the eleventh

fixing groove **422b**. That is, an upper face of the eleventh fixing groove **422b** is not exposed to the upper face of the sixth side wall **420**.

The fifth protuberance **122** protruding toward the sixth side wall **420** of the rear case **400** by a predetermined height is formed on the second side wall **120** of the top chassis **100** corresponding to the sixth side wall **420** of the rear case **400**. A portion of the second side wall **120** of the top chassis **100** is partially cut in the direction parallel with the bottom face **450** of the rear case **400**, and the cut portion of the second side wall **120** of the top chassis **100** is extended toward the sixth side wall **420** of the rear case **400**. The fifth protuberance **122** protrudes toward the sixth side wall **420** of the rear case **400**.

When the top chassis **100** is received in the rear case **400**, the fifth protuberance **122** of the top chassis **100** is inserted into the fifth fixing groove **422a** of the rear case **400**. The liquid crystal display module **300** moves toward the seventh side wall **430** of the rear case **400** when the fifth protuberance **122** makes contact with a bottom face of the fifth fixing groove **422a**. The fifth protuberance **122** is combined with the eleventh fixing groove **422b** so that the liquid crystal display module **300** is fixed in the rear case **400**. Namely, the fifth protuberance **122** is fixed by an upper end of the fifth protruding portion **422** adjacent the eleventh fixing groove **422b**, thereby preventing the liquid crystal display module **300** from being moved through the opened upper face of the rear case **400**. Therefore, the liquid crystal display module **300** received in the rear case **400** cannot move through the opened upper face of the rear case **400**.

FIG. **14** is a cross-sectional view taken along the line of A_1 – A_2 for illustrating the assembled structure of the top chassis and the rear case shown in FIG. **7A**, and FIG. **15** is a cross-sectional view taken along the line of B_1 – B_2 for illustrating the assembled structure of the liquid crystal display device shown in FIG. **8**.

Referring to FIG. **14**, the back light assembly **360** is received in the mold frame **200**. In particular, a reflection plate **340** is received in a bottom face of the mold frame **200**, and then a light guiding plate **330** is mounted thereon. Optical sheets **350** are mounted on the light guiding plate **330** so that the back light assembly **360** is received in the mold frame **200**. The display unit **310** is mounted on the back light assembly **360**.

When the back light assembly **360** and the display unit **310** are received in the mold frame **200**, the top chassis **100** is provided for fixing the back light assembly **360** and the display unit **310** in the mold frame **200**. The top chassis **100** is combined with the mold frame **200**, thereby completing the liquid crystal display module **300**.

The completed liquid crystal display module **300** is received in the rear case **400**. The sixth protuberance **123** formed on the second side wall **120** of the top chassis **100** is combined with the sixth and twelfth fixing grooves **423a** and **423b** formed on the sixth side wall **420** of the rear case **400**. That is, the sixth protuberance **123** of the top chassis **100** moves along the sixth fixing groove **423a** toward the twelfth fixing groove **423b** to be combined therewith. Hence, the liquid crystal display module **300** is fixed in the rear case **400** so that the liquid crystal display module **300** is not separated from the rear case **400** through the opened upper face of the rear case **400**.

Referring to FIG. **15**, the front case **500** is combined with the rear case **400** after the liquid crystal display module **300** is received in the rear case **400**. The ninth protuberance **511** is formed on the first upper face **510** of the front case **500**. The ninth protuberance **511** protrudes from the first upper

face **510** toward the rear case **400** and has a width substantially identical to the width $W1$ of the isolation space **A** formed between the liquid crystal display module **300** and the rear case **400**. Also, a height of the ninth protuberance **511** is identical to a height of the eighth side wall **440**.

When the liquid crystal display module **300** is received in the rear case **400**, the liquid crystal display module **300** moves toward the seventh side wall **430** of the rear case **400** to be combined therewith. The isolation space **A** is formed between the eighth side wall **440** of the rear case **400** and the fourth side wall **140** of the top chassis **100**. The ninth protuberance **511** formed on the first upper face **510** of the front case **500** is inserted into the isolation space **A**. Therefore, the liquid crystal display module **300** does not move toward the eighth side wall **440** of the rear case **400**.

FIG. **16** is a plan view showing a front case according to another embodiment of the present invention, and FIGS. **17** and **18** are cross-sectional views illustrating a combination of the front case and the rear case shown in FIG. **16**.

Referring to FIG. **16**, eleventh to sixteenth protuberances **531**, **532**, **533**, **541**, **542** and **543** toward the bottom face **450** of the rear case **400** are respectively formed on the third and fourth upper faces **530** and **540** of the front case **500** except the first and second upper faces **510** and **520** of the front case **500**. The eleventh to sixteenth protuberances **531**, **532**, **533**, **541**, **542** and **543** correspond to the first to sixth fixing grooves **411a**, **412a**, **413a**, **421a**, **422a** and **423a** of the rear case **400**, respectively. In addition, the eleventh to sixteenth protuberances **531**, **532**, **533**, **541**, **542** and **543** are spaced from the side walls of the front case **500** by a length identical to a width of each of the fifth and sixth side walls **410** and **420** of the rear case **400**.

As shown in FIGS. **17** and **18**, after the liquid crystal display module **300** is received in the rear case **400**, the eleventh to thirteenth protuberances **531**, **532** and **533** are respectively inserted into the first to third fixing grooves **411a**, **412a** and **413a** when the front case **500** is combined with the rear case **400**. Heights of the eleventh to thirteenth protuberances **531**, **532** and **533** are substantially the same as those of the first to third fixing grooves **411a**, **412a** and **413a**. As a result, a wall of each of the eleventh to thirteenth protuberances **531**, **532** and **533** close an inlet of each of the seventh to ninth fixing grooves **411b**, **412b** and **413b** when the eleventh to thirteenth protuberances **531**, **532** and **533** are received in the first to third fixing grooves **411a**, **412a** and **413a**. Therefore, the liquid crystal display module **300** cannot move toward the eighth side wall **440** of the rear case **400**.

Hereinafter, it will be described an assembled structure of a liquid crystal display module and cases of a liquid crystal display apparatus according to another embodiment of the present invention with reference to FIGS. **19** to **24**.

FIG. **19** is an exploded perspective view showing a liquid crystal display apparatus according to another embodiment of the present invention, FIG. **20** is a plan view showing a structure of a rear case shown in FIG. **19**, and FIG. **21** is a plan view showing a structure of a front case shown in FIG. **19**. In FIG. **19**, elements identical to those in FIG. **2** have the same reference numerals and the description concerning their functions will be omitted.

Referring to FIG. **19**, a liquid crystal display apparatus **900** has a liquid crystal display module **300** for displaying an image, and cases for receiving the liquid crystal display module **300**. Those cases include a front case **800** and a rear case **700**.

When a back light assembly **360** and a display unit **310** are successively received in a mold frame **200**, a top chassis

100 is mounted on the display unit 310. The top chassis 100 covers an upper portion of the display unit 310 besides an effective display area of the display unit 310, and insides of four side walls of the top chassis 100 are combined with outsides of side walls of the mold frame 200, respectively.

First to third protuberances 111, 112 and 113 are formed on a first side wall 110 of the top chassis 100, and fourth to sixth protuberances 121, 122 and 123 are formed on a second side wall 120 facing the first side wall 110 of the top chassis 100.

As shown in FIG. 20, the rear case 700 includes a bottom face 750 and ninth to twelfth side walls 710, 720, 730 and 740. Ninth to eleventh protruding portions 711, 712 and 713 having a predetermined height are formed on the ninth side wall 710 of the rear case 700 combined with the first side wall 110 of the top chassis 100. Also, twelfth to fourteenth protruding portions 721, 722 and 723 having a predetermined height are formed on the tenth side wall 720 of the rear case 700 combined with the second side wall 120 of the top chassis 100.

Fifteenth to seventeenth fixing grooves 711a, 712a and 713a are respectively formed on the ninth to eleventh protruding portions 711, 712 and 713 from an upper end of the ninth side wall 710 toward the bottom face 750 of the rear case 700. Eighteenth to twentieth fixing grooves 721a, 722a and 723a are respectively formed on the twelfth to fourteenth protruding portions 721, 722 and 723 from an upper end of the tenth side wall 720 of the rear case 700 toward the bottom face 750 of the rear case 700.

Referring to FIG. 21, the front case 800 is combined with the rear case 700 after the liquid crystal display module 300 is received in the rear case 700. Seventeenth to nineteenth protuberances 811, 812 and 813 having a predetermined height are formed on a fifth upper face 810 of the front case 800 adjacent to the ninth side wall 710 of the rear case 700. The seventeenth to nineteenth protuberances 811, 812 and 813 are formed toward the bottom face 750 of the rear case 700. In addition, twentieth to twenty-second protuberances 821, 822 and 823 having a predetermined height toward the bottom face 750 of the rear case 700 are formed on a sixth upper face 820 of the front case 800 adjacent to the tenth side wall 720 of the rear case 700. The seventeenth to twenty-second protuberances 811, 812, 813, 821, 822 and 823 are formed spaced from side walls of the front case 800 by a distance identical to each of the thickness of the ninth and tenth side walls 710 and 720.

FIGS. 22 and 23 are partially cut perspective views illustrating a method for combining the top chassis with the rear case in FIG. 19, and FIG. 24 is a cross-sectional view showing an assembled structure of the top chassis, the rear case and the front case shown in FIG. 19.

Referring to FIGS. 22 and 23, the tenth protruding portion 712 formed on the ninth side wall 710 of the rear case 700 includes the sixteenth fixing groove 712a formed from an upper end of the ninth side wall 710 toward the bottom face 750 of the rear case 700.

A second protuberance 112 having a predetermined height toward the ninth side wall 710 of the rear case 700 is formed on the first side wall 110 of the top chassis 100 corresponding to the ninth side wall 710 of the rear case 700. The first side wall 110 of the top chassis 100 is partially cut in parallel with the bottom face 750 of the rear case 700 and toward the ninth side wall 710 of the rear case 700, and the second protuberance 112 is protruded toward a cut portion of the first side wall 110 of the top chassis 100. When the top chassis 100 is received in the rear case 700, the second protuberance 112 of the top chassis 100 is inserted into the sixteenth fixing groove 712a of the rear case 700.

Referring to FIG. 24, when the liquid crystal display module 300 is received in the rear case 700, the front case 800 is mounted thereon. The seventeenth to nineteenth protuberances 811, 812 and 813 protruded from the fifth upper face 810 of the front case 800 are inserted into the fifteenth to seventeenth fixing grooves 711a, 712a and 713a, respectively. That is, each of the fifteenth to seventeenth fixing grooves 711a, 712a and 713a has a depth identical to a sum of heights of the first to third protuberances 111, 112 and 113 of the top chassis 100 and heights of the seventeenth to nineteenth protuberances 811, 812 and 813 of the front case 800. The seventeenth to nineteenth protuberances 811, 812 and 813 of the front case 800 pressurize the first to third protuberances 111, 112 and 113, thereby preventing the liquid crystal display module 300 from being deviated from the rear case 700.

Hereinafter, it will be described an assembled structure of a liquid crystal display module and cases of a liquid crystal display apparatus according to still another embodiment of the present invention with reference to FIGS. 25 to 33.

FIG. 25 is an exploded perspective view showing a liquid crystal display apparatus according to still another embodiment of the present invention, FIG. 26 is a plan view showing a structure of a top chassis shown in FIG. 25, FIG. 27 is a partial perspective view showing a structure of the top chassis shown in FIG. 25, and FIGS. 28 and 29 are side views illustrating the top chassis shown in FIG. 25.

Referring to FIG. 25, a liquid crystal display apparatus 1600 has a liquid crystal display module 1300 for displaying an image, and cases for receiving the liquid crystal display module 1300. Those cases include a front case 1500 and a rear case 1400.

When a back light assembly and a display unit are successively received in a mold frame 1200, a top chassis 1100 is mounted on the display unit. The top chassis 1100 has a rectangular cramp shape. The top chassis 1100 covers an upper portion of the display unit except for an effective display area of the display unit, and insides of four side walls of the top chassis 1100 are combined with outsides of side walls of the mold frame 1200, respectively.

As shown in FIGS. 26 to 29, the top chassis 1100 has thirteenth to sixteenth side walls 1110, 1120, 1130 and 1140. Twenty-third to twenty-fifth protuberances 1111, 1112 and 1113 each having a predetermined height are formed on the thirteenth side wall 1110 of the top chassis 1100, and twenty-sixth to twenty-eighth protuberances 1121, 1122 and 1123 each having a predetermined height are formed on the fourteenth side wall 1120 corresponding to the thirteenth side wall 1110. Also, twenty-ninth and thirtieth protuberances 1131 and 1132 each having a predetermined height are formed on the fifteenth side wall 1130 of the top chassis 1100. The twenty-third to thirtieth protuberances 1111, 1112, 1113, 1121, 1122, 1123, 1131 and 1132 are formed by cutting predetermined portions of the thirteenth to fifteenth side walls 1110, 1120 and 1130 of the top chassis 1100. The twenty-fourth, twenty-fifth, twenty-seventh and twenty-eighth protuberances 1112, 1113, 1122 and 1123 are extended parallel with a bottom face 1450 of the rear case 1400, with various shapes. The twenty-fourth, twenty-fifth, twenty-seventh and twenty-eighth protuberances 1112, 1113, 1122 and 1123 respectively have semicircular shapes, trapezoidal shapes or rectangular shapes when observed from the front and rear cases 1500 and 1400. Among them, trapezoidal shapes are preferable. In the meantime, the twenty-third and twenty-sixth protuberances 1111 and 1121 are extended perpendicular to the bottom face 1450 of the rear case 1400. The twenty-third and twenty-sixth protuber-

ances 1111 and 1121 have trapezoidal shapes when observed from the nineteenth side wall 1430 of the rear case 1400.

FIG. 30 is a partially cut perspective view showing the rear case shown in FIG. 25.

Referring to FIGS. 25 and 30, the rear case 1400 has seventeenth to twentieth side walls 1410, 1420, 1430 and 1440, and the bottom face 1450 enclosed by the seventeenth to twentieth side walls 1410, 1420, 1430 and 1440. An upper face of the rear case 1400 corresponding to the bottom face 1450 is opened. Fifteenth and sixteenth protruding portions 1412 and 1413 each having a predetermined height are formed on the seventeenth side wall 1410 of the rear case 1400 combined with the thirteenth side wall 1110 of the top chassis 1100. Seventeenth and eighteenth protruding portions 1422 and 1423 each having a predetermined height are formed on the eighteenth side wall 1420 of the rear case 1400 combined with the fourteenth side wall 1120 of the top chassis 1100.

Twenty-first to twenty-fourth fixing grooves 1412a, 1413a, 1422a and 1423a are formed on the fifteenth to eighteenth protruding portions 1412, 1413, 1422 and 1423. The twenty-first to twenty-fourth fixing grooves 1412a, 1413a, 1422a and 1423a are formed from upper ends of the seventeenth and eighteenth side walls 1410 and 1420 of the rear case 1400 toward the bottom face 1450 of the rear case 1400. Also, twenty-fifth to twenty-eighth fixing grooves 1412b, 1413b, 1422b and 1423b are formed on the fifteenth to eighteenth protruding portions 1412, 1413, 1422 and 1423. The twenty-fifth to twenty-eighth fixing grooves 1412b, 1413b, 1422b and 1423b are parallel with the bottom face 1450 of the rear case 1400 and protrude toward the nineteenth side wall 1430.

First and second fixing protuberances 1411 and 1412 are respectively formed on the seventeenth and eighteenth side walls 1410 and 1420 of the rear case 1400, and the first and second fixing protuberances 1411 and 1412 are combined with the twenty-third and twenty-sixth protuberances 1111 and 1121, respectively. The first and second fixing protuberances 1411 and 1412 respectively have supporting portions 1411a and 1421a, and bodies 1411b and 1421b. Supporting portions 1411a and 1421a protrude toward opposite side walls by a predetermined height, and bodies 1411b and 1421b are extended from ends of supporting portions 1411a and 1421a toward the nineteenth side wall 1430. Suspending portions 1411c and 1421c are formed on sides of the bodies 1411b and 1421b, and the suspending portions 1411c and 1421c are protruded from the bodies 1411b and 1421b. The suspending portions 1411c and 1421c are engaged with the twenty-third and the twenty-sixth protuberances 1111 and 1121.

The bodies 1411b and 1421b are separated from the seventeenth and the eighteenth side walls 1410 and 1420 by a predetermined interval, and the suspending portions 1411c and 1421c have a slope shape that is gradually wider toward the nineteenth side wall 1430 of the rear case 1400.

Twenty-ninth and thirtieth fixing grooves 1431a and 1432a are formed on the nineteenth and twentieth protruding portions 1431 and 1432 which are formed on the nineteenth side wall 1430 of the rear case 1400 and protrude toward the twentieth side wall 1440 by a predetermined height. The twenty-ninth and thirtieth fixing grooves 1431a and 1432a are combined with the twenty-ninth and thirtieth protuberances 1131 and 1132 formed on the fifteenth side wall 1130 of the top chassis 1100, respectively.

FIG. 31 is a plan view showing the top chassis and the rear case shown in FIG. 25 before the top chassis is completely combined with the rear case, FIG. 32 is an enlarged plan

view showing 'B' shown in FIG. 31, and FIG. 33 is a plan view illustrating an assembled structure of the top chassis and the rear case shown in FIG. 25.

Referring to FIG. 31, when the liquid crystal display module 1300 is received in the rear case 1400, the twenty-fourth and twenty-fifth protuberances 1112 and 1113 formed on the thirteenth side wall 1110 of the top chassis 1100 are respectively combined with the twenty-first and twenty-second fixing grooves 1412a and 1413a formed on the seventeenth side wall 1410 of the rear case 1400. Also, the twenty-seventh and twenty-eighth protuberances 1122 and 1123 of the top chassis 1100 are respectively combined with the twenty-third and twenty-fourth fixing grooves 1422a and 1423a of the rear case 1400.

The twenty-third and twenty-sixth protuberances 1111 and 1121 make contact with portions of bodies 1411a and 1421b positioned between the supporting portions 1411a and 1421a and the suspending portions 1411c and 1421c of the first and second fixing protuberances 1411 and 1421.

When the liquid crystal display module 1300 moves toward the nineteenth side wall 1430 of the rear case 1400, the twenty-fourth and twenty-fifth protuberances 1112 and 1113 formed on the thirteenth side wall 1110 of the top chassis 1100 are respectively combined with the twenty-fifth and twenty-sixth fixing grooves 1412b and 1413b formed on the seventeenth side wall 1410 of the rear case 1400. In addition, the twenty-seventh and twenty-eighth protuberances 1122 and 1123 formed on the fourteenth side wall 1120 of the top chassis 1100 are respectively combined with the twenty-seventh and twenty-eighth fixing grooves 1422a and 1423b formed on the eighteenth side wall 1420 of the rear case 1400.

Referring to FIG. 32, the twenty-third and twenty-sixth protuberances 1111 and 1121 are inclined to the seventeenth and eighteenth side walls 1410 and 1420 of the rear case 1400 and move toward the nineteenth side wall 1430 of the rear case 1400 through the suspending portions 1411c and 1421c having slope shapes as those bodies 1411b and 1421b are inclined toward the seventeenth and eighteenth side walls 1410 and 1420 of the rear case by elastic forces of bodies 1411b and 1421b.

As shown in FIG. 33, the twenty-third and twenty-sixth protuberances 1111 and 1121 are engaged with bodies 1411b and 1421b at ends of the suspending portions 1411c and 1421c, and the bodies 1411b and 1421b support the twenty-third and the twenty-sixth protuberances 1111 and 1121 by restoring force of the bodies 1411b and 1421b. The twenty-third and twenty-sixth protuberances 1111 and 1121 are hung by the suspending portions 1411c and 1421c, thereby preventing the liquid crystal display module 300 from being moved toward the twentieth side wall 1440 corresponding to the nineteenth side wall 1430 of the rear case 1400.

Also, the twenty-ninth and thirtieth protuberances 1131 and 1132 formed on the fifteenth side wall 1130 of the top chassis 1100 are respectively combined with the twenty-ninth and thirtieth fixing grooves 1431a and 1432a formed on the nineteenth side wall 1430 of the rear case 1400 when the liquid crystal display module 1300 moves toward the nineteenth side wall 1430 of the rear case 1400. Therefore, the liquid crystal module 1300 is not separated from the rear case 1400 through the open upper face of the rear case 1400.

An isolation space A is formed between the liquid crystal display module 1300 and the twentieth side wall 1440 of the rear case 1400 as shown in FIG. 33. Also, at least one protuberance inserted into the isolation space A may be formed on an upper face of the front case 1500 corresponding to the twentieth side wall 1440 of the rear case 1400 so

15

as to more effectively prevent the liquid crystal display module 1300 from being moved toward the isolation space A.

As described above, according to the liquid crystal display apparatus of the present invention, protuberances are formed on the top chassis, and fixing portions to be combined with the protuberances are formed on the rear case facing the top chassis. Also, fixing protuberances are formed on predetermined portions of the front case, and the fixing protuberances are inserted into between the liquid crystal display module and the rear case.

Therefore, the liquid crystal display module is fixed in the rear case as the protuberances formed on the top chassis are combined with the fixing portions formed on the rear case, and also the liquid crystal display module is tightly fixed therein by the fixing protuberances formed on the front case.

In addition, the combining strength between the liquid crystal module and the cases can increase, and productivity of the liquid crystal display apparatus can be improved by reducing the number of parts demanded in order to assemble the liquid crystal module and cases.

Although the preferred embodiments of the present invention have been described, it is understood that the present invention should not be limited to these preferred embodiments but various changes and modifications can be made by one skilled in the art within the spirit and scope of the present invention as hereinafter claimed.

What is claimed is:

1. A liquid crystal display apparatus comprising:

- a liquid crystal display module having at least one first protruding portion;
- a rear case for receiving said liquid crystal display module, said rear case having at least one first fixing portion for guiding and fixing said at least one first protruding portion; and
- a front case combined with said rear case, said front case having at least one second protruding portion for fixing said liquid crystal display module,

16

wherein said liquid crystal display module comprises:

- a back light assembly for generating a light;
- a display unit for receiving the light to display an image;
- a mold frame for receiving said back light assembly and said display unit; and

a top chassis for fixing said display unit and said back light assembly to said mold frame by combining with said mold frame, said top chassis having opposing first and second side walls wherein each of said first and second side walls of said top chassis comprises said at least one first protruding portion,

wherein said rear case comprises third and fourth side walls corresponding to said first and second side walls of said top chassis, and each of said third and fourth side walls comprises said at least one first fixing portion, and

wherein said at least one first fixing portion comprises at least one fixing groove extended from upper faces of said third and fourth side walls of said rear case toward a bottom face of said rear case.

2. The liquid crystal display apparatus of claim 1, wherein said at least one second protruding portion is protruded by a predetermined height from first and second upper faces of said front case corresponding to said third and fourth side wall of said rear case.

3. The liquid crystal display apparatus of claim 2, wherein said liquid crystal display module combines with said rear case by said first protruding portion of said top chassis being received in a lower portion of said fixing groove, and said second protruding portion of said front case received in an upper portion of said fixing groove so as to press said first protruding portion.

4. The liquid crystal display apparatus of claim 3, wherein a height of said fixing groove is substantially identical to a sum of heights of said first protruding portion of said top chassis and said second protruding portion of said front case.

* * * * *

专利名称(译)	液晶显示装置具有特定的突出部分和固定槽		
公开(公告)号	US7126651	公开(公告)日	2006-10-24
申请号	US11/103720	申请日	2005-04-12
[标]申请(专利权)人(译)	金东CHEOL 褚杨BEE KANG TAE GIL LEE YOUNG JAE 金正KI 崔在常 OH JEONG SEOK KWAK YONG SEOK		
申请(专利权)人(译)	金东哲 褚YOUNG-BEE KANG TAE-GIL 李英宰 金正KI 崔在常 OH JEONG-SEOK KWAK永硕		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	KIM DONG CHEOL CHU YOUNG BEE KANG TAE GIL LEE YOUNG JAE KIM JUNG KI CHOI JAE CHANG OH JEONG SEOK KWAK YONG SEOK		
发明人	KIM, DONG-CHEOL CHU, YOUNG-BEE KANG, TAE-GIL LEE, YOUNG-JAE KIM, JUNG-KI CHOI, JAE-CHANG OH, JEONG-SEOK KWAK, YONG-SEOK		
IPC分类号	G02F1/1333 G02F1/1335 H05K7/00 G02F1/13 G02F1/13357 G09F9/00 G09F9/35		
CPC分类号	G02F1/133308 G02F2001/133314 G02F2001/133322 G02F2201/465 G02F2201/503		
代理机构(译)	康托科尔伯恩LLP		
优先权	1020010060156 2001-09-27 KR		
其他公开文献	US20050179832A1		
外部链接	Espacenet USPTO		

摘要(译)

公开了一种液晶显示装置，其中液晶显示模块和壳体紧密结合。形成在液晶显示模块的顶部框架上的至少一个突起将至少一个固定部分组合在一起，该固定部分形成在对应于至少一个突起的后壳体的一部分上。而且，形成在前壳的一部分上的固定突起插入液晶显示模块和后壳之间，从而防止液晶显示模块移动。因此，液晶显示模块和壳体紧密结合，并且通过减少制造液晶显示模块和壳体所需的部件数量，可以提高液晶显示装置的生产率。

