



US006667790B2

(12) **United States Patent**
Yanagawa et al.

(10) **Patent No.:** **US 6,667,790 B2**
(45) **Date of Patent:** **Dec. 23, 2003**

(54) **LIQUID CRYSTAL DISPLAY HAVING
PARTICULAR SPACER**

(75) Inventors: **Kazuhiko Yanagawa**, Mobara (JP);
Keiichiro Ashizawa, Mobara (JP);
Masahiro Ishii, Mobara (JP);
Masayuki Hikiba, Mobara (JP)

(73) Assignee: **Hitachi, Ltd.**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

5,576,867 A	11/1996	Baur et al.	
5,598,285 A	1/1997	Kondo et al.	
5,786,876 A	7/1998	Ota et al.	
5,917,572 A *	6/1999	Kurauchi et al.	349/156
5,956,111 A	9/1999	Ohta et al.	
5,978,063 A *	11/1999	Crawford et al.	349/155
6,097,467 A *	8/2000	Fujimaki et al.	349/155
6,211,937 B1 *	4/2001	Miyachi et al.	349/156
6,320,636 B2 *	11/2001	Zhang et al.	349/139
6,411,360 B1 *	6/2002	Matsuyama et al.	349/156
6,433,852 B1 *	8/2002	Sonoda et al.	349/156
6,445,437 B1 *	9/2002	Miyazaki et al.	349/156

FOREIGN PATENT DOCUMENTS

JP 3-59522 * 3/1991 G02F/1/1335

* cited by examiner

Primary Examiner—Toan Ton

Assistant Examiner—Mike Qi

(21) Appl. No.: **10/106,954**

(22) Filed: **Mar. 28, 2002**

(65) **Prior Publication Data**

US 2002/0113935 A1 Aug. 22, 2002

Related U.S. Application Data

(63) Continuation of application No. 09/497,996, filed on Feb. 4, 2000.

(30) **Foreign Application Priority Data**

Feb. 5, 1999 (JP) 11-029053

(51) **Int. Cl.⁷** **G02F 1/1343**; G02F 1/1333;
G02F 1/1335

(52) **U.S. Cl.** **349/139**; 349/141; 349/110;
349/106

(58) **Field of Search** 349/139, 141,
349/155, 110, 106

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,904,056 A * 2/1990 Castleberry 350/333

(57) **ABSTRACT**

The present invention is to provide the multi-domain system IPS (In—Plane Switching mode) liquid crystal display which has high contrast and does not have an improper image display. According to an aspect of the present invention, there is provided a black matrix formed between a pair of substrates and formed over a plurality of drain lines and gate lines, a plurality of spaces arranged under the black matrix, wherein a plurality of liquid crystal molecules lined to a boundary direction of the black matrix in “OFF” state, and having a first group and a second group in “ON” state, wherein a switching angle of the second group is opposite to a switching angle of the first group.

21 Claims, 22 Drawing Sheets




FIG. 1






FIG. 2*FIG. 3*


FIG 4

FIG. 5




FIG. 6






FIG. 7A*FIG. 7B*

FIG 8




FIG. 9




FIG. 10











FIG. 11A*FIG. 11B*










FIG. 15*FIG. 16*



FIG. 17*FIG. 18*



FIG. 19*FIG. 20*



FIG. 21*FIG. 22*


FIG. 23



FIG. 24A*FIG. 24B*


FIG. 25


FIG. 26

FIG. 28





FIG 30

LIQUID CRYSTAL DISPLAY HAVING PARTICULAR SPACER

This application is a continuation application of U.S. application Ser. No. 09/497,996 filed on Feb. 4, 2000.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a liquid crystal display device. More specifically, the invention relates to a liquid crystal display device with high contrast characteristics of the multi-domain system using spacers.

2. Description of the Prior Art

Active matrix liquid crystal display devices using active elements as represented by thin-film transistors (TFT) have now been widely used as display terminals of OA equipment since they are light in weight and have picture quality equivalent to that of cathode-ray tubes.

The display system of the liquid crystal display devices can be roughly divided into two. One is a system in which liquid crystals are sandwiched by two substrates having transparent electrodes and are driven by a voltage applied to the transparent electrodes, and light incident upon the liquid crystals and transmitted through the transparent electrodes is modulated to achieve display.

Another one is a system in which liquid crystals are driven by an electric field which is nearly in parallel with the surface of a substrate between two electrodes that are formed on the same substrate, and light incident upon the liquid crystals through a gap between the two electrodes is modulated to provide display.

Features of the latter system have been disclosed in, for example, U.S. Pat. Nos. 5,576,867, 5,598,285, 5,786,876, 5,956,111 and Japanese Patent No. 02907137. Moreover features of a multi-domain system IPS (In-Plane Switching mode) liquid crystal display have been disclosed in, for example, U.S. Pat. No. 5,745,207.

In general, an orientation process that prepares an orientation film for controlling liquid crystal molecules is done by rubbing using a rotating rubbing roller on the surface of an orientation film. However, when spaces are formed on an orientation layer, an orientation process can cause alignment defects as a result of the differences in surface level. Specifically, when spacers are formed in the display region, an alignment defect can result in an improper image display.

SUMMARY OF THE INVENTION

Accordingly, an object of the present invention is to provide multi-domain system IPS (In-Plane Switching mode) liquid crystal display which have high contrast and do not suffer from improper image display. This invention provide a remarkable high contrast display (350:1) as compared to current model displays (200:1).

According to one aspect of the present invention, there is provided a black matrix formed between a pair of substrates and formed over a plurality of drain lines and gate lines, a plurality of spacers arranged under the black matrix, wherein a plurality of liquid crystal molecules are aligned to a boundary direction of the black matrix in the OFF state, and having a first group and a second group in the ON state, wherein a switching angle of the second group is opposite to a switching angle of the first group.

According to another aspect of the present invention, there is provided a plurality of liquid crystal molecules having a negative dielectric constant anisotropy and inter-

posed between said pair of orientation layers, a black matrix formed over another of a pair of substrates in a matrix shape, a plurality of spacers formed between the black matrix and one of a pair of orientation layers, wherein said plurality of liquid crystal molecules having X direction of an initial orientation angle, and twisted to +Y direction and -Y direction when driving voltage is applied.

According to another aspect of the present invention, there is provided a plurality of liquid crystal molecules having a positive dielectric constant anisotropy and interposed between a pair of orientation layers, a black matrix formed over another of a pair of substrates in a matrix shape, a plurality of spacers formed between the black matrix and one of the pair of orientation layers, wherein a plurality of liquid crystal molecules having Y direction of an initial orientation angle, and twisted to +X direction and -X direction when a driving voltage is applied.

According to another aspect of the present invention, there is provided a plurality of liquid crystal molecules having a negative dielectric constant anisotropy and interposed between said pair of orientation layers, a black matrix formed over another of a pair of substrates in a matrix shape, a plurality of spacers formed between the black matrix and one of a pair of orientation layers, wherein said plurality of crystal molecules having X direction of an initial orientation angle, and twisted to +Y direction and -Y direction when driving voltage is applied.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a plan view of the pixel of a liquid crystal display according to a first embodiment of the present invention.

FIG. 2 is a sectional view of the pixel of a liquid crystal display cut along the line II—II in FIG. 1. FIG. 3 is a sectional view of the spacer in illustration of a alignment defect on an orientation layer.

FIG. 4 is a plan view of the pixel of a liquid crystal display according to a second embodiment of the present invention.

FIG. 5 is a plan view of the pixel of a liquid crystal display according to a third embodiment of the present invention.

FIG. 6 is a plan view of the pixel of a liquid crystal display according to a fourth embodiment of the present invention.

FIGS. 7A and 7B are plan views of the pixel of a liquid crystal display according to a fifth embodiment of the present invention.

FIG. 8 is a sectional view of the liquid crystal display according to a seventh embodiment of the present invention.

FIG. 9 is a sectional view of the liquid crystal display according to an eighth embodiment of the present invention.

FIG. 10 is a sectional view of the spacer of a liquid crystal display according to a tenth embodiment of the present invention.

FIG. 11A is a plan view of the pixel of a liquid crystal display according to an eleventh embodiment of the present invention.

FIG. 11B is a plan view of the pixel of a liquid crystal display according to a twelfth embodiment of the present invention.

FIG. 12 is a sectional view of the spacer of a liquid crystal display according to a thirteenth embodiment of the present invention.

FIGS. 13A–13E are flow charts of sectional views of a spacer illustrating the steps A to E of fabricating a substrate 1B.

FIGS. 14A–14E are flow charts of sectional views of a spacer illustrating the steps A to E of fabricating a substrate 1B.

FIG. 15 is a sectional view of the spacer of a liquid crystal display according to a fourteenth embodiment of the present invention.

FIG. 16 is a sectional view of the spacer of a liquid crystal display according another invention of the fourteenth embodiment.

FIG. 17 is a sectional view of the spacer of a liquid crystal display according to a fifteenth embodiment of the present invention.

FIG. 18 is a plan view of the pixel of a liquid crystal display according to a sixteenth embodiment of the present invention.

FIG. 19 is a plan view of the pixel of a liquid crystal display according to another invention of the sixteenth embodiment.

FIG. 20 is a plan view of the pixel of a liquid crystal display according to a seventeenth embodiment of the present invention.

FIG. 21 is a plan view of the pixel of a liquid crystal display according to an eighteenth embodiment of the present invention.

FIG. 22 is a plan view of the pixel of a liquid crystal display according to a nineteenth embodiment of the present invention.

FIG. 23 is a plan view of the pixel of a liquid crystal display according to a twenty-first embodiment of the present invention.

FIGS. 24A–24B are plan views of the pixel of a liquid crystal display according to a twenty-second embodiment of the present invention.

FIG. 25 is a plan view of the pixel of a liquid crystal display according to a twenty-third embodiment of the present invention.

FIG. 26 is a plan view of the pixel of a liquid crystal display according to a twenty-fifth embodiment of the present invention.

FIG. 27 is a plan view of the pixel of a liquid crystal display according to a twenty-sixth embodiment of the present invention.

FIG. 28 is a plan view of the pixel of a liquid crystal display according to a twenty-seventh embodiment of the present invention.

FIG. 29 is a plan view of the pixel of a liquid crystal display according to a twenty-eighth embodiment of the present invention.

FIG. 30 is a plan view of the pixel of a liquid crystal display according to a twenty-ninth embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The present invention will hereunder be described in more detail.

[Embodiment 1]

FIG. 1 is a plan view of the pixel of a liquid crystal display according to a first embodiment of the present invention. In the first embodiment, a plurality of liquid crystal molecules having a positive dielectric constant anisotropy, and FIG. 1 shows one pixel of a plurality of pixels forming in matrix shape. Each pixel is defined in a region where two adjacent gate lines 2 and two adjacent drain lines 3 intersect. And each pixel includes a thin-film transistor TFT, a capacitor Cadd, a pixel electrode 5, a counter electrode 4A and a counter voltage line 4. The gate lines 2 and the counter

voltage lines 4 extend in the X direction in the drawing and are arranged in the Y direction. The drain lines 3 extend in the Y direction and are arranged in the X direction. The pixel electrode 5 is connected to the thin-film transistor TFT. The material of the gate line 2 is selected from a group of chromium, aluminum and molybdenum, and the counter voltage line 4 is formed by the same material with the gate line 2.

A counter voltage is supplied to the counter electrodes 4A via the counter voltage line 4 from an external circuit. And the counter electrodes 4A and the counter voltage line 4 have a shape of a letter H in the each pixels. The pixel electrode 5 and the counter electrode 4A are opposed to each other, and the optical state of the liquid crystals LC (ON state) is controlled by an electric field between each pixel electrode 5 and the counter electrode 4A, thereby to control the display. The pixel electrodes 5 and the counter electrodes 4A are formed like comb teeth, and extend in a slender form in the Y direction.

Here, the pixel electrode 5 and the counter electrode 4A have a herringbone shape for the multi-domain system. The counter electrode 4A maintains the distance with the pixel electrode 5 by increasing the width of the counter electrode 4A. Hence, the face of the drain line 3 side of the counter electrode 4A is formed parallel with the drain line 3, and the face of the pixel electrode 5 side of the counter electrode 4A is formed parallel with the pixel electrode 5.

Therefore, the direction of the electric field which is disposed in the upper pixel region of the counter voltage line 4 in a pixel between the pixel electrode 5 and the counter electrode 4A is different from the lower one pixel region. In FIG. 1, the direction of the electric field which is disposed at the upper pixel region has the angle of $+\theta$ with respect to the direction parallel to the counter voltage line 4, but the direction of the electric field which is disposed at the lower one has the angle of $-\theta$ with respect to the direction parallel to the counter voltage line 4.

The above-mentioned shape provides liquid crystal molecules to switch in reverse directions at each pixel region, and a light transmittance change at each pixel.

In this invention, it can prevent the inversion of luminance when the view point of the observer is at an angle with respect to the slanting direction of the liquid crystal display panel. In the first embodiment, one pixel has the difference angle of $\pm\theta$ dividing upper and lower pixel region, but it allows two adjoining two pixels to have difference angles of $+\theta$ and $-\theta$, respectively.

Thin film transistor TFT consists of the gate line 2, a drain electrode 3A, a source electrode 5A, a semiconductor layer 6 and a gate insulator (silicon nitride). An insulator is formed on the gate line 2 as a gate insulator, and the semiconductor layer 6 whose material is amorphous silicon is formed on the gate insulator. A drain electrode 3A and a source electrode 5A are formed on the semiconductor layer 6; and the thin film transistor TFT becomes an inverted stagger type thin film transistor. The drain electrode 3A and a source electrode 5A are the same layer, and the drain electrode 3A contacts with the drain line, and the source electrode 5A contacts with the pixel electrode, respectively.

In the first embodiment, an initial orientation angle is the Y direction, so a rubbing direction is also the Y direction. The absolute value of the angle between the drain line 3 and the direction of the electric field E is larger than the absolute value of the angle between the counter voltage line 4 and the direction of the electric field E. A capacitance Cadd consists of the pixel electrode 5, the counter voltage line 4 and the

gate insulator. To form the capacitance Cadd on the counter voltage line 4, the capacitance Cadd can be larger than any region in a pixel. The capacitance Cadd functions to improve the data retentivity. A protective film PAS (silicon nitride) is formed over the transparent substrate 1A after forming a plurality of thin film transistors TFT and pixels for preventing touching with liquid crystal molecules. Furthermore, an orientation layer which controls an initial orientation angle of liquid crystal molecules is formed over the protective film PAS. The orientation layer is surface rubbed with a rubbing roller along with the Y direction after coating synthetic resins thereon.

A color filter substrate 1B consists of a black matrix BM, a color filter 7 and an orientation layer 9. In FIG. 1, a boundary of the black matrix BM is shown as a plan view, and in FIG. 2, shows a sectional view of the black matrix BM. Here, the orientation layer 9 of the color filter substrate 1B is surface rubbed with a rubbing roller in the Y direction after coating synthetic resins thereon the same as the orientation layer of the transparent substrate 1A. Also, the orientation direction of each orientation layer of the transparent substrate 1A side and that of the color filter substrate 1B are the same Y direction. Therefore, a plurality of liquid crystal molecules are aligned to a boundary direction of the black matrix in the OFF state, and having the upper pixel region (a first group) and the lower pixel region (a second group) in the ON state, wherein a switching angle of the second group is opposite to a switching angle of the first group.

A spacer 10 is formed between the transparent substrate 1A and the color filter substrate 1B and formed over the drain line 3 to keep a gap therebetween.

FIG. 2 is a sectional view of the pixel of a liquid crystal display cut along the line II—II in FIG. 1. The black matrix BM is formed on the color filter substrate 1B which faces with liquid crystal molecules, the spacer 10 is made of the black matrix BM, the spacers 10 function to keep a gap between the transparent substrate 1A side and the color filter substrate 1B.

The black matrix BM is formed by the twice selective etching of a photo lithography method, the first selective etching to make the spacer 10 after coating black matrix material very thick, and the second selective etching to make a hole for the color filter 7. The black matrix BM is formed with either the drain line 3 or the gate line 2 thereon; a light transmittance region between the pixel electrode 5 and the counter electrode 4A are formed in an open region of the black matrix BM. An end of the pixel electrode 5 and the edge of the counter electrode 4A are covered with the black matrix BM, because this region is not the uniform electric field area between the pixel electrode 5 and the counter electrode 4A.

The open region of the black matrix BM would be able to improve an aperture ratio if it is large enough. On the other hand, the open region of the black matrix should be designed to cover the unnecessary electric field between the drain line 3 and the counter electrode 4A, and the improper electric field between the pixel electrode 5 and the edge of counter electrode 4A. The color filter 7 is former at the open region of the black matrix BM. Then, the over coating film 8 is formed over the color filter 7. Finally, the orientation layer 9 is formed over the over coating film 8.

FIG. 3 is a sectional view of the spacer 10 in illustration of an alignment defect on an orientation layer. The orientation layer 9 has its surface rubbed with rubbing roller 100 in the right direction (in the Y direction in FIG. 1). Here, an area 200 is not orientated and causes an alignment defect

with the spacer 10. Hence, in the area 200, the rubbing roller 100 out of contact with surface of the orientation layer 9, is not rubbed with the rubbing roller 100. Therefore, in this invention, the area 200 brings in the Y direction by using the multi-domain system IPS, and covers the area 200 by the black matrix. As a result, this combination provides remarkably high contrast (350:1) for a liquid crystal display.

Moreover, the spacer 10 is available to form over the counter voltage line 4 as another embodiment. As the counter voltage line 4 can be designed wider than the gate line 2, the drain line 3 and another electrode, the area 200 can be covered by the counter voltage line 4 easily.

[Embodiment 2]

FIG. 4 is a plan view of the pixel of a liquid crystal display according to a second embodiment of the present invention. In the second embodiment, a plurality of liquid crystal molecules having a negative dielectric constant anisotropy, rubbing direction (initial orientation angle) is in the X direction, so the spacer 10 is disposed over the gate line 2. As a result, even if alignment defects are formed in the area 200 on the gate line 2, the area 200 is hid by the black matrix BM. A plurality of liquid crystal molecules have the X direction for an initial orientation angle, and are twisted to +Y direction and -Y direction while a driving voltage is applied.

[Embodiment 3]

FIG. 5 is a plan view of the pixel of a liquid crystal display according a third embodiment of the present invention. In the embodiment, a plurality of liquid crystal molecules having a positive dielectric constant anisotropy, the pixel electrodes 5 and the counter electrodes 4A are formed in the direction X which are parallel with the gate line 2. In the third embodiment, a rubbing direction (initial orientation angle) is in the X direction.

In FIG. 5, the direction of the electric field which is disposed at the upper pixel region has the angle of $-\theta$ with respect to the direction perpendicular to the counter voltage line 4, but the direction of the electric field which is disposed at the lower pixel region has the angle of $+\theta$ with respect to the direction perpendicular to the counter voltage line 4. The above-mentioned shape provides the liquid crystal molecules with the ability to switch in reverse directions at each pixel region, and a light transmittance change in a pixel.

As each counter electrode 4A is arranged parallel with each pixel electrode 5, each of the counter electrodes 4A has a wider portion than the pixel electrodes 5. The absolute value of the angle between the drain line 3 and the direction of the electric field E is smaller than the absolute value of the angle between the gate line 2 and the direction of the electric field E. In this embodiment, an observer does not recognize the inversion of luminance when the view point of the observer is at an angle with respect to the slanting direction of the liquid crystal display panel.

A rubbing direction (initial orientation angle) of the transparent substrate 1A and the color filter substrate 1B are in the same X direction as the direction of gate line 2, so the spacer 10 is disposed over the gate line 2. As a result, even if alignment defects are made in the area 200 on the gate line 2, the area 200 is hidden by the black matrix BM in this embodiment.

This embodiment achieves both advantages of preventing the inversion of luminance when the view point of the observer is at an angle with respect to the slanting direction of the liquid crystal display panel, and of providing remarkably high contrast (350:1) for the liquid crystal display.

[Embodiment 4]

FIG. 6 is a plan view of the pixel of a liquid crystal display according to a fourth embodiment of the present invention. In the fourth embodiment, a plurality of liquid crystal molecules have a negative dielectric constant anisotropy; and a rubbing direction (initial orientation angle) is in the Y direction. The spacer 10 is disposed over the drain line 3. As a result, even if alignment defects are made in the area 200 on the drain line 3, the area 200 is hidden by the black matrix BM this embodiment.

That is, such liquid crystal display can prevent the inversion of luminance when the view point of the observer is at an angle with respect to the slanting direction of the liquid crystal display panel.

This embodiment achieves the advantages both of preventing the inversion of luminance when the view point of the observer is at an angle with respect to the slanting direction of the liquid crystal display panel, and of providing remarkably high contrast (350:1) for the liquid crystal display.

[Embodiment 5]

FIGS. 7A and 7B are plan views of the pixel of a liquid crystal display according to a fifth embodiment of the present invention. FIG. 7A shows a plan view of an arrangement of a plurality of pixels. Black frames show the black matrix BM, with an open region that corresponds to each pixel. The arrangement in FIG. 7A is called the delta arrangement, one group of pixels in the X direction (a row direction) is offset to the side by $\frac{1}{2}$ pitch relative to another group of pixels. As the delta arrangement, with pixels of red, green and blue adjacent each other, such arrangement is useful for a color active matrix liquid crystal display. In the fifth embodiment, the spacer 10 is formed over the gate line 2, and the rubbing direction (initial orientation angle) is in the X direction. As a result, even if alignment defects are made in the area 200 on the gate line 2, the area 200 is hidden by the black matrix BM. FIG. 7B shows a plan view of the delta arrangement, when the spacer 10 is formed over the drain line 3 and the rubbing direction (initial orientation angle) is in the Y direction. In this case, alignment defects inside the pixel region cause an improper image display.

[Embodiment 6]

The delta arrangement may be designed such that one group of pixels of the Y direction (a column direction) is offset to one side by $\frac{1}{2}$ pitch relative to another group of pixels. In a sixth embodiment, the spacer 10 is formed over the drain line 3, and the rubbing direction (initial orientation angle) is in the direction along with the drain line 3.

[Embodiment 7]

FIG. 8 is a sectional view of the liquid crystal display according to a seventh embodiment of the present invention. FIG. 8 shows a sectional view of the spacer 10 of a liquid crystal display cut along the gate line 2 in FIG. 1. The spacer 10 consists of the spacer 10A which is formed at both ends of the gate line 2 (FIELD A), and the spacer 10B which is formed at a pixel region (FIELD B). A sealing member 24 seals between the transparent substrate 1A and the color filter substrate 1B. Furthermore, a conductive layer 21 is formed under the spacers 10A and 10B forming on the color filter substrate 1B side, which is contacted with the gate line 2. Hence, this embodiment covers the spacer 10A with the conductive layer 21 and electrically contacts the gate line 2 with the spacer 10A. If the gate line 2 has a breakdown in its wiring at a part in FIELD B, scanning signals would be supported via the conductive layer 21 at FIELD A. The seventh embodiment is useful for video signals of the drain line 3 as another embodiment.

[Embodiment 8]

FIG. 9 is a sectional view of the liquid crystal display according to an eighth embodiment of the present invention. FIG. 9 shows a sectional view of the spacer 10 of a liquid crystal display cut along the counter voltage line 4 in FIG. 1. The spacer 10 consists of the spacer 10A which is formed at both ends of the gate line 2 (FIELD A), and the spacer 10B which is formed at a pixel region (FIELD B). A sealing member 24 seals between the transparent substrate 1A and the color filter substrate 1B. Furthermore, another counter voltage line 22 is formed under the spacer 10A and 10B forming on the color filter substrate 1B side in this embodiment. A conductive layer 23 is disposed like FIG. 9, and connects between the counter voltage line 22 and an external terminal for a counter voltage. Hence, this embodiment covers the spacer 10A with the counter voltage line 22 and electrically contacts the conductive layer 23 for a counter voltage.

[Embodiment 9]

It is clear that the spacer 10 should be formed on the color filter substrate side to prevent any deterioration in the characteristics of a thin film transistor. In the process of the spacer forming on the same substrate with a film transistor, a step increasing for a selective etching by a photo lithography method is added, wherein the etching solvent causes deterioration of the characteristics of the thin film transistor.

However, the spacer 10 should be formed on the transparent substrate 1A side, when the alignment between the transparent substrate, 1A, and the color filter substrate 1B is more important than the deterioration in the characteristics of a thin film transistor.

[Embodiment 10]

FIG. 10 is a sectional view of the spacer of a liquid crystal display according to a tenth embodiment of the present invention. The black matrix BM and the color filter 7 are formed under the color filter substrate 1B side which is opposite to the liquid crystal, and an overcoating film 8 made from a thermo setting resin film is formed thereunder. The spacer 10, made from a photocurable resin film, is formed under the over coating film 8. To make the spacer 10 from photo curable resin film, a selective etching method is excluded from the process of the spacer 10, and manufacturing steps for the color filter substrate 1B become simple and low cost. The embodiment 10 is useful for the transparent substrate 1A side having the spacer 10 as another embodiment.

[Embodiment 11]

FIG. 11A is a plan view of the pixel of a liquid crystal display according to an eleventh embodiment of the present invention. The spacers are uniformly arranged in a plurality of pixels so that the same number of pixels have the same number of the spacers. To decrease alignment defects caused by a spacer, a plurality of pixels have one spacer uniformly.

[Embodiment 12]

FIG. 11B is a plan view of the pixel of a liquid crystal display according to a twelfth embodiment of the present invention. A plurality of pixels are dotted with a plurality of spacers. Thus, the spacers are not uniformly arranged in a plurality of pixels like FIG. 11A. If alignment defects are uniform, an observer could see them easily.

[Embodiment 13]

FIG. 12 is a sectional view of the spacer of a liquid crystal display according to a thirteenth embodiment of the present invention. The spacer 10 adheres to an orientation layer formed on the transparent substrate 1A by an adhesive 30.

The portion where the spacer **10** adheres to an orientation layer is touched between orientation layers. In general, the bonding force between the orientation layers having the same material is weak. Consequently, the adhesive **30** including the Si coupling material is needed between orientation layers.

FIGS. **13A** and **13B** are flow charts of sectional views of a spacer illustrating the steps A to E fabricating a color filter substrate **1B**.

[Step 1]

FIG. **13A** shows a color filter substrate **1B** having the spacer **10** coating an orientation material. [Step 2]

First, the color filter substrate **1B** is moved near a vessel filled with adhesive material **30** like FIG. **13B**. Then, the color filter substrate **1B** is positioned to apply the top of the spacer **10** with adhesive material.

[Step 3]

FIG. **13C** shows the spacer **10** having the adhesive **30**.

[Step 4]

Second, the transparent substrate **1A** and the color filter substrate **1B** are positioned facing each other shown in FIG. **13D**.

[Step 5]

Finally, by applying heat to the pair of substrates, the adhesive **30** begins to solidify (FIG. **13E**).

FIGS. **14A**–**14E** are flow charts of sectional views of a spacer illustrating the steps A to E of fabricating a substrate **1B** according to another embodiment.

[Step 1]

FIG. **14A** shows a color filter substrate **1B** having the spacer **10** formed on an orientation material.

[Step 2]

First, the color filter substrate **1B** is coated by the roller **31** soaking in the a vessel filled with adhesive material shown in FIG. **14B**. As a result, the color filter substrate **1B** is formed with the tops of the spacer **10** covered with adhesive material.

[Step 3]

FIG. **14C** shows the spacer **10** having the adhesive **30**.

[Step 4]

Second, the transparent substrate **1A** and the color filter substrate **1B** are positioned facing each other shown in FIG. **14D**.

[Step 5]

Finally, by applying heat to the pair of substrates, then the adhesive **30** begins to solidify (FIG. **14E**).

[Embodiment 14]

FIG. **15** is a sectional view of the spacer of a liquid crystal display according to a fourteenth embodiment of the present invention. A concave **40** is formed on the transparent substrate **1A** as a counter tapered shape of a protective film **41** that adheres the spacer **10** with the protective film **41** via the concave **40**. In the embodiment, the concave **40** is used instead of the adhesive **30**.

FIG. **16** is a sectional view of the spacer of a liquid crystal display according to another invention of the fourteenth embodiment. A concave **42** is formed on the transparent substrate **1A** with the gate line **2** or the drain line **3**, wherein the concave **42** fits with the spacer **10**. In this embodiment, the concave **42** is used instead of the adhesive **30** or the concave **40**. Moreover, an area between the concaves **42** may be formed larger than the width of the spacer **10**, as the sealing material **24** holds a gap of substrates that correspond to the perpendicular direction. Therefore, the concaves **42** function as holding material for a gap of substrates that correspond to the parallel direction.

[Embodiment 15]

FIG. **17** is a sectional view of the spacer of a liquid crystal display according to a fifteenth embodiment of the present invention. The spacer **10** is formed over the drain over line **3**, the black matrix BM's pattern adjacent to the spacer **10** is formed wider than the other portions. In the embodiment **15**, a rubbing direction of the orientation layer follows with the drain line **3**. When an alignment defect is so large that the black matrix BM can not hide it perfectly, the embodiment **15** is useful thereby.

[Embodiment 16]

FIG. **18** is a plan view of the pixel of a liquid crystal display according to a sixteenth embodiment of the present invention. In this embodiment, a rubbing direction of an orientation layer has an angle θ , whereby alignment defects of the orientation layer caused by the spacer **10** also appear at an angle θ . As alignment defects of the orientation layer are related to the rubbing direction, therefore the right black matrix BM's pattern is wider than the left black matrix BM's pattern.

In other words, the black matrix BM's pattern covering the spacer **10** is needed as an outline whose shape is a circle with the center of the spacer, the radius of the circle depending on the occurrence of alignment defects.

FIG. **19** is a plan view of the pixel of a liquid crystal display according another invention of the sixteenth embodiment. It allows the black matrix BM's pattern covering the spacer **10** to form at one side.

[Embodiment 17]

FIG. **20** is a plan view of the pixel of a liquid crystal display according to a seventeenth embodiment of the present invention. The spacer **10** is formed over the gate line **2** or the drain line **3**. A shield layer **50** is disposed adjacently at both sides of the spacer **10**. In this embodiment, the shield layer **50** is a different layer from the black matrix BM, the gate line **2** and the drain line **3**. The rubbing direction of the orientation layer is the direction along with the gate line **2** or the drain line **3**. As alignment defects in the orientation layer are related to the rubbing direction, the shield layer **50** is arranged wider than the field of occurring alignment defects. Moreover, it allows the shield layer **50** to form the same layer with the gate line **2** or the drain line **3**, so as to be united with the gate line **2** or the drain line **3**. When the shield layer **50** is different layer from the drain line **3**, the shield layer **50** is made of the same material of the counter voltage line **4**. When the shield layer **50** is a different layer from the gate line **2**, the shield layer **50** is made of the same material of the drain line **3**. In another embodiment, it allows a rubbing direction of an orientation layer to have an angle θ , wherein the shield layer **50** is formed wider than the field occurring alignment defect.

[Embodiment 18]

FIG. **21** is a plan view of the pixel of a liquid crystal display according to an eighteenth embodiment of the present invention. The spacer **10** is formed over the gate line **2** or the drain line **3**, and a shield layer **50** is disposed at the one side of the spacer **10**. In more detail, the shield layer **50** is only formed on the side of the occurring alignment defect. In this way, an aperture ratio of a pixel can be improved more than embodiment **17**.

[Embodiment 19]

FIG. **22** is a plan view of the pixel of a liquid crystal display according to a nineteenth embodiment of the present invention. The shield layer **50** is disposed adjacent both sides to the spacer **10**. In this embodiment, the right side of the shield layer **50** is longer in the Y direction than the left side.

As alignment defects of the orientation layer are related to the rubbing direction, the shield layer **50** is longer in the

right than in the left. In other words, the shield layer **50** is needed as an outline whose shape is a circle with the center of the spacer, the radius of the circle depending on the occurrence of alignment defect.

[Embodiment 21]

FIG. **23** is a plan view of the pixel of a liquid crystal display according to a twenty-first embodiment of the present invention. In the embodiments 17–20, the shield layer **50** only functions as light shielding material, but this embodiment makes use of the shield layer **50** as any electrodes. In FIG. **23**, the counter electrodes **4A** which are disposed on the both sides of the drain line **2** have the function as the shield layer **50**. If the width of the counter electrodes **4A** is formed enough to hide alignment defects perfectly, the initial orientation angle would be designed not to depend on the presence of alignment defects. The reliability of the design improves by this embodiment.

[Embodiment 22]

FIG. **24A** is a plan view of the pixel of a liquid crystal display according to a twenty-second embodiment of the present invention. FIG. **24B** is a sectional view of the pixel of a liquid crystal display cut along the line b—b in FIG. **24A**. A pair of the transparent substrate **1A** and the color filter substrate **1B** face each other, the sealing material **24** is formed between the substrates as a frame to keep a gap between the substrates thereby. The spacer **10** is arranged inside the sealing material **24** to keep a gap at the display region thereby. The spacer **10** is formed on one of a pair of the substrates, every spacer having the same square measurement where the spacer touches the other of the pair of substrates.

In addition, the number of spacers **10** which are disposed at the center of the display region is more than at any other portion of the display region. Thus, the density of the spacers forming near the sealing material **24** is less than the density of the spacers forming at the center of the display region. By definition, the density of spacers is number of spacers per 1 cm² or 1 mm². So, the spacers which are disposed far from the sealing material **24** are required for the gap maintenance force in proportion to the size of the liquid crystal display panel. In general, the thickness of a substrate for LCD is 0.7 mm or less, the large size LCD substrate bends easily by virtue of its weight. In this embodiment, many spacers **10** keep a gap between substrates, preventing bending in large size LCD panels.

The spacer **10** is formed like the twenty-second embodiment by the selective etching of a photo-lithography method. Moreover, the density of the spacer from the center to the edge of the substrate should change smoothly, and not suddenly. If the density of the spacer changes suddenly, the gap between substrates would not be uniform. In this embodiment, it allows the density of the spacer to be different from the center portion in the X direction and the Y direction. Hence, the density of the spacer at the center portion in the X direction is more than in the Y direction to prevent a substrate from bending efficiently.

[Embodiment 23]

FIG. **25** is a plan view of the pixel of a liquid crystal display according to a twenty-third embodiment of the present invention. The spacers **10** are arranged uniformly, but the width of the spacers **10** disposed at the center of a display region is wider than other spacers **10** in other region. Hence, a square measure where the spacers touch the substrates is different between the center region and the edge region. The spacer **10** is formed like the twenty-second embodiment by a selective etching of a photo-lithography method. Moreover, it allows the material strength of spacers to be different between the center region and the edge region.

[Embodiment 24]

In a twenty-fourth embodiment, the spacer **10** is not only formed in the pixel whose color filter is green. Rather, the spacer **10** is formed selectively in the pixels whose color filters are red or blue. Because green is the highest light transmittance color among red, green and blue, an observer can recognize an improper image display in green pixel easily.

[Embodiment 25]

FIG. **26** is a plan view of the pixel of a liquid crystal display according to a twenty-fifth embodiment of the present invention. In this embodiment, a portion **20** functions as a shield material to hide alignment defects which are caused by the rubbing in the initial orientation direction. Moreover, in this embodiment, the portion **20** combines the shield material and the counter electrode **4A** which is arranged at the side of the pixel. Therefore, the material of the counter electrode **4A** is selected from the group consisting of aluminum, chromium, a metal alloy including aluminum or chromium as a main component, and so on.

[Embodiment 26]

FIG. **27** is a plan view of the pixel of a liquid crystal display according to a twenty-sixth embodiment of the present invention. In this embodiment, a portion **20** functions as a shield material to hide alignment defects which are caused by the rubbing in the initial orientation direction. Moreover, in this embodiment, the portion **20** combines the shield material and the pixel electrode **5**. Therefore, the material of the pixel electrode **5** is selected from the group consisting of aluminum, chromium, a metal alloy including aluminum or chromium as a main component, and so on.

[Embodiment 27]

FIG. **28** is a plan view of the pixel of a liquid crystal display according to a twenty-seventh embodiment of the present invention. In this embodiment, a portion **20** functions as a shield material to hide alignment defects which are caused by the rubbing in the initial orientation direction. Moreover, in this embodiment, the portion **20** combine the shield material and the counter electrode **4A** which is arranged at the center of the pixel. Therefore, the material of the counter electrode **4A** is selected from the group of aluminum, chromium, a metal alloy including aluminum or chromium as a main component, and so on.

[Embodiment 28]

FIG. **29** is a plan view of the pixel of a liquid crystal display according to a twenty-eighth embodiment of the present invention. In this embodiment, a portion **20** functions as a shield material to hide alignment defects which are caused by the rubbing in the initial orientation direction. Moreover, in this embodiment, the portion **20** combines the shield material and the pixel electrode **5**. Therefore, the material of the pixel electrode **5** is selected from the group consisting of aluminum, chromium, a metal alloy including aluminum or chromium as a main component, and so on. Furthermore, the portion **20** of the pixel electrode **5** is wider than another portion for increasing shield area and improving the precision of the design of a TFT cell.

[Embodiment 29]

FIG. **30** is a plan view of the pixel of a liquid crystal display according to a twenty-ninth embodiment of the present invention. In this embodiment, a portion **20** functions as a shield material to hide alignment defects which are caused by the rubbing in the initial orientation direction. Moreover, in this embodiment, the portion **20** combines the shield material and the counter electrode **4A** which is arranged at the center of a pixel. Therefore, the material of the counter electrode **4A** is selected from the group of aluminum, chromium, a metal alloy including aluminum or chromium as a main component, and so on.

13

Furthermore, the portion **20** of the counter electrode **4A** is wider than another portion for increasing shield area and improving the precision of the design of a TFT cell. In this way, this invention is to provide a multi-domain system IPS (In—Plane Switching mode) liquid crystal display which has high contrast and does not have an improper image display. Thus, this invention achieves both advantages of preventing the inversion of luminance when the view point of the observer is at an angle with respect to the slanting direction of the liquid crystal display panel, and providing remarkably high contrast (350:1) and high aperture ratio for a color active matrix crystal display.

What is claimed is:

1. A liquid crystal display device comprising:

a first substrate and a second substrate;

a liquid crystal layer interposed between said first and second substrates;

a plurality of first lines and second lines formed on the first substrate, each of said first lines is wider than each of said second lines;

at least a pixel with a spacer being selectively formed on each of the first lines in plane view;

a black matrix formed on the second substrate and having color filters formed therebetween; and

an overcoating film formed on the black matrix and the color filters,

wherein the spacer is formed on the overcoating film, and a portion of the spacer contacting the overcoating film is superposed substantially between the color filters in plane view, and said spacer is wider than said second lines.

2. A liquid crystal display device according to claim 1, wherein a black matrix is formed over said each first line, and said black matrix is wider than said each first line.

3. A liquid crystal display device according to claim 2, wherein said spacer is narrower than said first line.

4. A liquid crystal display device according to claim 3, wherein said first line is a gate line and said second line is a drain line.

5. A liquid crystal display device according to claim 3, wherein said spacer is arranged between neighboring second lines.

6. A liquid crystal display device according to claim 1, wherein said spacer is narrower than said first line.

7. A liquid crystal display device according to claim 1, wherein said first line is a gate line and said second line is a drain line.

8. A liquid crystal display device according to claim 1, wherein said spacer is arranged between neighboring second lines.

9. A liquid crystal display device comprising:

a first substrate and a second substrate;

a liquid crystal layer interposed between said first and second substrates;

a plurality of gate lines and drain lines formed on the first substrate, each of said gate lines is wider than each of said drain lines;

a plurality of pixels formed by adjoining gate lines and drain lines, at least one of the pixels is formed with at least one spacer;

a black matrix formed on the second substrate and having color filters formed therebetween; and

an overcoating film formed on the black matrix and the color filters,

wherein the spacer is formed on the overcoating film, and a portion of the spacer contacting the overcoating film is superposed substantially between the color filters in

14

plane view, said spacer is arranged selectively over one of the gate lines in plane view, and said spacer is wider than the drain lines.

10. A liquid crystal display device according to claim 9, wherein said spacer is narrower than said gate lines.

11. A liquid crystal display device according to claim 10, wherein a black matrix is formed over said gate lines, and said black matrix is wider than said gate lines.

12. A liquid crystal display device according to claim 11, wherein said spacer is arranged between neighboring drain lines.

13. A liquid crystal display device comprising:

a first substrate and a second substrate;

a liquid crystal layer interposed between said first and second substrates;

a plurality of first lines and second lines formed on the first substrate, each of said first lines is wider than each of said second lines;

a plurality of pixels, at least one of the pixels has a spacer being selectively formed on each of said first lines in plane view;

a black matrix formed on the second substrate and having color filters formed therebetween; and

an overcoating film formed on the black matrix and the color filters,

wherein the spacer is formed on the overcoating film, and a portion of the spacer contacting the overcoating film is superposed substantially between the color filters in plane view,

said spacer is wider than said second lines, and

said spacer is predeterminedly arranged among the pixels.

14. A liquid crystal display device according to claim 13, wherein said spacer is arranged over each of said second lines.

15. A liquid crystal display device according to claim 14, wherein said spacer is narrower than said first lines.

16. A liquid crystal display device according to claim 15, wherein at least one electrode is arranged next to each of the second lines, and said spacer extends over said electrode.

17. A liquid crystal display device according to claim 15, wherein a black matrix is formed over each of said second lines, and said black matrix is wider than each of said second lines.

18. A liquid crystal display device according to claim 14, wherein a black matrix is formed over each of said second lines,

at least an electrode is arranged next to said second lines, and

at least one edge of said black matrix overlaps said electrode.

19. A liquid crystal display device according to claim 15, wherein a black matrix is formed over each of said second lines,

at least an electrode is arranged next to said second lines, and

at least one edge of said black matrix overlaps said electrode.

20. A liquid crystal display device according to claim 14, wherein at least one electrode is arranged next to each of the second lines, and said spacer extends over said electrode.

21. A liquid crystal display device according to claim 14, wherein a black matrix is formed over each of said second lines, and said black matrix is wider than each of said second lines.

UNITED STATES PATENT AND TRADEMARK OFFICE

CERTIFICATE OF CORRECTION

PATENT NO. : 6,667,790 B2
DATED : December 23, 2003
INVENTOR(S) : Yanagawa et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title page.

Item [56], **References Cited**, U.S. PATENT DOCUMENTS, please add:

-- 6,356,335	3/2002	Kim et al.
6,342,937	1/2002	Hiroshi
6,016,181	1/2000	Shimada
6,281,960	8/2001	Kishimoto
5,745,207	4/1998	Asada et al.
5,946,066	8/1999	Lee et al.
5,905,556	5/1999	Suzuki et al.
6,049,369	4/2000	Yanagawa et al.
6,052,163	4/2000	Sung
6,091,473	7/2000	Hebiguchi --

Signed and Sealed this

Tenth Day of February, 2004

A handwritten signature in black ink, appearing to read "Jon W. Dudas". The signature is stylized with a large, looped initial "J" and a distinct "D" at the end.

JON W. DUDAS

Acting Director of the United States Patent and Trademark Office

专利名称(译)	具有特定间隔物的液晶显示器		
公开(公告)号	US6667790	公开(公告)日	2003-12-23
申请号	US10/106954	申请日	2002-03-28
[标]申请(专利权)人(译)	株式会社日立制作所		
申请(专利权)人(译)	HITACHI, LTD.		
当前申请(专利权)人(译)	松下液晶显示CO., LTD.		
[标]发明人	YANAGAWA KAZUHIKO ASHIZAWA KEIICHIRO ISHII MASAHIRO HIKIBA MASAYUKI		
发明人	YANAGAWA, KAZUHIKO ASHIZAWA, KEIICHIRO ISHII, MASAHIRO HIKIBA, MASAYUKI		
IPC分类号	G02F1/1343 G02F1/1339 G02F1/13 G02F1/1335 G02F1/1337 G02F1/136 G02F1/1368 G02F1/133 G02F1/1333		
CPC分类号	G02F1/1303 G02F1/134363 G02F1/13394 G02F1/133512 G02F1/1339 G02F2202/28 G02F2201/40		
优先权	1999029053 1999-02-05 JP		
其他公开文献	US20020113935A1		
外部链接	Espacenet USPTO		

摘要(译)

本发明提供一种多域系统IPS（面内切换模式）液晶显示器，其具有高对比度并且没有不适当的图像显示。根据本发明的一个方面，提供了一种黑矩阵，形成在一对基板之间并形成在多条漏极线和栅极线上，多个空间布置在黑矩阵下，其中多个液晶分子在“OFF”状态下排列到黑矩阵的边界方向，并且具有处于“ON”状态的第一组和第二组，其中第二组的切换角度与第一组的切换角度相反。

