



US007327410B2

(12) **United States Patent**  
**Cho et al.**

(10) **Patent No.:** **US 7,327,410 B2**  
(45) **Date of Patent:** **Feb. 5, 2008**

(54) **HIGH RESOLUTION 3-D IMAGE DISPLAY WITH LIQUID CRYSTAL SHUTTER ARRAY**

(75) Inventors: **Kun-ho Cho**, Suwon-si (KR); **Dao-sik Kim**, Suwon-si (KR); **Sung-ha Kim**, Suwon-si (KR); **Hee-joong Lee**, Anyang-si (KR)

(73) Assignee: **Samsung Electronics Co., Ltd.**, Suwon-si (KR)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 272 days.

(21) Appl. No.: **10/901,301**

(22) Filed: **Jul. 29, 2004**

(65) **Prior Publication Data**

US 2005/0057702 A1 Mar. 17, 2005

(30) **Foreign Application Priority Data**

Jul. 29, 2003 (KR) ..... 10-2003-0052460

(51) **Int. Cl.**  
**G02F 1/1335** (2006.01)

(52) **U.S. Cl.** ..... **349/15**; 356/12; 353/6; 353/7; 359/462; 359/466; 359/467; 359/468

(58) **Field of Classification Search** ..... 349/15; 356/12; 348/51; 353/617; 359/462, 466, 359/467, 468

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,751,479 A 5/1998 Hamagashi et al.

6,040,807 A *	3/2000	Hamagishi et al. ....	345/6
6,094,216 A	7/2000	Taniguchi et al.	
6,115,101 A *	9/2000	Kainen .....	355/22
6,856,341 B2 *	2/2005	Suzuki .....	348/51
7,016,116 B2 *	3/2006	Dolgoff .....	359/630

FOREIGN PATENT DOCUMENTS

JP	08-201726 A	8/1996
JP	10-142572 A	5/1998
JP	2000-275576 A	10/2000
KR	1999-0053446 A	7/1999
KR	2003-0021293 A	3/2003

\* cited by examiner

Primary Examiner—Huyen Ngo

(74) Attorney, Agent, or Firm—Sughrue Mion, Pllc.

(57) **ABSTRACT**

A 3-D image display comprising a backlight, a liquid crystal shutter array having an opening and a mask alternately formed therein and selectively passing light emitted from the backlight by switching the opening and the mask. A display device having left eye image information and right eye image information at a plurality of viewpoints, in which the left eye image information and the right eye image information are changed along the movement of the opening. An image according to the left eye image information and the right eye image information of a plurality of viewpoints is sequentially displayed through the opening.

**13 Claims, 5 Drawing Sheets**




FIG. 1A




FIG. 1B




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 4A





FIG. 4B



# HIGH RESOLUTION 3-D IMAGE DISPLAY WITH LIQUID CRYSTAL SHUTTER ARRAY

## CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the priority of Korean Patent Application No. 2003-52460, filed on Jul. 29, 2003, in the Korean Intellectual Property Office, the disclosure of which is incorporated herein in its entirety by reference.

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

The present invention relates to a 3-D image display, and more particularly, to a 3-D image display which improves a resolution by sequentially moving images of a plurality of viewpoints and selectively displaying the images.

### 2. Description of the Related Art

In general, a 3-D image is made by the principle of stereo vision through the eyes of a human. Binocular parallax occurring due to the eyes separated about 65 mm from each other can be considered the most important factor in producing a 3-D effect. There is a display using glasses or a display without using glasses in 3-D image displays. The display without using glasses obtains a 3-D image by separating left and right images without using glasses. There is a parallax barrier type and a lenticular type as the non-glasses type.

In the parallax barrier type, images to be seen by both left and right eyes are printed or photographed in an alternate vertical pattern and the pattern is seen by using a very thin vertical lattice, that is, a barrier. By doing so, a vertical pattern image to be seen by the left eye and a vertical pattern image to be seen by the right eye are separated by the barrier, and the left and right eyes see images at different viewpoints so as to see a 3-D image.

According to the parallax barrier type, as shown in FIG. 1A, a parallax barrier **10** having a vertical lattice shape and an opening **5** and a mask **7** is arranged in front of an LCD panel **3** having left eye image information L and a right eye image information R corresponding to a left eye LE and a right eye RE of an observer, respectively. An image is separated by the opening **5** of the parallax barrier **10**. In the LCD panel **3**, the image information L to be input to the left eye LE and the image information R to be input to the right eye RE are alternately arranged along a horizontal direction.

A pixel having the left eye image information L and a pixel having a right eye image information R form a set. The left and right pixels with respect to the opening **5** are pixels of different viewpoints so that a 3-D image is realized. For example, a first left eye image is input to the left eye LE and a first right eye image is input to a right eye RE. A second left eye image is input to the left eye LE and a second right eye image is input to the right eye. The left and right pixels input to the corresponding left and right eyes in the same method.

In the above method, since an image is formed by the opening **5** and the image is blocked by the mask **7**, as shown in FIG. 1B, for example, the left eye image L is formed only on the even-numbered line while the odd-numbered line is blocked by the mask **7**, so that a black line K is formed. Also, the right eye image R is formed only on the odd-numbered line while the even-numbered line is blocked by the mask **7**, so that a black line K is formed.

Thus, a resolution of a display is lowered as a whole and brightness of a 3-D image is lowered.

## SUMMARY OF THE INVENTION

To solve the above and/or other problems, the present invention provides a 3-D image display having an improved resolution by including image information of a plurality of viewpoints and displaying all images of a plurality of viewpoints while moving the opening and the mask.

According to an aspect of the present invention, a 3-D image display comprises a backlight, a liquid crystal shutter array having an opening and a mask alternately formed therein and selectively passing light emitted from the backlight by switching the opening and the mask, and a display device having left eye image information and right eye image information at a plurality of viewpoints, in which the left eye image information and the right eye image information are changed along the movement of the opening, wherein an image according to the left eye image information and the right eye image information of a plurality of viewpoints is sequentially displayed through the opening.

According to another aspect of the present invention, a 3-D image display comprises a light source array having an opening where light is emitted and a mask where light is not emitted, in which the opening and the mask are alternately formed therein and selectively switched, and a display device having left eye image information and right eye image information at a plurality of viewpoints, in which the left eye image information and the right eye image information are changed along the movement of the opening, wherein an image according to the left eye image information and the right eye image information of a plurality of viewpoints is sequentially displayed through the opening.

The image information has image information at the same viewpoint in a vertical direction and image information at a different viewpoint in a horizontal direction.

## BRIEF DESCRIPTION OF THE DRAWINGS

The above and other features and advantages of the present invention will become more apparent by describing in detail preferred embodiments thereof with reference to the attached drawings in which:

FIG. 1A is a view illustrating a conventional 3-D image display in a parallax barrier method;

FIG. 1B is a view illustrating a state in which the left eye image and the right eye image according to the conventional parallax barrier method are displayed;

FIGS. 2A and 2B are views illustrating a 3-D image display according to a first preferred embodiment of the present invention;

FIGS. 3A and 3B are views illustrating the process of displaying a left eye image and a right eye image according to the 3-D image display shown in FIGS. 2A and 2B; and

FIGS. 4A and 4B are views illustrating a 3-D image display according to a second preferred embodiment of the present invention.

## DETAILED DESCRIPTION OF THE INVENTION

Referring to FIG. 2A, a 3-D image display according to a first preferred embodiment of the present invention includes a backlight **20**, a display device **25**, and a liquid crystal shutter array **30**.

The liquid crystal shutter array **20** selectively applies power to areas in which an opening **32** and a mask **34** are alternately arranged and periodically switched. The display device **25**, for example, is a transmission LCD panel.

The process of forming a left eye image and a right eye image by a switching operation of the liquid crystal shutter array **30** is illustrated in FIGS. **2A** and **2B**. The display device **25** has left eye image information and right eye image information. Also, each of the left eye image information and the right eye image information includes image information according to a plurality of viewpoints. For example, the left eye image information and the right eye image information may include two pieces of image information having different viewpoints as image information of a frame.

In this case, the left eye image information and the right eye image information include odd-numbered image information and even-numbered image information, respectively. Light emitted from the backlight **20** passes through the opening **32** to form an image according to the image information of the display device **25**. The mask **34** blocks the light emitted from the backlight **20** so that an image is not formed. Thus, when an image is formed through the liquid crystal shutter array **30**, a line forming an image through the opening **32** and a line blocking the image by the mask **34** are alternately formed.

When the line forming the image is assumed to be an odd-numbered line, the image is referred to as an odd-numbered image. When the line forming the image is assumed to be an even-numbered line, the image is referred to as an even-numbered image.

An odd-numbered left eye image is represented as L1, L3, L5, . . . , L(2n-1) wherein "n" is a natural number. An even-numbered left eye image is represented as L2, L4, L6, . . . , L(2n) wherein "n" is a natural number. Also, an odd-numbered right eye image is represented as R1, R3, R5, . . . , R(2n-1) wherein "n" is a natural number. An even-numbered right eye image is represented as R2, R4, R6, . . . , R(2n) wherein "n" is a natural number.

Referring to FIG. **2A**, the liquid crystal shutter array **30** includes a first opening **32** and a first mask **34** when  $t=1$ . For example, the odd-numbered left eye images L1, L3, L5, L7, and L9 and the even-numbered right eye images R2, R4, R6, R8, and R10 are formed on the left and right eyes L and R, respectively, through the first opening **32**.

Next, referring to FIG. **2B**, the opening and the mask are switched by the switching operation of the liquid crystal shutter array **30**. That is, the opening is switched to the mask while the mask is switched to the opening. The switched opening and the switched mask are referred to as a second opening **32'** and a second mask **34'**, respectively.

Simultaneously with the switching operation of the liquid crystal shutter array **30**, the image information of the display device **25** is moved. Thus, as shown in FIG. **2B**, the even-numbered left eye images L2, L4, L6, L8, and L10 and the odd-numbered right eye images R1, R3, R5, R7, and R9 are formed.

FIG. **3A** shows the odd-numbered left eye images L1, L3, L5, . . . , L(2n-1) and the even-numbered left eye images L2, L4, L6, . . . , L(2n). A left eye image of a frame is formed by combining the odd-numbered left eye image and the even-numbered left eye image.

FIG. **3B** shows the even-numbered right eye images R1, R3, R5, . . . , R(2n) and the odd-numbered right eye images R2, R4, R6, . . . , R(2n-1). A right eye image of a frame is formed by combining the even-numbered right eye image and the odd-numbered right eye image.

As described above, the resolution of the 3-D image display according to the present invention is improved since an image at a plurality of viewpoints is provided while the aperture area scans the entire area of the liquid crystal shutter array. In the above description, an image of a frame

is formed by a set of the left eye image and the right eye image which correspond the odd-numbered image and the even-numbered image, respectively. Alternatively, an image of a frame may be formed by an image formed of three or more viewpoints. The image at a plurality of viewpoints is sequentially moved by using the liquid crystal shutter array. The image signals corresponding to the images at a plurality of viewpoints are sequentially moved.

In other words, while the image information of a plurality of viewpoints is sequentially and periodically moved in a horizontal direction (Y direction), the images are selectively sampled using the liquid crystal shutter array **30**. Thus, a 3-D image at a plurality of viewpoints can be obtained. Referring to FIGS. **3A** and **3B**, the image at a plurality of viewpoints has image information of the same viewpoint in the vertical direction (X direction) and different viewpoints in the horizontal direction (Y direction).

Thus, as the entire area of a screen is scanned by periodically moving the image of a plurality of viewpoints, resolution is improved and a viewing angle of a viewer is increased.

The display device **25** and the liquid crystal shutter array **30** can be arranged by switching the positions thereof.

Next, referring to FIGS. **4A** and **4B**, a 3-D image display according to a second preferred embodiment of the present invention includes a light source array **40** and a display device **50**.

The light source array **40** may be, for example, a PDP or an organic EL. Preferably, the light source array **40** can selectively form a light emitting area having a long slit shape in the vertical direction (X direction).

In the light source array **40**, an opening **44** and a mask **42** are alternately arranged along the horizontal direction (Y direction) which are controlled to be turned on or off. The opening **44** is an area where light is emitted and the mask **42** is an area where light is not emitted.

The opening **44** and the mask **42** have widths corresponding to a pixel unit of the display device **50** and are selectively switched by the on-off control of the light source array **40**. For the opening **44**, the light source array **40** is in an ON state in the vertical direction (X direction). For the mask **42**, the light source array **40** is in an OFF state in the vertical direction (X direction).

As the light emitted from the opening **44** passes through the display device **50**, the left eye image and the right eye image are formed according to an image signal of the display device **50**.

The widths of the opening **44** and the mask **42** may be changed according to the pitch of a pixel of the display device **50** and the number of images according to the viewpoints included in an image of a frame. For example, an image of a frame may include an image at two viewpoints or an image at three or more viewpoints. The widths of the opening and the mask can be adjusted according to the image of a plurality of viewpoints.

The display device **50** includes left eye image information and right eye image information. The left eye image information and the right eye image information may include image information according to a plurality of viewpoints with respect to the image information of a frame. For example, the left eye image information can include odd-numbered image information L1, L3, . . . , L(2n-1) and even-numbered image information L2, L4, . . . , L(2n). Also, the right eye image information includes odd-numbered image information R1, R3, . . . , R(2n-1) and even-numbered image information R2, R4, . . . , R(2n). The

odd-numbered right eye image and the even-numbered left eye image, neighboring each other, are combined to form an image of a frame.

For example, referring to FIG. 4A, when  $t=t_1$  and the first opening 44 and the first mask 42 are alternately formed, odd-numbered right eye images R1, R3, . . . , R9 and even-numbered left eye image L2, L4, . . . , L10 are formed through the first opening 42. Next, the first opening 44 and the first mask 42 are changed to a second mask 42' and a second opening 44', respectively, by the switching operation of the light source array 40 when  $t=t_2$ . Image information is moved together with the changing of the opening and the mask. By doing so, as shown in FIG. 4B, even-numbered right eye images R2, R4, . . . , R10 and odd-numbered left eye image L1, L3, . . . , L9 are formed through the second opening 44'.

A left eye image of a frame is formed by combining an even-numbered left eye image when  $t=t_1$  and an odd-numbered left eye image when  $t=t_2$ . A right eye image of a frame is formed by combining an odd-numbered right eye image when  $t=t_1$  and an even-numbered right eye image when  $t=t_2$ .

In the present invention, resolution is improved by scanning an image at a plurality of viewpoints onto the left and right eyes. Also, if there is a large amount of image information according to the viewpoints, a large range of vision of a viewer can be obtained.

As described above, the 3-D image display according to the present invention includes the image information of a plurality of viewpoints for the left eye and the image information of a plurality of viewpoints for the right eye. As images corresponding to the image information are sequentially scanned so that resolution is improved and a viewing angle of a viewer increases.

What is claimed is:

1. A 3-D image display comprising:

a backlight;

a liquid crystal shutter array having an opening and a mask alternately formed therein and selectively passing light emitted from the backlight by switching the opening and the mask periodically; and

a display device having left eye image information and right eye image information at a plurality of viewpoints, in which the left eye image information and the right eye image information are changed in accordance with a switching period of the opening and the mask, wherein images according to the left eye image information and the right eye image information of the plurality of viewpoints are sequentially displayed through the opening, and

wherein a left eye image of a frame is formed by combining left eye images which are sequentially displayed and a right eye image of the frame is formed by combining right eye images which are sequentially displayed.

2. The 3-D image display as claimed in claim 1, wherein the opening comprises a plurality of continuous long list extending in a vertical direction.

3. The 3-D image display as claimed in claim 1, wherein the image information has image information at the same viewpoint in a vertical direction and image information at a different viewpoint in a horizontal direction.

4. The 3-D image display as claimed in claim 1, wherein a left eye image and a right eye image are formed by a switching operation of the liquid crystal shutter array, which switches the opening and the mask.

5. The 3-D image display as claimed in claim 4, wherein the switching operation is a shutter operation.

6. The 3-D image display as claimed in claim 1, wherein the opening is switched to the mask, while the mask is switched to the opening.

7. The 3-D image display as claimed in claim 1, wherein the entire area of the liquid crystal shutter array is scanned by the sequential movement of the opening.

8. A method for displaying a 3-D image comprising the steps of:

selectively passing light emitted from a backlight by switching an opening and mask of a liquid crystal shutter periodically; and

changing left eye image information and right eye image information in accordance with a switching period of the opening and mask to sequentially display the 3-D image;

wherein said left eye image information and right eye image information have information regarding a plurality of viewpoints, and

wherein a left eye image of a frame is formed by combining left eye images which are sequentially displayed and a right eye image of the frame is formed by combining right eye images which are sequentially displayed.

9. The method for displaying a 3-D image of claim 8, wherein the opening comprises a plurality of continuous long list extending in a vertical direction.

10. The method for displaying a 3-D image of claim 8, wherein the image information has image information at the same viewpoint in a vertical direction and image information at a different viewpoint in a horizontal direction.

11. The method for displaying a 3-D image of claim 8, further comprising performing a switching operation, wherein the opening and the mask of the liquid crystal shutter array are switched.

12. The method for displaying a 3-D image of claim 11, wherein the switching operation is a shutter operation.

13. The method for displaying a 3-D image of claim 8, wherein the opening is switched to the mask, while the mask is switched to the opening.

\* \* \* \* \*

专利名称(译)	具有液晶快门阵列的高分辨率3-D图像显示器		
公开(公告)号	<a href="#">US7327410</a>	公开(公告)日	2008-02-05
申请号	US10/901301	申请日	2004-07-29
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
[标]发明人	CHO KUN HO KIM DAO SIK KIM SUNG HA LEE HEE JOONG		
发明人	CHO, KUN-HO KIM, DAO-SIK KIM, SUNG-HA LEE, HEE-JOONG		
IPC分类号	G02F1/1335 G02B27/22 G02F1/13 H04N13/00		
CPC分类号	G02B27/2264 H04N13/0411 H04N13/0413 H04N13/0418 H04N13/0447 G02B30/24 H04N13/312 H04N13/315 H04N13/32 H04N13/351		
优先权	1020030052460 2003-07-29 KR		
其他公开文献	US20050057702A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

一种3-D图像显示器，包括背光，具有开口的液晶快门阵列和在其中交替形成的掩模，并且通过切换开口和掩模选择性地使从背光发射的光通过。一种显示装置，具有在多个视点处的左眼图像信息和右眼图像信息，其中左眼图像信息和右眼图像信息沿着开口的移动而改变。通过开口依次显示根据左眼图像信息和多个视点的右眼图像信息的图像。

