



US008416367B2

(12) **United States Patent**
Son(10) **Patent No.:** **US 8,416,367 B2**
(45) **Date of Patent:** **Apr. 9, 2013**(54) **LIQUID CRYSTAL DISPLAY MODULE
WITHOUT BOTTOM COVER**(75) Inventor: **Nam Do Son**, Gyeongsangbuk-do (KR)(73) Assignee: **LG Display Co., Ltd.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 559 days.

(21) Appl. No.: **11/476,088**(22) Filed: **Jun. 28, 2006**(65) **Prior Publication Data**

US 2007/0139577 A1 Jun. 21, 2007

(30) **Foreign Application Priority Data**

Dec. 19, 2005 (KR) 10-2005-0125319

(51) **Int. Cl.****G02F 1/1333** (2006.01)**G02F 1/1335** (2006.01)**F21V 7/04** (2006.01)(52) **U.S. Cl.** **349/67; 349/60; 349/65; 362/609; 362/632**(58) **Field of Classification Search** 349/58, 349/60, 62, 65, 67, 113, 192; 362/608, 609, 362/632-634

See application file for complete search history.

(56) **References Cited****U.S. PATENT DOCUMENTS**

6,181,071 B1 * 1/2001 Yuuki et al. 315/169.3
 6,295,105 B1 * 9/2001 Lee et al. 349/65
 6,435,685 B2 * 8/2002 Matsushita 362/608
 6,452,649 B1 * 9/2002 Ono et al. 349/61
 6,490,016 B1 * 12/2002 Koura 349/58
 6,556,258 B1 4/2003 Yoshida et al.
 6,690,435 B1 2/2004 Ha et al.
 6,853,410 B2 * 2/2005 Matsuda et al. 349/67

6,962,430 B2 * 11/2005 Ito et al. 362/634
 7,056,002 B2 * 6/2006 Kang et al. 362/561
 7,259,810 B2 * 8/2007 Kim 349/67
 7,834,955 B2 * 11/2010 Suzuki et al. 349/67
 2004/0062057 A1 4/2004 Ha et al.
 2004/0169785 A1 9/2004 You et al.
 2004/0189887 A1 9/2004 You et al.
 2004/0218113 A1 11/2004 You
 2005/0007626 A1 1/2005 Takaiwa
 2005/0018104 A1 * 1/2005 Lee et al. 349/65
 2005/0068470 A1 3/2005 Won
 2005/0146650 A1 7/2005 Chung et al.
 2005/0243573 A1 11/2005 Kim et al.

FOREIGN PATENT DOCUMENTS

CN 1534335 10/2004
 CN 1549026 11/2004
 CN 1693954 11/2005
 JP 11-329043 11/1999
 JP 2001-125073 5/2001
 KR 2000-0050379 5/2000

* cited by examiner

Primary Examiner — Bumsuk Won*Assistant Examiner* — Paisley L Arendt(74) *Attorney, Agent, or Firm* — Morgan, Lewis & Bockius LLP(57) **ABSTRACT**

A liquid crystal display module includes a liquid crystal display panel to display an image; a back light unit to irradiate light onto the liquid crystal display panel includes a luminescent lamp to emit light, a light guide panel to convert light emitted from the luminescent lamp into plane light and to emit the plane light, a lamp housing to fix the luminescent lamp to the light guide panel, the lamp housing condenses the light generated from the luminescent lamp, a reflection plate formed on the rear surface of the light guide panel to reflect light, and optical sheets formed on the front surface of the light guide panel; a main support to receive the liquid crystal display panel and the back light unit; and a reinforcing member formed on the rear surface of the light guide panel and overlapping the lamp housing and the reflection plate.


7 Claims, 7 Drawing Sheets

FIG. 1
Related Art




FIG. 2
Related Art




FIG. 3
Related Art




FIG. 4




FIG. 5




FIG. 6





FIG. 7



LIQUID CRYSTAL DISPLAY MODULE WITHOUT BOTTOM COVER

This application claims the benefit of Korean Patent Appli-
cation No. 2005-0125319, filed on Dec. 19, 2005, which is
hereby incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a liquid crystal display
device, and more particularly, to a liquid crystal display mod-
ule that provides reliable and efficient module assembly.

2. Discussion of the Related Art

A cathode ray tube (CRT) is often used in TVs and moni-
tors as a measuring instrument and an information terminal.
However, due to its weight and size, the CRT cannot meet the
requirements of the current trend of thin profile and light
weight. Since the CRT cannot satisfy the above requirements,
the CRT is being replaced with a Liquid Crystal Display
(LCD) device that uses an electric field optical effect, a
Plasma Display Panel (PDP) device that uses discharge, and
an Electro Luminescent Display (ELD) device that uses an
electric field luminescent effect. Among these display
devices, the LCD device has been extensively researched and
developed.

The LCD device has several advantages including small
size, a light weight, and low power consumption. The LCD
device is often used now as a monitor for a laptop computer,
a monitor for a desktop computer, and a large-sized display
device. Accordingly, demand for the LCD device has contin-
uously increased. Most LCD devices are light-receiving
devices that display an image by adjusting the amount of light
supplied from the outside. Thus, this type of LCD device
requires a separate light source for irradiating light on an LCD
panel (i.e., a back light unit). Back light units are divided
according to the positions of lamp units, into an edge-type
back light unit and a right below-type back light unit.

An Electro Luminescence (EL), a Light Emitting Diode
(LED), a Cold Cathode Fluorescent Lamp (CCFL), or a Hot
Cathode Fluorescent Lamp (HCFL) is used as the light source
in LCD devices. Particularly, the CCFL, which has a long
lifespan, low power consumption, and a thin profile, is mainly
used in a large-sized color TFT-LCD.

FIG. 1 is a schematic exploded perspective view of a
related art liquid crystal display device. As shown in FIG. 1,
the related art liquid crystal display device includes a liquid
crystal display panel 30 displaying an image, a fluorescent
lamp 31 generating light, a lamp housing 32 formed in a U
shape for surrounding the fluorescent lamp 31, a diffusion
sheet 35, a first prism sheet 37, a second prism sheet 36, a
protection sheet 38, a light guide panel 33, and a reflection
plate 34.

The related art liquid crystal display device further
includes a main support 39 for receiving the liquid crystal
display panel 30 and a back light unit. Here, the fluorescent
lamp 31, the lamp housing 32, the diffusion sheet 35, the first
prism sheet 37, the second prism sheet 36, the protection sheet
38, the light guide panel 33, and the reflection plate 34 form
the back light unit. The back light unit serves as a light source
for the liquid crystal display panel 30 by irradiating light onto
a display region (A) of the liquid crystal display panel 30.
Although not shown in the drawings, the display region (A) of
the liquid crystal display panel 30 includes two transparent
substrates. Each transparent substrate has a polarization plate
attached to the outer surface thereof, and a liquid crystal layer
is formed between the inner surfaces of the two transparent

substrates. The related art liquid crystal display device further
includes a driving circuit 40 for driving the display region
(A).

The back light unit is operated by the following method.
When the fluorescent lamp 31 installed at one end of the light
guide panel 33 is turned on, light generated from the fluo-
rescent lamp 31 is reflected by the lamp housing 32. Reflected
light is transferred to the other end of the light guide panel 33
(opposite side to the fluorescent lamp 31) through the cross
section of the light guide panel 33. Accordingly, the light is
spread over the surface of the light guide panel 33, and the
spread light is irradiated onto the display region (A) by the
diffusion sheet 35.

In the above related art liquid crystal display device, TFTs
formed on the liquid crystal display panel 30 control pixels
according to the signal of the driving circuit. The pixels
selectively pass the light irradiated onto the display region
(A) to display an image on the display region (A) of the liquid
crystal panel 30. Hereinafter, a related art liquid crystal dis-
play module will be described with references to FIGS. 2 and
3.

FIG. 2 is a perspective view of the related art liquid crystal
display module, and FIG. 3 is a sectional view taken along the
line II-II' of FIG. 2. As shown in FIGS. 2 and 3, the related art
liquid crystal display module includes a main support 2, a
back light unit 26 and a liquid crystal display panel 10 stacked
next to the main support 2, a bottom cover 14 surrounding a
first side surface and the bottom surface of the main support 2,
and a top case 16 surrounding the edge of the liquid crystal
display panel 10 and the side of the bottom cover 14.

Here, the main support 2 is a molded structure and has the
stepped shape inner wall. The back light unit 26 is installed at
the lowermost portion of the main support 2, and the liquid
crystal display panel 10 is installed on the back light unit 26.
The liquid crystal display panel 10 includes a lower substrate
10b on which TFTs are mounted, and an upper substrate 10a
on which color filters are formed.

A liquid crystal is injected into a space between the lower
substrate 10b and the upper substrate 10a. Polarization plates
22 and 24 are installed on the lower and upper surfaces of the
liquid crystal display panel 10. The lower polarization plate
22 installed on the lower surface of the liquid crystal display
panel 10 polarizes light supplied from the back light unit, then
supplies the polarized light to the liquid crystal display panel
10. The upper polarization plate 24 installed on the upper
surface of the liquid crystal display panel 10 polarizes light
supplied from the liquid crystal display panel 10, and dis-
charges the polarized light to the outside.

The bottom cover 14 surrounds the first side surface and the
bottom surface of the main support 2. The top case 16 sur-
rounds the upper portion and the portion of first side surface
of the main support 2 to fix the main support 2 and the liquid
crystal panel 10. The back light unit 26 includes a lamp
housing 18 on which a light source 20 is mounted, a light
guide panel 6 for converting light incident from the light
source 20 into surface light, optical sheets 12 attached to the
front surface of the light guide panel 6 to increase the effi-
ciency of light incident on the liquid crystal display panel 10,
and a reflection plate 4 attached to the rear surface of the light
guide panel 6 for reflecting the light emitted from the rear
surface of the light guide panel 6 towards the liquid crystal
panel 10.

The light source 20 supplies designated light to the light
guide panel 6 in response to power supplied from an external
power source. Here, light emitted from the light source 20 in
the direction opposite to the light guide panel 6 is reflected by
the lamp housing 18, and is incident upon the light guide

panel 6. The light guide panel 6 uniformly distributes the light incident from the light source 20 thereupon throughout the light guide panel 6, thereby allowing the light to be uniformly incident on the liquid crystal display panel 10.

Furthermore, the reflection plate 4 reflects light emitted from the lower portion of the light guide panel 6, thus supplying the light to the liquid crystal panel 10. The optical sheets 12 include upper and lower diffusion sheets and upper and lower prism sheets. The optical sheets 12 scatter light incident from the light guide panel 6 thereupon so that the light is uniformly distributed to the overall surface of the liquid crystal panel 10. Moreover, the optical sheets 12 refract and concentrate the scattered light to increase surface brightness, and diffuse the light to increase a viewing angle.

To meet the current trends of thin profile and light weight, the LCD devices incorporating these features are developed. Specifically, a liquid crystal display device for a notebook computer is developed to provide enhanced portability. However, the above related art liquid crystal display module has several disadvantages.

The main support and the bottom cover are required in the related art LCD module, thus increasing the total number of steps for fabricating the related art liquid crystal display module. In addition, an overall fabrication time is increased. The bottom cover made of a metal increases the overall production cost. Furthermore, the related art LCD module fabrication processes include connecting the bottom cover and the main support by screw, hence lengthening the fabrication time. Moreover, since the bottom cover and the main support are screw-connected, the portions of the bottom cover and the main support connecting the two parts may wear out. In addition, the use of the bottom cover increases the overall weight and volume of the liquid crystal display module.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to a liquid crystal display module that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

An object of the present invention is to provide a liquid crystal display module that eliminates the need for a bottom cover to improve production yield and by doing so to reduce the production cost.

Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described, the liquid crystal display module includes a liquid crystal display panel to display an image; a back light unit to irradiate light onto the liquid crystal display panel includes a luminescent lamp to emit light, a light guide panel to convert light emitted from the luminescent lamp into plane light and to emit the plane light, a lamp housing to fix the luminescent lamp to one side of the light guide panel, wherein the lamp housing condenses the light generated from the luminescent lamp, a reflection plate formed on the rear surface of the light guide panel to reflect light upwardly, and optical sheets formed on the front surface of the light guide panel; a main support to receive the liquid crystal display panel and the back light unit; and a reinforcing member

formed on the rear surface of the light guide panel of the back light unit, and overlapping the lamp housing and the reflection plate.

In another aspect, the liquid crystal display module includes a liquid crystal display panel to display an image; a back light unit to irradiate light onto the liquid crystal display panel includes a luminescent lamp to emit light, a light guide panel to convert light emitted from the luminescent lamp into plane light and to emit the plane light, a reflection plate formed on the rear surface of the light guide panel to reflect light upwardly, a main support to receive the liquid crystal display panel, and a lamp housing to fix the luminescent lamp to one side of the light guide panel, wherein the lamp housing condenses the light generated from the luminescent lamp and overlaps a portion of the reflection plate; and optical sheets formed on the front surface of the light guide panel.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this application, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention. In the drawings:

FIG. 1 is a schematic view of a related art liquid crystal display device;

FIG. 2 is a perspective view of the related art liquid crystal display module;

FIG. 3 is a sectional view taken along the line II-II' of FIG. 2;

FIG. 4 is a rear view of a liquid crystal display module in accordance with a first exemplary embodiment of the present invention;

FIG. 5 is a sectional view taken along the line IV-IV' of FIG. 4;

FIG. 6 is a rear view of a liquid crystal display module in accordance with a second exemplary embodiment of the present invention; and

FIG. 7 is a sectional view taken along the line VI-VI' of FIG. 6.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings.

FIG. 4 is a rear view of a liquid crystal display module in accordance with a first exemplary embodiment of the present invention, and FIG. 5 is a sectional view taken along the line IV-IV' of FIG. 4. A written description for the like elements having similar features may be omitted. Written descriptions of the functions for the like elements are omitted. As shown in FIGS. 4 and 5, the first exemplary liquid crystal display module includes a liquid crystal panel 100 displaying an image, a back light unit 460 irradiating light onto the liquid crystal display panel 100, a main support 200 for receiving the liquid crystal display panel 100 and the back light unit 460, and a top case 300 surrounding the edge of the liquid crystal display panel 100 and portions of side surfaces of the main support 200.

In the liquid crystal display panel **100**, liquid crystal cells are arranged in an active matrix shape between upper and lower substrates **100a** and **100b**. TFTs for converting a video signals are installed in each of the liquid crystal cells. The video signals change the Refractivities of the liquid crystal cells, thereby displaying an image on the liquid crystal panel **100**. A tape carrier package (not shown) having a driver IC (integrated circuit) for applying driving signals to the TFTs is attached to the lower substrate **100b** of the liquid crystal display panel **100**.

Polarization plates **110** and **120** are respectively installed on two surfaces of the liquid crystal display panel **100**. Specifically, the polarization plate **110** is installed on the front surface of the upper substrate **100a** and the polarization plate **120** is installed on the bottom surface of the lower substrate **100b**. The polarization plates **110** and **120** serve to improve the viewing angle of the image displayed by the liquid crystal cells.

The back light unit **460** includes a lamp **410** receiving power from an external power source through a wire and irradiating light onto the liquid crystal display panel **100**, a light guide panel **420** guiding light incident from the lamp to the liquid crystal panel **100**, a lamp housing **430** surrounding the lamp **410** and body of the light guide panel **420**, a reflection plate **440** disposed on the bottom surface of the light guide panel **420**, and a plurality of optical sheets **450** to improve the transmittance efficiency of light emitted from the light guide panel **420** and irradiating the light onto the liquid crystal panel **100**. The lamp housing **430** also functions to reflect light irradiated from the lamp **410** towards the guide panel **420**, thereby minimizing the loss of light and increasing the efficiency of light.

In order to achieve light-weight and thin-profile requirements, the test module having no bottom cover is prepared. In the test module, the light guide panel **420** and the lamp **410** are supported only by the lamp housing **430**. Accordingly, reduction of overall module thickness and weight is achieved. Thereafter, vibration test, impact test, and drop test are conducted to check the reliability of the test module. The result indicates that the lamp housing **430** does not absorb all the impact, and thus the lamp housing **430** may be deformed or the light guide panel **420** may be separated from the liquid crystal display panel. This generates other problems, such as leakage of light at the guide panel and darkening of the liquid crystal panel.

To solve the above problems, a beading portion **431** is additionally formed on the lamp housing **430**, thereby reinforcing the strength of the lamp housing **430**. The beading portion **431** is formed at a designated location where the lamp housing **430** and the reflection plate **440** overlap. A portion of the reflection plate **440** protrudes and the beading portion **431** surrounds this protruded portion. The light guide panel **420** guides light, which is incident from the lamp **410** thereupon at a designated tilt angle, to the liquid crystal display panel **100**. The reflection plate **440** reflects the light generated from the lamp **410** towards the light guide panel **420** and prevents light loss.

The optical sheets **450** include upper and lower diffusion sheets and upper and lower prism sheets. The optical sheets **450** scatter light emitted from the light guide panel **420** so that the light is uniformly distributed to overall surface of the liquid crystal panel **100**. The optical sheets **450** refract and concentrate the scattered light to increase surface brightness, and diffuse the light to increase a viewing angle. The top case **300** has a rectangular band structure including a flat portion and a side portion that bends perpendicularly from the flat

portion. The top case **300** surrounds the edge of the liquid crystal display panel **100** and side surfaces of the main support **200**.

FIG. **6** is a rear view of a liquid crystal display module in accordance with a second exemplary embodiment of the present invention, and FIG. **7** is a sectional view taken along the line VI-VI' of FIG. **6**. The second exemplary liquid crystal display module is similar to the first exemplary liquid crystal display module except for a reinforcing member **500**. The reinforcing member **500** prevents deformation of the lamp housing **430**. Accordingly, the second exemplary liquid crystal display module includes two additional parts, the beading portion **431** and the reinforcing member **500** to strengthen the lamp housing **430**.

As shown in FIGS. **6** and **7**, to prevent the deformation of the lamp housing **430**, the reinforcing member **500** that overlaps portion of lamp housing **430** and portion of reflection plate **440** is installed. The reinforcing member **500** is made of the same material as the lamp housing **430** (i.e., aluminum or alloy) and has a designated size. One portion of the reinforcing member **500** overlaps the end of the lamp housing **430**, and the other portion of the reinforcing member **500** is attached to the reflection plate **440** so that light does not leak to the outside.

As shown in FIG. **7**, a portion of lamp housing **430** protrudes outwardly directly below the lamp **410**. The height of beading portion **431**, and the thickness of the lamp housing **430** and the reinforcing member **500** fit within the height of this protruded portion. Thus, even if the reinforcing member **500** is attached to the lamp housing **430**, the overall thickness of the liquid crystal display module is not increased.

To increase a level of adhesiveness between the lamp housing **430** and the reinforcing member **500**, the reinforcing member **500** is attached to the lamp housing **430** using a double-sided adhesive tape. A beading portion may be additionally formed on the reinforcing member **500** to additionally improve the strength of the reinforcing member **500**. The reinforcing member **500** is fixed to the lamp housing **430** using a screw **470**. A screw hole is formed through the portion of the reinforcing member **500** where it overlaps the lamp housing **430**. The reinforcing member **500** is fixed to the lamp housing **430** by tightening the screw **470** through the screw hole. Furthermore, the reinforcing member **500** and the main support **200** may be fixed, or the reinforcing member **500**, the lamp housing **430**, and the main support **200** may be simultaneously connected using the screw **470**.

As described above, the exemplary liquid crystal display module of the present invention has several advantages. First, the liquid crystal display module omits the use of a bottom cover, thereby reducing the overall thickness and the weight. In addition, this omission simplifies the module assembly process. Second, since a reinforcing member is attached to a lamp housing to strengthen the lamp housing, it is possible to prevent the deformation of the lamp housing so that light leakage is prevented. Third, the use of the reinforcing member improves the reliability of the liquid crystal display module.

It will be apparent to those skilled in the art that various modifications and variations can be made in the liquid crystal display module of the present invention without departing from the spirit or scope of the inventions. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A liquid crystal display module, comprising:
a liquid crystal display panel to display an image;

7

- a back light unit to irradiate light onto the liquid crystal display panel including a luminescent lamp to emit light, a light guide panel to convert light emitted from the luminescent lamp into plane light and to emit the plane light, a lamp housing to fix the luminescent lamp to one side of the light guide panel, wherein the lamp housing condenses the light generated from the luminescent lamp, a reflection plate separate from the lamp housing and formed on a rear surface of the light guide panel to reflect light upwardly, and optical sheets formed on a front surface of the light guide panel;
- a main support to receive the liquid crystal display panel and the back light unit;
- a reinforcing member formed on the rear surface of the light guide panel of the back light unit, and overlapping the lamp housing and the reflection plate, to prevent a deformation of the lamp housing; and
- a beading portion that is a concave portion of the lamp housing and formed to prevent a deformation of the lamp housing and to receive a protruded portion of the reflection plate at a location where the liquid crystal display panel, the light guide panel and the reflection plate overlap to reinforce a strength of the lamp housing;
- wherein the reinforcing member is fixed to the lamp housing using a screw or a double-sided adhesive tape.
2. The liquid crystal display module as set forth in claim 1, wherein the reinforcing member is made of a same material as the lamp housing.
3. The liquid crystal display module as set forth in claim 1, wherein the reinforcing member is fixed to the main support using a screw.
4. The liquid crystal display module as set forth in claim 1, wherein the reinforcing member is made of aluminum or alloy.

8

5. The liquid crystal display module as set forth in claim 1, wherein the reinforcing member is formed large enough to overlap the lamp housing and the reflection plate.
6. A liquid crystal display module, comprising:
- a liquid crystal display panel to display an image;
- a back light unit to irradiate light onto the liquid crystal display panel including a luminescent lamp to emit light, a light guide panel to convert light emitted from the luminescent lamp into plane light and to emit the plane light, a reflection plate formed on a rear surface of the light guide panel to reflect light upwardly, and a lamp housing separate from the reflection plate to fix the luminescent lamp to one side of the light guide panel, wherein the lamp housing condenses the light generated from the luminescent lamp and overlaps a portion of the reflection plate;
- a main support to receive the liquid crystal display panel and the back light unit;
- optical sheets formed on a front surface of the light guide panel; and
- a beading portion that is a concave portion of the lamp housing and formed to prevent a deformation of the lamp housing and to receive a protruded portion of the reflection plate at a location where the liquid crystal display panel, the light guide panel and the reflection plate overlap to reinforce a strength of the lamp housing.
7. The liquid crystal display module as set forth in claim 6, wherein the lamp housing is fixed to the main support using a screw.

* * * * *

专利名称(译)	没有底盖的液晶显示模块		
公开(公告)号	US8416367	公开(公告)日	2013-04-09
申请号	US11/476088	申请日	2006-06-28
[标]申请(专利权)人(译)	乐金显示有限公司		
申请(专利权)人(译)	LG.PHILIPS LCD CO. , LTD.		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	SON NAM DO		
发明人	SON, NAM DO		
IPC分类号	G02F1/1333 G02F1/1335 F21V7/04		
CPC分类号	G02F1/133608		
审查员(译)	WON , BUMSUK		
优先权	1020050125319 2005-12-19 KR		
其他公开文献	US20070139577A1		
外部链接	Espacenet USPTO		

摘要(译)

液晶显示模块包括显示图像的液晶显示面板;用于将光照射到液晶显示面板上的背光单元包括用于发光的发光灯,用于将从发光灯发出的光转换成平面光并发射平面光的导光板,用于固定发光的灯壳在灯导光板上,灯壳会聚光从发光灯产生的光,形成在导光板后表面上的反射板以反射光,以及形成在导光板前表面上的光学片;接收液晶显示面板和背光单元的主要支撑;加强构件形成在导光板的后表面上并与灯壳和反射板重叠。

