



US007944539B2

(12) **United States Patent**
Lee

(10) **Patent No.:** **US 7,944,539 B2**
(45) **Date of Patent:** **May 17, 2011**

(54) **LIQUID CRYSTAL DISPLAY DEVICE**

(75) Inventor: **Dong-Ho Lee, Yongin-si (KR)**

(73) Assignee: **Samsung Electronics Co., Ltd. (KR)**

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **10/412,451**

(22) Filed: **Apr. 11, 2003**

(65) **Prior Publication Data**

US 2004/0150771 A1 Aug. 5, 2004

(30) **Foreign Application Priority Data**

Jan. 30, 2003 (KR) 10-2003-0006189

(51) **Int. Cl.**

G02F 1/1345 (2006.01)

G02F 1/1343 (2006.01)

G02F 1/1339 (2006.01)

(52) **U.S. Cl.** **349/151; 349/139; 349/153**

(58) **Field of Classification Search** 349/141, 349/139, 149-152, 153
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,647,156	A *	3/1987	Fujimura et al.	349/153
5,811,835	A *	9/1998	Seiki et al.	257/57
5,896,117	A	4/1999	Moon	
6,040,882	A *	3/2000	Jun et al.	349/39
6,072,556	A *	6/2000	Hirakata et al.	349/153
6,115,097	A *	9/2000	Yamazaki	349/151
6,266,116	B1 *	7/2001	Ohta et al.	349/141
6,320,630	B1	11/2001	Yamashita et al.	
6,355,510	B1	3/2002	Kim	
6,407,430	B1	6/2002	Ohtani et al.	

6,466,280	B1	10/2002	Park et al.	349/43
6,466,294	B1 *	10/2002	Yamagishi et al.	349/155
6,587,162	B1 *	7/2003	Kaneko et al.	349/43
6,654,076	B2 *	11/2003	Ha et al.	349/43
6,774,968	B2 *	8/2004	Hagiwara	349/139
6,888,605	B2 *	5/2005	Yamaguchi	349/149
7,023,518	B1 *	4/2006	Koyama et al.	349/151
7,190,430	B2 *	3/2007	Miyazaki et al.	349/190

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 444 621 A2 9/1991

(Continued)

OTHER PUBLICATIONS

PCT Notification of Transmittal of the International Search Report or the Declaration; International application No. PCT/KR03/00759; International filing date: Apr. 15, 2003; Date of Mailing: Nov. 26, 2003.

(Continued)

Primary Examiner — **Dung T. Nguyen**



(74) *Attorney, Agent, or Firm* — **Cantor Colburn LLP**

(57)

ABSTRACT

An LCD device provides enhanced display quality. An insulating layer is formed on a first substrate. The insulating layer covers the contact portion of a switching device in which the switching device is electrically connected to a transparent electrode and has an opening for exposing a portion of the transparent electrode. A reflection electrode is electrically connected to the transparent electrode through the opening. The insulation layer covers a first portion of a driving circuit formed on the first substrate. A sealant is interposed between the first and second substrate to engage the first and second substrate and to cover a second portion of the driving circuit. Therefore, the driver circuit may operate normally, and the distortion of the signal outputted from the driver circuit may be prevented.

51 Claims, 16 Drawing Sheets



US 7,944,539 B2

Page 2

U.S. PATENT DOCUMENTS

2001/0048501	A1	12/2001	Kim et al.	349/141
2001/0048502	A1*	12/2001	Moon et al.	349/153
2002/0030190	A1	3/2002	Ohtani et al.	
2003/0016308	A1	1/2003	Jeon	

FOREIGN PATENT DOCUMENTS

EP	0444621	A2	9/1991
JP	04-324826	A	11/1992
JP	08-062635	A	3/1996
JP	2505046	Y2	5/1996
JP	09-311342	A	12/1997
JP	11-194367	A	7/1999
JP	11-242226	A	9/1999
JP	11-326957	A	11/1999
JP	11305262	A	11/1999

JP	2000305110	11/2000
JP	2001125094	5/2001
KR	1019990037027	A 5/1999
KR	1020010086702	A 9/2001
TW	469484	3/2000
TW	471180	1/2002
WO	02092718	A1 11/2002

OTHER PUBLICATIONS

Taiwanese Office Action; May 4, 2007. All references cited in the Office action and not previously submitted are listed above.

Chinese Patent Application No. 038258102; Text of the First Office Action, dated May 25, 2007. All references cited in the Office action and not previously submitted are listed above.

* cited by examiner

FIG. 1

400




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 9

400




FIG. 10

500




FIG. 11A

500




FIG. 11B

500




FIG. 12

500




FIG. 13

600





FIG. 14

600



LIQUID CRYSTAL DISPLAY DEVICE**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application relies for priority upon Korean Patent Application No. 2003-06189 filed on Jan. 30, 2003, the contents of which are herein incorporated by reference in its entirety.

BACKGROUND OF THE INVENTION**1. Field of the Invention**

The present invention relates to a liquid crystal display (LCD) device, and more particularly to a liquid crystal display device having an enhanced display quality.

2. Description of the Related Art

An LCD device includes a first substrate, a second substrate and a liquid crystal layer interposed between the first and second substrates. When electric field is formed between the first and second substrates by an external electric signal, the alignment angles of the molecules of the liquid crystal layer are varied by the electric field, so that the LCD device displays an image.

The first substrate includes a display region through which the image is displayed and a peripheral region surrounding the display region. A plurality of pixels is arranged in a matrix shape. Each of the pixels includes a gate line, a data line, a thin film transistor (TFT) and a pixel electrode connected to the TFT.

A gate driver circuit for driving the gate of the TFT is disposed in the peripheral region, and the gate driver circuit may be formed on the first substrate through the process by which the TFT is formed on the first substrate. The gate driver circuit includes a plurality of transistors, capacitors and wirings. An insulation film covers the gate driver circuit. The insulation film has a contact hole. The insulation layer includes a conduction layer that is electrically connected to the TFT through the contact hole. The conduction layer is disposed on the outer surface of the gate driver circuit.

The second substrate includes a common electrode facing the pixel electrode, and the liquid crystal layer is formed between the common electrode and the pixel electrode. Since the common electrode is formed on an entire surface of the second substrate, the common electrode faces the gate driver circuit, and the liquid crystal layer is formed between the common electrode and the gate driver circuit. Accordingly, a parasite capacitance between the conduction layer and the common electrode exists.

The gate driver circuit may not normally operate due to the parasite capacitance. The delay of the signal outputted from the gate driver circuit may happen, and the distortion of the signal outputted from the gate driver circuit may happen. The display quality of the LCD device may be deteriorated due to the parasite capacitance.

SUMMARY OF THE INVENTION

Accordingly, it is a feature of the present invention to provide a LCD device having an enhanced display quality.

In one aspect of the present invention, there is provided a liquid crystal display device including a first substrate, a second substrate, a sealing member and a liquid crystal layer. The first substrate includes a display part for displaying an image and a driver part for driving the display unit. The second substrate faces the first substrate. The sealing member is disposed between the first and second substrates to engage

the first substrate with the second substrate, and the sealing member covers the driving part. The liquid crystal layer is disposed between the first and second substrates.

In another aspect of the present invention, there is provided a liquid crystal display device including a first substrate, a second substrate and a liquid crystal layer. The first substrate includes a display part for displaying an image and a driver part for driving the display unit. The display part includes a switching device, a transparent electrode, a first insulation layer and a reflection electrode. The transparent electrode is electrically coupled with the switching device. The first insulation layer is disposed on the transparent electrode to cover a contact portion of the switching device in which the switching device is electrically coupled with the transparent electrode. The first insulation layer has an opening through which a portion of the transparent electrode is exposed. The reflection electrode is disposed on the first insulation layer and is electrically coupled with the transparent electrode at the opening. The second substrate includes a common electrode facing the transparent electrode and the reflection electrode. The second substrate has a first portion and a second portion. The driver part is disposed only under the first portion, the driver part is not disposed under the second portion, and the common electrode is formed on the second portion of the second substrate. The liquid crystal layer is disposed between the first and second substrates.

As described above, according to the liquid crystal display device of this invention, the gate driver circuit formed in the first substrate is covered by the insulation layer and (or sealant) having a dielectric constant lower than that of the liquid crystal layer. In addition, the common electrode disposed over the gate driver circuit is removed.

The parasite capacitance between the gate driver circuit and the common electrode may be reduced. Therefore, the gate driver circuit may operate normally, and the distortion of the signal outputted from the gate driver circuit may be prevented. In addition, the LCD device may provide enhanced display quality.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other features and advantages of the present invention will become more apparent by describing in detail the preferred embodiments thereof with reference to the accompanying drawings, in which:

FIG. 1 is a plan view showing an example of a liquid crystal display device of the present invention;

FIG. 2A is cross-sectional view showing a transmissive and reflective type liquid crystal display device according to a first exemplary embodiment of the present invention;

FIG. 2B is cross-sectional view showing a transmissive type liquid crystal display device according to a second exemplary embodiment of the present invention;

FIG. 3 is a cross-sectional view showing a liquid crystal display device according to a third exemplary embodiment of the present invention;

FIG. 4 is a block diagram showing the gate driver circuit of FIG. 3;

FIG. 5 is a layout showing each of the stage of the gate driver circuit of FIG. 3;

FIG. 6 is a cross-sectional view showing a liquid crystal display device according to a fourth exemplary embodiment of the present invention;

FIG. 7 is a cross-sectional view showing a liquid crystal display device according to a fifth exemplary embodiment of the present invention;

FIG. 8 is a cross-sectional view showing a liquid crystal display device according to a sixth exemplary embodiment of the present invention;

FIG. 9 is a cross-sectional view showing a liquid crystal display device according to a seventh exemplary embodiment of the present invention;

FIG. 10 is a plan view showing another example of a liquid crystal display device of the present invention;

FIG. 11A is cross-sectional view showing a transmissive and reflective type liquid crystal display device according to an eighth exemplary embodiment of the present invention;

FIG. 11B is cross-sectional view showing a transmissive type liquid crystal display device according to a ninth exemplary embodiment of the present invention;

FIG. 12 is a cross-sectional view showing a liquid crystal display device according to a tenth exemplary embodiment of the present invention;

FIG. 13 is a cross-sectional view showing a liquid crystal display device according to an eleventh exemplary embodiment of the present invention; and

FIG. 14 is a cross-sectional view showing a liquid crystal display device according to a twelfth exemplary embodiment of the present invention.

DESCRIPTION OF PREFERRED EMBODIMENTS

Hereinafter preferred embodiment of the present invention will be described in detail with reference to the accompanying drawings.

FIG. 1 is a plan view showing an example of a liquid crystal display device of the present invention. FIG. 2A is cross-sectional view showing a transmissive and reflective type liquid crystal display device according to a first exemplary embodiment of the present invention, and FIG. 2B is cross-sectional view showing a transmissive type liquid crystal display device according to a second exemplary embodiment of the present invention.

Referring to FIGS. 1 and 2A, the liquid crystal display device according to a first exemplary embodiment of the present invention includes a first substrate 100, a second substrate 200 facing the first substrate 100 and a liquid crystal layer 300 interposed between the first and second substrate 100 and 200.

The first substrate 100 includes a display area (DA) through which an image is displayed and a peripheral area (PA) surrounding the display area (DA). The display area (DA) includes a plurality of pixels arranged in a matrix shape. Each of the pixels includes a thin film transistor (TFT) 110 and a pixel electrode connected to the TFT 110. The TFT 110 is connected to a gate line (GL) and a data line (DL). The data line (DL) is extended in a first direction, and the gate line (GL) is extended in a second direction substantially perpendicular to the first direction. The pixel electrode includes a transparent electrode 120 and a reflection electrode 140.

As shown in FIG. 2A, the display area (DA) is divided into a reflective area (RA) and a transmissive area (TA). The reflection electrode 140 is formed in the reflective area (RA), and the first light generated from an external light source is reflected by the reflection electrode 140 in the reflective area (RA). The transparent electrode 120 is formed in the transmissive area (TA), and the second light generated from an internal light source of the LCD device is passed through the transparent electrode 120 in the transmissive area (TA).

The TFT 110 is formed on the first substrate 100, an organic insulation layer 130 having an embossing pattern is deposited on the first substrate 100 on which the TFT 110 is

formed. The organic insulation layer 130 includes a contact hole 130a through which a drain of the TFT 110 is exposed.

The transparent electrode 120 is deposited on the organic insulation layer 130. The transparent electrode 120 comprises indium tin oxide (ITO) or indium zinc oxide (IZO).

The reflection electrode comprises aluminum-neodymium (AlNd) having a high reflectivity, and is deposited uniformly on the transparent electrode 120. The reflection electrode 140 has the same surface profile as the organic insulation layer 130. Accordingly, the reflection efficiency of the reflection electrode 140 may be enhanced.

A gate driver circuit 160 is formed in the peripheral area (PA). The gate driver circuit 160 is connected to an end of the gate line (GL) and supplies a gate driving signal for driving the gate of the TFT 110. The gate driver circuit 160 is electrically connected to the gate line (GL) disposed in the display area (DA) through the wiring 165. The gate driver circuit 160 and the wiring 165 may be formed through the same process in which the TFT 110 is formed in the display area (DA).

The second substrate 200 includes color filters 210 and a common electrode 220. The color filter 210 has red (R), green (G) and blue (B) color filters to display predetermined colors in combination of the red (R), green (G) and blue (B) colors. The common electrode 220 is deposited uniformly on the color filter 210 and faces the transparent electrode 120 and the reflection electrode 140.

The second substrate 200 is engaged with the first substrate 100 by sealant 350. The sealant 350 is disposed in the peripheral area (PA) and covers the second portion (A2) of the gate driver circuit 160 except the first portion (A1) of the gate driver circuit 160.

The liquid crystal layer 300 is interposed between the first and second substrates 100 and 200 that are engaged each other by the sealant 350, to thereby complete the LCD device 400.

The gate driver circuit 160 is covered by the sealant 350 having a dielectric constant lower than that of the liquid crystal layer 300. Since the capacitance is in proportional to the dielectric constant and the sealant 350 is interposed between the gate driver circuit 160 and the common electrode 220, the capacitance between the gate driver circuit 160 and the common electrode 220 may be reduced.

The above structure in which the sealant 350 and the gate driver circuit 160 are arranged may be employed in the transmissive type LCD device.

As shown in FIG. 2B, the transmissive type LCD device has the same peripheral area structure as the transmissive and reflective type LCD device of FIG. 2A. Although the above preferred embodiment shows the configuration according to the transmissive type LCD device shown in FIG. 2B, any other configurations known to one of the ordinary skill in the art may also be utilized in place of the configuration according to the transmissive type LCD device of FIG. 2B.

FIG. 3 is a cross-sectional view showing a liquid crystal display device according to a third exemplary embodiment of the present invention.

Referring to FIG. 3, the first substrate 100 includes a display area (DA) through which an image is displayed and a peripheral area (PA) surrounding the display area (DA). The display area (DA) includes a plurality of TFTs 110 and pixel electrodes connected to the TFTs 110. The pixel electrode 120 includes a transparent electrode 120 and a reflection electrode 140. The transparent electrode 120 is directly connected to the TFT 110, and the reflection electrode 140 is electrically connected to the TFT 110 through the transparent electrode 120. While the TFT 110 is formed on the first substrate 100, the transparent electrode 120 is directly con-

nected to a drain (not shown) of the TFT 110. An organic insulation layer 130 is formed on the first substrate 100 on which the TFT 110 and the transparent electrode 120 are formed. The organic insulation layer 130 covers a contact portion of the TFT 110 in which the TFT 110 is electrically connected to the transparent electrode 120. The organic insulation layer 130 includes an opening 131 through which a portion of the transparent electrode 120 is exposed. The transmissive area (TA) corresponds to the opening 131.

The reflection electrode 140 is formed on the organic insulation layer 130 and is electrically connected to the transparent electrode 120 through the opening 131. In other words, the reflection electrode 140 is extended to a portion of the transparent electrode 120 that is exposed by the opening 131 and contacts with the transparent electrode 120. Accordingly, the reflection electrode 140 is electrically connected to the drain of the TFT 110 through the transparent electrode 120.

A gate driver circuit 160 is formed in the peripheral area (PA). The gate driver circuit 160 is connected to an end of the gate line (GL) and supplies a gate driving signal for driving the gate of the TFT 110. The organic insulation layer 130 covers a first portion (A1) of the gate driver circuit.

The sealant 350 is disposed in the peripheral area (PA) and covers the second and covers the second portion (A2) of the gate driver circuit 160 except the first portion (A1) of the gate driver circuit 160.

The gate driver circuit 160 is covered by the sealant 350 and the organic insulation layer 130. The sealant 350 and the organic insulation layer 130 have dielectric constants lower than that of the liquid crystal layer 300. Since the capacitance is in proportional to the dielectric constant and the sealant 350 and the organic insulation layer 130 are interposed between the gate driver circuit 160 and the common electrode 220, the capacitance between the gate driver circuit 160 and the common electrode 220 may be reduced.

FIG. 4 is a block diagram showing the gate driver circuit of FIG. 3, and FIG. 5 is a layout showing each of the stage of the gate driver circuit of FIG. 3.

Referring to FIG. 4, the gate driver circuit 160 includes a shift register 161. The shift register 161 includes a plurality of stages each of which is cascade-connected.

An output terminal (OUT) of the present stage is connected to the corresponding gate line and is connected to an input terminal (IN) of the next stage and a control terminal (CT) of the previous stage. Each of the stages receives electric power 'VSS' and 'VDD' through power lines, and clock signals 'CK' and 'CKB' through clock lines. Accordingly, each of the stages outputs sequentially a gate driving signal having a high voltage level to the corresponding gate lines.

Each of the stages includes a plurality of NMOS transistors NT1, NT2, NT3, NT4, NT5, NT6, and NT7 and a capacitor (C). Specifically, each of the stages includes a first conduction pattern 114 and a second conduction pattern 115. The first conduction pattern 114 includes a plurality of gate electrodes of the NMOS transistors NT1, NT2, NT3, NT4, NT5, NT6, and NT7 and a first wiring extended from the gate electrodes. The second conduction pattern 115 includes a plurality of source and drain electrodes of the NMOS transistors NT1, NT2, NT3, NT4, NT5, NT6, and NT7 and a second wiring extended from the source and drain electrodes.

The first and second conduction patterns 114 and 115 is insulated each other by a gate insulation layer. Since the organic insulation layer 130 is formed on the second conduction pattern 115, each of the stages requires a conduction layer 117 for electrically connecting the first conduction pattern 114 and the second conduction pattern 115.

Each of the stages includes first, second, third, fourth and fifth contact hole regions CON1, CON2, CON3, CON4, and CON5. A gate electrode of the first NMOS transistor NT1 is electrically connected to a source electrode of the third NMOS transistor NT3 by the first contact hole region CON1. A gate electrode of the second NMOS transistor NT2 is electrically connected to a drain electrode of the seventh NMOS transistor NT7 by the second contact hole region CON2. A gate electrode of the seventh NMOS transistor NT7 is electrically connected to a source electrode of the third NMOS transistor NT3 by the third contact hole region CON3. A gate electrode of the second NMOS transistor NT2 is electrically connected to a source electrode of the sixth NMOS transistor NT6 by the fourth contact hole region CON4. A gate electrode of the sixth NMOS transistor NT6 is electrically connected to a drain electrode of the sixth NMOS transistor NT6 by the fifth contact hole region CON5. The conduction layer 117 is formed so as to correspond to the first, second, third, fourth and fifth contact hole regions CON1, CON2, CON3, CON4, and CON5.

Specifically, the gate electrode of the seventh NMOS transistor NT7 is electrically connected to the source electrode of the third NMOS transistor NT3 through the third contact hole region CON3. An organic insulation layer 130 has a first contact hole 141 and a second contact hole 143. The first contact hole 141 is formed on a portion of the organic insulation layer 130 corresponding to the source electrode of the third NMOS transistor NT3. The first contact hole 141 exposes the gate electrode of the seventh NMOS transistor NT7. The second contact hole 143 is formed on another portion of the organic insulation layer 130 corresponding to the drain electrode of the seventh NMOS transistor NT7. The second contact hole 143 exposes the source electrode of the third NMOS transistor NT3. The conduction layer 117 is connected to the gate electrode of the seventh NMOS transistor NT7 and the source electrode of the third NMOS transistor NT3 through the first and second contact holes 141 and 143. Accordingly, the conduction layer 117 electrically connects the gate electrode of the seventh NMOS transistor NT7 and the source electrode of the third NMOS transistor NT3. For example, the conduction layer 117 comprises a transparent conducting material such as indium tin oxide (ITO).

Although each of the stages of FIG. 5 shows the configuration including NMOS transistors NT1, NT2, NT3, NT4, NT5, NT6, and NT7, each of the stages may include various configurations in place of the configuration of FIG. 5. Although each of the stages has other configurations in place of the configuration of FIG. 5, each of the stages has the conduction layer 117.

FIG. 6 is a cross-sectional view showing a liquid crystal display device according to a fourth exemplary embodiment of the present invention, and FIG. 7 is a cross-sectional view showing a liquid crystal display device according to a fifth exemplary embodiment of the present invention.

Referring to FIG. 6, in the display area (DA), the first substrate 100 includes a TFT 110 and a pixel electrode, and the second substrate 200 includes a color filter 210 and a common electrode 220. The pixel electrode includes a reflection electrode 140 and a transparent electrode 120 and is connected to the TFT 110.

Specifically, the first substrate 100 includes the TFT 110 having gate electrode 111, source electrode 112 and drain electrode 113. The transparent electrode 120 is formed on the first substrate 100 on which the TFT 110 is formed. The transparent electrode 120 comprises ITO. The transparent electrode 120 is electrically connected to the drain electrode

113. The transparent electrode **120** receives a signal that is applied to the drain electrode of the TFT **110**.

An organic insulation layer **130** is formed by a predetermined thickness on the first substrate **100** on which the TFT **110** and the transparent electrode **120**. For example, the organic insulation layer **130** comprises a photosensitive resin. The organic insulation layer **130** covers a contact portion of the drain electrode in which the drain electrode contacts with the transparent electrode **120**. An opening **131** is formed on a first portion of the organic insulation layer **130** for exposing a portion of the transparent electrode **120**. The first portion of the organic insulation layer **130** does not correspond to the contact portion of the drain electrode in which the drain electrode contacts with the transparent electrode **120**. Accordingly, the reflectivity of the reflection electrode **140** may be enhanced.

The reflection electrode **140** is formed uniformly on the organic insulation layer **130**. For example, the reflection electrode **140** comprises aluminum-neodymium (AlNd). The reflection electrode **140** is electrically connected to the transparent electrode **120** through the opening **131**. Accordingly, the reflection electrode **140** receives the signal applied to the drain electrode **113** of the TFT **110** through the transparent electrode **120**.

A reflective area (RA) is referred to as an area by which the first light (L1) incident from the front surface of the LCD device **400** is reflected. A transmissive area (TA) is an area in which the transparent electrode **120** is exposed. The transmissive area (TA) is referred to as an area through which the second light (L2) incident from the rear surface of the LCD device **400** is transmitted.

Since the opening **131** is formed on the organic insulation layer **130**, the reflective area (RA) of the LCD device **400** has a first cell gap (D1) and the transmissive area (TA) of the LCD device **400** has a second cell gap (D2). In other words, the LCD device has the structure in which the cell gap of the reflective area (RA) is different from that of the transmissive area (TA).

The liquid crystal layer **300** includes a first liquid crystal (not shown) adjacent to the second substrate **200** and a second liquid crystal (not shown) adjacent to the first substrate **100**. A twist angle of the first and second liquid crystal is referred to as the angle formed between the major axis of the first and second liquid crystals and the a reference line parallel to the first substrate.

The larger the twist angle is, the smaller has the transmissivity of the LCD device **400**. Therefore, the second cell gap (D2) of the transmissive area (TA) is double the first cell gap (D1) of the reflective area (RA) so as to compensate the difference of the light loss due to the polarization characteristics of the LCD device. In the transmissive area (TA), the liquid crystal has a homogeneous alignment (or parallel alignment) so as to increase the transmissivity of the transmissive area (TA). In other words, the twist angle of the liquid crystal in the transmissive area (TA) is substantially 0° .

As shown in FIG. 7, in display area (DA) of the LCD device according to a fifth exemplary embodiment of the present invention, the first substrate **100** includes a TFT **110**, a pixel electrode having a transparent electrode **120** and a reflection electrode **140**, an inorganic insulation layer **150** and an organic insulation layer **130**.

Specifically, the first substrate **100** includes the TFT **110** having gate electrode **111**, source electrode **112** and drain electrode **113**. The inorganic insulation layer **150** is formed on the first substrate **100** on which the TFT **110** is formed so as to protect the TFT **110**. For example, the inorganic insulation layer **150** comprises a transparent inorganic material

such as silicon nitride (SiNx) or chrome oxide (Cr₂O₃). The inorganic insulation layer **150** has a contact hole **151** for exposing the drain electrode **113** of the TFT **110**.

The transparent electrode **120** is formed on the inorganic insulation layer **150**. The transparent electrode **120** is electrically connected to the drain electrode **113** through the contact hole **151**. The transparent electrode **120** receives a signal applied to the drain electrode **113** of the TFT **110**.

The organic insulation layer **130** is formed by a predetermined thickness on the first substrate **100** on which the TFT **110**, inorganic insulation layer **150** and the transparent electrode **120**. For example, the organic insulation layer **130** comprises a photosensitive acrylic resin. An opening **131** is formed on a first portion of the organic insulation layer **130** to expose a portion of the transparent electrode **120**. The first portion of the organic insulation layer **130** does not correspond to the contact portion of the TFT **110** in which the TFT **110** contacts with the transparent electrode **120**. Accordingly, the reflectivity of the reflection electrode **140** may be enhanced. An embossing pattern having a plurality of convex portions and concave portions is formed on the surface of the organic insulation layer **130** so as to enhance the reflection efficiency of the reflection electrode **140**.

The reflection electrode **140** is formed uniformly on the organic insulation layer **130**. For example, the reflection electrode **140** comprises aluminum-neodymium (AlNd). The reflection electrode **140** is electrically connected to the transparent electrode **120** through the opening **131**. Accordingly, the reflection electrode **140** receives the signal applied to the drain electrode **113** of the TFT **110** through the transparent electrode **120**.

Another contact hole for electrically connecting the reflection electrode **140** with the transparent electrode **120** and the drain electrode **113** is not required since the reflection electrode **140** is electrically connected to the exposed transparent electrode **120** through the opening **131**. Therefore, the reflection efficiency of the reflection electrode **140** may be enhanced. The reflection electrode **140** is formed on the upper surface and the sidewall of the organic insulation layer **130** and also is extended onto the upper surface of the transparent electrode **120** so as to enhance the reflective efficiency of the reflection electrode.

A reflective area (RA) is referred to as an area by which the first light (L1) incident from the front surface of the LCD device **400** is reflected. A transmissive area (TA) is an area in which the transparent electrode **120** is exposed. The transmissive area (TA) is referred to as an area through which the second light (L2) incident from the rear surface of the LCD device **400** is transmitted.

The second substrate **200** includes a thickness-regulating member **230**, a color filter **210** and a common electrode **220** facing the transparent electrode **120** and the reflection electrode **140**. The color filter formed on the second substrate **200** has a first thickness (t1) in the reflection area (RA), and has a second thickness (t2) thicker than the first thickness (t1). For example, the second thickness (t2) is twice the first thickness (t1).

The thickness-regulating member **230** is formed on a remained portion of the entire surface of the second substrate **200** except the portion of the entire surface of the second substrate **200** corresponding to the transmissive area (TA). The thickness-regulating member **230** has a first thickness (t1). The color filter **210** is formed on the second substrate **200** on which the thickness-regulating member **230** is formed. The color filter may have a uniform surface. Accordingly, the color filter formed in the reflection area (RA) has a first thickness (t1) and has a second thickness (t2) in the transmissive

sive area (TA). The common electrode **220** having a uniform thickness is formed on the color filter **210**.

The first light (L1) is incident into the reflection area (RA) and is reflected by the reflection electrode **140**. The first light (L1) transmits twice the color filter **210** having the second thickness (t2) and exits from the color filter **210**. The second light (L2) transmit the transmissive area (TA) and transmits one time the color filter **210** having the second thickness (t2) and exits from the color filter **210**. Therefore, the color reproduction in the reflection area (RA) is substantially the same as the color reproduction in the transmissive area (TA).

FIG. **8** is a cross-sectional view showing a liquid crystal display device according to a sixth exemplary embodiment of the present invention.

Referring to FIG. **8**, the first substrate **100** includes the TFT **110** having gate electrode **111**, source electrode **112** and drain electrode **113**. A transparent electrode **120** comprised of indium tin oxide (ITO) is formed on the first substrate **100** on which the TFT **110** is formed. The transparent electrode is electrically connected to the drain electrode **113**. The transparent electrode **120** receives the signal applied to the drain electrode **113** of the TFT **110**.

The organic insulation layer **130** is formed by a predetermined thickness on the first substrate **100** on which the transparent electrode **120** is formed. For example, the organic insulation layer **130** comprises a photosensitive acryl resin. The organic insulation layer **130** covers the contact portion of drain electrode **113** of the TFT **110** in which drain electrode **113** of the TFT **110** makes contact with the transparent electrode **120**. An opening **131** is formed on a first portion of the organic insulation layer **130** to expose a portion of the transparent electrode **120**. The first portion of the organic insulation layer **130** does not correspond to the contact portion of the TFT **110** in which the TFT **110** makes contact with the transparent electrode **120**.

A first reflection electrode **143** and a second reflection electrode **145** are formed in the order named on the organic insulation layer **130**. The first reflection electrode **143** comprises molybdenum-tungsten (MoW). The second reflection electrode **145** comprises aluminum-neodymium (AlNd). The first reflection electrode **143** is electrically connected to the transparent electrode **120** through the opening **131**. The first reflection electrode **143** and second reflection electrode **145** receives the signal applied to the drain electrode **113** of the TFT **110** through the transparent electrode **120**.

As shown in FIG. **8**, the first reflection electrode **143** is interposed between the second reflection electrode **145** and the transparent electrode **120** in the area where the opening **131** is formed. Accordingly, the electric cell reaction generated between the second reflection electrode **145** and the transparent electrode **143** may be prevented.

FIG. **9** is a cross-sectional view showing a liquid crystal display device according to a seventh exemplary embodiment of the present invention. FIG. **8** represents the reflective type LCD device, and is different from the first exemplary embodiment in that the display area (DA) has a reflection area (RA) and does not have a transmissive area (TA).

Referring to FIG. **9**, the light supplied from the external light source is reflected by the reflection electrode **140** in the reflection area (RA).

A sealant **350** has a dielectric constant lower than that of the liquid crystal layer **300** and covers the gate driver circuit **160**. Since the sealant **350** is interposed between the gate driver circuit **160** and the common electrode **220**, a parasitic capacitance between the gate driver circuit **160** and the common electrode **220** may be reduced.

FIG. **10** is a plan view showing another example of a liquid crystal display device of the present invention. FIG. **11A** is cross-sectional view showing a transmissive and reflective type liquid crystal display device according to an eighth exemplary embodiment of the present invention, and FIG. **11B** is cross-sectional view showing a transmissive type liquid crystal display device according to a ninth exemplary embodiment of the present invention. Throughout FIGS. **10**, **11A** and **11B**, the same elements are designated by the same reference numerals of FIGS. **1** and **3**, and detailed descriptions about the identical elements are omitted.

Referring FIGS. **10** and **11A**, the LCD device **500** includes a display area (DA) through which an image is displayed and a peripheral area (PA) surrounding the display area (DA).

A gate driver circuit **160** is formed in the peripheral area (PA). The gate driver circuit **160** is connected to an end of the gate line (GL) and supplies a gate driving signal for driving the gate of the TFT **110**. The gate driver circuit **160** is electrically connected to the gate line (GL) disposed in the display area (DA) through the wiring **165**. The gate driver circuit **160** and the wiring **165** may be formed through the same process in which the TFT **110** is formed in the display area (DA).

The second substrate **200** is engaged with the first substrate **100** by sealant **350**. The sealant **350** is disposed in the peripheral area (PA) and covers entire surface of the gate driver circuit **160**.

The liquid crystal layer **300** is interposed between the first and second substrates **100** and **200** that are engaged with each other by the sealant **350**, to thereby complete the LCD device **500**.

The sealant **350** has a dielectric constant lower than those of the liquid crystal layer **300** and the organic insulation layer **130** formed on the display area (DA) and the peripheral area (PA). The capacitance is in proportional to the dielectric constant, and the sealant **350** having a dielectric constant lower than those of the liquid crystal layer **300** and the organic insulation layer **130** is interposed between the gate driver circuit **160** and the common electrode **220**. The entire surface of the gate driver circuit **160** is covered by the sealant **350**, so that the parasitic capacitance between the gate driver circuit **160** and the common electrode **220** may be reduced.

The above structure in which the sealant **350** and the gate driver circuit **160** are arranged may be employed not only in the transmissive type LCD device but also in the reflective type LCD device (not shown) or in the transmissive type LCD device (refer to FIG. **11B**). Although FIG. **11B** shows the configuration of the transmissive type LCD device, any other configurations known to one of the ordinary skill in the art may also be utilized in place of the configuration according to the transmissive type LCD device of FIG. **11B**.

FIG. **12** is a cross-sectional view showing a liquid crystal display device according to a tenth exemplary embodiment of the present invention.

Referring to FIG. **12**, the LCD device according to the tenth exemplary embodiment of the present invention has the structure in which the common electrode is removed on a portion of the second substrate **200**. The portion of the second substrate **200** is disposed over the gate driver circuit **160** and the wiring **165**. The common electrode **220** may be formed in a display area (DA) except the peripheral area (PA). In addition, the common electrode **220** may be further formed in the peripheral area (PA) in which the sealant **350** exists.

The portion of the common electrode **220** disposed over the gate driver circuit **160** and the wiring **165** is etched away by a photolithography process. Accordingly, the parasitic capacitance generated in the peripheral area (PA) may be prevented.

In addition, the sealant and insulation layer having a dielectric constant lower than that of the liquid crystal layer **300** covers the gate driver circuit **160**, and the insulation layer having a dielectric constant lower than that of the liquid crystal layer **300** covers the wiring **165**. In addition, the portion of the common electrode disposed over the gate driver circuit **160** is removed.

The parasitic capacitance between the gate driver circuit and the common electrode may be reduced. Therefore, the gate driver circuit may operate normally, and the distortion of the signal outputted from the gate driver circuit may be prevented.

The structure of the common electrode in FIG. **12** may be employed not only in the transmissive and reflective type LCD device, but also in a reflective type LCD (not shown) device or in a transmissive type LCD device.

FIG. **13** is a cross-sectional view showing a liquid crystal display device according to an eleventh exemplary embodiment of the present invention.

Referring to FIG. **13**, the liquid crystal display device includes a first substrate **100**, a second substrate **200** facing the first substrate **100** and a liquid crystal layer **300** interposed between the first and second substrate **100** and **200**. The LCD device includes a display area (DA) through which an image is displayed and a peripheral area (PA) surrounding the display area (DA).

The display area (DA) includes a plurality of pixels arranged in a matrix shape. Each of the pixels includes a thin film transistor (TFT) **110** and a pixel electrode connected to the TFT **110**. The TFT **110** is connected to a gate line (GL) and a data line (DL). The data line (DL) is extended in a first direction, and the gate line (GL) is extended in a second direction substantially perpendicular to the first direction. The pixel electrode includes a transparent electrode **120** and a reflection electrode **140**. The transparent electrode **120** is directly connected to the TFT **110**, and the reflection electrode **140** is electrically connected to TFT **110** through the transparent electrode **120**.

An organic insulation layer **130** is formed on the first substrate **100** on which the TFT **110** and the transparent electrode **120** are formed. The organic insulation layer **130** covers a contact portion of the TFT **110** in which the TFT **110** is electrically connected to the transparent electrode **120**. The organic insulation layer **130** includes an opening **131** through which a portion of the transparent electrode **120** is exposed. The transmissive area (TA) corresponds to the opening **131**.

The reflection electrode **140** is formed on the organic insulation layer **130** and is electrically connected to the transparent electrode **120** through the opening **131**. In other words, the reflection electrode **140** is extended to a portion of the transparent electrode **120** that is exposed by the opening **131** and makes contact with the transparent electrode **120**. Accordingly, the reflection electrode **140** is electrically connected to the drain of the TFT **110** through the transparent electrode **120**.

A gate driver circuit **160** is formed in the peripheral area (PA). The gate driver circuit **160** is connected to an end of the gate line (GL) and supplies a gate driving signal for driving the gate of the TFT **110**. The gate driver circuit **160** is electrically connected to the gate line (GL) disposed in the display area (DA) through the wiring **165**. The gate driver circuit **160** and the wiring **165** may be formed through the same process in which the TFT **110** is formed in the display area (DA). The organic insulation layer **160** having a dielectric constant lower than that of the liquid crystal layer **300** covers the entire surface of the gate driver circuit **160**.

The second substrate **200** includes color filters **210** and a common electrode **220**. The common electrode **220** is deposited uniformly on the color filter **210**. The common electrode **220** is formed only in the display area (DA) and is not formed in the peripheral area (PA). However, the common electrode **220** may be further formed in the peripheral area (PA) where the sealant **350** exists.

The portion of the common electrode **220** disposed over the gate driver circuit **160** is etched away by the photolithography process. Accordingly, the parasitic capacitance generated in the peripheral area (PA) may be prevented.

FIG. **14** is a cross-sectional view showing a liquid crystal display device according to a twelfth exemplary embodiment of the present invention.

Referring to FIG. **14**, in the display area (DA), the first substrate **100** includes TFT **110**, pixel electrode, inorganic insulation layer **150** and organic insulation layer **130**. The pixel electrode includes a transparent electrode **120** and a reflection electrode **130**. In the display area (DA), the LCD device has the same structure as that of the LCD device of FIG. **7**. The first substrate **100** includes a second insulation layer. The second insulation layer electrically connects the TFT **110** and the transparent electrode **120**.

The structure of the common electrode of FIGS. **11A** and **11B** may be employed not only in the LCD device having the same structure of the display area (DA) shown in FIGS. **11A** and **11B** but also the LCD device having the same structure of the display area (DA) shown in FIGS. **2**, **6** and **8**. In addition, the structure of the common electrode of FIGS. **11A** and **11B** may be employed not only in the transmissive and the reflective type LCD device but also may be employed in a reflective type LCD device or a transmissive type LCD device.

While the exemplary embodiments of the present invention and its advantages have been described in detail, it should be understood that various changes, substitutions and alterations can be made herein without departing from the scope of the invention as defined by appended claims.

What is claimed is:

1. A liquid crystal display device comprising:

a first substrate including a display part displaying images and disposed in a display area of the liquid crystal display device, and a driving part driving the display part, the display part including a switching device and a pixel electrode electrically coupled with the switching device;

a first insulation layer disposed on the switching device;

a wiring electrically connecting the driving part to the display part;

a second substrate including a common electrode facing the pixel electrode, the second substrate having a first portion corresponding to areas except the display area, and a second portion corresponding to the display area, the driving part being disposed to face the first portion, and the common electrode being formed on the second portion of the second substrate except the first portion;

a liquid crystal layer disposed between the first and second substrates; and

a sealing member disposed between the first and second substrates to engage the first substrate with the second substrate and not covering the driving part,

wherein the driving part, the sealing member, and at least one part of the wiring are disposed corresponding to the first portion of the second substrate,

wherein the driving part comprises a shift register applying a signal to the switching device to turn on the switching device, and the shift register is disposed between the display part and the sealing member, and

wherein the shift register comprises:

a first conduction pattern,
 a second conduction pattern between the first conduction pattern and the first insulation layer,
 a gate insulation layer between the first and second conduction patterns; and
 a conduction layer which is disposed on the first insulation layer and electrically connected to at least one of the first conduction pattern and the second conduction pattern.

2. The liquid crystal display device of claim 1, wherein the pixel electrode comprises a transparent electrode, the first insulation layer being disposed on the transparent electrode to cover a contact portion of the switching device in which the switching device is electrically coupled with the transparent electrode, the first insulation layer having an opening through which a portion of the transparent electrode is exposed.

3. The liquid crystal display device of claim 2, wherein the pixel electrode further comprises a reflection electrode disposed on the first insulation layer and electrically coupled with the transparent electrode at the opening.

4. The liquid crystal display device of claim 3, wherein the first substrate further comprises a second insulation layer formed between the switching device and the transparent electrode, the second insulation layer having a contact hole through which the switching device is electrically coupled with the transparent electrode.

5. The liquid crystal display device of claim 1, wherein the first insulation layer covers at least a portion of the driving part.

6. The liquid crystal display device of claim 1, wherein the pixel electrode comprises a transparent electrode disposed on the first insulation layer, the first insulation layer including a contact hole through which the switching device is electrically connected to the pixel electrode.

7. The liquid crystal display device of claim 6, wherein the pixel electrode further comprises a reflection electrode disposed on the transparent electrode.

8. The liquid crystal display device of claim 1, wherein the driving part comprises:

the first conduction pattern including a plurality of gate electrodes of NMOS transistors; and

the second conduction pattern including a plurality of source and drain electrodes of the NMOS transistors.

9. The liquid crystal display device of claim 8, wherein the switching device comprises:

a gate electrode formed on the first substrate;

a gate insulation layer formed on the first substrate having the gate electrode;

a source electrode formed on a portion of the gate insulation layer; and

a drain electrode formed on another portion of the gate insulation layer.

10. The liquid crystal display device of claim 1, further comprising a wiring connecting the driving part to the display part,

wherein the driving part, the wiring and the sealant are disposed corresponding to the first portion of the second substrate.

11. The liquid crystal display device of claim 1, wherein the first insulation layer is an organic insulation layer.

12. The liquid crystal display device of claim 11, wherein the conduction layer is disposed on the organic insulation layer.

13. The liquid crystal display device of claim 1, wherein the conductive layer is disposed on the first insulation layer.

14. The liquid crystal display device of claim 1, wherein the conduction layer is electrically connected to the first con-

duction pattern through a first contact hole formed in the first insulation layer and the gate insulation layer or to the second conduction pattern through a second contact hole formed in the first insulation layer.

15. The liquid crystal display device of claim 1, wherein the driving part comprises a clock line and a power line.

16. The liquid crystal display device of claim 15, wherein the first insulation layer is an organic insulation layer.

17. The liquid crystal display device of claim 16, wherein the conduction layer is disposed on the organic insulation layer.

18. The liquid crystal display device of claim 15, wherein the conduction layer is disposed on the first insulation layer.

19. The liquid crystal display device of claim 15, wherein the conduction layer is electrically connected to the first conduction pattern through a first contact hole formed in the first insulation layer and the gate insulation layer or to the second conduction pattern through a second contact hole formed in the first insulation layer.

20. The liquid crystal display device of claim 1, wherein the sealing member is contact with the first insulation layer.

21. The liquid crystal display device of claim 20, wherein the first insulation layer is an organic insulation layer.

22. The liquid crystal display device of claim 21, wherein the conduction layer is disposed on the organic insulation layer.

23. The liquid crystal display device of claim 22, wherein the conduction layer is electrically connected to the first conduction pattern through a first contact hole formed in the first insulation layer and the gate insulation layer or to the second conduction pattern through a second contact hole formed in the first insulation layer.

24. The liquid crystal display device of claim 23, wherein the driving part comprises a clock line and a power line.

25. A liquid crystal display device comprising:

a first substrate comprising:

a display part displaying images, including a switching device and a pixel electrode electrically coupled with the switching device, and disposed in a display area of the liquid crystal display device;

a driving part driving the display part;

a first insulation layer disposed on the switching device; and

a wiring electrically connecting the driving part to the display part;

a second substrate facing the first substrate;

a sealing member disposed between the first and second substrates to engage the first substrate with the second substrate, the sealing member not covering the driving part; and

a liquid crystal layer disposed between the first and second substrates;

wherein the second substrate further comprises a common electrode facing the pixel electrode, and has a first portion corresponding to areas except the display area, and a second portion corresponding to the display area, the driving part being disposed to face the first portion, and the common electrode being formed on the second portion of the second substrate except the first portion, and wherein the driving part, the sealing member, and at least one part of the wiring are disposed corresponding to the first portion of the second substrate,

wherein the driving part comprises a shift register applying a signal to the switching device to turn on the switching device, and the shift register is disposed between the display part and the sealing member, and

wherein the shift register comprises:

a first conduction pattern,
 a second conduction pattern between the first conduction pattern and the first insulation layer,
 a gate insulation layer between the first and second conduction patterns, and
 a conduction layer which is disposed on the first insulation layer and electrically connected to at least one of the first conduction pattern and the second conduction pattern.

26. The liquid crystal display device of claim 25, wherein the display part has the switching device that includes a gate electrode formed on the first substrate, the gate insulation layer formed on the first substrate having the gate electrode, a source electrode formed on a portion of the gate insulation layer, and a drain electrode formed on another portion of the gate insulation layer.

27. The liquid crystal display device of claim 25, wherein the first conduction pattern includes a plurality of gate electrodes of NMOS transistors and the second conduction pattern includes a plurality of source and drain electrodes of the NMOS transistors.

28. The liquid crystal display device of claim 25, wherein the sealing member has a dielectric constant lower than the liquid crystal layer.

29. The liquid crystal display device of claim 25, wherein the display part comprises a switching device, a first insulation layer disposed on the switching device and a pixel electrode electrically coupled with the switching device.

30. The liquid crystal display device of claim 29, wherein the pixel electrode comprises a transparent electrode.

31. The liquid crystal display device of claim 30, wherein the first insulation layer is disposed on the transparent electrode to cover a contact portion of the switching device in which the switching device is electrically coupled with the transparent electrode, and has an opening through which a portion of the transparent electrode is exposed.

32. The liquid crystal display device of claim 31, wherein the pixel electrode further comprises a reflection electrode disposed on the first insulation layer and electrically coupled with the transparent electrode at the opening.

33. The liquid crystal display device of claim 32, further comprising a second insulation layer formed between the switching device and the transparent electrode, the second insulation layer having a contact hole through which the switching device is electrically coupled with the transparent electrode.

34. The liquid crystal display device of claim 30, wherein the transparent electrode is disposed on the first insulation layer, and the first insulation layer includes a contact hole through which the switching device is exposed.

35. The liquid crystal display device of claim 34, wherein the pixel electrode further comprises a reflection electrode disposed on the transparent electrode.

36. The liquid crystal display device of claim 29, wherein the first insulation layer is disposed on the driving part.

37. The liquid crystal display device of claim 36, wherein the first insulation layer is an organic insulation layer.

38. The liquid crystal display device of claim 37, wherein the conduction layer is disposed on the organic insulation layer.

39. The liquid crystal display device of claim 36, wherein the sealing member is contact with the first insulation layer.

40. The liquid crystal display device of claim 39, wherein the first insulation layer is an organic insulation layer.

41. The liquid crystal display device of claim 40, wherein the conduction layer is disposed on the organic insulation layer.

42. The liquid crystal display device of claim 41, wherein the conduction layer is electrically connected to the first conduction pattern through a first contact hole formed in the first insulation layer and the gate insulation layer or to the second conduction pattern through a second contact hole formed in the first insulation layer.

43. The liquid crystal display device of claim 42, wherein the driving part comprises a clock line and a power line.

44. The liquid crystal display device of claim 29, wherein the conduction layer is disposed on the first insulation layer.

45. The liquid crystal display device of claim 29, wherein the conduction layer is electrically connected to the first conduction pattern through a first contact hole formed in the first insulation layer and the gate insulation layer or to the second conduction pattern through a second contact hole formed in the first insulation layer.

46. The liquid crystal display device of claim 29, wherein the driving part comprises a clock line and a power line.

47. The liquid crystal display device of claim 46, wherein the first insulation layer is an organic insulation layer.

48. The liquid crystal display device of claim 47, wherein the conduction layer is disposed on the organic insulation layer.

49. The liquid crystal display device of claim 46, wherein the conduction layer is disposed on the first insulation layer.

50. The liquid crystal display device of claim 46, wherein the conduction layer is electrically connected to the first conduction pattern through a first contact hole formed in the first insulation layer and the gate insulation layer or to the second conduction pattern through a second contact hole formed in the first insulation layer.

51. The liquid crystal display device of claim 25, wherein the driving part comprises:
 the first conduction pattern including a plurality of gate electrodes of NMOS transistors;
 the second conduction pattern including a plurality of source and drain electrodes of the NMOS transistors.

* * * * *

专利名称(译)	液晶显示装置		
公开(公告)号	US7944539	公开(公告)日	2011-05-17
申请号	US10/412451	申请日	2003-04-11
[标]申请(专利权)人(译)	李东HO		
申请(专利权)人(译)	李东HO		
当前申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
[标]发明人	LEE DONG HO		
发明人	LEE, DONG-HO		
IPC分类号	G02F1/1345 G02F1/1339 G02F1/1343 G02F1/133 G02F1/1362		
CPC分类号	G02F1/1339 G02F1/13454 G02F2203/09 G02F1/136227 G02F1/133345 G02F1/136286 G02F1/1368		
代理机构(译)	康托科尔伯恩LLP		
审查员(译)	NGUYEN , 龚便T.		
优先权	1020030006189 2003-01-30 KR		
其他公开文献	US20040150771A1		
外部链接	Espacenet USPTO		

摘要(译)

LCD设备提供增强的显示质量。在第一基板上形成绝缘层。绝缘层覆盖开关装置的接触部分，其中开关装置电连接到透明电极并且具有用于暴露透明电极的一部分的开口。反射电极通过开口电连接到透明电极。绝缘层覆盖形成在第一基板上的驱动电路的第一部分。密封剂插入第一和第二基板之间以接合第一和第二基板并覆盖驱动电路的第二部分。因此，驱动电路可以正常操作，并且可以防止从驱动电路输出的信号的失真。

