



US008836889B2

(12) **United States Patent**
Park et al.

(10) **Patent No.:** **US 8,836,889 B2**
(45) **Date of Patent:** **Sep. 16, 2014**

(54) **TRANSPARENT DISPLAY DEVICE
INCLUDING A LIGHT GUIDE PLATE
FORMED WITH A PLURALITY OF
CONCAVE PATTERNS AT THE LOWER
SURFACE THEREOF**

(75) Inventors: **Se-Hong Park**, Gyeonggi-Do (KR);
Jong-Sin Park, Seoul (KR)

(73) Assignee: **LG Display Co., Ltd.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 327 days.

(21) Appl. No.: **12/836,352**

(22) Filed: **Jul. 14, 2010**

(65) **Prior Publication Data**

US 2011/0013123 A1 Jan. 20, 2011

(30) **Foreign Application Priority Data**

Jul. 15, 2009 (KR) 10-2009-0064664

(51) **Int. Cl.**

G02F 1/1335 (2006.01)
G02F 1/1333 (2006.01)
F21V 9/14 (2006.01)
F21V 7/04 (2006.01)
F21V 8/00 (2006.01)

(52) **U.S. Cl.**

CPC **G02B 6/0056** (2013.01); **G02F 1/133615**
(2013.01); **G02B 6/0036** (2013.01)
USPC **349/62**; 349/61; 349/64; 349/65;
349/96; 362/19; 362/611; 362/612; 362/615

(58) **Field of Classification Search**

USPC 349/61–62, 64–65, 96; 362/19,
362/611–612, 615

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2002/0085368 A1* 7/2002 Taniguchi et al. 362/31
2008/0205084 A1* 8/2008 Chen et al. 362/629
2009/0279324 A1* 11/2009 Chen et al. 362/616

* cited by examiner

Primary Examiner — Lauren Nguyen

(74) *Attorney, Agent, or Firm* — McKenna Long & Aldridge
LLP

(57) **ABSTRACT**

Disclosed is a transparent display device including a light guide plate formed with a plurality of concave patterns at the lower surface thereof to totally reflect polarized light entered in a lateral direction while transmitting natural light entered from a lower direction therethrough; a light source disposed in a lateral direction of the light guide plate to emit visible light including first and second polarized lights; a first polarizing plate disposed at a lateral portion of the light guide plate to transmit either one of the first and second polarized lights through the light guide plate; a liquid crystal panel for driving liquid crystals to change the phase of the polarized light; and a second polarizing plate for controlling an amount of the polarized light according to the changed phase of the polarized light.

9 Claims, 7 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12





FIG. 13



1

**TRANSPARENT DISPLAY DEVICE
INCLUDING A LIGHT GUIDE PLATE
FORMED WITH A PLURALITY OF
CONCAVE PATTERNS AT THE LOWER
SURFACE THEREOF**

CROSS-REFERENCE TO RELATED
APPLICATIONS

Pursuant to 35 U.S.C. §119(a), this application claims the benefit of Korean Application No. 10-2009-0064664, filed on Jul. 15, 2009, the contents of which are incorporated by reference herein in its entirety.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a display device, and more particularly, to a transparent display device having a liquid crystal panel.

2. Description of the Related Art

In recent years, studies on transparent display devices for allowing rear objects to be seen as well as capable of making a display thereon have been actively carried out.

In general, a transparent display device is capable of making a transparent display in an organic light-emitting panel or plasma panel using spontaneous light emission.

However, such a transparent display is not allowed in a liquid crystal panel incapable of emitting spontaneous light but using backlight. It is because a non-transparent backlight assembly should be provided at a rear surface of the panel and also polarizing plates should be provided respectively at both front and rear surfaces of the liquid crystal panel to control the transmission of light. In particular, in the polarizing plates provided respectively at both front and rear surfaces of the liquid crystal panel, light is transmitted therethrough when liquid crystals are driven in the liquid crystal panel, but light is in a non-transparent state when liquid crystals are not driven, and thus it may be impossible to implement a transparent display.

Such transparent display devices may be applicable to vehicle front glasses or house glasses to provide the user's desired information.

Therefore, the applicability of such transparent display devices is expected to be drastically expanded. In particular, a liquid crystal panel has wide viewing angle, high luminance, high contrast and full color, and thus it is urgently required to develop a transparent display device having a liquid crystal panel.

SUMMARY OF THE INVENTION

The objective of the present invention is to provide a transparent display device capable of implementing a transparent display by removing the polarizing plates and changing the structure of a light guide plate.

In order to accomplish the foregoing objective, a transparent display device according to the present invention is characterized by including a light guide plate formed with a plurality of concave patterns at the lower surface thereof to totally reflect polarized light entered in a lateral direction while transmitting natural light entered from a lower direction therethrough; a light source disposed in a lateral direction of the light guide plate to emit visible light including a first and a second polarized light; a first polarizing plate disposed at a lateral portion of the light guide plate to transmit either one of the first and second polarized lights through the light guide

2

plate; a liquid crystal panel for driving liquid crystals to change the phase of the polarized light; and a second polarizing plate for controlling an amount of the polarized light according to the changed phase of the polarized light.

In order to accomplish the foregoing objective, a transparent display device according to the present invention is characterized by including a light guide plate formed with a plurality of concave patterns at the lower surface thereof having an inclined cross-section to totally reflect polarized light entered in both lateral directions while transmitting natural light entered from a lower direction therethrough; a first and a second light source disposed in both lateral directions of the light guide plate to emit visible light including a first and a second polarized light; a first and a second polarizing plate disposed at both lateral surfaces of the light guide plate to transmit either one of the first and second polarized lights through the light guide plate; a liquid crystal panel for driving liquid crystals to change the phase of the polarized light; and a third polarizing plate for controlling an amount of the polarized light according to the changed phase of the polarized light.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention.

In the drawings:

FIG. 1 is a schematic view illustrating a transparent display device according to an embodiment of the present invention;

FIG. 2 is a schematic cross-sectional view illustrating a transparent display device according to an embodiment of the present invention;

FIG. 3 is a schematic view illustrating the change process of a polarized light generated from a light source of the transparent display device according to an embodiment of the present invention;

FIG. 4 is a schematic cross-sectional view illustrating a state that the light rays generated from a light source of the transparent display device according to an embodiment of the present invention is polarized through a polarizing plate and a light guide plate;

FIG. 5 is a schematic plan view illustrating concave patterns formed at a lower surface of the light guide plate of the transparent display device according to an embodiment of the present invention;

FIG. 6 is a schematic view illustrating a transparent display device according to another embodiment of the present invention;

FIG. 7 is a schematic cross-sectional view illustrating a transparent display device according to another embodiment of the present invention;

FIG. 8 is a schematic cross-sectional view illustrating a state that the light rays generated from a light source of the transparent display device according to another embodiment of the present invention is polarized through a polarizing plate and a light guide plate;

FIG. 9 is a schematic plan view illustrating concave patterns formed at a lower surface of the light guide plate of the transparent display device according to another embodiment of the present invention;

FIG. 10 is a schematic view illustrating a transparent display device according to still another embodiment of the present invention;

FIG. 11 is a schematic cross-sectional view illustrating a transparent display device according to still another embodiment of the present invention;

FIG. 12 is a schematic cross-sectional view illustrating a state that the light rays generated from a light source of the transparent display device according to still another embodiment of the present invention is polarized through a polarizing plate and a light guide plate; and

FIG. 13 is a schematic plan view illustrating concave patterns formed at a lower surface of the light guide plate of the transparent display device according to still another embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Hereinafter, a transparent display device according to a preferred embodiment of the present invention will be described in detail with reference to the accompanying drawings.

FIG. 1 is a schematic view illustrating a transparent display device according to an embodiment of the present invention.

FIG. 2 is a schematic cross-sectional view illustrating a transparent display device according to an embodiment of the present invention.

FIG. 3 is a schematic view illustrating the change process of a polarized light generated from a light source of the transparent display device according to an embodiment of the present invention.

FIG. 4 is a schematic cross-sectional view illustrating a state that the light rays generated from a light source of the transparent display device according to an embodiment of the present invention is polarized through a polarizing plate and a light guide plate.

FIG. 5 is a schematic plan view illustrating concave patterns formed at a lower surface of the light guide plate of the transparent display device according to an embodiment of the present invention.

Referring to FIGS. 1 and 2, a transparent display device according to an embodiment of the present invention may be configured by including a light source 10 for generating light, a first polarizing plate 30 for polarizing the light generated from the light source, a light guide plate 20 for outputting polarized light entered through the first polarizing plate 30 to the front surface thereof, and a liquid crystal panel 40 and a second polarizing plate 50 for making a display by the light outputted to the front surface through the light guide plate 20.

Here, referring to FIG. 2, the liquid crystal panel 40 may be configured by including a first substrate 41 having a thin-film transistor (not shown) which is a switching device and a pixel electrode electrically connected to the thin-film transistor; a second substrate 42 having a black matrix 43 formed at the upper surface thereof with regular intervals to block light coming from the light source, a color filter pattern 44 formed in a region between the black matrices 43, and an overcoat layer 45 formed on the color filter patterns 44; and a liquid crystal layer 47 inserted between the first substrate 41 and the second substrate 42.

On the other hand, the light source 10 is disposed to face a light incident surface 20a located at a side of the light guide plate 20. The light source 10 may be a lamp, such as a cold cathode fluorescence (CCFL) and external electrode fluorescence lamp (EEFL), or a light-emitting diode array. At this time, the light-emitting diode array may be configured with a red light-emitting diode, a green light-emitting diode, and blue light-emitting diode, or a plurality of white light-emitting diodes.

Furthermore, the light emitted from the light source 10 may include a first polarized light (vertical polarized light) and a second polarized light (horizontal polarized light).

In addition, the first polarizing plate 30 is disposed to adjoin and face the light incident surface 20a located at a side of the light guide plate 20. In other words, the first polarizing plate 30 is disposed between the light source 10 and the light incident surface 20a of the light guide plate 20. At this time, the first polarizing plate 30 transmits only the first polarized light from the light including the first polarized light and the second polarized light therethrough.

If the light emitted from the light source 10 is entered to the first polarizing plate 30, then only the first polarized light from the light is transmitted by the first polarizing plate 30.

The light guide plate 20 allows the first polarized light passed through the first polarizing plate 30 to be entered into the liquid crystal panel 40 at the front side.

On the other hand, referring to FIG. 3, the light emitted from the light source 10 may include a first and a second polarized light, and only the first polarized light is passed through the first polarizing plate 30, and the first polarized light is entered into the liquid crystal panel 40 through the light guide plate 20, and a phase difference of the first polarized light is changed by driving liquid crystals in the liquid crystal panel 40, and the amount of light passed through the second polarizing plate 50 is changed depending on the changed level of the phase difference to express the gradation.

Moreover, natural light coming from a lower direction of the light guide plate 20 is passed through the second polarizing plate 50 regardless of driving the liquid crystal panel 40, thereby allowing the user to see an object at a lower portion of the light guide plate 20 regardless of making a display.

Accordingly, light prior to entering into the light guide plate 20 is polarized, thereby implementing a display using the polarized light while maintaining a transparent state using natural light coming from a lower direction of the light guide plate 20. At this time, for a light source of the present invention, natural light entered from a lateral direction of the light guide plate 20 may be used as a light source of the present invention, and polarized light emitted by an indoor lamp may be also used.

On the other hand, it is difficult for the light guide plate 20 to uniformly distribute light over an overall surface thereof as located away from the light source 10, and thus the thickness of the light guide plate 20 becomes smaller as located away from the light source 10.

Furthermore, as illustrated in FIGS. 4 and 5, the light guide plate 20 is formed with a plurality of concave patterns 25 to make a uniform surface light source by scattering the light at the lower surface thereof. At this time, the plurality of concave patterns 25 are formed by performing laser irradiation at a lower surface of the light guide plate 20 using a separate mask (not shown) defined by the same pattern shape as the concave patterns. At this time, irradiation energy, irradiation time, and the like when performing laser irradiation may be applied differently depending on the size or kind of the product. The transparency and luminance of the plurality of concave patterns 25 may vary depending on the size and interval of the patterns, and thus it is required to properly adjust the size and interval of the patterns. Alternatively, the concave patterns 25 may be formed using a method such as ruggedness, etching, printing, and the like, as well as laser irradiation.

Referring to FIG. 5, it is designed such that a distance (D1) between the left and right concave patterns 25 adjacent to each other in a horizontal direction (namely, X-direction) of the plurality of concave patterns 25 is 50-350 μm , and a

distance (D2) between the upper and lower concave patterns 25 adjacent to each other in a vertical direction (namely, Y-direction) is 50-350 μm . At this time, it is preferably designed such that a distance (D1) between the left and right concave patterns 25 adjacent to each other in the horizontal direction (namely, X-direction) is about 150-250 μm , and a distance (D2) between the upper and lower concave patterns 25 adjacent to each other in the vertical direction (namely, Y-direction) is about 80-150 μm . On the other hand, it is more preferably designed such that a distance (D1) between the left and right concave patterns 25 adjacent to each other in the horizontal direction (namely, X-direction) is about 200-230 μm , and a distance (D2) between the upper and lower concave patterns 25 adjacent to each other in the vertical direction (namely, Y-direction) is about 90-120 μm .

At this time, the intervals (D1, D2) between the concave patterns 25 formed in a second region (P2) of the plurality of concave patterns 25 located away from the light source 10 on the basis of a central portion of the light guide plate 20 are formed narrower than the intervals (D1, D2) between the concave patterns 25 formed in a first region (P1) thereof near to the light source 10. The intervals (D1, D2) between the concave patterns 25 are formed narrower because the second region (P2) of the light guide plate 20 is located away from the light source 10, thereby allowing the light generated from the light source 10 to be easily reached.

In addition, the plurality of concave patterns 25 are formed with an oval-shaped structure, and the concave patterns 25 are 50-350 μm in horizontal length (L1) and 50-300 μm in vertical length (L2). At this time, it is preferably designed such that a size of the concave patterns 25 formed in the first region (P1) of the plurality of concave patterns 25 which is located near to the light source 10 on the basis of a central portion of the light guide plate 20 is 100-150 μm in horizontal length (L1) and 50-150 μm in vertical length (L2).

Also, it is preferably designed such that a size of the concave patterns 25 formed in the first region (P2) which is located away from the light source 10 on the basis of a central portion of the light guide plate 20 is 100-200 μm in horizontal length (L1) and 50-150 μm in vertical length (L2).

On the other hand, natural light may be entered from a lower surface of the light guide plate 20, and at this time the natural light may be entered to the liquid crystal panel 40 via a portion between the concave patterns 25 of the light guide plate 20. The transparent display device of the invention is capable of maintaining a transparent state regardless of whether or not being displayed by such natural light. Accordingly, an object located at a lower portion of the light guide plate is allowed to be viewed by the user at the front side.

At this time, the liquid crystal panel 40 contains liquid crystals 47, the phase of the first polarized light may be varied by driving liquid crystals. The phase of the first polarized light that can be varied by driving liquid crystals may have a range of 0-90 degrees.

In addition, as described above, natural light is entered to the liquid crystal panel 40 through a lower surface of the light guide plate 20, where in the natural light may include a first polarized light and a second polarized light. Accordingly, both first and second polarized lights of the natural light are entered to the liquid crystal panel 40, and thus the second polarized light of the natural light is passed through the liquid crystal panel 40 when liquid crystals are not driven, and the first polarized light of the natural light is passed through the liquid crystal panel 40 when liquid crystals are driven. As a result, an object located at a lower portion of the light guide plate 20 is allowed to be viewed by the user regardless of driving liquid crystals, namely, making a display.

Furthermore, the second polarizing plate 50 may have an optical axis perpendicular to the first polarizing plate 30. Therefore, the light transmission amount may be controlled depending on the phase of the first polarized light varied by driving liquid crystals. For example, in case where the phase of the first polarized light is 0 degree, then the first polarized light is not passed through the second polarizing plate 50, but a more amount of the first polarized light can be passed through the second polarizing plate 50 as increasing the phase of the first polarized light, and thus it may be possible to obtain more gradation as increasing the amount of the first polarized light.

On the other hand, a transparent display device according to another embodiment of the present invention will be described below with reference to FIGS. 6 through 9.

FIG. 6 is a schematic view illustrating a transparent display device according to another embodiment of the present invention.

FIG. 7 is a schematic cross-sectional view illustrating a transparent display device according to another embodiment of the present invention.

FIG. 8 is a schematic cross-sectional view illustrating a state that the light rays generated from a light source of the transparent display device according to another embodiment of the present invention is polarized through a polarizing plate and a light guide plate.

FIG. 9 is a schematic plan view illustrating concave patterns formed at a lower surface of the light guide plate of the transparent display device according to another embodiment of the present invention.

Referring to FIGS. 6 and 7, a transparent display device according to another embodiment of the present invention may be configured by including a light source 110 for generating light, a first polarizing plate 130 for polarizing the light generated from the light source, a light guide plate 120 for outputting polarized light entered through the first polarizing plate 130 to the front surface thereof, and a liquid crystal panel 140 and a second polarizing plate 150 for making a display by the light outputted to the front surface through the light guide plate 120.

Here, referring to FIG. 7, the liquid crystal panel 140 may be configured by including a first substrate 141 having a thin-film transistor (not shown) which is a switching device and a pixel electrode electrically connected to the thin-film transistor; a second substrate 142 having a black matrix 143 formed at the upper surface thereof with regular intervals to block light coming from the light source, a color filter pattern 144 formed in a region between the black matrices 143, and an overcoat layer 145 formed on the color filter patterns 144; and a liquid crystal layer 147 inserted between the first substrate 141 and the second substrate 142.

On the other hand, the light source 110 is disposed to face a light incident surface 120a located at a side of the light guide plate 120. The light source 110 may be a lamp, such as a cold cathode fluorescence (CCFL) and external electrode fluorescence lamp (EEFL), or a light-emitting diode array. At this time, the light-emitting diode array may be configured with a red light-emitting diode, a green light-emitting diode, and blue light-emitting diode, or a plurality of white light-emitting diodes.

Furthermore, the light emitted from the light source 110 may include a first polarized light (vertical polarized light) and a second polarized light (horizontal polarized light).

In addition, the first polarizing plate 130 is disposed to adjoin and face the light incident surface 120a located at a side of the light guide plate 120 and inclined by a predetermined angle ($\theta 1$). In other words, the first polarizing plate 130

is disposed between the light source **110** and the light incident surface **120a** of the light guide plate **120**. At this time, the first polarizing plate **130** transmits only the first polarized light from the light including the first polarized light and the second polarized light therethrough. The inclined angle ($\theta 1$) of the light guide plate **120** has a range of about 35-55 degrees. At this time, it is preferable that the inclined angle ($\theta 1$) of the light guide plate **120** has a range of about 40-50 degrees.

If the light emitted from the light source **110** is entered to the first polarizing plate **130**, then only the first polarized light from the light is transmitted by the first polarizing plate **130**.

The light guide plate **120** allows the first polarized light passed through the first polarizing plate **130** to be entered into the liquid crystal panel **140** at the front side.

On the other hand, the light emitted from the light source **110** may include a first and a second polarized light, and only the first polarized light is passed through the first polarizing plate **130**, and the first polarized light is entered into the liquid crystal panel **140** through the light guide plate **120**, and a phase difference of the first polarized light is changed by driving liquid crystals in the liquid crystal panel **140**, and the amount of light passed through the second polarizing plate **150** is changed depending on the changed level of the phase difference to express the gradation.

Moreover, natural light coming from a lower direction of the light guide plate **120** is passed through the second polarizing plate **150** regardless of driving the liquid crystal panel **140**, thereby allowing the user to see an object at a lower portion of the light guide plate **120** regardless of making a display.

Accordingly, light prior to entering into the light guide plate **120** is polarized, thereby implementing a display using the polarized light while maintaining a transparent state using natural light coming from a lower direction of the light guide plate **120**. At this time, for a light source of the present invention, natural light entered from a lateral direction of the light guide plate **120** may be used as a light source of the present invention, and polarized light emitted by an indoor lamp may be also used.

On the other hand, it is difficult for the light guide plate **120** to uniformly distribute light over an overall surface thereof as located away from the light source **110**, and thus the thickness of the light guide plate **120** becomes smaller as located away from the light source **110**.

Furthermore, as illustrated in FIGS. **8** and **9**, the light guide plate **120** is formed with a plurality of concave patterns **125** to make a uniform surface light source by scattering the light at the lower surface thereof. At this time, the plurality of concave patterns **125** are formed by performing laser irradiation at a lower surface of the light guide plate **120** using a separate mask (not shown) defined by the same pattern shape as the concave patterns. At this time, irradiation energy, irradiation time, and the like when performing laser irradiation may be applied differently depending on the size or kind of the product. The transparency and luminance of the plurality of concave patterns **125** may vary depending on the size and interval of the patterns, and thus it is required to properly adjust the size and interval of the patterns.

Referring to FIG. **9**, it is designed such that a distance (D1) between the left and right concave patterns **125** adjacent to each other in a horizontal direction (namely, X-direction) of the plurality of concave patterns **125** is 50-350 μm , and a distance (D2) between the upper and lower concave patterns **125** adjacent to each other in a vertical direction (namely, Y-direction) is 50-350 μm . At this time, it is preferably designed such that a distance (D1) between the left and right concave patterns **125** adjacent to each other in the horizontal

direction (namely, X-direction) is about 150-250 μm , and a distance (D2) between the upper and lower concave patterns **125** adjacent to each other in the vertical direction (namely, Y-direction) is about 80-150 μm . On the other hand, it is more preferably designed such that a distance (D1) between the left and right concave patterns **125** adjacent to each other in the horizontal direction (namely, X-direction) is about 200-230 μm , and a distance (D2) between the upper and lower concave patterns **125** adjacent to each other in the vertical direction (namely, Y-direction) is about 90-120 μm .

At this time, the intervals (D1, D2) between the concave patterns **125** formed in a second region (P2) of the plurality of concave patterns **125** located away from the light source **110** on the basis of a central portion of the light guide plate **120** are formed narrower than the intervals (D1, D2) between the concave patterns **125** formed in a first region (P1) thereof near to the light source **110**. The intervals (D1, D2) between the concave patterns **125** are formed narrower because the second region (P2) of the light guide plate **120** is located away from the light source **110**, thereby allowing the light generated from the light source **110** to be easily reached.

In addition, the plurality of concave patterns **125** are formed with a oval-shaped structure, and the concave patterns **125** are 50-350 μm in horizontal length (L1) and 50-300 μm in vertical length (L2). At this time, it is preferably designed such that a size of the concave patterns **125** formed in the first region (P1) of the plurality of concave patterns **125** which is located near to the light source **110** on the basis of a central portion of the light guide plate **120** is 100-150 μm in horizontal length (L1) and 50-150 μm in vertical length (L2).

Also, it is preferably designed such that a size of the concave patterns **125** formed in the first region (P2) which is located away from the light source **110** on the basis of a central portion of the light guide plate **120** is 100-200 μm in horizontal length (L1) and 50-150 μm in vertical length (L2).

On the other hand, natural light may be entered from a lower surface of the light guide plate **120**, and at this time the natural light may be entered to the liquid crystal panel **140** via a portion between the concave patterns **125** of the light guide plate **120**. The transparent display device of the invention is capable of maintaining a transparent state regardless of whether or not being displayed by such natural light. Accordingly, an object located at a lower portion of the light guide plate is allowed to be viewed by the user at the front side.

At this time, the liquid crystal panel **140** contains liquid crystals **147**, the phase of the first polarized light may be varied by driving liquid crystals. The phase of the first polarized light that can be varied by driving liquid crystals may have a range of 0-90 degrees.

In addition, as described above, natural light is entered to the liquid crystal panel **140** through a lower surface of the light guide plate **120**, where in the natural light may include a first polarized light and a second polarized light. Accordingly, both first and second polarized lights of the natural light are entered to the liquid crystal panel **140**, and thus the second polarized light of the natural light is passed through the liquid crystal panel **140** when liquid crystals are not driven, and the first polarized light of the natural light is passed through the liquid crystal panel **140** when liquid crystals are driven. As a result, an object located at a lower portion of the light guide plate **120** is allowed to be viewed by the user regardless of driving liquid crystals, namely, making a display.

Furthermore, the second polarizing plate **150** may have an optical axis perpendicular to the first polarizing plate **130**. Therefore, the light transmission amount may be controlled depending on the phase of the first polarized light varied by driving liquid crystals. For example, in case where the phase

of the first polarized light is 0 degree, then the first polarized light is not passed through the second polarizing plate **150**, but a more amount of the first polarized light can be passed through the second polarizing plate **150** as increasing the phase of the first polarized light, and thus it may be possible to obtain more gradation as increasing the amount of the first polarized light.

On the other hand, a transparent display device according to still another embodiment of the present invention will be described below with reference to FIGS. **10** through **13**.

FIG. **10** is a schematic view illustrating a transparent display device according to still another embodiment of the present invention.

FIG. **11** is a schematic cross-sectional view illustrating a transparent display device according to still another embodiment of the present invention.

FIG. **12** is a schematic cross-sectional view illustrating a state that the light rays generated from a light source of the transparent display device according to still another embodiment of the present invention is polarized through a polarizing plate and a light guide plate.

FIG. **13** is a schematic plan view illustrating concave patterns formed at a lower surface of the light guide plate of the transparent display device according to still another embodiment of the present invention.

Referring to FIGS. **10** and **11**, a transparent display device according to still another embodiment of the present invention may be configured by including a light sources **210**, **215** for generating light, first polarizing plates **230**, **235** for polarizing the light generated from the light sources, a light guide plate **220** for outputting polarized light entered through the first polarizing plates **230**, **235** to the front surface thereof, and a liquid crystal panel **240** and a second polarizing plate **250** for making a display by the light outputted to the front surface through the light guide plate **220**.

Here, referring to FIG. **11**, the liquid crystal panel **240** may be configured by including a first substrate **241** having a thin-film transistor (not shown) which is a switching device and a pixel electrode electrically connected to the thin-film transistor; a second substrate **242** having a black matrix **243** formed at the upper surface thereof with regular intervals to block light coming from the light source, a color filter pattern **244** formed in a region between the black matrices **243**, and an overcoat layer **245** formed on the color filter patterns **244**; and a liquid crystal layer **247** inserted between the first substrate **241** and the second substrate **242**.

On the other hand, the light sources **210**, **215** are disposed to face inclined-shaped light incident surfaces **220a**, **220b** located at both sides of the light guide plate **220**. The light sources **210**, **215** may be a lamp, such as a cold cathode fluorescence lamp (CCFL) and external electrode fluorescence lamp (EEFL), or a light-emitting diode array. At this time, the light-emitting diode array may be configured with a red light-emitting diode, a green light-emitting diode, and blue light-emitting diode, or a plurality of white light-emitting diodes.

Furthermore, the light emitted from the light sources **210**, **215** may include a first polarized light (vertical polarized light) and a second polarized light (horizontal polarized light).

In addition, the first polarizing plates **230**, **235** are disposed to adjoin and face the light incident surfaces **220a**, **220b** located at both sides of the light guide plate **220** and inclined by a predetermined angle ($\theta 1$). In other words, the first polarizing plates **230**, **235** are disposed between the light sources **210**, **215** and the light incident surfaces **220a**, **220b** of the light guide plate **220**. At this time, the first polarizing plates **230**, **235** transmit only the first polarized light from the light

including the first polarized light and the second polarized light therethrough. The inclined angle ($\theta 1$) of the light guide plate **220** has a range of about 35-55 degrees. At this time, it is preferable that the inclined angle ($\theta 1$) of the light guide plate **220** has a range of about 40-50 degrees.

If the light emitted from the light sources **210**, **215** is entered to the first polarizing plates **230**, **235**, then only the first polarized light from the light is transmitted by the first polarizing plates **230**, **235**.

The light guide plate **220** allows the first polarized light passed through the first polarizing plates **230**, **235** to be entered into the liquid crystal panel **240** at the front side.

On the other hand, the light emitted from the light sources **210**, **215** may include a first and a second polarized light, and only the first polarized light is passed through the first polarizing plates **230**, **235**, and the first polarized light is entered into the liquid crystal panel **240** through the light guide plate **220**, and a phase difference of the first polarized light is changed by driving liquid crystals in the liquid crystal panel **240**, and the amount of light passed through the second polarizing plate **250** is changed depending on the changed level of the phase difference to express the gradation.

Moreover, natural light coming from a lower direction of the light guide plate **220** is passed through the second polarizing plate **250** regardless of driving the liquid crystal panel **240**, thereby allowing the user to see an object at a lower portion of the light guide plate **220** regardless of making a display.

Accordingly, light prior to entering into the light guide plate **220** is polarized, thereby implementing a display using the polarized light while maintaining a transparent state using natural light coming from a lower direction of the light guide plate **220**. At this time, for a light source of the present invention, natural light entered from a lateral direction of the light guide plate **220** may be used as a light source of the present invention, and polarized light emitted by an indoor lamp may be also used.

On the other hand, it is difficult for the light guide plate **220** to uniformly distribute light over an overall surface thereof as located away from the left and right light sources **210**, **215**, and thus the thickness of the light guide plate **220** becomes smaller as located away from the light sources **210**, **215**. In other words, the thickness is formed thinner as it goes toward a central portion of the light guide plate **220**. In particular, a lower surface of the light guide plate **220** is formed to be inclined and smaller in the thickness as it goes toward a central portion thereof from both sides of the light guide plate. At this time, an inclined angle of the lower central portion of the light guide plate **220** is preferably formed to be smaller than 180 degrees.

Furthermore, as illustrated in FIGS. **12** and **13**, the light guide plate **220** is formed with a plurality of concave patterns **225** to make a uniform surface light source by scattering the light at the lower surface thereof. At this time, the plurality of concave patterns **225** are formed by performing laser irradiation at a lower surface of the light guide plate **220** using a separate mask (not shown) defined by the same pattern shape as the concave patterns. At this time, irradiation energy, irradiation time, and the like when performing laser irradiation may be applied differently depending on the size or kind of the product. The transparency and luminance of the plurality of concave patterns **225** may vary depending on the size and interval of the patterns, and thus it is required to properly adjust the size and interval of the patterns.

Referring to FIG. **13**, it is designed such that a distance ($D1$) between the left and right concave patterns **225** adjacent to each other in a horizontal direction (namely, X-direction)

of the plurality of concave patterns **225** is 50-350 μm , and a distance (D2) between the upper and lower concave patterns **225** adjacent to each other in a vertical direction (namely, Y-direction) is 50-350 μm . At this time, it is preferably designed such that a distance (D1) between the left and right concave patterns **225** adjacent to each other in the horizontal direction (namely, X-direction) is about 150-250 μm , and a distance (D2) between the upper and lower concave patterns **225** adjacent to each other in the vertical direction (namely, Y-direction) is about 80-150 μm . On the other hand, it is more preferably designed such that a distance (D1) between the left and right concave patterns **225** adjacent to each other in the horizontal direction (namely, X-direction) is about 200-230 μm , and a distance (D2) between the upper and lower concave patterns **225** adjacent to each other in the vertical direction (namely, Y-direction) is about 90-120 μm .

At this time, the intervals (D1, D2) between the concave patterns **225** formed in a second region (P2) of the plurality of concave patterns **225** located away from the light sources **210**, **215** on the basis of a central portion of the light guide plate **120** are formed narrower than the intervals (D1, D2) between the concave patterns **225** formed in a first region (P1) thereof near to the light sources **210**, **215**. The intervals (D1, D2) between the concave patterns **225** are formed narrower because the second region (P2) of the light guide plate **220** is located away from the light sources **210**, **215**, thereby allowing the light generated from the light sources **210**, **215** to be easily reached.

In addition, the plurality of concave patterns **225** are formed with a oval-shaped structure, and the concave patterns **225** are 50-350 μm in horizontal length (L1) and 50-300 μm in vertical length (L2). At this time, it is preferably designed such that a size of the concave patterns **225** formed in the first region (P1) of the plurality of concave patterns **225** which is located near to the light sources **210**, **215** on the basis of a central portion of the light guide plate **220** is 100-150 μm in horizontal length (L1) and 50-150 μm in vertical length (L2).

Also, it is preferably designed such that a size of the concave patterns **225** formed in the first region (P2) which is located away from the light sources **210**, **215** on the basis of a central portion of the light guide plate **220** is 100-200 μm in horizontal length (L1) and 50-150 μm in vertical length (L2).

On the other hand, natural light may be entered from a lower surface of the light guide plate **220**, and at this time the natural light may be entered to the liquid crystal panel **240** via a portion between the concave patterns **225** of the light guide plate **220**. The transparent display device of the invention is capable of maintaining a transparent state regardless of whether or not being displayed by such natural light. Accordingly, an object located at a lower portion of the light guide plate is allowed to be viewed by the user at the front side.

At this time, the liquid crystal panel **240** contains liquid crystals **247**, the phase of the first polarized light may be varied by driving liquid crystals. The phase of the first polarized light that can be varied by driving liquid crystals may have a range of 0-90 degrees.

In addition, as described above, natural light is entered to the liquid crystal panel **240** through a lower surface of the light guide plate **220**, where in the natural light may include a first polarized light and a second polarized light. Accordingly, both first and second polarized lights of the natural light are entered to the liquid crystal panel **240**, and thus the second polarized light of the natural light is passed through the liquid crystal panel **240** when liquid crystals are not driven, and the first polarized light of the natural light is passed through the liquid crystal panel **240** when liquid crystals are driven. As a result, an object located at a lower portion of the light guide

plate **220** is allowed to be viewed by the user regardless of driving liquid crystals, namely, making a display.

Furthermore, the second polarizing plate **250** may have an optical axis perpendicular to the first polarizing plates **230**, **235**. Therefore, the light transmission amount may be controlled depending on the phase of the first polarized light varied by driving liquid crystals. For example, in case where the phase of the first polarized light is 0 degree, then the first polarized light is not passed through the second polarizing plate **250**, but a more amount of the first polarized light can be passed through the second polarizing plate **250** as increasing the phase of the first polarized light, and thus it may be possible to obtain more gradation as increasing the amount of the first polarized light.

As described above, according to the present invention, a polarizing plate disposed at an upper or lower portion is removed from the polarizing plates that have been disposed at the upper and lower portions of a conventional liquid crystal panel, thereby allowing the implementation of a transparent display even in liquid crystal panels which were formerly considered to be impossible to realize to expand the applicability of such liquid crystal panels.

In addition, according to the present invention, some of the polarizing plates required in the existing liquid crystal display devices and some of materials of the backlight unit (optical sheets, etc.) can be removed, thereby reducing the production cost of a transparent display device.

Although the present invention has been described with reference to the preferred embodiments as illustrated in the drawings, these are merely illustrative, and it should be understood by those skilled in the art that various modifications and equivalent other embodiments of the present invention can be made.

What is claimed is:

1. A transparent display device, comprising:

a light guide plate formed with a plurality of concave patterns at the lower surface thereof to totally reflect polarized light entered in a lateral direction while transmitting natural light entered from a lower direction therethrough;

a light source disposed in a lateral direction of the light guide plate to emit visible light including a first and a second polarized light;

a first polarizing plate disposed at a lateral portion of the light guide plate to transmit either one of the first and second polarized lights through to the light guide plate;

a liquid crystal panel arranged directly above an upper surface of the light guide plate without any intervening structure between a first substrate of the liquid crystal panel and the light guide plate, wherein the liquid crystal panel drives liquid crystals to change the phase of the polarized light; and

a second polarizing plate on a second substrate of the liquid crystal panel, the second polarizing plate being arranged to control an amount of the polarized light according to the changed phase of the polarized light,

wherein the natural light is entered from a lower surface of the light guide plate, and at this time the natural light is entered to the liquid crystal panel via a portion between the concave patterns of the light guide plate so that the transparent display device is maintained at a transparent state regardless of whether or not being displayed by the natural light and an object located at a lower portion of the light guide plate is allowed to be viewed by the user at the front side,

wherein intervals D1 and D2 between the concave patterns formed in a second region P2 of the plurality of concave

13

patterns located away from the light source on the basis of a central portion of the lower surface of the light guide plate are formed narrower than the intervals D1 and D2 between the concave patterns formed in a first region P1 thereof located adjacent to the light source, and wherein the plurality of concave patterns have an oval-shaped structure, and the concave patterns formed in the first region (P1) of the plurality of concave patterns which is located near to the light source on the basis of a central portion of the light guide plate is 100-150 μm in horizontal length (L1) and 50-150 μm in vertical length (L2), and the concave patterns formed in the second region (P2) which is located away from the light source 10 on the basis of a central portion of the light guide plate is 100-200 μm in horizontal length (L1) and 50-150 μm in vertical length (L2).

2. The transparent display device of claim 1, wherein the light source is any one of a lamp, a light-emitting diode array, an indoor light, and natural light.

3. The transparent display device of claim 1, wherein the light entered in a lateral direction of the light guide plate is used to make a display, and the natural light entered from a lower direction of the light guide plate is used in a transparent state.

4. The transparent display device of claim 1, wherein the plurality of concave patterns are formed by laser irradiation.

14

5. The transparent display device of claim 1, wherein a size of the concave patterns formed in a second region of the plurality of concave patterns located away from the light source on the basis of a central portion of the lower surface of the light guide plate is formed smaller than that of the concave patterns formed in a first region thereof located adjacent to the light source.

6. The transparent display device of claim 5, wherein the concave patterns formed in the first region are 50-350 μm in horizontal length and 50-300 μm in vertical length, and the concave patterns formed in the second region are 100-200 μm in horizontal length and 50-150 μm in vertical length.

7. The transparent display device of claim 1, wherein the interval (D1) between the left and right concave patterns adjacent to each other in a horizontal direction (X-direction) of the plurality of concave patterns is 50-350 μm , and the interval (D2) between the upper and lower concave patterns adjacent to each other in a vertical direction (Y-direction) is 50-350 μm .

8. The transparent display device of claim 1, wherein a light incident surface of the light guide plate is formed with an inclined structure.

9. The transparent display device of claim 8, wherein an inclined angle of the light incident surface of the light guide plate is between 35 and 55 degrees.

* * * * *

专利名称(译)	透明显示装置包括导光板，导光板在其下表面处形成有多个凹形图案		
公开(公告)号	US8836889	公开(公告)日	2014-09-16
申请号	US12/836352	申请日	2010-07-14
[标]申请(专利权)人(译)	PARK SE HONG 朴钟SIN		
申请(专利权)人(译)	PARK SE-HONG 朴钟-SIN		
当前申请(专利权)人(译)	LG DISPLAY CO. , LTD.		
[标]发明人	PARK SE HONG PARK JONG SIN		
发明人	PARK, SE-HONG PARK, JONG-SIN		
IPC分类号	G02F1/1335 G02F1/1333 F21V9/14 F21V7/04 F21V8/00		
CPC分类号	G02B6/0056 G02F1/133615 G02B6/0036 G02B6/0023 G02B6/0046		
优先权	1020090064664 2009-07-15 KR		
其他公开文献	US20110013123A1		
外部链接	Espacenet USPTO		

摘要(译)

本发明公开了一种透明显示装置，其包括导光板，该导光板在其下表面处形成有多个凹形图案，以全反射在横向方向上进入的偏振光，同时透射从下方进入的自然光;光源设置在导光板的横向方向上，以发射包括第一和第二偏振光的可见光;第一偏振板，设置在导光板的侧部，以通过导光板传输第一和第二偏振光中的任何一个;液晶面板，用于驱动液晶以改变偏振光的相位;和第二偏振板，用于根据偏振光的变化相位控制偏振光的量。

