



US007502085B2

(12) **United States Patent**
Hirai

(10) **Patent No.:** **US 7,502,085 B2**
(45) **Date of Patent:** **Mar. 10, 2009**

(54) **DISPLAY DEVICE HAVING FUNCTIONAL
TRANSPARENT PLATE IN PRISMATIC
STRUCTURE ON RETARDER PROVIDED ON
POLARIZER ABOVE DISPLAY PANEL
ASSEMBLY**

(75) Inventor: **Akira Hirai**, Seongnam-si (KR)

(73) Assignee: **Samsung Electronics Co., Ltd.** (KR)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 424 days.

(21) Appl. No.: **11/404,232**

(22) Filed: **Apr. 14, 2006**

(65) **Prior Publication Data**

US 2006/0238679 A1 Oct. 26, 2006

(30) **Foreign Application Priority Data**

Apr. 26, 2005 (KR) 10-2005-0034414
Apr. 26, 2005 (KR) 10-2005-0034416

(51) **Int. Cl.**
G02F 1/1335 (2006.01)

(52) **U.S. Cl.** 349/117; 349/96; 349/9

(58) **Field of Classification Search** 349/117,
349/96, 9, 114, 113
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,712,694 A * 1/1998 Taira et al. 349/9
6,166,787 A * 12/2000 Akins et al. 349/57
6,707,519 B1 3/2004 Okumura et al.
6,847,425 B2 1/2005 Tanada et al.
6,989,875 B2 * 1/2006 Yoon 349/96
2005/0041180 A1 2/2005 Ozawa

FOREIGN PATENT DOCUMENTS

JP	07-043506	2/1995
JP	09-189811	7/1997
JP	2000-098364	4/2000
JP	2000-113705	4/2000
JP	2000-113707	4/2000
JP	2001-083509	3/2001
JP	2001-228333	8/2001
JP	2001-337207	12/2001
JP	2001-356344	12/2001
JP	2002-006134	1/2002
JP	2002-014336	1/2002
JP	2002-072196	3/2002
JP	2002072196 A *	3/2002
JP	2002-202506	7/2002
JP	2003-177236	6/2003
JP	2004-125885	4/2004
JP	2004-177591	6/2004
KR	1020040015307	2/2004
KR	1020040020798	3/2004
KR	1020040055932	6/2004
KR	1020040084205	10/2004
KR	1020050014594	2/2005

* cited by examiner

Primary Examiner—Mike Qi

(74) *Attorney, Agent, or Firm*—Cantor Colburn LLP

(57) **ABSTRACT**

An optical system consisting of a reflective polarizer, a $\lambda/4$ retarder, and a functional transparent plate with first facets and second facets which is provided on a display panel assembly improves utilization efficiency of exterior light, so that display luminance of a reflective or a transmissive LCD operating in a reflection mode is improved. In another embodiment, an optical system consisting of a $\lambda/4$ retarder, a selective reflection layer, and a functional transparent plate with first facets and second facets may be used.

68 Claims, 21 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3





FIG. 4

FIG. 5




FIG. 6





FIG. 7*FIG. 8**FIG. 9*



FIG. 10*FIG. 11**FIG. 12*


FIG. 13

FIG. 14




FIG. 15




FIG. 17





FIG. 18

FIG. 19




FIG. 20








FIG. 21*FIG. 22**FIG. 23**FIG. 24*


FIG. 25*FIG. 26**FIG. 27*




FIG. 28*FIG. 29**FIG. 30*



FIG. 31

FIG. 32



1

**DISPLAY DEVICE HAVING FUNCTIONAL
TRANSPARENT PLATE IN PRISMATIC
STRUCTURE ON RETARDER PROVIDED ON
POLARIZER ABOVE DISPLAY PANEL
ASSEMBLY**

BACKGROUND OF THE INVENTION

(a) Field of the Invention

The present invention relates to a transfective liquid crystal display or a reflective liquid crystal display.

(b) Description of the Related Art

Generally, a liquid crystal display (LCD) includes a pair of panels individually having electrodes on their inner surfaces, and a dielectric anisotropy liquid crystal (LC) layer interposed between the panels. In an LCD, a variation of a voltage difference between the field generating electrodes, i.e., a variation in the strength of an electric field generated by the electrodes, changes the transmittance of light passing through the LCD, and thus desired images are obtained by controlling the voltage difference between the electrodes.

Depending on the kinds of light source used for image display, LCDs are divided into three types: transmissive, reflective, and transfective. In transmissive LCDs, pixels are illuminated from behind using a backlight. In reflective LCDs, the pixels are illuminated from the front using incident light originating from the ambient environment. The transfective LCDs combine transmissive and reflective characteristics. Under medium light conditions such as in an indoor environment, or under complete darkness conditions, these LCDs are operated in a transmissive mode, while under very bright conditions such as in an outdoor environment, they are operated in a reflective mode.

In the reflective LCDs and the transfective LCDs, two absorbing polarizers, which are films produced by adding iodine molecules or bichromatic dyes to stretched PVA, are individually attached to the outer surfaces of the panels. In general, the absorbing polarizers have unique optical characteristics. That is, they allow only P-waves of incident light to pass and absorb S-waves. Theoretically, an absorbing polarizer transmits 50% of incident light and absorbs the remaining 50%. However, the absorbing polarizer actually transmits only 43% to 45% due to a light loss at its surface. In the case when the light passing through the absorbing polarizer is returned to the same polarizer again by reflection at a reflective electrode, the transmittance of the light passing through the polarizer again is only 39% to 41%, even if the reflectance at the reflective electrode is 100% and the color filters cause no light loss. Accordingly, the actual transmittance is less than 39% to 41% because the color filters used for the color display cause a light loss and also because the actual reflectance at the reflective electrode is not 100%.

SUMMARY OF THE INVENTION

An objective of the present invention is to improve visibility and display luminance of an LCD operating in reflective mode.

To achieve the objective, a reflective LCD or an transmissive LCD of the present invention utilizes an optical system consisting of a reflective polarizer, a $\lambda/4$ retarder, and a functional transparent plate with first facets and second facets, which are disposed on a display panel assembly in that order. Otherwise, another optical system may be utilized, which consists of a $\lambda/4$ retarder, a selective reflection layer, and a

2

functional transparent plate with first facets and second facets, which are disposed on a display panel assembly in that order.

In detail, according to an aspect of the present invention, there is provided a display device including: a display panel assembly; a reflective polarizer that is provided above the display panel assembly to transmit external incident light which is linearly polarized in a first direction and to reflect external incident light which is linearly polarized in a second direction perpendicular to the first direction; a first $\lambda/4$ retarder that is provided on the reflective polarizer; and a functional transparent plate that is provided on the first $\lambda/4$ retarder and which has a top surface including portions without a cholesteric liquid crystal material and portions with a cholesteric liquid crystal material.

The display device may further include a second $\lambda/4$ retarder that is provided between the reflective polarizer and the display panel assembly, a first absorbing polarizer that is provided between the second $\lambda/4$ retarder and the reflective polarizer, a second absorbing polarizer that is provided under the display panel assembly, and a third $\lambda/4$ retarder that is provided between the second absorbing polarizer and the display panel assembly.

The reflective polarizer may utilize a dual brightness enhancement film (DBEF) that is produced based on reflectance anisotropy caused by refractive index anisotropy, or delicate linear patterns.

The display device may further include a backlight unit that is provided under the display panel assembly.

In this device, the display panel assembly, the reflective polarizer, the first $\lambda/4$ retarder, and the functional transparent plate may be bonded by an adhesive agent.

Between the functional transparent plate and the first $\lambda/4$ retarder, spaces may be formed due to a surface structure of either of a bottom surface of the functional transparent plate or a top surface of the first $\lambda/4$ retarder, and these spaces may be filled with a filling material with a refractive index that is equal to an average of refractive indices of the functional transparent plate and the first $\lambda/4$ retarder. As the filling material for the spaces, an organic silicon-based material such as silicon resin may be used.

The display panel assembly includes an LC layer. LC molecules in the LC layer may be aligned in a 90°-twisted nematic (TN) mode, a vertical alignment (VA) mode, an electrically controlled birefringence (ECB) mode, or an in-plane switching (IPS) mode.

The top surface of the functional transparent plate may have a plurality of prisms consisting of first facets, on which a cholesteric liquid crystal layer does not exist, and second facets, on which a cholesteric liquid crystal exists. In this case, the first facets without the cholesteric liquid crystal material and the second facets with the cholesteric liquid crystal material are formed at the top surface of the functional transparent plate and may reflect light once, respectively. As a result, the reflected light is returned toward the first $\lambda/4$ retarder again.

The functional transparent plate may have a top and a bottom surface with an embossed carving or a depressed carving pattern. At this time, apexes formed in the patterns of the two surfaces may be formed to deviate from one another.

According to another aspect of the present invention, there is provided a display device including: a display panel assembly; a first $\lambda/4$ retarder that is provided on the display panel assembly; a reflective polarizer that is provided above the first $\lambda/4$ retarder to transmit incident light which is linearly polarized in a first direction and to reflect incident light which is linearly polarized in a second direction perpendicular to the

first direction; a second $\lambda/4$ retarder that is provided on the reflective polarizer; a functional transparent plate that is provided on the second $\lambda/4$ retarder and which has a top surface with first facets and second facets where the second facets transmit only a component of incident light which is polarized in a specific direction and reflect the remaining components; a third $\lambda/4$ retarder that is provided under the display panel assembly; and a lower polarizer that is provided under the third $\lambda/4$ retarder.

The second facets that are formed at the top surface of the functional transparent plate may have a cholesteric liquid crystal layer thereon.

The display device may further include an upper polarizer that is provided between the first $\lambda/4$ retarder and the reflective polarizer.

The reflective polarizer may be a polarizer utilizing a dual brightness enhancement film (DBEF) that is produced based on reflectance anisotropy caused by refractive index anisotropy, or delicate linear patterns.

The display device may further include a backlight unit that is provided under the lower polarizer.

In this device, the functional transparent plate, the second $\lambda/4$ retarder, the reflective polarizer, the first $\lambda/4$ retarder, the display panel assembly, the third $\lambda/4$ retarder, and the lower polarizer may be bonded by an adhesive agent.

Spaces may be formed between the functional transparent plate and the second $\lambda/4$ retarder, due to a surface structure of either of a bottom surface of the functional transparent plate or a top surface of the second $\lambda/4$ retarder, and the spaces may be filled with a filling material with a refractive index that is equal to an average of refractive indices of the functional transparent plate and the second $\lambda/4$ retarder. As the filling material for the spaces, an organic silicon-based material such as silicon resin may be used.

The second facets which are formed at the top surface of the functional transparent plate may only transmit either of a right-handed circularly polarized component or a left-handed circularly polarized component of incident light, while reflecting the remaining components.

The top surface of the functional transparent plate may have a prismatic structure including the first facets, on which a cholesteric liquid crystal layer does not exist, and the second facets, on which a cholesteric liquid crystal exists. In this case, the first facet and the second facet may reflect light which is incident from the second $\lambda/4$ retarder once, respectively. As a result, the reflected light is returned toward the second $\lambda/4$ retarder again.

The functional transparent plate may have a top surface and a bottom surface with an embossed carving or a depressed carving pattern. In this structure, apexes formed in the patterns of the two surfaces may be formed to deviate from one another.

According to still another embodiment of the present invention, there is provided a display device including: a display panel assembly; a first $\lambda/4$ retarder that is provided on the display panel assembly; a reflective polarizer that is provided above the first $\lambda/4$ retarder to transmit incident light which is linearly polarized in a first direction and to reflect incident light which is linearly polarized in a second direction perpendicular to the first direction; a second $\lambda/4$ retarder that is provided on the reflective polarizer; and a functional transparent plate that is provided on the second $\lambda/4$ retarder and which has a top surface with first facets and second facets where the second facets transmit only a component of incident light which is polarized in a specific direction and reflect the remaining components.

The second facets which are formed at the top surface of the functional transparent plate may have a cholesteric liquid crystal layer thereon. In addition, the second facets which are formed at the top surface of the functional transparent plate may only transmit either of a right-handed circularly polarized component or a left-handed circularly polarized component of incident light, while reflecting the remaining components.

The top surface of the functional transparent plate may have a prismatic structure including the first facets, on which a cholesteric liquid crystal layer does not exist, and the second facets, on which a cholesteric liquid crystal exists.

The functional transparent plate may have a top surface and a bottom surface with an embossed carving or a depressed carving pattern. In this case, apexes formed in the patterns of the two surfaces may be formed to deviate from one another.

The first facets and the second facets which are formed at the top surface of the functional transparent plate may reflect light which is incident from the second $\lambda/4$ retarder once, respectively. As a result, the reflected light is returned toward the second $\lambda/4$ retarder again.

Between the functional transparent plate and the second $\lambda/4$ retarder, spaces may be formed due to a surface structure of either of a bottom surface of the functional transparent plate or a top surface of the second $\lambda/4$ retarder. In this case, the spaces may be filled with a filling material with a refractive index that is equal to an average of refractive indices of the functional transparent plate and the second $\lambda/4$ retarder. As the filling material for the spaces, an organic silicon-based material, such as silicon resin or the like, may be used.

According to still another embodiment of the present invention, there is provided a display device including: a display panel assembly; a selective reflection layer that is provided above the display panel assembly to transmit a component of incident exterior light which is circularly polarized in a first direction and to reflect a component of incident exterior light which is circularly polarized in a second direction perpendicular to the first direction; and a functional transparent plate that is provided on the selective reflection layer and which has a top surface including portions without a cholesteric liquid crystal material and portions with a cholesteric liquid crystal material.

The display device may further include a first polarizer that is provided between the selective reflection layer and the display panel assembly, a first $\lambda/4$ retarder that is provided between the first polarizer and the display panel assembly, a second $\lambda/4$ retarder that is provided between the selective reflection layer and the first polarizer, a second polarizer that is provided under the display panel assembly, a third $\lambda/4$ retarder that is provided between the second polarizer and the display panel assembly, and a backlight unit that is provided under the display panel assembly.

In this structure, the selective reflection layer may be formed of a cholesteric liquid crystal material.

In this device, the display panel, the selective reflection layer, and the functional transparent plate may be bonded using an adhesive agent.

Spaces may be formed between the functional transparent plate and the selective reflection layer, due to a surface structure of either of a bottom surface of the functional transparent plate or a top surface of the selective reflection layer, and the spaces may be filled with a filling material with a refractive index that is equal to an average of refractive indices of the functional transparent plate and the selective reflection layer. As the filling material for the spaces, an organic silicon-based material such as silicon resin may be used.

The display panel assembly includes an LC layer. LC molecules in the LC layer may be aligned in a 90°-twisted nematic (TN) mode, a vertical alignment (VA) mode, an electrically controlled birefringence (ECB) mode, or an in-plane switching (IPS) mode.

The top surface of the functional transparent plate may have a plurality of prisms consisting of first facets, on which a cholesteric liquid crystal layer does not exist, and second facets, on which a cholesteric liquid crystal exists. In this structure, the first facets and the second facets formed at the top surface of the functional transparent plate may reflect light which is incident from the selective reflection layer once, respectively. As a result, the reflected light is returned toward the selective reflection layer again.

The functional transparent plate may have a top surface and a bottom surface with an embossed carving or a depressed carving pattern. In this case, apexes formed in the patterns of the two surfaces may be formed to deviate from one another.

According to still another embodiment of the present invention, there is provided a display device including: a display panel assembly; a first $\lambda/4$ retarder that is provided on the display panel assembly; a first polarizer that is provided on the first $\lambda/4$ retarder where the first polarizer transmits external incident light which is linearly polarized in a first direction and that reflects external incident light which is linearly polarized in a second direction perpendicular to the first direction; a second $\lambda/4$ retarder that is provided on the first polarizer; a selective reflection layer that is provided on the second $\lambda/4$ retarder to transmit a component of incident light which is circularly polarized in a third direction and to reflect a component of incident light which is circularly polarized in a fourth direction that is perpendicular to the third direction; a functional transparent plate that is provided on the selective reflection layer and which has a top surface with first facets and second facets where the second facets transmit only a component of incident light which is polarized in a specific direction and reflect the remaining components; a third $\lambda/4$ retarder that is provided under the display panel assembly; and a second polarizer that is provided under the third $\lambda/4$ retarder.

In this structure, the second facets which are formed at the top surface of the functional transparent plate may have a cholesteric liquid crystal layer thereon, and the selective reflection layer may be formed of a cholesteric liquid crystal material.

The display device may further include a backlight unit that is provided under the second polarizer.

In this device, the functional transparent plate, the selective reflection layer, the second $\lambda/4$ retarder, the first polarizer, the first $\lambda/4$ retarder, the display panel assembly, the third $\lambda/4$ retarder, and the second polarizer may be bonded by an adhesive agent.

Between the functional transparent plate and the selective reflection layer, spaces may be formed due to a surface structure of either of a bottom surface of the functional transparent plate or a top surface of the selective reflection layer. These spaces may be filled with a filling material with a refractive index that is equal to an average of refractive indices of the functional transparent plate and the selective reflection layer. As the filling material for the spaces, an organic silicon-based material such as silicon resin may be used.

The second facets which are formed at the top surface of the functional transparent plate may only transmit either of a right-handed circularly polarized component or a left-handed circularly polarized component of incident light, while reflecting the remaining components.

The top surface of the functional transparent plate may have a prismatic structure including the first facets, on which a cholesteric liquid crystal layer does not exist, and the second facets, on which the cholesteric liquid crystal exists. In this case, the first facets and the second facets which are formed at the top surface of the functional transparent plate may reflect light which is incident from the selective reflection layer once, respectively. As a result, the reflected light is returned toward the selective reflection layer again.

The functional transparent plate may have a top surface and a bottom surface with an embossed carving or a depressed carving pattern. In this case, apexes formed in the patterns of the two surfaces may be formed to deviate from one another.

According to still another embodiment of the present invention, there is provided a display device including: a display panel assembly; a first $\lambda/4$ retarder that is provided on the display panel assembly; a first polarizer that is provided on the first $\lambda/4$ retarder where the first polarizer transmits light which is linearly polarized in a first direction and reflects light which is linearly polarized in a second direction perpendicular to the first direction; a second $\lambda/4$ retarder that is provided on the first polarizer; a selective reflection layer that is provided on the second $\lambda/4$ retarder to transmit light which is circularly polarized in a third direction and to reflect light which is circularly polarized in a fourth direction that is opposite to the third direction; and a functional transparent plate that is provided on the selective reflection layer and which has a top surface with first facets and second facets where the second facets transmit only light which is polarized in a specific direction and reflect the remaining light.

The second facets which are formed at the top surface of the functional transparent plate may have a cholesteric liquid crystal layer thereon, and may only transmit either of a right-handed circularly polarized component or a left-handed circularly polarized component of incident light and reflect the remaining components.

The top surface of the functional transparent plate may have a prismatic structure including the first facets, on which a cholesteric liquid crystal layer does not exist, and the second facets, on which a cholesteric liquid crystal exists. In this case, the first facets and the second facets which are formed at the top surface of the functional transparent plate may reflect light which is incident from the selective reflection layer once, respectively. As a result, the reflected light is returned toward the selective reflection layer again.

The functional transparent plate may have a top surface and a bottom surface with an embossed carving or a depressed carving pattern. In this case, apexes of the patterns of the two surfaces may be formed to deviate from one another.

Spaces may be formed between the functional transparent plate and the selective reflection layer, due to a surface structure of either of a bottom surface of the functional transparent plate or a top surface of the selective reflection layer. These spaces may be filled with a filling material with a refractive index that is equal to an average of refractive indices of the functional transparent plate and the selective reflection layer. As the filling material for the spaces, an organic silicon-based material such as silicon resin may be used.

BRIEF DESCRIPTION OF THE DRAWINGS

The above objects and other advantages of the present invention will become more apparent by describing the preferred embodiments thereof in more detail with reference to the accompanying drawings.

FIG. 1 is a layout view of an LCD according to an embodiment of the present invention.

FIG. 2 is a schematic cross-sectional view cut along II-II' of FIG. 1.

FIG. 3 is a schematic cross-sectional view cut along III-III' of FIG. 1.

FIG. 4 shows a vertical scheme of the LCD according to an embodiment of the present invention.

FIG. 5 shows variations of the polarization state of light at an upper portion of an LCD according to an embodiment of the present invention.

FIG. 6 is a view for comparing the polarization states of light when an LCD operates in a reflection mode utilizing exterior light and in a transmission mode utilizing internal light.

FIG. 7 through FIG. 12 are schematic cross-sectional views showing process steps to manufacture a functional transparent plate of an LCD according to an embodiment of the present invention.

FIG. 13 is a schematic cross-sectional view of a functional transparent plate of an LCD according to another embodiment of the present invention.

FIG. 14 is a cross-sectional view showing variations of the polarization state of light in a reflective LCD according to still another embodiment of the present invention.

FIG. 15 is a layout view of an LCD according to still another embodiment of the present invention.

FIG. 16 is a schematic cross-sectional view cut along XVI-XVI' of FIG. 15.

FIG. 17 is a schematic cross-sectional view cut along XVII-XVII' of FIG. 15.

FIG. 18 shows a vertical scheme of an LCD according to still another embodiment of the present invention.

FIG. 19 shows variations of the polarization state of light at an upper part of an LCD according to still another embodiment of the present invention.

FIG. 20 is a view for comparing the polarization states of light when an LCD operates in a reflection mode utilizing exterior light and in a transmission mode utilizing internal light from a backlight unit.

FIG. 21 through FIG. 24 are schematic cross-sectional views showing process steps to manufacture a selective reflection layer of an LCD according to still another embodiment of the present invention.

FIG. 25 through FIG. 30 are schematic cross-sectional views showing process steps to manufacture a functional transparent plate of an LCD according to still another embodiment of the present invention.

FIG. 31 is a schematic cross-sectional view of a functional transparent plate of an LCD according to still another embodiment of the present invention.

FIG. 32 is a cross-sectional view showing variations of the polarization state of light in a reflective LCD according to still another embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. The present invention may, however, be embodied in different forms and should not be construed as being limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art.

In the drawings, the thickness of the layers, films, and regions are exaggerated for clarity. Like numerals refer to like

elements throughout. It will be understood that when an element such as a layer, film, region, or substrate is referred to as being "on" another element, it can be directly on the other element or intervening elements may also be present.

Hereinafter, an LCD according to a preferred embodiment of the present invention will be described in detail with reference to FIG. 1 through FIG. 3.

FIG. 1 is a layout view of an LCD according to an embodiment of the present invention, and FIG. 2 and FIG. 3 are schematic cross-sectional views cut along II-II' and III-III' of FIG. 1, respectively.

Referring to FIG. 1 to FIG. 3, the LCD of this embodiment includes a TFT array panel **100** and a common electrode panel **200** facing each other, and an LC layer **3** that is interposed therebetween with LC molecules that are aligned perpendicular or parallel to the surfaces of the two panels **100** and **200**.

LC molecules in the LC layer **3** are aligned in a 90°-twisted nematic (TN) mode, a vertical alignment (VA) mode, or an electrically controlled birefringence (ECB) mode.

The TFT array panel **100** is configured as follows.

A plurality of gate lines **121** and a plurality of storage electrode lines **131** are formed on an insulating substrate **110** made of transparent glass or plastic.

The gate lines **121** for transmitting gate signals extend substantially in a horizontal direction, while being separated from each other. Each gate line **121** includes a plurality of gate electrodes **124** protruding upward and an end portion **125** having a relatively large dimension to be connected to an external device.

The storage electrode lines **131** extend substantially in a horizontal direction and are substantially parallel to the gate lines **121**. Each storage electrode line **131** includes a plurality of storage electrodes **133** protruding upward and downward. The storage electrode lines **131** receive a predetermined voltage, such as a common voltage that is applied to a common electrode **270** of the common electrode panel **200**.

The gate lines **121** and the storage electrode lines **131** are preferably made of an aluminum (Al) containing metal such as Al and an Al alloy, a silver-(Ag) containing metal such as Ag and a Ag alloy, a copper-(Cu) containing metal such as Cu and a Cu alloy, a molybdenum-(Mo) containing metal such as Mo and a Mo alloy, chrome (Cr), titanium (Ti), or tantalum (Ta). The gate lines **121** and the storage electrode lines **131** may be configured as a multi-layered structure, in which at least two conductive layers (not shown) having different physical properties are included. In such a structure, an upper layer of the two is made of a low resistivity metal, such as an Al-containing metal, an Ag-containing metal, a Cu-containing metal, or the like, in order to reduce delay of the signals or a voltage drop in the gate lines **121** and the storage electrode lines **131**, and a lower layer is made of material having prominent physical, chemical, and electrical contact properties with other materials such as indium tin oxide (ITO), indium zinc oxide (IZO), etc. For example, a Mo-containing metal, Cr, Ta, or Ti, etc., may be used for the formation of the same layer. A desirable example of the combination of the two layers is a lower Cr layer and an upper Al—Nd layer. However, the gate lines **121** and the storage electrode lines **131** may be configured as single-layered structures.

All lateral sides of the gate lines **121** and the storage electrode lines **131** preferably slope in a range from about 20° to 80° to the surface of the substrate **110**.

A gate insulating layer **140** made of silicon nitride (SiN_x) or silicon oxide (SiO₂) is formed on the gate lines **121** and the storage electrode lines **131**.

A plurality of linear semiconductors **151** made of hydrogenated amorphous silicon (abbreviated as "a-Si") or poly-

silicon are formed on the gate insulating layer **140**. Each linear semiconductor **151** extends substantially in a vertical direction and includes a plurality of projections **154** that extend along the respective gate electrodes **124** and a plurality of extensions **157** that extend from the respective projections **154**. The linear semiconductors **151** are enlarged in the vicinities of the gate lines **121** and the storage electrode lines **131** to cover them entirely.

A plurality of linear ohmic contacts **161** and island-shaped ohmic contacts **165** are formed on the linear semiconductors **151**. The ohmic contacts **161** and **165** may be made of N⁺ hydrogenated amorphous silicon that is highly doped with N-type impurities, or silicide. The linear ohmic contacts **161** include a plurality of projections **163**. A set of a projection **163** and an island-shaped ohmic contact **165** is placed on the projection **154** of the semiconductor **151**.

All lateral sides of the semiconductors **151** and the ohmic contacts **161** and **165** slope in the range from about 20° to 80° to the surface of the substrate **110**.

A plurality of data lines **171** and a plurality of drain electrodes **175**, separated from the data lines **171**, are formed on the ohmic contacts **161** and **165** and the gate insulating layer **140**.

The data lines **171** for transmitting data signals extend substantially in a vertical direction to be crossed with the gate lines **121** and the storage electrode lines **131**. Each data line **171** includes an end portion **179** having a relatively large dimension to be connected to a different layer or an external device.

Each drain electrode **175** includes an expansion **177** that is overlapped with one of the storage electrodes **133**. Each data line **171** further includes a plurality of source electrodes **173** protruding along and extending toward the respective gate electrodes **124**. Each source electrode **173** surrounds a partial portion of a bar-shaped end portion of the drain electrode **175**.

A gate electrode **124**, a source electrode **173**, a drain electrode **175**, and a projection **154** of the semiconductor **151** form a thin film transistor (TFT). A TFT channel is formed in the projection **154** provided between the source electrode **173** and the drain electrode **175**.

The data lines **171** and the drain electrodes **175** are preferably made of a refractory metal, such as a Mo-containing metal, a Cr-containing metal, Ta, Ti, or the like, and may be configured as multi-layered structures including a lower layer (not shown) consisting of one among Mo, a Mo alloy, Cr, etc., and an upper layer (not shown) consisting of an Al-containing metal.

Similarly to the gate lines **121** and the storage electrode lines **131**, all lateral sides of the data lines **171** and the drain electrodes **175** slope in the range from about 20° to 80° to the surface of the substrate **110**.

The ohmic contacts **161** and **165** exist only between the underlying semiconductors **151** and the overlying data lines **171** and between the overlying drain electrodes **175** and the underlying semiconductors **151**, in order to reduce contact resistance therebetween. The linear semiconductors **151** are partially exposed at places where the data lines **171** and the drain electrodes **175** do not cover them, as well as between the source electrodes **173** and the drain electrodes **175**.

A passivation layer **180**, made of an inorganic material such as SiN_x or SiO₂, is formed on the data lines **171**, the drain electrodes **175**, and the exposed portions of the semiconductors **151**.

An organic insulating layer **187**, made of a photosensitive organic insulator having a prominent planarization property, is formed on the passivation layer **180**. A top surface of the organic insulating layer **187** is uneven. Due to the uneven

surface, reflective electrodes **194** overlying the organic insulating layer **187** have uneven top surfaces. The uneven top surfaces of the reflective electrodes **194** prevent mirror reflection. Accordingly, images that may be shown on an LCD screen due to the mirror reflection are eliminated. The organic insulating layer **187** is removed at the end portions **125** and **179** of the gate lines **121** and the data lines **171**, so only the passivation layer **180** remains on the end portions **125** and **179**.

The passivation layer **180** is provided with a plurality of contact holes **183**, through which the end portions **179** of the data lines **171** are exposed. A plurality of contact holes **182** are formed in the passivation layer **180** and the gate insulating layer **140**, and the end portions **125** of the gate lines **121** are exposed therethrough. A plurality of contact holes **185** are formed in the passivation layer **180** and the organic insulating layer **187**, and the expansions **177** of the drain electrodes **175** are exposed therethrough. The contact holes **182**, **183**, and **185** may have polygonal or circular shapes. The sidewalls of the contact holes **182**, **183**, and **185** slope in the range from about 30° to 85° to the surface of the substrate **110** or are shaped as steps.

A plurality of pixel electrodes **190** are formed on the organic insulating layer **187**.

Each pixel electrode **190** includes a transparent electrode **192** and a reflective electrode **194** overlying the transparent electrode **192**. The transparent electrodes **192** are made of a transparent conductive material such as ITO or IZO, and the reflective electrodes **194** are made of a reflective opaque material such as Al, an Al alloy, Ag, or an Ag alloy. Each pixel electrode **190** may further include a contact assistant (not shown) made of Mo, a Mo alloy, Cr, Ti, or Ta. The contact assistants ensure contact properties between the transparent electrodes **192** and the reflective electrodes **194**, while preventing the transparent electrodes **192** from oxidizing the reflective electrodes **194**.

Each pixel is divided into a transmission area TA without the reflective electrode **194** and a reflection area RA with the reflective electrode **194**. The organic insulating layer **187** is removed from the transmission area TA, so that a transmission window **195** is formed there. Due to the transmission window **195**, a cell gap of the transmission area TA becomes nearly twice as large as that of the reflection area RA, so that a light path difference between the transmission area TA and the reflection area RA is compensated.

The pixel electrodes **190** are physically and electrically connected to the expansions **177** of the drain electrodes **175** through the contact holes **185** to receive data voltages from the drain electrodes **175**. The pixel electrodes **190** are supplied with the data voltages to generate electric fields in cooperation with the common electrode **270** of the common electrode panel **200**, determining the molecular orientation of the LC layer **3** interposed between the two electrodes.

Each set of the pixel electrode **190** and the common electrode **270** forms an LC capacitor that is capable of storing the applied voltage after the TFT is turned off. To enhance the voltage storage ability of the LC capacitors, storage capacitors, connected to the LC capacitors in parallel, are further provided. Overlapping of the expansions **177** of the drain electrodes **175** with the storage electrodes **133** implements the storage capacitors. Otherwise, overlapping of the pixel electrodes **190** with the gate lines **121** adjacent thereto may implement the storage capacitors. In this case, the storage electrode lines **131** may be omitted.

The pixel electrodes **190** may be overlapped with the data lines **171** adjacent thereto as well as the gate lines **121** adja-

cent thereto, in order to increase the aperture ratio, but such overlap portions are not always necessary.

The pixel electrodes **190** may be made of a transparent conductive polymer. However, opaque reflective metals may be used in reflective LCDs.

A plurality of contact assistants **95** and **97** are formed on the passivation layer **180** relating to a pad portion, and are individually connected to the end portions **125** of the gate lines **121** and the end portions **179** of the data lines **171** through the contact holes **182** and **183**. The contact assistants **95** and **97** supplement adhesion between the end portions **125** and **179** and exterior devices, and protect them. The contact assistants **95** and **97** may be formed on the same layer as the transparent electrodes **192** or the reflective electrodes **194**. However, they may be omitted because they are not essential elements.

The common electrode panel **200** facing the TFT array panel **100** is configured as follows.

A light-blocking member **220** called a "black matrix" is provided on an insulating substrate **210** made of a transparent insulating material such as glass. The light-blocking member **220** prevents light from leaking out through barriers between the pixel electrodes **190** and delimits aperture regions facing the pixel electrodes **190**.

A plurality of color filters **230** are formed on the substrate **210** and the light-blocking member **220**, and most of them are placed within the aperture regions delimited by the light-blocking member **220**. Each color filter **230** is formed between the two adjacent data lines **171** in a vertical direction, and exhibits one among red, green, and blue colors. The color filters **230** are connected to one another in the form of stripes.

In the case of a typical transmissive LCD, in the transmission areas TA, light passes through the color filters **230** only once, while it passes twice in the reflection areas RA. Accordingly, a difference of color tone between the transmission areas TA and the reflection areas RA is generated. To reduce the difference of color tone between the two areas TA and RA, two methods can be used. The first method is to form the thickness of each color filter **230** differently depending on its location. That is, in this method, a specific portion of the color filter **230**, which is placed at the transmission area TA, is formed thicker than the remaining portion, which is placed at the reflection area RA. The second method is to form light holes in the reflection areas RA of the color filters **230**.

The common electrode **270**, made of a transparent conductive material such as ITO or IZO, is formed on the light-blocking member **220** and the color filters **230**.

The LC layer **3** is interposed between the two panels **100** and **200** facing each other.

A lower polarizer **12** and an upper polarizer **22** are individually attached to the outer surfaces of the two panels **100** and **200**. A transmission axis (θ) of the upper polarizer **22** and a transmission axis ($\theta+90^\circ$) of the lower polarizer **12** are mutually crossed at a right angle.

A lower $\lambda/4$ retarder **13** is interposed between the TFT array panel **100** and the lower polarizer **12**, and a first upper $\lambda/4$ retarder **14** is interposed between the common electrode panel **200** and the upper polarizer **22**.

A reflective polarizer **15** is disposed on the upper polarizer **22**, and a second upper $\lambda/4$ retarder **16** is disposed on the reflective polarizer **15**.

A functional transparent plate **17** is disposed on the second upper $\lambda/4$ retarder **16**. A top surface of the functional transparent plate **17** consists of a plurality of prisms. Each prism includes a first facet **17-1** on which no additional material exists and a second facet **17-2** on which a cholesteric LC layer exists.

Hereinafter, the structure of the above-mentioned LCD and the polarization principles of light in the same LCD will be described in detail.

FIG. 4 shows a vertical scheme of the LCD of an embodiment of the present invention.

A display panel assembly **300** of FIG. 4 comprises the TFT array panel **100** and the common electrode panel **200**, and the LC layer **3** interposed therebetween.

The lower $\lambda/4$ retarder **13** is attached to a lower surface of the display panel assembly **300**, and the lower polarizer **12** is attached to a lower surface of the lower $\lambda/4$ retarder **13**.

Meanwhile, the first upper $\lambda/4$ retarder **14** is attached to an upper surface of the display panel assembly **300**, and the upper polarizer **22** is attached to an upper surface of the first upper $\lambda/4$ retarder **14**. The reflective polarizer **15** is attached to an upper surface of the upper polarizer **22** and the second upper $\lambda/4$ retarder **16** is attached onto the reflective polarizer **15**. The functional transparent plate **17**, whose top surface consists of a plurality of combinations of the first facet **17-1** and second facet **17-2**, is formed on the second upper $\lambda/4$ retarder **16**.

A more detailed description for the above-discussed structure is given below.

The polarizers **12** and **22** are individually attached to the outer surfaces of the panels **100** and **200**. Their transmission axes are mutually crossed at a right angle. The two polarizers **12** and **22** are absorption-type polarizers that transmit linearly polarized incident light vibrating parallel to their transmission axes and absorb linearly polarized incident light vibrating perpendicular to their transmission axes.

The LCD of this embodiment utilizes three $\lambda/4$ retarders in total. Each of the three $\lambda/4$ retarders **13**, **14**, and **16** converts circularly polarized light into linearly polarized light or linearly polarized light into circularly polarized light by causing a phase difference of a quarter wavelength between two polarized components that are orthogonal to each other and are individually parallel to a fast axis and a slow axis thereof. Here, the circularly polarized light may be elliptically polarized light in actuality, but the elliptically polarized light will also be referred to as circularly polarized light for convenience.

The fast axes of the three $\lambda/4$ retarders **13**, **14**, and **16** are preferably formed at $\pm 45^\circ$ to the transmission axes (θ and $\theta+90^\circ$) of the polarizers **12** and **22** to maximize the phase difference between the two polarized components. However, they may be disposed at different angles, except being disposed perpendicular or parallel to each other.

The reflective polarizer **15** is disposed on the upper polarizer **22**. A transmission axis and a reflection axis of the reflective polarizer **15** are mutually perpendicular. Accordingly, the reflective polarizer **15** transmits linearly polarized incident light that vibrates parallel to the transmission axis, while reflects linearly polarized incident light that vibrates parallel to the reflection axis. The reflective polarizer **15** is formed of a dual brightness enhancement film (DBEF), as disclosed in U.S. Pat. No. 5,825,543, utilizing the reflectance anisotropy caused by the refractive index anisotropy. Otherwise, the reflective polarizer **15** may utilize delicate linear patterns disclosed by Japanese Patent Publication No. 1990-308166. The transmission axes of the reflective polarizer **15** and the upper polarizer **22** are disposed in the same direction.

The functional transparent plate **17** is made of a transparent material and has a prismatic top surface consisting of a plurality of first facets **17-1** and a plurality of second facets **17-2**, as shown in FIG. 4. No additional material exists on the first facets **17-1**, while the cholesteric LC layer exists on the second facets **17-2**. The second facets **17-2** transmit circularly

polarized incident light rotating in the same direction as an optical axis of the cholesteric LC layer, while reflecting circularly polarized incident light rotating in an opposite direction. A fabrication method of the first facets 17-1 and the second facets 17-2 will be described later.

The functional transparent plate 17, the second upper $\lambda/4$ retarder 16, the reflective polarizer 15, the upper polarizer 22, the first upper $\lambda/4$ retarder 14, the display panel assembly 300, the lower $\lambda/4$ retarder 13, and the lower polarizer 12 are bonded by an adhesive agent in that order.

FIG. 5 shows variations of the polarization state of light at an upper part of the LCD with the functional transparent plate 17, the second upper $\lambda/4$ retarder 16, the reflective polarizer 15, and the upper polarizer 22.

As shown in FIG. 5, light, which is incident onto the functional transparent plate 17, is classified into three light rays (A, B, and C) depending on incident position and incident angle.

First, incident light (A) of the three light rays is described.

The light (A), which is incident onto the second facets 17-2 of the functional transparent plate 17, is separated into two individual light rays (A-1) and (A-2) having different light paths from each other. That is, when the light (A) impacts the second facets 17-2 where the cholesteric LC layer is formed, only right-handed circularly polarized light (A-1) of the incident light (A), which rotates in the same direction as the optical axis of the cholesteric LC layer, passes through the functional transparent plate 17, while left-handed circularly polarized light (A-2), which rotates in the opposite direction, is reflected.

The light (A-1) passing through the transparent plate 17 then travels through the second upper $\lambda/4$ retarder 16. At this time, the light (A-1) is converted into light that is linearly polarized in the X direction. Next, the linearly polarized light (A-1) sequentially passes through the reflective polarizer 15 and the upper polarizer 22. In this structure, the transmission axis of the upper polarizer 22 is in the X-direction, while the reflection axis of the reflective polarizer 15 is in the Y-direction.

Meanwhile, the left-handed circularly polarized reflected light (A-2) passes through the first facets 17-1 and is then reflected again by an adjacent second facet 17-2. The polarization state of the light (A-2) is maintained with no change during these sequential processes. This is possible because the second facets 17-2 that are formed with the cholesteric LC do not cause any change in the polarization state of the light when reflecting it. Next, the left-handed circularly polarized light (A-2) enters the second upper $\lambda/4$ retarder 16. At this time, the second upper $\lambda/4$ retarder 16 converts the incident light (A-2) into linearly polarized light in the Y direction. Then, the linearly polarized light (A-2) is returned back by the reflective polarizer 15 because the reflection axis of the reflective polarizer 15 and the polarized direction of the light (A-2) are in the same direction. The light that is reflected by the reflective polarizer 15 is designated as (A-3) in FIG. 5.

Incident light (B) of FIG. 5 is described below.

The light (B), which is incident onto the first facets 17-1 of the functional transparent plate 17, passes through the functional transparent plate 17 and the second upper $\lambda/4$ retarder 16. Even after passing through the second upper $\lambda/4$ retarder 16, the light (B) includes all-directional components without a change. In other words, the second upper $\lambda/4$ retarder 16 transmits all components of the incident light (B). Next, the light (B) enters the reflective polarizer 15, which allows only those components of the light that are parallel to its transmission axis (i.e., the X direction) to pass and reflects the components perpendicular to the transmission axis. Accordingly,

the light (B) is divided into two separate light rays (B-1) and (B-2) by the reflective polarizer 15.

Meanwhile, light (C), which is perpendicularly incident to the second facets 17-2 of the functional transparent plate 17, is also divided into two separate light rays (C-1) and (C-2) having different light paths. That is, a right-handed circularly polarized component (C-1) of the incident light (C), which rotates in the same direction as the optical axis of the cholesteric LC layer, passes through the functional transparent plate 17 and then proceeds along the same light path as the light (A-1), while a left-handed circularly polarized component (C-2) of the incident light (C), which rotates in the opposite direction, exits the LCD by reflection at the second facets 17-2. Here, plane angles of the first facets 17-1 and the second facets 17-2 may be controlled so that the left-handed circularly polarized reflected light (C-2) is incident onto the first facets 17-1 again and then enters the second upper $\lambda/4$ retarder 16 after being reflected or refracted by the functional transparent plate 17.

In the meantime, the linearly polarized light rays (A-3) and (B-2), which are reflected by the reflective polarizer 15, enter the second upper $\lambda/4$ retarder 16 again. At this time, the second upper $\lambda/4$ retarder 16 converts the incident light (A-3) and (B-2) into left-handed circularly polarized light (D). The left-handed circularly polarized light (D) is divided into two light rays (D-1) and (D-2) depending on incident positions of the light (D). That is, the light (D-1) is incident onto the first facets 17-1 of the functional transparent plate 17, while the light D-2 is incident onto the second facets 17-2. The two light rays (D-1) and (D-2) are doubly reflected by the first facets 17-1 and the second facets 17-2, respectively. At this time, the light rays (D-1) and (D-2) undergo 180° phase changes with the reflection at the first facets 17-1, so that they are all converted into right-handed polarized light rays. Next, the right-handed polarized light rays (D-1) and (D-2) enter the second upper $\lambda/4$ retarder 16 again, and the second upper $\lambda/4$ retarder 16 transmits the incident light rays (D-1) and (D-2), converting them into linearly polarized light rays in the X direction, in a similar manner to the light (A-1).

As described above, the light, which is incident from the ambient environment through the first facets 17-1 and the second facets 17-2 of the functional transparent plate 17, does not exit the LCD after being reflected by the reflective polarizer 15 and is returned to the reflection polarizer 15 again by changing its polarization direction, so that display luminance of the LCD in a reflection mode is improved. To accomplish this effect, it is preferable to design the functional transparent plate 17 so that the first facets 17-1 and the second facets 17-2 thereof represent the largest possible refractive index difference, while having the largest possible dimensions. It is also preferable to form angles between the two facets 17-1 and 17-2 to be large and as far as possible. In the case that the difference between the refractive indices of the exterior air and the functional transparent plate 17 is large, no total reflection occurs when exterior light enters the functional transparent plate 17, but a total reflection occurs when the light is emitted from the functional transparent plate 17. Accordingly, utilization efficiency for the exterior light is improved.

FIG. 6 is a view for comparing the polarization states of light when the LCD operates in a reflection mode utilizing exterior light and in a transmission mode utilizing internal light.

In this embodiment, the LC layer 3 consists of twisted nematic LC molecules. The twisted nematic LC molecules have peculiar optical properties. In detail, they are aligned in a vertical direction when an electric field is applied, thereby causing no change in the polarization state of light passing

15

through the LC layer 3, but they are alighted in a horizontal direction when no electric field is applied, thereby changing the polarization state of light passing through the LC layer 3.

Hereinafter, variations of the polarization states of light when no electric field is applied to the LC layer 3 will be first described with reference to FIG. 6.

In FIG. 6, leftmost light (R1) is incident light from the ambient environment when no electric field is applied to the LC layer 3 in a reflection mode. The light (R1) successively passes through the reflective polarizer 15 and the upper polarizer 22 as linearly polarized light in the X direction. The linearly polarized light (R1) then enters the first upper $\lambda/4$ retarder 14. At this time, the first upper $\lambda/4$ retarder 14 converts the incident light into right-handed circularly polarized light. The right-handed circularly polarized light (R1) enters the LC layer 3 after passing through the upper insulating substrate 210 and the color filters 230. In this case, since the LC layer 3 is supplied with no electric field, the light is converted into linearly polarized light in the Y direction. The linearly polarized light (R1) rotates by 180° with the reflection at the reflective polarizer 15. However, the light (R1) maintains the polarization state without a change even after rotation. The reflected light (R1) is converted into right-handed circularly polarized light again when passing through the LC layer 3, and then enters the first upper $\lambda/4$ retarder 14 after passing through the color filters 230 and the upper insulating substrate 210. At this time, the first upper $\lambda/4$ retarder 14 converts the right-handed circularly polarized light (R1) into linearly polarized light in the X direction. Next, the linearly polarized light (R1) enters the second upper $\lambda/4$ retarder 16 after passing through the upper polarizer 22 and the reflective polarizer 15. At this time, the linearly polarized light (R1) is converted into right-handed circularly polarized light by the second upper $\lambda/4$ retarder 16 and then exits the LCD after passing through the functional transparent plate 17. At this time, the LCD screen is shown as a white state.

Meanwhile, light is supplied from an internal light source, i.e., a backlight unit 500. The light passes through the lower polarizer 12. In this step, only a linearly polarized component of the light (T) in the Y direction remains and the remaining components are removed by absorption. The linearly polarized component (T) is converted into left-handed circularly polarized light (T1, T2) by the lower $\lambda/4$ retarder 13. Light (T1) is light supplied from the internal light source when no electric field is applied to the LC layer 3 in a transmission mode. The left-handed circularly polarized light (T1) enters the LC layer 3 after passing through the lower insulating substrate 110, and is converted into right-handed circularly polarized light when passing through the LC layer 3. The right-handed circularly polarized light (T1) passes through the upper insulating substrate 210 and then enters the first upper $\lambda/4$ retarder 14. At this time, the light (T1) is converted into linearly polarized light in the X direction by the first upper $\lambda/4$ retarder 14. Next, the linearly polarized light (T1) successively passes through the upper polarizer 22 and the reflective polarizer 15. Then, the light (T1) passing through the two polarizers passes through the second upper $\lambda/4$ retarder 16, thereby being converted into right-handed circularly polarized light. The right-handed circularly polarized light (T1) then exits the LCD. At this time, the LCD screen is shown as a white state.

Hereinafter, variations of the polarization states in the case of the field-applied LC layer 3 will be discussed with reference to FIG. 6.

In FIG. 6, light (R2) is incident light from the ambient environment when an electric field is applied to the LC layer 3 in a reflection mode. The light (R2) successively passes

16

through the reflective polarizer 15 and the upper polarizer 22 as linearly polarized light in the X direction. The linearly polarized light (R2) then enters the first upper $\lambda/4$ retarder 14. At this time, the first upper $\lambda/4$ retarder 14 converts the incident light (R2) into right-handed circularly polarized light. Next, the right-handed circularly polarized light (R2) enters the LC layer 3 after passing through the upper insulating substrate 210 and the color filters 230. In this case, the field-applied LC layer 3 does not cause a change in the polarization state of the light passing therethrough. Sequentially, the right-handed circularly polarized light (R2) rotates by 180° with the reflection at the reflective electrodes 194, thereby being converted into left-handed circularly polarized light. The left-handed circularly polarized light (R2), reflected by the reflective electrodes 194, passes through the LC layer 3 again without a change of the polarization state, and then enters the first upper $\lambda/4$ retarder 14 after passing through the color filters 230 and the upper insulating substrate 210. At this time, the first upper $\lambda/4$ retarder 14 converts the incident left-handed circularly polarized light (R2) into linearly polarized light in the Y direction. Next, the upper polarizer 22 completely absorbs linearly polarized light in the Y direction, so that no light exits the LCD. In this case, the LCD screen is shown as a black state.

Meanwhile, light (T2) of FIG. 6 is light supplied from the backlight unit 500 when an electric field is applied to the LC layer 3 in a transmission mode. The light supplied from the backlight unit 500 passes through the lower polarizer 13. In this step, only a linearly polarized component (T) in the Y direction of the light remains and the remaining components are removed by absorption. The linearly polarized component in the Y direction is converted into left-handed circularly polarized light by the lower $\lambda/4$ retarder 13. The left-handed circularly polarized light (T2) enters the LC layer 3 after passing through the lower insulating substrate 110, and then exits the LC layer 3 with no change of the polarization state. Next, the left-handed circularly polarized light (T2) passes through the color filters 230 and the upper insulating substrate 210, and then enters the first upper $\lambda/4$ retarder 14. At this time, the light (T2) is converted into linearly polarized light in the Y direction by the first upper $\lambda/4$ retarder 14. Next, the upper polarizer 22 completely absorbs the linearly polarized light (T2), so that no light exits the LCD. In this case, the LCD screen is shown as a black state.

As described above, regardless of the operation modes of the LCD, the LCD screen exhibits the black state when the field is applied to the LC layer 3, while exhibiting the white state when the field is not applied to the LC layer 3.

FIG. 7 through FIG. 12 are schematic cross-sectional views showing process steps to manufacture a functional transparent plate 17 of an LCD according to a preferred embodiment of the present invention.

The functional transparent plate 17 is manufactured as follows.

As shown in FIG. 7, the functional transparent plate 17 with a prismatic top surface, which consists of first facets 17-1 and second facets 17-2, is first formed, and then an optical alignment agent 20 is coated thereon. The resultant structure of FIG. 7 is then selectively exposed to light through a first mask 30 as shown in FIG. 8. After exposure, as shown in FIG. 9, a development process is performed so that an optical alignment layer 21 remains only on the first facets 17-1. Subsequent to the development, a cholesteric LC material 40 is coated on the functional transparent plate 17, as shown in FIG. 10. Next, the resultant structure of FIG. 10 is selectively exposed to light through a second mask 35 as shown in FIG. 11. Then, as shown in FIG. 12, a development process and a

17

UV curing process are successively performed, so that a cholesteric LC layer **41** is formed only on the second facets **17-2**. As a result, each second facet **17-2** consists of the optical alignment layer **21** and the cholesteric LC layer **41**.

FIG. **13** is a schematic cross-sectional view of a functional transparent plate of an LCD according to still another embodiment of the present invention.

Referring to FIG. **13**, the functional transparent plate **17** of this embodiment has a top surface with first facets **17-1** and second facets **17-2** that are inwardly formed from the surface, and a prismatic bottom surface that is similar to the top surface of the functional transparent plate **17** of the previous embodiment. In this structure, it is preferable that first apexes **P1** and second apexes **P3** of the prismatic bottom surface and third apexes **P2** of the top surface are positioned on different vertical lines from each other. This is because such a structure enables much of the reflected light to reach the cholesteric LC layer of the second facets **17-2**, thus improving utilization efficiency of the light.

In this structure, an important problem is how to attach the functional transparent plate **17** with the prismatic bottom surface onto the second upper $\lambda/4$ retarder **16**. Two possible methods are discussed below.

The first method is to directly form the second upper $\lambda/4$ retarder **16** on the bottom surface of the functional transparent plate **17**. In this case, the second upper $\lambda/4$ retarder **16** is shaped as the bottom surface of the functional transparent plate **17**. Accordingly, spaces are formed between the second upper $\lambda/4$ retarder **16** and the reflective polarizer **15**. In the case that the functional transparent plate **17** and the second upper $\lambda/4$ retarder **16** are produced as separate films, an assembly process to bond the two films using an adhesive agent is further required. However, this method does not require such a process.

The second method is to attach the second upper $\lambda/4$ retarder **16** onto the reflective polarizer **15** and then to dispose the functional transparent plate **17** on the second upper $\lambda/4$ retarder **16**. In this case, spaces are formed between the functional transparent plate **17** and the second upper $\lambda/4$ retarder **16**.

In both methods, the spaces may be filled with the air. In this case, however, a problem may occur that light entering through an upper layer forming the spaces is totally reflected when impacting the air that fills the spaces, so the light does not reach a lower layer forming the spaces. To solve this problem, it is preferable to fill the spaces with a material with a refractive index that is very similar to an average of refractive indices of the upper layer and lower layer. For example, an organic silicon-based material, such as silicon resin or the like can be used as the filling material.

Instead of the functional transparent plates **17** as shown in FIG. **2** and FIG. **13**, other functional transparent plates **17** having variously forms of modified top or bottom surfaces can be used. In all cases, it is preferable to form the first facets **17-1** and the second facets **17-2** at the functional transparent plate **17** to enable the total reflection to occur there, but it is not necessary that either surface of the functional transparent plate **17** has a planar structure or a prismatic structure. To optimize an optical system of the LCD, the form of the functional transparent plate **17** should be designed to allow the partial reflection and the total reflection to occur between the upper surface of the second upper $\lambda/4$ retarder **16** and the functional transparent plate **17** in desired manners. In other word, it is preferable to design the form of the functional transparent plate **17** in order for the functional transparent

18

plate **17** to improve utilization efficiency of exterior light and display characteristics, such as viewing angle, contrast, and the like.

In the above-mentioned embodiment, the upper polarizer **22** is provided under the reflective polarizer **15**. Here, the two polarizers **22** and **15** have the same transmission axes. Accordingly, even if the upper polarizer **22** is omitted, the results are not changed. In fact, the reflective polarizer **15** has a relatively low polarization performance compared with the upper polarizer **22** (which is an absorption-type polarizer). Accordingly, after passing through the reflective polarizer **15**, light still contains a partial portion of a component that should ordinarily be reflected by the reflective polarizer. In the case that this phenomenon can be treated as a minor problem or the thickness of the LCD and the production cost are treated as the most important matters, the upper polarizer **22** may be omitted even though contrast of display images degrades.

In the above-mentioned embodiment, the TN LC material is used for the LC layer **3**. However, a VA mode or an ECB mode LC material may also be used instead of the TN LC. Also, the common electrode **270** and the transparent electrodes **192** or the reflective electrodes **194** of the pixel electrodes **190** may be formed on the same insulating substrate using an in-plane switching technique.

FIG. **14** is a cross-sectional view showing variations of the polarization state of light in a reflective LCD according to still another embodiment of the present invention.

Differing from the LCD shown in FIG. **6**, this LCD does not include the lower $\lambda/4$ retarder **13**, the lower polarizer **12**, or the backlight unit **500**. In addition, this LCD does not require the transparent electrodes **192** because it is a reflective LCD.

Hereinafter, an LCD according to still another embodiment of the present invention will be described in detail with reference to FIG. **15** through FIG. **17**.

FIG. **15** is a layout view of an LCD according to another embodiment of the present invention, and FIG. **16** and FIG. **17** are schematic cross-sectional views cut along XVI-XVI' and XVII-XVII' of FIG. **15**, respectively.

Referring to FIG. **15** to FIG. **17**, the LCD of this embodiment includes a TFT array panel **100** and a common electrode panel **200** facing each other, and an LC layer **3** that is interposed therebetween with LC molecules that are aligned perpendicular or parallel to the surfaces of the two panels **100** and **200**.

LC molecules in the LC layer **3** may be aligned in a 90° twisted nematic (TN) mode, a vertical alignment (VA) mode, or an electrically controlled birefringence (ECB) mode.

The TFT array panel **100** is configured as follows.

A plurality of gate lines **121** and a plurality of storage electrode lines **131** are formed on an insulating substrate **110** made of transparent glass or plastic.

The gate lines **121** for transmitting gate signals extend substantially in a horizontal direction, while being separated from each other. Each gate line **121** includes a plurality of gate electrodes **124** protruding upward and an end portion **125** having a relatively large dimension to be connected to an external device.

The storage electrode lines **131** extend substantially in a horizontal direction and are substantially parallel to the gate lines **121**. Each storage electrode line **131** includes a plurality of storage electrodes **133** protruding upward and downward. The storage electrode lines **131** receive a predetermined voltage, such as a common voltage that is applied to a common electrode **270** of the common electrode panel **200**.

The gate lines **121** and the storage electrode lines **131** are preferably made of an aluminum-(Al) containing metal such

as Al and an Al alloy, a silver-(Ag) containing metal such as Ag and a Ag alloy, a copper-(Cu) containing metal such as Cu and a Cu alloy, a molybdenum (Mo)-containing metal such as Mo and a Mo alloy, chrome (Cr), titanium (Ti), or tantalum (Ta). The gate lines **121** and the storage electrode lines **131** may be configured as a multi-layered structure, in which at least two conductive layers (not shown) having different physical properties are included. In such a structure, an upper layer of the two is made of a low resistivity metal, such as an Al-containing metal, a Ag-containing metal, a Cu-containing metal, or the like, in order to reduce delay of the signals or voltage drop in the gate lines **121** and the storage electrode lines **131**, and a lower layer is made of material having prominent physical, chemical, and electrical contact properties with other materials such as indium tin oxide (ITO), indium zinc oxide (IZO), etc. For example, a Mo-containing metal, Cr, Ta, Ti, etc., may be used for the formation of the same layer. A desirable example of the combination of the two layers is a lower Cr layer and an upper Al—Nd layer. However, the gate lines **121** and the storage electrode lines **131** may be configured as single-layered structures.

All lateral sides of the gate lines **121** and the storage electrode lines **131** preferably slope in the range from about 20° to 80° to the surface of the substrate **110**.

A gate insulating layer **140** made of SiN_x or SiO₂ is formed on the gate lines **121** and the storage electrode lines **131**.

A plurality of linear semiconductors **151** made of hydrogenated amorphous silicon (abbreviated as “a-Si”) or polysilicon are formed on the gate insulating layer **140**. Each linear semiconductor **151** extends substantially in a vertical direction and includes a plurality of projections **154** that extend along the respective gate electrodes **124** and a plurality of extensions **157** that extend from the respective projections **154**. The linear semiconductors **151** are enlarged in the vicinities of the gate lines **121** and the storage electrode lines **131** to cover them entirely.

A plurality of linear ohmic contacts **161** and island-shaped ohmic contacts **165** are formed on the linear semiconductors **151**. The ohmic contacts **161** and **165** may be made of N⁺ hydrogenated amorphous silicon that is highly doped with N-type impurities, or silicide. The linear ohmic contacts **161** include a plurality of projections **163**. A set of a projection **163** and an island-shaped ohmic contact **165** is placed on the projection **154** of the semiconductor **151**.

All lateral sides of the semiconductors **151** and the ohmic contacts **161** and **165** slope in the range from about 20° to 80° to the surface of the substrate **110**.

A plurality of data lines **171** and a plurality of drain electrodes **175**, separated from the data lines **171**, are formed on the ohmic contacts **161** and **165** and the gate insulating layer **140**.

The data lines **171** for transmitting data signals extend substantially in a vertical direction to be crossed with the gate lines **121** and the storage electrode lines **131**. Each data line **171** includes an end portion **179** having a relatively large dimension to be connected to a different layer or an external device.

Each drain electrode **175** includes an expansion **177** that is overlapped with one of the storage electrodes **133**. Each data line **171** further includes a plurality of source electrodes **173** protruding along and extending toward the respective gate electrodes **124**. Each source electrode **173** surrounds a partial portion of a bar-shaped end portion of the drain electrode **175**.

A gate electrode **124**, a source electrode **173**, a drain electrode **175**, and a projection **154** of the semiconductor **151**

form a thin film transistor (TFT). A TFT channel is formed in the projection **154** provided between the source electrode **173** and the drain electrode **175**.

The data lines **171** and the drain electrodes **175** are preferably made of a refractory metal, such as a Mo-containing metal, a Cr-containing metal, Ta, Ti, or the like, and may be configured as multi-layered structures including a lower layer (not shown) consisting of one among Mo, a Mo alloy, Cr, etc., and an upper layer (not shown) consisting of an Al-containing metal.

Similarly to the gate lines **121** and the storage electrode lines **131**, all lateral sides of the data lines **171** and the drain electrodes **175** slope in the range from about 20° to 80° to the surface of the substrate **110**.

The ohmic contacts **161** and **165** exist only between the underlying semiconductors **151** and the overlying data lines **171** and between the overlying drain electrodes **175** and the underlying semiconductors **151**, in order to reduce contact resistance therebetween. The linear semiconductors **151** are partially exposed at places where the data lines **171** and the drain electrodes **175** do not cover them, as well as between the source electrodes **173** and the drain electrodes **175**.

A passivation layer **180**, made of an inorganic material such as SiN_x or SiO₂, is formed on the data lines **171**, the drain electrodes **175**, and the exposed portions of the semiconductors **151**.

An organic insulating layer **187**, made of a photosensitive organic insulator having a prominent planarization property, is formed on the passivation layer **180**. A top surface of the organic insulating layer **187** is uneven. Due to the uneven surface, reflective electrodes **194** overlying the organic insulating layer **187** have uneven top surfaces. The uneven top surfaces of the reflective electrodes **194** prevent mirror reflection. Accordingly, images that may be shown on an LCD screen due to the mirror reflection are eliminated. The organic insulating layer **187** is removed at the end portions **125** and **179** of the gate lines **121** and the data lines **171**, so only the passivation layer **180** remains on the end portions **125** and **179**.

The passivation layer **180** is provided with a plurality of contact holes **183**, through which the end portions **179** of the data lines **171** are exposed. A plurality of contact holes **182** are formed in the passivation layer **180** and the gate insulating layer **140**, and the end portions **125** of the gate lines **121** are exposed therethrough. A plurality of contact holes **185** are formed in the passivation layer **180** and the organic insulating layer **187**, and the expansions **177** of the drain electrodes **175** are exposed therethrough. The contact holes **182**, **183**, and **185** may have polygonal or circular shapes. The sidewalls of the contact holes **182**, **183**, and **185** slope in the range from about 30° to 85° to the surface of the substrate **110** or are shaped as steps.

A plurality of pixel electrodes **190** are formed on the organic insulating layer **187**.

Each pixel electrode **190** includes a transparent electrode **192** and a reflective electrode **194** overlying the transparent electrode **192**. The transparent electrodes **192** are made of a transparent conductive material such as ITO or IZO, and the reflective electrodes **194** are made of a reflective opaque material such as Al, an Al alloy, Ag, or a Ag alloy. Each pixel electrode **190** may further include a contact assistant (not shown) made of Mo, a Mo alloy, Cr, Ti, or Ta. The contact assistants ensure contact properties between the transparent electrodes **192** and the reflective electrodes **194**, while preventing the transparent electrodes **192** from oxidizing the reflective electrodes **194**.

Each pixel is divided into a transmission area TA without the reflective electrode **194** and a reflection area RA with the reflective electrode **194**. The organic insulating layer **187** is removed at in the transmission area TA, so that a transmission window **195** is formed there. Due to the transmission window **195**, a cell gap of the transmission area TA becomes nearly twice as large as that of the reflection area RA, so that a light path difference between the transmission area TA and the reflection area RA is compensated.

The pixel electrodes **190** are physically and electrically connected to the expansions **177** of the drain electrodes **175** through the contact holes **185** to receive data voltages from the drain electrodes **175**. The pixel electrodes **190** supplied with the data voltages generate electric fields in cooperation with the common electrode **270** of the common electrode panel **200**, determining the molecular orientation of the LC layer **3** interposed between the two electrodes.

Each set of the pixel electrode **190** and the common electrode **270** forms an LC capacitor that is capable of storing the applied voltage after the TFT is turned off. To enhance the voltage storage ability of the LC capacitors, storage capacitors, connected to the LC capacitors in parallel, are further provided. Overlapping of the expansions **177** of the drain electrodes **175** with the storage electrodes **133** implements the storage capacitors. Otherwise, overlapping of the pixel electrodes **190** with the gate lines **121** adjacent thereto may implement the storage capacitors. In this case, the storage electrode lines **131** may be omitted.

The pixel electrodes **190** may be overlapped with the data lines **171** adjacent thereto as well as the gate lines **121** adjacent thereto, in order to increase the aperture ratio, but such overlap portions are not always necessary.

The pixel electrodes **190** may be made of a transparent conductive polymer. However, opaque reflective metals may be used in reflective LCDs.

A plurality of contact assistants **95** and **97** are formed on the passivation layer **180** relating to a pad portion, and are individually connected to the end portions **125** of the gate lines **121** and the end portions **179** of the data lines **171** through the contact holes **182** and **183**. The contact assistants **95** and **97** supplement adhesion between the end portions **125** and **179** and exterior devices, and to protect them. The contact assistants **95** and **97** may be formed on the same layer as the transparent electrodes **192** or the reflective electrodes **194**. However, they may be omitted because they are not essential elements.

The common electrode panel **200** facing the TFT array panel **100** is configured as follows.

A light-blocking member **220** called a "black matrix" is provided on an insulating substrate **210** made of a transparent insulating material such as glass. The light-blocking member **220** prevents light from leaking out through barriers between the pixel electrodes **190** and delimits aperture regions facing the pixel electrodes **190**.

A plurality of color filters **230** are formed on the substrate **210** and the light-blocking member **220**, and most of them are placed within the aperture regions delimited by the light-blocking member **220**. Each color filter **230** is formed between the two adjacent data lines **171** in a vertical direction, and exhibits one among red, green, and blue colors. The color filters **230** are connected to one another in the form of stripes.

In the case of a typical transmissive LCD, in the transmission areas TA, light passes through the color filters **230** only once, while it passes twice in the reflection areas RA. Accordingly, a difference of color tone between the transmission areas TA and the reflection areas RA is generated. To reduce the difference of color tone between the two areas TA and RA,

two methods can be used. The first method is to form the thickness of each color filter **230** differently depending on its location. That is, in this method, a portion of the color filter **230**, which is placed at the transmission area TA, is formed thicker than the remaining portion, which is placed at the reflection area RA. The second method is to form light holes in the reflection areas RA of the color filters **230**.

The common electrode **270**, made of a transparent conductive material such as ITO or IZO, is formed on the light-blocking member **220** and the color filters **230**.

The LC layer **3** is interposed between the two panels **100** and **200** facing each other.

A lower polarizer **12** and an upper polarizer **22** are individually attached to the outer surfaces of the two panels **100** and **200**. A transmission axis (θ) of the upper polarizer **22** and a transmission axis ($\theta+90^\circ$) of the lower polarizer **12** are mutually crossed at a right angle.

A lower $\lambda/4$ retarder **13** is interposed between the TFT array panel **100** and the lower polarizer **12**, and a first upper $\lambda/4$ retarder **14** is interposed between the common electrode panel **200** and the upper polarizer **22**.

A second upper $\lambda/4$ retarder **16** is provided on the upper polarizer **22**, and a selective reflection layer **18** is provided thereon.

A functional transparent plate **17** is provided on the selective reflection layer **18**. A top surface of the functional transparent plate **17** consists of a plurality of prisms. Each prism includes a first facet **17-1**, on which no additional material exists, and a second facet **17-2**, on which a cholesteric LC layer exists.

Hereinafter, the structure of the above-mentioned LCD and the polarization principles of light in the same LCD will be described in detail.

FIG. **18** shows a vertical scheme of an LCD of another embodiment of the present invention.

Referring to FIG. **18**, a display panel assembly **300** comprises a TFT array panel **100** and a common electrode panel **200**, and an LC layer **3** interposed therebetween.

The lower $\lambda/4$ retarder **13** is attached to a lower surface of the display panel assembly **300**, and the lower polarizer **12** is attached to a lower surface of the lower $\lambda/4$ retarder **13**.

Meanwhile, the first upper $\lambda/4$ retarder **14** is attached to an upper surface of the display panel assembly **300**, and the upper polarizer **22** is attached to an upper surface of the first upper $\lambda/4$ retarder **14**. The second upper $\lambda/4$ retarder **16** and the selective reflection layer **18** in this order are attached to an upper surface of the upper polarizer **22**. The functional transparent plate **17**, of which the top surface consists of the first sides **17-1** and second sides **17-2**, is formed on the selective reflection layer **18**.

Hereinafter, the above-mentioned structure will be described in more detail.

The polarizers **12** and **22** are individually attached to the outer surfaces of the panels **100** and **200**. Their transmission axes are mutually crossed at a right angle. The polarizers **12** and **22** are absorption-type polarizers that transmit only linearly polarized incident light that vibrates parallel to their transmission axes and absorbs linearly polarized incident light that vibrates perpendicular to the axes.

The LCD of this embodiment utilizes three $\lambda/4$ retarders in all. Each of the three $\lambda/4$ retarders **13**, **14**, and **16** converts circularly polarized light into linearly polarized light or linearly polarized light into circularly polarized light by causing a phase difference of a quarter wavelength between two polarized components that are orthogonal to each other and are individually parallel to a fast axis and a slow axis thereof. The above-mentioned circularly polarized light may be ellipti-

cally polarized light in actuality, but the elliptically polarized light will be also referred to as circularly polarized light for convenience.

The fast axes of the three $\lambda/4$ retarders **13**, **14**, and **16** are preferably formed at $\pm 45^\circ$ to the transmission axes (θ and $\theta + 90^\circ$) of the polarizers **12** and **22** to maximize the phase difference between the two polarized components. However, they may be disposed at different angles, except being disposed perpendicular to or parallel to each other.

The selective reflection layer **18** is attached to the upper surface of the second upper $\lambda/4$ retarder **16**. The selective reflection layer **18** allows only circularly polarized light in a specific direction to pass, while reflecting circularly polarized light in a direction that is opposite to the specific direction. In this embodiment, the selective reflection layer **18**, which selectively transmits the circularly polarized light, consists of cholesteric LC material. In detail, the selective reflection layer **18** transmits circularly polarized incident light rotating in the same direction as an optical axis of the cholesteric LC material, while reflecting circularly polarized incident light rotating in an opposite direction. In general, the cholesteric LC material can be aligned in various alignment manners. However, in this embodiment, a cholesteric LC material of a planar-alignment mode where spiral axes of LC molecules are aligned perpendicular to the surfaces of the substrates is preferably used, in order for the selective reflection layer **18** to selectively reflect or transmit the circularly polarized light. A fabrication method of the selective reflection layer **18** will be described later.

The functional transparent plate **17** is made of a transparent material and has a prismatic top surface consisting of a plurality of first facets **17-1** and a plurality of second facets **17-2**, as shown in FIG. **16**. No additional material exists on the first facets **17-1**, while the cholesteric LC layer **3** exists on the second facets **17-2**. The second facets **17-2** transmit circularly polarized incident light rotating in the same direction as the optical axis of the cholesteric LC layer, while reflecting circularly polarized incident light rotating in an opposite direction. A fabrication method of the first facets **17-1** and the second facets **17-2** will be described later.

The functional transparent plate **17**, the selective reflection layer **18**, the second upper $\lambda/4$ retarder **16**, the upper polarizer **22**, the first upper $\lambda/4$ retarder **14**, the display panel assembly **300**, the lower $\lambda/4$ retarder **13**, and the lower polarizer **12** are bonded by an adhesive agent, in that order.

FIG. **19** shows variations of the polarization state of light at an upper part of the LCD with the functional transparent plate **17**, the selective reflection layer **18**, the second upper $\lambda/4$ retarder **16**, and the upper polarizer **22**.

As shown in FIG. **19**, light that is incident onto the functional transparent plate **17** is divided into four light rays (A, B-1, B-2, and C) depending on incident position and incident angle.

Incident light (A) of the four is first described.

The light (A), which is incident onto the second facets **17-2** of the functional transparent plate **17**, is separated into two individual light rays (A-1) and (A-2) having different light paths. That is, when the light (A) impacts the second facets **17-2** where the cholesteric LC layer is formed, right-handed circularly polarized light (A-1) of the incident light (A), which rotates in the same direction as the optical axis of the cholesteric LC layer, passes through the functional transparent plate **17**, while left-handed circularly polarized light (A-2), which rotates in an opposite direction, is reflected.

The light (A-1) passing through the functional transparent plate **17** is then incident onto the selective reflection layer **18**. At this time, the selective reflection layer **18** transmits the

right-handed circularly polarized incident light (A-1) since it is designed to allow right-handed circularly polarized light to pass and to reflect left-handed circularly polarized light. Next, the right-handed circularly polarized light (A-1) travels through the second upper $\lambda/4$ retarder **16**. At this time, the light (A-1) is converted into linearly polarized light in the X direction by the second upper $\lambda/4$ retarder **16**. Next, the linearly polarized light (A-1) passes through the upper polarizer **22** whose transmission axis is in the X direction.

Meanwhile, the left-handed circularly polarized reflected light (A-2), reflected the second facets **17-2**, passes through the first facets **17-1** and is then reflected again by an adjacent second facet **17-2**. The polarization state of the light (A-2) is maintained with no change during these sequential processes. This is possible because the second facets **17-2** that are formed with the cholesteric LC material do not cause any change in the polarization state of the light when reflecting. Next, the left-handed circularly polarized light (A-2) is total reflected by the selective reflection layer **18**. The light that is reflected by the selective reflection layer **18** is designated as (A-3) in FIG. **19**.

Two light rays (B-1) and (B-2) of FIG. **19** are described below.

Both of the light rays (B-1) and (B-2) are incident onto the first facets **17-1** of the functional transparent plate **17**, but have different incident angles. That is, the light (B-1) is slantingly incident onto the first facets **17-1** of the functional transparent plate **17**, while the light (B-2) is perpendicularly incident onto the first facets **17-1**. Regardless of the different incident angles, the two light rays (B-1) and (B-2) proceed along the same light path with the same polarization states after entering the functional transparent plate **17**. In detail, the two light rays (B-1) and (B-2) pass through the functional transparent plate **17** with all-directional polarized components. Next, the light rays (B-1) and (B-2) are incident onto the selective reflection layer **18**. At this time, the selective reflection layer **18** transmits only right-handed circularly polarized light rays (B1-1) and (B2-1) of the incident rays (B-1) and (B-2) and reflects the left-handed circularly polarized light rays (B1-2) and (B2-2). After this process, the right-handed circularly polarized light rays (B1-1) and (B2-1) enters the second upper $\lambda/4$ retarder **16**, thereby being converted into linearly polarized light rays in the X direction. Then, the linearly polarized light rays (B1-1) and (B2-1) travel through the upper polarizer **22**.

Next, light (C) of FIG. **19** is described.

The light (C) that is perpendicularly incident onto the second facets **17-2** of the functional transparent plate **17** is also divided into two separate light rays (C-1) and (C-2) having different light paths. That is, right-handed circularly polarized light (C-1) of the incident light (C), which rotates in the same direction as the optical axis of the cholesteric LC, passes through the functional transparent plate **17** and then proceeds along the same light path as the light (A-1), while left-handed circularly polarized light (C-2) of the incident light (C), which rotates in the opposite direction, is directed to the outside by reflection at the second facets **17-2**.

Here, plane angles of the first facets **17-1** and the second facets **17-2** may be controlled so that the left-handed circularly polarized reflected light (C-2) is incident onto the first facets **17-1** again and enters the second upper $\lambda/4$ retarder **16** after being reflected or refracted by the functional transparent plate **17**.

In the meantime, the left-handed circularly polarized light rays (A-3), (B1-2), and (B2-2), reflected by the selective reflection layer **18**, enters the functional transparent plate **17** again. In this case, incident light is designated as (D) in FIG.

19. The light (D) is divided into two light rays (D-1) and (D-2) depending on incident positions of the light (D). That is, the light (D-2) is incident onto the first facets 17-1 of the functional transparent plate 17, while the light (D-1) is incident onto the second facets 17-2. The two light rays (D-1) and (D-2) are doubly reflected by the first facets 17-1 and the second facets 17-2, respectively. At this time, the light rays (D-1) and (D-2) undergo 180° phase changes with the reflection at the first facets 17-1, so that they are all converted into right-handed polarized light rays (D-1) and (D-2). Next, the right-handed polarized lights (D-1) and (D-2) enter the selective reflection layer 18 again. The selective reflection layer 18 transmits all the right-handed polarized light rays (D-1) and (D-2) without a change of the polarization state. Subsequently, the two light rays (D-1) and (D-2) travel through the second upper $\lambda/4$ retarder 16, while being converted into linearly polarized light rays in the X direction. Then, the linearly polarized lights (D-1) and (D-2) pass through the upper polarizer 22.

As described above, the light, which is incident from the ambient environment through the first facets 17-1 and the second facets 17-2 of the functional transparent plate 17, does not exit the LCD after being reflected by the selective reflection layer 18 and is returned to the selective reflection layer 18 again by changing its polarization direction, so that display luminance of the LCD in a reflection mode is improved. To accomplish this effect, it is preferable to design the functional transparent plate 17 so that the first facets 17-1 and the second facets 17-2 thereof represent the largest possible refractive index difference therebetween, both having largest possible dimensions. It is also preferable to form angles between the two facets 17-1 and 17-2 to be as large as possible. In the case that the difference of the refractive index between the exterior air and the functional transparent plate 17 is relatively large, no total reflection occurs when exterior light enters the functional transparent plate 17, but a total reflection occurs in the case when the light emerges from the functional transparent plate 17 toward the outside. Accordingly, utilization efficiency of the exterior light is improved.

FIG. 20 is a view for comparing the polarization states of light when the LCD operates in a reflection mode utilizing exterior light and in a transmission mode utilizing internal light from a backlight unit 500.

In this embodiment, the LC layer 3 consists of TN mode LC molecules. The TN LC molecules have peculiar optical properties. That is, they are aligned in a vertical direction when an electric field is applied, thereby causing no change in the polarization state of light passing through the LC layer 3, but they are aligned in a horizontal direction when no electric field is applied, thereby changing the polarization state of light passing through the LC layer 3.

Hereinafter, variations of the polarization states of light when no electric field is applied to the LC layer 3 will be first described with reference to FIG. 20.

In FIG. 20, leftmost light (R1) is incident light from the ambient environment when no electric field is applied to the LC layer 3 in a reflection mode. The light (R1) passes through the upper polarizer 22 as linearly polarized light in the X direction. Then, the linearly polarized light (R1) enters the first upper $\lambda/4$ retarder 14. At this time, the first upper $\lambda/4$ retarder 14 converts the light (R1) into right-handed circularly polarized light. The right-handed circularly polarized light (R1) enters the LC layer 3 after passing through the upper insulating substrate 210 and the color filters 230. In this case, since the LC layer 3 is supplied with no electric field, the light (R1) is converted into linearly polarized light in the Y direction. The linearly polarized light (R1) rotates by 180°

with the reflection at the reflective electrode 194. However, the light (R1) maintains the polarization state without a change even after the rotation. The reflected light (R1) is converted into right-handed circularly polarized light again when passing through the LC layer 3, and then enters the first upper $\lambda/4$ retarder 14 after successively passing through the color filters 230 and the upper insulating substrate 210. At this time, the first upper $\lambda/4$ retarder 14 converts the right-handed circularly polarized light (R1) into linearly polarized light in the X direction. Next, the linearly polarized light (R1) enters the second upper $\lambda/4$ retarder 16 after passing through the upper polarizer 22. At this time, the linearly polarized light in the X direction (R1) is converted into right-handed circularly polarized light by the second upper $\lambda/4$ retarder 16. Subsequently, the right-handed circularly polarized light (R1) passes through the selective reflection layer 18 and the functional transparent plate 17 without a change of the polarization state, and then exits the LCD. At this time, the LCD screen is shown as a white state.

Meanwhile, light (T1) of FIG. 20 is light supplied from an internal light source of the LCD, i.e., the backlight unit 500, when no electric field is applied to the LC layer 3 in a transmission mode. First, the light (T) passes through the lower polarizer 13. In this step, only a linearly polarized component in the Y direction of the light (T) is transmitted and the remaining components are removed by absorption. The linearly polarized component in the Y direction (T) is converted into left-handed circularly polarized light (Ti) by the lower $\lambda/4$ retarder 13. The left-handed circularly polarized light (T1) enters the LC layer 3 after passing through the lower insulating substrate 110, and is then converted into right-handed circularly polarized light when passing through the LC layer 3. Next, the right-handed circularly polarized light (T1) passes through the color filters 230 and the upper insulating substrate 210 and then enters the first upper $\lambda/4$ retarder 14. At this time, the light (T1) is converted into linearly polarized light in the X direction by the first upper $\lambda/4$ retarder 14. Next, the linearly polarized light (T1) passes through the upper polarizer 22 and then enters the second upper $\lambda/4$ retarder 16, thereby being converted into right-handed circularly polarized light by the second upper $\lambda/4$ retarder 16. Subsequently, the right-handed circularly polarized light (T1) passes through the selective reflection layer 18 and the functional transparent plate 17 without a change of the polarization state, and then exits the LCD. At this time, the LCD screen is shown as a white state.

Hereinafter, variations of the polarization states in the case of the field-applied LC layer 3 will be described with reference to FIG. 20.

In FIG. 20, light (R2) is incident light from the ambient environment when an electric field is applied to the LC layer 3 in a reflection mode. The light (R2) passes through the upper polarizer 22 as linearly polarized light in the X direction. Next, the linearly polarized light in the X direction (R2) enters the first upper $\lambda/4$ retarder 14. At this time, the first upper $\lambda/4$ retarder 14 converts the light (R2) into right-handed circularly polarized light. The right-handed circularly polarized light (R2) enters the LC layer 3 after passing through the upper insulating substrate 210 and the color filters 230. In this case, the field-applied LC layer 3 does not cause a change in the polarization state of the light passing therethrough. Sequentially, the right-handed circularly polarized light (R2) rotates by 180° with the reflection at the reflective electrodes 194, thereby being converted into left-handed circularly polarized light. The left-handed circularly polarized light (R2), reflected by the reflective electrodes 194, passes through the LC layer 3 again without a change of the polar-

ization state, and then enters the first upper $\lambda/4$ retarder **14** after passing through the color filters **230** and the upper insulating substrate **210**. At this time, the first upper $\lambda/4$ retarder **14** converts the left-handed circularly polarized light (R2) into linearly polarized light in the Y direction. Next, the upper polarizer **22** absorbs all of the linearly polarized light in the Y direction (R2), so that no light exits the LCD. In this case, the LCD screen is shown as a black state.

Meanwhile, light (T2) of FIG. **20** is light supplied from an internal light source, i.e., a backlight unit **500**, when an electric field is applied to the LC layer **3** in a transmission mode. The light (T) supplied from the backlight unit **500** passes through the lower polarizer **13**. In this step, only a linearly polarized component in the Y direction of the light (T) remains and the remaining components are removed. The linearly polarized component in the Y direction (T) is converted into left-handed circularly polarized light (T2) by the lower $\lambda/4$ retarder **13**. The left-handed circularly polarized light (T2) enters the LC layer **3** after passing through the lower insulating substrate **110**, and then exits the LC layer **3** with no change of the polarization state. Next, the left-handed circularly polarized light (T2) passes through the color filters **230** and the upper insulating substrate **210**, and then enters the first upper $\lambda/4$ retarder **14**. At this time, the light (T2) is converted into linearly polarized light in the Y direction by the first upper $\lambda/4$ retarder **14**. Next, the upper polarizer **22** completely absorbs the linearly polarized light in the Y direction (T2), so that no light exits the LCD. At this time, the LCD screen is shown as a black state.

As described above, regardless of the operation modes of the LCD, the LCD screen exhibits the black state when the field is applied to the LC layer **3**, while it exhibits the white state when the field is not applied to the LC layer **3**.

FIG. **21** through FIG. **24** are schematic cross-sectional views showing process steps to manufacture a selective reflection layer **18** of an LCD according to another embodiment of the present invention.

The selective reflection layer **18** is manufactured as follows.

An optical alignment agent is first coated on a second upper $\lambda/4$ retarder **16**, and is then exposed to light, thereby forming an optical alignment layer **25** as shown in FIG. **21**. Next, as shown in FIG. **22**, a cholesteric LC material **45** containing a UV cross-linking agent is coated over the optical alignment layer **25**. At this time, it is preferable that molecules in the LC layer **3** have planar orientations. Subsequently, UV irradiation is applied to the resultant structure of FIG. **22**, as shown in FIG. **23**, to cure the cholesteric LC material **45**. As a result, a cholesteric LC layer **46** is formed. The cholesteric LC layer **46** and the optical alignment layer **25** form a selective reflection layer **18**, as shown in FIG. **24**.

In the above, the selective reflection layer **18** is formed on the second upper $\lambda/4$ retarder **16**, but it may be formed on a different substrate and separately prepared.

FIG. **25** through FIG. **30** are schematic cross-sectional views showing process steps to manufacture a functional transparent plate **17** of an LCD according to another embodiment of the present invention.

The functional transparent plate **17** is manufactured as follows.

As shown in FIG. **25**, after the functional transparent plate **17** with a prismatic top surface, which consists of first facets **17-1** and second facets **17-2**, is first formed, an optical alignment agent **20** is coated thereon. The resultant structure of FIG. **25** then is selectively exposed to light through a first mask **30** as shown in FIG. **26**. After exposure, a development process is performed. As a result, an optical alignment layer

21 is formed only on the second facets **17-2**, as shown in FIG. **27**. Subsequent to the formation of the optical alignment layer **21**, a cholesteric LC material **40** is coated on the functional transparent plate **17**, as shown in FIG. **28**. Next, the resultant structure of FIG. **28** is selectively exposed to light through a second mask **35**, as shown in FIG. **29**. Then, as shown in FIG. **30**, development and UV curing processes are successively performed, so that a cholesteric LC layer **41** is formed only on the second facets **17-2**. As a result, each second facet **17-2** consists of the optical alignment layer **21** and the cholesteric LC layer **41**.

FIG. **31** is a schematic cross-sectional view of a functional transparent plate of an LCD according to still another embodiment of the present invention.

Referring to FIG. **31**, the functional transparent plate **17** of this embodiment has a top surface with first facets **17-1** and second facets **17-2** that are inwardly formed from the surface thereof, and a prismatic bottom surface that is similar to the top surface of the functional transparent plate **17** of the previous embodiment. In this structure, it is preferable that first apexes **P1** and second apexes **P3** of the bottom surface and third apexes **P2** of the top surface are positioned on different vertical lines from each other. This is because such a structure enables much of the reflected light to reach the cholesteric LC layer **41** of the second facets **17-2**, thus improving utilization efficiency of the light.

In this structure, an important problem is how to attach the functional transparent plate **17** with the prismatic bottom surface onto the selective reflection layer **18**. Two possible methods are discussed below.

The first method is to directly form the selective reflection layer **18** on the bottom surface of the functional transparent plate **17**. In this case, the selective reflection layer **18** has the same form as the bottom surface of the functional transparent plate **17**. Accordingly, spaces are formed between the selective reflection layer **18** and the second upper $\lambda/4$ retarder **16**. In the case that the functional transparent plate **17** and the selective reflection layer **18** are produced as separated films, an assembly process to bond the two films using an adhesive agent is additionally required. However, this method does not require such a process.

The second method is to attach the selective reflection layer **18** onto the second upper $\lambda/4$ retarder **16** and then to dispose the functional transparent plate **17** thereon. In this case, spaces are formed between the selective reflection layer **18** and the functional transparent plate **17**.

In both methods, the spaces may be filled with the air. In this case, however, a problem may occur in which light entering through an upper layer forming the spaces is totally reflected when impacting the air that fills the spaces, so the light does not reach a lower layer forming the spaces. To settle this problem, it is preferable to fill the spaces with a material with a refractive index that is very similar to an average of refractive indices of the upper layer and lower layer. For example, an organic silicon-based material, such as silicon resin or the like, can be used as the filling material.

Instead of the functional transparent plates **17** as shown in FIG. **16** and FIG. **31**, other functional transparent plates **17** having variously forms of modified top or bottom surfaces can be used. In all cases, it is preferable to form the first facets **17-1** and the second facets **17-2** at the functional transparent plate **17** to enable the total reflection to occur at there, but it is not necessary that either surface of the functional transparent plate **17** has a planar structure or a prismatic structure. To optimize an optical system of the LCD, the form of the functional transparent plate **17** should be designed to allow the partial reflection and the total reflection to occur between the

upper surface of the second upper $\lambda/4$ retarder 16 and the functional transparent plate 17 in desired manners. In other words, it is preferable to design the form of the functional transparent plate 17 in order for the functional transparent plate 17 to improve utilization efficiency of exterior light and display characteristics, such as viewing angle, contrast, and the like.

In the above-mentioned embodiment, the TN LC material is used for the LC layer 3. However, a VA mode or an ECB mode LC material may also be used instead of the TN LC. Also, the common electrode 270 and the transparent electrodes 192 or the reflective electrodes 194 of the pixel electrodes 190 may be formed on the same insulating substrate using an in-plane switching technique.

FIG. 32 is a cross-sectional view showing variations of the polarization state of light in a reflective LCD according to still another embodiment of the present invention.

Differing from the transmissive LCD of FIG. 20, this LCD does not include the lower $\lambda/4$ retarder 13, the lower polarizer 12, or the backlight unit 500. In addition, this LCD does not require the transparent electrodes 192 because it is a reflective LCD.

As described above, in the reflective or Transmissive LCD according to an aspect of the present invention, the reflective polarizer, the $\lambda/4$ retarder, and the functional transparent plate with the first facets and the second facets, which are disposed on the display panel assembly in that order, improve utilization efficiency of light incident from the ambient environment so that display luminance of the LCD operating in a reflection mode is improved.

Alternately, in the reflective or transmissive LCD according to another aspect of the present invention, the $\lambda/4$ retarder, the selective reflection layer, and the functional transparent plate with the first facets and the second facets, which are disposed on the display panel assembly in that order, improve utilization efficiency of light incident from ambient environment so that display luminance of the LCD operating a reflection mode is improved.

The present invention should not be considered limited to the particular examples described above, but rather should be understood to cover all aspects of the invention as fairly set out in the attached claims. Various modifications, equivalent processes, as well as numerous structures to which the present invention may be applicable will be readily apparent to those of skill in the art to which the present invention is directed upon review of the instant specification.

What is claimed is:

1. A display device comprising:
 - a display panel assembly;
 - a reflective polarizer that is provided above the display panel assembly to transmit external incident light which is linearly polarized in a first direction and to reflect external incident light which is linearly polarized in a second direction perpendicular to the first direction;
 - a second $\lambda/4$ retarder that is provided on the reflective polarizer; and
 - a functional transparent plate that is provided on the second $\lambda/4$ retarder and which has a top surface including portions without a cholesteric liquid crystal material and portions with a cholesteric liquid crystal material.
2. The display device of claim 1, further comprising a first $\lambda/4$ retarder that is provided between the reflective polarizer and the display panel assembly.
3. The display device of claim 2, further comprising a first absorbing polarizer that is provided between a first $\lambda/4$ retarder and the reflective polarizer.

4. The display device of claim 1, further comprising a second absorbing polarizer that is provided under the display panel assembly.

5. The display device of claim 4, further comprises third $\lambda/4$ retarder that is provided between the second absorbing polarizer and the display panel assembly.

6. The display device of claim 1, wherein the reflective polarizer utilizes a dual brightness enhancement film (DBEF) that is produced based on reflectance anisotropy caused by refractive index anisotropy, or delicate linear patterns.

7. The display device of claim 1, further comprising a backlight unit that is provided under the display panel assembly.

8. The display device of claim 1, wherein the display panel assembly, the reflective polarizer, the first $\lambda/4$ retarder, and the functional transparent plate are bonded by an adhesive agent.

9. The display device of claim 1, wherein spaces are formed between the functional transparent plate and the second $\lambda/4$ retarder due to a surface structure of either of a bottom surface of the functional transparent plate or a top surface of the first $\lambda/4$ retarder, and the spaces are filled with a filling material with a refractive index that is equal to an average of refractive indices of the functional transparent plate and the second $\lambda/4$ retarder.

10. The display device of claim 9, wherein the filling material for the spaces comprises an organic silicon-based material such as silicon resin.

11. The display device of claim 1, wherein the display panel assembly includes an LC layer with LC molecules that are aligned in a 90.degree.-twisted nematic (TN) mode, a vertical alignment (VA) mode, an electrically controlled birefringence (ECB) mode, or an in-plane switching (IPS) mode.

12. The display device of claim 1, wherein the top surface of the functional transparent plate has a plurality of prisms consisting of first facets, on which a cholesteric liquid crystal layer does not exist, and second facets, on which a cholesteric liquid crystal exists.

13. The display device of claim 1, wherein the portions without the cholesteric liquid crystal material and the portions with the cholesteric liquid crystal material of the top surface of the functional transparent plate reflect light once, respectively, so that the reflected light is returned toward the second $\lambda/4$ retarder again.

14. The display device of claim 1, wherein the functional transparent plate has a top surface with an embossed carving or a depressed carving pattern and a bottom surface with an embossed carving or a depressed carving pattern, and apexes formed in the patterns of the two surfaces are formed to deviate from one another.

15. A display device comprising:

- a display panel assembly;
- a first $\lambda/4$ retarder that is provided on the display panel assembly;
- a reflective polarizer that is provided above the first $\lambda/4$ retarder to transmit incident light which is linearly polarized in a first direction and to reflect incident light which is linearly polarized in a second direction perpendicular to the first direction;
- a second $\lambda/4$ retarder that is provided on the reflective polarizer;
- a functional transparent plate that is provided on the second $\lambda/4$ retarder and which has a top surface with first facets and second facets, wherein the second facets transmit only a component of incident light which is polarized in a specific direction and reflect the remaining components;

31

a third $\lambda/4$ retarder that is provided under the display panel assembly; and

a lower polarizer that is provided under the third $\lambda/4$ retarder.

16. The display device of claim 15, wherein the second facets that are formed at the top surface of the functional transparent plate have a cholesteric liquid crystal layer thereon.

17. The display device of claim 15, further comprising an upper polarizer that is provided between the first $\lambda/4$ retarder and the reflective polarizer.

18. The display device of claim 15, wherein the reflective polarizer utilizes a dual brightness enhancement film (DBEF) that is produced based on reflectance anisotropy caused by the refractive index anisotropy, or delicate linear patterns.

19. The display device of claim 18, further comprising a backlight unit that is provided under the lower polarizer.

20. The display device of claim 15, wherein the functional transparent plate, the second $\lambda/4$ retarder, the reflective polarizer, the first $\lambda/4$ retarder, the display panel assembly, the third $\lambda/4$ retarder, and the lower polarizer are bonded by an adhesive agent.

21. The display device of claim 15, wherein spaces are formed between the functional transparent plate and the second $\lambda/4$ retarder due to a surface structure of either of a bottom surface of the functional transparent plate or a top surface of the second $\lambda/4$ retarder, and the spaces are filled with a filling material with a refractive index that is equal to an average of refractive indices of the functional transparent plate and the second $\lambda/4$ retarder.

22. The display device of claim 21, wherein the filling material for the spaces comprises an organic silicon-based material such as silicon resin.

23. The display device of claim 15, wherein the second facets which are formed at the top surface of the functional transparent plate only transmit either of a right-handed circularly polarized component or a left-handed circularly polarized component of incident light and reflect the remaining components.

24. The display device of claim 15, wherein the top surface of the functional transparent plate has a prismatic structure including the first facets, on which a cholesteric liquid crystal layer does not exist, and the second facets, on which a cholesteric liquid crystal exists.

25. The display device of claim 15, wherein the first facets and the second facets which are formed at the top surface of the functional transparent plate reflect light which is incident from the second $\lambda/4$ retarder once, respectively, so that the reflected light is returned toward the second $\lambda/4$ retarder again.

26. The display device of claim 15, wherein the functional transparent plate has a top surface with an embossed carving or a depressed carving pattern and a bottom surface with an embossed carving or a depressed carving pattern, and apexes formed in the patterns of the two surfaces are formed to deviate from one another.

27. A display device comprising:

a display panel assembly;

a first $\lambda/4$ retarder that is provided on the display panel assembly;

a reflective polarizer that is provided above the first $\lambda/4$ retarder to transmit incident light which is linearly polarized in a first direction and to reflect incident light which is linearly polarized in a second direction perpendicular to the first direction;

a second $\lambda/4$ retarder that is provided on the reflective polarizer; and

32

a functional transparent plate that is provided on the second $\lambda/4$ retarder and which has a top surface with first facets and second facets, wherein the second facets transmit only a component of incident light which is polarized in a specific direction and reflect the remaining components.

28. The display device of claim 27, wherein the second facets which are formed at the top surface of the functional transparent plate have a cholesteric liquid crystal layer thereon.

29. The display device of claim 27, wherein the second facets which are formed at the top surface of the functional transparent plate only transmit either of a right-handed circularly polarized component or a left-handed circularly polarized component of incident light and reflect the remaining components.

30. The display device of claim 27, wherein the top surface of the functional transparent plate has a prismatic structure including the first facets, on which a cholesteric liquid crystal layer does not exist, and the second facets, on which a cholesteric liquid crystal exists.

31. The display device of claim 27, wherein the functional transparent plate has a top surface with an embossed carving or a depressed carving pattern and a bottom surface with an embossed carving or a depressed carving pattern, and apexes formed in the patterns of the two surfaces are formed to deviate from one another.

32. The display device of claim 27, wherein the first facets and the second facets which are formed at the top surface of the functional transparent plate reflect light which is incident from the second $\lambda/4$ retarder once, respectively, so that the reflected light is returned toward the second $\lambda/4$ retarder again.

33. The display device claim 27, wherein spaces are formed between the functional transparent plate and the second $\lambda/4$ retarder due to a surface structure of either of a bottom surface of the functional transparent plate or a top surface of the second $\lambda/4$ retarder, and the spaces are filled with a filling material with a refractive index that is equal to an average of refractive indices of the functional transparent plate and the second $\lambda/4$ retarder.

34. The display device of claim 33, wherein the filling material for the spaces comprises an organic silicon-based material such as silicon resin.

35. A display device comprising:

a display panel assembly;

a selective reflection layer that is provided above the display panel assembly to transmit a component of exterior incident light which is circularly polarized in a first direction and to reflect a component of exterior incident light which is circularly polarized in a second direction perpendicular to the first direction; and

a functional transparent plate that is provided on the selective reflection layer and which has a top surface including portions without a cholesteric liquid crystal material and portions with a cholesteric liquid crystal material.

36. The display device of claim 35, further comprising a first polarizer that is provided between the selective reflection layer and the display panel assembly.

37. The display device of claim 36, further comprising a first $\lambda/4$ retarder that is provided between the first polarizer and the display panel assembly.

38. The display device of claim 36, further comprising a second $\lambda/4$ retarder that is provided between the selective reflection layer and the first polarizer.

33

39. The display device of claim 35, further comprising a second polarizer that is provided under the display panel assembly.

40. The display device of claim 39, further comprising a third $\lambda/4$ retarder that is provided between the second polarizer and the display panel assembly.

41. The display device of claim 35, wherein the selective reflection layer is formed of a cholesteric liquid crystal material.

42. The display device of claim 35, further comprising a backlight unit that is provided under the display panel assembly.

43. The display device of claim 35, wherein the display panel, the selective reflection layer, and the functional transparent plate are bonded using an adhesive agent.

44. The display device of claim 35, wherein spaces are formed between the functional transparent plate and the selective reflection layer due to a surface structure of either of a bottom surface of the functional transparent plate or a top surface of the selective reflection layer, and the spaces are filled with a filling material with a refractive index that is equal to an average of refractive indices of the functional transparent plate and the selective reflection layer.

45. The display device of claim 44, wherein the filling material for the spaces comprises an organic silicon-based material such as silicon resin.

46. The display device of claim 35, wherein the display panel assembly includes an LC layer with LC molecules that are aligned in a 90.degree.-twisted nematic (TN) mode, a vertical alignment (VA) mode, an electrically controlled birefringence (ECB) mode, or an in-plane switching (IPS) mode.

47. The display device of claim 35, wherein the top surface of the functional transparent plate has a plurality of prisms consisting of first facets, on which a cholesteric liquid crystal layer does not exist, and second facets, on which a cholesteric liquid crystal exists.

48. The display device of claim 35, wherein the first facets and the second facets formed at the top surface of the functional transparent plate reflect light which is incident from the selective reflection layer once, respectively, so that the reflected light is returned toward the selective reflection layer again.

49. The display device of claim 35, wherein the functional transparent plate has a top surface with an embossed carving or a depressed carving pattern and a bottom surface with an embossed carving or a depressed carving pattern, and apexes formed in the patterns of the two surfaces are formed to deviate from one another.

50. A display device comprising:

a display panel assembly;

a first $\lambda/4$ retarder that is provided on the display panel assembly;

a first polarizer that is provided on the first $\lambda/4$ retarder, wherein the first polarizer transmits external incident light which is linearly polarized in a first direction and reflects external incident light which is linearly polarized in a second direction perpendicular to the first direction;

a second $\lambda/4$ retarder that is provided on the first polarizer; a selective reflection layer that is provided on the second $\lambda/4$ retarder to transmit a component of incident light which is circularly polarized in a third direction and to reflect a component of incident light which is circularly polarized in a fourth direction perpendicular to the third direction;

a functional transparent plate that is provided on the selective reflection layer and which has a top surface with first

34

facets and second facets, wherein the second facets transmit only a component of incident light which is polarized in a specific direction and reflect the remaining components;

a third $\lambda/4$ retarder that is provided under the display panel assembly; and

a second polarizer that is provided under the third $\lambda/4$ retarder.

51. The display device of claim 50, wherein the second facets which are formed at the top surface of the functional transparent plate have a cholesteric liquid crystal layer thereon.

52. The display device of claim 50, wherein the selective reflection layer is formed of a cholesteric liquid crystal material.

53. The display device of claim 50, further comprising a backlight unit that is provided under the second polarizer.

54. The display device of claim 50, wherein the functional transparent plate, the selective reflection layer, the second $\lambda/4$ retarder, the first polarizer, the first $\lambda/4$ retarder, the display panel assembly, the third $\lambda/4$ retarder, and the second polarizer are bonded by an adhesive agent.

55. The display device of claim 50, wherein spaces are formed between the functional transparent plate and the selective reflection layer due to a surface structure of either of a bottom surface of the functional transparent plate or a top surface of the selective reflection layer, and the spaces are filled with a filling material with a refractive index that is equal to an average of refractive indices of the functional transparent plate and the selective reflection layer.

56. The display device of claim 55, wherein the filling material for the spaces comprises an organic silicon-based material such as silicon resin.

57. The display device of claim 50, wherein the second facets which are formed at the top surface of the functional transparent plate only transmit either of a right-handed circularly polarized component or a left-handed circularly polarized component of incident light and reflect the remaining components.

58. The display device of claim 50, wherein the top surface of the functional transparent plate has a prismatic structure including the first facets, on which a cholesteric liquid crystal layer does not exist, and the second facets, on which a cholesteric liquid crystal exists.

59. The display device of claim 50, wherein the first facets and the second facets which are formed at the top surface of the functional transparent plate reflect light which is incident from the selective reflection layer once, respectively, so that the reflected light is returned toward the selective reflection layer again.

60. The display device of claim 50, wherein the functional transparent plate has a top surface with an embossed carving or a depressed carving pattern and a bottom surface with an embossed carving or a depressed carving pattern, and apexes formed in the patterns of the two surfaces are formed to deviate from one another.

61. A display device comprising:

a display panel assembly;

a first $\lambda/4$ retarder that is provided on the display panel assembly;

a first polarizer that is provided on the first $\lambda/4$ retarder, wherein the first polarizer transmits light which is linearly polarized in a first direction and reflects light which is linearly polarized in a second direction perpendicular to the first direction;

a second $\lambda/4$ retarder that is provided on the first polarizer;

35

a selective reflection layer that is provided on the second $\lambda/4$ retarder to transmit light which is circularly polarized in a third direction and to reflect light which is circularly polarized in a fourth direction opposite to the third direction; and

a functional transparent plate that is provided on the selective reflection layer and which has a top surface with first facets and second facets, wherein the second facets transmit only light which is polarized in a specific direction and reflect the remaining light.

62. The display device of claim 61, wherein the second facets which are formed at the top surface of the functional transparent plate have a cholesteric liquid crystal layer thereon.

63. The display device of claim 61, wherein the second facets which are formed at the top surface of the functional transparent plate only transmit either of a right-handed circularly polarized component or a left-handed circularly polarized component of incident light and reflect the remaining components.

64. The display device of claim 61, wherein the top surface of the functional transparent plate has a prismatic structure including the first facets, on which a cholesteric liquid crystal layer does not exist, and the second facets, on which a cholesteric liquid crystal exists.

36

65. The display device of claim 61, wherein the first facets and the second facets which are formed at the top surface of the functional transparent plate reflect light which is incident from the selective reflection layer once, respectively, so that the reflected light is returned toward the selective reflection layer again.

66. The display device of claim 61, wherein the functional transparent plate has a top surface with an embossed carving or a depressed carving pattern and a bottom surface with an embossed carving or a depressed carving pattern, and apexes of the patterns of the two surfaces are formed to deviate from one another.

67. The display device of claim 61, wherein spaces are formed between the functional transparent plate and the selective reflection layer due to a surface structure of either of a bottom surface of the functional transparent plate or a top surface of the selective reflection layer, and the spaces are filled with a filling material with a refractive index that is equal to an average of refractive indices of the functional transparent plate and the selective reflection layer.

68. The display device of claim 67, wherein the filling material for the spaces comprises an organic silicon-based material such as silicon resin.

* * * * *

专利名称(译)	在显示面板组件上方的偏振器上设置的延迟器上具有棱镜结构的功能透明板的显示装置		
公开(公告)号	US7502085	公开(公告)日	2009-03-10
申请号	US11/404232	申请日	2006-04-14
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	三星DISPLAY CO. , LTD.		
[标]发明人	HIRAI AKIRA		
发明人	HIRAI, AKIRA		
IPC分类号	G02F1/1335		
CPC分类号	G02F1/133528 G02F1/133536 G02F1/133555 G02F1/13363 G02F2001/133538 G02F2001/133543 G02F2001/13355 G02F2001/133562 G02F2001/133638 G02F2413/03		
代理机构(译)	康托科尔伯恩LLP		
优先权	1020050034414 2005-04-26 KR 1020050034416 2005-04-26 KR		
其他公开文献	US20060238679A1		
外部链接	Espacenet USPTO		

摘要(译)

由反射偏振器， $\lambda/4$ 延迟器和具有第一小平面和第二小平面的功能透明板组成的光学系统提供在显示面板组件上，提高了外部光的利用效率，从而显示反射的亮度或者在反射模式下操作的透射LCD得到改善。在另一个实施例中，可以使用由 $\lambda/4$ 延迟器，选择性反射层和具有第一刻面和第二刻面的功能性透明板组成的光学系统。

