



US008520168B2

(12) **United States Patent**
Jang et al.

(10) **Patent No.:** **US 8,520,168 B2**
(45) **Date of Patent:** **Aug. 27, 2013**

(54) **REFLECTIVE COLOR DISPLAY DEVICE**

(56) **References Cited**

(75) Inventors: **Jae-eun Jang**, Seoul (KR); **Jae-eun Jung**, Seoul (KR); **Gae-hwang Lee**, Hwaseong-si (KR); **Kyu-young Hwang**, Seoul (KR)

U.S. PATENT DOCUMENTS

5,629,783	A *	5/1997	Kanbara et al.	349/70
5,719,647	A *	2/1998	Fujikawa et al.	349/40
6,373,538	B2 *	4/2002	Okumura et al.	349/106
2002/0015121	A1	2/2002	Okumura et al.	

(73) Assignee: **Samsung Electronics Co., Ltd.**, Gyeonggi-Do (KR)

FOREIGN PATENT DOCUMENTS

JP	6-289381	A	10/1994
JP	8-054618	A	2/1996
JP	08054618	A *	2/1996
JP	9-281489	A	10/1997
JP	2001-166340	A	6/2001
JP	2001166340	A *	6/2001
KR	1999-0035822	A	5/1999

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 263 days.

(21) Appl. No.: **12/926,949**

(22) Filed: **Dec. 20, 2010**

(65) **Prior Publication Data**

US 2011/0299014 A1 Dec. 8, 2011

(30) **Foreign Application Priority Data**

Jun. 8, 2010 (KR) 10-2010-0053994

(51) **Int. Cl.**
G02F 1/1333 (2006.01)
G02F 1/1335 (2006.01)

(52) **U.S. Cl.**
USPC **349/86; 349/106**

(58) **Field of Classification Search**
USPC 349/86, 106
See application file for complete search history.

* cited by examiner

Primary Examiner — Mike Qi

(74) *Attorney, Agent, or Firm* — Harness, Dickey & Pierce, P.L.C.

(57) **ABSTRACT**

Example embodiments are directed to a reflective color display device including a first substrate and a second substrate spaced apart from each other; a plurality of first and second electrodes respectively on the first and second substrates; a polymer dispersed liquid crystal (PDLC) layer between the first and second electrodes and including a polymer and liquid crystals in the polymer; and a CMY color filter on the second substrate.

14 Claims, 7 Drawing Sheets




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9



REFLECTIVE COLOR DISPLAY DEVICE

CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims priority under 35 U.S.C. §119 to Korean Patent Application No. 10-2010-0053994, filed on Jun. 8, 2010, in the Korean Intellectual Property Office, the disclosure of which is incorporated herein in its entirety by reference.

BACKGROUND

1. Field

Example embodiments relate to display devices, and to reflective color display devices including polymer dispersed liquid crystals (PDLC).

2. Description of the Related Art

Polymer dispersed liquid crystals (PDLC) scatter and/or transmit light by adjusting a difference in the refractive indices of liquid crystals and polymers. Accordingly, the PDLC are used in reflective display devices for displaying information or images by using an external light source. Reflective color display devices including the PDLC may include a color filter for color realization. In detail, light is transmitted through the color filter so as to display images having predetermined/desired colors.

The color filter may be, for example, a RGB color filter including red, green, and blue color filter layers. In this case, light transmissivity may be ideally $\frac{1}{3}$ of external incident light (white light). When a reflectivity of the PDLC is from about 10% to about 20%, a reflectivity of the reflective PDLC display device including a RGB filter may be from about 3.3% to about 6.6%, indicating that a very dark image is obtained therefrom. Accordingly, the brightness of the reflective display device needs to be improved.

SUMMARY

According to example embodiments, a reflective color display device includes a first substrate and a second substrate spaced apart from each other; a plurality of first and second electrodes respectively on the first and second substrates; a polymer dispersed liquid crystal (PDLC) layer between the first and second electrodes and including a polymer and liquid crystals in the polymer; and

a cyan magenta yellow (CMY) color filter on the second substrate and including cyan, magenta, and yellow color filter layers.

According to example embodiments, an absorption layer that absorbs incident light or a material layer that reflects the incident light outside a range of a viewing angle is on the first substrate.

According to example embodiments, the PDLC layer further includes a black dye.

According to example embodiments, the black dye includes a dichroic dye having optical anisotropy.

According to example embodiments, a reflection layer that reflects incident light is on the first substrate.

According to example embodiments, the first and second substrates are transparent substrates, and the first and second electrodes include transparent conductive materials.

According to example embodiments, the plurality of first electrodes correspond to the cyan, magenta, and yellow color filter layers, and the plurality of second electrodes are a single unit that functions as a common electrode.

According to example embodiments, the first and second electrodes are stripes that cross each other.

According to example embodiments, a reflective color display device includes a first substrate and a second substrate spaced apart from each other; a plurality of first and second electrodes respectively on the first and second substrates; a polymer dispersed liquid crystal (PDLC) layer between the first and second electrodes and including a polymer and liquid crystals in the polymer; a cyan magenta yellow (CMY) color filter on the second substrate and including cyan, magenta, and yellow color filter layers; and a reflection layer on the first substrate and configured to reflect incident light.

According to example embodiments, the PDLC layer further includes a black dye.

According to example embodiments, the black dye includes a dichroic dye having optical anisotropy.

According to example embodiments, the first and second substrates are transparent substrates, and the first and second electrodes include transparent conductive materials.

According to example embodiments, the plurality of first electrodes correspond to the cyan, magenta, and yellow color filter layers, and the plurality of second electrodes are a single unit that functions as a common electrode.

According to example embodiments, the first and second electrodes are stripes that cross each other.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other features and advantages will become more apparent by describing in detail example embodiments with reference to the attached drawings. The accompanying drawings are intended to depict example embodiments and should not be interpreted to limit the intended scope of the claims. The accompanying drawings are not to be considered as drawn to scale unless explicitly noted.

FIG. 1A illustrates absorption spectrums of red light, green light, and blue light;

FIG. 1B illustrates absorption spectrums of cyan light, magenta light, and yellow light;

FIG. 2 is a cross-sectional view illustrating a reflective color display device according to example embodiments;

FIG. 3 is a schematic view illustrating a driving method of the reflective color display device of FIG. 2, according to example embodiments;

FIG. 4 illustrates examples of colors that may be recognized by an observer using the reflective color display device of FIG. 2;

FIG. 5 is a cross-sectional view illustrating a reflective color display device according to example embodiments;

FIG. 6 is a schematic view illustrating a driving method of the reflective color display device of FIG. 5, according to example embodiments;

FIG. 7 illustrates examples of colors that may be recognized by an observer using the reflective color display device of FIG. 5;

FIG. 8 is a cross-sectional view illustrating a reflective color display device according to example embodiments; and

FIG. 9 is a cross-sectional view illustrating a reflective color display device according to example embodiments.

DETAILED DESCRIPTION

Detailed example embodiments are disclosed herein. However, specific structural and functional details disclosed herein are merely representative for purposes of describing example embodiments. Example embodiments may, how-

ever, be embodied in many alternate forms and should not be construed as limited to only the embodiments set forth herein.

Accordingly, while example embodiments are capable of various modifications and alternative forms, embodiments thereof are shown by way of example in the drawings and will herein be described in detail. It should be understood, however, that there is no intent to limit example embodiments to the particular forms disclosed, but to the contrary, example embodiments are to cover all modifications, equivalents, and alternatives falling within the scope of example embodiments. Like numbers refer to like elements throughout the description of the figures.

It will be understood that, although the terms first, second, etc. may be used herein to describe various elements, these elements should not be limited by these terms. These terms are only used to distinguish one element from another. For example, a first element could be termed a second element, and, similarly, a second element could be termed a first element, without departing from the scope of example embodiments. As used herein, the term "and/or" includes any and all combinations of one or more of the associated listed items.

It will be understood that when an element is referred to as being "connected" or "coupled" to another element, it may be directly connected or coupled to the other element or intervening elements may be present. In contrast, when an element is referred to as being "directly connected" or "directly coupled" to another element, there are no intervening elements present. Other words used to describe the relationship between elements should be interpreted in a like fashion (e.g., "between" versus "directly between", "adjacent" versus "directly adjacent", etc.).

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of example embodiments. As used herein, the singular forms "a", "an" and "the" are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms "comprises", "comprising", "includes" and/or "including", when used herein, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

It should also be noted that in some alternative implementations, the functions/acts noted may occur out of the order noted in the figures. For example, two figures shown in succession may in fact be executed substantially concurrently or may sometimes be executed in the reverse order, depending upon the functionality/acts involved.

FIG. 1A illustrates absorption spectrums of red light, green light, and blue light, and FIG. 1B illustrates absorption spectrums of cyan light, magenta light, and yellow light. Referring to FIG. 1A, red light, green light, and blue light have different wavelength ranges. Referring to FIG. 1B, cyan light is a combination of green light and blue light, and magenta light is a combination of red light and blue light, and yellow light is a combination of green light and red light.

When a RGB color filter formed of red, green, and blue color filter layers is used as a color filter, a light transmissivity of the RGB color filter with respect to external white light may be about $\frac{1}{3}$. Meanwhile, when a CMY color filter including cyan, magenta, and yellow color filter layers is used as a color filter, a light transmissivity of the CMY color filter with respect to external white light may be about $\frac{2}{3}$. Thus the light transmissivity of the CMY color filter is about twice as that of the RGB color filter. Accordingly, when the CMY color filter is used in a reflective color display device, reflectivity of the

reflective color display device is increased so as to increase the brightness of the reflective color display device and to generate clearer images. Therefore, according to example embodiments, the CMY color filter including cyan, magenta, and yellow color filter layers is used as a color filter for color realization.

FIG. 2 is a cross-sectional view illustrating a reflective color display device according to example embodiments.

Referring to FIG. 2, the reflective color display device includes a plurality of pixel units **100**, which each comprise sub-pixels having desired colors, namely cyan, magenta, and yellow sub-pixels **140C**, **140M**, and **140Y**. The pixel units **100** may each be formed of a cyan sub-pixel **140C**, a magenta sub-pixel **140M**, and a yellow sub-pixel **140Y**. In FIG. 2, one of the pixel units **100** is shown for convenience of description. The pixel unit **100** may be formed of a cyan sub-pixel **140C**, a magenta sub-pixel **140M**, and a yellow sub-pixel **140Y**. The cyan, magenta, and yellow sub-pixels **140C**, **140M**, and **140Y** respectively correspond to cyan, magenta, and yellow color filter layers **141C**, **141M**, and **141Y**, which will be described later.

The pixel units **100** include first and second substrates **110** and **120** spaced apart from each other, a plurality of first and second electrodes **112** and **122** respectively formed on the first and second substrates **110** and **120**, a polymer dispersed liquid crystal (PDLC) layer **150** formed between the first and second electrodes **112** and **122**, a CMY color filter, which includes the cyan, magenta, and yellow color filter layers **141C**, **141M**, and/or **141Y**, formed on the second substrate **120**, and an absorption layer **131** formed on the first substrate **110**.

In detail, the first substrate **110**, which is a lower substrate, and the second substrate **120**, which is an upper substrate, may be transparent substrates. The first and second substrates **110** and **120** may be formed of glass or plastic. However, the first and second substrates **110** and **120** are not limited thereto and may also be formed of other materials. The absorption layer **131**, which absorbs incident light, is formed on an upper surface of the first substrate **110**. Alternatively, unlike shown in FIG. 2, the absorption layer **131** may also be formed on a lower surface of the first substrate **110**. Meanwhile, according to the example embodiments, a material layer (not shown) that reflects incident light at a predetermined/desired angle may be applied instead of the absorption layer **131**. The material layer reflects the incident light out of a range of a viewing angle of an observer, thus functioning as the absorption layer **131** within the range of the viewing angle of the observer.

The CMY color filter is disposed on a lower surface of the second substrate **120** that is the upper substrate. The CMY color filter includes the cyan color filter layer **141C**, the magenta color filter layer **141M**, and/or the yellow color filter layer **141Y**.

A plurality of first electrodes **112** are formed on the first substrate **110**, on which the absorption layer **131** is formed, and the plurality of second electrodes **122** are formed on the second substrate **120**, on which the CMY color filter is formed. Unlike shown in FIG. 2, the CMY color filter may also be formed on lower surfaces of the second electrodes **122**. For example, the first and second electrodes **112** and **122** may be formed of a transparent conductive material, such as an indium tin oxide (ITO). In a passive matrix (PM) type display device, the first electrodes **112** may be in a form of stripes and be arranged parallel to one another, and the second electrodes **122** may also be in a form of stripes and arranged parallel to one another across the first electrodes **112**. In an active matrix (AM) type display device, the first electrodes

112 are formed in a form corresponding to the cyan sub-pixels **140C**, the magenta sub-pixels **140M**, and/or the yellow sub-pixels **140Y**, and the second electrodes **122** may be formed as a single unit so as to function as a common electrode.

The PDLC layer **150** is formed between the first electrodes **112** and the second electrodes **122**. The PDLC layer **150** includes a polymer **151** and liquid crystals **152** dispersed in the polymer **151**. The PDLC layer **150** may scatter or transmit light by adjusting a difference in the refractive indices of the liquid crystals **152** and the polymer **151**.

FIG. 3 is a schematic view illustrating a driving method of the reflective color display device of FIG. 2, according to example embodiments.

Referring to FIG. 3, when a desired voltage V_1 is applied to the first and second electrodes **112** and **122** corresponding to the cyan sub-pixel **140C**, liquid crystal molecules (not shown) of the liquid crystals **152** corresponding to the cyan sub-pixel **140C** are aligned parallel to an electrical field formed between the first electrodes **112** and the second electrodes **122**. Accordingly, a refractive index of the liquid crystals **152** becomes somewhat similar to that of the polymer **151**, and thus the PDLC layer **150** of the cyan sub-pixel **140C** may become transparent. Accordingly, in the cyan sub-pixel **140C**, only cyan light C among external white light W transmits through the cyan color filter layer **141C**, and then through the PDLC layer **150** to be absorbed by the absorption layer **131**. In the magenta and yellow sub-pixels **140M** and **140Y** to which no voltage is applied, the PDLC layer **150** scatters incident light due to a difference in the refractive indices of the polymer **151** and the liquid crystals **152**. Accordingly, in the magenta sub-pixel **140M**, only magenta light M among external white light W transmits through the magenta color filter layer **141M**, is scattered by the PDLC layer **150**, and is emitted to the outside through the second substrate **120**, which is the upper substrate. Also, in the yellow sub-pixel **140Y**, only yellow light Y among external white light W transmits through the yellow color filter layer **141Y**, is scattered by the PDLC layer **150**, and is emitted to the outside through the second substrate **120**, which is the upper substrate. As described above, the cyan sub-pixel **140C** displays black color, and the magenta and yellow sub-pixels **140M** and **140Y** respectively emit magenta light M and yellow light Y such that the observer recognizes the pixel units **100** as a red color.

In the above-described manner, various colors may be realized through the pixel units **100** by adjusting voltages each applied to the cyan sub-pixels **140C**, the magenta sub-pixels **140M**, and/or the yellow sub-pixels **140Y**. FIG. 4 illustrates example five colors (white, blue, red, green, and black) that may be recognized by an observer by adjusting voltages applied to each of the cyan sub-pixels **140C**, the magenta sub-pixels **140M**, and the yellow sub-pixels **140Y** of the reflective color display device of FIG. 2.

As described above, by using the CMY color filter in the reflective color display device including the PDLC layer **150**, reflectivity of the reflective color display device may be improved, compared to when using a RGB color filter, which increases the brightness of a screen, and clearer images are obtained accordingly.

FIG. 5 is a cross-sectional view illustrating a reflective color display device according to example embodiments.

Referring to FIG. 5, the reflective color filter display device includes a plurality of pixel units **200** which are each formed of sub-pixels having desired colors, namely cyan, magenta, and/or yellow sub-pixels **240C**, **240M**, and **240Y**. In FIG. 5, one of the pixel units **200** is shown for convenience of descrip-

tion. The pixel unit **200** may be formed of a cyan sub-pixel **240C**, a magenta sub-pixel **240M**, and/or a yellow sub-pixel **240Y**.

The pixel units **200** include first and second substrates **210** and **220** spaced apart from each other, a plurality of first and second electrodes **212** and **222** respectively formed on the first and second substrates **210** and **220**, a PDLC layer **250** formed between the first and second electrodes **212** and **222**, and a CMY color filter, which includes the cyan, magenta, and/or yellow color filter layers **241C**, **241M**, and **241Y**, and a reflection layer **232** formed on the first substrate **210**.

The first substrate **210**, which is a lower substrate, and the second substrate **220**, which is an upper substrate, may be transparent substrates. The reflection layer **232** that reflects incident light is formed on an upper surface of the first substrate **210**. Alternatively, the reflection layer **232** may also be formed on a lower surface of the first substrate **210**, unlike shown in FIG. 5.

The plurality of first electrodes **212** are formed on an upper surface of the reflection layer **232** of the first substrate **210**, and the plurality of second electrodes **222** are formed on a lower surface of the second substrate **220**. The first and second electrodes **212** and **222** may be formed of transparent conductive materials as described above. In a PM type display device, the first electrodes **212** may be in a form of stripes and be arranged parallel to one another, and the second electrodes **222** may also be in a form of stripes and arranged parallel to one another across the first electrodes **212**. In an AM type display device, the first electrodes **212** are formed in a form corresponding to the cyan, magenta, and/or yellow sub-pixels **240C**, **240M**, and **240Y**, and the second electrodes **222** may be formed as a single unit so as to function as a common electrode.

The CMY color filter is formed on upper surfaces of the first electrodes **212**. The CMY color filter includes the cyan color filter layer **241C**, the magenta color filter layer **241M**, and/or the yellow color filter layer **241Y**. Unlike as shown in FIG. 5, the CMY color filter may also be formed on lower surfaces of the first electrodes **212**. The PDLC layer **250** is formed between the first electrodes **212** and the second electrodes **222**. The PDLC layer **250** includes a polymer **251** and liquid crystals **252** dispersed in the polymer **251**.

FIG. 6 is a schematic view illustrating a driving method of the reflective color display device of FIG. 5, according to example embodiments.

Referring to FIG. 6, when a desired voltage V_2 is applied to the first and second electrodes **212** and **222** corresponding to the cyan and yellow sub-pixel **240C** and **240Y**, liquid crystal molecules (not shown) of the liquid crystals **252** corresponding to the cyan and yellow sub-pixel **240C** and **240Y** are aligned parallel to an electrical field formed between the first electrodes **212** and the second electrodes **222**. Accordingly, a refractive index of the liquid crystals **252** becomes approximately similar to that of the polymer **251**, and thus the PDLC layer **250** of the cyan sub-pixel **240C** becomes transparent. Accordingly, external white light W transmits through the PDLC layer **250** and is incident on the cyan color filter layer **241C**. Also, only cyan light C among the white light W transmits through the cyan color filter layer **241C**, is reflected by the reflection layer **232**, and emitted to the outside through the second substrate **220**. In the yellow sub-pixel **240Y**, the external white light W transmits through the PDLC layer **250** and is incident on the yellow color filter layer **241Y**. Then, only yellow light Y transmits through the yellow color filter layer **241Y** among the white light W, is reflected by the reflection layer **232**, and emitted to the outside through the second substrate **220**. In the magenta sub-pixel **240M** to

which no voltage is applied, the PDLC layer **250** scatters the incident light due to a difference in the refractive indices of the polymer **251** and the liquid crystals **252**. Accordingly, the external white light **W** is scattered by the PDLC layer **250** in the magenta sub-pixel **240M** and is emitted to the outside through the second substrate **220**. As described above, the magenta sub-pixel **240M** displays white color, and the cyan and yellow sub-pixels **240C** and **240Y** respectively emit cyan light **C** and yellow light **Y** such that the observer recognizes the pixel unit **200** as a green color. In the reflective color display device of example embodiments, white color characteristics of images are increased, compared to the previous example embodiments.

As described above, various colors may be obtained through the pixel units **200** by adjusting voltages applied to the cyan, magenta, and/or yellow sub-pixels **240C**, **240M**, and **240Y**. FIG. 7 illustrates example five colors (white, blue, red, green, and black) that may be recognized by an observer by adjusting voltages applied to each of the cyan sub-pixels **240C**, the magenta sub-pixels **240M**, and/or the yellow sub-pixels **240Y** of the reflective color display device of FIG. 5.

FIG. 8 is a cross-sectional view illustrating a reflective color display device according to example embodiments.

Referring to FIG. 8, the reflective color filter display device includes a plurality of pixel units **300** which are each formed of sub-pixels having colors, cyan, magenta, and yellow sub-pixels **340C**, **340M**, and/or **340Y**. In detail, the pixel units **300** may each be formed of a cyan sub-pixel **340C**, a magenta sub-pixel **340M**, and/or a yellow sub-pixel **340Y**.

The pixel units **300** include first and second substrates **310** and **320** spaced apart from each other, a plurality of first and second electrodes **312** and **322** respectively formed on the first and second substrates **310** and **320**, a PDLC layer **350** that is formed between the first and second electrodes **312** and **322** and includes a black dye **353**, and a CMY color filter formed on the second substrate **320**, and a reflection layer **332** formed on the first substrate **310**.

The first and second substrates **310** and **320** may be transparent substrates. The reflection layer **332** that reflects incident light is formed on an upper surface of the first substrate **310**. Alternatively, the reflection layer **322** may also be formed on a lower surface of the first substrate **310**, unlike shown in FIG. 8. The CMY color filter is formed on a lower surface of the second substrate **320**, which is an upper substrate. The CMY color filter includes cyan, magenta, and/or yellow color filter layers **341C**, **341M**, and **341Y**.

The first electrodes **312** are formed on the first substrate **310**, on which the reflection layer **332** is formed, and the second electrodes **322** are formed on the second substrate **320**, on which the CMY color filter is formed. Unlike as shown in FIG. 8, the CMY color filter may also be formed on lower surfaces of the second electrodes **322**. The first and second electrodes **312** and **322** may be formed of a transparent conductive material. In a PM type display device, the first electrodes **312** may be in a form of stripes and be arranged parallel to one another, and the second electrodes **322** may also be in a form of stripes and arranged parallel to one another across the first electrodes **312**. In an AM type display device, the first electrodes **312** are formed in a form corresponding to the cyan sub-pixels **340C**, the magenta sub-pixels **340M**, and/or the yellow sub-pixels **340Y**, and the second electrodes **322** may be formed as a single unit so as to function as a common electrode.

The PDLC layer **350** is formed between the first electrodes **312** and the second electrodes **322**. The PDLC layer **350** includes a polymer **351**, liquid crystals **352** dispersed in the

polymer **351**, and/or the black dye **353** formed in the liquid crystals **352**. The black dye **353** may be a dichroic dye having optical anisotropy.

The reflective color display device of FIG. 8 is driven in the following manner. For example, no voltage is applied to the cyan sub-pixel **340C**, and voltages are applied to the magenta and yellow sub-pixels **340M** and **340Y**. In this case, liquid crystal molecules (not shown) and the black dye **353** included in the liquid crystals **352** of the cyan sub-pixels **340C** are irregularly aligned. Accordingly, in the cyan sub-pixel **340C**, only cyan light among external white light transmits through the cyan color filter layer **341C**, and the cyan light is absorbed by the black dye **353** in the PDLC layer **350**. Liquid crystal molecules and the black dye **353** included in the liquid crystals **352** corresponding to the magenta and yellow sub-pixels **340M** and **340Y** are aligned parallel to an electric field applied thereto, and the PDLC layer **350** becomes transparent accordingly. Consequently, in the magenta sub-pixel **340M**, only magenta light among external white light transmits through the magenta color filter layer **341M**, and the magenta light transmits through the PDLC layer **350** and then is reflected by the reflection layer **332**, and is emitted to the outside through the second substrate **320**, which is the upper substrate. In the yellow sub-pixel **340Y**, only yellow light among external white light transmits through the yellow color filter layer **341Y**, and the yellow light transmits through the PDLC layer **350** and is reflected by the reflection layer **332**, and is emitted to the outside through the second substrate **320**, which is the upper substrate. As described above, the cyan sub-pixel **340C** displays black color, and the magenta and yellow sub-pixels **340M** and **340Y** respectively emit magenta light **M** and yellow light **Y** such that the observer recognizes the pixel units **300** as a red color. As described above, various colors may be realized through the pixel units **300** by adjusting voltages each applied to the cyan, magenta, and/or yellow sub-pixels **340C**, **340M**, and **340Y**.

FIG. 9 is a cross-sectional view illustrating a reflective color display device according to example embodiments.

Referring to FIG. 9, the reflective color filter display device includes a plurality of pixel units **400** which are each formed of sub-pixels **440C**, **440M**, and **440Y** having desired colors. In detail, the pixel units **400** each may be formed of a cyan sub-pixel **440C**, a magenta sub-pixel **440M**, and a yellow sub-pixel **440Y**.

The pixel units **400** include first and second substrates **410** and **420** spaced apart from each other, a plurality of first and second electrodes **412** and **422** respectively formed on the first and second substrates **410** and **420**, a PDLC layer **450** that is formed between the first and second electrodes **412** and **422** and includes a black dye **453**, and a CMY color filter and a reflection layer **432** formed on the first substrate **410**.

The first and second substrates **410** and **420** may be transparent substrates. The reflection layer **432** that reflects incident light is formed on an upper surface of the first substrate **410**. Alternatively, the reflection layer **432** may also be formed on a lower surface of the first substrate **410**, unlike shown in FIG. 9.

The first electrodes **412** are formed on an upper surface of the reflection layer **432**, and the second electrodes **422** are formed on a lower surface of the second substrate **420**. The first and second electrodes **412** and **422** may be formed of a transparent conductive material. In a PM type display device, the first electrodes **412** may be in a form of stripes and be arranged parallel to one another, and the second electrodes **422** may also be in a form of stripes and arranged parallel to one another across the first electrodes **412**. In an AM type display device, the first electrodes **412** are formed in a form

corresponding to the cyan, magenta, and/or yellow sub-pixels **440C**, **440M**, and **440Y**, and the second electrodes **422** may be formed as a single unit so as to function as a common electrode.

The CMY color filter is formed on an upper surface of the first electrodes **412**. The CMY color filter includes the cyan, magenta, and yellow color filter layers **441C**, **441M**, and/or **441Y**. Unlike shown in FIG. 9, the CMY color filter may also be formed on a lower surface of the first electrodes **412**. The PDLC layer **450** is formed between the first electrodes **412** and the second electrodes **422**. The PDLC layer **450** includes a polymer **451**, liquid crystals **452** dispersed in the polymer **451**, and/or the black dye **453** formed in the liquid crystals **452**. The black dye **453** may be dichroic dye having optical anisotropy.

The reflective color display device of FIG. 9 is driven in the following manner. For example, no voltage is applied to the cyan sub-pixel **440C**, and voltages are applied to the magenta and yellow sub-pixels **440M** and **440Y**. In this case, liquid crystal molecules (not shown) and the black dye **453** included in the liquid crystals **452** of the cyan sub-pixels **440C** are irregularly aligned. Accordingly, in the cyan sub-pixel **440C**, external white light is absorbed by the black dye **453** in the PDLC layer **450**. Liquid crystal molecules and the black dye **453** included in the liquid crystals **452** corresponding to the magenta and yellow sub-pixels **440M** and **440Y** are aligned parallel to an electric field applied thereto, and the PDLC layer **450** becomes transparent accordingly. Consequently, in the magenta sub-pixel **440M**, external white light transmits through the PDLC layer **450**, and only magenta light among the transmitted white light transmits through the magenta color filter layer **441M**. Then the magenta light is reflected by the reflection layer **432**, and is emitted to the outside through the second substrate **420**, which is the upper substrate. In the yellow sub-pixel **440Y**, external white light transmits through the PDLC layer **450**, and only yellow light among the transmitted external white light transmits through the yellow color filter layer **441Y**. Then the yellow light is reflected by the reflection layer **432**, and is emitted to the outside through the second substrate **420**, which is the upper substrate. As described above, the cyan sub-pixel **440C** displays black color, and the magenta and yellow sub-pixels **440M** and **440Y** respectively emit magenta light and yellow light such that the observer recognizes the pixel unit **400** as a red color. As described above, various colors may be realized through the pixel units **400** by adjusting voltages each applied to the cyan, magenta, and yellow sub-pixels **440C**, **440M**, and **440Y**.

As described above, according to example embodiments, by using the CMY filter including cyan, magenta, and yellow color filter layers, a reflective color display device having improved reflectivity, compared to when using a RGB color filter, may be manufactured.

Example embodiments having thus been described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the intended spirit and scope of example embodiments, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following claims.

What is claimed is:

1. A reflective color display device comprising:

a first substrate and a second substrate spaced apart from each other;

a plurality of first and second electrodes respectively on the first and second substrates;

a polymer dispersed liquid crystal (PDLC) layer between the first and second electrodes and including a polymer and liquid crystals in the polymer;

a cyan magenta yellow (CMY) color filter on the second substrate and including cyan, magenta, and yellow color filter layers, each one of the cyan, magenta, and yellow color filter layers corresponding to one of the plurality of first electrodes and one of the plurality of second electrodes; and

one of an absorption layer and a reflection layer on the first substrate configured to control a color of an emitted light by applying a voltage to the first and second electrodes corresponding to at least one of the cyan, magenta, and yellow color filter layers causing the liquid crystals of the PDLC layer to allow an external light travelling through the CMY color filter and the PDLC layer to be one of absorbed and reflected by the absorption layer and reflection layer respectively, such that no visible light is emitted from the reflective color display device, when no voltage is applied to the first and second electrodes corresponding to the at least one of the cyan, magenta, and yellow color filter layers the liquid crystals of the PDLC layer reflect visible light through the at least one of the cyan, magenta, and yellow color filter layers.

2. The reflective color display device of claim 1, wherein the absorption layer absorbs incident light and the reflection layer reflects incident light outside a range of a viewing angle.

3. The reflective color display device of claim 1, wherein the PDLC layer further includes a black dye.

4. The reflective color display device of claim 3, wherein the black dye includes a dichroic dye having optical anisotropy.

5. The reflective color display device of claim 3, wherein the reflection layer that reflects incident light is on the first substrate.

6. The reflective color display device of claim 1, wherein the first and second substrates are transparent substrates, and the first and second electrodes include transparent conductive materials.

7. The reflective color display device of claim 1, wherein the plurality of first electrodes correspond to the cyan, magenta, and yellow color filter layers, and the plurality of second electrodes are a single unit that functions as a common electrode.

8. The reflective color display device of claim 1, wherein the first and second electrodes are stripes that cross each other.

9. A reflective color display device comprising:

a first substrate and a second substrate spaced apart from each other;

a plurality of first and second electrodes respectively on the first and second substrates;

a polymer dispersed liquid crystal (PDLC) layer between the first and second electrodes and including a polymer and liquid crystals in the polymer;

a cyan magenta yellow (CMY) color filter on the second substrate and including cyan, magenta, and yellow color filter layers, each one of the cyan, magenta, and yellow color filter layers corresponding to one of the plurality of first electrodes and one of the plurality of second electrodes; and

a reflection layer on the first substrate and configured to reflect incident light outside a range of a viewing angle, the reflection layer configured to control a color of an emitted light by applying a voltage to the first and second electrodes corresponding to at least one of the cyan, magenta, and yellow color filter layers causing the liquid

crystals of the PDLC layer to allow an external light travelling through the CMY color filter and the PDLC layer to be reflected by the reflection layer such that no visible light is emitted from the reflective color display device, when no voltage is applied to the first and second electrodes corresponding to the at least one of the cyan, magenta, and yellow color filter layers the liquid crystals of the PDLC layer reflect visible light through the at least one of the cyan, magenta, and yellow color filter layers.

10 **10.** The reflective color display device of claim **9**, wherein the PDLC layer further includes a black dye.

11. The reflective color display device of claim **10**, wherein the black dye includes a dichroic dye having optical anisotropy.

15 **12.** The reflective color display device of claim **9**, wherein the first and second substrates are transparent substrates, and the first and second electrodes include transparent conductive materials.

20 **13.** The reflective color display device of claim **9**, wherein the plurality of first electrodes correspond to the cyan, magenta, and yellow color filter layers, and the plurality of second electrodes are a single unit that functions as a common electrode.

25 **14.** The reflective color display device of claim **9**, wherein the first and second electrodes are stripes that cross each other.

* * * * *

专利名称(译)	反光彩色显示装置		
公开(公告)号	US8520168	公开(公告)日	2013-08-27
申请号	US12/926949	申请日	2010-12-20
[标]申请(专利权)人(译)	三星电子株式会社		
申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
当前申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
[标]发明人	JANG JAE EUN JUNG JAE EUN LEE GAE HWANG HWANG KYU YOUNG		
发明人	JANG, JAE-EUN JUNG, JAE-EUN LEE, GAE-HWANG HWANG, KYU-YOUNG		
IPC分类号	G02F1/1333 G02F1/1335		
CPC分类号	G02F1/1334 G02F1/133553 G02F1/133514 G02F1/13725 G02F2201/52		
优先权	1020100053994 2010-06-08 KR		
其他公开文献	US20110299014A1		
外部链接	Espacenet USPTO		

摘要(译)

示例实施例涉及一种反射彩色显示装置，包括彼此间隔开的第一基板和第二基板；分别在第一和第二基板上的多个第一和第二电极；聚合物分散液晶（PDLC）层，位于第一和第二电极之间，并在聚合物中包含聚合物和液晶；和第二基板上的CMY滤色器。

