



US008064006B2

(12) **United States Patent**
Park et al.

(10) **Patent No.:** **US 8,064,006 B2**
(45) **Date of Patent:** **Nov. 22, 2011**

(54) **BACKLIGHT ASSEMBLY AND METHOD OF ASSEMBLING THE SAME AND LIQUID CRYSTAL DISPLAY INCLUDING BACKLIGHT ASSEMBLY**

(58) **Field of Classification Search** 349/58, 349/64, 61, 65; 362/97.2, 97.3, 97.1, 244, 362/600; 445/24

See application file for complete search history.

(75) Inventors: **Jin-Hee Park**, Cheonan-si (KR);
Bong-Hyun You, Yongin-si (KR);
Jae-Chang Choi, Yongin-si (KR)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2006/0216982 A1* 9/2006 Ishida 439/331
2007/0002590 A1 1/2007 Jang et al.
2007/0053176 A1* 3/2007 Chou 362/97
2007/0153515 A1* 7/2007 Hong et al. 362/237

(73) Assignee: **Samsung Electronics Co., Ltd.**,
Suwon-Si (KR)

FOREIGN PATENT DOCUMENTS

WO WO2008108039 9/2008

OTHER PUBLICATIONS

European Search Report dated May 3, 2009 for Application No. 08021855.5-2205.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 312 days.

* cited by examiner

(21) Appl. No.: **12/205,152**

Primary Examiner — Brian M. Healy

(22) Filed: **Sep. 5, 2008**

Assistant Examiner — Jerry Blevins

(65) **Prior Publication Data**

US 2009/0174838 A1 Jul. 9, 2009

(74) *Attorney, Agent, or Firm* — F. Chau & Associates, LLC

(30) **Foreign Application Priority Data**

Jan. 3, 2008 (KR) 10-2008-0000817

(57) **ABSTRACT**

A backlight assembly includes a light source unit including a circuit board, a light source disposed on a first plane of the circuit board, and at least one connection unit disposed on a second plane opposite to the first plane of the circuit board and electrically connected to the light source, a receiving container having a bottom plate and sidewalls extending from edges of the bottom plate and receiving the light source unit, the bottom plate including at least one opening portion in which the connection unit is inserted and exposed to the outside, and at least one driving unit disposed at a rear surface of the receiving container and connected to the connection unit for driving the light source unit.

(51) **Int. Cl.**

G02F 1/1333 (2006.01)
G02F 1/1335 (2006.01)
G09F 13/04 (2006.01)
G09F 13/08 (2006.01)
F21V 5/00 (2006.01)
F21V 7/04 (2006.01)
H01J 9/24 (2006.01)

17 Claims, 8 Drawing Sheets

(52) **U.S. Cl.** **349/58; 349/61; 349/64; 349/65; 362/97.1; 362/97.2; 362/244; 362/600; 445/24**




FIG. 1B




FIG. 1C




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6





FIG. 7



**BACKLIGHT ASSEMBLY AND METHOD OF
ASSEMBLING THE SAME AND LIQUID
CRYSTAL DISPLAY INCLUDING
BACKLIGHT ASSEMBLY**

CROSS-REFERENCE TO RELATED
APPLICATION

This application claims priority from Korean Patent Application No. 10-2008-0000817 filed on Jan. 3, 2008, the disclosure of which is incorporated by reference herein.

BACKGROUND OF THE INVENTION

1. Technical Field

The present disclosure relates to a backlight assembly and a method of assembling the same, and a liquid crystal display including the backlight assembly, and more particularly, to a method of assembling the backlight assembly, and a liquid crystal display including the backlight assembly.

2. Discussion of the Related Art

Liquid crystal displays (LCDs) are one of the most widely used flat panel displays. LCDs include a liquid crystal panel for displaying an image and a backlight assembly for supplying light to the liquid crystal panel. The backlight assembly typically includes a light source that generates light, one or more optical members for diffusing/focusing the light distributed from the light source sheets, and a housing unit for receiving the light source and the one or more optical members. The backlight assembly may further include a driving unit that can drive the light source, e.g., an inverter assembly.

Recently, a light emitting diode (LED) characterized by low power consumption and high brightness has been widely used as a light source unit of the backlight assembly. For example, a plurality of LEDs are mounted on a printed circuit board to form a light source unit. As the size of an LCD panel increases, a direct-type light source unit may be disposed under the LCD panel.

Conventional direct-type backlight assemblies include a plurality of lamps as the light source unit and are received horizontally in a receiving container. A driving unit may be disposed in the rear of the receiving container. In this case, the receiving container may include a plurality of opening portions, e.g., wire leads, to connect the light source unit with the driving unit.

In the aforementioned backlight assembly, however, it is necessary to additionally attach a blocking member, e.g., tape, for preventing light leakage or infiltration of foreign matter through the opening portions formed in the receiving container. Accordingly, the backlight assembly may be more difficult to assemble and the production cost of the backlight assembly may increase.

SUMMARY OF THE INVENTION

Embodiments of the present invention provide a method of assembling the backlight assembly.

Embodiments of the present invention also provide a liquid crystal display including the backlight assembly.

According to an exemplary embodiment of the present invention, there is provided a backlight assembly including a light source unit including a circuit board, a light source disposed on a first plane of the circuit board, and at least one connection unit disposed on a second plane opposite to the first plane of the circuit board and electrically connected to the light source, a receiving container having a bottom plate and sidewalls extending from edges of the bottom plate and

receiving the light source unit, the bottom plate including at least one opening portion in which the connection unit is inserted and exposed to the outside, and at least one driving unit disposed at a rear surface of the receiving container, connected to the connection unit and driving the light source unit.

According to an exemplary embodiment of the present invention, there is provided a method of assembling a backlight assembly, the method including preparing a light source unit including a circuit board, a light source disposed on a first plane of the circuit board, and at least one connection unit disposed on a second plane opposite to the first plane of the circuit board and electrically connected to the light source, and a receiving container having a bottom plate and sidewalls extending from edges of the bottom plate and receiving the light source unit, the bottom plate including at least one opening portion in which the connection unit is inserted and exposed to the outside, assembling the light source unit with the receiving container by receiving the light source unit in the receiving container so that the connection unit is exposed to the outside through the opening portion, and disposing at least one driving unit at a rear surface of the receiving container and connecting the driving unit to the exposed connection unit.

According to an exemplary embodiment of the present invention, there is provided a liquid crystal display including a liquid crystal display panel displaying an image, and a backlight assembly disposed under the liquid crystal display panel and providing light to the liquid crystal display panel, wherein the backlight assembly includes a light source unit including a circuit board, a light source disposed on a first plane of the circuit board, and at least one connection unit disposed on a second plane opposite to the first plane of the circuit board and electrically connected to the light source, a receiving container having a bottom plate and sidewalls extending from edges of the bottom plate and receiving the light source unit, the bottom plate including at least one opening portion in which the connection unit is inserted and exposed to the outside, and at least one driving unit disposed at a rear surface of the receiving container and connected to the connection unit for driving the light source unit.

BRIEF DESCRIPTION OF THE DRAWINGS

Exemplary embodiments of the present invention will become apparent by reference to the following detailed description taken in conjunction with the accompanying drawings, wherein:

FIG. 1A is a perspective view of an exemplary light source unit used in a backlight assembly according to an exemplary embodiment of the present invention;

FIG. 1B is a perspective view illustrating a rear surface of the light source unit shown in FIG. 1A;

FIG. 1C is a perspective view illustrating a rear surface of another exemplary light source unit according to an exemplary embodiment of the present invention;

FIG. 2 is an exploded perspective view of a backlight assembly according to an exemplary embodiment of the present invention;

FIG. 3 is a perspective view illustrating a rear surface of the backlight assembly shown in FIG. 2;

FIG. 4A is an enlarged view of a portion "A" shown in FIG. 3;

FIG. 4B is an enlarged view illustrating another example of the portion "A" shown in FIG. 3;

FIG. 5 is an exploded perspective view of a backlight assembly according to an exemplary embodiment of the present invention;

FIG. 6 is a perspective view illustrating a rear surface of the backlight assembly shown in FIG. 5; and

FIG. 7 is an exploded perspective view of a liquid crystal display according to an exemplary embodiment of the present invention, including the backlight assembly shown in FIG. 2.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

Exemplary embodiments of the present invention will be described in detail with reference to the accompanying drawings. The present invention may, however, be embodied in many different forms and should not be construed as being limited to the embodiments set forth herein. Like reference numerals refer to like elements throughout the specification.

A light source unit used in a backlight assembly according to an exemplary embodiment of the present invention will be described in detail with reference to FIGS. 1A through 1C.

Referring to FIGS. 1A and 1B, a light source unit 10 includes a circuit board 11, a plurality of LED chip packages 30, and a connection unit 20.

The circuit board 11 may be formed of an insulating material, e.g., epoxy resin, and may include a plurality of connection pads 13 and a plurality of wires 17 on its first or second plane.

The plurality of connection pads 13 of the circuit board 11 are connected to the plurality of wires 17 and may be formed of a metal having excellent conductivity, e.g., gold (Au) or copper (Cu). The plurality of connection pads 13 may be formed on the first or second plane of the circuit board 11, and the plurality of LED chip packages 30 and the connection unit 20 are mounted thereon.

The plurality of wires 17 of the circuit board 11 are connected to the plurality of connection pads 13 and provide an externally applied signal, e.g., a driving signal for driving the plurality of LED chip packages 30 mounted on the connection pads 13, to the connection pads 13. The plurality of wires 17 may be formed of substantially the same material as the connection pads 13, e.g., a metal having excellent conductivity.

The LED chip packages 30 are operated using a light source which generates light by the externally applied driving signal. The plurality of LED chip packages 30 are mounted on the plurality of connection pads 13 formed on the first plane of the circuit board 11. Each of the LED chip packages 30 includes a LED chip (not shown) generating internal light, and a mold (not shown) surrounding the LED chip made of, for example, EMC. In addition, shapes of the LED chip packages 30 should not be limited to the particular shapes shown and described herein and all well-known shapes can be applied thereto.

The plurality of LED chip packages 30 may be disposed on the first plane of the circuit board 11 to be spaced apart from each other at constant intervals. Here, white light is emitted from each of the plurality of LED chip packages 30. Also, red light, green light, and blue light are emitted from the corresponding LED chip packages 30, respectively. In such cases, the LED chip packages 30 may be arranged in a stripe shape, however, exemplary embodiments of the present invention are not limited thereto.

A predetermined reflective member (not shown) may be formed on the first plane of the circuit board 11, that is, the surface of the circuit board 11 having the plurality of LED chip packages 30. That is, in order to prevent the light emitted

from the LED chip packages 30 from being leaked downward with respect to the circuit board 11 and to allow the light to be uniformly illuminated upward with respect to the circuit board 11, the reflective member may be formed on an area other than the area of the surface of the circuit board 11 where the plurality of LED chip packages 30 are positioned. Here, as the reflective member, common reflective sheets, for example, can be used, however, exemplary embodiments of the present invention are not limited thereto. Any type of known reflective member capable of reflecting light may be used as the reflective member.

At least one connection unit 20 may be disposed on a second plane of the circuit board 11. Referring to FIG. 1B, the at least one connection unit 20 may be disposed on the plurality of connection pads 13 formed on the second plane of the circuit board 11. While an exemplary embodiment shows an arrangement in which a pair of connection units are formed on the circuit board 11, embodiments of the present invention are not limited to the illustrated arrangement.

The connection unit 20 may be electrically connected to the plurality of wires 17 formed on the circuit board 11 through the connection pads 13. The connection unit 20 may be electrically connected to the plurality of LED chip packages 30 formed on the first plane of the circuit board 11 through the wires 17. The connection unit 20 may be formed of a connector type, as shown by way of example, or a socket type.

Referring to FIG. 1B, the connection unit 20 includes a housing 21 made of an insulator, a plurality of leads 22 formed at one side of the housing 21, and a slot 23 formed at the opposite side of the housing 21.

The plurality of leads 22 formed at one side of the housing 21 may be electrically connected to the plurality of connection pads 13 of the circuit board 11 by soldering, for example. A predetermined connection member (not shown), e.g., an external connection member, is inserted into the slot 23. A plurality of connection pins 24 may be arranged inside the slot 23. The plurality of connection pins 24 are correspondingly connected to the external connection member inserted into the slot 23 to be connected to the plurality of leads 22 in a one-to-one relationship.

The light source unit 10 may be received in a receiving container 60 to be described later. The connection unit 20 of the light source unit 10 may be inserted into the opening portion 65 formed in the receiving container 60. Accordingly, the connection unit 20 of the light source unit 10 may be exposed to and easily connected to the outside of the receiving container 60, e.g., the driving unit 70 connected to the rear surface of the receiving container 60.

Referring to FIG. 1C, another exemplary light source unit 10' according to an exemplary embodiment of the present invention may further include a dummy circuit board 12.

The light source unit 10' may include a circuit board 11, a plurality of LED chip packages 30, and at least one connection unit 20.

The plurality of LED chip packages 30 may be formed on the first plane of the circuit board 11, and the connection unit 20 may be mounted on the second plane of the circuit board 11. The connection unit 20 may be electrically connected to the LED chip packages 30 through the plurality of wires 17 of the circuit board 11.

A dummy circuit board 12 may be disposed on the second plane of the circuit board 11. The dummy circuit board 12 may be disposed on an area of the second plane of the circuit board 11 having the connection unit 20. Accordingly, the connection unit 20 may be positioned on the dummy circuit board 12 as well.

A plurality of connection pads **14** where the connection unit **20** can be mounted may be formed on the dummy circuit board **12**. In addition, a plurality of wires **18** electrically connected to the plurality of connection pads **14** may also be formed on the connection pads **14**. The wires **18** of the dummy circuit board **12** may be electrically connected to the wires **17** of the circuit board **11**, as described above.

Thus, the connection unit **20** disposed on the dummy circuit board **12** may be electrically connected to the plurality of wires **17** of the circuit board **11** formed on the dummy circuit board **12** through the plurality of connection pads **14** and the plurality of wires **18**. The plurality of wires **18** are electrically connected to the plurality of LED chip packages (**30** of FIG. 1A) positioned on one plane of the circuit board **11**.

The dummy circuit board **12** may be formed of substantially the same material as the circuit board **11**, e.g., epoxy resin.

The dummy circuit board **12** of the light source unit **10'** has a size substantially the same as the opening portion **65** of the receiving container **60**, and will be described later. Accordingly, when the light source unit **10'** is received in the receiving container **60**, the dummy circuit board **12** of the light source unit **10'** and the connection unit **20** can be simultaneously inserted into the opening portion **65** of the receiving container **60** to then be connected with each other.

The dummy circuit board **12** of the light source unit **10'** may have substantially the same thickness as that of the receiving container **60**. Accordingly, when the light source unit **10'** is received in the receiving container **60**, and the dummy circuit board **12** of the light source unit **10'** and the connection unit **20** are together inserted into the opening portion **65** of the receiving container **60** to then be connected, only the connection unit **20** of the light source unit **10'** may protrude outside the receiving container **60**.

That is, the light source unit **10'** is formed so as to overlap with the dummy circuit board **12** having a stepped portion with respect to the circuit board **11** and the connection unit **20** on the second plane of the circuit board **11**. In such a manner, when the light source unit **10'** and the receiving container **60** are connected with each other, the dummy circuit board **12** of the light source unit **10'** can prevent infiltration of foreign matter or a light leak due to the opening portion **65** of the receiving container **60**. Accordingly, the light efficiency of the light source unit **10'** can be increased and the ease of assembly of the light source unit **10'** and the receiving container **60** can be improved.

A backlight assembly according to an embodiment of the present invention will be described in more detail with reference to FIGS. **2** through **4B**. For convenience of illustration, backlight assemblies using the light source units shown in FIGS. **1A** and **1B** will be described. However, the light source unit shown in FIG. **1C** may also be used in the backlight assembly.

FIG. **2** is an exploded perspective view of a backlight assembly according to an exemplary embodiment of the present invention, FIG. **3** is a perspective view illustrating a rear surface of the backlight assembly shown in FIG. **2**, FIG. **4A** is an enlarged view of a portion "A" shown in FIG. **3**, and FIG. **4B** is an enlarged view illustrating another example of the portion "A" shown in FIG. **3**.

Referring to FIGS. **1A**, **1B**, and **2**, the backlight assembly **100** includes a light source unit **10**, optical sheets **40**, a mold frame **50**, a receiving container **60**, and a driving unit **70**.

As described above with reference to FIGS. **1A** and **1B**, the light source unit **10** may be configured such that a plurality of light sources, e.g., a plurality of LED chip packages **30**, are disposed on a first plane of a circuit board **11**, and a connec-

tion unit **20** connected to an external circuit is disposed on a second plane of the circuit board **11**.

The light source unit **10** may be plural light source units disposed inside the receiving container **60**. Here, the plural light source units **10** are arranged in a longitudinal direction of the receiving container **60**, e.g., in a direction substantially parallel to the short side of the receiving container **60**, to be received in the receiving container **60**.

The optical sheets **40** are disposed on the light source unit **10**, and serve to diffuse and focus light coming from the light source unit **10**. Examples of the optical sheets **40** include a diffusion sheet, a prism sheet, a protective sheet, and various other sheets with similar properties.

The mold frame **50** has a quadrangle shape, and receives the optical sheets **40** and the light source unit **10**. The mold frame **50** can be formed of, for example, an insulating resin.

The receiving container **60** includes a bottom plate **61** and sidewalls **62** extending from the bottom plate **61**. The receiving container **60** may have a rectangular parallelepiped shape, and an upper surface thereof may be open to provide a receiving space. The receiving container **60** receives the light source unit **10** and the optical sheets **40** in the receiving space. The receiving container **60** is combined to the mold frame **50** to fixedly receive the light source unit **10** and the optical sheets **40**.

At least one opening portion **65** may be formed on the bottom plate **61** of the receiving container **60**. The at least one connection unit **20** of the aforementioned light source unit **10** may be inserted into the at least one opening portion **65** to then be connected with each other in a one-to-one relationship.

The opening portion **65** may be formed along the long side or short side of the bottom plate **61** of the receiving container **60** and may be plurally formed along one of long sides of the bottom plate **61** of the receiving container **60**. Alternatively, the opening portion **65** may be plurally formed along one or both of the long sides of the bottom plate **61** of the receiving container **60**. By way of example, the opening portion **65** is formed along one of the long sides of the bottom plate **61**, however, the opening portion **65** may also be plurally formed along both sides of the long sides of the bottom plate **61** of the receiving container **60**.

The plurality of connection units **20** of the light source unit **10** are inserted into the opening portions **65** of the receiving container **60** to then be connected with each other. Here, the connection units **20** are fittingly inserted into the opening portions **65** to be connected with each other, but the connection method is not limited to the illustrated example.

The connection units **20** of the light source unit **10** fittingly connected to the opening portions **65** of the receiving container **60** are exposed to the outside of the receiving container **60**, i.e., a rear surface of the receiving container **60**. Accordingly, the driving unit **70** (described later) can be connected to the connection units **20** of the exposed light source unit **10**, thereby improving the assembling efficiency of the light source unit **10** and the receiving container **60**.

The opening portions **65** of the receiving container **60** are blocked by the connection units **20** of the light source unit **10**, thereby preventing infiltration of foreign matter and a light leak of the light source unit **10**.

At least one connection hole (not shown) may be correspondingly disposed on the circuit board **11** of the light source unit **10** and on the bottom plate **61** of the receiving container **60**, respectively. Accordingly, the plurally formed connection hole allows the light source unit **10** and the receiving container **60** to be more securely connected to each other via a screw connection.

The connection hole may be plurally formed on the bottom plate **61** adjacent to the opening portion **65** of the receiving container **60** or on the circuit board **1** adjacent to the connection unit **20** of the light source unit **10**. Accordingly, infiltration of foreign matter and a light leak of the light source unit **10** can be prevented by securely connecting the connection unit **20** of the light source unit **10** to the opening portion **65** of the receiving container **60**. The receiving container **60** may be formed of a metal, for example, Al or Al alloy, but is not limited thereto.

At least one driving unit **70** may be disposed at a rear surface of the receiving container **60** and may be connected to the connection unit **20** of the light source unit **10** exposed by the opening portion **65**. The driving unit **70** may include a plurality of electronic components and can generate a predetermined driving signal which can drive the light source unit **10**.

Referring to FIGS. **3** and **4A**, the light source unit **10** and the driving unit **70** are connected to each other using a predetermined connection member **90**. Therefore, the driving signal generated from the driving unit **70** may be provided to the light source unit **10** through the connection member **90** to drive the light source unit **10**.

The driving unit **70** is connected to and disposed on the rear surface of the receiving container **60**. Here, the driving unit **70** may be positioned at one of the long sides of the receiving container **60**, i.e., at one side of the bottom plate **61** where the opening portion **65** is formed, to be adjacent to the opening portion **65**.

In addition, at least one connection unit **80** may be formed at the driving unit **70** to be connected to the connection unit **20** of the light source unit **10**.

The light source unit **10** is received in the receiving container **60** and connected to the connection unit **80**. The connection unit **20** of the light source unit **10** is inserted into the opening portion **65** of the receiving container **60** to be exposed to the outside of the receiving container **60**, i.e., a rear surface of the bottom plate **61** of the receiving container **60**.

The connection unit **20** of the light source unit **10** has substantially the same connection type as described above with reference to FIG. **1B**, e.g., a connector type.

Like the connection unit **20** of the light source unit **10**, the connection unit **80** of the driving unit **70** includes a housing **81** made of an insulator, a plurality of leads **82** formed at one side of the housing **81**, and a slot (not shown) formed at the opposite side of the housing **81**. In addition, a plurality of connection pins (not shown) may be arranged inside the slot of the connection unit **80** of the driving unit **70**.

The connection unit **80** of the driving unit **70** may be mounted on the circuit board **71** of the driving unit **70** and connected to the plurality of wires **75** formed on the circuit board **71**.

A predetermined connection member **90** may be provided between the connection unit **20** of the light source unit **10** and the connection unit **80** of the driving unit **70** for connecting the same. By way of example, the connection member **90** uses a flexible cable **91**, but is not limited thereto.

The connection member **90** may include a flexible cable **91** and a cable holder **95**. That is, the connection member **90** may include a flexible cable **91** having a plurality of wires separated and insulated from each other, and a cable holder **95** made of an insulator positioned at opposite ends of the flexible cable **91**.

Accordingly, the connection unit **20** of the light source unit **10** and the connection unit **80** of the driving unit **70** are connected to each other by the connection member **90**, that is, the flexible cable **91** and the cable holder **95**. Thus, one cable

holder **95** connected to one end of the flexible cable **91** is inserted into the slot **23** of the connection unit **20** of the light source unit **10**, and another cable holder **95** connected to the other end of the flexible cable **91** is inserted into the slot of the connection unit **80** of the driving unit **70**.

A plurality of pinholes **97** that can be correspondingly connected to the slot **23** of the connection unit **20** of the light source unit **10** and the slot of the connection unit **80** of the driving unit **70** may be arranged on each cable holder **95**. The plurality of pinholes **97** and the plurality of wires of the flexible cable **91** are correspondingly connected to each other in a one-to-one relationship.

Therefore, the connection unit **20** of the light source unit **10** is electrically connected to the connection unit **80** of the driving unit **70** by the cable holder **95** and the flexible cable **91**. Accordingly, the driving signal generated by the driving unit **70** may be provided to the connection unit **20** of the light source unit **10** through the connection unit **80** of the driving unit **70**, the cable holder **95** and the flexible cable **91**.

The light source unit **10** and the driving unit **70** may also be connected to each other by a socket connection, which will now be described in more detail with reference to FIGS. **3** and **4B**. The light source unit **10** is received in the receiving container **60**. The connection unit **20** of the light source unit **10** is inserted into the opening portion **65** of the receiving container **60** to be exposed to the outside of the receiving container **60**, i.e., a rear surface of the bottom plate **61** of the receiving container **60**.

Here, the connection unit **20'** of the light source unit **10** may be formed of a socket type. That is, the connection unit **20'** includes a housing **21'** made of an insulator, a plurality of leads **22'** formed at one side of the housing **21'**, and a slot **23'** formed at the opposite side of the housing **21'**.

As described above, the plurality of leads **22'** may be electrically connected to the plurality of connection pads **13** formed on the circuit board **11** of the light source unit **10**. In addition, a plurality of connection pins **24'** opposite to the plurality of leads **22'** are arranged inside the slot **23'**. The plurality of connection pins **24'** may be inwardly bent at a predetermined angle, e.g., about 90°, with respect to the housing **21'** so as to be connected to socket connection units **72** of a driving unit **70**.

The driving unit **70** may be positioned on the rear surface of the receiving container **60** to be adjacent to a plurality of opening portions **65**.

At least one socket connection unit **72** into which the connection unit **20'** of the light source unit **10** can be inserted for connection may be formed at one side of the circuit board **71** of the driving unit **70**. The socket connection unit **72** may protrude outwardly in consideration of a length in which it is inserted into the connection unit **20'** of the light source unit **10**.

In addition, the socket connection unit **72** may further include a plurality of connection pads **86** connected to the plurality of connection pins **24'** arranged inside the slot **23'** of the connection unit **20'** of the light source unit **10**. The plurality of connection pads **86** may be electrically connected to the plurality of wires **75** formed on the circuit board **71** of the driving unit **70**.

Meanwhile, the driving unit **70** and the light source unit **10** are connected to each other by inserting the socket connection unit **72** of the driving unit **70** into the connection unit **20'** of the light source unit **10** exposed to the rear surface of the receiving container **60**. Therefore, the driving signal generated by the driving unit **70** may be provided to the socket connection unit **72** of the driving unit **70** through the plurality of connec-

tion pads **86** and the connection unit **20'** of the light source unit **10** to drive the light source unit **10**.

Referring back to FIGS. **2** and **3**, a predetermined blocking member, e.g., an insulating tape (not shown), is attached to the opening portion **65** of the receiving container **60** to be shielded from the outside. That is, as shown in FIG. **3**, when the connection unit **20** of the light source unit **10** is inserted into the opening portion **65** of the receiving container **60** and connected to the driving unit **70**, the insulating tape is attached to the opening portion **65** of the receiving container **60**. The insulating tape can prevent light leakage or infiltration of foreign matter.

A backlight assembly according to an exemplary embodiment of the present invention will be described in detail with reference to FIGS. **5** and **6**.

The backlight assembly **101** includes a light source unit **10**, optical sheets **40**, a mold frame **50**, a receiving container **60**, and driving units **70a** and **70b**.

The light source unit **10**, the optical sheets **40**, and the mold frame **50** are substantially the same as those in FIGS. **2** and **3**, and detailed explanations thereof will be omitted.

The receiving container **60** includes a bottom plate **61** and sidewalls **62** extending from the bottom plate **61**. The receiving container **60** may have a rectangular parallelepiped shape, and an upper surface thereof may be open to provide a receiving space. The receiving container **60** receives the light source unit **10** and the optical sheets **40** in the receiving space. The receiving container **60** is combined with the mold frame **50** to fixedly receive the light source unit **10** and the optical sheets **40**.

At least one opening portion **65** may be formed on the bottom plate **61** of the receiving container **60**. The at least one connection unit **20** of the aforementioned light source unit **10** may be inserted into the at least one opening portion **65** to then be connected with each other.

By way of example, the opening portion **65** may be formed along the long side or short side of the bottom plate **61** of the receiving container **60**.

The opening portion **65** may be plurally formed along both of the short sides of the bottom plate **61** of the receiving container **60**. The plurality of opening portions **65** may be formed opposite to each other.

The light source unit **10** may be disposed as plural units inside the receiving container **60** to be connected thereto. The light source unit **10**, that is, the plurality of light source units **10**, are arranged in a horizontal direction of the receiving container **60**, e.g., in a direction substantially parallel to the long side of the receiving container **60**, to be received in the receiving container **60**.

The connection unit **20** of the light source unit **10** may be inserted into the opening portion **65** in the receiving container **60** to then be connected with each other. The connection unit **20** may be fittingly inserted into the opening portion **65** to be connected with each other, but the connection method is not limited to the illustrated example.

The connection units **20** of the light source unit **10** fittingly connected to the opening portions **65** of the receiving container **60** are exposed to the outside of the receiving container **60**, i.e., a rear surface of the receiving container **60**. Accordingly, the driving units **70a** and **70b** can be connected to the connection units **20** of the exposed light source unit **10**, thereby improving the ease of assembly of the light source unit **10** and the receiving container **60**.

The opening portion **65** of the receiving container **60** may be blocked by the connection unit **20** of the light source unit **10**, thereby preventing infiltration of foreign matter and light leaks of the light source unit **10**.

As described above, at least one connection hole (not shown) may be correspondingly disposed on the light source unit **10** and the receiving container **60**, respectively. That is, the connection hole may be plurally disposed on the bottom plate **61** adjacent to the opening portion **65** of the receiving container **60** and on the circuit board **11** adjacent to the connection unit **20** of the light source unit **10**, respectively. Accordingly, the plurally formed connection hole allows the connection unit **20** of the light source unit **10** and the opening portion **65** of the receiving container **60** to be more securely connected to each other by a screw connection.

Accordingly, infiltration of foreign matter and a light leak of the light source unit **10** can be prevented by securely connecting the connection unit **20** of the light source unit **10** to the opening portion **65** of the receiving container **60**.

The receiving container **60** may be formed of a metal, for example, Al or Al alloy, but is not limited thereto.

The driving units **70a** and **70b** may be positioned on the rear surface of the receiving container **60**. The driving units **70a** and **70b** may include a plurality of electronic components and can generate a predetermined driving signal which can drive the light source unit **10**.

The driving units **70a** and **70b** may be disposed at both of the short sides of the rear surface of the receiving container **60**, i.e., the short sides of the rear surface adjacent to the opening portion **65**, respectively, and may be electrically connected to the connection unit **20** of the light source unit **10** through the opening portion **65** of the receiving container **60**. The driving signal generated from the driving units **70a** and **70b** may be provided to the light source unit **10** to drive the light source unit **10**.

Connecting the driving units **70a** and **70b** with the light source unit **10** may be performed in substantially the same manner as in FIGS. **4A** and **4B**.

As described above, the driving units **70a** and **70b** may be connected to the light source unit **10** using a cable with a connector or socket, and a detailed explanation thereof will not be repeated.

In addition, a predetermined blocking member, e.g., an insulating tape (not shown), is attached to the opening portion **65** of the receiving container **60** to be shielded from the outside. That is, when the connection unit **20** of the light source unit **10** is connected to the driving units **70a** and **70b** by a connection member **90**, the blocking member, that is, the insulating tape, is attached to the opening portion **65** of the receiving container **60**. The insulating tape can then prevent light leakage or infiltration of foreign matter.

A liquid crystal display according to an exemplary embodiment of the present invention, including the aforementioned backlight assembly, will be described with reference to FIG. **7**. For convenience of illustration, a liquid crystal display using the backlight assembly shown in FIG. **2** will be described. However, the backlight assembly shown in FIG. **5** may also be used in the liquid crystal display.

FIG. **7** is an exploded perspective view of a liquid crystal display according to an exemplary embodiment of the present invention, including the backlight assembly shown in FIG. **2**.

Referring to FIG. 7, the liquid crystal display 200 generally includes a liquid crystal panel assembly 130 and a backlight assembly 100.

The liquid crystal panel assembly 130 includes a liquid crystal panel 131 including two substrates, i.e., a thin film transistor (“TFT”) substrate 132 and a color filter substrate 133, liquid crystals (not shown), driving chip packages 134 and 135, and a printed circuit board 136.

In the liquid crystal panel 131, the TFT substrate 132 includes gate lines (not shown), data lines (not shown), an array of TFTs (not shown), pixel electrodes, and other various components. The color filter substrate 133 includes color filters, black matrices (not shown), a common electrode, and other various components, and is disposed opposite to the TFT substrate 132. A liquid crystal layer having optical anisotropy is interposed between the TFT substrate 132 and the color filter substrate 133.

The driving chip packages 134 and 135 include gate-driving chip packages 134, and data-driving chip packages 135. The gate-driving chip packages 134 are connected to gate lines formed on the TFT substrate 132 and the data-driving chip packages 135 are connected to data lines formed on the TFT substrate 132. The driving chip packages 134 and 135 may be formed as a tape carrier package (“TCP”) type, for example.

A plurality of electronic components are mounted on the printed circuit board 136 to provide gate-driving signals to the gate-driving chip packages 134 and data-driving signals to data-driving chip packages 135. The printed circuit board 136 may be bent to the rear surface of the receiving container 60 of the backlight assembly 100 and connected thereto.

The backlight assembly 100 for providing light to the liquid crystal panel 131 is disposed under the liquid crystal panel assembly 130.

As described above with reference to FIGS. 1A through 6, the backlight assembly 100 includes the light source unit 10, the optical sheets 40, mold frame 50, the receiving container 60, and the driving unit 70.

An upper receiving container 140 may be disposed to cover an upper portion the liquid crystal panel 131. The upper receiving container 140 may be combined with the receiving container 60 of the backlight assembly 100. A window (not shown) may be formed on a top surface of the upper receiving container 140 to expose the liquid crystal panel 131 to the outside.

While exemplary embodiments of the present invention have been described for illustrative purposes, it will be understood by those of ordinary skill in the art that various changes in form and details may be made therein without departing from the spirit and scope of the disclosure.

What is claimed is:

1. A backlight assembly comprising:

a light source unit including a circuit board, a light source disposed on a first plane of the circuit board, and at least one connection unit disposed on a second plane opposite to the first plane of the circuit board and electrically connected to the light source;

a receiving container having a bottom plate and sidewalls extending from edges of the bottom plate and receiving the light source unit, the bottom plate including at least one opening portion in which the connection unit is inserted and exposed to the outside; and

at least one driving unit disposed at a rear surface of the receiving container and connected to the connection unit for driving the light source unit, wherein the light source unit further includes a dummy circuit board disposed between the circuit board and the connection unit, and the dummy circuit board is substantially the same size as or smaller than the opening portion so as to be inserted into the opening portion.

2. The backlight assembly of claim 1, wherein the connection unit is one of a connector type or a socket type.

3. The backlight assembly of claim 1, wherein the bottom plate is of a rectangular shape.

4. The backlight assembly of claim 3, wherein the opening portion is formed along at least one of a long side or a short side of the bottom plate.

5. The backlight assembly of claim 1, wherein the driving unit is connected to the connection unit with a connector using one of a cable or a socket.

6. The backlight assembly of claim 1, further comprising an insulating tape attached to the receiving container to cover the opening portion.

7. The backlight assembly of claim 1, wherein the light source includes a plurality of light emitting diodes (LEDs).

8. A method of assembling a backlight assembly, the method comprising:

preparing a light source unit including a circuit board, a light source disposed on a first plane of the circuit board, and at least one connection unit disposed on a second plane opposite to the first plane of the circuit board and electrically connected to the light source, and a receiving container having a bottom plate and sidewalls extending from edges of the bottom plate and receiving the light source unit, the bottom plate including at least one opening portion in which the connection unit is inserted and exposed to the outside;

assembling the light source unit with the receiving container by receiving the light source unit in the receiving container so that the connection unit is exposed to the outside through the opening portion; and

disposing at least one driving unit at a rear surface of the receiving container and connecting the driving unit to the exposed connection unit, wherein the light source unit further includes a dummy circuit board disposed between the circuit board and the connection unit, and the dummy circuit board is substantially the same size as or smaller than the opening portion so as to be inserted into the opening portion.

9. The method of claim 8, wherein the connecting of the driving unit to the exposed connection unit comprises connecting the driving unit to the connection unit with a connector using one of a cable or a socket.

10. The method of claim 8, wherein the opening portion is formed along at least one of a long side or a short side of the bottom plate, and the connection unit is fittingly connected to the opening portion.

11. The method of claim 8, wherein after connecting the driving unit with the exposed connection unit, further comprising attaching an insulating tape to the receiving container to cover the opening portion.

12. A liquid crystal display comprising:

a liquid crystal display panel displaying an image; and

13

a backlight assembly disposed under the liquid crystal display panel and providing light to the liquid crystal display panel, wherein the backlight assembly comprises:
a light source unit including a circuit board, a light source disposed on a first plane of the circuit board, and at least one connection unit disposed on a second plane opposite to the first plane of the circuit board and electrically connected to the light source;
a receiving container having a bottom plate and sidewalls extending from edges of the bottom plate and receiving the light source unit, the bottom plate including at least one opening portion in which the connection unit is inserted and exposed to the outside; and
at least one driving unit disposed at a rear surface of the receiving container and connected to the connection unit for driving the light source unit, wherein the light source unit further includes a dummy circuit board disposed

14

between the circuit board and the connection unit, and the dummy circuit board is substantially the same size as or smaller than the opening portion so as to be inserted into the opening portion.

5 **13.** The liquid crystal display of claim 12, wherein the bottom plate is of a rectangular shape.

14. The liquid crystal display of claim 13, wherein the opening portion is formed along at least one of a long side or a short side of the bottom plate.

10 **15.** The liquid crystal display of claim 12, wherein the driving unit is connected to the connection unit with a connector using one of a cable or a socket.

15 **16.** The liquid crystal display of claim 12, further comprising an insulating tape attached to the receiving container to cover the opening portion.

17. The liquid crystal display of claim 12, wherein the light source includes a plurality of light emitting diodes (LEDs).

* * * * *

专利名称(译)	背光组件及其组装方法和包括背光组件的液晶显示器		
公开(公告)号	US8064006	公开(公告)日	2011-11-22
申请号	US12/205152	申请日	2008-09-05
[标]申请(专利权)人(译)	朴真熙 你BONG HYUN 崔在常		
申请(专利权)人(译)	朴真熙 YOU BONG-HYUN 崔在常		
当前申请(专利权)人(译)	SAMSUNG ELECTRONICS CO. , LTD.		
[标]发明人	PARK JIN HEE YOU BONG HYUN CHOI JAE CHANG		
发明人	PARK, JIN-HEE YOU, BONG-HYUN CHOI, JAE-CHANG		
IPC分类号	G02F1/1333 G02F1/1335 G09F13/04 G09F13/08 F21V5/00 F21V7/04 H01J9/24		
CPC分类号	G02F1/133608 G09F13/04 G02F1/133603 G02F2001/133612 G02F2001/133311		
助理审查员(译)	BLEVINS , 杰里		
优先权	1020080000817 2008-01-03 KR		
其他公开文献	US20090174838A1		
外部链接	Espacenet USPTO		

摘要(译)

一种背光组件，包括：光源单元，包括电路板；光源，设置在电路板的第一平面上；以及至少一个连接单元，设置在与电路板的第一平面相对的第二平面上并且电连接到电路板光源，接收容器，具有底板和从底板的边缘延伸并容纳光源单元的侧壁，底板包括至少一个开口部分，连接单元插入该开口部分并暴露于外部，以及至少一个驱动单元设置在接收容器的后表面上并连接到连接单元以驱动光源单元。

