



US008711294B2

(12) **United States Patent**
Lee et al.

(10) **Patent No.:** **US 8,711,294 B2**
(45) **Date of Patent:** **Apr. 29, 2014**

(54) **MULTI-MODE 3-DIMENSIONAL IMAGE
DISPLAY APPARATUS**

(75) Inventors: **Sung-Jung Lee**, Incheon (KR);
Min-Jung Kim, Incheon (KR);
Eui-Tack Shim, Incheon (KR)

(73) Assignee: **Pavoninekorea, Inc.**, Incheon (KR)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 181 days.

(21) Appl. No.: **13/510,054**

(22) PCT Filed: **Sep. 2, 2010**

(86) PCT No.: **PCT/KR2010/005938**

§ 371 (c)(1),
(2), (4) Date: **May 16, 2012**

(87) PCT Pub. No.: **WO2011/074763**

PCT Pub. Date: **Jun. 23, 2011**

(65) **Prior Publication Data**

US 2012/0229720 A1 Sep. 13, 2012

(30) **Foreign Application Priority Data**

Dec. 16, 2009 (KR) 10-2009-0125626

(51) **Int. Cl.**

G02F 1/1335 (2006.01)

G02F 1/133 (2006.01)

G02F 1/1333 (2006.01)

(52) **U.S. Cl.**

USPC **349/15**; 349/31; 349/110; 349/111

(58) **Field of Classification Search**

CPC G02F 1/133348; G02F 1/10333; G02F
1/13334; G02F 1/136209; G02F 1/133512;
G02F 2001/133388; G02B 27/2214; H04N
13/0404

USPC 349/15, 31, 110, 111

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,055,103 A *	4/2000	Woodgate et al.		359/489.07
7,787,064 B2 *	8/2010	Kwon et al.		349/15
7,940,342 B2 *	5/2011	Lee		349/15
7,954,967 B2 *	6/2011	Kashiwagi et al.		362/97.1
2009/0279025 A1	11/2009	Machidori et al.		
2012/0147281 A1 *	6/2012	Matsuhiro et al.		349/15

* cited by examiner

Primary Examiner — Mike Qi

(74) *Attorney, Agent, or Firm* — IPLA P.A.; James E. Bame

(57) **ABSTRACT**

A multi-mode 3-dimensional image display apparatus comprises a backlight for emitting light; an image liquid crystal panel for displaying an image using the light emitted from the backlight; and a parallax barrier liquid crystal panel including a first transparent substrate, a first transparent electrode plate disposed on the first transparent substrate and having a front surface formed as a transparent electrode, a first insulation plate disposed on the first transparent electrode plate, a second transparent electrode plate disposed on the first insulation plate and having a transparent electrode material patterned in parallel in a vertical direction, a first alignment layer disposed on the second transparent electrode plate, a liquid crystal layer disposed on the first alignment layer, a second alignment layer disposed on the liquid crystal layer, a third transparent electrode plate disposed on the second alignment layer and having a transparent electrode material patterned in parallel in a vertical direction, in which the transparent electrode material is patterned so as to overlap a certain area with an area of the second transparent electrode plate patterned with the transparent electrode material, a second insulation plate disposed on the third transparent electrode plate, a fourth transparent electrode plate disposed on the second insulation plate and having a front surface formed as a transparent electrode, a second transparent substrate disposed on the fourth transparent electrode plate, and a polarizer plate disposed on the second transparent substrate.

3 Claims, 4 Drawing Sheets




FIG. 1




FIG. 2




FIG. 3





FIG. 4



MULTI-MODE 3-DIMENSIONAL IMAGE DISPLAY APPARATUS

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a multi-mode 3-dimensional image display apparatus, and more specifically, to a multi-mode 3-dimensional image display apparatus, in which two sheets of transparent electrode substrates patterned with a transparent electrode material in parallel in the vertical direction are disposed so as to overlap the areas patterned with the transparent electrode material with each other, and thus a 3-dimensional image is effectively displayed when an observer observes the 3-dimensional image while moving.

2. Background of the Related Art

Generally, since two eyes of a person are spaced apart from each other by about 65 mm, each of the eyes sees a different surface of an object when the person sees the object, and thus the person feels a 3-dimensional effect. This is called as a binocular disparity caused by both of the left and right eyes, and the binocular disparity is perceived as an image having a feeling of 3-dimensional effect as the images acquired by the two eyes are synthesized in the brain. A 3-dimension image can be displayed based on such a principle.

The techniques for displaying a 3-dimension image include a stereoscopic technique, an auto-stereoscopic technique and the like. The stereoscopic technique uses disparity images of the left and right eyes having a largest 3-dimensional effect. Among the stereoscopic techniques, a 3-dimensional image display apparatus of a parallax barrier technique is spotlighted.

However, a 3-dimensional image display apparatus of a conventional parallax barrier technique is difficult to effectively observe a 3-dimensional image if an object is not positioned within a range of accurate viewing angles. Particularly, when an observer (e.g., a doctor) with a 3-dimensional endoscope observes a 3-dimensional image while moving, it is difficult to accurately observe the 3-dimensional image.

SUMMARY OF THE INVENTION

Therefore, the present invention has been made in view of the above problems, and it is an object of the present invention to provide a multi-mode 3-dimensional image display apparatus, in which two sheets of transparent electrode substrates patterned with a transparent electrode material in parallel in the vertical direction are disposed so as to overlap the areas patterned with the transparent electrode material with each other, and thus a 3-dimensional image is effectively displayed when an observer observes the 3-dimensional image while moving.

The technical problems to be solved in the present invention are not limited to those described above, and other unmentioned technical problems may be apparently understood by those skilled in the art from the descriptions described below.

To accomplish the above object, according to one aspect of the present invention, there is provided a multi-mode 3-dimensional image display apparatus comprising: a backlight for emitting light; an image liquid crystal panel for displaying an image using the light emitted from the backlight; and a parallax barrier liquid crystal panel including a first transparent substrate, a first transparent electrode plate disposed on the first transparent substrate and having a front surface formed as a transparent electrode, a first insulation plate disposed on the first transparent electrode plate, a second

transparent electrode plate disposed on the first insulation plate and having a transparent electrode material patterned in parallel in a vertical direction, a first alignment layer disposed on the second transparent electrode plate, a liquid crystal layer disposed on the first alignment layer, a second alignment layer disposed on the liquid crystal layer, a third transparent electrode plate disposed on the second alignment layer and having a transparent electrode material patterned in parallel in a vertical direction, in which the transparent electrode material is patterned so as to overlap a certain area with an area of the second transparent electrode plate patterned with the transparent electrode material, a second insulation plate disposed on the third transparent electrode plate, a fourth transparent electrode plate disposed on the second insulation plate and having a front surface formed as a transparent electrode, a second transparent substrate disposed on the fourth transparent electrode plate, and a polarizer plate disposed on the second transparent substrate.

In the multi-mode 3-dimensional image display apparatus according to an embodiment of the present invention, the area patterned with a transparent electrode material and an area not patterned with a transparent electrode material are disposed on the second transparent electrode plate preferably at a ratio of 2 to 1.

In the multi-mode 3-dimensional image display apparatus according to an embodiment of the present invention, an area patterned with a transparent electrode material and an area not patterned with a transparent electrode material are disposed on the third transparent electrode plate at a ratio of 2 to 1, and an area of the third transparent electrode plate is overlapped with the area of the second transparent electrode plate patterned with the transparent electrode material preferably by 40 to 60%.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view showing a multi-mode 3-dimensional image display apparatus according to an embodiment of the present invention.

FIG. 2 is a view showing an operation of the multi-mode 3-dimensional image display apparatus of FIG. 1.

FIG. 3 is a view showing a connection state between the multi-mode 3-dimensional image display apparatus of FIG. 1 and a camera.

FIG. 4 is a view showing an observer of the multi-mode 3-dimensional image display apparatus of FIG. 1 moving left or right.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Preferred embodiments of the present invention will be described below in more detail with reference to the accompanying drawings. Details of the other embodiments are included in the detailed descriptions and figures. Advantages and features of the present invention, and implementation methods thereof will be clarified through following embodiments described with reference to the accompanying drawings. Like reference numerals refer to like elements throughout.

FIG. 1 is a perspective view showing a multi-mode 3-dimensional image display apparatus according to an embodiment of the present invention, FIG. 2 is a view showing an operation of the multi-mode 3-dimensional image display apparatus of FIG. 1, FIG. 3 is a view showing a connection state between the multi-mode 3-dimensional image display apparatus of FIG. 1 and a camera, and FIG. 4 is a view

showing an observer of the multi-mode 3-dimensional image display apparatus of FIG. 1 moving left or right.

As shown in FIG. 1, a 3-dimensional image display apparatus according to an embodiment of the present invention may include a backlight 100, an image liquid crystal panel 110 and a barrier liquid crystal panel 500.

Here, the backlight 100 emits light, and a Cold Cathode Fluorescent Lamp (CCFL), an External Electrode Fluorescent Lamp (EEFL), a Light Emitting Diode (LED) or the like can be used as a light source.

Meanwhile, the image liquid crystal panel 110 defines pixels for displaying an image using the light emitted from the backlight 100 in the form of a matrix. Each pixel is provided with an opposing pixel and a common electrode with the intervention of a liquid crystal layer, and a thin film transistor (TFT) for switching the driving voltage transferred to each pixel electrode may be provided.

In addition, the barrier liquid crystal panel 500 includes a first transparent substrate 130, a first transparent electrode plate 140, a first insulation plate 150 disposed on the first transparent electrode plate 140, a second transparent electrode plate 160, a first alignment layer 170, a liquid crystal layer 180, a second alignment layer 190, a third transparent electrode plate 200, a second insulation plate 210, a fourth transparent electrode plate 220, a second transparent substrate 230, and a polarizer plate 240.

Meanwhile, the first transparent electrode plate 140 is disposed on the first transparent substrate 130 and has a front surface formed as a transparent electrode, and the first insulation plate 150 is disposed on the first transparent electrode plate 140. The second transparent electrode plate 160 is disposed on the first insulation plate 150 and has a transparent electrode patterned in parallel in the vertical direction. The first alignment layer 170 is disposed on the second transparent electrode plate 160, and the liquid crystal layer 180 is disposed on the first alignment layer 170. Here, the liquid crystal layer 180 may be formed of a twisted nematic (TN) liquid crystal.

Meanwhile, an area patterned with a transparent electrode material and an area not patterned with a transparent electrode material may be disposed on the second transparent electrode plate 160 approximately at a ratio of 2 to 1.

In addition, the second alignment layer 190 is disposed on the liquid crystal layer 180, and the third transparent electrode plate 200 has a transparent electrode material patterned in parallel in the vertical direction. The transparent electrode material is patterned so as to overlap a certain area of the third transparent electrode plate 200 with the area of the second transparent electrode plate 160 patterned with the transparent electrode material.

Specifically, an area patterned with a transparent electrode material and an area not patterned with a transparent electrode material are disposed on the third transparent electrode plate 200 approximately at a ratio of 2 to 1, and an area of the third transparent electrode plate 200 is overlapped with the area of the second transparent electrode plate 160 patterned with the transparent electrode material preferably by 40 to 60%, and further preferably by 50%.

Meanwhile, the second insulation plate 210 is disposed on the third transparent electrode plate 200, and the fourth transparent electrode plate 220 is disposed on the second insulation plate 210 and has a front surface formed as a transparent electrode. The second transparent substrate 230 is disposed on the fourth transparent electrode plate 220, and the polarizer plate 240 is disposed on the second transparent substrate 230.

As shown in FIG. 2, in the multi-mode 3-dimensional image display apparatus according to an embodiment of the present invention, the area of the second transparent electrode plate 160 patterned with a transparent electrode material, in which a ratio of the area patterned with a transparent electrode material to the area not patterned with a transparent electrode material is 2 to 1, and the area of the third transparent electrode plate 200 patterned with a transparent electrode material, in which a ratio of the area patterned with a transparent electrode material to the area not patterned with a transparent electrode material is 2 to 1, are disposed so as to overlap with each other by about 40 to 60%, and thus a 3-dimensional image may be effectively displayed when an observer observes the 3-dimensional image while moving.

The multi-mode 3-dimensional image display apparatus according to an embodiment of the present invention disposes right images R and left images L on the image liquid crystal panel 110 at regular intervals and installs a camera 300 for recognizing a position of an observer in the middle of the image liquid crystal panel 110 combined with the parallax barrier liquid crystal panel 500 as shown in FIG. 3. If the multi-mode 3-dimensional image display apparatus traces the position of the observer and applies a driving signal to the second transparent electrode plate 160 and the fourth transparent electrode plate 220 of the parallax barrier liquid crystal panel 500 through an interface circuit 400 based on the traced position information, the observer may observe an accurate 3-dimensional image. If the observer moves left or right as shown in FIG. 4, the position recognition camera 300 detects the movement, and a driving signal is applied to the first transparent electrode plate 140 and the third transparent electrode plate 200 of the parallax barrier liquid crystal panel 500 through the interface circuit 400 based on the movement information. Then, if positions of the right images R and the left images L are exchanged with each other on the image liquid crystal panel 110, the observer may observe an accurate 3-dimensional image.

In the multi-mode 3-dimensional image display apparatus according to the embodiments of the present invention, two sheets of transparent electrode substrates patterned with a transparent electrode material in parallel in the vertical direction are disposed so as to overlap the areas patterned with the transparent electrode material with each other, and thus a 3-dimensional image is effectively displayed when an observer observes the 3-dimensional image while moving.

While the present invention has been described with reference to the particular illustrative embodiments, it is not to be restricted by the embodiments but only by the appended claims. It is to be appreciated that those skilled in the art can change or modify the embodiments without departing from the scope and spirit of the present invention.

What is claimed is:

1. A multi-mode 3-dimensional image display apparatus comprising:

- a backlight for emitting light;
- an image liquid crystal panel for displaying an image using the light emitted from the backlight; and
- a parallax barrier liquid crystal panel including a first transparent substrate, a first transparent electrode plate disposed on the first transparent substrate and having a front surface formed as a transparent electrode, a first insulation plate disposed on the first transparent electrode plate, a second transparent electrode plate disposed on the first insulation plate and having a transparent electrode material patterned in parallel in a vertical direction, a first alignment layer disposed on the second transparent electrode plate, a liquid crystal layer disposed on

the first alignment layer, a second alignment layer disposed on the liquid crystal layer, a third transparent electrode plate disposed on the second alignment layer and having a transparent electrode material patterned in parallel in a vertical direction, in which the transparent electrode material is patterned so as to overlap a certain area with an area of the second transparent electrode plate patterned with the transparent electrode material, a second insulation plate disposed on the third transparent electrode plate, a fourth transparent electrode plate disposed on the second insulation plate and having a front surface formed as a transparent electrode, a second transparent substrate disposed on the fourth transparent electrode plate, and a polarizer plate disposed on the second transparent substrate.

2. The apparatus according to claim 1, wherein the area patterned with a transparent electrode material and an area not patterned with a transparent electrode material are disposed on the second transparent electrode plate at a ratio of 2 to 1.

3. The apparatus according to claim 1, wherein the area patterned with a transparent electrode material and an area not patterned with a transparent electrode material are disposed on the third transparent electrode plate at a ratio of 2 to 1, and the area of the third transparent electrode plate is overlapped with the area of the second transparent electrode plate patterned with the transparent electrode material by 40 to 60%.

* * * * *

专利名称(译)	多模式三维图像显示装置		
公开(公告)号	US8711294	公开(公告)日	2014-04-29
申请号	US13/510054	申请日	2010-09-02
[标]申请(专利权)人(译)	李成JUNG 金敏贞 SHIM EUI TAEK		
申请(专利权)人(译)	李成JUNG 金玟廷 SHIM EUI泽		
当前申请(专利权)人(译)	PAVONINEKOREA INC.		
[标]发明人	LEE SUNG JUNG KIM MIN JUNG SHIM EUI TAEK		
发明人	LEE, SUNG-JUNG KIM, MIN-JUNG SHIM, EUI-TAEK		
IPC分类号	G02F1/133 G02F1/1333 G02F1/1335		
CPC分类号	G02F2001/133565 G02B27/2214 H04N13/0468 H04N13/0413 G02F1/133509 G02B30/27 H04N13/315 H04N13/366		
优先权	1020090125626 2009-12-16 KR		
其他公开文献	US20120229720A1		
外部链接	Espacenet USPTO		

摘要(译)

多模式三维图像显示装置包括用于发光的背光;图像液晶面板,用于使用从背光源发出的光显示图像;视差屏障液晶面板,包括第一透明基板,设置于第一透明基板上且具有形成透明电极的前表面的第一透明电极板,设置于第一透明电极板上的第一绝缘板,第二透明电极板电极板设置于第一绝缘板上并具有在垂直方向上平行图案化的透明电极材料,第一取向层设置于第二透明电极板上,液晶层设置于第一取向层上,设置在液晶层上的第二取向层,设置在第二取向层上并具有在垂直方向上平行图案化的透明电极材料的第三透明电极板,其中透明电极材料被图案化以便重叠具有透明电极材料图案的第二透明电极板区域的特定区域,设置在第三透明电极板上的第二绝缘板,设置在第二绝缘板上并具有形成第二绝缘板的前表面的第四透明电极板透明电极,设置在第四透明电极板上的第二透明基板,和设置在第二透明电极板上的偏振板基质。

