



US 20020001060A1

(19) **United States**(12) **Patent Application Publication**(10) **Pub. No.: US 2002/0001060 A1****Matsuzawa**(43) **Pub. Date:****Jan. 3, 2002**

(54) **METHOD AND SYSTEM FOR FABRICATING
A LIQUID CRYSTAL DISPLAY BY
OPTICALLY DETECTING ANISOTROPIC
ANGULAR MISALIGNMENT**

(30) **Foreign Application Priority Data**


Jun. 30, 2000 (JP) 2000-199562

Publication Classification(51) **Int. Cl.⁷** **G02F 1/13**(52) **U.S. Cl.** **349/187**(57) **ABSTRACT**

A liquid crystal display panel is placed on a fixed base and an anisotropic film is set in a position relative to the orientation layer of the display panel. Linearly polarized light is directed to the panel and the anisotropic film and light passing through them are detected. According to the intensity of the detected light, the angle of orientation of the anisotropic film is adjusted relative to the orientation layer. Angular misalignment, which may exist between the anisotropic film and the orientation layer, is minimized.

(75) **Inventor:** **Tadashi Matsuzawa, Tokyo (JP)****Correspondence Address:**

**Norman P. Soloway
HAYES, SOLOWAY, HENNESSEY,
GROSSMAN & HAGE, P.C.
175 Canal Street
Manchester, NH 03101 (US)**

(73) **Assignee:** **NEC Corporation**(21) **Appl. No.:** **09/892,836**(22) **Filed:** **Jun. 27, 2001**




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4





FIG. 5






FIG. 7





FIG. 8






FIG. 9B




FIG. 9C





FIG. 9D



METHOD AND SYSTEM FOR FABRICATING A LIQUID CRYSTAL DISPLAY BY OPTICALLY DETECTING ANISOTROPIC ANGULAR MISALIGNMENT

BACKGROUND OF THE INVENTION

[0001] 1. Field of the Invention

[0002] The present invention relates generally to liquid crystal display and more specifically to a method and a system for fabricating LCD panels by with a reduced angular misalignment between the anisotropic axes of laminated layers.

[0003] 2. Description of the Related Art

[0004] Liquid crystal displays, such as twisted nematic type, usually comprise a liquid crystal layer and a pair of orientation (alignment) layers, one on each side of the liquid crystal layer, to cause their molecules to twist along its thickness and orient in mutually orthogonal directions on its opposite surface when no voltage is applied. On the outer side of each orientation layer is a polarization film so arranged that its polarization (anisotropic) is aligned with that of the orientation layer. When one of the polarization films is illuminated with natural light, only that portion of the incident light linearly aligned with the polarization axis of the film is allowed to enter the liquid crystal layer. Under zero electrical field, the linearly polarized light is subjected to a full 90-degree twist as it traverses the liquid crystal layer and allowed to pass through other polarization film, producing a maximum level of brightness (white luminance representation). When a full voltage is applied across the liquid crystal layer, the molecules are transposed in the direction of thickness, causing the polarized light aligned with one polarization polarization film to be twisted out of alignment with the other polarization film, producing a maximum level of darkness (black luminance representation). In the IPS (in plane switching) type of liquid crystal displays, the axes of the orientation layers are equally aligned so that ON/OFF switching modes are in reverse to those of the twisted nematic types.

[0005] One of the important characteristics used to evaluate the quality of an LCD panel is the black-to-white contrast ratio, i.e., the ratio of the white luminance to the black luminance. Angular misalignment between the polarization film and the orientation layer, which may occur when they are pasted together, represents a potential cause of low contrast ratios. Experiments indicate that the angular misalignment of as small as 4 degrees causes the contrast ratio of LCD panels to decrease from the maximum value of 400 to as low as 150.

[0006] Mechanical methods are currently employed to align polarization films with the orientation layers of liquid crystal panels. However, due to manufacturing tolerances, precision alignment cannot consistently be obtained. As a result, variability exists in contrast ratio, which ranges significantly between 400 and 200 for misalignments of plus/minus 2 to 3 degrees.

[0007] To overcome this problem, Japanese Patent Publication 11-271778 discloses a method in which a polarization film is initially pasted on one surface of a liquid crystal layer where a light sensitive layer is applied and ultraviolet light of 350 nanometers is then used to illuminate the liquid

crystal layer through the polarization film. The molecules in the illuminated light sensitive layer are excited and their axis is oriented in the same direction as the polarization film.

[0008] However, suitable materials for use with such orientation layers are not available at present.

[0009] In addition, optical compensation films are currently used in LCD panels. The films of this type is a birefringence characteristic that compensates for the loss of light transmissivity of the panel when viewed at a skewed angle. Since this optical compensation film has an anisotropic axis, it must be aligned with the axis of a polarization film when they are pasted together.

SUMMARY OF THE INVENTION

[0010] It is therefore an object of the present invention to provide a method and system for fabricating a liquid crystal display that eliminates angular misalignment between optically anisotropic films and orientation layers.

[0011] According to a first aspect, the present invention provides a method of fabricating a liquid crystal display, comprising the steps of setting a liquid crystal display panel on a fixed base, the panel including a liquid crystal layer and an orientation layer on one surface of the liquid crystal layer, setting an anisotropic film relative to the orientation layer, directing linearly polarized light to the panel and the anisotropic film and detecting light therefrom, and adjusting angle of orientation of the anisotropic film relative to the orientation layer according to intensity of the detected light.

[0012] According to a second aspect, the present invention provides a method of fabricating a liquid crystal display, comprising the steps of setting a liquid crystal display panel on a fixed base, the panel including a liquid crystal layer and an orientation layer on one surface of the liquid crystal layer, setting an optical compensation film and a polarizer relative to the orientation layer, directing linearly polarized light to the panel, the optical compensation film and the polarizer at a skewed angle and detecting light therefrom, the linearly polarized light having a polarization axis aligned with polarization axis of the polarizer, and adjusting angle of orientation of the optical compensation film relative to the orientation layer according to intensity of the detected light.

[0013] According to a third aspect, the present invention provides a system for fabricating a liquid crystal display, comprising base means for setting a liquid crystal display panel, the panel including a liquid crystal layer and an orientation layer on one surface of the liquid crystal layer, carrier means for setting an anisotropic film relative to the orientation layer, a light source for directing linearly polarized light to the panel and the anisotropic film, and an optical sensor for detecting the directed light from the anisotropic film. The carrier means is rotatable so that angle of orientation of the anisotropic film can be adjusted relative to the orientation layer according to intensity of the detected light.

[0014] According to a fourth aspect, the present invention provides a system for fabricating a liquid crystal display, comprising base means for setting a liquid crystal display panel, the panel including a liquid crystal layer and an orientation layer on one surface of the liquid crystal layer, carrier means for setting an optical compensation film and a polarizer relative to the orientation layer, a light source for directing linearly polarized light to the panel, the optical

compensation film and the polarizer at a skewed angle, and an optical sensor for detecting the directed light from the polarizer. The linearly polarized light has a polarization axis aligned with polarization axis of the polarizer. The carrier means is rotatable so that angle of orientation of the optical compensation film can be adjusted relative to the orientation layer according to intensity of the detected light.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] The present invention will be described in detail further with reference to the following drawings, in which:

[0016] **FIG. 1** is a schematic diagram of a manufacturing system of the present invention for fabricating liquid crystal displays ;

[0017] **FIG. 2** is a side view of an optical system of a first embodiment of the present invention shown mounted on a suction plate with respect to a suction base on which an LCD panel is secured in place;

[0018] **FIG. 3A** is an enlarged perspective view of a portion of an LCD panel and the polarizer of the first embodiment through which polarized light is directed for detecting misalignment between a first polarization film and the first orientation layer of the LCD panel;

[0019] **FIG. 3B** is an enlarged perspective view of a portion of an LCD panel and the polarizer of the first embodiment through which polarized light is directed for detecting misalignment between a second polarization film and the second orientation layer of the LCD panel;

[0020] **FIG. 4** is a side view of a suction plate when pasting a polarization film on an LCD panel;

[0021] **FIG. 5** is a side view of a suction plate on which an optical system of a second embodiment is mounted for sensing polarized light directed through an LCD panel and a polarization film;

[0022] **FIGS. 6A** is an enlarged perspective view of a portion of an LCD panel and a first polarization film of the second embodiment through which polarized light is directed;

[0023] **FIGS. 6B** is an enlarged perspective view of a portion of the LCD panel and a second polarization film of the second embodiment through which polarized light is directed;

[0024] **FIG. 7** is a side view of a suction plate on which an optical system of a third embodiment of the present invention is mounted for sensing polarized light directed through an LCD panel and a polarization film;

[0025] **FIG. 8** is a side view of a suction plate on which an optical system of a fourth embodiment of the present invention is mounted for sensing polarized light directed at a skewed angle through an LCD panel and an optical compensation film;

[0026] **FIG. 9A** is an enlarged perspective view of a portion of an LCD panel and a first optical compensation film of the fourth embodiment;

[0027] **FIG. 9B** is an enlarged perspective view of a portion of the LCD panel and a first polarization film of the fourth embodiment;

[0028] **FIG. 9C** is an enlarged perspective view of a portion of the LCD panel and a second optical compensation film of the fourth embodiment; and

[0029] **FIG. 9D** is an enlarged perspective view of a portion of the LCD panel and a second polarization film of the fourth embodiment.

DETAILED DESCRIPTION

[0030] In **FIG. 1**, there is shown a system for pasting a polarization film on each surface of an LCD (liquid crystal display) panel according to the present invention. The system is comprised of first, second, third and fourth work stations 61 to 64.

[0031] At the first work station 61, a holder (suction) base 21 is provided for setting a polarization film 4 in a predetermined fixed position using three vertically movable edge guides 70 and holding it in position with a flow of sucking air that is drawn to the outside through a plurality of holes provided on the surface of the base 21. Guides 70 are lowered below the surface of the base 21 when the film 4 is properly held in position. Polarization film 4 is coated with a layer of transparent adhesive 41 covered with a separable sheet 42. When the polarization film 4 is held on the surface of the base 21, the separable sheet 42 is facing downwards.

[0032] Further, at the first work station, a film carrier 65 is provided above the suction base 21. Carrier 65 includes a suction plate 22 which is supported by a movable arm 80 connected to a drive system, not shown, so that the plate 22 is vertically movable between high and low positions and horizontally slidable between the first and second stations 61 and 62.

[0033] When the carrier 65 is in the lower position, the suction air that is holding the film 4 on the base 21 is stopped and the suction plate 22 starts sucking air upwards so that the film 4 is removed from the base 21 and attached to the bottom of the plate 22. Carrier 65 is then raised to the higher position and is started moving towards the second work station 62. Before reaching the second station, the carrier 65 encounters a sheet remover 66 where the separable sheet 42 of the polarization film is brought into contact with a roll 24 of adhesive tape which is rotating about its horizontal axis. While rotating about its axis, the roll 24 slides from one edge of the polarization film 4 to the other in a direction normal to the direction of its rotation. As a result, an adhesive layer is applied to the lower side of separable sheet 42. At the end of the travel, the roll 24 stops and then moves backwards while rotating about its axis so that the separable sheet 42 is peeled off the polarization film 4, exposing the sticking layer 41 to the outside.

[0034] Then, the carrier 65 moves to the second work station 62. At the second work station, an LCD panel 10 is set on a suction base 25 using three vertically movable edge guides 71 and held under negative pressure caused by air downwardly sucked through a plurality of holes provided on the surface of the base 25. Guides 71 are lowered below the surface of the base 25 when the LCD panel 10 is held in position.

[0035] As illustrated, the LCD panel 10 is comprised of a pair of glass substrates 11 and 12, a color filter 13 below the substrate 11, a common electrode 14 and a pixel electrode 15. A liquid crystal layer 1, which is sandwiched between

orientation (or alignment) layers **2** and **3**, is disposed between the electrodes **14** and **15**. Each of these orientation layers has a polarization axis orthogonal to the polarization axis of the other.

[0036] In order to provide precision alignment of polarization axes between the polarization film **4** and the orientation layer **2** which is positioned on the upper side of the liquid crystal layer **1**, polarized light is directed from a polarized light source **26** mounted on the suction base **25** through the LCD panel **10** to an optical system **23** on the suction plate **22**.

[0037] Referring briefly to FIGS. **2** to **4**, the optical system **23** according to a first embodiment of the present invention is illustrated.

[0038] In FIG. **2**, the optical system **23** is shown comprising a polarizer **90** secured to one side of the suction plate **22** and an optical sensor **91** located above the polarizer **90**. Suction plate **22** horizontally and vertically moves with respect to the suction base **25** when the arm **80** is driven by the drive mechanism, not shown, so that the polarizer **90** is positioned above the LCD panel **10**. Polarization film **4**, whose polarization axis must be aligned with that of orientation layer **2**, is attached to the bottom of the suction plate **22** so that its axis is orthogonal to that of polarizer **90**. To allow adjustment for axial alignment, the suction plate is made to swivel on the vertical axis **81** of the arm **80** when the polarizer **90** is positioned above the LCD panel **10**. Polarized light source **26** includes a natural light source **84** and a polarizer **85** for forming the natural light into linearly polarized light whose polarization axis is aligned with the polarization axis of one of the orientation layers which is positioned on the lower side of the LCD panel **10**. Details of the optical alignment system of the first embodiment are shown in FIG. **3A**.

[0039] When the polarization film **4** is in the process of axial alignment, the orientation layer **3** is on the lower side of liquid crystal layer **1** and is irradiated from below with the linearly polarized light. With the electrodes **14** and **15** being turned off, the liquid crystal layer **1** is free of electrostatic charges. Under the influence of orientation layers **2** and **3**, liquid crystal molecules LC in the layer **1** are twisted and align at the opposite surfaces of the layer **1** with the orthogonal axes **(3)** and **(2)** of the orientation layers **3** and **2**. The polarized light from source **26**, having the same polarization axis **(3)** of the orientation layer **3**, is incident on the liquid crystal layer **1**. The incident light undergoes a 90-degree rotation of its axis as it travels across the liquid crystal layer **1** and emanates from the orientation layer **2** with an axis oriented in the same axis **(2)** of orientation layer **2**. The light from the LCD panel **10** is passed through the polarizer **90** and impinges on the optical sensor **91**. The amount of light incident on the optical sensor **91** is monitored and adjusted by turning the plate **22** on the vertical axis **81**. Since the polarizer **90** has its axis oriented in a direction orthogonal to that of polarization film **4**, a minimum amount of rays will be incident on the optical sensor **91** when the axis of polarization film **4** is aligned with the axis of orientation layer **2**. The orthogonal orientation permits observers to perform black luminance measurement, rather than white luminance measurement. Since axial alignment occurs when the observed light is at a minimum level, the black luminance measurement allows a higher degree of precision than

the white luminance measurement. If white luminance measurement is preferred for some reasons, the polarization film **4** has its axis aligned with that of the polarizer **90**.

[0040] When the optical alignment process is complete, a pasting process is provided for pasting the polarization film **4** to the LCD panel **10**. For this purpose, a roller **83** is attached to the opposite side of the plate **22** and the latter is mounted on a horizontal axle **82** of the arm **80** so that the surface of polarization film **4** can be tilted with respect to the surface of the LCD panel **10** and one edge of the former is in contact with a corresponding edge of the latter, as shown in FIG. **4**. In this position, the roller **83** is brought into pressure contact with the polarization film **4**. Suction plate **22** is then moved to slide over the suction base **25**. As the suction plate **22** is moved, the polarization film **4** is slidably moved downwards against the air-sucking holes (not shown) provided on the bottom of plate **22** and pressed into contact with the LCD panel **10**. Since the lower surface of polarization film **4** is applied with an adhesive layer, the contact portion of the film **4** is cemented to the LCD panel **10**.

[0041] Returning to FIG. **1**, the LCD panel **10** with the polarization film **4** being cemented is mounted on a reversing suction plate **27** which is hinged at one end on a horizontal pivot axle. The pivot axle of the reversing suction plate **27** is driven by a motor, not shown, whereby the LCD panel is turned upside down and set on a suction base **32** of the fourth work station **64**. Polarization film **4** is now positioned on the lower side of LCD panel **10**. LCD panel **10** is held in position using three vertically movable edge guides **73** and the air suction system, not shown.

[0042] In a manner similar to that described above, a polarization film **5** is positioned on a suction base **2** at the third work station **63** using movable upright guides **72** which are then lowered below the surface of the suction base **28** when the film **5** is properly held in position. Polarization film **5** is coated with a transparent adhesive layer **51** covered with a separable sheet **52**. When the polarization film **5** is held on the surface of the base **28**, the separable sheet **52** is facing downwards.

[0043] At the third work station **63**, a film carrier **68** is provided above the suction base **28**. Carrier **68** includes a suction plate **29** which is supported by a movable arm **86** connected to a drive system, not shown, so that the suction plate **29** is vertically movable between high and low positions and horizontally slidable between the third and fourth stations **63** and **64**. When the carrier **68** is in the lower position, the suction air that is holding the film **5** on the base **28** is stopped and the suction plate **29** starts sucking air upwards so that the film **5** is removed from the base **28** and attached to the bottom of the plate **29**. Polarization film **5**, whose polarization axis must be aligned with that of orientation layer **3**, is secured to the suction plate **29** with its axis oriented in a direction orthogonal to that of the polarizer **90** of optical system **30**.

[0044] Carrier **68** is then raised to the higher position and is started moving towards the fourth station **64**. Before reaching the fourth station, the carrier **68** encounters a sheet remover **69** where the separable sheet **52** of the polarization film is brought into contact with a pressure roller **31** of adhesive tape which is rotating about its horizontal axis. While rotating about its axis, the pressure roller **31** slides

from one edge of the polarization film 5 to the other in a direction normal to the direction of its rotation. As a result, an adhesive layer is applied to the lower side of separable sheet 52. At the end of the travel, the pressure roller 31 stops and then moves backwards while rotating about its axis so that the separable sheet 52 is peeled off the polarization film 5, exposing the sticking layer 51 to the outside.

[0045] Then the carrier 68 moves to a position above the suction base 32 of the fourth station 64. An optical system 30, identical to the optical system 23, is mounted on the suction plate 29 to begin an optical alignment process to align the axis of polarization film 5 with that of orientation layer 3 which is now positioned on the upper side of liquid crystal layer 1. A light source 33 is mounted on the suction base 32 to direct natural light to the polarization film 4 which is now positioned on the lower side of liquid crystal layer 1. As shown in detail in FIG. 3B, the natural light is converted to polarized light as it passes through the polarization film 4. This polarized light is aligned with the polarization axis (4) of the film 4 as it impinges on the orientation layer 2.

[0046] When the polarization film 5 is subjected to the optical alignment process, the orientation layer 2 is on the lower side of liquid crystal layer 1 and is irradiated from below with the light polarized by polarization film 4 cemented to the lower side of LCD panel 10. The polarized light from the polarization film 4, having the same polarization axis (2) of the orientation layer 2, is incident on the liquid crystal layer 1 and undergoes a 90-degree rotation of its axis as it travels across the liquid crystal layer 1 and emanates from the orientation layer 3 with an axis aligned with the same axis (3) of orientation layer 3.

[0047] The light from the orientation layer 3 is passed through the polarizer 90 of the optical system 30 and impinges on the optical sensor 91. The amount of light incident on the optical sensor 91 is monitored and adjusted by turning the suction plate 29 on the vertical axis 81 in the same manner as described in connection with the polarization film 4. Since the polarizer 90 of the optical system 30 is orthogonal to the polarization film 5, a minimum amount of rays is incident on the optical sensor 91 when the axis of polarization film 5 is aligned with the axis of orientation layer 3.

[0048] Optical system 30 may also include the optional polarizer 92 located above the first polarizer 90 to provide black luminance measurement, rather than white luminance measurement. A pasting process follows to paste the polarization film 5 to the LCD panel 10 in a manner identical to that described with reference to FIG. 4.

[0049] In the first embodiment, the polarization films 4 and 5 are orthogonal to the polarizer 90 of the optical systems 23 and 30. Since polarizer 90 is mounted on a machine and hence its polarization axis is fixed and precisely determined, misalignment between the polarization film 4 (or 5) and the polarizer 90 is smaller than misalignment which usually occurs between polarization films and orientation layers. However, the misalignment between the polarization film 4 (or 5) and the polarizer 90 can be eliminated by passing polarized light through the polarization films 4 and 5.

[0050] As illustrated in FIG. 5, the optical system 23 (30) includes an optical sensor 93 which is mounted on the suction plate 22 (29) above the polarization film 4 (5) and the light from source 26 (33) is passed through the film 4 to the optical sensor 93. Misalignment between the polarization

film 4 (or 5) and the orientation layer 2 (or 3) is eliminated when a maximum light level is obtained at the optical sensor 93 by swiveling the suction plate 22 (or 29) as seen from FIG. 6A (FIG. 6B). Preferably, a polarizer 94, whose axis is orthogonal to that of the polarization films 4 and 5, may be provided below the optical sensor 93 to provide black luminance measurement.

[0051] The amount of variation that occurs in the output voltage of optical sensor 93 as the suction plate is turned on its vertical axis can be increased to advantage for precision measurement. This is achieved by a modification of the arrangement of FIG. 5 as shown in FIG. 7. In this modification, the optical sensor 93 is arranged to receive polarized light whose optical path traverses the LCD panel 10 and the polarization film 4 or 5 at a skewed angle relative to their surfaces.

[0052] In order to enlarge the viewing angle of an LCD panel, a film known as optical compensation film is sandwiched between a polarization film and an orientation layer on each side of a liquid crystal layer. The optical compensation film is an anisotropic liquid crystal layer of predetermined thickness in which molecules are arranged in a hybrid orientation. The use of optical compensation films prevents leakage of light from excited (turned-on) pixels which is seen at a skewed viewing angle. In contrast with twisted nematic LCD panels whose anisotropy is positive (i.e., molecules are elongated in z-axis direction), the optical compensation film has a negative anisotropic characteristics (i.e., molecules are elongated on the x-y plane). Combined use of a twisted nematic LCD panel and an optical compensation film results in a display having an isotropic refractive characteristic, enabling it to be seen at equal optical levels in a wide range of viewing angles.

[0053] However, angular misalignment can occur between the polarization film and the optical compensation film. While the angular misalignment between the polarization film and the orientation layer can be eliminated as described above, the misalignment between the anisotropic axis of the optical compensation film and the axis of the orientation layer cannot be minimized by the use of the previous embodiments.

[0054] The embodiment shown in FIG. 8 overcomes this shortcoming. The optical system 23 of this embodiment is basically similar in configuration to that shown in FIG. 7. However, the optical system 23 of this embodiment has a polarizer 101 whose axis is aligned with that of the polarizer 85 of light source 26. Optical compensation films are pasted to the LCD panel using the system of FIG. 1 prior to the pasting of polarization films. In FIG. 8, an optical compensation film 6 is shown as a pasting step prior to the pasting of a polarization film 4. FIG. 8 shows that the optical compensation film 6 was secured to the bottom of the suction plate 22 at the first work station 61 and then carried to the second work station 62, where an LCD panel 10 has been held in place. At the second work station, the optical compensation film 6 is irradiated at a skewed angle with polarized light that has been subjected to a 90-degree rotation as it traversed through the LCD panel 10.

[0055] Details of the optical arrangement for axial alignment of optical compensation film 6 at the second work station are shown in FIG. 9A. The light incident on the optical compensation film 6 is one that is linearly polarized as it exits the orientation layer 2. As the light traverses the optical compensation film 6 at a skewed angle, it undergoes a change from linear polarization to elliptical polarization.

Since the elliptically polarized light contains a linear component in the direction of axis (3) of orientation layer 3. This linear component, which would otherwise be seen as leakage light when viewed at an angle, is selected by the polarizer 101 and detected by an optical sensor 100. Misalignment, which may exist between the anisotropic axis (6) of optical compensation film 6 and the polarization axis (2) of orientation layer 2, is minimized by turning the suction plate 22 when the black luminance measurement of optical sensor 100 produces a minimum value. When this occurs, the viewing angle of the LCD panel 10 expands in the direction of polarization axis (3).

[0056] Optical compensation film 6 is then pasted on to LCD panel 10 in the same way as the polarization film 4 was pasted by using the arrangement of FIG. 4.

[0057] With the optical compensation film 6 being pasted on the LCD panel 10 as shown in FIG. 9B, the axis (3) of polarizer 101 is orthogonal to the axis (4) of polarization film 4. Therefore, a minimum value is obtained for black luminance measurement at the output of optical sensor 100 when the polarization film 4 is aligned with the orientation layer 2. Polarization film 4 is then pasted on the optical compensation film 6 and then turned upside down by the reversing suction plate 27 and placed on the suction base 32 at the fourth work station 64.

[0058] Processes similar to those described with reference to FIGS. 9A and 9B are repeated on an optical compensation film 7 and a polarization film 5.

[0059] FIG. 9C shows that the optical compensation film 7 is first placed on the suction base of third station 63 and carried by the carrier 68 to the fourth station 64. Polarizer 101 of the optical system 40 is aligned with the axis (2) of the orientation layer 2. Misalignment, which may exist between the anisotropic axis (7) of optical compensation film 7 and the polarization axis (3) of orientation layer 3, is minimized by turning the suction plate 29 of the carrier 68 when the black luminance measurement of optical sensor 100 produces a minimum value. When this occurs, the viewing angle of the LCD panel 10 expands in the direction of polarization axis (2). Optical compensation film 7 is then pasted on the LCD panel 10.

[0060] With the optical compensation film 7 being pasted on the LCD panel 10 as shown in FIG. 9D, the axis (3) of polarizer 101 is orthogonal to the axis (5) of polarization film 5. A minimum value is thus obtained for black luminance measurement at the output of optical sensor 100 when the polarization film 5 is aligned with the orientation layer 3. Polarization film 5 is then pasted on the optical compensation film 7.

[0061] Note that in FIGS. 9B and 9D, the polarizer 101 may be dispensed with if white luminance measurement is used for detecting misalignment.

What is claimed is;

1. A method of fabricating a liquid crystal display, comprising the steps of:

setting a liquid crystal display panel on a fixed base, said panel including a liquid crystal layer and an orientation layer on one surface of said liquid crystal layer;

setting an anisotropic film relative to said orientation layer;

directing linearly polarized light to said panel and said anisotropic film and detecting light therefrom; and

adjusting angle of orientation of said anisotropic film relative to said orientation layer according to intensity of the detected light.

2. The method of claim 1, wherein the step (b) further comprises setting a second anisotropic film and the first-mentioned anisotropic film relative to said orientation layer, and wherein said second anisotropic film has a polarization axis aligned with polarization axis of the first anisotropic film.

3. The method of claim 2, wherein the polarization axis of said first anisotropic film is orthogonal to polarization axis of said orientation layer.

4. The method of claim 1, wherein the step (b) further comprises setting a second anisotropic film parallel to the first-mentioned anisotropic film, whereby said linearly polarized light passes through the first and second anisotropic films, said second anisotropic film having a polarization axis orthogonal to polarization axis of the first anisotropic film.

5. The method of claim 1, further comprising pasting said anisotropic film on said orientation layer after the step (e) is performed.

6. The method of claim 1, wherein the step (c) comprises directing said linearly polarized light in a direction perpendicular to said panel.

7. The method of claim 1, wherein the step (c) comprises directing said linearly polarized light at a skewed angle to said panel.

8. A method of fabricating a liquid crystal display, comprising the steps of:

setting a liquid crystal display panel on a fixed base, said panel including a liquid crystal layer and an orientation layer on one surface of said liquid crystal layer;

setting an optical compensation film and a polarizer relative to said orientation layer;

directing linearly polarized light to said panel, said optical compensation film and said polarizer at a skewed angle and detecting light therefrom, said linearly polarized light having a polarization axis aligned with polarization axis of said polarizer; and

adjusting angle of orientation of said optical compensation film relative to said orientation layer according to intensity of the detected light.

9. The method of claim 8, further comprising pasting said optical compensation film on said orientation layer after the adjusting step is performed.

10. The method of claim 9, further comprising the steps of:

setting a polarization film relative to said orientation layer;

directing linearly polarized light to said panel, said optical compensation film, and said polarization film at said skewed angle and detecting light therefrom; and

adjusting angle of orientation of said polarization film relative to said orientation layer according to intensity of the detected light.

11. The method of claim 9, further comprising the steps of:

setting a polarization film and said polarizer relative to said orientation layer;

directing linearly polarized not to said panel, said optical compensation film, said polarization film and said polarizer at said skewed angle and detecting light therefrom, said linearly polarized light having a polarization axis aligned with polarization axis of said polarizer; and

adjusting angle of orientation of said polarization film relative to said orientation layer according to intensity of the detected light.

12. The method of claim 10, further comprising pasting said polarization film on said optical compensation film after the adjusting step is performed.

13. The method of claim 11, further comprising pasting said polarization film on said optical compensation film after the adjusting step is performed.

14. A system for fabricating a liquid crystal display, comprising:

base means for setting a liquid crystal display panel, said panel including a liquid crystal layer and an orientation layer on one surface of said liquid crystal layer;

carrier means for setting an anisotropic film relative to said orientation layer;

a light source for directing linearly polarized light to said panel and said anisotropic film; and

an optical sensor for detecting the directed light from said anisotropic film,

said carrier means being rotatable so that angle of orientation of said anisotropic film can be adjusted relative to said orientation layer according to intensity of the detected light.

15. The system of claim 14, wherein said carrier means includes means for setting a second anisotropic film and the first-mentioned anisotropic film relative to said orientation layer, and wherein said second anisotropic film has a polarization axis aligned with polarization axis of the first anisotropic film.

16. The system of claim 15, wherein the polarization axis of said first anisotropic film is orthogonal to polarization axis of said orientation layer.

17. The system of claim 14, wherein the carrier means further comprises means for setting a second anisotropic film parallel to the first-mentioned anisotropic film, whereby said linearly polarized light passes through the first and second anisotropic films, said second anisotropic film having a polarization axis orthogonal to polarization axis of the first anisotropic film.

18. The system of claim 14, wherein said carrier means includes means for pasting said anisotropic film on said orientation layer.

19. The system of claim 14, wherein the light source is arranged to direct said linearly polarized light in a direction perpendicular to said liquid crystal display panel.

20. The system of claim 14, wherein the light source is arranged to direct said linearly polarized light at a skewed angle to said liquid crystal display panel.

21. A system for fabricating a liquid crystal display, comprising:

base means for setting a liquid crystal display panel, said panel including a liquid crystal layer and an orientation layer on one surface of said liquid crystal layer;

carrier means for setting an optical compensation film and a polarizer relative to said orientation layer;

a light source for directing linearly polarized light to said panel said optical compensation film and said polarizer at a skewed angle;

an optical sensor for detecting the directed light from said polarizer,

said linearly polarized light having a polarization axis aligned with polarization axis of said polarizer; and

said carrier means being rotatable so that angle of orientation of said optical compensation film can be adjusted relative to said orientation layer according to intensity of the detected light.

22. The system of claim 21, wherein said carrier means includes means for pasting said optical compensation film on said orientation layer.

* * * * *

专利名称(译)	通过光学检测各向异性角度不对准来制造液晶显示器的方法和系统		
公开(公告)号	US20020001060A1	公开(公告)日	2002-01-03
申请号	US09/892836	申请日	2001-06-27
申请(专利权)人(译)	NEC公司		
[标]发明人	MATSUZAWA TADASHI		
发明人	MATSUZAWA, TADASHI		
IPC分类号	G02F1/13 G02F1/1335 G02F1/13363		
CPC分类号	G02F1/133528 G02F1/13363 G02F2413/08		
优先权	2000199562 2000-06-30 JP		
其他公开文献	US6621551		
外部链接	Espacenet USPTO		

摘要(译)

液晶显示面板放置在固定基底上，各向异性膜设置在相对于显示面板的取向层的位置。线性偏振光被引导到面板，并且检测各向异性膜和穿过它们的光。根据检测到的光的强度，相对于取向层调节各向异性膜的取向角。可以存在于各向异性膜和定向层之间的角度不对准被最小化。

