



US 20080186435A1

(19) **United States**(12) **Patent Application Publication**
Son(10) **Pub. No.: US 2008/0186435 A1**(43) **Pub. Date: Aug. 7, 2008**(54) **LIQUID CRYSTAL DISPLAY DEVICE AND
METHOD OF FABRICATING THE SAME****Publication Classification**(51) **Int. Cl.****G02F 1/1335** (2006.01)(52) **U.S. Cl.** **349/106; 445/24**


(57)

ABSTRACT

A liquid crystal display device includes a black matrix between first and second substrates, the black matrix having openings defined therein, color filters between the first and second substrates and aligned with the openings defined in the black matrix, the color filters including first filters having a first color, second filters having a second color, and third filters having a third color; and spacers configured to maintain a predetermined cell gap. The second filters have a recess, such that the second filters have an area that is less than an area of the first filters, the spacers are aligned with regions of the black matrix adjacent to the recesses in the second filters, and alignment layers are on the first and second substrates.

(76) **Inventor: Dong Soo Son, Suwon-si (KR)****Correspondence Address:****LEE & MORSE, P.C.****3141 FAIRVIEW PARK DRIVE, SUITE 500****FALLS CHURCH, VA 22042**(21) **Appl. No.: 12/068,423**(22) **Filed: Feb. 6, 2008**(30) **Foreign Application Priority Data**

Feb. 7, 2007 (KR) 10-2007-12869






FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D





FIG. 5E



LIQUID CRYSTAL DISPLAY DEVICE AND METHOD OF FABRICATING THE SAME

BACKGROUND OF THE INVENTION

[0001] 1. Field of the Invention

[0002] Embodiments relate to a liquid crystal display device and a method of fabricating the same. More particularly, embodiments relate to a liquid crystal display device having a black matrix with a predetermined distance around a patterned spacer, and a method of fabricating the same.

[0003] 2. Description of the Related Art

[0004] A liquid crystal display device is a flat panel display device widely used in televisions, computers, mobile devices, embedded applications, etc. The liquid crystal display device utilizes unique physical and optical properties of a liquid crystal. Generally, the liquid crystal is arranged between two substrates having a pattern of electrodes, e.g., transparent electrodes, the two substrates being sealed with a sealing agent and kept separated by spacers arranged between the two sealed substrates.

[0005] The spacer serves to maintain a constant distance, or cell gap, between the two substrates. A ball spacer, e.g., a generally spherical spacer, has been widely used, but such ball spacers tend to be nonuniformly arranged on the substrate. The low aspect ratio of the ball may reduce the aperture ratio and transmittance of the liquid crystal display device. Further, the nonuniform distribution of the ball spacers may make it difficult or impossible to maintain a constant cell gap.

SUMMARY OF THE INVENTION

[0006] Embodiments are therefore directed to a liquid crystal display device and method of fabricating the same, which substantially overcome one or more of the problems due to the limitations and disadvantages of the related art.

[0007] It is therefore a feature of an embodiment to provide a liquid crystal display device having spacers aligned on a black matrix, and having color filters and the black matrix configured to provide a predetermined distance around the spacers.

[0008] It is therefore another feature of an embodiment to provide a method of fabricating a liquid crystal display device that includes forming color filters, a black matrix, and spacers aligned with the black matrix such that a predetermined distance between a color filter area and the spacers is provided.

[0009] At least one of the above and other features and advantages may be realized by providing a liquid crystal display device, including a black matrix between first and second substrates, the black matrix having openings defined therein, color filters between the first and second substrates and aligned with the openings defined in the black matrix, the color filters including first filters having a first color, second filters having a second color, and third filters having a third color, and spacers configured to maintain a predetermined cell gap. The second filters may have a recess, such that the second filters have an area that is less than an area of the first filters, the spacers may be aligned with regions of the black matrix adjacent to the recesses in the second filters, and alignment layers may be on the first and second substrates.

[0010] The first substrate may include first electrodes extending in a first direction, the second substrate may include second electrodes extending in a second direction and crossing the first electrodes, and the openings in the black matrix may correspond to overlapping regions of the first and

second electrodes. The first filters may have a shape corresponding to the overlapping regions of the first and second electrodes. The color filters may be arranged in a stripe pattern, the second filters may be immediately adjacent to each other in a first direction, and the second filters may alternate with the first and third filters in a second direction.

[0011] Immediately adjacent second filters may have recesses facing one another. The black matrix may include first portions extending in the first direction, the black matrix may include second portions extending in the second direction and passing between the immediately adjacent second filters, the second portions may be wider in regions between the facing recesses of the second filters than in regions between facing portions of immediately adjacent first filters, and the spacers may be aligned with the wider regions.

[0012] The first substrate may include first electrodes extending in the first direction, the second substrate may include second electrodes extending in the second direction and crossing the first electrodes, and the openings in the black matrix may correspond to overlapping regions of the first and second electrodes. The first filters may not be recessed and the first color may be red. The recesses may be defined by angled sides of the second filters.

[0013] At least one of the above and other features and advantages may also be realized by providing a method of fabricating a liquid crystal display device, the method including forming a black matrix between first and second substrates, the black matrix having openings defined therein, forming color filters between the first and second substrates such that the color filters are aligned with the openings defined in the black matrix, the color filters including first filters having a first color, second filters having a second color, and third filters having a third color, and forming spacers configured to maintain a predetermined cell gap. The second filters may be formed to have a recess, such that the second filters are formed with an area that is less than an area of the first filters, and the spacers may be formed to be aligned with regions of the black matrix adjacent to the recesses in the second filters. Alignment layers may be formed on the first and second substrates.

[0014] The first substrate may include first electrodes extending in a first direction, the second substrate may include second electrodes extending in a second direction and crossing the first electrodes, and the openings in the black matrix may correspond to overlapping regions of the first and second electrodes. The first filters may be formed to have a shape corresponding to the overlapping regions of the first and second electrodes.

[0015] The color filters may be arranged in a stripe pattern, the second filters may be immediately adjacent to each other in a first direction, and the second filters may alternate with the first and third filters in a second direction. Immediately adjacent second filters may be formed to have recesses facing one another. The black matrix may include first portions extending in the first direction, the black matrix may include second portions extending in the second direction and passing between the immediately adjacent second filters, the second portions may be wider in regions between the facing recesses of the second filters than in regions between facing portions of immediately adjacent first filters, and the spacers may be aligned with the wider regions.

[0016] The first substrate may include first electrodes extending in the first direction, the second substrate may include second electrodes extending in the second direction

and crossing the first electrodes, and the openings in the black matrix may correspond to overlapping regions of the first and second electrodes. The first filters may not be recessed and the first color may be red. The recesses may be defined by angled sides of the second filters. Forming the spacers may include forming a spacer material layer on the second substrate, and patterning the spacer material layer to form the spacers aligned with regions of the black matrix adjacent to the recesses in the second filters. Forming the alignment layer on the second substrate may include performing a rubbing operation to form an alignment pattern after patterning the spacer material layer.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] The above and other features and advantages of the present invention will become more apparent to those of ordinary skill in the art by describing in detail exemplary embodiments thereof with reference to the attached drawings, in which:

[0018] FIG. 1 illustrates a schematic cross-sectional view of a liquid crystal display device according to an embodiment;

[0019] FIG. 2 illustrates a configuration of first and second electrodes in the liquid crystal display device of FIG. 1;

[0020] FIG. 3 illustrates a plan view of a color filter substrate of the liquid crystal display device of FIG. 1;

[0021] FIG. 4 illustrates a cross-sectional view along a region (I-I') of FIG. 3; and

[0022] FIG. 5A to FIG. 5E illustrate cross-sectional views of stages in a method of forming a color filter substrate in the liquid crystal display device of FIG. 1.

DETAILED DESCRIPTION OF THE INVENTION

[0023] Korean Patent Application No. 10-2007-0012869, filed on Feb. 7, 2007, in the Korean Intellectual Property Office, and entitled: "Liquid Crystal Display Device and Method of Fabricating the Same," is incorporated by reference herein in its entirety.

[0024] Example embodiments will now be described more fully hereinafter with reference to the accompanying drawings; however, they may be embodied in different forms and should not be construed as limited to the embodiments set forth herein. Rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art.

[0025] In the figures, the dimensions of layers and regions may be exaggerated for clarity of illustration. It will also be understood that when a layer or element is referred to as being "on" another layer or substrate, it can be directly on the other layer or substrate, or intervening layers may also be present. Further, it will be understood that when a layer is referred to as being "under" another layer, it can be directly under, and one or more intervening layers may also be present. In addition, it will also be understood that when a layer is referred to as being "between" two layers, it can be the only layer between the two layers, or one or more intervening layers may also be present. Like reference numerals refer to like elements throughout.

[0026] FIG. 1 illustrates a schematic cross-sectional view of a liquid crystal display device 100 according to an embodiment, and FIG. 2 illustrates a configuration of first and second electrodes in the liquid crystal display device 100 of FIG. 1. Referring to FIGS. 1 and 2, the liquid crystal display device

100 may be, e.g., a passive matrix mode device in which liquid crystal is sandwiched between an electrode lead (segment) and an electrode plate (common), wherein subpixels are driven by two opposing electrodes. The liquid crystal display device 100 may be, e.g., a twisted nematic liquid crystal display device (TN-LCD), a super twisted nematic liquid crystal display device (STN-LCD), etc. In an implementation, the liquid crystal display device 100 may be a STN-LCD having an angle of twist of about 240° to about 270°, and may exhibit a transmittance that changes sharply according to an applied voltage. The STN-LCD may be desirable for a passive matrix mode liquid crystal display device, since the change in the arrangement of the liquid crystal molecules may be high for changes in voltage adjacent to the threshold voltage.

[0027] The liquid crystal display device 100 may include a first substrate 110 and a second substrate 120 arranged to face the first substrate 110, as well as spacers 130, e.g., patterned column spacers or photo spacers, formed in predetermined regions of the second substrate 120 and maintaining a cell gap between the first and second substrates 110 and 120. The spacers 130 may extend between the substrates 110 and 120, e.g., parallel to the Z axis direction shown in FIGS. 1 and 2. In an implementation, the liquid crystal display device 100 may be a passive matrix mode device in which the spacers 130 have a diameter of about 17 μm. A liquid crystal 105 may be injected between the first and second substrates 110 and 120.

[0028] In greater detail, a first alignment layer 116 and a second alignment layer 129 may be formed at facing surfaces of the first and second substrates 110 and 120, respectively. The first and second alignment layers 116 and 129 may each have alignment patterns formed therein, the alignment patterns determining an alignment angle of the liquid crystal. The alignment patterns may be formed by, e.g., a rubbing operation. In an implementation, the alignment layers 116 and 129 may be formed on planarization layers 114 and 126, respectively.

[0029] First electrodes 112 may be formed in a pattern on the first substrate 110, and second electrodes 128 may be formed in a pattern on the second substrate 120. The first electrodes 112 may extend in a first direction, e.g., parallel to the Y axis shown in FIGS. 1 and 2. The second electrodes may extend in a second direction, e.g., parallel to the X axis shown in FIGS. 1 and 2. The second electrodes 128 may be arranged to cross the first electrodes 112, e.g., at right angles so as to be perpendicular to the first electrodes 112, etc. The first electrodes 112 may include electrodes 112r, 112g, and 112b corresponding to red, green, and blue subpixels 200, respectively. Regions of overlap between the first electrodes 112 and the second electrodes 128 may correspond to subpixels 200. For example, a subpixel 200 may be formed at each position where a first electrode 112 and a second electrode 128 cross each other, as shown in FIG. 2. One subpixel 200 of each color may be disposed between spacers 130 that are immediately adjacent to one another in the second direction. For example, a pattern of a spacer 130, one each of red, green and blue subpixels 200, a second spacer 130, a second one of each of red, green and blue subpixels 200, etc., may be arranged in sequence along the X axis direction.

[0030] The second substrate 120 may include a black matrix 122 surrounding color filters 124 in the subpixels 200. The black matrix 122 may be a non-display region serving as an optical barrier layer for preventing image quality degradation due to optical leakage between the subpixels 200. The

color filters **124**, e.g., red (R), green (G) and blue (B) color filters **124r**, **124g**, and **124b**, may be respectively formed in openings defined in the black matrix **122**.

[0031] FIG. 3 illustrates a plan view of the second substrate **120** of the liquid crystal display device **100**. Referring to FIG. 3, the liquid crystal display device **100** may have the black matrix **122** and at least one of the color filters **124** shaped so as to provide an enlarged black matrix region around the spacers **130**. For example, a side of a predetermined one of the red, green or blue color filters **124r**, **124g** or **124b** may be recessed corresponding to an enlarged portion of the black matrix **122**. In an implementation, the color filters having the recesses may be the green color filters **124g**. In another implementation the color filters having the recesses may be the blue color filters **124b**. In an implementation, facing sides of the predetermined color of the color filters **124**, e.g., facing sides of the green color filters **124g**, or facing sides of the blue color filters **124b**, may be patterned to have mirror-image recesses therein, as illustrated by the green color filters **124g** in FIG. 3.

[0032] The enlarged black matrix region **122** corresponding to the recesses of the color filters **124** may provide a larger distance, e.g., a constant distance provided by the recessed shape, between the spacers **130** and the color filters **124** than would exist if no recess were provided in the color filters **124**. Thus, the arrangement illustrated in FIG. 3 may help prevent light leakage in the subpixels **200** adjacent to the spacers **130**. In particular, in a conventional liquid crystal display device, light leakage caused by nonuniformities in the alignment layer may result where a rubbing operation, used to form the alignment pattern in the alignment layer, is locally disrupted by the presence of protrusions such as spacers. In contrast, the larger distance between the spacers **130** and the color filters **124** in the liquid crystal display device **100** may reduce or eliminate nonuniformities in the alignment layer in the subpixels **200**. Thus, it will be appreciated that the enlarged regions of the black matrix **122** provided by the recessed color filters **124** in the liquid crystal display device **100** may further enhance the advantages afforded by the use of patterned spacers as compared to conventional ball spacers. Accordingly, even if a rubbing process is carried out on the second substrate **120**, it may be possible to avoid the light leakage phenomenon typically associated with patterned spacers, while obtaining the positive effects, e.g., improved transmittance and uniform cell gaps, afforded by having regularly spaced patterned spacers outside of the subpixels.

[0033] FIG. 4 illustrates a cross-sectional view along a region (I-I') of FIG. 3. Referring to FIGS. 3 and 4, the liquid crystal display device **100** may have the black matrix **122**, the color filters **124**, the second electrodes **128** and the spacers **130** all formed on the second substrate. The black matrix **122** may be formed on the second substrate **120** in a matrix pattern and may divide pixels into a plurality of subpixels **200** in which the color filters **124** will be subsequently formed. Further, as described above, the black matrix **122** may help prevent light interference between the adjacent subpixels **200** during operation of the liquid crystal display device **100**.

[0034] The color filters **124** may be formed in the subpixels **200** defined by the black matrix **122**. The color filters **124** may be formed by respective red, green and blue color materials, which may produce red, green and blue colors in the subpixels **200** forming one unit pixel. The subpixels **200** may correspond to intersections of the first electrodes **112** and the second electrodes **128**, and may have a shape corresponding to the overlapping regions of the intersections, e.g., a gener-

ally rectangular shape. As discussed above, the shape may be recessed for a predetermined color of the color filters **124**. For example, the green color filters **124g** or the blue color filters **124b** may be formed with recesses, such that facing sides of adjacent color filters of the same color, e.g., green or blue, are each recessed as compared to the rectangular shapes of the remaining color filters, e.g., blue and red, or green and red, respectively. The shape of the recess is preferably an angle, such as the inclined shape of the green color filters **124g** shown in FIG. 3.

[0035] The second electrode **128** may be formed on the substrate **120** on which the color filters **124** and the black matrix **122** are formed, and the liquid crystal may be disposed between the first and second substrates **110** and **120**. A reference voltage for driving the liquid crystal may be supplied to the second electrodes **128**. In an implementation, the planarization layer **126** may be formed on the color filters **124** and the black matrix **122**, and the second electrode **128** may be formed on the planarization layer **126**. The spacers **130** may be formed on the planarization layer **126** or the second electrode **128** corresponding to the recesses in the color filters **124**. In an implementation, the spacers **130** may be formed on the planarization layer **126**, as illustrated in FIGS. 1 and 4.

[0036] In an implementation, the spacers **130** may be disposed in regions of the black matrix **122** that are enlarged by recessing, e.g., with an inclined shape, predetermined regions of both facing sides of the adjacent color filters **124** having the same color. Recessing both facing sides may be preferable to recessing just one of the facing sides.

[0037] FIG. 5A to FIG. 5E illustrate cross-sectional views of stages in a method of forming a color filter substrate in the liquid crystal display device of FIG. 1, with the view illustrated in FIG. 5E corresponding to that illustrated in FIG. 4. Referring to FIG. 5A, the second substrate **120** may be a transparent substrate. The black matrix **122** may be formed on the second substrate by, e.g., coating the entire substrate **120** with an opaque material layer and patterning the opaque material layer. In an implementation, the opaque material layer may include an opaque metal or opaque resin containing chromium (Cr), and patterning the layer may include forming a photoresist layer on the opaque material and then patterning the photoresist. The photoresist may be patterned in a cutoff region corresponding to a barrier unit of a photomask by lining up the photomask having a predetermined pattern with the second substrate **120** and exposing and developing the photoresist. Then, the black matrix **122** may be formed by patterning the opaque material, e.g. using an etching process through the photoresist pattern.

[0038] Referring to FIG. 5B, the second substrate **120** on which the black matrix **122** is formed may be coated with a red color photoresist. In an implementation, the red color photoresist may be soft-baked for a predetermined time on a hot plate having a temperature of, e.g., about 80° C. to about 110° C., exposed using a photomask, and then developed. Subsequently, the developed red color photoresist may be post-baked to form the red color filters **124r** in first predetermined openings of the black matrix **122** defined by a surrounding edge of the black matrix **122**. Then, the green color filters **124g** may be formed in the same manner as described for the red color filters **124r**, the green color filters **124g** being in second predetermined openings in the black matrix **122** and separated from the red color filters **124r** by portions of the black matrix **122**. Subsequently, blue color filters **124b** may be formed in the same manner as described for the red color

filters **124r**, the blue color filters **124b** being in third predetermined openings in the black matrix **122** and separated from the red and green color filters **124r** and **124g** by portions of the black matrix **122**.

[0039] With particular respect to the shapes of the red, green and blue color filters **124r**, **124g** and **124b**, two photomasks, each defining a different shape, may be employed to pattern the respectively colored photoresists. A first photomask may be employed to pattern one or more of the colored photoresists with patterns corresponding to the shape of overlapping regions of the first and second electrodes **112** and **128**. A second photomask may be employed to pattern another of the colored photoresists with a recessed pattern. For example, the first photomask may be employed to pattern the red and blue photoresists, and the second photomask may be employed to pattern the green photoresist. In another example, the first photomask may be employed to pattern the red and green photoresists, and the second photomask may be employed to pattern the blue photoresist. The second photomask may generate a shape that is a truncated form, e.g., an oblique shape, of the shape generated by the first photomask. The second photomask may generate pairs of shapes, with each shape having a recess that faces the recess of the opposing shape.

[0040] Next, referring to FIG. 5C, a planarization layer **126** and second electrodes **128** may be formed, the planarization layer **126** protecting the black matrix **122** and the color filters **124** from external impacts and environmental factors, as well as enhancing its smoothness. In forming the planarization layer **126**, an organic transparent resin, e.g., an acrylate, a polyimide, a polyacrylate, a polyurethane, etc., having high surface hardness and excellent light transmission may be formed to a predetermined thickness and then heated, e.g., for about 1 hour in a baking oven having a temperature of about 200° C. The second electrodes **128** may be configured to apply power to the liquid crystal in cooperation with the first electrodes **112** formed on the first substrate **110** in order to drive the liquid crystal. In forming the second electrodes **128**, a transparent metal-containing material, e.g., ITO, etc., may be deposited on the entire surface of the planarization layer **126**, e.g., at a thickness of about 1,500 Å to 2,200 Å. The transparent metal-containing material may then be patterned to form the second electrodes **128**.

[0041] Next, the spacers **130** may be formed on the enlarged regions of the black matrix **122** corresponding to the recessed color filters **124**, as shown in FIG. 5D. The patterned spacer **130** may be formed to extend to the planarization layer **126**, as illustrated in FIG. 5D. In another implementation (not shown), the spacers **130** may be formed to extend to the second electrodes **128**.

[0042] In an implementation, forming the spacers **130** may include providing a spacer material mixture, e.g., a mixture of a solvent, a binder, a monomer and a photoinitiator, and printing the spacer material mixture on the substrate. The spacer material mixture may then be dried and the solvent volatilized to form a spacer material in which the binder, the monomer and the photoinitiator are mixed. The spacer material may then be polymerized.

[0043] The second substrate **120** having the polymerized spacer material thereon may then be coated with a photoresist. A photomask for defining the spacers **130** may be aligned with the second substrate **120**. The photomask may include a mask substrate formed of transparent material to form an exposed region, and may further include a barrier layer on the

mask substrate to form a cutoff region. A photoresist pattern may be formed by carrying out an exposure process that selectively irradiates the photoresist with ultraviolet light through the photomask, and then developing the exposed photoresist. Referring to FIG. 5D, the spacers **130** having a predetermined height may be formed by patterning the spacer material using an etching process, the patterned photoresist serving as an etch mask.

[0044] Referring to FIG. 5E, the alignment layer **129** may then be formed on the second substrate **120**. Forming the alignment layer **129** may include applying an alignment material layer, e.g., a polyimide layer, on the second substrate **120** and surrounding the spacers **130**. An alignment pattern may then be formed in the alignment material layer using, e.g., a rubbing process, to produce the alignment layer **129**. Due to the distance provided by the recesses in the color filters adjacent to the spacers **130**, any nonuniformities in the alignment layer **129** resulting from the rubbing process in the vicinity of the spacers may not overlap the color filters **124**, i.e., any such nonuniformities may overlap the enlarged portions of black matrix **122**. Accordingly, the liquid crystal display device may exhibit little or no light leakage.

[0045] As described above, a liquid crystal display device according to embodiments may avoid the problems associated with the use of ball spacers. Further a liquid crystal display device according to embodiments may avoid the problem of light leakage associated with the use of a rubbing process in displays that incorporate patterned spacers. A liquid crystal display device according to embodiments may also provide an improved contrast ratio as compared to a passive matrix mode liquid crystal display device using the conventional ball spacers.

[0046] Example embodiments of the present invention have been disclosed herein, and although specific terms are employed, they are used and are to be interpreted in a generic and descriptive sense only and not for purpose of limitation. For instance, although a passive matrix mode liquid crystal display device is described in an example embodiment, an active matrix mode liquid crystal display device may be similarly provided. Additionally, although a striped pattern color filter is described in an example embodiment, other color filter patterns, e.g., mosaics, etc., may be similarly provided. Further, although a patterned spacer having a circular section is described in an example embodiment, other shapes, e.g., ovals, rectangles, etc. may be similarly provided. Accordingly, it will be understood by those of ordinary skill in the art that various changes in form and details may be made without departing from the spirit and scope of the present invention as set forth in the following claims.

What is claimed is:

1. A liquid crystal display device, comprising:

a black matrix between first and second substrates, the black matrix having openings defined therein;

color filters between the first and second substrates and aligned with the openings defined in the black matrix, the color filters including first filters having a first color, second filters having a second color, and third filters having a third color; and

spacers configured to maintain a predetermined cell gap, wherein:

the second filters have a recess, such that the second filters have an area that is less than an area of the first filters,

the spacers are aligned with regions of the black matrix adjacent to the recesses in the second filters, and alignment layers are on the first and second substrates.

2. The liquid crystal display device as claimed in claim 1, wherein:

the first substrate includes first electrodes extending in a first direction,

the second substrate includes second electrodes extending in a second direction and crossing the first electrodes, and

the openings in the black matrix correspond to overlapping regions of the first and second electrodes.

3. The liquid crystal display device as claimed in claim 2, wherein the first filters have a shape corresponding to the overlapping regions of the first and second electrodes.

4. The liquid crystal display device as claimed in claim 1, wherein:

the color filters are arranged in a stripe pattern,

the second filters are immediately adjacent to each other in a first direction, and

the second filters alternate with the first and third filters in a second direction.

5. The liquid crystal display device as claimed in claim 4, wherein immediately adjacent second filters have recesses facing one another.

6. The liquid crystal display device as claimed in claim 5, wherein:

the black matrix includes first portions extending in the first direction,

the black matrix includes second portions extending in the second direction and passing between the immediately adjacent second filters,

the second portions are wider in regions between the facing recesses of the second filters than in regions between facing portions of immediately adjacent first filters, and the spacers are aligned with the wider regions.

7. The liquid crystal display device as claimed in claim 4, wherein:

the first substrate includes first electrodes extending in the first direction,

the second substrate includes second electrodes extending in the second direction and crossing the first electrodes, and

the openings in the black matrix correspond to overlapping regions of the first and second electrodes.

8. The liquid crystal display device as claimed in claim 4, wherein:

the first filters are not recessed, and

the first color is red.

9. The liquid crystal display device as claimed in claim 1, wherein the recesses are defined by angled sides of the second filters.

10. A method of fabricating a liquid crystal display device, the method comprising:

forming a black matrix between first and second substrates, the black matrix having openings defined therein;

forming color filters between the first and second substrates such that the color filters are aligned with the openings defined in the black matrix, the color filters including first filters having a first color, second filters having a second color, and third filters having a third color;

forming spacers configured to maintain a predetermined cell gap, wherein:

the second filters are formed to have a recess, such that the second filters are formed with an area that is less than an area of the first filters, and

the spacers are formed to be aligned with regions of the black matrix adjacent to the recesses in the second filters; and

forming alignment layers on the first and second substrates.

11. The method as claimed in claim 10, wherein:

the first substrate includes first electrodes extending in a first direction,

the second substrate includes second electrodes extending in a second direction and crossing the first electrodes, and

the openings in the black matrix correspond to overlapping regions of the first and second electrodes.

12. The method as claimed in claim 11, wherein the first filters are formed to have a shape corresponding to the overlapping regions of the first and second electrodes.

13. The method as claimed in claim 10, wherein:

the color filters are arranged in a stripe pattern, the second filters are immediately adjacent to each other in a first direction, and

the second filters alternate with the first and third filters in a second direction.

14. The method as claimed in claim 13, wherein immediately adjacent second filters are formed to have recesses facing one another.

15. The method as claimed in claim 14, wherein:

the black matrix includes first portions extending in the first direction,

the black matrix includes second portions extending in the second direction and passing between the immediately adjacent second filters,

the second portions are wider in regions between the facing recesses of the second filters than in regions between facing portions of immediately adjacent first filters, and the spacers are aligned with the wider regions.

16. The method as claimed in claim 13, wherein:

the first substrate includes first electrodes extending in the first direction,

the second substrate includes second electrodes extending in the second direction and crossing the first electrodes, and

the openings in the black matrix correspond to overlapping regions of the first and second electrodes.

17. The method as claimed in claim 13, wherein:

the first filters are not recessed, and

the first color is red.

18. The method as claimed in claim 9, wherein the recesses are defined by angled sides of the second filters.

19. The method as claimed in claim 10, wherein forming the spacers includes:

forming a spacer material layer on the second substrate, and

patterning the spacer material layer to form the spacers aligned with regions of the black matrix adjacent to the recesses in the second filters.

20. The method as claimed in claim 19, wherein forming the alignment layer on the second substrate includes performing a rubbing operation to form an alignment pattern after patterning the spacer material layer.

专利名称(译)	液晶显示装置及其制造方法		
公开(公告)号	US20080186435A1	公开(公告)日	2008-08-07
申请号	US12/068423	申请日	2008-02-06
[标]申请(专利权)人(译)	SON董SOO		
申请(专利权)人(译)	SON董SOO		
当前申请(专利权)人(译)	SON董SOO		
[标]发明人	SON DONG SOO		
发明人	SON, DONG SOO		
IPC分类号	G02F1/1335		
CPC分类号	G02F1/13394 G02F1/133514		
优先权	1020070012869 2007-02-07 KR		
其他公开文献	US7791690		
外部链接	Espacenet USPTO		

摘要(译)

一种液晶显示装置，包括在第一和第二基板之间的黑矩阵，黑矩阵具有限定在其中的开口，在第一和第二基板之间的滤色器，并与在黑矩阵中限定的开口对准，滤色器包括具有第一颜色，第二滤色器具有第二颜色，第三滤色器具有第三颜色;和间隔物配置成保持预定的单元间隙。第二滤光器具有凹槽，使得第二滤光器的面积小于第一滤光器的面积，间隔物与黑色矩阵的与第二滤光器中的凹槽相邻的区域对准，并且对准层在第一和第二基板。

