



US008477271B2

(12) **United States Patent**  
**Enomoto**

(10) **Patent No.:** **US 8,477,271 B2**  
(45) **Date of Patent:** **Jul. 2, 2013**

- (54) **LIQUID CRYSTAL DISPLAY DEVICE**
- (75) Inventor: **Hiromi Enomoto**, Osaka (JP)
- (73) Assignee: **Sharp Kabushiki Kaisha**, Kyoto (JP)
- (\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 142 days.

2005/0134768	A1 *	6/2005	Sugiura et al.	349/113
2007/0146616	A1 *	6/2007	Nouchi et al.	349/155
2008/0137013	A1	6/2008	Kamoshida	
2008/0303976	A1	12/2008	Nishizawa et al.	
2009/0148616	A1	6/2009	Itami et al.	
2009/0161048	A1 *	6/2009	Satake et al.	349/110
2011/0102721	A1 *	5/2011	Enomoto	349/137

- (21) Appl. No.: **13/141,088**
- (22) PCT Filed: **Aug. 5, 2009**
- (86) PCT No.: **PCT/JP2009/003743**

**FOREIGN PATENT DOCUMENTS**

JP	11-295750	A	10/1999
JP	2002-221716	A	8/2002
JP	2007-193077	A	8/2007
JP	2008-145778	A	6/2008
JP	2008-198481	A	8/2008
RU	2 031 424	C1	3/1995

- (2) (4) Date: **Jun. 21, 2011**
- (87) PCT Pub. No.: **WO2010/073427**  
PCT Pub. Date: **Jul. 1, 2010**
- (65) **Prior Publication Data**  
US 2011/0255039 A1 Oct. 20, 2011

**OTHER PUBLICATIONS**

English translation of Official Communication issued in corresponding Russian Patent Application No. 2011131059, mailed on Jul. 18, 2012.

Official Communication issued in International Patent Application No. PCT/JP2009/003743, mailed on Sep. 8, 2009.

Enomoto, "Liquid Crystal Display Device," U.S. Appl. No. 13/001,635, filed Dec. 28, 2010.

- (30) **Foreign Application Priority Data**  
Dec. 26, 2008 (JP) ..... 2008-334594

\* cited by examiner

*Primary Examiner* — Edward Glick

*Assistant Examiner* — Mark Teets

(74) *Attorney, Agent, or Firm* — Keating & Bennett, LLP

- (51) **Int. Cl.**  
**G02F 1/1335** (2006.01)
- (52) **U.S. Cl.**  
USPC ..... 349/113; 349/114
- (58) **Field of Classification Search**  
USPC ..... 349/113, 114, 58  
See application file for complete search history.

**ABSTRACT**

(57) A liquid crystal display device includes a first substrate having a plurality of pixels defined thereon, each of which is provided with a reflection layer, a second substrate disposed opposite the first substrate, and a display surface which displays images by the pixels, where the display surface is curved in one direction, and each of the reflection layers is formed so that a reflectance of light reflected from each of the reflection layers in a direction normal to the display surface is higher in both edge portions in a curvature direction than in a middle portion in the curvature direction on the display surface.

- (56) **References Cited**  
U.S. PATENT DOCUMENTS  
6,341,002 B1 \* 1/2002 Shimizu et al. .... 349/119  
7,986,394 B2 7/2011 Kamoshida  
2002/0140886 A1 10/2002 Sugiura et al.  
2004/0144754 A1 7/2004 Itami et al.

**5 Claims, 13 Drawing Sheets**




FIG.1




FIG.2




FIG.3






FIG.5




FIG.6




FIG.7




FIG. 8






FIG.10




FIG.11




FIG.12





FIG.13



**LIQUID CRYSTAL DISPLAY DEVICE**

## TECHNICAL FIELD

The present invention relates to liquid crystal display (hereinafter referred to as "LCD") devices.

## BACKGROUND ART

A transmissive LCD device is configured such that light of a backlight unit is transmitted through an LCD panel having a pair of substrates bonded together, and images are generated by the transmitted light. In addition to the transmissive LCD devices, reflective and transreflective LCD devices are conventionally known. A reflective LCD device is configured such that light of a front light unit, or external light, incident upon an LCD panel is reflected from a substrate opposite the one in the incident side, and images are generated by the reflected light. A transreflective LCD device is configured such that images are generated by using both the transmitted light and the reflected light.

The reflective and the transreflective LCD devices are each provided with a reflection layer to reflect light in each pixel of the LCD panel. The surface of each reflection layer is formed with a homogeneous raised and recessed profile in each pixel in order to scatter the light incident from the surroundings, and to uniformly reflect the light toward the front of the LCD device, and the raised and recessed profile of each reflection layer is formed so that the reflectance of light in the direction normal to the display surface is relatively high to allow bright display (see, e.g., Patent Document 1).

## CITATION LIST

Patent Document

PATENT DOCUMENT 1: Japanese Patent Publication No. 2002-221716

## SUMMARY OF THE INVENTION

## Technical Problem

However, if a flat LCD panel is transformed only to a curved shape in order to produce a curved reflective or transreflective LCD device, the direction of light reflected uniformly from each reflection layer varies along the curved shape of the LCD panel, and thus the reflectance of light in the direction toward the front of the LCD device is likely to decrease along the directions from the middle portion to the both edge portions in the curvature direction on the display surface. Accordingly, a curved LCD device has a problem in that brightness may vary along the curvature direction of the display surface.

The present invention was made in view of the above problem, and it is an object of the present invention to reduce variation in brightness and to improve display quality in curved LCD devices.

## Solution to the Problem

In order to achieve the above object, in the present invention, the reflection layer provided in each pixel is formed so that the reflectance of light reflected from each reflection layer in the direction normal to the display surface is higher in both edge portions in the curvature direction than in a middle portion in the curvature direction on the display surface.

Specifically, a liquid crystal display device according to the present invention includes a first substrate having a plurality of pixels defined thereon, each of which is provided with a reflection layer, a second substrate disposed opposite the first substrate, and a display surface configured to display images by the pixels, where the display surface is curved in one direction; and each of the reflection layers is formed so that a reflectance of light reflected from each of the reflection layers in a direction normal to the display surface is higher in both edge portions in a curvature direction than in a middle portion in the curvature direction on the display surface.

As used herein, the term "curvature direction" means the direction along the curvature of the display surface.

With this configuration, each of the reflection layers is formed so that the reflectance of light reflected from each of the reflection layers in the direction normal to the display surface is higher in both edge portions in the curvature direction than in a middle portion in the curvature direction on the display surface. Accordingly, the reflectance of light reflected from each of the reflection layers toward the front of the LCD device is higher in the both edge portions in the curvature direction relative to that in a middle portion in the curvature direction on the display surface, and thus variation in brightness is reduced, and display quality is improved in the curved LCD device.

A surface of each of the reflection layers may be formed with a raised and recessed profile, and the raised and recessed profile of each of the reflection layers may be formed so that the reflectance of each of the reflection layers is higher in the both edge portions in the curvature direction than in the middle portion in the curvature direction on the display surface.

With this configuration also, the raised and recessed profile of each of the reflection layers causes the reflectance at each of the reflection layers in a direction normal to the display surface to be higher in the both edge portions in the curvature direction than in the middle portion in the curvature direction on the display surface. Thus, the features and advantages of the present invention are specifically achieved.

A display area formed by the plurality of pixels may include a first region, provided in the middle portion in the curvature direction on the display surface, where a reflectance of each of the reflection layers is a first reflectance, second regions, respectively provided on both sides of the first region, where a reflectance of each of the reflection layers is a second reflectance which is higher than the first reflectance, and third regions, respectively provided on opposite sides of the respective second regions from the first region, where a reflectance of each of the reflection layers is a third reflectance which is higher than the second reflectance.

With this configuration, the reflectance of light in each of the reflection layers in a direction normal to the display surface increases in a stepwise fashion along the directions from the middle portion in the curvature direction to the both edge portions in the curvature direction on the display surface. Thus, variation in brightness is effectively reduced in the curved LCD device.

Each of the pixels may include a reflection region in which the reflection layer is provided and a transmission region in which the reflection layer is not provided.

With this configuration, the features and advantages of the present invention are specifically achieved in a transreflective LCD device in which each of the pixels includes a reflection region and a transmission region.

The raised and recessed profile of each of the reflection layers may be formed so that the reflectance toward a periph-

eral side of the display surface is lower than the reflectance toward a front side of the display surface.

With this configuration, the raised and recessed profile of each of the reflection layers causes the reflectance toward a peripheral side of the display surface to be lower than the reflectance toward a front side of the display surface. Thus, image displays are hardly visible from a peripheral side of the display surface. Accordingly, intentional reduction in the visibility in peripheral sides of the display surface so that image displays are only visible to a user in front can prevent the image displays from being viewed by others.

#### Advantages of the Invention

According to the present invention, the reflection layer provided in each of the pixels is formed so that the reflectance of light reflected from each of the reflection layers in the direction normal to the display surface is higher in the both edge portions in the curvature direction than in the middle portion in the curvature direction on the display surface. Thus, variation in brightness is reduced, and display quality is improved in curved LCD devices.

#### BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view schematically illustrating an LCD device according to the first embodiment.

FIG. 2 is a cross-sectional view schematically illustrating the LCD device, taken along line II-II of FIG. 1.

FIG. 3 is a plan view schematically illustrating a display area of the LCD panel.

FIG. 4 is a plan view schematically illustrating a part of the thin film transistor (hereinafter referred to as "TFT") substrate of the first embodiment.

FIG. 5 is a cross-sectional view of a part corresponding to locations along line X-X of FIG. 4 in a first region of the first embodiment.

FIG. 6 is a cross-sectional view of a part corresponding to locations along line X-X of FIG. 4 in a second region of the first embodiment.

FIG. 7 is a cross-sectional view of a part corresponding to locations along line X-X of FIG. 4 in a third region of the first embodiment.

FIG. 8 is a plan view schematically illustrating a part of the TFT substrate of the second embodiment.

FIG. 9 is a cross-sectional view of a part corresponding to locations along line Y-Y of FIG. 8 in a first region of the second embodiment.

FIG. 10 is a cross-sectional view of a part corresponding to locations along line Y-Y of FIG. 8 in a second region of the second embodiment.

FIG. 11 is a cross-sectional view of a part corresponding to locations along line Y-Y of FIG. 8 in a third region of the second embodiment.

FIG. 12 is a perspective view schematically illustrating an LCD device according to the third embodiment.

FIG. 13 is a plan view schematically illustrating a part of the TFT substrate of the fourth embodiment.

#### DESCRIPTION OF EMBODIMENTS

Example embodiments of the present invention will be described below in detail with reference to the drawings. Note that the present invention is not limited to the embodiments described hereinafter.

##### First Embodiment

FIGS. 1 to 7 illustrate the first embodiment of the present invention. FIG. 1 is a perspective view schematically illus-

trating an LCD device S according to this embodiment. FIG. 2 is a cross-sectional view schematically illustrating the LCD device S, taken along line II-II of FIG. 1. FIG. 3 is a plan view schematically illustrating a display area 2 of an LCD panel 1. FIG. 4 is a plan view schematically illustrating a part of a TFT substrate 10. FIGS. 5 to 7 are cross-sectional views of parts corresponding to locations along line X-X of FIG. 4 in respective regions A, B, and C of the display area 2. Note that polarizing plates 43 and 44 are not shown in FIG. 1.

As shown in FIGS. 1 and 2, the LCD device S includes the LCD panel 1 and a backlight unit 5 disposed on the back side (lower side in FIG. 2) of the LCD panel 1.

The LCD panel 1 includes the TFT substrate 10, which is a first substrate, disposed on the backlight unit 5 side, and a color filter substrate 30, which is a second substrate, both of which are bonded together so as to face each other across a liquid crystal layer 40. In the LCD panel 1, the display area 2 is defined in an area where the TFT substrate 10 and the color filter substrate 30 face each other across the liquid crystal layer 40. The LCD panel 1 has a display surface 2s for displaying images on a surface on the color filter substrate 30 side in the display area 2.

Each of the substrates 10 and 30 included in the LCD panel 1 has flexibility, and the LCD panel 1 is fixed under transformation into a curved shape as a whole. Specifically, as shown in FIGS. 1 and 2, the LCD panel 1 is curved in one direction (downward direction in the figures) throughout the long side direction (lateral direction in the figures) so that the display surface 2s forms a concave curved surface. The display surface 2s has a curvature of, for example, approximately  $1/500$  to  $1/50$  (1/mm). The arrows in FIG. 1 indicate the curvature direction of the LCD panel 1 (the display surface 2s). Here, the term "curvature direction" means the direction along the curvature of the LCD panel 1.

Although this embodiment assumes that the LCD panel 1 is curved in the long side direction, the LCD panel 1 may be curved in a short side direction (longitudinal direction in FIG. 1). In addition, the LCD panel 1 is not limited to the one described above, but a rectangular display surface 2s may be configured to curve in an oblique direction.

The TFT substrate 10 and the color filter substrate 30 are formed in, for example, a rectangular shape etc., and as shown in FIG. 2, alignment films 41 and 42 are respectively provided on surfaces on the liquid crystal layer 40 side, and polarizing plates 43 and 44 are respectively provided on surfaces opposite the liquid crystal layer 40. A sealing member 45, having a frame structure, made of epoxy resin etc. is provided between the TFT substrate 10 and the color filter substrate 30 so as to surround the display area 2, and sealing in liquid crystal material within the space surrounded by the sealing member 45 forms the liquid crystal layer 40.

As shown in FIG. 4, the TFT substrate 10 includes a plurality of pixels 11 defined in a matrix, which form the display area 2. The LCD device S of this embodiment is a transreflective LCD device, and thus each of the pixels 11 includes a reflection region 11r which reflects external light incident from the color filter substrate 30 side, and a transmission region 11t which transmits light from the backlight unit 5. For example, the reflection region 11r is disposed in an upper portion column-wise (longitudinal direction in FIG. 4) in each of the pixels 11, and the transmission region 11t is disposed in an underside of the reflection region 11r column-wise in each of the pixels 11.

The TFT substrate 10 has a thin glass substrate 12 shown in FIG. 5. On the glass substrate 12, as shown in FIG. 4, a plurality of gate bus lines 13 are provided so as to extend row-wise (in the lateral direction in the figure) with respect to

the pixels 11 in parallel with each other, a plurality of source bus lines 14 are provided so as to extend, in parallel with each other, in a perpendicular direction to each of the gate bus lines 13, and storage capacitor bus lines 15 are provided in lower portions column-wise (in the longitudinal direction in the figure) of the respective pixels 11 so as to extend between respective pairs of the gate bus lines 13. The gate bus lines 13 and the source bus lines 14 define the pixels 11, and TFTs 16, connected to both the gate bus lines 13 and the source bus lines 14 which form intersections, are respectively provided near the intersections of the gate bus lines 13 and source bus lines 14.

As shown in FIG. 5, each of the TFTs 16 includes a gate electrode 16g, provided on the glass substrate 12, and including a part of a gate bus line 13, a semiconductor layer 16h, provided so as to overlap the gate electrode 16g across a gate insulating film 17 provided over nearly the entire surface of the glass substrate 12 so as to cover the gate electrode 16g, a source electrode 16s, connected to an end portion of the semiconductor layer 16h and connected to a source bus line 14, and a drain electrode 16d, connected to the other end portion of the semiconductor layer 16h. As shown in FIG. 4, a terminal layer 18 is provided in an upper portion column-wise of each of the pixels 11, and a storage capacitor electrode 19 is provided in a lower portion column-wise of each of the pixels 11 so as to overlap a storage capacitor bus line 15, both in a monolithic fashion with the drain electrode 16d of the TFT 16 in each of the pixels 11, over the gate insulating film 17.

In addition, as shown in FIG. 5, an insulating film 20 is provided in the TFT substrate 10 so as to cover the source bus lines 14, the TFTs 16, the terminal layers 18, and the storage capacitor electrodes 19. A pixel electrode 21 is provided for each of the pixels 11 on the insulating film 20.

As shown in FIG. 4, contact holes 20h are provided in the insulating film 20 respectively over a terminal layer 18 and a storage capacitor electrode 19. As shown in FIGS. 5 to 7, the surface of the reflection region 11r of each of the pixels 11 of the insulating film 20 is formed with a raised and recessed profile, and this raised and recessed profile is, for example, a crease-like profile in which recessed portions and raised portions extend in a random manner.

As shown in FIG. 4, each of the pixel electrodes 21 includes a reflective electrode 21r, which is provided in the reflection region 11r, and which is a reflection layer formed of metal material having a high reflectance such as Al or Ag, and a transparent electrode 21t, which is provided in the transmission region lit, and formed of metal material having a high transmittance such as indium tin oxide (ITO). In each of the pixels 11, the reflective electrode 21r and the transparent electrode 21t are spaced apart from each other. The reflective electrode 21r is connected to the terminal layer 18 through a contact hole 20h, and the transparent electrode 21t is connected to the storage capacitor electrode 19 through a contact hole 20h.

As shown in FIG. 4, the surface of each of the reflective electrodes 21r is formed with a crease-like, raised and recessed profile where recessed portions 22 and raised portions 23 extend in a random manner, reflecting the raised and recessed profile of the insulating film 20. Thus, the surface of each of the reflective electrode 21r scatters light incident from the surroundings, and reflects the light toward the front of the LCD device S. In addition, the raised and recessed profile of each of the reflective electrodes 21r is formed so that the reflectance of light reflected from each of the reflective electrodes 21r in the direction normal to the display surface 2s is

higher in both edge portions in the curvature direction than in a middle portion in the curvature direction on the display surface 2s.

As shown in FIG. 3, the display area 2 has a plurality of elongated regions (first through third regions A to C) whose reflectances of light in the direction normal to the display surface 2s in each of the reflective electrodes 21r differ from each other along the directions from a middle portion in the curvature direction (longitudinal direction in the figure) to both edge portions in the curvature direction on the display surface 2s, and the elongated regions are arranged in parallel. Specifically, the display area 2 includes a first region A, which is provided in a middle portion in the curvature direction of the display surface 2s, and in which a reflectance of light in the direction normal to the display surface 2s in each of the reflective electrodes 21r is greater than 0% and less than 5%, second regions B, which are respectively provided on both sides of the first region A, and in which a reflectance of light in the direction normal to the display surface 2s in each of the reflective electrodes 21r is equal to or greater than 5% and less than 10%, and third regions C, which are respectively provided on opposite sides of the respective second regions B from the first region A, and in which a reflectance of light in the direction normal to the display surface 2s in each of the reflective electrodes 21r is equal to or greater than 10% and less than 15%.

The reflectances of light in the direction normal to the display surface 2s in each of the reflective electrodes 21r in the plurality of elongated regions A to C arranged in parallel increase in a stepwise fashion along the directions from the middle portion to the both edge portions in the curvature direction on the display surface 2s by adjusting, in each of the elongated regions A to C, the distribution range of slope angle  $\alpha$  and the level of average slope angle of the raised and recessed profile in each of the reflective electrodes 21r by the surface conditions of the insulating film 20.

The raised and recessed profile of each of the reflective electrodes 21r in the first through third regions A to C of this embodiment is formed with the distribution range of slope angle  $\alpha$  being adjusted so that the average slope angle increases along the directions from the middle portion in the curvature direction to the both edge portions in the curvature direction on the display surface 2s. Here, as shown in FIGS. 5 to 7, the phrase "slope angle  $\alpha$  of the raised and recessed profile in a reflective electrode 21r" means the slope angle between the bottom of a recessed portion 22 and the top of a raised portion 23 adjacent to each other, that is, an angle contained by the line connecting the bottom of a recessed portion 22 and the top of a raised portion 23 adjacent to each other and a plane parallel to the surface of the glass substrate 12, in the raised portion 23. The term "average slope angle" means the arithmetic average of all the values of slope angle  $\alpha$  between the bottoms of the recessed portions 22 and the tops of the raised portions 23 adjacent to each other in the reflective electrodes 21r.

In this embodiment, the raised and recessed profile in each of the reflective electrodes 21r in the first region A is a relatively gradually raised and recessed profile as shown in FIG. 5. For example, the slope angle  $\alpha$  lies in a range between 1.0 and 4.0°, and the average slope angle is approximately 2.5°. The raised and recessed profile in each of the reflective electrodes 21r in each of the second regions B is more steeply raised and recessed than the raised and recessed profile in each of the reflective electrodes 21r in the first region A as shown in FIG. 6. For example, the slope angle  $\alpha$  lies in a range between 4.0 and 7.0°, and the average slope angle is approximately 5.5°. The raised and recessed profile in each of the

reflective electrodes **21r** in each of the third regions C is even more steeply raised and recessed than the raised and recessed profile in each of the reflective electrodes **21r** in each of the second regions B as shown in FIG. 7. For example, the slope angle  $\alpha$  lies in a range between 7.0 and 10.0°, and the average slope angle is approximately 8.5°.

In addition, as shown in FIGS. 1 and 2, the TFT substrate **10** is longer in the long side direction of the LCD panel **1**, and has a larger area, than the color filter substrate **30**; and has a mounting portion **10a** protruding externally of the color filter substrate **30**. In the mounting portion **10a**, an integrated circuit chip **25** for driving the TFT etc., a flexible printed wiring board **26** for supplying power to the integrated circuit chip **25** and for supplying a signal from an external circuit to the LCD panel **1**, etc. are mounted.

As shown in FIG. 5, the color filter substrate **30** includes a glass substrate **31**. A plurality of color filters **32** are provided over the glass substrate **31** so as to overlap the pixel electrodes **21**. A black matrix **33** is provided so as to define each of the color filters **32**. A transparent layer **34** is provided in the color filter substrate **30** so as to overlap the reflection region **11r** of each of the pixels **11** in order to reduce the thickness of the liquid crystal layer **40** over each of the reflection regions **11r** to a thickness less than the thickness of the liquid crystal layer **40** over each of the transmission regions **11t**. Thus, the thickness of the liquid crystal layer **40** over each of the reflection regions **11r** is reduced to approximately half of the thickness of the liquid crystal layer **40** over each of the transmission regions lit so that the optical path lengths of light passing through the liquid crystal layer **40** over a reflection region **11r** and over a transmission region lit are almost the same, thereby improving display quality. In addition, in the color filter substrate **30**, a common electrode **35** is provided so as to cover the transparent layers **34** and the color filters **32**.

Although not shown, the backlight unit **5** includes a light source such as a fluorescent lamp (cold cathode fluorescent tube) or a light emitting diode (LED), a light guide plate, and a plurality of optical sheets such as prism sheets. The light guide plate and the optical sheets are made of resin, and have flexibility. As shown in FIGS. 1 and 2, the backlight unit **5** is fixed under transformation into a curved shape as a whole along the LCD panel **1**, and is configured so as to emit light incident from the light source onto the light guide plate, from an emitting surface of the light guide plate through the optical sheets to the LCD panel **1** side, as uniform plane light.

Thus, the transreflective LCD device S applies a voltage across each of the pixel electrodes **21** and the common electrode **35**, and controls the orientation of liquid crystal molecules on each of the pixels **11** while, in each of the pixels **11**, the reflection region **11r** reflects external light and the transmission region **11t** transmits light from the backlight unit **5**, so as to display images as desired on the display surface **2s** (display area 2).

#### Manufacturing Method

Next, a manufacturing method of the LCD device S described above will be described.

First, the two glass substrates **12** and **31** are prepared. Next, the bus lines **13**, **14**, and **15**, the TFTs **16**, the terminal layers **18**, and the storage capacitor electrodes **19** are formed on the glass substrate **12**. Then, positive photosensitive resin is applied and a film thereof is formed on the glass substrate **12** using a spin coater etc., and prebaking at a temperature about 110° C. for two minutes, an exposure treatment using a mask, and development are sequentially conducted on the photosensitive resin film to form the contact holes **20h**.

Next, the photosensitive resin film in which the contact holes **20h** are formed is postbaked at a temperature about 135° C. for about eight minutes, and thereafter, ultraviolet light is sequentially radiated using a mask onto regions, of the photosensitive resin film, which will be the reflection regions **11r** of the elongated regions A to C with irradiation energies suitable for the raised and recessed profiles of the insulating film **20** formed in the respective regions. That is, on the photosensitive resin film, ultraviolet light is respectively radiated onto a region which will be the first region A with a relatively low irradiation energy, onto regions which will be the second regions B with a higher irradiation energy than the irradiation energy for the region which will be the first region A, and onto regions which will be the third regions C with an even higher irradiation energy than the irradiation energy for the regions which will be the second regions B. Then, final baking on the photosensitive resin film at a temperature about 210° C. for about 60 minutes yields, on a surface of the photosensitive resin film, a crease-like, raised and recessed profile having different distribution ranges of slope angle  $\alpha$  and different levels of average slope angle between the regions which will be the elongated regions A to C. Thus, the insulating film **20** having a surface with a predetermined raised and recessed profile in each of the regions which will be the elongated regions A to C is formed.

Thereafter, the reflective electrodes **21r** are respectively formed in regions, of the insulating film **20**, which will be the respective reflection regions **11r**. In doing so, the surface of each of the reflective electrodes **21r** is formed with a raised and recessed profile, reflecting the raised and recessed profile of the insulating film **20**. In addition, respectively forming the transparent electrodes **21t** in regions of the insulating film **20** which will be the respective transmission regions **11t** produces the TFT substrate **10**. Then, the alignment film **41** is formed over the TFT substrate **10** by a printing method etc.

Moreover, forming the black matrix **33**, the color filters **32**, the transparent layers **34**, and the common electrode **35** on and over the other glass substrate **31** produces the color filter substrate **30**. Then, the alignment film **42** is formed on the surface of the color filter substrate **30** by a printing method. Next, the sealing member **45** is formed in a frame structure on the TFT substrate **10** by drawing using a dispenser etc. or by a printing method. Thereafter, a predetermined amount of liquid crystal material is dropped into a region, on the TFT substrate **10**, surrounded by the sealing member **45**. Subsequently, in the processing chamber under vacuum, the TFT substrate **10** and the color filter substrate **30** are aligned so that the respective pixel electrodes **21** and the respective color filters **32** overlap, and the both substrates **10** and **30** are bonded together with the sealing member **45** therebetween. Then, the sealing member **45** is cured to make the both substrates **10** and **30** adhere with respect to each other. Thus, the LCD panel **1** is produced.

Although, in this embodiment, the manufacturing process of the LCD panel **1** has been described using an example of so-called "one drop filling" in which the material of the sealing member **45** is supplied onto the TFT substrate **10** in a frame structure, and liquid crystal material is dropped into the space surrounded by the sealing member **45**, and then the TFT substrate **10** and the color filter substrate **30** are bonded together, the LCD panel may be manufactured by so-called "vacuum injection method" in which the material of the sealing member is applied to the TFT substrate **10** to form the sealing member almost in a frame structure having incision, the TFT substrate **10** and the color filter substrate **30** are bonded together with the sealing member therebetween, and then, the liquid crystal material is injected under vacuum

through an injection hole configured by the incision in the sealing member, before sealing the injection hole.

Thereafter, the polarizing plates **43** and **44** are bonded to the respective surfaces of the LCD panel **1**, and the integrated circuit chip **25** and the flexible printed wiring board **26** are each mounted on the mounting portion **10a** of the TFT substrate **10**. Then, the previously prepared backlight unit **5** is attached on the backside of the LCD panel **1**, and the LCD panel **1** and the backlight unit **5** are transformed and fixed so that the display surface **2s** forms a concave curved surface. Thus, the LCD device **S** shown in FIG. **1** is completed.

#### Advantages of First Embodiment

Thus, according to the first embodiment, the raised and recessed profile in each of the reflective electrodes **21r** is formed such that the reflectance of light reflected from each of the reflective electrodes **21r** in the direction normal to the display surface **2s** is higher in the both edge portions in the curvature direction than in the middle portion in the curvature direction on the display surface **2s**. Accordingly, the reflectance of light reflected from each of the reflective electrodes **21r** toward the front of the LCD device **S** can be higher in both the edge portions in the curvature direction than in the middle portion in the curvature direction on the display surface **2s**, and thus, variation in brightness is reduced, and display quality is improved in the curved LCD device **S**.

Moreover, since the display area **2** includes the first through third regions **A** to **C**, the reflectance of light in the direction normal to the display surface **2s** in each of the reflective electrodes **21r** increases in a stepwise fashion along the directions from the middle portion to the both edge portions in the curvature direction on the display surface **2s**. Thus, variation in brightness can be effectively reduced in the curved LCD device **S**.

#### Second Embodiment

FIGS. **8** to **11** illustrate the second embodiment of the present invention. In the embodiments hereafter, the same reference numerals are used to represent equivalent elements to those shown in FIGS. **1** to **7**, and the detailed explanation thereof will be omitted. FIG. **8** is a plan view schematically illustrating a part of the TFT substrate **10** of this embodiment. FIGS. **9** to **11** are cross-sectional views of parts corresponding to locations along line **Y-Y** of FIG. **8** in the respective regions **A**, **B**, and **C** of the display area **2**.

While the first embodiment described above has been presented in terms of the transmissive LCD device **S**, this embodiment is presented in terms of a reflective LCD device **S**.

As shown in FIG. **8**, the LCD device **S** according to this embodiment includes pixel electrodes **21** each having a reflective electrode **21r**. Each of the reflective electrodes **21r** is connected through a contact hole **20h** to the storage capacitor electrode **19**, which is formed in a monolithic fashion with the drain electrode **16d** of the TFT **16** with respect to each of the pixels **11**. As with the first embodiment described above, the LCD panel **1** of this embodiment also has the display surface **2s** which is curved to form a concave curved surface, and the display surface **2s** has a plurality of elongated regions **A** to **C** whose reflectances of light in the direction normal to the display surface **2s** in each of the reflective electrodes **21r** differ from each other. As shown in FIG. **8**, the surface of each of the reflective electrodes **21r** is formed with a crease-like, raised and recessed profile where recessed portions **22** and raised portions **23** extend in a random manner; and adjust-

ment, in each of the elongated regions **A** to **C**, of the distribution range of slope angle  $\alpha$  and the level of average slope angle of the raised and recessed profile in each of the reflective electrodes **21r** causes the reflectance of light in the direction normal to the display surface **2s** in each of the reflective electrodes **21r** to increase in a stepwise fashion along the directions from the middle portion to the both edge portions in the curvature direction on the display surface **2s**.

As with the first embodiment described above, the raised and recessed profile of each of the reflective electrodes **21r** in the first through third regions **A** to **C** of this embodiment is also formed with the distribution range of slope angle  $\alpha$  being adjusted so that the average slope angle increases along the directions from the middle portion in the curvature direction to the both edge portions in the curvature direction on the display surface **2s**. The raised and recessed profile in each of the reflective electrodes **21r** in the first region **A** is a relatively gradually raised and recessed profile as shown in FIG. **9**. For example, the slope angle  $\alpha$  lies in a range between  $1.0^\circ$  and  $4.0^\circ$ , and the average slope angle is approximately  $2.5^\circ$ . The raised and recessed profile in each of the reflective electrodes **21r** in each of the second regions **B** is more steeply raised and recessed than the raised and recessed profile in each of the reflective electrodes **21r** in the first region **A** as shown in FIG. **10**. For example, the slope angle  $\alpha$  lies in a range between  $4.0^\circ$  and  $7.0^\circ$ , and the average slope angle is approximately  $5.5^\circ$ . The raised and recessed profile in each of the reflective electrodes **21r** in each of the third regions **C** is even more steeply raised and recessed than the raised and recessed profile in each of the reflective electrodes **21r** in each of the second regions **B** as shown in FIG. **11**. For example, the slope angle  $\alpha$  lies in a range between  $7.0^\circ$  and  $10.0^\circ$ , and the average slope angle is approximately  $8.5^\circ$ .

The configuration of the other part of the LCD device **S** of this embodiment is similar to that of the first embodiment described above, and a front light unit is attached as necessary on the front face side (upper side in FIG. **1**) of the LCD panel **1**.

#### Advantages of Second Embodiment

Thus, also according to the second embodiment, since the display area **2** includes the first through third regions **A** to **C**, the reflectance of light in the direction normal to the display surface **2s** in each of the reflective electrodes **21r** increases in a stepwise fashion along the directions from the middle portion to the both edge portions in the curvature direction on the display surface **2s**. Thus, similar advantages to those of the first embodiment described above can be obtained.

#### Third Embodiment

FIG. **12** illustrates the third embodiment of the present invention. FIG. **12** is a perspective view schematically illustrating an LCD device **S** according to this embodiment.

While the first and second embodiments described above have assumed that the LCD panel **1** has the display surface **2s** which is curved to form a concave curved surface, the LCD panel **1** of this embodiment is configured such that the display surface **2s** is curved in the long side direction so as to form a convex curved surface as shown in FIG. **12**. The arrows in FIG. **12** indicate the curvature direction of the LCD panel **1** (the display surface **2s**). The backlight unit **5** is also configured to curve along the LCD panel **1**.

Although this embodiment assumes that the LCD panel **1** is curved in the long side direction, the LCD panel **1** may be

curved in a short side direction, and moreover, the rectangular display surface **2s** may be configured to curve in an oblique direction.

Also in the LCD device **S** of this embodiment, as with the first embodiment described above, the surface of each of the reflective electrodes **21r** is formed with a crease-like, raised and recessed profile; and adjustment, in each of the elongated regions (first through third regions) **A** to **C**, of the distribution range of slope angle  $\alpha$  and the level of average slope angle of the raised and recessed profile in each of the reflective electrodes **21r** causes the reflectance of light in the direction normal to the display surface **2s** in each of the reflective electrodes **21r** to increase in a stepwise fashion along the directions from the middle portion to the both edge portions in the curvature direction on the display surface **2s**.

#### Advantages of Third Embodiment

Thus, also according to the third embodiment, since the display area **2** includes the first through third regions **A** to **C**, the reflectance of light in the direction normal to the display surface **2s** in each of the reflective electrodes **21r** increases in a stepwise fashion along the directions from the middle portion to the both edge portions in the curvature direction on the display surface **2s**. Thus, similar advantages to those of the first embodiment described above can be obtained.

#### Fourth Embodiment

FIG. **13** illustrates the fourth embodiment of the present invention. FIG. **13** is a plan view schematically illustrating a part of the TFT substrate **10** according to this embodiment.

While the second embodiment described above has assumed that the surface of each of the reflective electrodes **21r** is formed with a crease-like, raised and recessed profile where recessed portions **22** and raised portions **23** extend in a random manner, the crease-like, raised and recessed profile of each of the reflective electrodes **21r** of this embodiment is formed in a ladder structure as shown in FIG. **13**, in which recessed portions **22** and raised portions **23** are provided so as to extend row-wise (in the lateral direction in the figure) in each of the pixels **11** in parallel with each other inside a raised portion **23** having a frame structure, and to lie alternately in stripes column-wise (in the longitudinal direction in the figure) with respect to the pixels **11**. Accordingly, the raised and recessed profile of each of the reflective electrodes **21r** of this embodiment is formed so that a smaller area of sloped surface faces row-wise in each of the pixels **11**, and that the reflectance of light toward the both side portions on the display surface **2s** is lower than the reflectance of light toward the front portion on the display surface **2s**. The configuration of the other part of the LCD device **S** of this embodiment is similar to that of the second embodiment described above.

The raised and recessed profiles of the reflective electrodes **21r** as described above are formed, in a manufacturing method of the TFT substrate **10**, such that when the source bus lines **14** and the drain electrodes **16d** are formed, a plurality of patterns extending row-wise and lying in stripes column-wise are formed in each region which will be a pixel **11**. Then, by forming the insulating film **20** in a similar way to that of the first embodiment described above, final baking yields recessed portions **22** and raised portions **23** extending along the respective patterns, and thus the raised and recessed profile in a ladder structure is formed on the insulating film **20**. Thereafter, formation of the reflective electrodes **21r** causes the surface of each of the reflective electrodes **21r** to be

formed with the raised and recessed profile in a ladder structure, reflecting the raised and recessed profile of the insulating film **20**.

#### Advantages of Fourth Embodiment

Thus, according to the fourth embodiment, variation in brightness can be effectively reduced, and display quality can be improved in the curved LCD device **S** as with the second embodiment. Moreover, the raised and recessed profile of each of the reflective electrodes **21r** allows the reflectance of light at each of the reflective electrodes **21r** to be lower in the both side portions on the display surface **2s** than in the front portion on the display surface **2s**, and thus image displays can be hardly visible from the both side portions of the display surface **2s**. Accordingly, intentional reduction in the visibility in the both side portions of the display surface **2s** so that image displays are only visible to a user in front can prevent the image displays from being viewed by others.

#### Other Embodiments

Although the first embodiment described above has been presented in terms of a method for forming the raised and recessed profile on the surface of the insulating film **20** in which ultraviolet light is radiated onto the photosensitive resin film forming the insulating film **20**, and then final baking is conducted, the present invention is not limited thereto, the raised and recessed profile may be formed on the surface of the insulating film in such a way that ultraviolet light is radiated onto the photosensitive resin film forming the insulating film, and then the photosensitive resin film is developed, or the raised and recessed profile may be formed on the surface of the insulating film **20** by another known method in which, for example, a pattern is formed on a layer under the insulating film to form the surface of the insulating film with a raised and recessed profile.

In addition, although each of the described embodiments assumes that the raised and recessed profile of each surface of the reflective electrodes **21r** is formed with a crease-like profile where the recessed portions and the raised portions extend in a random manner, or is formed in a ladder structure, the present invention is not limited thereto, the raised and recessed profile of the insulating film **20** may be a raised and recessed profile in which a plurality of dot-shaped raised portions are provided at random, or otherwise, various raised and recessed profiles may be used.

Although the fourth embodiment described above has been presented in terms of the reflective LCD device **S** in which each of the reflective electrodes **21r** is configured such that the reflectance of light at each of the reflective electrodes **21r** is lower in the both side portions on the display surface **2s** than in the front portion on the display surface **2s**, the present invention is not limited thereto, the transmissive LCD device **S** may be configured such that the surface of each of the reflective electrodes **21r** is formed with a raised and recessed profile in a ladder structure as with the fourth embodiment described above, and thus the reflectance of light at each of the reflective electrodes **21r** is lower in the both side portions on the display surface **2s** than in the front portion on the display surface **2s**. With such a configuration, in the curved transmissive LCD device **S**, the raised and recessed profile of each of the reflective electrodes **21r** allows the reflectance of light at each of the reflective electrodes **21r** to be lower in the both side portions on the display surface **2s** than in the front portion on the display surface **2s**, and thus image displays can

be hardly visible from the both side portions of the display surface 2s, and can be prevented from being viewed by others.

INDUSTRIAL APPLICABILITY

As described above, the present invention is useful for LCD devices, and more particularly for curved LCD devices in which reduction in variation in brightness and improvement in display quality are demanded.

DESCRIPTION OF REFERENCE CHARACTERS

- A First Region
- B Second Region
- C Third Region
- S Liquid Crystal Display (LCD) Device
- 2 Display Area
- 2s Display Surface
- 10 Thin Film Transistor (TFT) Substrate (First Substrate)
- 11 Pixel
- 11r Reflection Region
- 11t Transmission Region
- 21r Reflective Electrode (Reflection Layer)
- 30 Color Filter Substrate (Second Substrate)

The invention claimed is:

1. A liquid crystal display device, comprising:  
 a first substrate including a plurality of pixels defined thereon, each of which is provided with a reflection layer;  
 a second substrate disposed opposite the first substrate; and  
 a display surface configured to display images by the plurality of pixels,  
 wherein  
 the display surface is curved in a curvature direction, and  
 a reflectance of light in a direction normal to the display surface in all of the reflection layers located in outer edge portions of the display surface in the curvature direction is higher than a reflectance of light in the direction normal to the display surface in all of the reflection layers located in a middle portion of the display surface in the curvature direction.

2. The liquid crystal display device of claim 1, wherein a surface of each of the reflection layers is provided with a raised and recessed profile, and

the raised and recessed profile of each of the reflection layers is arranged so that the reflectance of light in the direction normal to the display surface in all of the reflection layers located in the outer edge portions of the display surface in the curvature direction is higher than the reflectance of light in the direction normal to the display surface in all of the reflection layers located in the middle portion of the display surface in the curvature direction.

3. The liquid crystal display device of claim 1, wherein a display area defined by the plurality of pixels includes a first region, provided in the middle portion of the display surface in the curvature direction, where a reflectance of the reflection layers in the first region is a first reflectance,

second regions, respectively provided on both sides of the first region in the curvature direction, where a reflectance of the reflection layers in the second regions is a second reflectance which is higher than the first reflectance, and

third regions, respectively provided on opposite sides of the respective second regions from the first region in the curvature direction, where a reflectance of the reflection layers in the third regions is a third reflectance which is higher than the second reflectance.

4. The liquid crystal display device of claim 1, wherein each of the plurality of pixels includes a reflection region in which one of the reflection layers is provided and a transmission region in which no reflection layer is provided.

5. The liquid crystal display device of claim 2, wherein the raised and recessed profile of each of the reflection layers is arranged so that the reflectance toward a peripheral side of the display surface is lower than the reflectance toward a front side of the display surface.

\* \* \* \* \*

专利名称(译)	液晶显示装置		
公开(公告)号	<a href="#">US8477271</a>	公开(公告)日	2013-07-02
申请号	US13/141088	申请日	2009-08-05
[标]申请(专利权)人(译)	夏普株式会社		
申请(专利权)人(译)	夏普株式会社		
当前申请(专利权)人(译)	夏普株式会社		
[标]发明人	ENOMOTO HIROMI		
发明人	ENOMOTO, HIROMI		
IPC分类号	G02F1/1335		
CPC分类号	G02F1/133305 G02F1/133504 G02F1/133553 G09F9/35 G09F9/301 G02F1/133555 G02F1/1323 G02F2001/133391 G02F2203/02		
优先权	2008334594 2008-12-26 JP		
其他公开文献	US20110255039A1		
外部链接	<a href="#">Espacenet</a> <a href="#">USPTO</a>		

摘要(译)

一种液晶显示装置，包括：第一基板，具有限定在其上的多个像素，每个像素设置有反射层；第二基板，与第一基板相对设置；以及显示表面，通过像素显示图像，其中显示器表面在一个方向上弯曲，并且每个反射层形成为使得在垂直于显示表面的方向上从每个反射层反射的光的反射率在曲率方向上的两个边缘部分中比在中间的中间更高在显示表面上的曲率方向上的部分。

