



US 20040095533A1


(19) **United States**(12) **Patent Application Publication**
Stallinga et al.(10) **Pub. No.: US 2004/0095533 A1**(43) **Pub. Date: May 20, 2004**(54) **LIQUID CRYSTAL DISPLAY DEVICE****Related U.S. Application Data**(75) Inventors: **Sjoerd Stallinga**, Eindhoven (NL);
Peter Van De Witte, Heerlen (NL)(62) Division of application No. 09/787,249, filed on Mar.
16, 2001, now Pat. No. 6,674,498.(30) **Foreign Application Priority Data**

Jul. 16, 1999 (EP) 99202351.5

Correspondence Address:

Corporate Patent Counsel**Philips Intellectual Property & Standards****P.O. Box 3001****Briarcliff Manor, NY 10510-8001 (US)****Publication Classification**(51) **Int. Cl.⁷** **G02F 1/1335**(52) **U.S. Cl.** **349/117**(73) Assignee: **U.S. PHILIPS CORPORATION**(21) Appl. No.: **10/705,318**(22) Filed: **Nov. 10, 2003**(57) **ABSTRACT**

In a normally black double cell, grey scale enhancement is obtained by dividing pixels in the driving cell into sub-pixels which are rotated preferably through 180° with respect to each other.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

LIQUID CRYSTAL DISPLAY DEVICE

[0001] The invention relates to a liquid crystal display device having, between a polarizer and an analyzer, a first layer of twisted liquid crystal material with a twisted structure between two transparent substrates, with pixels being realized between the substrates, and a compensator layer. Such display devices are generally used in, for example, automotive displays, but also in monitors, etc.

[0002] An example of such a display device is shown in, for example, U.S. Pat. No. 5,287,207. This patent shows a double cell in which a second cell functions as a compensator in order to obtain an optimum contrast. Although a satisfactory contrast is obtained in these types of display devices upon perpendicular passage of the light, it appears that there is a considerable grey scale inversion in such a double cell, when viewed at an angle.

[0003] It is, inter alia, an object of the present invention to reduce or eliminate said grey scale inversion.

[0004] To this end, a display device according to the invention is characterized in that a pixel comprises at least two sub-pixels having the same twist and, viewed transversely to the substrates, twist angles which are rotated with respect to each other. The twist angles, viewed transversely to the substrates, are rotated substantially 180 degrees with respect to each other. The effects on the grey scale of one sub-pixel are then compensated, as it were, by the effects of the other sub-pixel. Also in the case of rotations different from 180 degrees, an enhancement is obtained dependent on the type of usage (for example, in cockpit applications or in applications where a display device is viewed by different persons from two directions).

[0005] The twist angles are preferably in the range between 50 and 100 degrees.

[0006] A first preferred embodiment of a liquid crystal display device according to the invention is characterized in that the compensator layer has a twisted structure with a twist which is opposite to that of the layer of twisted liquid crystal material. The compensator layer preferably has a twist angle which is opposite to that of the layer of twisted liquid crystal material.

[0007] Further enhancements are possible by adding a retardation layer with an optical axis perpendicular to the compensator layer.

[0008] It is also possible to use negative birefringent materials such as discotic materials for the compensator layer.

[0009] These and other aspects of the invention are apparent from and will be elucidated with reference to the embodiments described hereinafter.

[0010] In the drawings:

[0011] FIG. 1 is a cross-section of a display device according to the invention,

[0012] FIG. 2 shows diagrammatically some parts of the display device according to the invention,

[0013] FIG. 3 shows diagrammatically different orientation directions in the display device of FIG. 1,

[0014] FIGS. 4 and 5 show the luminance as a function of the viewing angle for a double cell without using and using, respectively, the measure according to the invention, while

[0015] FIG. 6 shows diagrammatically different orientation directions, and

[0016] FIGS. 7 and 8 show the luminance again as a function of the viewing angle for a double cell in a display device with a compensation cell based on discotic material without using and using, respectively, the measure according to the invention.

[0017] The drawings are diagrammatic and not drawn to scale. Corresponding parts are generally denoted by the same reference numerals.

[0018] The display device of FIG. 1 comprises a first display cell 10 with a layer 11 of a liquid crystal material having a positive dielectric anisotropy between transparent supporting plates 2, 3. On the side of the liquid crystal material, electrodes 12, 13 defining, for example, a matrix of pixels are present on the supporting plates 2, 3. The pixels may be driven directly via row and column electrodes (positive drive). In this example, the pixels are defined by overlapping portions of picture electrodes 12 and a counter electrode 13, in which the picture electrodes are provided with pixel voltages by switching elements (not shown) via row and column electrodes (active drive). The drive voltages (selection and data signals) are obtained, for example, by means of a drive circuit 7 which converts incoming information 8 into said drive voltages which are applied to the electrodes 12, 13 via the switching elements (not shown) (here diagrammatically shown by means of switch 15 in one of the connection lines 16, 16'). Layers 14 of an insulating material, which in this example also serve as orienting layers, are present on the layers 12, 13. The layers 14 give the liquid crystal molecules a twist angle Φ_1 at a voltage of 0 volt across the electrodes 12, 13. The twist angle Φ_1 is between 50° and 100° and, in this example, 90°.

[0019] The device further comprises a compensator layer, in this example, a second cell 20 with a second layer 21 of a liquid crystal material having, in this example, also a positive dielectric anisotropy between two transparent supporting plates 3, 4. The supporting plate 3 is chosen to be common for both cells 10, 20, but this is not strictly necessary, although it simplifies the manufacture in which also the double cell maintains a small total thickness. Layers 24 for insulation and orientation are present on the supporting plates 3, 4. The liquid crystal material 21 and the orienting effect of the layers 24 are chosen to be such that the liquid crystal molecules acquire a twist angle Φ_2 opposed to Φ_1 . The direction of orientation in this example is the same for the layers 14, 24. The cells 10 and 20 are situated between a polarizer 6 and an analyzer 5 whose directions of polarization are mutually crossed perpendicularly.

[0020] According to the invention, parts 14', of one orientation layer within a pixel are provided in such a way (for example, via masked rubbing or vapor deposition) that the direction of orientation is substantially 180° different for the liquid crystal molecules in the two sub-pixels. This is further shown in FIG. 2 in which the polarizer 6, parts 14', of an orientation layer on the supporting plate 2, the orientation layers 14, 24 on the supporting plate 3, the orientation layer 24 on the supporting plate 4 and the analyzer 5 are shown

diagrammatically. The directions of orientation of the parts **14'**, of the orientation layer on the supporting plate **2**, the orientation layers **14**, **24** on the supporting plate **3** and the orientation layer **24** on the supporting plate **4** are denoted by the reference numerals **27'**, **27''**, **27**, **28** and **29**, respectively. The directions **27**, **28** cross each other substantially perpendicularly.

[0021] The absorbing axis **26** of the polarizer **6** extends at an angle of 0° (180°) to the orientation direction **27'** (**27''**) in this example. Also other angles between the axis **26** and the direction **27** are possible. The wall orientation of the layers **14**, **24** is chosen to be such that the director in the center of the cell **10** (at 0 volt) is perpendicular to the director in the center of the cell **20**. Due to the division thus chosen, two twist angles Φ_1 are introduced in sub-pixels of the cell **10**, which angles, viewed transversely to the substrates, are rotated through substantially 180° degrees with respect to each other. This is shown diagrammatically in FIG. 3. The twist angles of the sub-pixels are determined by orientation directions **27'**, **27** and **27''**, **27** for the cell **10**. In one sub-pixel, polarized light (polarized in the direction **26** of polarization of polarizer **6**) is twisted through an angle Φ_1 from direction **27'** to direction **27** at 0 volt, and in the other sub-pixel from direction **27''** to direction **27**. In the second cell **20** (twist angle $-\Phi_1$), the directions of polarization for both sub-pixels are twisted back through the same angle from direction **28** (parallel to direction **27**) to direction **29**, so that it does not pass the analyzer **5** with the pass direction **25** (normally black).

[0022] For the grey scales as a function of the viewing angle of this double cell, it now holds that it is composed, as it were, from those of the two sub-pixels. Since these are symmetrically situated with respect to each other, a symmetrical characteristic is obtained. This is shown in FIGS. 4 and 5. FIG. 4 shows the characteristic curve of the luminance as a function of the viewing angle for a double cell without said measure (with a twist angle of 60° and $d\Delta n=330$ nm) for different drive voltages. Grey scale inversion already starts at a viewing angle of 20° and occurs for all grey values. FIG. 5 shows this characteristic curve for a double cell, using said measure. Grey scale inversion now starts at viewing angles of more than 50° and then only for some grey values.

[0023] In the device shown diagrammatically in FIG. 6, the twist angle Φ_1 of the cell **10** is 90° and $d\Delta n=400$ nm. In this example, the second cell **20** has a second layer **21** of a liquid crystal material with a negative dielectric anisotropy. The orienting effect of the layers **24** is chosen to be such that the liquid crystal molecules acquire a twist angle of $-\Phi_1$. Such a cell **20** is obtained, for example, by choosing a discotic liquid crystalline material for the liquid material. In this example, the layer **21** is liquid but it may also consist of a polymerized liquid crystalline material. The orientation layers **24** are adapted in such a way that the directors of the discotic molecules acquire an orientation direction **28** at the area of substrate **3**, transverse to the orientation direction **27** of the (calamatic) molecules at the area of substrate **3**.

[0024] FIG. 7 shows for this double cell the luminance as a function of the viewing angle for a double cell comprising a compensation cell **20** which is based on a discotic material, without using said measure, and for different drive voltages, and FIG. 5 shows the characteristic curve for such a double cell, using the measure according to the invention.

[0025] The invention is of course not limited to the examples shown. For example, the compensation cell **20** may comprise a foil of polymerized liquid crystal with a twisted (director) structure instead of a liquid crystal material.

[0026] In summary, the invention yields an improvement of the grey scale in "normally black" double cells by dividing a pixel in the cell to be driven into sub-pixels which are rotated preferably through 180° with respect to each other.

[0027] The invention resides in each and every inventive characteristic feature and each and every combination of characteristic features.

1. A liquid crystal display device having, between a polarizer and an analyzer, a first layer of twisted liquid crystal material with a twisted structure between two transparent substrates, with pixels being realized between the substrates, and a compensator layer, characterized in that a pixel comprises at least two sub-pixels having the same twist and, viewed transversely to the substrates, twist angles which are rotated with respect to each other.

2. A liquid crystal display device as claimed in claim 1, characterized in that, the twist angles have a value of between 50° and 100° .

3. A liquid crystal display device as claimed in claim 1, characterized in that viewed transversely to the substrates, the twist angles are rotated through substantially 180° with respect to each other.

4. A liquid crystal display device as claimed in claim 1, characterized in that the compensator layer has a twisted structure with a twist which is opposite to that of the layer of twisted liquid crystal material.

5. A liquid crystal display device as claimed in claim 4, characterized in that the compensator layer has a twist angle which is opposite to that of the layer of twisted liquid crystal material.

6. A liquid crystal display device as claimed in claim 1, characterized in that the compensator layer comprises at least a retardation layer with an optical axis perpendicular to the compensator layer.

7. A liquid crystal display device as claimed in claim 1, characterized in that the compensator layer comprises a negative birefringent material.

8. A liquid crystal device as claimed in claim 1, characterized in that the compensator layer comprises a liquid crystal material with a twisted structure.

* * * * *

专利名称(译)	液晶显示装置		
公开(公告)号	US20040095533A1	公开(公告)日	2004-05-20
申请号	US10/705318	申请日	2003-11-10
申请(专利权)人(译)	美国Philips公司		
当前申请(专利权)人(译)	美国Philips公司		
[标]发明人	STALLINGA SJOERD VAN DE WITTE PETER		
发明人	STALLINGA, SJOERD VAN DE WITTE, PETER		
IPC分类号	G02F1/1347 G02F1/13363 G02F1/1337 G02F1/1335		
CPC分类号	G02F1/133753 G02F2413/15 G02F2001/133757		
优先权	1999202351 1999-07-16 EP 09/787249 2001-03-16 US		
其他公开文献	US6933999		
外部链接	Espacenet USPTO		

摘要(译)

在常黑的双单元中，通过将驱动单元中的像素划分为相对于彼此优选地旋转 180° 的子像素来获得灰度增强。

