



US009097950B2

(12) **United States Patent**
Zhao et al.

(10) **Patent No.:** **US 9,097,950 B2**
(45) **Date of Patent:** **Aug. 4, 2015**

(54) **LIQUID CRYSTAL DISPLAY PANEL AND APPARATUS HAVING THE LIQUID CRYSTAL DISPLAY PANEL**

3/3614 (2013.01); G09G 2300/0426 (2013.01); G09G 2310/0281 (2013.01); G09G 2320/0209 (2013.01); G09G 2320/0247 (2013.01); G09G 2330/021 (2013.01)

(75) Inventors: **Guo Zhao**, Guangdong (CN); **Tao Ding**, Guangdong (CN); **Ming Liu**, Guangdong (CN)

(58) **Field of Classification Search**

None

See application file for complete search history.

(73) Assignee: **SHENZHEN CHINA STAR OPTOELECTRONICS TECHNOLOGY CO., LTD.**, Guangdong (CN)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 378 days.

5,748,165	A	5/1998	Kubota et al.
8,717,523	B2	5/2014	Lee et al.
2009/0262054	A1	10/2009	Hsu et al.
2010/0066967	A1	3/2010	Takahashi et al.
2011/0128261	A1	6/2011	Hung et al.
2012/0127412	A1*	5/2012	Lee et al. 349/139
2013/0141660	A1	6/2013	Wang et al.

(21) Appl. No.: **13/700,407**

(22) PCT Filed: **Sep. 4, 2012**

FOREIGN PATENT DOCUMENTS

(86) PCT No.: **PCT/CN2012/080973**

CN	1115535	1/1996
CN	2881693	3/2007

§ 371 (c)(1),

(2), (4) Date: **Nov. 27, 2012**

(Continued)

(87) PCT Pub. No.: **WO2014/023050**

PCT Pub. Date: **Feb. 13, 2014**

Primary Examiner — Lucy Chien

(74) Attorney, Agent, or Firm — Kirton McConkie; Evan R. Witt

(65) **Prior Publication Data**

US 2014/0036191 A1 Feb. 6, 2014

(30) **Foreign Application Priority Data**

Aug. 6, 2012 (CN) 2012 1 0276385

(51) **Int. Cl.**

G02F 1/1343 (2006.01)

G02F 1/1362 (2006.01)

G09G 3/36 (2006.01)


(52) **U.S. Cl.**

CPC **G02F 1/136286** (2013.01); **G09G 3/3648** (2013.01); **G09G 3/3674** (2013.01); **G09G**

(57) **ABSTRACT**

The present invention provides a liquid crystal display panel. An Nth set of scan lines is disposed between two neighboring row of pixels. Each set of the scan lines comprises an upper scan line and a lower scan line. Gate electrodes of the thin film transistors in the neighboring row of pixels are alternatively coupled to the upper scan line and the lower scan line sequentially. An Nth data line is disposed between a 2N-1th column of pixels and a 2Nth column of pixels. The Nth data line is coupled to source electrodes of the thin film transistors of the neighboring 2N-1th column of pixels and 2Nth column of pixels.

6 Claims, 4 Drawing Sheets



(56)

References Cited

FOREIGN PATENT DOCUMENTS

CN	101582422	11/2009
CN	102081246	6/2011

CN	102081270	6/2011
CN	102290026	12/2011
CN	102385200	3/2012
CN	102478736	5/2012
CN	102629053	8/2012

* cited by examiner




Fig. 1 (Prior art)




Fig. 2




Fig. 3




Fig. 4

LIQUID CRYSTAL DISPLAY PANEL AND APPARATUS HAVING THE LIQUID CRYSTAL DISPLAY PANEL

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a liquid crystal display (LCD) technology, more particularly, to a liquid crystal display panel an apparatus having the liquid crystal panel.

2. Description of the Related Art

Nowadays, LCDs are becoming the main stream of displaying technology, and are being extensively applied to various electronic products, such as a mobile phone, a PDA, a digital camera, a computer screen, a notebook screen and the like.

Please refer to FIG. 1, FIG. 1 is a schematic diagram showing a structure of pixels of a conventional LCD panel. The conventional LCD panel comprises m data lines D"1~D"m and n scan lines G"1~G"n. The scan lines cross the data lines, and a pixel (not indicated) is defined by two neighboring data lines and two neighboring scan lines crossing the two neighboring data lines. A thin film transistor (not indicated) and a liquid crystal capacitor (not indicated) are disposed in each of the pixel.

Generally speaking, the data signals transmitted on the data lines (D"1~D"m) are classified into positive polarity data signals and negative polarity data signals with respect to a reference voltage, which is the common voltage (Vcom). A data signal having a voltage higher than the common voltage Vcom is called a positive polarity data signal, and a data signal having a voltage lower than the common voltage Vcom is called a negative polarity data signal. There is no difference between the display effects of a grey scale value when it is represented by a positive polarity data signal and a negative polarity data signal.

Liquid crystal molecules are characterized in that their rotation character will be destroyed if the direction of an electrical field applied to two ends of them is not changed over a long period of time. That means, the liquid crystal molecules will no longer rotate in response to the change of the electrical field, let apart the different gray scales that are expected to be generated. In order to retain their rotation character, the electrical field applied to them must be reversed so that the liquid crystal molecules will invert at scheduled time intervals. Hence, the industry has developed various driving methods to invert the liquid crystal molecules, such as the dot inverse method.

However, the conventional driving method is to keep changing the polarity of the data voltage transmitted on the data line so as to invert the liquid crystal molecules. The frequently switched polarity of the data voltage will increase the power consumption of the LCD panel, resulting in a waste of resources.

SUMMARY OF THE INVENTION

The present invention provides a LCD panel so as to resolve the problems of flicking pictures, cross talk and high power consumption caused by the frequent change of the common electrode voltage of the color filter substrate.

According to the present invention, a liquid crystal display panel comprising a pixel matrix arranged along a row direction and a column direction, each of the pixels comprises a pixel unit and a thin film transistor, the liquid crystal display panel further comprising a source driver and a gate driver, the

source driver and the gate driver disposed on a same side of the pixel matrix along the column direction;

wherein an Nth set of scan line is disposed between two neighboring row of pixels, N being a natural number, each set of the scan lines comprises an upper scan line and a lower scan line arranged along the column direction, and gate electrodes of the thin film transistors in the neighboring row of pixels are alternatively coupled to the upper scan line and the lower scan line sequentially;

an Nth data line is disposed between a 2N-1th column of pixels and a 2Nth column of pixels, and the Nth data line is coupled to source electrodes of the thin film transistors of the neighboring 2N-1th column of pixels and 2Nth column of pixels; and

an Nth signal connection line is disposed and corresponds to the Nth column of pixels, the signal connection line and the data line are disposed on both sides of the corresponding column of pixels.

In one aspect of the present invention, the source driver is coupled to the data line, the scan line is coupled to the gate driver through the signal connection line;

wherein a 4N-3th signal connection line is coupled to the upper scan line of a 2N-1th set of scan lines, a 4N-2th signal connection line is coupled to the lower scan line of the 2N-1th set of scan lines, a 4N-1th signal connection line is coupled to the lower scan line of a 2Nth set of scan lines, a 4N signal connection line is coupled to the upper scan line of the 2Nth set of scan lines.

In still another aspect of the present invention, a plurality of via holes are disposed on the liquid crystal display panel, and the signal connection line is coupled to the upper scan line or the lower scan line of the set of scan lines through the via holes.

In yet another aspect of the present invention, the signal connection line and the scan line are formed by etching a same metal layer with a same mask.

The present invention further provides a LCD panel so as to resolve the problems of flicking pictures, cross talk and high power consumption caused by the frequent change of the common electrode voltage of the color filter substrate.

According to the present invention, a liquid crystal display panel, comprising a pixel matrix arranged along a row direction and a column direction, each of the pixels comprising a pixel unit and a thin film transistor;

wherein an Nth set of scan lines is disposed between two neighboring row of pixels, each set of the scan lines comprises an upper scan line and a lower scan line arranged along the column direction, and gate electrodes of the thin film transistors in the neighboring row of pixels are alternatively coupled to the upper scan line and the lower scan line sequentially; and

an Nth data line is disposed between a 2N-1th column of pixels and a 2Nth column of pixels, and the Nth data line is coupled to source electrodes of the thin film transistors of the neighboring 2N-1th column of pixels and 2Nth column of pixels.

In one aspect of the present invention, the liquid crystal display panel further comprising a source driver and a gate driver, the source driver and the gate driver disposed on a same side of the pixel matrix along the column direction.

In another aspect of the present invention, an Nth signal connection line is disposed and corresponds to the Nth column of pixels, the signal connection line and the data line are disposed on both sides of the corresponding column of pixels, the source driver is coupled to the data line, the scan line is coupled to the gate driver through the signal connection line;

wherein a 4N-3th signal connection line is coupled to the upper scan line of a 2N-1th set of scan lines, a 4N-2th signal

3

connection line is coupled to the lower scan line of the 2N-1th set of scan lines, a 4N-1th signal connection line is coupled to the lower scan line of a 2Nth set of scan lines, a 4N signal connection line is coupled to the upper scan line of the 2Nth set of scan lines.

In still another aspect of the present invention, a plurality of via holes are disposed on the liquid crystal display panel, and the signal connection line is coupled to the upper scan line or the lower scan line of the set of scan lines through the via holes.

In yet another aspect of the present invention, the signal connection line and the scan line are formed by etching a same metal layer with a same mask.

The present invention further provides a display apparatus having the LCD panel so as to resolve the problems of flicking pictures, cross talk and high power consumption caused by the frequent change of the common electrode voltage of the color filter substrate.

According to the present invention, a display apparatus comprising a liquid crystal display panel, the liquid crystal display panel comprising a pixel matrix arranged along a row direction and a column direction, each of the pixels comprising a pixel unit and a thin film transistor;

wherein an Nth set of scan lines is disposed between two neighboring row of pixels, each set of the scan lines comprises an upper scan line and a lower scan line arranged along the column direction, and gate electrodes of the thin film transistors in the neighboring row of pixels are alternatively coupled to the upper scan line and the lower scan line sequentially; and

an Nth data line is disposed between a 2N-1th column of pixels and a 2Nth column of pixels, and the Nth data line is coupled to source electrodes of the thin film transistors of the neighboring 2N-1th column of pixels and 2Nth column of pixels.

In one aspect of the present invention, the liquid crystal display panel further comprising a source driver and a gate driver, the source driver and the gate driver disposed on a same side of the pixel matrix along the column direction.

In another aspect of the present invention, an Nth signal connection line is disposed and corresponds to the Nth column of pixels, the signal connection line and the data line are disposed on both sides of the corresponding column of pixels, the source driver is coupled to the data line, the scan line is coupled to the gate driver through the signal connection line;

wherein a 4N-3th signal connection line is coupled to the upper scan line of a 2N-1th set of scan lines, a 4N-2th signal connection line is coupled to the lower scan line of the 2N-1th set of scan lines, a 4N-1th signal connection line is coupled to the lower scan line of a 2Nth set of scan lines, a 4N signal connection line is coupled to the upper scan line of the 2Nth set of scan lines.

In still another aspect of the present invention, a plurality of via holes are disposed on the liquid crystal display panel, and the signal connection line is coupled to the upper scan line or the lower scan line of the set of scan lines through the via holes.

In yet another aspect of the present invention, the signal connection line and the scan line are formed by etching a same metal layer with a same mask.

In contrast to the prior art, a set of scan lines is disposed between two neighboring row of pixels according to the present invention. The set of scan lines comprises an upper scan line and a lower scan line, and the upper scan line and the lower scan line respectively couple to the pixels of odd columns and even columns. By performing suitably progressive scanning, dot inversion is achieved. Not only the power con-

4

sumption is lowered, but also the picture is clear since the common electrode voltage of the color filter substrate is not changed frequently.

These and other features, aspects and advantages of the present disclosure will become understood with reference to the following description, appended claims and accompanying figures.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic diagram showing a structure of pixels of a conventional LCD panel.

FIG. 2 is a schematic diagram showing a structure of pixels of the present invention LCD panel according to a preferred embodiment of the present invention.

FIG. 3 is a schematic diagram showing scan signals of scan lines G_{2N-1} , G_{2N} , waveforms of data lines S_N , and waveforms of a common electrode in a frame period when the present invention LCD panel is driven.

FIG. 4 is a schematic diagram showing a structure of a pixel matrix constituted by pixels of a first to a third row and a first to a sixth column according to the present invention LCD panel.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Spatially relative terms, such as "beneath", "below", "lower", "above", "upper" and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures.

Please refer to FIG. 2, FIG. 2 is a schematic diagram showing a structure of pixels of the present invention LCD panel according to a preferred embodiment of the present invention. The LCD panel 20 comprises a pixel matrix arranged along a row direction A and a column direction B. A pixel unit 21, a thin film transistor (not indicated), and a liquid crystal capacitor (not indicated) are disposed in each of the pixels. The LCD panel 20 further comprises a source driver 22 and a gate driver 23. The source driver 22 and the gate driver 23 are disposed on a same side of the pixel matrix of the LCD panel 20. For example, in FIG. 2, the source driver 22 and the gate driver 23 are disposed on an upper portion of the LCD panel 20, namely, on top of the pixel matrix along the column direction B.

According to the present invention, a set of scan lines is disposed between two neighboring row of pixels. Each set of the scan lines comprises an upper scan line G_{2N-1} and a lower scan line G_{2N} arranged along the column direction B. Gate electrodes of the thin film transistor in the neighboring row of pixels are alternatively coupled to the upper scan line G_{2N-1} and the lower scan line G_{2N} sequentially. For example, the upper scan line G_{2N-1} of each set of the scan lines couples to the gate electrodes of the thin film transistors of odd columns, while the lower scan line G_{2N} couples to the gate electrodes of the thin film transistors of even columns. The upper scan line G_{2N-1} and the lower scan line G_{2N} are used for providing scan signals to the pixel matrix.

For example, a first set of scan lines is disposed between a first row of pixels and a second row of pixels. The first set of scan lines comprises an upper scan line G_1 and a lower scan line G_2 . The upper scan line G_1 couples to the gate electrodes of the odd-column thin film transistors of the first row. The

lower scan line G_2 couples to the gate electrodes of the even-column thin film transistors of the first row.

Please refer to FIG. 2, an N th data line S_N is disposed between a $2N-1$ th column of pixels and a $2N$ th column of pixels. The data line S_N couples to the source driver 22. The data line S_N is coupled to source electrodes of the thin film transistors of the neighboring $2N-1$ th column of pixels and the $2N$ th column of pixels. The data line S_N is used for providing grey scale voltage to the pixel matrix. For example, the second data line S_2 is coupled to the source electrodes of the thin film transistors of the third column of pixels and the fourth column of pixels.

Since the gate driver 23 is disposed on the upper portion of the LCD panel 20, signal connection lines are disposed so that the gate driver 23 is coupled to the scan lines G_{2N-1} , G_{2N} through the signal connection lines. More specifically, two signal connection lines are disposed between the neighboring data lines S_N . Please refer to FIG. 2, the two neighboring column of pixels share one data line S_N . Two signal connection lines P_{2N-1} , P_{2N} are disposed on both sides of the two neighboring column of pixels. The signal connection lines P_{2N-1} , P_{2N} couple to the source driver 22. For example, a signal connection line P_1 is on the left side of the first column of pixels, a data line S_1 is on the right side of the first column of pixels. The data line S_1 is on the left side of the second column of pixels. A signal connection line P_2 is on the right side of the second column of pixels. A data line S_4 is on the left side of the eighth column of pixels. A signal connection line P_8 is on the right side of the eighth column of pixels. The rest may be deduced by analogy.

A $4N-3$ th signal connection line couples to the upper scan line G_{2N-1} of a $2N-1$ th set of scan lines, a $4N-2$ th signal connection line couples to the lower scan line G_{2N} of the $2N-1$ th set of scan lines. A $4N-1$ th signal connection line couples to the lower scan line G_{2N} of a $2N$ th set of scan lines, a $4N$ th signal connection line couples to the upper scan line G_{2N-1} of the $2N$ th set of scan lines.

For example, the first signal connection line P_1 is coupled to the upper scan line G_1 of the first set of scan lines. The second signal connection line P_2 is coupled to the lower scan line G_2 of the first set of scan lines. A third signal connection line P_3 is coupled to a lower scan line G_4 of the second set of scan lines. A fourth signal connection line P_4 is coupled to an upper scan line G_3 of the second set of scan lines. A fifth signal connection line P_5 is coupled to an upper scan line G_5 of the third set of scan lines. A sixth signal connection line P_6 is coupled to a lower scan line G_6 of the third set of scan lines. The rest may be deduced by analogy.

According to the present invention, in order to realize the objective of coupling the signal connection lines to the scan lines G_{2N-1} , G_{2N} , via holes 24 are disposed on the LCD panel 20. The scan lines G_{2N-1} , G_{2N} are coupled to their corresponding signal connection lines through via holes 24.

By doing so, the manner in which the upper scan lines and the lower scan lines of the even-row pixels are coupled to their corresponding signal connection lines is different from that in which the upper scan lines and the lower scan lines of the odd-row pixels are coupled to their corresponding signal connection lines.

According to the present invention, the gate driver 23 and the source driver 22 are disposed on top of the pixel matrix. The gate driver 23 is coupled to the scan lines G_{2N-1} , G_{2N} through the signal connection line P_N . The signal connection lines P_N distribute between the columns of pixels. The bezel on both left side and right side of the LCD panel 20 is thus narrowed. As a result, the display area is widened. For example, the bezel width on both the left side and the right

side, being conventionally 13 mm, will become 7 mm with such an improvement, while the bezel width on both top side and bottom side of the LCD panel 20 is not changed. The number of source driver IC is decreased.

According to the present invention, since the signal connection lines P_N and the data lines S_N are both elongated along the column direction B, they may be formed by the same process. They may also be made of a same material. The cost is therefore reduced.

Please also refer to FIG. 3 and FIG. 4, FIG. 3 is a schematic diagram showing scan signals of scan lines G_{2N-1} , G_{2N} , waveforms of data lines S_N , and waveforms of a common electrode in a frame period when the present invention LCD panel is driven. FIG. 4 is a schematic diagram showing a structure of a pixel matrix constituted by pixels of a first to a third row and a first to a sixth column according to the present invention LCD panel 20.

Please refer to FIG. 2, FIG. 3, and FIG. 4, the driving method of the present invention liquid LCD panel is illustrated as following:

During the period t1, the gate driver 23 provides the scan line G_1 with a scan signal via the signal connection line P_1 . The odd-column (the first, third, fifth column) thin film transistors of the first row of pixels are turned on. The source driver 22 provides a positive polarity gray scale voltage to the data line S_1 . Since the data line S_1 is only coupled to the first and second columns of pixels, a pixel at the intersection of the first row and the first column is turned on. The light unit 51 is thus positively polarized.

During the period t2, the gate driver 23 provides the scan line G_2 with a scan signal via the signal connection line P_2 . The even-column (the second, fourth, sixth column) thin film transistors of the first row of pixels are turned on. The source driver 22 provides a negative polarity gray scale voltage to the data line S_1 . Since the data line S_1 is only coupled to the first and second columns of pixels, a pixel at the intersection of the first row and the second column is turned on. Hence, the light unit 52 is negatively polarized.

During the period t3, the gate driver 23 provides the scan line G_4 with a scan signal via the signal connection line P_3 . The even-column thin film transistors of the second row of pixels are turned on. The source driver 22 provides a positive polarity gray scale voltage to the data line S_2 . Since the data line S_2 is only coupled to the third and fourth columns of pixels, a pixel at the intersection of the second row and the fourth column is turned on. The light unit 53 is thus positively polarized.

During the period t4, the gate driver 23 provides the scan line G_3 with a scan signal via the signal connection line P_4 . The odd-column thin film transistors of the second row of pixels are turned on. The source driver 22 provides a negative polarity gray scale voltage to the data line S_2 . Since the data line S_2 is only coupled to the third and fourth columns of pixels, a pixel at the intersection of the second row and the third column is turned on. Hence, the light unit 54 is negatively polarized.

During the period t5, the gate driver 23 provides the scan line G_5 with a scan signal via the signal connection line P_5 . The odd-column thin film transistors of the third row of pixels are turned on. The source driver 22 provides a positive polarity gray scale voltage to the data line S_3 . Since the data line S_3 is only coupled to the fifth and sixth columns of pixels, a pixel at the intersection of the third row and the fifth column is turned on. The light unit 55 is thus positively polarized.

During the period t6, the gate driver 23 provides the scan line G_6 with a scan signal via the signal connection line P_6 . The even-column thin film transistors of the third row of

pixels are turned on. The source driver **22** provides a negative polarity gray scale voltage to the data line S_3 . Since the data line S_3 is only coupled to the fifth and sixth columns of pixels, a pixel at the intersection of the third row and the sixth column is turned on. Hence, the light unit **56** is negatively polarized.

The method for driving the other pixels in other periods is similar to the driving method shown in FIG. 4 and needs not be elaborated further. It is obvious that inversion driving is achieved within a period according to the above-mentioned driving method.

In contrast to the prior art, a set of scan lines is disposed between two neighboring row of pixels according to the present invention. The set of scan lines comprises an upper scan line and a lower scan line, and the upper scan line and the lower scan line respectively couple to the pixels of odd columns and even columns. By performing suitably progressive scanning, dot inversion is achieved. Not only the power consumption is lowered, but also the picture is clear because the common electrode voltage of the color filter substrate is not changed frequently.

While the present invention has been described in connection with what is considered the most practical and preferred embodiments, it is understood that this invention is not limited to the disclosed embodiments but is intended to cover various arrangements made without departing from the scope of the broadest interpretation of the appended claims.

What is claimed is:

1. A liquid crystal display panel comprising a pixel matrix arranged along a row direction and a column direction, each of the pixels comprises a pixel unit and a thin film transistor, the liquid crystal display panel further comprising a source driver and a gate driver, the source driver and the gate driver disposed on a same side of the pixel matrix along the column direction;

wherein an Nth set of scan line is disposed between two neighboring row of pixels, N being a natural number, each set of the scan lines comprises an upper scan line and a lower scan line arranged along the column direction, and gate electrodes of the thin film transistors in the neighboring row of pixels are alternatively coupled to the upper scan line and the lower scan line sequentially; an Nth data line is disposed between a 2N-1th column of pixels and a 2Nth column of pixels, and the Nth data line is coupled to source electrodes of the thin film transistors of the neighboring 2N-1th column of pixels and 2Nth column of pixels; and

an Nth signal connection line is disposed and corresponds to the Nth column of pixels, the signal connection line and the data line are disposed on both sides of the corresponding column of pixels,

wherein the source driver is coupled to the data line, the scan line is coupled to the gate driver through the signal connection line;

wherein a 4N-3th signal connection line is coupled to the upper scan line of a 2N-1th set of scan lines, a 4N-2th signal connection line is coupled to the lower scan line of

the 2N-1th set of scan lines, a 4N-1th signal connection line is coupled to the lower scan line of a 2Nth set of scan lines, a 4N signal connection line is coupled to the upper scan line of the 2Nth set of scan lines.

2. The liquid crystal display panel as claimed in claim 1, wherein a plurality of via holes are disposed on the liquid crystal display panel, and the signal connection line is coupled to the upper scan line or the lower scan line of the set of scan lines through the via holes.

3. The liquid crystal display panel as claimed in claim 1, wherein the signal connection line and the scan line are formed by etching a same metal layer with a same mask.

4. A display apparatus comprising a liquid crystal display panel, the liquid crystal display panel comprising a pixel matrix arranged along a row direction and a column direction, each of the pixels comprising a pixel unit and a thin film transistor;

wherein an Nth set of scan lines is disposed between two neighboring row of pixels, each set of the scan lines comprises an upper scan line and a lower scan line arranged along the column direction, and gate electrodes of the thin film transistors in the neighboring row of pixels are alternatively coupled to the upper scan line and the lower scan line sequentially; and

an Nth data line is disposed between a 2N-1th column of pixels and a 2Nth column of pixels, and the Nth data line is coupled to source electrodes of the thin film transistors of the neighboring 2N-1th column of pixels and 2Nth column of pixels,

wherein the liquid crystal display panel further comprising a source driver and a gate driver, the source driver and the gate driver disposed on a same side of the pixel matrix along the column direction,

wherein an Nth signal connection line is disposed and corresponds to the Nth column of pixels, the signal connection line and the data line are disposed on both sides of the corresponding column of pixels, the source driver is coupled to the data line, the scan line is coupled to the gate driver through the signal connection line;

wherein a 4N-3th signal connection line is coupled to the upper scan line of a 2N-1th set of scan lines, a 4N-2th signal connection line is coupled to the lower scan line of the 2N-1th set of scan lines, a 4N-1th signal connection line is coupled to the lower scan line of a 2Nth set of scan lines, a 4N signal connection line is coupled to the upper scan line of the 2Nth set of scan lines.

5. The display apparatus as claimed in claim 4, wherein a plurality of via holes are disposed on the liquid crystal display panel, and the signal connection line is coupled to the upper scan line or the lower scan line of the set of scan lines through the via holes.

6. The display apparatus as claimed in claim 4, wherein the signal connection line and the scan line are formed by etching a same metal layer with a same mask.

* * * * *

专利名称(译)	液晶显示面板和具有液晶显示面板的设备		
公开(公告)号	US9097950	公开(公告)日	2015-08-04
申请号	US13/700407	申请日	2012-09-04
[标]申请(专利权)人(译)	赵国 丁涛 刘明		
申请(专利权)人(译)	赵，郭 丁陶 刘，MING		
当前申请(专利权)人(译)	深圳市中国星光电科技有限公司.		
[标]发明人	ZHAO GUO DING TAO LIU MING		
发明人	ZHAO, GUO DING, TAO LIU, MING		
IPC分类号	G02F1/1343 G02F1/1362 G09G3/36		
CPC分类号	G02F1/136286 G09G3/3648 G09G3/3674 G09G3/3614 G09G2300/0426 G09G2310/0281 G09G2320/0209 G09G2320/0247 G09G2330/021		
优先权	201210276385.5 2012-08-06 CN		
其他公开文献	US20140036191A1		
外部链接	Espacenet USPTO		

摘要(译)

本发明提供一种液晶显示面板。第N组扫描线设置在两个相邻像素行之间。每组扫描线包括上扫描线和下扫描线。相邻行像素中的薄膜晶体管的栅极电极交替地依次耦合到上扫描线和下扫描线。第N条数据线设置在第2N-1列像素和第2N列像素之间。第N条数据线耦合到相邻的第2N-1列像素和第2N列像素的薄膜晶体管的源电极。

